

BOOK 4078

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

COMPLETION SURVEY

Subdivisional Lines

Township 3 North, Range 13 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Leonard W. Murphy, Cadastral Surveyor

Under special instructions dated June 27, 19 62, which provided for the surveys
included under Group Number 380, approved July 2, 1962,
and assignment instructions dated April 2, 19 63.

Survey commenced April 2, 19 63

Survey completed April 19, 19 63

1A

BOOK 4670

INDEX DIAGRAM

Township 3 North, Range 13 West,

6 30 29	5 21 29	4 16 20	3 10 15	2 5 9	1 4
7 28 27	8 20 27	9 14 20	10 9 14	11 4 8	12 4
18 26 26	17 19 25	16 14 19	15 8 13	14 3 8	13 3
19 24 24	20 18 23	21 13 18	22 7 12	23 2 7	24 2
30 23 22	29 17 22	28 11 17	27 6 11	26 1 6	25
31 21	32 16	33 10	34 5	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

1. B

CHAINS

Township 3 North, Range 13 West, G&SRM, Arizona

The east boundary was surveyed in 1923 by Thorn and White. The west boundary was surveyed in 1926 by W. H. Thorn. The south boundary was surveyed in 1941 by Hiester and White. The north boundary and section 36 were surveyed in 1955 by P. K. Russell.

The following field notes are those of the completion survey of the subdivisional lines of Township 3 North, Range 13 West.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 27, 1962.

The geographic position of the southeast corner of the township is: Latitude 33°33'06" N. and Longitude 113°32'31" W. as determined by computation from C. & G. S. Triangulation Station SALOME FIELD and checked by direct tie to Triangulation Station 511, Los Angeles-Phoenix Airway Beacon No. 27-B, both of which are located in section 27 of this township.

The magnetic declination was found to be 14°15' East.

Subdivisional Lines, T. 3 N., R. 13 W., Arizona

From the cor. of secs. 25, 26, 35 and 36, monumented by an iron post as described in the official record.

N. 0°01' W., bet. secs. 25 and 26.

Over nearly level desert land, through scattered timber and undergrowth.

40.00

Point for the ¼ sec. cor. of secs. 25 and 26.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W

¼

S26 | S25

1963

Raise a mound of earth and stone W. of the post.

64.90

Old road, bears E. and W.

80.00

Point for the cor. of secs. 23, 24, 25 and 26.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W

S23 | S24

S26 | S25

1963

Raise a small mound of earth and stone W. of the post.

CHAINS	
	<p>Land, nearly level. Soil, sandy. Timber, mesquite and ironwood; undergrowth, greasewood, sage and cactus.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>S. 89°53' W., bet. secs. 24 and 25.</p> <p>Over nearly level land.</p>
0.30	Bladed road, bears N. 68° E. and S. 68° W.
40.01	<p>Point for the ¼ sec. cor. of secs. 24 and 25.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T3NR13W ¼ $\frac{S\ 24}{S\ 25}$ 1963</p> </div> <p>Raise a small mound of stone N. of the post.</p>
80.02	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, level. Soil, sandy. Timber, mesquite and palo verde; undergrowth, greasewood and cactus.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over nearly level desert land.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 23 and 24.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T3NR13W ¼ S23 S24 1963</p> </div> <p>Raise a small mound of stone W. of the post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T3NR13W S14 S13 S23 S24 1963</p> </div> <p>from which</p> <p style="text-align: center;">U.S. Coast and Geodetic Survey triangulation station RUST bears N. 61°09' E., 94.36 chains dist.</p> <p>Land, level. Soil, sandy. Timber, none; undergrowth, greasewood, cactus, ocotillo and sage.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Subdivision, T. 3 N., R. 13 W., Arizona

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, monumented by an iron post as described in the official record.

S. 89°55' W., bet. secs.' 13 and 24.

Over nearly level desert land, through sparse timber and undergrowth.

40.01 Point for the $\frac{1}{4}$ sec. cor. of 13 and 24.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
 $\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$
1963

Raise a small mound of stone N. of the post.

80.02 The cor. of secs. 13, 14, 23 and 24.

Land, level.

Soil, sandy and gravelly.

Timber, mesquite, ironwood and palo verde; undergrowth, greasewood.

N. 0°01' W., bet. secs. 13 and 14.

Over nearly level land, through scattered timber and undergrowth.

27.90 Center of proposed Interstate Highway No. 10, bears N. 79°51' W., and S. 79°51' E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
 $\frac{1}{4}$
S14 | S13
1963

48.20 Small wash, drains SW.

80.00 Point for the cor. of secs. 11, 12, 13 and 14.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
S11 | S12
S14 | S13
1963

Raise a small mound of earth and stone W. of the post.

Land, level.

Soil, sandy.

Timber, none; undergrowth, greasewood, ocotillo, sage and cactus.

4

CHAINS

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township, monumented by an iron post as described in the official record.

S. 89°50' W., bet. secs. 12 and 13.

Over nearly level desert land.

40.03

Point for the 1/4 sec. cor. of secs. 12 and 13.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W

1/4 S 12
S 13

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the post.

80.06

The cor. of secs. 11, 12, 13 and 14.

Land, level.

Soil, sandy and gravelly.

Timber, ironwood, mesquite and palo verde.

Undergrowth, greasewood, sage and cactus.

N. 0°01' W., bet. secs. 11 and 12.

Over level land, through scattered undergrowth.

40.00

Point for the 1/4 sec. cor. of secs. 11 and 12.

Set the iron post 18 ins. in the ground, cap mkd.

T3NR13W

1/4 S11 | S12

1963

Raise a small mound of earth and stone to W. of the post.

52.00

Small wash, drains S. 20° E.

78.10

Small wash, drains SW.

80.00

Point for the cor. of secs. 1, 2, 11 and 12.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W

S 2 | S 1
S11 | S12

1963

Raise a small mound of stone W. of the post.

Land, level.

Soil, sandy and gravelly.

Timber, palo verde; undergrowth, greasewood, catclaw and cactus.

From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township, monumented by an iron post as described in the official record.

S. 89°52' W., bet. secs. 1 and 12.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 3 N., R. 13 W., Arizona
40.05	<p>Over level land, through sparse timber and undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ $\frac{S}{S}$ $\frac{1}{12}$ 1963</p> <p>Raise a small mound of stone N. of the post.</p>
80.10	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, level. Soil, sandy and gravelly. Timber, palo verde, mesquite and ironwood. Undergrowth, greasewood and sage.</p>
	<p>N. 0°03' E., bet. secs. 1 and 2.</p>
14.50	<p>Over nearly level land, through sparse undergrowth.</p> <p>Small wash, drains irregularly S.</p>
27.80	<p>Same wash, same general drainage.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ S2 S1 1963</p>
52.80	<p>Raise a small mound of stone W. of the post; falls on level land.</p> <p>Small wash, drains irregularly SE.</p>
79.93	<p>The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>Land, level. Soil, gravelly. Timber, palo verde, ironwood and mesquite. Undergrowth, greasewood, sage and cactus.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over level desert land, through dense mesquite thicket.</p>

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ S34 S35 1963</p>
57.30	<p>Unimproved road, bears N. 45° W. and S. 45° E.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W S27 S26 S34 S35 1963</p> <p>Raise a small mound of stone W. of the post.</p> <p>Land, level. Soil, sandy. Timber, mesquite; undergrowth, greasewood, catclaw and cactus.</p>
<hr/>	
25.60	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°50' W., bet. secs. 26 and 35.</p> <p>Over desert land, through scattered timber and undergrowth.</p> <p>Graded road, bears N. 5° E. to Micro-wave station site and S. 5° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ S 26 S 35 1963</p> <p>Raise a small mound of stone N. of the post.</p>
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, level. Soil, sandy. Timber, palo verde and mesquite; undergrowth, greasewood and cactus.</p>
<hr/>	
40.00	<p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over level land, through sparse undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ S27 S26 1963</p> <p>Raise a small mound of stone W. of the post.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

7.

CHAINS	
	Subdivision, T. 3 N., R. 13 W., Arizona
65.00	Bladed road, bears W. to Salome airstrip and E.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T3NR13W <u>S22 S23</u> <u>S27 S26</u> 1963 </div>
	Land, level. Soil, sandy. Timber, palo verde; undergrowth, sage and cactus.
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89°50' W., bet. secs. 23 and 26.
	Over level land, through sparse timber and undergrowth.
40.01	Point for the ¼ sec. cor. of secs. 23 and 26.
	Set the iron post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T3NR13W ¼ <u>S 23</u> <u>S 26</u> 1963 </div>
	Raise a small mound of stone N. of the post.
80.02	The cor. of secs. 22, 23, 26 and 27.
	Land, level. Soil, sandy. Timber, scattered palo verde and mesquite; undergrowth, cactus and sage.
	N. 0°01' W., bet. secs. 22 and 23.
	Over nearly level desert land.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23.
	Set the iron post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T3NR13W ¼ <u>S22 S23</u> 1963 </div>
	Raise a small mound of stone to W. of the post.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T3NR13W <u>S15 S14</u> <u>S22 S23</u> 1963 </div>

CHAINS

Raise a small mound of earth and stone W. of the post.

Land, level.

Soil, sandy.

Timber, scattered palo verde; undergrowth, cactus, bur sage and ocotillo.

From the cor. of secs. 13, 14, 23 and 24.

S. 89°52' W., bet. secs. 14 and 23.

Over level desert land.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
 $\frac{1}{4}$ $\frac{S\ 14}{S\ 23}$
 1963

Raise a small mound of earth and stone N. of the post.

80.02 The cor. of secs. 14, 15, 22 and 23.

Land, level.

Soil, sandy.

Timber, palo verde and mesquite; undergrowth, cactus and greasewood.

N. 0°01' W., bet. secs. 14 and 15.

Over level land, through scattered timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
 $\frac{1}{4}$
 S15|S14
 1963

42.33 Center of proposed Interstate Highway No. 10, bears S. 79°55' E. and N. 79°55' W.

80.00 Point for the cor. of secs. 10, 11, 14 and 15.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
 S10|S11
 S15|S14
 1963

Raise a small mound of stone W. of the post.

Land, level.

Soil, sandy.

Timber, mesquite, ironwood and palo verde; undergrowth, greasewood.

From the cor. of secs. 11, 12, 13 and 14.

S. 89°55' W., bet. secs. 11 and 14.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p style="text-align: center;">Subdivision, T. 3 N., R. 13 W., Arizona</p> <hr/>
	<p>Over level land, through scattered timber and undergrowth.</p>
40.01	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T3NR13W $\frac{1}{4}$ $\frac{S 11}{S 14}$ 1963</p>
	<p>Raise a small mound of stone to N. of the post.</p>
80.02	<p>The cor. of secs. 10, 11, 14 and 15.</p>
	<p>Land, level. Soil, sandy and gravelly. Timber, mesquite and ironwood; undergrowth, greasewood, cactus and sage.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 10 and 11.</p>
	<p>Over nearly level land, through scattered undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p>
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T3NR13W $\frac{1}{4}$ S10 S11 1963</p>
	<p>Raise a small mound of stone W. of the post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p>
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T3NR13W S3 S2 S10 S11 1963</p>
	<p>Raise a small mound of stone W. of the post.</p>
	<p>Land, nearly level. Soil, sandy and gravelly. Timber, mesquite and ironwood; undergrowth, greasewood, scrub palo verde, catclaw, ocotillo and cactus.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p>
	<p>S. 89°51' W., bet. secs. 2 and 11.</p>
	<p>Over gently rolling land, through medium dense undergrowth.</p>
4.90	<p>Wash, 20 lks. wide, 2 ft. deep, drains S. 10° W.</p>

CHAINS		
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Set the iron post 22 ins. in the ground, cap mkd.	
	T3NR13W $\frac{1}{4}$ $\frac{S\ 2}{S\ 11}$ 1963	
80.00	The cor. of secs. 2, 3, 10 and 11. Land, gently rolling. Soil, sandy and gravelly. Timber, ironwood and mesquite; undergrowth, greasewood and cactus.	
	N. 0°04' E., bet. secs. 2 and 3. Over gently rolling land, through medium dense undergrowth.	
22.10	Wash, 10 lks. wide, 1 ft. deep, drains S. 12° W.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3. Set the iron post 24 ins. in the ground, cap mkd.	
	T3NR13W $\frac{1}{4}$ S 3 S 2 1963	
79.83	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the township, monumented by an iron post as described in the official record. Land, gently rolling. Soil, gravelly. Timber, ironwood, mesquite and palo verde; undergrowth, greasewood.	
	From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township, monumented by an iron post as described in the official record.	
	N. 0°02' W., bet. secs. 33 and 34. Over level desert lowland, through medium dense timber and undergrowth.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34. Set the iron post 24 ins. in the ground, cap mkd.	
	T3NR13W $\frac{1}{4}$ S33 S34 1963	
	Raise a small mound of earth and stone to W. of the post.	
80.00	Point for the cor. of secs. 27, 28, 33 and 34. Set the iron post 24 ins. in the ground, cap mkd.	
	T3NR13W S28 S27 S33 S34 1963	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 3 N., R. 13 W., Arizona
	<p>Raise a small mound of stone W. of the post.</p> <p>Land, level. Soil, sandy. Timber, mesquite; undergrowth, catclaw, greasewood and scrub mesquite.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°51' W., bet. secs. 27 and 34.</p> <p>Over level land, through scattered mesquite thickets.</p>
39.95	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$ 1963</p>
	<p>Raise a small mound of stone N. of the post.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, level desert. Soil, sandy loam. Timber, mesquite and ironwood; undergrowth, greasewood and cactus.</p>
79.90	
	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over level desert land, through scattered undergrowth.</p>
34.70	<p>Old road, bears N. 45° E. and S. 50° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ S28 S27 1963</p>
	<p>from which</p> <p style="padding-left: 40px;">A well, leased to Mr. August Nord, bears N. 68° 38' W., 15.96 chs. dist.; one chain S. of the well is a stock corral and watering trough.</p>
46.60	<p>Bladed road, bears irregularly E. and W. to the well.</p>
73.40	<p>Road, leads from Salome to Salome emergency airstrip, bears E. and W.</p>
76.80	<p>Point selected for a witness point.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>

CHAINS		
80.00	<p>Post set in E. and W. barbed wire fence on S. edge of Salome emergency airstrip.</p> <p>Across airstrip, bearing E. and W.</p> <p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set the iron post 34 ins. in the ground, cap mkd.</p>	<p>T3NR13W WP S28 S27 1963</p>
22.00	<p>Post set in airstrip, 4 ins. below surface of runway.</p> <p>Land, level. Soil, sandy loam. Timber, mesquite and ironwood; undergrowth, greasewood, cactus and sage.</p>	<p>T3NR13W S21 S22 S28 S27 1963</p>
31.70	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°51' W., bet. secs. 22 and 27.</p> <p>Over level land, through dense mesquite thicket.</p> <p>Leave mesquite thicket.</p> <p>Point selected for a witness point.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>	
39.96	<p>Post set in barbed wire fence bearing N. and S. on the E. edge of the Salome emergency airstrip.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 27.</p> <p>Set the iron post 34 ins. in the ground, cap mkd.</p>	<p>T3NR13W S 22 S 27 WP 1963</p>
79.92	<p>Post set in airstrip, 4 ins. below surface of runway.</p> <p>from which</p> <p>U.S. Coast and Geodetic triangulation station SALOME FIELD bears S. 24°43' W., 16.72 chs. dist.</p> <p>U.S. Geological Survey bench mark bears S. 21°05' W., 18.83 chs. dist. and mkd. 1951 1345 feet 31D, a standard brass tablet set in concrete.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, level. Soil, sandy loam. Timber, mesquite, ironwood and palo verde; undergrowth, greasewood.</p>	<p>T3NR13W ¼ S 22 S 27 1963</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 3 N., R. 13 W., Arizona
	N. 0°02' W., bet. secs. 21 and 22.
	Over level land, through medium dense undergrowth.
5.00	Point selected for a witness point.
	Set the iron post 22 ins. in the ground, cap mkd.
	T3NR13W WP S21 S22 1963
	Post set in barbed wire fence bearing E. and W. on the N. edge of the Salome emergency airstrip.
16.40	Erosion control dike for Salome emergency airstrip, bears N. 56° W. and S. 56° E.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set the iron post 24 ins. in the ground, cap mkd.
	T3NR13W 1/4 S21 S22 1963
	Raise a small mound of stone W. of the post.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set the iron post 24 ins. in the ground, cap mkd.
	T3NR13W S16 S15 S21 S22 1963
	Raise a small mound of stone W. of the post.
	Land, level.
	Soil, sandy loam.
	Timber, none; undergrowth, greasewood, cactus, sage and scrub palo verde.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89°51' W., bet. secs. 15 and 22.
	Over level desert land, no timber.
39.96	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set the iron post 22 ins. in the ground, cap mkd.
	T3NR13W 1/4 S15 S22 1963
	Raise a small mound of earth and stone N. of the post.

CHAINS

79.92	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, level. Soil, sandy loam. Timber, none; undergrowth, scrub ironwood, mesquite and greasewood.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over level land, through sparse undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ S16 S15 1963</p>
56.80	<p>Center of proposed Interstate Highway No. 10 bears N. 79°52' W., and S. 79°52' E.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W <u>S 9 S10</u> <u>S16 S15</u> 1963</p> <p>Raise a small mound of stone to W. of the post.</p> <p>Land, level. Soil, sandy loam. Timber, none; undergrowth, greasewood, sage and cactus.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°51' W., bet. secs. 10 and 15.</p> <p>Over level desert land.</p>
39.96	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ <u>S 10</u> <u>S 15</u> 1963</p> <p>Raise a small mound of stone N. of the post.</p>
79.92	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, level. Soil, sandy loam. Timber, none; undergrowth, greasewood, cactus, ocotillo and sage.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over level desert land, through sparse undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p>

BOOK 4079
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T . 3 N., R. 13 W., Arizona
	Set the iron post 24 ins. in the ground, cap mkd.
	T3NR13W $\frac{1}{2}$ S 9 S10 1963
	Raise a small mound of stone W. of post.
72.10	Wash, 10 lks. wide, 1 ft. deep, drains irregularly SW.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 22 ins. in the ground, cap mkd.
	T3NR13W S 4 S 3 S 9 S10 1963
	Raise a small mound of stone to W. of post.
	Land, nearly level. Soil, gravelly. Timber, none; undergrowth, greasewood, cactus, scrub mesquite and sage.
	From the cor. of secs. 2, 3, 10 and 11.
	S. 89°53' W., bet. secs. 3 and 10.
	Over nearly level land, through scattered timber and undergrowth.
6.00	Wash, 15 lks. wide, 1 ft. deep, drains SE.
15.80	Small wash, drains irregularly S.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	Set the iron post 22 ins. in the ground, cap mkd.
	T3NR13W $\frac{1}{4}$ $\frac{S 3}{S 10}$ 1963
	Raise a small mound of stone N. of the post.
54.80	Small wash, drains SE.
78.40	Small wash, drains irregularly S.
79.98	The cor. of secs. 3, 4, 9 and 10.
	Land, nearly level. Soil, sandy and gravelly. Timber, scattered palo verde; undergrowth, greasewood and catclaw.

CHAINS		
	N. 0°02' E., bet. secs. 3 and 4. Over nearly level desert land.	
31.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 40° W.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. Set the iron post 24 ins. in the ground, cap mkd.	
		T3NR13W $\frac{1}{4}$ S4 S3 1963
	Raise a small mound of stone W. of the post.	
62.50	Wash, 30 lks. wide, 3 ft. deep, drains irregularly SW.	
62.70	Asc. SW. slope of malpai covered ridge.	
76.80	Crest of ridge, bears E. and W.; desc. N. slope to cor.	
79.80	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the township, monumented by an iron post as described in the official record. Land, nearly level S. $\frac{1}{2}$ mile; rolling N. $\frac{1}{2}$ mile. Soil, rocky. Timber, sparse mesquite and ironwood; undergrowth, greasewood and cactus.	
	From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, monumented by an iron post as described in the official record. N. 0°02' W., bet. secs. 32 and 33. Over level desert land.	
2.50	Old road, bears irregularly E. and W.	
38.80	Asc. S. slope of low ridge.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33. Set the iron post 18 ins. in the ground to bedrock and in a collar of stone to top, cap mkd.	
		T3NR13W $\frac{1}{4}$ S32 S33 1963
	Raise a small mound of stone W. of the post; falls on gentle S. slope.	
49.30	Crest of ridge, slopes S. 50° W.; desc. along NW. slope.	
57.80	Head of small wash, drains irregularly W.; asc. gentle SW. slope.	
61.60	Crest of low ridge, bears N. 30° W. and S. 30° E.; desc. along NE. slope.	
80.00	Point for the cor. of secs. 28, 29, 32 and 33. Set the iron post 18 ins. in the ground to bedrock and in a collar of stone to top, cap mkd.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 3 N., R. 13 W., Arizona
	T3NR13W S29 S28 S32 S33 1963
	Cor. falls on nearly level land. Land, nearly level. Soil, rocky. Timber, none; undergrowth, scrub palo verde, sage, ocotillo and saguaro.
	From the cor. of secs. 27, 28, 33 and 34. S. 89°52' W., bet. secs. 28 and 33. Over nearly level land, through dense undergrowth, no timber.
39.98	Point for the ¼ sec. cor. of secs. 28 and 33. Set the iron post 24 ins. in the ground, cap mkd.
	T3NR13W ¼ S 28 S 33 1963
	Raise a small mound of stone N. of the post.
42.40	Bladed road, bears N. 45° E. and S. 45° W.
51.70	Bladed road, bears N. 15° E. toward Nord's Well and S. 15° W.
79.96	The cor. of secs. 28, 29, 32 and 33. Land, nearly level. Soil, sandy and gravelly. Timber, none; undergrowth, scrub mesquite, palo verde, sage and cactus.
	N. 0°02' W., bet. secs. 28 and 29. Over nearly level land, through sparse undergrowth.
40.00	Point for the ¼ sec. cor. of secs. 28 and 29. Set the iron post 24 ins. in the ground, cap mkd.
	T3NR13W ¼ S29 S28 1963
	Raise a small mound of stone W. of the post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 24 ins. in the ground, cap mkd.
	T3NR13W S20 S21 S29 S28 1963

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the post.

Land, nearly level.

Soil, rocky.

Timber, none; undergrowth, greasewood, scrub palo verde and cactus.

From the cor. of secs. 21, 22, 27 and 28.

S. 89°50' W., bet. secs. 21 and 28.

Over level land, through patches of undergrowth.

14.83 Barbed wire fence, bears N. and S.; leave Salome emergency airstrip.

16.00 Bladed road, bears N. and S. for 3.50 chs., then E. to entrance of airstrip.

39.97 Point for the ¼ sec. cor. of secs. 21 and 28.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W

¼ S 21
S 28

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the post.

65.10 Unimproved road, bears S. 45° E. and N. 45° W.

79.94 The cor. of secs. 20, 21, 28 and 29.

Land, level.

Soil, sandy and gravelly.

Timber, none; undergrowth, greasewood, scrub mesquite, palo verde and ironwood.

N. 0°02' W., bet. secs. 20 and 21.

Over level land, through sparse undergrowth.

10.20 Unimproved road, bears S. 45° E. and N. 45° W.

40.00 Point for the ¼ sec. cor. of secs. 20 and 21.

Set the iron post 22 ins. in the ground, cap mkd.

T3NR13W

¼ S20|S21

1963

Raise a small mound of stone W. of the post.

60.30 Asc. SW. slope of rocky knoll.

69.10 Top of knoll; desc. NE. slope.

77.50 Over level land.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set the iron post 22 ins. in the ground, cap mkd.

T3NR13W

S17|S16
S20|S21

1963

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 3 N., R. 13 W., Arizona
	<p>Raise a small mound of stone W. of the post.</p> <p>Land, gently rolling. Soil, rocky and sandy. Timber, none; undergrowth, greasewood and bur sage.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°49' W., bet. secs. 16 and 21.</p> <p>Over level desert land, no timber.</p>
22.70	Bladed road, bears N. 5° W. toward Salome and S. 5° E. to Salome emergency airstrip.
39.98	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$ 1963</p>
79.96	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the post.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, level. Soil, alluvial and adobe. Timber, none; undergrowth, greasewood, ocotillo, sage and cactus.</p>
	<p>N. 0°02' W., bet. secs. 16 and 17.</p> <p>Over level land, through low undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ S17 S16 1963</p>
71.36	<p>Raise a small mound of stone W. of the post.</p> <p>Center of proposed Interstate Highway No. 10, bears N. 79°50' W. and S. 79°50' E.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W S8 S9 S17 S16 1963</p>

CHAINS

Raise a small mound of stone W. of the post.
 Land, level.
 Soil, alluvial and adobe.
 Timber none; undergrowth, greasewood and cactus.

From the cor. of secs. 9, 10, 15 and 16.

S. 89°47' W., bet. secs. 9 and 16.

Over level land.

39.98

Point for the 1/4 sec. cor. of secs. 9 and 16.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
 1/4 S 9
 S 16
 1963

Raise a small mound of stone N. of the post.

43.60

Bladed road, bears N. 10° W. toward Salome and S. 10° E. to Salome emergency airstrip.

79.96

The cor. of secs. 8, 9, 16 and 17.

Land, level.
 Soil, alluvial and adobe.
 Timber, none; undergrowth, greasewood, scrub mesquite and bur sage.

N. 0°02' W., bet. secs. 8 and 9.

Over level desert land, through low undergrowth.

40.00

Point for the 1/4 sec. cor. of secs. 8 and 9.

Set the iron post 22 ins. in the ground with the cap mkd.

T3NR13W
 1/4 S 8 | S 9
 1963

Raise a small mound of stone W. of the post.

80.00

Point for the cor. of secs. 4, 5, 8 and 9.

Set the iron post 22 ins. in the ground, cap mkd.

T3NR13W
 S 5 | S 4
 S 8 | S 9
 1963

Raise a small mound of stone W. of the post.

Land, level.
 Soil, sandy and gravelly.
 Timber, none; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 3, 4, 9 and 10.

S. 89°47' W., bet. secs. 4 and 9.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 3 N., R. 13 W., Arizona
	Over nearly level land, through scattered timber and undergrowth.
36.50	Small wash, drains irregularly S.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
	Set the iron post 24 ins. in the ground, cap mkd. T3NR13W $\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$ 1963
	Raise a small mound of stone N. of the post.
53.70	Bladed road, bears N. 9° W. toward Salome and S. 9° E. to Salome emergency airstrip.
79.98	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level. Soil, sandy and gravelly. Timber, scattered ironwood and mesquite. Undergrowth, greasewood, sage and cactus.
	N. 0°01' E., bet. secs. 4 and 5.
	Over level land, through low undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set the iron post 24 ins. in the ground, cap mkd. T3NR13W $\frac{1}{4}$ S 4 S 5 1963
	Raise a small mound of stone W. of the post.
79.88	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the township, monumented by an iron post as described in the official record.
	Land, nearly level. Soil, gravelly and sandy. Timber, none; undergrowth, greasewood, sage, ocotillo and cactus.
	From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township, monumented by an iron post as described in the official record.
	N. 0°03' W., bet. secs. 31 and 32.
	Over level land, through medium dense undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

CHAINS		
80.00	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{2}$ S31 S32 1963</p> <p>Raise a small mound of stone W. of the post.</p> <p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W S30 S29 S31 S32 1963</p> <p>Raise a small mound of stone W. of the post.</p> <p>Land, level. Soil, alluvial and adobe. Timber, none; undergrowth, greasewood, sage and cactus.</p>	
19.15	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°56' W., bet. secs. 29 and 32.</p> <p>Over broken hills, through sparse undergrowth; asc. NE. slope.</p>	
40.02	<p>Crest of ridge, bears N. and S.; desc. SW. slope.</p>	
48.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.</p> <p>Set the iron post 16 ins. in the ground to bedrock and in a collar of stone to top, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$ 1963</p> <p>Raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, N. of the post.</p> <p>Cont. desc. SW. slope.</p>	
80.04	<p>Over level land.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, hilly E. $\frac{1}{2}$ mile; nearly level W. $\frac{1}{2}$ mile. Soil, rocky. Timber, none; undergrowth, greasewood and scrub palo verde.</p>	
40.00	<p>S. 89°50' W., bet. secs. 30 and 31.</p> <p>Over level land, through low brush.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W $\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$ 1963</p> <p>Raise a small mound of stone N. of the post.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 3 N., R. 13 W., Arizona
77.46	<p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the township, monumented by an iron post as described in the official record. Cor. falls in barbed wire fence bearing N. and S.</p> <p>Land, level. Soil, gravelly alluvial. Timber, none; undergrowth, greasewood and sage.</p>
27.00	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over low broken hills.</p> <p>Asc. gentle S. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 29 and 30.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T3NR13W ¼ S30 S29 1963</p> <p>Raise a small mound of stone W. of the post; falls on gentle S. slope.</p>
58.90	<p>Wash, 15 lks. wide, 3 ft. deep, drains S. 75° W.; asc. SW. slope.</p>
79.40	<p>Crest of ridge, bears N. 45° W. and S. 45° E.; desc. NE. slope.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 8 ins. in the ground to bedrock and in a mound of stone to top, cap mkd.</p> <p style="text-align: center;">T3NR13W S19 S20 S30 S29 1963</p> <p>Post is on gentle NE. slope.</p> <p>Land, rolling and broken. Soil, rocky. Timber, none; undergrowth, scrub mesquite, palo verde and greasewood.</p>
40.05	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°58' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through sparse undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 29.</p>

CHAINS

Set the iron post 22 ins. in the ground, cap mkd.

T3NR13W
1/4 S 20
S 29
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post; falls on level land.

42.50 Asc. gentle E. slope.

49.70 Top of small knoll; desc. W. slope.

64.05 Wash, 10 lks. wide, 2 ft. deep, drains N. 10° W.; asc. NE. slope.

70.30 Jeep trail, bears N. 45° W. and S. 45° E.

80.10 The cor. of secs. 19, 20, 29 and 30.

Land, nearly level E. 1/2 mile; rolling W. 1/2 mile.
Soil, sandy and rocky.
Timber, none; undergrowth, ocotillo, buckhorn and cactus.

S. 89°48' W., bet. secs. 19 and 30.

Over rolling and broken land; asc. NE. slope.

0.70 Crest of ridge, bears N. 45° W. and S. 45° E.; desc. NW. slope.

7.00 Ravine, drains SW.; cont. desc.

29.10 Graded road, bears S. 20° E. and N. 20° W.; thence over level land.

40.00 Point for the 1/4 sec. cor. of secs. 19 and 30.

Set the iron post 22 ins. in the ground, cap mkd.

T3NR13W
1/4 S 19
S 30
1963

Raise a small mound of stone N. of the post.

46.60 Graded road, bears S. 40° W. and N. 40° E.

77.42 The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the township, monumented by an iron post as described in the official record.

Land, level and rolling.
Soil, rocky.
Timber, none; undergrowth, greasewood, sage and cactus.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°03' W., bet. secs. 19 and 20.

Desc. NE. slope of ridge.

22.00 Wash, 20 lks. wide, 3 ft. deep, drains W.

40.00 Point for the 1/4 sec. cor. of secs. 19 and 20.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Subdivision, T. 3 N., R. 13 W., Arizona

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
1/4
S19|S20
1963

Raise a small mound of stone W. of the post; falls on level land.

42.30 Wash, 20 lks. wide, 3 ft. deep, drains S. 80° W.

44.70 Graded road, bears N. 80° E. and S. 80° W.; asc. along W. slope.

71.70 Wash, 60 lks. wide, 2 ft. deep, drains S. 70° W.

80.00 Point for the cor. of secs. 17, 18, 19 and 20.

Set the iron post 12 ins. in the ground to bedrock and in a mound of stone to top, cap mkd.

T3NR13W
S18|S17
S19|S20
1963

Post is on a gentle SW. slope.

Land, rolling and broken.

Soil, rocky.

Timber, none; undergrowth, greasewood and cactus.

From the cor. of secs. 16, 17, 20 and 21.

S. 89°59' W., bet. secs. 17 and 20.

Over level land, through sparse undergrowth.

40.06 Point for the 1/4 sec. cor. of secs. 17 and 20.

Set the iron post 24 ins. in the ground, cap mkd.

T3NR13W
1/4 S 17
S 20
1963

Raise a small mound of stone N. of the post; falls on level land.

48.70 Bladed road, bears N. and S.

50.30 Bladed road, bears S. 20° W. and NE., 2.50 chs. to another road.

55.40 Small wash, drains NW.

76.80 Desc. SW. slope to cor.

80.12 The cor. of secs. 17, 18, 19 and 20.

CHAINS		
	<p>Land, level E. $\frac{1}{2}$ mile; rolling W. $\frac{1}{2}$ mile. Soil, rocky. Timber, none; undergrowth, greasewood.</p> <hr/> <p>S. $89^{\circ}47'$ W., bet. secs. 18 and 19.</p> <p>Over nearly level land.</p>	
18.50	Bladed road, bears N. 20° W. and S. 20° E.	
21.00	Small wash, drains SW.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	<p>T3NR13W $\frac{1}{4}$ $\frac{S\ 18}{S\ 19}$ 1963</p>	
	Raise a small mound of stone to N. of the post; falls on level land.	
77.30	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township, monumented by an iron post as described in the official record.	
	Land, nearly level. Soil, sandy and gravelly. Timber, none; undergrowth, greasewood. <hr/>	
	From the cor. of secs. 17, 18, 19 and 20.	
	N. $0^{\circ}03'$ W., bet. secs. 17 and 18.	
	Asc. broken SW. slope of ridge.	
8.90	Crest of small ridge, bears E. and W.; gradual desc. N. slope.	
19.50	Wash, 30 lks. wide, 4 ft. deep, drains W.	
27.20	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.; asc. gentle SE. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	<p>T3NR13W $\frac{1}{4}$ S18 S17 1963</p>	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the post; falls on gentle S. slope.	
41.95	Crest of ridge, bears E. and W.; desc. over rolling land.	
52.60	Wash, 20 lks. wide, 2 ft. deep, drains E.	
77.30	Jeep road, bears SE. and NE.	
80.00	Point for the cor. of secs. 7, 8, 17 and 18.	
	Set the iron post 12 ins. in the ground to bedrock and in a collar of stone to top, cap mkd.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 3 N., R. 13 W., Arizona
	<hr/> T3NR13W S 7 S 8 S18 S17 1963
	from which U.S. Coast and Geodetic Survey triangulation station SADDLE bears N. 63°57' E., 9.58 chains dist. Raise a mound of stone, 5 ft. base, 3 ft. high, W. of the post; falls on level land. Land, rolling. Soil, rocky and gravelly. Timber, none; undergrowth, cactus, greasewood and saguaro.
	<hr/> From the cor. of secs. 8, 9, 16 and 17. S. 89°56' W., bet. secs. 8 and 17. Over level desert land, through sparse undergrowth.
40.05	Point for the ¼ sec. cor. of secs. 8 and 17. Set the iron post 22 ins. in the ground, cap mkd.
	T3NR13W ¼ $\frac{S 8}{S 17}$ 1963
	Raise a small mound of stone N. of the post.
42.50	Graded road, bears N. 15° E. and S. 15° W.
48.05	Center of proposed Interstate Highway No. 10, bears N. 79°50' W. and S. 79°50' E.
64.00	Leave level land, asc. over rolling hills.
80.10	The cor. of secs. 7, 8, 17 and 18. Land, nearly level. Soil, alluvial and adobe. Timber, none; undergrowth, greasewood, catclaw and scrub palo verde.
	<hr/> S. 89°47' W., bet. secs. 7 and 18. Over gently rolling land, through low underbrush and cactus.
32.25	Wash, 30 lks. wide, 4 ft. ^{deep} drains S. 30° W.; over level land.
35.35	Bladed road, bears NE. and SW.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18.

CHAINS

Set the iron post 22 ins. in the ground, cap mkd.

T3NR13W

1/4 S 7 / S 18

1963

Raise a small mound of stone N. of the post; falls on level land.

44.00 Bladed road, bears N. 15° W. and S. 15° E.

77.19 The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township, monumented by an iron post as described in the official record.

Land, gently rolling to level.
Soil, gravelly and rocky.
Timber, none; undergrowth, greasewood, saguaro, catclaw and sage.

From the cor. of secs. 7, 8, 17 and 18.

N. 0°03' W., bet. secs. 7 and 8.

Over rolling land, through sparse undergrowth.

0.90 Jeep road, bears generally E. and W.

1.20 Wash, 15 lks. wide, 3 ft. deep, drains S. 70° W.; asc. gentle S. slope.

5.76 Center of proposed Interstate Highway No. 10, bears N. 79°50' W. and S. 79°50' E.

12.00 Same wash, drains S. 15° E.; slope changes to SW.

36.70 Saddle of spur, bears N. 80° W. and S. 80° E.; desc. N. slope.

40.00 Point for the 1/4 sec. cor. of secs. 7 and 8.

Set the iron post 18 ins. in the ground to bedrock and in a collar of stone to top, cap mkd.

T3NR13W

1/4 S 7 | S 8

1963

Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the post; falls on gentle N. slope.

50.00 Enter level land.

55.00 Wash, 35 lks. wide, 1 ft. deep, drains S. 70° E.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set the iron post 12 ins. in the ground to bedrock and in mound of stone to top, cap mkd.

T3NR13W

S 6 | S 5 / S 7 | S 8

1963

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of the post; falls on level land.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Subdivision, T. 3 N., R. 13 W., Arizona

Land, rolling S. $\frac{1}{2}$ mile; level N. $\frac{1}{2}$ mile.
Soil, gravelly and rocky.
Timber, none; undergrowth, greasewood and cactus.

From the cor. of secs. 4, 5, 8 and 9.

S. $89^{\circ}53'$ W., bet. secs. 5 and 8.

Over level desert land.

17.25 Graded road, bears N. 10° E. toward Salome and generally South.

40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

Set the iron post 22 ins. in the ground, cap mkd.

T3NR13W

$\frac{1}{4}$ $\frac{S \ 5}{S \ 8}$

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the post.

59.00 Leave level valley floor, enter rolling land.

66.50 Saddle of low spur, bears S. and N. 20° W.; desc. W. slope.

78.90 Wash, 15 lks. wide, 4 ft. deep, drains S. 40° E.

80.12 The cor. of secs. 5, 6, 7 and 8.

Land, level E. 60 chains; rolling W. 20 chains.
Soil, alluvial and adobe.
Timber, none; undergrowth, greasewood and cactus.

S. $89^{\circ}51'$ W., bet. secs. 6 and 7.

Over rolling and broken land; no timber.

8.30 Asc. SE. slope of ridge.

15.90 Desc. along S. slope of same ridge.

32.40 Small wash, drains S. 45° E.; asc. SE. slope of ridge.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

Set the iron post 20 ins. in the ground to bedrock and in a collar of stone to top, cap mkd.

T3NR13W

$\frac{1}{4}$ $\frac{S \ 6}{S \ 7}$

1963

Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, N. of the post; falls on gentle SE. slope.

CHAINS

45.70	Ravine, drains S. 25° E.
52.00	Crest of ridge, bears N. and S.; desc. along SW. slope.
67.30	Draw, drains S. 20° W.
73.80	Spur, bears N. and S. 20° W.; desc. SW. slope to cor.
77.16	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township, monumented by an iron post as described in the official record.
	Land, rolling and broken. Soil, rocky. Timber, none; undergrowth, scrub palo verde, cholla and greasewood.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°04' E., bet. secs. 5 and 6.
	Over gently rolling land, through sparse timber and undergrowth.
0.80	Wash, 15 lks. wide, 4 ft. deep, drains S. 40° E.
3.40	Asc. SE. slope of low spur.
14.20	Spur, bears W. and S. 70° E.; thence along E. slope of ridge.
32.50	Crest of ridge, bears N. 40° E. and S. 40° W.; desc. N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	Set the iron post 8 ins. in the ground to bedrock and in a mound of stone to top, cap mkd.
	T3NR13W $\frac{1}{4}$ S 6 S 5 1963
	Raise a mound of stone, 6 ft. base, 4 ft. high, W. of the post; falls on gentle N. slope.
44.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 70° E.; thence over level valley floor.
50.10	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.
64.55	Wash, 15 lks. wide, 1 ft. deep, drains N. 65° E.
80.10	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township, monumented by an iron post, marked and witnessed as described in the official record.
	Land, rolling and level. Soil, gravelly and rocky. Timber, scattered ironwood and palo verde. Undergrowth, cholla, greasewood and ocotillo.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 3 North, Range 13 West, G&SRM, Arizona

General Description

The major portion of Township 3 North, Range 13 West consists of almost level desert land cut with numerous small washes. The land has no surface water and is unfit for anything except limited grazing. The vegetation is sparse with no commercial timber and only scattered undergrowth along the wash areas. Nord's Well, the only well in this township, is located in section 28.

Improvements include the F.A.A. emergency airstrip located in sections 21, 22, 27 and 28, the micro wave station being constructed in sections 35 and 36 at the time of this survey and several unimproved roads leading to these man-made facilities. The proposed route for Interstate Highway No. 10 has been surveyed and when completed will bisect the township as it enters in section 7 and leaves in section 13. This proposed highway is generally known as the Brenda Cutoff.

There are no settlements in this township and no mining activity.

The soil consists of adobe and sand mixed with gravel and stones.

CERTIFICATE OF SURVEY

I, Leonard W. Murphy, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 27 day of June, 1962, I have made a completion survey of the subdivisional lines of Township 3 North, Range 13 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 20, 1963
(Date)

Leonard W. Murphy
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the completion survey of the subdivisional lines of Township 3 North, Range 13 West, Gila and Salt River Meridian, Arizona,

executed by Leonard W. Murphy, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

Washington, D.C.

DEC 23 1963
(Date)

Clark I. Lumm
Acting (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)