

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY

Completion of South Boundary

Completion of Subdivisional Lines

Township 7 North, Range 13 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Leonard W. Murphy, Cadastral Surveyor

Under special instructions dated June 27, 19 62, which provided for the surveys included under Group Number 379, approved July 2, 1962, and assignment instructions dated February 18, 19 63.

Survey commenced February 18, 19 63

Survey completed April 1, 19 63

1A

4691

INDEX DIAGRAM

Township 7 North, Range 13 West,

6	5	4 24	3 17 24	2 9 16	1 8
7	8 30 37	9 23 29	10 15 22	11 8 15	12 7
18 36 36	17 29 35	16 22 28	15 14 21	14 6 13	13 6
19 34 34	20 28 33	21 20 27	22 13 19	23 5 12	24 4
30 32 32	29 26 31	28 19 26	27 11 18	26 3 11	25 3
31 30	32 25	33 17 2	34 10 1	35 2	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 7 North, Range 13 West, Arizona

The north, south, east and west boundaries were surveyed in 1914 by Thorn and Kierulff. Sections 5, 6 and 7 were surveyed in 1914 by W. H. Thorn.

The following field notes are those of a completion survey of a portion of the south boundary and the completion survey of the subdivisional lines of Township 7 North, Range 13 West.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 27, 1962.

The geographic position of the southeast corner of the township is: Latitude 33°53'53" North and Longitude 113°33'24" West as taken from the official plat of the township dated December 30, 1915.

The observed magnetic declination is 14°30' East.

Completion Survey, Portion South Boundary,
T. 7 N., R. 13 W., Arizona

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post as described in the official record.

N. 89°53' W., bet. secs. 3 and 34.

Over mountainous land.

15.00 Leave valley floor; asc. steep and rocky E. slope.

37.90 Crest of ridge, bears N. 10° W. and S. 10° E.; along S. slope.

40.10 Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate dist.; there being no corner set during original survey.

Set the iron post 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with the cap mkd.

T7NR13W
¼ $\frac{S\ 34}{S\ 3}$
T6N
1963

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of post.

Cont. along S. slope.

CHAINS	
52.00	Ravine, 120 lks. wide, drains S. 20° E.; asc. very steep E. slope.
66.50	Top of mountain bears N. and S. 10° W.; desc. over steep SW. slope.
80.20	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there being no corner set during original survey. Set the iron post 6 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T7NR13W S33 S34 S 4 S 3 T6N 1963
	Land, mountainous. Soil, rocky. Timber, scrub palo verde. Undergrowth, greasewood and cactus.
	N. 89°53' W., bet. secs. 4 and 33. Over mountainous land. Desc. steep and rocky SW. slope.
14.80	Ravine, 30 lks. wide, 3 ft. deep, drains S. 10° W.
34.80	Spur, projects S.; cont. along S. slope.
40.10	The ¼ sec. cor. of secs. 4 and 33, monumented by an iron post as described in the official record. Land, mountainous. Soil, rocky. Timber, sparse palo verde. Undergrowth, greasewood and cactus.
Survey Completing the Subdivisional Lines, T. 7 N., R. 13 W., Arizona	
	From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township, monumented by an iron post as described in the official record. N. 0°01' W., bet. secs. 35 and 36. Over nearly level land.
8.30	Wash, 80 lks. wide, 2 ft. deep, drains S. 10° E.
15.70	Jeep road, bears N. 15° W., S. 15° E.
29.60	Wash, 40 lks. wide, 4 ft. deep, drains S. 25° E.
40.00	Point for the ¼ sec. cor. of secs. 35 and 36. Set the iron post 20 ins. in the ground, cap mkd.
	T7NR13W ¼ S35 S36 1963

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 7 N., R. 13 W., Arizona
43.50	Wash, 15 lks. wide, 1 ft. deep, drains S. 20° E.
52.50	Wash, 100 lks. wide, 10 ft. deep, drains S. 25° E.
64.20	Wash, 40 lks. wide, 4 ft. deep, drains S. 20° E.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
	Set the iron post 22 ins. in the ground, cap mkd.
	T7NR13W S26 S25 S35 S36 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.
	Land, nearly level. Soil, rocky. Timber, palo verde, mesquite. Undergrowth, ocotillo, greasewood and cactus.
	<hr/> From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township, monumented by an iron post as described in the official record.
	N. 89°55' W., bet. secs. 25 and 36.
	Over nearly level land, through scattered timber.
16.40	Wash, 110 lks. wide, 2 ft. deep, drains S. 20° E.
40.01	Point for the ¼ sec. cor. of secs. 25 and 36.
	Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W ¼ S 25 S 36 1963
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of post.
49.00	Wash, 140 lks. wide, 10 ft. deep, drains S. 30° E.
62.00	Graded road, bears N. 15° W. and S. 15° E.; leads to Bonanza mine.
77.60	Wash, 40 lks. wide, 3 ft. deep, drains S.
80.02	The cor. of secs. 25, 26, 35 and 36.
	Land, nearly level. Soil, rocky and gravelly. Timber, scattered palo verde and mesquite. Undergrowth, cactus.
	<hr/> N. 0°01' W., bet. secs. 25 and 26.
	Over mountainous land.

CHAINS		
16.50	Graded road, bears N. 45° W. and S. 45° E.; leads to Bonanza mine.	
19.00	Wash, 80 lks. wide, 8 ft. deep, drains S. 45° E.	
40.00	Point for the ¼ sec. cor. of secs. 25 and 26.	
	Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	<p style="text-align: center;">T7NR13W ¼ S26 S25 1963</p>	
48.40	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of post.	
51.20	Spur, bears N. 60° E. and S. 60° W.	
80.00	Ravine, drains irregularly SW.; asc. steep and rocky S. slope.	
80.00	Point for the cor. of secs. 23, 24, 25 and 26.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	<p style="text-align: center;">T7NR13W S23 S24 S26 S25 1963</p>	
29.00	Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of post; falls on steep S. slope.	
	<p>Land, mountainous N ½ mile; nearly level S ½ mile. Soil, rocky and gravelly. Timber, sparsely scattered palo verde. Undergrowth, ocotillo, greasewood and cactus.</p>	
40.04	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township, monumented by an iron post as described in the official record.	
40.04	N. 89°56' W., bet. secs. 24 and 25.	
29.00	Asc. gentle E. slope, over a series of small washes draining generally S.	
40.04	Enter onto broken land; asc. steep and rocky slope draining SE.	
40.04	Point for the ¼ sec. cor. of secs. 24 and 25.	
	Set the iron post 18 inches in the ground to bedrock, mound with stone to top, cap mkd.	
	<p style="text-align: center;">T7N R13W ¼ $\frac{S\ 24}{S\ 25}$ 1963</p>	
40.50	Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of post; falls on steep E. slope.	
	Cont. ascending E. slope.	
40.50	Crest of low spur, slopes SE.; desc. W. slope.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 7 N., R. 13 W., Arizona
50.00	Wash, 25 lks. wide, drains S. 30° E.
59.00	Spur, slopes SE.; along S. slope.
67.00	Wash, 20 lks. wide, drains S.
72.00	Spur, slopes S.
80.08	The cor. of secs. 23, 24, 25 and 26.
	Land, mountainous. Soil, rocky. Timber, scattered palo verde. Undergrowth, greasewood, ocotillo, saguaro and other cacti..
	N. 0°01' W., bet. secs. 23 and 24.
	Over mountainous land, through sparse vegetation.
	Cont. asc. rocky and very steep S. slope of mountain.
7.30	Spur, bears N. 20° E. and S. 20° W.; continue ascending.
20.40	Top of mountain, bears E. and W.; desc. N. slope.
29.65	Ravine, drains N. 55° E.; asc. along E. slope.
36.80	Crest of spur, bears N. 35° E. and S. 35° W.; desc. abrupt N. slope.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set the iron post on solid rock, mound with stone to top, cap mkd.
	T7NR13W 1/4 S23 S24 1963
	Cont. desc. N. slope.
49.60	Slope changes; asc. along W. slope.
71.50	Ridge, bears N. 45° W. and S. 45° E.; desc. N. slope.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W S14 S13 S23 S24 1963
	Raise a mound of stone, 3 1/2 ft. base, 3 ft. high, W. of post; falls on gentle N. slope.
	Land, mountainous. Soil, rocky. Timber, scattered palo verde. Undergrowth, ocotillo, barrel, cholla and other cacti.

CHAINS		
	<p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. 89°56' W., bet. secs. 13 and 24.</p> <p>Over mountainous land.</p> <p>Asc. over a series of small spurs and washes draining generally E.</p>	
33.37	Crest of mountain ridge, bears N. and S.; desc. W. slope.	
40.04	<p>Point for the ¼ sec. cor. of secs. 13 and 24.</p> <p>Set the iron post 18 ins. in the ground to bedrock and in a collar of stone to top, with the cap mkd.</p> <p style="text-align: center;">T7NR13W ¼ S 13 S 24 1963</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post; falls on steep W. slope.</p>	
41.50	End desc.; thence over gentle W. slope.	
61.70	Ravine, 3 chains wide, drains N. 35° W.; along gentle N. slope.	
80.08	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, mountainous. Soil, rocky, gravelly. Timber, scattered palo verde, mesquite. Undergrowth, ocotillo, bur sage, cholla, prickly pear and yucca.</p>	
	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land, through sparse timber.</p>	
15.20	Ravine, 50 lks. wide, drains N. 20° W.; end desc.	
25.30	Wash, 20 lks. wide, 2 ft. deep, drains N. 40° W. for 2 chs. thence N.	
30.00	Low ridge, slopes W.; desc. N. slope.	
34.20	Jeep road, bears N. 10° E. and S.	
40.00	<p>Point for the ¼ sec. cor. of secs. 13 and 14.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W ¼ S14 S13 1963</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post; falls on nearly level land.</p>	
56.00	Wash, 45 lks. wide, 3 ft. deep, drains N. 15° E.; asc. along E. slope.	
57.80	Jeep road, bears N. 20° E. and S. 20° W.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 7 N., R. 13 W., Arizona
75.81	Section line intersects bearing rock for Cor. No. 1 of the Critic Mining Claim which is marked with the letters C 1 'x' 2468 chiseled on a granite rock 8 ft. by 7 ft.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W <u>S11</u> <u>S12</u> <u>S14</u> <u>S13</u> 1963
	from which U.S. Location Monument No. 2468 Harcuvar Mining District, bears N. 15°54' E., 5.82 chs. dist., monumented by an 'x' on a granite rock in place, marked USLM No. 2468 H.D. The rock is badly decomposed. I find the bearing rocks in excellent condition. Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of post; falls on gentle E. slope. Land, rolling. Soil, rocky. Timber, scattered palo verde. Undergrowth, ocotillo, greasewood and cactus.
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township, monumented by an iron post as described in the official record. S. 89°59' W., bet. secs. 12 and 13. Over gently rolling land; desc. SW. slope.
2.25	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
5.50	Road, graded, leads to Alamo Crossing; asc. E. slope.
10.67	Intersect line 2-3, Old Timer lode, M.S. 3529 at a point from which Cor. No. 2 bears S. 39°04' E., 7.08 chs. dist.
20.00	Spur, slopes N.; along N. slope.
20.10	Intersect line 1-2, Teddy lode, M.S. 3530 at a point from which Cor. No. 2 bears S. 30°40' W., 3.14 chs. dist.
24.84	Intersect line 2-3, Teddy lode, M.S. 3530 at a point from which Cor. No. 2 bears S. 49°13'30" E., 4.15 chs. dist.
34.20	Powerline, bears N. 56° W. and S. 56° E.
37.00	Powerline, bears N. 56° W. and S. 56° E.
38.60	Powerline maintenance road, bladed only, parallels powerline.
40.07	Point for the ¼ sec. cor. of secs. 12 and 13. Set the iron post 22 ins. in the ground, cap mkd.
	T7NR13W ¼ <u>S 12</u> <u>S 13</u> 1963

CHAINS	
	Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of post.
59.34	Intersect line 3-4, Last Chance lode, M.S. 2470, at a point from which Cor. No. 4 bears N. 40°30' W., 6.76 chs. dist.
67.35	Jeep road, bladed only, bears N. and S.
67.93	Intersect line 1-4, Last Chance lode, M.S. 2470, at a point from which Cor. No. 4 bears N. 39°15' E., 6.64 chs. dist.
70.00	Jeep road, bladed, leads S. to the Critic Mine and NW.
74.40	Wash, 50 lks. wide, 2 ft. deep, drains N. 5° W.; asc. to cor.
80.14	The cor. of secs. 11, 12, 13 and 14. Land, rolling. Soil, gravelly, rocky. Timber, palo verde. Undergrowth, ocotillo, greasewood and bur sage.
	N. 0°01' W., bet. secs. 11 and 12. Over gently rolling land.
5.10	Top of rocky knoll; desc. N. slope.
13.15	Bladed road, bears E. and W.
16.30	Wash, 45 lks. wide, drains N. 70° W.; over level land.
35.30	Powerline, bears N. 56° W. and S. 56° E.; also maintenance road.
37.65	Powerline, bears N. 56° W. and S. 56° E.; also maintenance road.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12. Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W ¼ S11 S12 1963
	Raise a mound of earth and stone, 3 ft. base, 2 ft. high, W. of post; falls on level land.
58.50	Wash, 40 lks. wide, 1 ft. deep, drains N. 40° W.
64.10	Graded road, leads to Alamo Crossing, bears approx. N. 30° W. and S. 30° E.
72.30	Wash, 15 lks. wide, 2 ft. deep, drains N. 25° W.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W S 2 S 1 S11 S12 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post. Land, gently rolling. Soil, gravelly. Timber, scattered palo verde. Undergrowth, cactus.
	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township, monumented by an iron post as described in the official record. S. 89°57' W., bet. secs. 1 and 12.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
	Over gently sloping land; desc. W. slope.
22.80	Wash, 15 lks. wide, 1 ft. deep, drains N. 25° W.
28.50	Jeep road, bears N. 15° E. and S. 15° W.
37.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.
40.08	Point for the ¼ sec. cor. of secs. 1 and 12.
	Set the iron post 22 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4} \begin{array}{c} S \ 1 \\ S \ 12 \end{array}$ 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post.
58.00	El Paso natural gas pipeline, bears N. 25° W. and S. 25° E.
70.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 60° W.
80.16	The cor. of secs. 1, 2, 11 and 12.
	Land, broken E. ½ mile; level W. ½ mile. Soil, sandy, gravelly. Timber, scattered palo verde. Undergrowth, greasewood, ocotillo and cactus.
	N. 0°02' W., bet. secs. 1 and 2.
	Over nearly level land, through medium dense timber.
14.10	Wash, 20 lks. wide, 1 ft. deep, drains N. 30° W.
21.20	Wash, 50 lks. wide, 2 ft. deep, drains N. 45° W.
28.50	El Paso natural gas pipeline, bears N. 25° W. and S. 25° E.
39.40	Point selected for the witness ¼ sec. cor. of secs. 1 and 2.
	Set the iron post 20 ins. in the ground, cap mkd.
	T7NR13W WC $\frac{1}{4}$ S 2 S 1 1963
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of post.
40.00	True point for the ¼ sec. cor. of secs. 1 and 2 falls in center of wash, 60 lks. wide, 2 ft. deep, drains N. 30° W.; area subject to flood where the monument cannot be perpetuated.
42.00	Asc. S. slope.

CHAINS

49.75 Spur, slopes W.; desc. along NW. slope.

58.00 Enter nearly level valley floor.

80.12 The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the township, monumented by an iron post as described in the official record.

Land, gently rolling.
Soil, rocky.
Timber, medium-dense palo verde.
Undergrowth, cactus.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post as described in the official record.

N. 0°01' W., bet. secs. 34 and 35.

Over rolling land, through scattered timber and undergrowth.

14.50 Crest of low spur, slopes SE.

25.40 Wash, 20 lks. wide, 5 ft. deep, drains S. 45° E.

38.18 Wash, 40 lks. wide, 8 ft. deep, drains S. 45° E.

40.00 Point for the ¼ sec. cor. of secs. 34 and 35.

Set the iron post 12 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T7NR13W
¼
S34|S35
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.

Cor. falls on gentle SW. slope and W. side of large boulder.

59.30 Asc. rocky and steep S. slope.

66.50 Spur, bears N. 45° W. and S. 45° E.; desc. along NE. slope.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T7NR13W
S27|S26
S34|S35
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.

Cor. falls on gentle NE. slope.

Land, gently rolling.
Soil, rocky.
Timber, scattered palo verde.
Undergrowth, ocotillo, bur sage and cactus.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
	<p>From the cor. of secs. 25, 26, 35 and 36. N. 89°57' W., bet. secs. 26 and 35. Over level land, through scattered timber.</p>
37.00	Asc. SE. slope.
40.02	Point for the ¼ sec. cor. of secs. 26 and 35.
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W ¼ $\frac{S\ 26}{S\ 35}$ 1963</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post. Cor. falls on SE. slope.</p>
45.00	Asc. along SE. slope.
47.90	Spur, bears N. 30° W. and S. 30° E.; desc. along S. slope.
80.04	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling and broken W. ½ mile; nearly level E. ½ mile. Soil, rocky. Timber, scattered palo verde. Undergrowth, ocotillo, cholla and other desert cacti.</p>
	<p>N. 0°01' W., bet. secs. 26 and 27. Over mountainous land, no timber.</p>
6.00	Asc. steep SW. slope.
19.57	Crest of broken spur, slopes SE.; desc. broken NE. slope.
33.50	Rocky ravine, drains NE.; asc. along E. slope.
39.60	<p>Point selected for the witness ¼ sec. cor. of secs. 26 and 27.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W WC ¼ S27 S26 1963</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post. Cor. set on steep E. slope of mountain.</p>
40.00	True point for the ¼ sec. cor. of secs. 26 and 27 falls on steep and rocky face where it is impossible to monument.

CHAINS

- 40.20 Rocky wash, drains SE.; asc. steep S. slope.
- 43.00 Crest of ridge, projects E.; thence over a series of small spurs sloping E.
- 69.00 Spur, bears NW. and SE.; desc. steep NE. slope.
- 78.00 Rocky wash, drains SE.; asc. steep SW. slope.
- 80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T7NR13W
 S22 | S23
 S27 | S26
 1963

Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of post.

Cor. falls on steep SW. slope.

Land, broken mountainous.

Soil, rocky.

Timber, none.

Undergrowth, saguaro, barrel and other cacti.

From the cor. of secs. 23, 24, 25 and 26.

N. $89^{\circ}56'$ W., bet. secs. 23 and 26.

Asc. along S. slope.

- 2.50 Crest of spur, slopes S.
- 12.00 Wash, 40 lks. wide, 3 ft. deep, drains S. 35° W.; over rolling land.
- 27.00 Wash, 45 lks. wide, 2 ft. deep, drains S. 30° E.; leave rolling land, asc. broken S. slope.
- 36.00 Spur, slopes SE.; desc. along S. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.

Set the iron post on solid rock, mound with stone, 4 ft. base to top, cap mkd.

T7NR13W
 $\frac{1}{4}$ S 23
 S 26
 1963

Cor. falls on rocky SW. slope.

- 41.00 Rocky wash, drains SE.; asc. steep NE. slope.
- 55.00 Rocky spur, slopes SE.; desc. SW. slope.
- 62.00 Wash, 50 lks. wide, 4 ft. deep, drains SSE.
- 78.50 Spur, slopes SE.; desc. S. slope.
- 80.00 The cor. of secs. 22, 23, 26 and 27.

Land, mountainous.

Soil, rocky.

Timber, scattered palo verde.

Undergrowth, ocotillo, saguaro and other cacti.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 7 N., R. 13 W., Arizona
	N. 0°01' W., bet. secs. 22 and 23.
	Over mountainous land.
1.00	Crest of spur, slopes SE.; asc. steep and rocky SE. slope.
16.50	Ridge top, bears NE. and SW.; desc. W. slope.
24.60	Spur, slopes N. 10° W., desc. steep E. slope.
37.40	Slope changes to NE.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23.
	Set the iron post 20 ins. in the ground, cap mkd.
	T7NR13W ¼ S22 S23 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.
	Cor. falls on steep and rocky NE. slope.
54.00	Wash, 40 lks. wide, 3 ft. deep, drains irregularly E.; asc. along steep SE. slope.
71.00	Wash, drains SE.; cont. along SE. slope.
76.00	Spur, slopes E.; desc. along NE. slope.
79.90	Point selected for the witness cor. of secs. 14, 15, 22 and 23.
	Set the iron post 10 ins. in the ground to bedrock, mound with stone, 3 ft. base to top, cap mkd.
	T7NR13W WC S15 S14 S22 S23 1963
	Cor. sets on small ledge of steep NE. slope.
80.00	True point for the cor. of secs. 14, 15, 22 and 23 falls on steep face of mountain where the cor. cannot be set.
	Land, mountainous. Soil, rocky. Timber, scattered palo verde. Undertrowth, greasewood and cactus.
	From the cor. of secs. 13, 14, 23 and 24.
	S. 89°58' W., bet. secs. 14 and 23.
	Over mountainous land, through scattered timber.

14

CHAINS	
	Asc. along N. slope.
5.00	Spur, slopes NE.; desc. NW. slope.
10.00	Over gently rolling land.
25.50	Wash, 60 lks. wide, 5 ft. deep, drains N.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	Set the iron post 22 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4}$ $\frac{S 14}{S 23}$ 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post.
42.10	Rocky wash, 50 lks. wide, 4 ft. deep, drains N. 70° E.
51.00	Bladed road, bears irregularly NE. and SW.
65.30	Leave rolling land; asc. broken E. slope of mountain.
75.00	Rocky draw, drains SE.; cont. asc.
80.02	True point for the cor. of secs. 14, 15, 22 and 23.
	Land, mountainous. Soil, rocky. Timber, scattered palo verde. Undergrowth, greasewood and cactus.
	N. 0°01' W., bet. secs. 14 and 15.
	Over mountainous land; desc. along NE. slope.
.50	Rocky wash, drains SE.; asc. rocky SE. slope.
8.80	Spur, slopes SE.; desc. rocky NE. slope.
18.00	Wash, 30 lks. wide, 3 ft. deep, drains E.
32.20	Wash, 20 lks. wide, 2 ft. deep, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
	Set the iron post 4 ins. in the ground to bedrock, mound with stone, 3 ft. base to top, cap mkd.
	T7NR13W $\frac{1}{4}$ S15 S14 1963
	Cor. falls on crest of spur that slopes E.
	Desc. NE. slope.
53.10	Wash, 15 lks. wide, 2 ft. deep, drains N. 35° E.
56.40	Spur, slopes E.; desc. along E. slope.
76.50	Wash, 30 lks. wide, 3 ft. deep, drains N.; over a series of small spurs slope NW.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set the iron post 24 ins. in the ground, cap mkd.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 7 N., R. 13 W., Arizona
	T7NR13W <u>S10</u> <u>S11</u> <u>S15</u> <u>S14</u> 1963
	Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of post. Cor. falls on rocky N. slope. Land, mountainous. Soil, rocky. Timber, none. Undergrowth, ocotillo, saguaro, buckhorn and other cacti.
	From the cor. of secs. 11, 12, 13 and 14. S. 89°56' W., bet. secs. 11 and 14. Asc. steep NE. slope of mountain.
4.71	Intersect line 1-2, Critic Mine lode, at a point from which Cor. No. 1 bears S. 53°28' E., 5.52 chs. dist.
12.00	Rocky spur, slopes NE.
19.94	Intersect line 3-4, Critic Mine lode, at a point from which Cor. No. 3 bears N. 53°28' W., 4.90 chs. dist.
28.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 15° E.; asc. rocky NE. slope.
34.00	Crest of spur, slopes NE.; desc. NW. slope.
39.20	Small wash, drains N. 10° W.; asc. NE. slope.
40.00	Point for the ¼ sec. cor. of secs. 11 and 14. Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T7NR13W ¼ <u>S 11</u> <u>S 14</u> 1963
	Cor. falls on rocky NE. slope. Cont. asc. NE. slope.
59.90	Spur, slopes N.; desc. along N. slope.
68.00	Low spur, slopes NW.; desc. steep W. slope.
78.15	Small wash, drains irregularly N.
80.00	The cor. of secs. 10, 11, 14 and 15. Land, mountainous. Soil, rocky. Timber, scattered palo verde. Undergrowth, greasewood and cactus.
	N. 0°01' W., bet. secs. 10 and 11. Desc. gentle NE. slope.
2.00	Small wash, drains N. 35° E.

CHAINS		
8.10	Bladed road, bears irregularly NE. and SW.; over nearly level land.	
25.60	Wash, 40 lks. wide, 2 ft. deep, drains N. 25° W.	
40.00	Point for the ¼ sec. cor. of secs. 10 and 11.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T7NR13W	
	¼	
	S10 S11	
	1963	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.	
	Cor. falls on nearly level land.	
44.40	Small wash, drains N. 45° W.	
65.10	Bladed road, bears N. 80° E. and S. 80° W.	
80.00	Point for the cor. of secs. 2, 3, 10 and 11.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T7NR13W	
	S 3 S 2	
	S10 S11	
	1963	
	from which	
	U.S. Geological Survey bench mark bears N. 55°28' W., 10.58 chs. dist., mkd. 1951 2117 FT 4D.	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.	
	Land, nearly level.	
	Soil, sandy, gravelly.	
	Timber, scattered palo verde.	
	<hr/>	
	From the cor. of secs. 1, 2, 11 and 12.	
	S. 89°56' W., bet. secs. 2 and 11.	
	Over nearly level land.	
8.50	Graded road, through Cunningham Pass, bears N. 30° W. and S. 30° E.	
22.00	Wash, 50 lks. wide, 5 ft. deep, drains irregularly NW.	
40.02	Point for the ¼ sec. cor. of secs. 2 and 11.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T7NR13W	
	¼ $\frac{S 2}{S 11}$	
	1963	
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of post.	
	Cor. falls on moderate W. slope.	
40.60	Wash, 40 lks. wide, 4 ft. deep, drains irregularly NW.	
42.00	Powerline maintenance road, bears N. and S. at this point.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
43.20	Crest of low spur, bears N.; desc. W. slope.
50.00	Powerline maintenance road, curves around low spur noted above.
74.30	Powerline, bears N. 67°W. and S. 67° E.
78.10	Powerline, bears N. 67° W. and S. 67° E.
80.04	The cor. of secs. 2, 3, 10 and 11. Land, nearly level. Soil, sandy and gravelly. Timber, palo verde. Undergrowth, greasewood and cactus.
	N. 0°02' W., bet. secs. 2 and 3.
	Over nearly level land, through medium dense timber and undergrowth.
.60	Powerline, bears N. 67° W. and S. 67° E.
2.10	Powerline, bears N. 67° W. and S. 67° E.
9.20	Bladed road, bears S. 45° W. and N. 45° E.
25.10	Jeep road, bears N. 70° W. and S. 70° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3. Set the iron post 24 ins. in the ground, cap mkd. T7NR13W $\frac{1}{4}$ S 3 S 2 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.
49.10	Wash, 25 lks. wide, 2 ft. deep, drains N. 45° W.
80.34	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the township, monumented by an iron post as described in the official record. Land, nearly level. Soil, sandy, gravelly. Timber, palo verde. Undergrowth, cactus.
	From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township.
	N. 0°02' W., bet. secs. 33 and 34.
	Asc. SW. slope of mountain.
1.50	Crest of spur, slopes W.; desc. over broken land.
13.00	Draw, drains W.; asc. S. slope.

CHAINS		
33.00	Draw, drains SW.; cont. asc.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.	
	Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	<p style="text-align: center;">T7NR13W $\frac{1}{4}$ S33 S34 1963</p>	
	Cor. falls 5 lks. N. of a rock, 10 ft. long, 6 ft. high.	
	Cont. asc. SE. slope.	
56.70	Ridge top, bears irregularly NE. and NW.; desc. E. slope.	
68.80	Crest of spur, slopes NE.; desc. over broken land.	
76.90	Draw, drains E.; asc. S. slope to cor.	
80.00	Point for the cor. of secs. 27, 28, 33 and 34.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	<p style="text-align: center;">T7NR13W <u>S28 S27</u> S33 S34 1963</p>	
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of post.	
	Cor. falls on S. slope.	
	<p>Land, mountainous. Soil, rocky. Timber, sparse palo verde. Undergrowth, ocotillo, saguaro and greasewood.</p>	
	From the cor. of secs. 26, 27, 34 and 35.	
	N. $89^{\circ}48'$ W., bet. secs. 27 and 34.	
	Asc. steep and broken NE. slope.	
23.00	Crest of spur, slopes SE.; cont. asc.	
29.10	Crest of spur, slopes irregularly SE.; desc. steep SW. slope.	
38.60	Rocky ravine, drains S.; asc. along S. slope of mountain.	
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.	
	Set the iron post on solid rock, mound with stone, $3\frac{1}{2}$ ft. base, to top, cap mkd.	
	<p style="text-align: center;">T7NR13W $\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$ 1963</p>	
	Cor. falls on steep SE. slope.	
48.00	Rocky ravine, drains SE.; cont. asc.	
56.20	Crest of spur, slopes NE. for 3 chs., then E.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
66.30	Crest of spur, slopes N.; desc. NW. slope.
74.80	Rocky wash, drains NE.; asc. along S. slope.
80.24	The cor. of secs. 27, 28, 33 and 34.
	Land, broken, mountainous. Soil, rocky. Timber, none. Undergrowth, greasewood and cactus.
	N. 0°02' W., bet. secs. 27 and 28.
	Over broken land, no timber.
6.40	Rocky draw, drains SE.; cont. asc.
18.80	Crest of spur, slopes SE.; desc. W. slope.
39.70	Crest of spur, slopes W.; cont. desc. NW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	Set the iron post 16 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T7N R13W $\frac{1}{4}$ S28 S27 1963
	Cor. falls on NW. slope.
54.00	Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. over broken land.
70.50	Crest of broken spur, slopes N. 70° E.; desc. N. slope.
79.70	Wash, 30 lks. wide, 2 ft. deep, drains E.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set the iron post 10 ins. in the ground to bedrock, mound with stone, 4 ft. base to top, cap mkd.
	T7NR13W S21 S22 S28 S27 1963
	Cor. falls on S. slope, 15 lks. N. of wash.
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, ocotillo, yucca, and other cacti.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°47' W., bet. secs. 22 and 27.
	Desc. along S. slope.

CHAINS		
5.00	Rocky draw, drains S. 10° E.; asc. steep E. slope.	
9.10	Ridge top, bears irregularly NE. and SW.; desc. NW. slope.	
22.00	Draw, drains N. 15° W.	
33.00	Rocky wash, 65 lks. wide, 2 ft. deep, drains N.; asc. steep NE. slope.	
40.08	Point for the ¼ sec. cor. of secs. 22 and 27.	
	Set the iron post on bedrock, mound with stone, 3½ ft. base to top, cap mkd.	
	T7NR13W	
	¼ S 22	
	S 27	
	1963	
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of post.	
	Cor. falls on steep NE. slope.	
	Asc. NE. slope.	
40.20	Narrow gage railroad track, bears S. 70° W. to prospect hole and N. 70° E.	
51.20	Crest of spur, slopes NE.; along N. slope.	
67.00	Rocky draw, drains N. 40° E.	
78.40	Wash, 30 lks. wide, 2 ft. deep, drains N. 80° E.	
80.16	The cor. of secs. 21, 22, 27 and 28.	
	Land, mountainous.	
	Soil, rocky.	
	Timber, none.	
	Undergrowth, ocotillo, saguaro and other cacti.	
	N. 0°02' W., bet. secs. 21 and 22.	
	Over mountainous land, no timber.	
.15	Asc. very steep S. slope.	
11.60	Ridge, bears E. and W.; desc. NE. slope.	
18.00	Ravine, drains N. 70° E.; asc. along E. slope.	
25.90	Spur, bears E. and W.; desc. N. slope.	
40.00	Point for the ¼ sec. cor. of secs. 21 and 22.	
	Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	T7NR13W	
	¼	
	S21 S22	
	1963	
	Cor. falls on steep N. slope.	
55.50	Ravine, 60 lks. wide, drains N. 35° W.; asc. SW. slope.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
60.15	Spur, slopes W.; desc. N. slope.
67.00	Wash, 20 lks. wide, drains N. 65° W.; along W. slope of mountain.
74.80	Wash, 20 lks. wide, drains N. 70° W.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.
	T7NR13W <u>S16</u> <u>S15</u> <u>S21</u> <u>S22</u> 1963
	Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of post.
	Cor. falls on NW. slope of mountain.
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, ocotillo, Spanish sword and cacti.
	From the true point for the cor. of secs. 14, 15, 22 and 23.
	N. 89°48' W., bet. secs. 15 and 22.
	Asc. steep broken SE. slope of mountain.
11.50	Top of mountain, bears NE. and SW.; desc. NW. slope.
18.00	Draw, drains N. 45° E.; asc. E. slope.
27.00	Ridge, bears N. and SW.; desc. steep W. slope.
38.40	Head of draw, drains N.
39.80	Crest of spur, slopes NW.; desc. SW. slope.
40.12	Point for the ¼ sec. cor. of secs. 15 and 22.
	Set the iron post 10 ins. in the ground to bedrock, mound with stone 3½ ft. base to top, cap mkd.
	T7NR13W ¼ <u>S 15</u> <u>S 22</u> 1963
	Cor. falls on SW. slope.
53.00	Rocky wash, 40 lks. wide, 3 ft. deep, drains N. 45° W.
60.00	Wash, 45 lks. wide, 3 ft. deep, drains N. 40° W.
71.00	Crest of spur, slopes N. 25° W.; desc. NW. slope.
80.24	The cor. of secs. 15, 16, 21 and 22.
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, greasewood and cactus.

CHAINS	
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over mountainous land, no timber.</p> <p>Along the W. slope of mountain.</p>
16.80	Wash, 30 lks. wide, 3 ft. deep, drains N. 75° W.
29.89	Intersect line 3-4, Midget lode, at a point from which Cor. No. 4 bears S. 58°26' E., 2.89 chs. dist.
33.90	Wash, 25 lks. wide, 3 ft. deep, drains N. 35° W.; asc. along W. slope.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W 1/4 S16 S15 1963</p> <p>from which</p> <p style="padding-left: 40px;">U.S.L.M. No. 2482 bears N. 45°38' E., 4.72 chs. dist., monumented by a granite stone, 48 x 20 x 7 ins., firmly set, mkd. USLM No. 2482 chiseled on W. face and X to mark the exact point. Mound of stone 6 ft. by 5 ft. alongside the monument. Both of the bearing rocks are as noted in the official record.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.</p> <p>Asc. along W. slope.</p>
46.15	Spur, slopes W.; desc. along gentle W. slope.
57.90	Wash, 40 lks. wide, 2 ft. deep, drains N. 20° W.
61.90	Intersect line 2-3, Ada lode, at a point from which Cor. No. 3 bears N. 58°26' W., 3.05 chs. dist.
73.10	Wash, 10 lks. wide, 2 ft. deep, drains N. 15° W.
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set the iron post 22 ins. in the ground, mound with stone, 4 ft. base to top, cap mkd.</p> <p style="text-align: center;">T7NR13W S9 S10 S16 S15 1963</p> <p>Cor. falls on gentle W. slope.</p> <p>Land, mountainous. Soil, rocky. Timber, none. Undergrowth, ocotillo, cholla and other cacti.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°44' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through scattered timber.</p>
1.00	Small wash, drains NE.; asc. over rolling land.
17.10	Small wash, drains irregularly N.; asc. E. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
20.00	Crest of low spur, slopes NE.
37.30	Wash, 30 lks. wide, 2 ft. deep, drains N.
39.80	Wash, 30 lks. wide, 2 ft. deep, drains NE. for 4 chs., then N.
40.14	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Set the iron post 5 ins. in the ground to bedrock, mound with stone, 4 ft. base to top, cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{1}{4}$ $\frac{S 10}{S 15}$ 1963</p> <p>Cor. falls on gentle NE. slope.</p> <p>Asc. along N. slope.</p>
45.90	Crest of spur, projects N. 10° E.; desc. steep W. slope.
55.00	Rocky wash, 35 lks. wide, 3 ft. deep, drains N.
66.20	Wash, 30 lks. wide, 2 ft. deep, drains NW.; asc. steep NE. slope.
78.80	Crest of broken spur, slopes NW.; desc. SW. slope to corner.
80.28	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, rocky. Timber, none. Undergrowth, greasewood, saguaro and ocotillo.</p>
	<p>N. $0^\circ 02'$ W., bet. secs. 9 and 10.</p> <p>Desc. NW, slope of mountain.</p>
14.50	Enter valley.
26.00	Unimproved road, bears NE. and SW.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{1}{4}$ S 9 S 10 1963</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of post.</p>
58.20	Unimproved road, bears N. 40° W. and S. 40° E.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.

CHAINS		
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{S\ 4}{S\ 9} \frac{S\ 3}{S\ 10}$ 1963</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of post.</p> <p>Land, rolling 15 chains; nearly level 65 chains. Soil, sandy and gravelly. Timber, sparse palo verde; undergrowth, greasewood and cactus.</p>	
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°44' W., bet. secs. 3 and 10.</p> <p>Over nearly level land of Butler Valley.</p>	
1.90	Small wash, drains S. 40° W.	
40.12	<p>Point for the ¼ sec. cor. of secs. 3 and 10.</p> <p>Set the iron post 24 ins. in the ground with cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{1}{4} \frac{S\ 3}{S\ 10}$ 1963</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, N. of post.</p>	
59.00	Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.	
80.24	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, level. Soil, sandy and gravelly. Timber, scattered palo verde. Undergrowth, greasewood.</p>	
	<p>N. 0°04' E., bet. secs. 3 and 4.</p> <p>Over nearly level land, through scattered timber.</p>	
21.60	Wash, 40 lks. wide, 1 ft. deep, drains W.	
32.00	Maintenance road for powerline, bears N. 68° W. and S. 68° E.	
32.40	Powerline, bears N. 67°55' W. and S. 67°55' E.	
34.10	Powerline, bears N. 67°55' W. and S. 67°55' E.	
40.00	<p>Point for the ¼ sec. cor. of secs. 3 and 4.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{1}{4} \frac{S\ 4}{S\ 3}$ 1963</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of post.</p>	
44.30	Wash, 30 lks. wide, 1 ft. deep, drains N. 45° W.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
65.70	Graded road, bears N. 40° W. toward Swansea and S. 40° E.
69.40	Jeep road, bears N. 45° W. and S. 45° E.
77.20	Small wash, drains W.
80.21	<p>The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>Land, nearly level. Soil, gravelly and sandy. Timber, sparse palo verde. Undergrowth, greasewood and cactus.</p>
15.00	<p>From the true point for the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township; the witness cor. bears N. 89°55' W., 0.57 chs. dist., monumented by an iron post as described in the official record.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Asc. over rolling land, through scattered timber.</p>
25.00	Wash, 35 lks. wide, 3 ft. deep, drains S. 20° E.
40.00	Begin asc. steep SW. slope.
48.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
58.50	Set the iron post 10 ins. in the ground to bedrock, mound with stone, 4 ft. base to top, cap mkd.
	<p style="text-align: center;">T7NR13W 1/4 S32 S33 1963</p>
	Cor. falls on rocky SW. slope.
48.00	Rocky draw, drains S. 70° W.; cont. asc.
58.50	Rocky draw, drains S. 45° W.
67.00	Crest of spur, slopes sharply SW.
79.20	Rocky draw, drains S. 35° W.; cont. asc.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set the iron post 4 ins. in the ground to bedrock, mound with stone, 5 ft. base to top, cap mkd.
	<p style="text-align: center;">T7NR13W S29 S28 S32 S33 1963</p>
	Cor. falls on S. slope.
	<p>Land, broken mountainous. Soil, rocky. Timber, scattered palo verde. Undergrowth, greasewood and cactus.</p>

CHAINS	
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°54' W., bet. secs. 28 and 33.</p> <p>Over mountainous land, through sparse timber.</p> <p>Asc. along S. slope.</p>
13.30	Ridge, bears NE. and SW.
31.00	Crest of spur, slopes S. 20° E.; along top of mountain.
40.03	<p>Point for the ¼ sec. cor. of secs. 28 and 33.</p> <p>Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{1}{4}$ $\frac{S\ 28}{S\ 33}$ 1963</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post.</p> <p>Cor. falls on gentle S. slope.</p>
43.20	Crest of long spur, slopes S. 15° W.; desc. steep SW. slope.
73.50	Rocky draw, drains S. 30° W.; asc. steep SE. slope.
76.20	Crest of rocky spur, slopes irregularly SW.; desc. W. slope.
79.50	Rocky draw, drains S. 35° W.
80.06	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered palo verde. Undergrowth, ocotillo, greasewood and cactus.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over mountainous land, no timber.</p> <p>Asc. steep S. slope.</p>
2.90	Crest of rocky spur, slopes sharply SW.; desc. broken NW. slope.
20.00	Rocky draw, drains S. 20° W.; asc. steep SW. slope.
33.40	Saddle of ridge, bears E. and W.; desc. NW. slope.
36.40	<p>Point selected for the witness ¼ sec. cor. of secs. 28 and 29.</p> <p>Set the iron post 6 ins. in the ground to bedrock, mound with stone, 3½ ft. base to top, cap mkd.</p> <p style="text-align: center;">T7NR13W WC $\frac{1}{4}$ S29 S28 1963</p> <p>Cor. set on rock ledge of NW. slope.</p>
40.00	True point for the ¼ sec. cor. of secs. 28 and 29 falls on slide rock area where the cor. point cannot

BOLX 4861
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
	<p>be perpetuated.</p> <p>Cont. desc. NW. slope.</p>
51.00	Rocky draw, drains N. 15° E.
65.50	Rocky draw, drains N. 20° W.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T7NR13W S20 S21 S29 S28 1963</p>
	Raise a mound of stone, 6 ft. base, 4 ft. high, W. of post.
	Cor. falls on NW. rocky slope.
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, ocotillo, saguaro and greasewood.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°53' W., bet. secs. 21 and 28.
	Over broken mountainous land; asc. steep SE. slope.
19.90	Ridge, bears N. and S.; desc. N. slope.
33.90	Rocky draw, drains N.
39.90	Crest of spur, bears N. 40° W. and S.; desc. steep W. slope.
40.00	Point for the ¼ sec. cor. of secs. 21 and 28.
	Set the iron post on solid rock, mound with stone, 4 ft. base to top, cap mkd.
	<p>T7NR13W ¼ S 21 S 28 1963</p>
	Cor. falls on steep W. slope.
48.00	Rocky draw, drains N. 55° W.
69.00	Crest of spur, slopes NW.; desc. NW. slope.
80.00	The cor. of secs. 20, 21, 28 and 29.
	Land, mountainous, broken. Soil, rocky. Timber, none. Undergrowth, cactus.

CHAINS

N. 0°02' W., bet. secs. 20 and 21.

Desc. along W. slope.

7.00 Crest of spur, slopes N. 25° W.; desc. to rolling land.

18.20 Wash, 35 lks. wide, 3 ft. deep, drains N. 25° W.

38.50 Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.

40.00 Point for the 1/4 sec. cor. of secs. 20 and 21.

Set the iron post 20 ins. in the ground, cap mkd.

T7NR13W

1/4
S20 | S21
1963

Raise a mound of stone, 4 ft. base, 2 ft. high, W. of post.

Cor. falls on E. bank near wash.

58.60 Wash, 30 lks. wide, 2 ft. deep, drains N.

63.00 Same wash, drains N. 10° W.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set the iron post 20 ins. in the ground, mound with stone, 4 ft. base to top, cap mkd.

T7NR13W

S17 | S16
S20 | S21
1963

Cor. falls in bottom of wash not subject to flood.

Land, moderate rolling.

Soil, rocky.

Timber, scattered palo verde.

Undergrowth, greasewood and cactus.

From the cor. of secs. 15, 16, 21 and 22.

N. 89°47' W., bet. secs. 16 and 21.

Over rollingland, through sparse undergrowth.

22.50 Jeep road, bears N. and S. to old mine workings.

31.60 Crest of spur, slopes NE.; desc. SW. slope.

39.97 Point for the 1/4 sec. cor. of secs. 16 and 21.

Set the iron post 22 ins. in the ground, cap mkd.

T7NR13W

1/4 S 16
S 21
1963

Cor. falls on SW. slope of small spur.

44.70 Small wash, drains irregularly NW.

55.30 Rocky draw, drains N. 30° E.

79.50 Wash, 10 lks. wide, 1 ft. deep, drains irregularly W.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
79.94	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, rocky and gravelly. Timber, scattered palo verde. Undergrowth, ocotillo, greasewood and cactus.</p>
	<p>N. 0°02' W., bet. secs. 16 and 17. Over rolling land.</p>
5.30	Small draw, drains SW.; asc. SE. slope.
14.30	Ridge, bears NE. and SW.; desc. NW. slope.
31.20	Small wash, drains N. 70° W.
39.80	Small wash, drains W.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{1}{4}$ S17 S16 1963</p>
	<p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of post.</p>
47.70	Wash, 15 lks. wide, 1 ft. deep, drains N. 30° W.
79.60	Small wash, drains N. 20° W.
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17. Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W S8 S9 S17 S16 1963</p>
	<p>Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, greasewood and cactus.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16. N. 89°49' W., bet. secs. 9 and 16.</p>
	Over rolling land; desc. W. slope of spur.
7.50	Rocky wash, drains irregularly NE.; enter valley.
12.50	Jeep road, bears N. 30° E. and S. 30° W.
32.60	Wash, 100 lks. wide, 1 ft. deep, drains N.
39.87	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T7NR13W $\frac{1}{4}$ $\frac{S 9}{S 16}$ 1963</p>
	Cor. falls on nearly level land.

CHAINS

42.55	Graded road, bears N. and S.
45.20	Small wash, drains irregularly N.
79.74	The cor. of secs. 8, 9, 16 and 17.
	Land, nearly level W. 70 chains; rolling E. 10 chains. Soil, sandy and gravelly. Timber, scattered palo verde. Undergrowth, cactus and greasewood.
	N. 0°09' W., bet. secs. 8 and 9. Over nearly level land, sparse undergrowth.
18.50	Rocky wash, 20 lks. wide, 2 ft. deep, drains N. 25° W.
35.60	Small wash, drains N. 30° W.
40.13	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9. Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4}$ S 8 S 9 1963
41.60	Raise a small mound of earth and stone to W. of post. Wash, 20 lks. wide, 3 ft. deep, drains N. 30° W.
80.15	Bladed road, bears N. 80° E. and S. 80° W.
80.26	The cor. of secs. 4, 5, 8 and 9, monumented by an iron post as described in the official record.
	Land, nearly level. Soil, sandy and gravelly. Timber, none. Undergrowth, greasewood and cactus.
	From the cor. of secs. 3, 4, 9 and 10. N. 89°41' W., bet. secs. 4 and 9. Over nearly level desert land, through sparse vegetation, no timber.
32.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 30° W.
39.94	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9. Set the post 20 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4}$ $\frac{S 4}{S 9}$ 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
43.50	Road, unimproved, bears irregularly NW. and SE.
48.00	Wash, 20 lks. wide, 1 ft. deep, drains irregularly W.
61.10	Same wash, drains NW.
79.55	Bladed road, bears N. 80° E. and S. 80° W.
79.88	The cor. of secs. 4, 5, 8 and 9, monumented by an iron post as described in the official record.
	Land, nearly level. Soil, sandy and gravelly. Timber, none; undergrowth, greasewood and cactus.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 7 N., R. 13 W., Arizona
	<p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Desc. NW. slope.</p>
4.80	Rocky draw, drains N. 30° E.
16.30	Rocky draw, drains S. 20 E.; asc. along S. slope.
39.30	Small rocky wash, drains S. 25° W.; cont. asc. along S. slope.
40.00	Point for the ¼ sec. cor. of secs. 31 and 32.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T7NR13W $\frac{1}{4}$ S31 S32 1963</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.
	Cor. falls on gentle SW. slope.
45.60	Same rocky wash, drains irregularly S.
54.30	Saddle of ridge, bears N. 65° E. and S. 65° W.
58.00	Rocky draw, drains S. 80° W.
67.00	Rocky draw, drains W.; asc. steep SW. slope of Harcuvar Mountain.
76.00	Rocky draw, drains S. 80° W.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set the iron post 10 ins. in the ground to bedrock, mound with stone, 4 ft. base to top, cap mkd.
	<p>T7NR13W S30 S29 S31 S32 1963</p>
	from which
	U.S. Coast and Geodetic Survey triangulation station HARCUVAR bears N. 57°46' E., 24.12 chs. dist.
	Cor falls on steep SW. slope of Harcuvar Mountain.
	Land, mountainous.
	Soil, rocky.
	Timber, palo verde; undergrowth, cactus.
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89°55' W., bet. secs. 29 and 32.
	Desc. S. slope of mountain.
5.50	Ravine, drains S. 12° W.
7.00	Trail, follows ravine to prospect area; asc. SE. slope of Harcuvar Mountain.

CHAINS	
36.80	Spur, slopes S.; desc. along S. slope.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32. Set the iron post on solid rock, mound with stone, 4 ft. base to top, cap mkd.
	T7NR13W $\frac{1}{4} \frac{S \ 29}{S \ 32}$ 1963
	Cor. falls on steep S. slope, 20 lks. N. of small ravine.
40.40	Ravine, drains S.; asc. along S. slope.
47.25	Crest of spur, slopes S.; cont. along S. slope of Harcuvar Mountain.
61.00	Spur, projects S.; desc. steep and rocky SW. slope.
80.04	The cor. of secs. 29, 30, 31 and 32.
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, greasewood, scrub palo verde and cactus.
	<hr/> N. 89°50' W., bet. secs. 30 and 31. Over mountainous land, through sparse undergrowth. Desc. along SW. slope of Harcuvar Mountain.
27.70	Ravine, 40 lks. wide, drains N. 50° W.; asc. along N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31. Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4} \frac{S \ 30}{S \ 31}$ 1963
	Cor. falls on rolling N. slope.
55.00	Ridge, bears N. for one chain and S. 60° W.; desc. along NW. slope of long spur.
73.10	Spur, bears N. 30° W. and S. 60° W.; desc. very steep W. slope of spur.
80.51	True point for the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township; the witness cor. bears South, 1.00 chain dist., an iron post as described in the official record.
	Land, mountainous. Soil, rocky. Timber, none; undergrowth, greasewood, ocotillo, yucca and bur brush.
	<hr/> From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over mountainous land, through sparse undergrowth and no timber. Cont. asc. steep and rocky SW. slope.
22.30	Narrow ridge, bears N. 80° W. and S. 80° E.; desc. steep N. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
28.50	Rocky draw, drains N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set the iron post 8 ins. in the ground to bedrock, mound with stone, 4 ft. base to top, cap mkd. T7NR13W 1/4 S30 S29 1963 Cor. falls on N. slope, 15 lks. N. of a huge boulder.
51.50	Wash, 40 lks. wide, 3 ft. deep, drains N. 35° W.
60.00	Broken spur, slopes NW.
67.10	Rocky draw, drains N. 45° W.
74.20	Broken spur, slopes irregularly NW.; desc. N. slope.
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set the iron post 12 ins. in the ground to bedrock, mound with stone, 3 1/2 ft. base to top, cap mkd. T7NR13W S19 S20 S30 S29 1963 Cor. falls on crest of spur that slopes N. Land, broken and mountainous. Soil, rocky. Timber, none. Undergrowth, ocotillo, saguaro and other cacti.
	From the cor. of secs. 20, 21, 28 and 29. N. 89°54' W., bet. secs. 20 and 29. Over high mountainous land; no timber.
.60	Small wash, drains irregularly N.; asc. steep E. slope.
3.50	Rocky wash, 40 lks. wide, 2 ft. deep, drains N.
21.70	Rocky spur, slopes N. 10° W.; desc. broken NW. slope.
35.50	Rocky draw, drains N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29. Set the iron post 20 ins. in the ground, mound with stone, 4 ft. base to top, cap mkd. T7NR13W 1/4 S 20 S 29 1963

CHAINS		
	Cor. falls on rocky NW. slope.	
40.80	Small rocky draw, drains NW. for 3 chs. thence N.	
50.00	Wash, 15 lks. wide, 1 ft. deep, drains N.	
63.20	Crest of spur, slopes N. 5° W.; desc. W. slope.	
74.00	Rocky wash, 20 lks. wide, 2 ft. deep, drains N. 15° W.; asc. to cor.	
80.00	The cor. of secs. 19, 20, 29 and 30.	
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, ocotillo, saguaro and other cacti.	
	<hr/>	
	N. 89°53' W., bet. secs. 19 and 30.	
	Over mountainous land, through sparse undergrowth.	
6.00	Spur, slopes irregularly NW.; desc. steep SW. slope.	
17.00	Wash, 20 lks. wide, 2 ft. deep, drains irregularly NW.; over rolling land.	
33.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 15° W.; asc. NE. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.	
	Set the iron post 10 ins. in the ground to bedrock, mound with stone, $3\frac{1}{2}$ ft. base to top, cap mkd.	
	T7NR13W $\frac{1}{4}$ $\frac{S 19}{S 30}$ 1963	
	Cor. falls on rocky NE. slope.	
46.00	Rocky draw, drains irregularly N.; asc. E. slope.	
51.00	Spur, slopes N.; desc. W. slope.	
63.20	Wash, 40 lks. wide, 3 ft. deep, drains N. 10° E.	
71.00	Rocky spur, slopes N.; desc. W. slope.	
75.10	Small rocky draw, drains N.; asc. rocky NE. slope.	
80.47	True point for the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the township; the witness cor. bears South, 1.00 chain dist., monumented by an iron post as described in the official record.	
	Land, rolling and mountainous. Soil, gravelly and rocky. Timber, none. Undergrowth, greasewood and cactus.	
	<hr/>	
	From the cor. of secs. 19, 20, 29 and 30.	
	N. 0°03' W., bet. secs. 19 and 20.	
	Over broken land, through scattered timber and undergrowth.	
16.00	Wash, 25 lks. wide, 2 ft. deep, drains N. 80° W.; asc. S. slope.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 7 N., R. 13 W., Arizona
21.70	Spur, slopes irregularly NW.; desc. steep N. slope.
31.80	Wash, 15 lks. wide, 2 ft. deep, drains N. 20° W.
40.00	Point for the ¼ sec. cor. of secs. 19 and 20. Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T7NR13W $\frac{1}{4}$ S19 S20 1963</p> <p>Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of post.</p> <p>Cor. falls on gentle N. slope.</p>
50.70	Wash, 30 lks. wide, 4 ft. deep, drains irregularly N.
58.90	Same wash, drains N. 30° W.
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T7NR13W S18 S17 S19 S20 1963</p> <p>Raise a small mound of earth and stone to W. of post.</p> <p>Land, gently sloping to N. Soil, rocky and gravelly. Timber, scattered palo verde. Undergrowth, scrub palo verde, greasewood, catclaw and cholla.</p>
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over gently rolling land, through scattered timber.</p>
1.30	Wash, 15 lks. wide, 1 ft. deep, drains N. 40° W.
23.30	Jeep trail, bears irregularly E. and W.
39.80	Small wash, drains N.
40.02	Point for the ¼ sec. cor. of secs. 17 and 20. Set the iron post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T7NR13W $\frac{1}{4}$ $\frac{S 17}{S 20}$ 1963</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, N. of post.</p> <p>Cor. falls on nearly level land.</p>

CHAINS	
51.50	Rocky wash, 15 lks. wide, 2 ft. deep, drains N. 45° W.
60.90	Unimproved road, bears N. 15° W. and S. 15° E.
71.70	Wash, 20 lks. wide, 2 ft. deep, drains N. 45° W.
80.04	The cor. of secs. 17, 18, 19 and 20.
	Land, nearly level. Soil, gravelly. Timber, scattered palo verde. Undergrowth, greasewood brush and cactus.
	N. 89°46' W., bet. secs. 18 and 19.
	Over gently rolling land, over series of small washes with general drainage to NW.
33.50	Wash, 25 lks. wide, 2 ft. deep, drains N. 30° W.
40.00	Point for the ¼ sec. cor. of secs. 18 and 19.
	Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4}$ $\frac{S 18}{S 19}$ 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post.
	Cor. falls on nearly level land.
43.70	Wash, 15 lks. wide, 1 ft. deep, drains N.
70.50	Small wash, drains N. 35° W.
80.41	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township; monumented by an iron post as described in the official record.
	Land, gently rolling to nearly level. Soil, gravelly. Timber, scattered palo verde. Undergrowth, greasewood, ocotillo, cholla, saguaro and other cacti.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°09' W., bet. secs. 17 and 18.
	Over nearly level land, through scattered timber and undergrowth.
7.10	Wash, 60 lks. wide, 4 ft. deep, drains N. 30° W.
25.40	Unimproved road, bears irregularly NW. and SE.
40.15	Point for the ¼ sec. cor. of secs. 17 and 18.
	Set the iron post 24 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4}$ S18 S17 1963
	Raise a small mound of earth and stone to W. of post.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 7 N., R. 13 W., Arizona
44.80	Wash, 50 lks. wide, 5 ft. deep, drains N. 50° W.
59.00	Wash, 10 lks. wide, 2 ft. deep, drains N. 20° W.
80.30	True point for the cor. of secs. 7, 8, 17 and 18; the witness cor. bears N. 0°03' W., 0.60 chs. dist., monumented by an iron post as described in the official record.
	Land, nearly level. Soil, sandy and gravelly. Timber, scattered palo verde. Undergrowth, black brush, greasewood and cactus.
	From the cor. of secs. 8, 9, 16 and 17.
	N. 89°43' W., bet. secs. 8 and 17.
	Over nearly level land, through sparse undergrowth.
10.90	Wash, 20 lks. wide, 3 ft. deep, drains N. 20° W.
37.10	Wash, 200 lks. wide, 1 ft. deep, drains N. 30° W.
40.07	Point for the ¼ sec. cor. of secs. 8 and 17.
	Set the iron post 20 ins. in the ground, cap mkd.
	T7NR13W $\frac{1}{4} \begin{matrix} S & 8 \\ S & 17 \end{matrix}$ 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post.
47.70	Jeep road, bears N. 15° W. and S. 15° E.
56.90	Wash, 30 lks. wide, 3 ft. deep, drains N. 10° W.
70.90	Wash, 30 lks. wide, 2 ft. deep, drains N.
80.14	True point for the cor. of secs. 7, 8, 17 and 18.
	Land, nearly level. Soil, sandy and gravelly. Timber, scrub palo verde. Undergrowth, greasewood, cholla and ocotillo.
	General Description
	The land surveyed in Township 7 North, Range 13 West consists mainly of broken, mountainous terrain, with the exception of the Butler Valley portion which includes sections 1 through 12.
	The soil is rocky in the southern portion, gravelly in the central portion, and sandy in the northerly portion.

CHAINS

There were no springs noted in the township. The Harcuvar Mountains split the township, running from the southwest corner to the northeast corner. The drainage south of the mountain range is generally southeast, whereas the portion north of the Harcuvar Mountains drains to the northwest, eventually draining into Cunningham and Bouse Washes and then into the Colorado River.

There are no hard surfaced roads in the township though the road leading from Wenden to Alamo Crossing is presently being surveyed by the U. A. Army Corps of Engineers and will eventually become an asphalt light duty road. This road enters the township through Cunningham Pass in Section 12 and bears generally northwest through sections 2 and 3 across Butler Valley.

This area was once a very active mining district, and mine shafts, drill machinery and prospect holes remain as evidence of the workings. There appears to be little activity of any nature now. The timber is of no commercial value and the vegetation consists of scattered greasewood, palo verde and cactus.

40

BOOK 4681
CERTIFICATE OF SURVEY

I, Leonard W. Murphy, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 27th day of June, 1962,
I have made a completion survey of a portion of the south boundary and
the subdivisional lines of Township 7 North, Range 13 West

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

April 2, 1963
(Date)

Leonard W. Murphy
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL
Bureau of Land Management

The foregoing field notes of the survey of a portion of the south boundary and
the subdivisional lines, T. 7 N., R. 13 W., Gila and Salt River Meridian,
Arizona,

executed by Leonard W. Murphy, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

Washington, D.C.

DEC 27 1963

(Date)

Clark L. Gumm
Acting (Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Engineering)~~