

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

RETRACEMENT

of the

East Boundary,

a Portion of the South Boundary,

a Portion of the Subdivisional Lines,

and a

COMPLETION SURVEY

of the

Subdivisional Lines

Township 10 North, Range 14 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Horace G. Parker, Cadastral Surveyor

and

Virgil E. Spratt, Cadastral Surveyor

Under special instructions dated March 20, 19 61, which provided for the surveys
included under Group Number 359, approved March 24, 1961,
and assignment instructions dated March 24, November 2, 19 61.

Survey commenced April 12, 19 61

Survey completed January 29, 19 62

1A

INDEX DIAGRAM

Township 10 North, Range 14 West,

6	5	4	3 16 16	2 14 15	1 2 13($\frac{1}{4}$) 12
7 30($\frac{1}{4}$) 29	8	9	10 14	11 11 11	12 2 13($\frac{1}{4}$) 10
18 30($\frac{1}{4}$) 28	17	16	15	14 9 4	13 2 10($\frac{1}{4}$) 8
19 28 27	20 24 27	21 19 23	($\frac{1}{4}$)21 22 20 5	23 4 3	24 2 9($\frac{1}{4}$) 7
30 26 26	29 23 25	28 18 22	($\frac{1}{4}$)21 27 5 18	26 4 6	25 2 7($\frac{1}{4}$) 5
31 25 4	32 21 3	33 17 3	34 5 3	35 4	36 1 3

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 10 North, Range 14 West
Gila and Salt River Meridian, Arizona

The east two miles of the south boundary were surveyed in 1911 by J. F. Hesse. The south boundary of section 35 was resurveyed in 1956 by Harding and Smith. The north, east, and west boundaries and the west four miles of the south boundary were surveyed in 1913 by S. E. Blout. The east half of sections 15 and 22, the south half of section 14, section 23, and the lines between sections 25 and 26, 26 and 27, 35 and 36, 34 and 35 were surveyed in 1911 by J. F. Hesse. Sections 4, 5, 6, 8, 9, 16, 17 and the west half of section 15 were surveyed in 1913 by S. E. Blout.

The following notes are those of a retracement of the east boundary, a retracement of the west 4 miles and the east mile of the south boundary; a retracement of a portion of the subdivisional lines and a completion survey of the subdivisional lines of Township 10 North, Range 14 West, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 20, 1961.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless otherwise noted all corners were monumented with standard iron posts, 30 inches long, 2½ inches in diameter, flanged at the bases and with brass caps riveted to the tops.

The geographic position of the southeast corner of the township is: Latitude 34°09'28" North and Longitude 113°39'39" West.

The magnetic declination was found to be 14°30" E.

Retracement of the East Boundary
Township 10 North, Range 14 West

Retracement of the Survey executed by S. E. Blout in 1913

Topography remains essentially the same as reported in the official record; the only items of topography given are those of a recent nature.

Beginning at the cor. of secs. 1, 6, 31 and 36, Ts. 9 and 10 N., Rs. 13 and 14 W., monumented by an iron post as described in the official record.

N. 0°05' W., bet. secs. 31 and 36.

40.09

True point for the ¼ sec. cor. of secs. 31 and 36.

N. 0°05' W., beginning new measurement.

1.25

The witness ¼ sec. cor. of secs. 31 and 36, monumented by an iron post as described in the official record.

CHAINS	
39.95	The cor. of secs. 25, 30, 31 and 36, monumented by an iron post as described in the official record. <hr/>
	N. 0°05' W., bet. secs. 25 and 30.
40.07	True point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30. <hr/>
	N. 0°05' W., beginning new measurement.
2.57	The witness $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by an iron post as described in the official record.
40.04	The cor. of secs. 19, 24, 25 and 30, monumented by an iron post as described in the official record. <hr/>
	N. 0°01' W., bet. secs. 19 and 24.
40.02	The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented by an iron post as described in the official record. <hr/>
	N. 0°05' W., beginning new measurement.
40.04	The cor. of secs. 13, 18, 19 and 24, monumented by an iron post as described in the official record. <hr/>
	N. 0°08' W., bet. secs. 13 and 18.
40.02	The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented by an iron post as described in the official record. <hr/>
	N. 0°08' W., beginning new measurement.
30.93	The witness sec. cor. of secs. 7, 12, 13 and 18, monumented by an iron post as described in the official record.
39.98	Point for the cor. of secs. 7, 12, 13 and 18. <hr/>
	N. 0°02' W., bet. secs. 12 and 7.
40.18	The $\frac{1}{4}$ sec. cor. of secs. 12 and 7, monumented by an iron post as described in the official record. <hr/>
	N. 0°14' W., beginning new measurement.
40.14	The sec. cor. of secs. 1, 6, 7 and 12, monumented by an iron post, as described in the official record. <hr/>
	N. 0°09' W., bet. secs. 1 and 6,
39.86	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented by an iron post as described in the official record. <hr/>
	N. 0°10' W., beginning new measurement.
40.12	The cor. of secs. 1, 6, 31 and 36, Ts. 10 and 11 N., Rs. 13 and 14 W., monumented by an iron post as described in the official record. <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Retracement of the East Mile and the West 4 Miles of the South Boundary, Township 10 North, Range 14 West</p> <hr/> <p>Retracement of the Survey in 1911 by J. F. Hesse</p> <p>From the cor. of secs. 1, 6, 31 and 36, Ts. 9 and 10 N., Rs. 13 and 14 W.</p> <p>West, bet. secs. 1 and 36.</p>
40.13	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented by an iron post as described in the official record.</p> <hr/> <p>S. 89°50' W., beginning new measurement.</p>
40.40	<p>The cor. of secs. 1, 2, 35 and 36, monumented by an iron post as described in the official record.</p> <hr/> <p>Retracement of the Survey in 1913 by S. E. Blout</p> <p>From the cor. of secs. 2, 3, 34 and 35 on the south boundary of the township, monumented by an iron post as described in the official record.</p> <p>N. 89°47' W., bet. secs. 3 and 34.</p>
39.95	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented by an iron post as described in the official record.</p> <hr/> <p>N. 89°46' W., beginning new measurement,</p>
40.05	<p>The cor. of secs. 3, 4, 33 and 34, monumented by an iron post as described in the official record.</p> <hr/> <p>N. 89°50' W., bet. secs. 4 and 33.</p>
39.96	<p>The true point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, not monumented.</p> <hr/> <p>N. 89°53' W., beginning new measurement.</p>
1.50	<p>The witness $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented by an iron post as described in the official record.</p>
40.02	<p>The cor. of secs. 4, 5, 32 and 33, monumented by an iron post as described in the official record.</p> <hr/> <p>N. 89°51' W., bet. secs. 5 and 32.</p>
39.98	<p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented by an iron post as described in the official record.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p>
40.04	<p>The cor. of secs. 5, 6, 31 and 32, monumented by an iron post as described in the official record.</p> <hr/>

CHAINS		
	N. 89°47' W., bet. secs. 6 and 31.	
40.08	The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented by an iron post as described in the official record.	
	N. 89°48' W., beginning new measurement.	
39.57	The cor. of secs. 1, 6, 31 and 36, Ts. 9 and 10 N., Rs. 14 and 15 W., monumented by an iron post as described in the official record.	
Retracement of a Portion of the Subdivisional Lines T. 10 N., R. 14 W., G. & S.R. Meridian, Arizona		
Re-establishment of the Survey in 1911 by J. F. Hesse		
From the cor. of secs. 1, 2, 35 and 36 on the south boundary of the township.		
	N. 0°17' W., bet. secs. 35 and 36.	
39.85	The witness $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented by an iron post as described in the official record.	
40.85	True point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.	
	N. 0°17' W., beginning new measurement.	
39.05	The witness sec. cor. for Secs. 25, 26, 35 and 36, monumented by an iron post as described in the official record.	
40.05	The true point for the cor. of secs. 25, 26, 35 and 36.	
	N. 0°17' W., bet. secs. 25 and 26.	
40.10	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented by an iron post as described in the official record.	
	N. 0°17' W., beginning new measurement.	
40.08	The cor. of secs. 23, 24, 25 and 26, monumented by an iron post as described in the official record.	
	N. 0°15' W., bet. secs. 23 and 24.	
40.12	The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented by an iron post as described in the official record.	
	N. 0°15' W., beginning new measurement.	
40.08	The cor. of secs. 13, 14, 23 and 24, monumented by an iron post as described in the official record.	
	N. 0°21' W., bet. secs. 13 and 14.	
40.18	The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented by an iron post as described in the official record.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

5.

CHAINS	
	Retracement, Subdivisions, T. 10 N., R. 14 W., Arizona
	From the cor. of secs. 2, 3 , 34 and 35 on the south boundary of the township.
	N. 0°04' W., bet. secs. 34 and 35.
40.32	The true point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, not monumented.
	N. 0°04' W., beginning new measurement.
2.00	The witness $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented by an iron post as described in the official record.
40.18	The cor. of secs. 26, 27, 34 and 35, monumented by an iron post as described in the official record.
	N. 0°04' W., bet. secs. 26 and 27.
40.24	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented by an iron post as described in the official record.
	N. 0°04' W., beginning new measurement.
40.37	The cor. of secs. 22, 23, 26 and 27, monumented by an iron post as described in the official record.
	S. 89°30' W., bet. secs. 22 and 27.
41.33	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented by an iron post as described in the official record.
	Completion Survey of the Subdivisional Lines, T. 10 N. R. 14 W.
	From the true point for the cor. of secs. 25, 26, 35 and 36.
	S. 89°26' E., bet. secs. 25 and 36.
	Over rolling land, through scattered palo verde, cactus and greasewood.
6.80	Wash, 5 ft. deep, 50 lks. wide, drains N.
10.70	Spur, projects N. 20° E.
12.80	Wash, 3 ft. deep, 30 lks. wide, drains N. 20° E.
29.90	Wash, 4 ft. deep, 50 lks. wide, drains NE.
39.50	Point selected for the witness $\frac{1}{4}$ sec. cor. of sec. 25.
	Set the post 18 ins. in the ground, mound with stone to top, cap mkd.

CHAINS		
	WC T10N R14W $\frac{1}{4}$ <u>S 25</u> 1961	
40.00	The true point for the $\frac{1}{4}$ sec. cor. of sec. 25 falls in a deep wash, impossible to perpetuate. At 40 chs. in easting.	
40.10	Wash, 20 ft. deep, 20 lks. wide, drains N.	
40.38	Point for the $\frac{1}{4}$ sec. cor. of sec. 36. At mid-point. Set the post 4 ins. in the ground, mound with stone to top, cap mkd.	
	T10N R14W $\frac{1}{4}$ <u>S 36</u> 1962	
52.50	Wash, 3 ft. deep, 50 lks. wide, drains NW.	
76.10	Unimproved road, bears SW. and N. 70° E.	
80.76	The cor. of secs. 25, 30, 31 and 36, on E. bdy. of the township. Land, rolling. Soil, sandy clay. Timber, none; undergrowth, palo verde, cactus and greasewood.	
	From the true point for the cor. of secs. 25, 26, 35 and 36. S. 89°43' W., bet. secs. 26 and 35. Over rolling land, through scattered palo verde, cactus and greasewood.	
25.30	Ridge, bears N. 20° W. and S. 20° E.	
35.90	Wash, 3 ft. deep, 100 lks. wide, drains N.	
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35. Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.	
	T10N R14W $\frac{1}{4}$ <u>S 26</u> $\frac{1}{4}$ <u>S 35</u> 1961	
45.30	Low ridge, bears N. and S.	
58.40	Road to Lincoln Ranch, bears N. 10° W. and S. 10° E.	
58.80	Gas pipe line, 2 ins. diameter, bears N. 10° W. and S. 10° E.	
64.20	Wash, 2 ft. deep, 200 lks. wide, drains N. 10° E.	
75.80	Road, graded, bears NW. and SE.	
76.80	El Paso gas pipe line, 36 ins. diameter, visible for 2 chs. in wash, bears NW. and SE.	
80.48	The cor. of secs. 26, 27, 34 and 35.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/> <p>Land, rolling, cut by series of washes. Soil, sandy clay with metamorphic extrusions. Timber, none; undergrowth, palo verde, cactus and greasewood.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26. East, bet. secs. 24 and 25. Over rolling land, through scattered desert vegetation.</p>
19.50	Ravine, 50 ft. deep, 30 lks. wide, drains NW. to Lincoln Ranch.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor of secs. 24 and 25.</p> <p>Set the post 22 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> <p>T10N R14W $\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$ 1961</p> </div>
56.10	Canyon, drains NW.
67.40	Wash, 2 ft. deep, 30 lks. wide, drains NW.
72.90	Wash, 2 ft. deep, 30 lks. wide, drains NW.
81.02	<p>Point for the closing cor of secs. 24 and 25, on the E. bdy. of the township.</p> <p>Set the post 18 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> <p>T10N R14W CC S 24 S 25 1962</p> </div> <p>From this cor. the cor. of secs. 19, 24, 25 and 30 bears S. 0°01' E., 91 lks. dist. This cor. now functions as the cor. of secs. 19 and 30 only, therefore I remark the cap to read</p> <div style="text-align: center;"> <p>T10N R13W S19 S30 1913 1962</p> </div> <p>Land, rolling. Soil, sandy clay. Timber, none; undergrowth, palo verde, cactus and greasewood.</p> <hr/> <p>The true point for the E. $\frac{1}{4}$ sec. cor. of sec. 25 is 40 chs. in southing from the closing cor. of secs. 24 and 25, and falls in a wash where it is impossible to perpetuate.</p>

CHAINS

From the true point for the $\frac{1}{4}$ sec. cor. of sec. 25, the point selected for the witness $\frac{1}{4}$ sec. cor. bears N. $0^{\circ}05'$ W., 2.38 chs. dist.

Set the post 18 ins. in the ground, mound with stone to top, cap mkd.

T10N
R14W
S 25 |
W | C
1962

From the true point for this cor. the true point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30 bears S. $0^{\circ}05'$ E., 95 lks. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 30 only, therefore I remark the cap of the witness cor. to read

$\frac{1}{4}$
| S30
W | C
1913
1962

From the cor. of secs. 13, 14, 23 and 24.

East, bet. secs. 13 and 24.

Over broken mountainous land, through scattered palo verde, cactus and greasewood.

Ascend along N. bank of large wash draining westerly.

15.40 N. bank of wash, drains N. 80° W. from S. 45° E.; continue over nearly level bench.

33.80 Wash, 4 ft. deep, 100 lks. wide, drains N. 70° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
 $\frac{1}{4}$ $\frac{S 13}{S 24}$
1961

Asc. steep W. slope.

52.30 High rocky point; desc. E. slope.

71.25 Rocky canyon, drains N.

78.40 Spur, projects NW.; desc. E. slope.

81.21 Point for the closing cor. of secs. 13 and 24, on the E. bdy. of the township.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

T10N
R14W
CC $\frac{S 13}{S 24}$
1962

From this cor., the cor. of sections 13, 18, 19 and 24 bears S. $0^{\circ}08'$ E., 1.09 chs. dist. This cor. now functions as the cor. of secs. 18 and 19 only, therefore I remark the cap to read

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p style="text-align: center;">T10N R 13 W <u>S 18</u> <u>S 19</u> 1913 1962</p> <p>Land, broken and mountainous. Soil, shallow sandy clay. Timber, none; undergrowth, palo verde, cactus and greasewood.</p> <hr/> <p>The point for the E. $\frac{1}{4}$ sec. cor. of sec. 24 is at mid-point bet. closing cors. on the E. bdy.</p> <p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T10N R14W $\frac{1}{4}$ S24 1962</p> <p>From this cor., the $\frac{1}{4}$ sec. cor. of secs. 19 and 24 bears S. $0^{\circ}05'$ E., 1.01 chs. dist. This cor. now functions as the cor. of sec. 19 only, therefore I remark the cap to read</p> <p style="text-align: center;">$\frac{1}{4}$ S19 1913 1962</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.</p> <p>N. $0^{\circ}01'$ W., bet. secs. 13 and 14.</p> <p>Over rugged broken mountainous land, through scattered desert vegetation.</p> <p>Desc. sheer N. slope.</p> <p>6.40 Bill Williams River, course W.</p> <p>11.70 North bank, Bill Williams River; asc. steep S. slope.</p> <p>26.30 Spur, projects SW.</p> <p>34.90 Steep rocky gully, drains W.; asc. steep broken S. slope.</p> <p>40.00 Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T10N R14W <u>S11</u> <u>S12</u> <u>S14</u> <u>S13</u> 1962</p> <p>Land, steep and broken. Soil, alluvial silt and sandy clay. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/>

CHAINS

East, bet. secs. 12 and 13, over rugged broken mountains, through scattered cactus, palo verde and greasewood.

- 6.50 Spur, projects SW.; desc. steep E. slope.
- 13.30 Steep rocky gully, drains SE.
- 16.40 Spur, projects S.
- 28.40 Spur, projects SW.; desc. sheer rock wall.
- 31.00 Wash, 2 ft. deep, 200 lks. wide, drains S.
- 40.00 Point for the 1/4 sec. cor. of secs. 12 and 13.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W

1/4 $\frac{S\ 12}{S\ 13}$

1962

- 40.70 Spur, projects SW.
- 46.70 Spur, projects SW.
- 48.70 Deep gulch, drains S.; asc. steep broken W. slope.
- 55.90 Spur, rocky, projects SW.
- Thence by triangulation, topography is estimated.
- 62.00 Steep rocky canyon, drains SW.
- 72.00 Rocky point, projects SW.
- 81.07 Point for the closing cor. of secs. 12 and 13, on the E. bdy. of the township, falls in cliff area, impossible to monument.

From the true point for this cor., the true point for the cor. of secs. 7, 12, 13 and 18 bears S. 0°02' E., 1.23 chs. dist. This corner now functions as the cor. of secs. 7 and 18 only, therefore I remark the cap of the witness cor. to read

WC
R14W R13W

$\frac{S\ 7}{S18}$

T10N

1962

Land, extremely rugged, with sheer rock faces.
Soil, shallow, poor clay and sand.
Timber, none; undergrowth, cactus, palo verde and greasewood.

The true point for the E. 1/4 sec. cor. of sec. 13 is at mid-point bet. closing corners on the E. bdy., impossible to perpetuate at this location.

From the true point for the 1/4 sec. cor. of sec. 13, the point selected for the witness cor. bears S. 0°08' E., 1.30 chs. dist.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/> <p style="text-align: center;">WC T10N R14W $\frac{1}{2}$ S13 1962</p> <p>From the true point for this cor. the $\frac{1}{2}$ cor. of secs. 13 and 18 bears S. 0°08' E., 114 lks. dist. This cor. now functions as the cor. of sec. 18 only, therefore I remark the cap to read</p> <p style="text-align: center;">$\frac{1}{2}$ S18 1913 1962</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°49' W., bet. secs. 11 and 14.</p> <p>Over rugged mountainous land, through scattered desert vegetation.</p> <p>8.00 Canyon, drains S. 20° W.</p> <p>15.00 Spur, projects S. 20° W.</p> <p>20.00 Rocky canyon, drains SW.</p> <p>24.00 Spur, projects S.</p> <p>39.38 Point selected for the witness $\frac{1}{2}$ sec. cor. of secs. 11 and 14.</p> <p>Set the post 2 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T10N R14W $\frac{1}{2}$ $\frac{W S11}{C S14}$ 1962</p> <p>39.98 True point for the $\frac{1}{2}$ sec. cor. of secs. 11 and 14, impossible to perpetuate in this location.</p> <p>58.00 Canyon, drains S.</p> <p>79.96 The cor. of secs. 10, 11, 14 and 15, monumented by an iron post as described in the official record.</p> <p>Land, rolling and broken. Soil, shallow, poor clay and alluvial silt. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rugged mountainous land, through scattered palo verde, cactus and greasewood.</p>

CHAINS

- 1.70 Spur, projects SW.
 - 40.00 Point for the 1/4 sec. cor. of secs. 11 and 12, located on a steep NW. slope, approximately 1 chain from crest.

Set the iron post 8 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
1/4
S11|S12
1962
 - 47.40 Steep rocky canyon, drains SW.
 - 73.20 Spur, projects SW.
 - 80.00 Point for the cor. of secs. 1, 2, 11 and 12.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
S 2|S 1
S11|S12
1961
-
- Land, mountainous and broken.
Soil, sand and shale.
Timber, none; undergrowth, cactus, palo verde and greasewood.
-
- East, bet. secs. 1 and 12.
 - Over rugged, broken mountainous land, through scattered palo verde, cactus and greasewood.
 - 9.50 Spur, projects SW.; desc. along steep SE. slope.
 - 18.60 Steep rocky ravine, drains S. 30° W.; asc. steep W. slope.
 - 26.00 Spur, projects S.; desc. steep SE. slope.
 - 36.10 Rocky ravine, drains S.; asc. steep W. slope.
 - 40.00 Point for the 1/4 sec. cor. of secs. 1 and 12.

Set the post 4 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
1/4 S 1
S12
1961
 - Corner is located on steep N. slope, approximately 5 chs. from crest.
 - 44.50 Spur, projects S.; desc. steep SE. slope.
 - 64.20 Deep ravine, drains S.; begin asc. along steep broken SW. slope.
 - 80.52 Point for the closing cor. of secs. 1 and 12 on the E. bdy. of the township.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion, Subdivision, T. 10 N., R. 14 W., Arizona

T10N
R14W
S 1 c | R13W
S12 c |
1961

From this cor., the cor. of secs. 1, 6, 7 and 12 bears S. 0°09' E., 89 lks. dist. This cor. now functions as the cor. of secs. 6 and 7 only, therefore I remark the cap to read

T10N R13W
| S6
| S7
1913
1961

Land, extremely rugged and mountainous.
Soil, light, poor clay and sand.
Timber, none; undergrowth, cactus, palo verde and greasewood.

The point for the E. $\frac{1}{4}$ sec. cor. of sec. 12 is at mid-point bet. closing corners on the E. bdy.

Set the post 8 ins. in the ground, mound with stone to top, cap mkd.

T10N
R14W
 $\frac{1}{4}$ S12 |
1961

From this cor., the $\frac{1}{4}$ sec. cor. of secs. 7 and 12 bears S. 0°14' E., 1.04 chs. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 7 only, therefore I remark cap to read

$\frac{1}{4}$
| S 7
1961

The point for the E. $\frac{1}{4}$ sec. cor. of sec. 1 is at 40.00 chs. in northing from the closing corner of secs. 1 and 12 and on the E. bdy.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T10N
R14W R13W
 $\frac{1}{4}$ S1 |
1963

From this cor., the $\frac{1}{4}$ sec. cor. of secs. 1 and 6 bears S. 0°10' E., 1.03 chs. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 6 only, therefore I remark cap to read

CHAINS

$\frac{1}{4}$
| S6
1913
1963

From the cor. of secs. 1, 2, 11 and 12.

N. 0°17' E., bet. secs. 1 and 2.

Over rugged mountainous land, through scattered desert vegetation.

- 1.00 Wash, 4 ft. deep, 50 lks. wide, drains SW.; asc. steep S. slope.
- 11.80 Spur, projects SW.; continue asc. along broken SW. slope.
- 39.40 Ridge, bears S. and NW.; desc. N. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
 $\frac{1}{4}$
S2|S1
1961

- 62.30 Steep ravine, drains NW.; begin asc. along steep SW. slope.
- 71.40 Top of rocky knoll; desc. along NW. slope.
- 79.09 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the township, monumented by an iron post as described in the official record.

Land, mountainous and broken.
Soil, shallow, poor clay and sand and metamorphic extrusions.
Timber, none; undergrowth, cactus, palo verde and greasewood.

From the cor. of secs. 10, 11, 14 and 15.

N. 0°01' W., bet. secs. 10 and 11.

Over mountainous land, through scattered desert vegetation.

Asc. broken S. slope.

- 16.10 Spur, projects SE.
- 22.80 Spur, projects SW.
- 31.20 Ridge bears NE. and SW.; desc. broken N. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
 $\frac{1}{4}$
S10|S11
1961

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/>
41.60	<p>Spur, projects W.</p>
57.00	<p>Steep Ravine, drains E.; asc. along steep SE. slope.</p>
69.00	<p>Ridge, bears N. 10° W. and S. 10° E.; desc. E. slope.</p>
80.00	<p>Point for the sec. cor. of secs. 2, 3, 10 and 11.</p>
	<p>Set the post 22 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T10N R14W S 3 S 2 S10 S11 1961</p>
	<p>This cor. is located on a steep S. slope, approximately 2 chs. from crest.</p>
	<p>Land, mountainous. Soil, clay, broken sandstone and metamorphic extrusions. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p>
	<p>S. 89°49' W., bet. secs. 2 and 11.</p>
	<p>Over rolling mountainous land, through scattered desert vegetation.</p>
4.20	<p>Steep ravine, drains SW.</p>
15.00	<p>Wash, 5 ft. deep, 100 lks. wide, drains SW.</p>
18.50	<p>Same wash, drains NW.</p>
27.90	<p>Same wash, drains SW.; asc. rolling E. slope.</p>
40.07	<p>Point for the ¼ sec. cor. of secs. 2 and 11.</p>
	<p>Set the post 4 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T10N R14W ¼ S 2 S11 1961</p>
60.20	<p>Ridge, bears irregularly N. and S.</p>
	<p>Thence by triangulation, topography is estimated.</p>
70.00	<p>Wash, 4 ft. deep, 300 lks. wide, drains S.</p>
80.14	<p>The cor. of secs. 2, 3, 10 and 11.</p>
	<p>Land, rolling and mountainous. Soil, shallow, poor clay and metamorphic rock. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/>

CHAINS	
	<p>S. 89°54' W., bet. secs. 3 and 10.</p> <p>Over rugged broken mountains, through scattered desert vegetation.</p> <p>Asc. E. slope.</p>
10.60	Top of slope on high rocky point; desc. rolling W. slope.
25.30	Spur, projects N.
39.60	Wash, 2 ft. deep, 30 lks. wide, drains SW.; asc. steep broken E. slope.
39.92	<p>Point for the ¼ sec. cor. of secs. 3 and 10.</p> <p>Set the post 10 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p>T10N R14W</p> <p>¼ $\frac{S\ 3}{S10}$</p> <p>1961</p>
	Cor is located 10 lks. N. of wash draining SW.
56.90	Ridge, bears NE. and SW.; desc. gentle NW. slope.
60.80	Slope changes from NW. to SW.
66.20	Deep rocky ravine, drains S. 20° W.
79.84	<p>The cor. of secs. 3, 4, 9 and 10, monumented by an iron post as described in the official record.</p> <p>Land, steep broken mountains.</p> <p>Soil, sand, poor clay and metamorphic extrusions.</p> <p>Timber, none; undergrowth, cactus, palo verde and greasewood.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 0°17' E., bet. secs. 2 and 3.</p> <p>Over steep broken mountains, through scattered desert vegetation.</p> <p>Asc. steep S. slope.</p>
2.00	Spur, projects E.; desc. along E. slope.
37.50	Steep ravine, drains S. 60° E.
38.90	Ridge, rocky, bears E. and W.
40.00	<p>Point for the ¼ sec. cor. of secs. 2 and 3.</p> <p>Set the post 4 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p>T10N R14W</p> <p>¼ $\frac{S3}{S2}$</p> <p>1962</p>
48.00	Wide draw, drains SE.; asc. along steep SW. slope.
62.60	Ridge, bears E. and W.; desc. steep broken N. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/>
70.30	<p>Wash, 3 ft. deep, 200 lks. wide, drains irregularly W.</p>
79.34	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the township, monumented by an iron post as described in the official record.</p>
	<p>Land, broken and mountainous. Soil, sand, sandstone, clay and shale. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/>
	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township, monumented by an iron post as described in the official record.</p>
	<p>N. 0°02' W., bet. secs. 33 and 34.</p>
	<p>Over mountainous land, through scattered desert vegetation.</p>
1.40	<p>Wash, 50 lks. wide, drains NW.</p>
10.50	<p>Spur, slopes E.</p>
22.90	<p>Wash, 50 lks. wide, 3 ft. deep, drains W.</p>
25.80	<p>Spur, slopes W.</p>
31.80	<p>Spur, slopes W.</p>
38.00	<p>Spur, slopes E.</p>
40.00	<p>Point for the ½ sec. cor. of secs. 33 and 34.</p>
	<p>Set the post 24 ins. in the ground, deposit broken glass 6 ins. below surface, no stone available for mound, cap mkd.</p>
	<p style="text-align: center;">T10N R14W ½ S33 S34 1961</p>
51.90	<p>Wash, 30 lks. wide, 3 ft. deep, drains NE.</p>
56.10	<p>Spur, slopes NE.</p>
61.60	<p>Wash, 20 lks. wide, 4 ft. deep, drains E.</p>
67.40	<p>Spur, slopes E.</p>
69.40	<p>Wash, 20 lks. wide, 4 ft. deep, drains E.</p>
73.40	<p>Spur, slopes E.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p>
	<p>Set the post 10 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T10N R14W S28 S27 S33 S34 1961</p>

CHAINS	
	<p>Land, rolling. Soil, clay, sand and decomposed sandstone. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°46' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through scattered cactus, palo verde and greasewood.</p>
22.00	Spur, slopes N.
27.20	Wash, 100 lks. wide, 5 ft. deep, drains N.
33.90	Spur, slopes N.
37.00	Wash, 30 lks. wide, 5 ft. deep, drains N.
39.93	Point for the ¼ sec. cor. of secs. 27 and 34.
	Set the post 24 ins. in the ground, cap mkd.
	<p>T10N R14W ¼ $\frac{S\ 27}{S\ 34}$ 1961</p>
	Deposit broken glass 6 ins. below the surface, no stone available for mound.
40.40	Spur, slopes N.
45.40	Spur, slopes N.
55.10	Wash, 20 lks. wide, 10 ft. deep, drains N.
58.00	Spur, slopes N.
58.50	Wash, 30 lks. wide, 20 ft. deep, drains N.
68.80	Wash, 50 lks. wide, 20 ft. deep, drains NE.
78.10	Spur, slopes N. 30° E.
79.86	The cor. of secs. 27, 28, 33 and 34.
	<p>Land, rolling. Soil, clay and alluvial silt. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land, through scattered cactus, palo verde and greasewood.</p>
3.40	Wash, 20 lks. wide, 2 ft. deep, drains E.
11.50	Wash, 20 lks. wide, 2 ft. deep, drains NE.
19.50	Spur, slopes E.
22.50	Spur, slopes N. 75° E.
26.50	Wash, 20 lks. wide, 4 ft. deep, drains NE.
34.30	Spur, slopes E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N , R. 14 W., Arizona</p> <hr/>
38.00	<p>Spur, slopes E.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 28. Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T10N R14W $\frac{1}{4}$ S28 1961</p>
	<p>Deposit broken glass 6 ins. below surface, no stone available for mound.</p>
41.10	<p>Natural gas pipe line, bears E. and W.</p>
41.50	<p>Road, bladed, along gas line, bears E. and W.</p>
44.30	<p>Wash, 20 lks. wide, 4 ft. deep, drains NE.</p>
45.50	<p>Wash, 20 lks. wide, 4 ft. deep, drains E.</p>
49.60	<p>Spur, slopes NE.</p>
57.00	<p>Wash, 100 lks. wide, 3 ft. deep, drains E.</p>
80.00	<p>Point for the cor. of secs. 21 and 28. Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T10N R14W S21 S27 S28 1961</p>
	<p>Land, rolling. Soil, clay, sand and sandstone. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/>
	<p>N. 0°21'W., bet. secs. 21 and 22.</p>
	<p>Over rolling land, through scattered palo verde, cactus and greasewood.</p>
20.56	<p>Wash, 100 lks. wide, 3 ft. deep, drains NE.</p>
26.60	<p>Spur, slopes N. 10° E.</p>
30.50	<p>Wash, 50 lks. wide, 3 ft. deep, drains NE.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 21. Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T10N R14W $\frac{1}{4}$ S21 1961</p>
	<p>Deposit broken glass 6 ins. below the surface, no stone available for mound.</p>

CHAINS

- 48.00 Spur, slopes N. 10° E.
- 56.50 Wash, 100 lks. wide, 2 ft. deep, drains N.
- 68.00 Wash, 300 lks. wide, 3 ft. deep, drains NE.
- 69.80 Road, graded, bears E. and W.
- 80.70 Wash, 500 lks. wide, 2 ft. deep, drains N.
- 81.19 The cor. of secs. 15, 16, 21 and 22, monumented by an iron post as described in the official record.

Land, rolling.
Soil, sand, clay and alluvial silt.
Timber, none; undergrowth, cactus, palo verde and greasewood.

From the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.

West, bet. secs. 22 and 27.

Over rolling land, through scattered palo verde and greasewood.

- 1.50 Wash, 50 lks. wide, 2 ft. deep, drains N.
- 13.50 Wash, 100 lks. wide, 3 ft. deep, drains N.
- 16.20 Spur, slopes N.; desc. W. slope.
- 24.60 Wash, 100 lks. wide, 2 ft. deep, drains N.; asc. E. slope.
- 31.50 Ridge, bears N. and S.
- 36.30 Wash, 30 lks. wide, 1 ft. deep, drains N.
- 38.38 The point for the closing cor. of secs. 22 and 27 on the E. bdy. of sec. 21.

Set the post 24 ins. in the ground, cap mkd.

T10N R14W
S21 | $\frac{S22}{S27}$ CC
1961

Deposit broken glass, 6 ins. below the surface, no stone available for mound.

From this cor. the cor. of secs. 21 and 28 bears S. 0°21' E., 0.62 lks. dist.

Land, rolling.
Soil, clay, sand and sandstone.
Timber, none; undergrowth, cactus, palo verde and greasewood.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 27 is at mid-point.

Set the post 24 ins. in the ground, cap mkd.

T10N R14W

 $\frac{1}{4}$ S27
1961

BOOK 480
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/> <p>Deposit broken glass 6 ins. below the surface of the ground, no stone available for mound.</p> <p>From this cor. the $\frac{1}{4}$ sec. cor. of secs. 22 and 27 bears S. $89^{\circ}30'$ W., 1.47 chs. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 22 only; I remark cap to read</p> <div style="text-align: center;"> $\frac{1}{4}$ S22 <hr style="width: 50%; margin: 0 auto;"/> 1911 1961 </div> <hr/> <p>The W. $\frac{1}{4}$ sec. cor. of sec. 27 is at mid-point.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> T10N R14W $\frac{1}{4}$ S27 1961 </div> <hr/> <p>From this cor. the $\frac{1}{4}$ sec. cor. of sec. 28 bears S. $0^{\circ}02'$ E., 0.31 lks. dist.</p> <hr/> <p>The W. $\frac{1}{4}$ sec. cor. of sec. 22 is at mid-point.</p> <p>Set the post 20 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> T10N R14W $\frac{1}{4}$ S22 1961 </div> <hr/> <p>From this cor. the $\frac{1}{4}$ sec. cor. of sec. 21 bears S. $0^{\circ}21'$ E., 0.90 lks. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. $0^{\circ}02'$ W., bet. secs. 32 and 33.</p> <p>Over rolling land, through scattered palo verde, cactus and greasewood.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.</p> <p>Set the post 18 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> T10N R14W $\frac{1}{4}$ S32 S33 1961 </div> <p>Desc. along NE. slope.</p>
53.70	<p>Enter wash, 50 ft. deep, drains N. 20° W.</p>

CHAINS		
56.80	Leave wash.	
76.50	Spur, projects NE.	
78.25	Point selected for the witness cor. of secs. 28, 29, 32 and 33.	
	Set the post 24 ins. in the ground, mound with stone to top, cap mkd.	
	T10N R14W <u>S29</u> <u>S28</u> <u>S32</u> <u>S33</u> W C 1961	
80.00	Point for the cor. of secs. 28, 29, 32 and 33 falls in a wash 100 lks. wide, impossible to perpetuate.	
	Land, rolling. Soil, clay and sand. Timber, none; undergrowth, cactus, palo verde and greasewood.	
	From the cor. of secs. 27, 28, 33 and 34.	
	N. 89°53' W., bet. secs. 28 and 33.	
	Over rolling land, through scattered cactus and palo verde.	
7.50	Spur, slopes N.	
9.40	Wash, 30 lks. wide, 20 ft. deep, drains N.	
15.50	Spur, slopes NE.	
20.00	Wash, 20 lks. wide, 10 ft. deep, drains N.	
22.70	Spur, slopes N.	
28.00	Wash, 20 lks. wide, 10 ft. deep, drains N.	
32.30	Spur, slopes N.	
39.50	Wash, 20 lks. wide, 20 ft. deep, drains N.	
40.05	The point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.	
	Set the post 24 ins. in the ground, cap mkd.	
	T10N R14W $\frac{1}{4}$ <u>S 28</u> <u>S 33</u> 1961	
	Deposit broken glass 6 ins. below the surface of the ground, no stone available for mound.	
43.60	Wash, 40 lks. wide, 5 ft. deep, drains N.	
51.90	Wash, 20 lks. wide, 5 ft. deep, drains NE.	
60.70	Saddle in spur, bearing N. and S.	
72.30	Center of wash area, approximately 4 chs. wide, drains N.	
80.10	True point for the cor. of secs. 28, 29, 32 and 33.	

BOOK 4885
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/> <p>Land, rolling. Soil, clay and alluvial silt. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land, through scattered cactus, palo verde and greasewood.</p> <p>1.00 N. bank of wash, draining NE.; asc. 40 ft. over steep bank.</p> <p>1.90 Top of bank, bears N. 75° E.; desc. over gentle NE. slope.</p> <p>37.30 Road, graded, bears S. 75° W. and N. 75° E.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T10N R14W $\frac{1}{4}$ S29 S28 1961</p> <p>Deposit broken glass, 6 ins. below the surface of the ground, no stone available for mound.</p> <p>61.60 Road, graded, on curve, bears N. 30° E. and S. 30° E.</p> <p>80.00 Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T10N R14W S20 S21 S29 S28 1961</p> <p>Deposit broken glass 6 ins. below the surface of the ground, no stone available for mound.</p> <p>Land, gently rolling. Soil, clay and alluvial silt. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>From the cor. of secs. 21 and 28.</p> <p>N. 89°47' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through scattered desert vegetation.</p> <p>4.10 Wash, 150 lks. wide, 5 ft. deep, drains N. 30° W.</p> <p>11.20 Spur, slopes N.</p> <p>22.20 Wash, 40 lks. wide, 15 ft. deep, drains N.</p>

CHAINS		
36.00	Wash, 30 lks. wide, 5 ft. deep, drains NE.	
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.	
	Set the post 18 ins. in the ground, mound with stone to top, cap mkd.	
	T10N R14W $\frac{1}{4}$ $\frac{S 21}{S 28}$ 1961	
	Deposit broken glass 6 ins. below the surface of the ground.	
51.00	Road, graded, bears N. and S.	
57.50	Natural gas pipe line, bears S. 75° E. and N. 75° W.	
58.10	Center of wash area, approximately 4 chs. wide, 20 ft. deep, drains N.	
73.40	Road, graded, bears N. and S.	
80.14	The cor. of secs. 20, 21, 28 and 29.	
	Land, rolling. Soil, clay and sand. Timber, none; undergrowth, cactus, palo verde and greasewood.	
	N. 0°06' W., bet. secs. 20 and 21.	
	Over rolling land, through scattered vegetation.	
6.20	Wash, 20 lks. wide, 5 ft. deep, drains N. 25° E.	
12.20	Wash area, approximately 4 chs. wide, 20 ft. deep, drains NE.	
20.70	Natural gas pipe line, bears N. 70° W. and S. 70° E.	
20.90	Road, graded, bears N. 70° W. and S. 70° E.	
26.90	Wash, 30 lks. wide, 3 ft. deep, drains E.	
31.30	Wash, 2 chs. wide, 10 ft. deep, drains N. 75° E.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.	
	Set the post 24 ins. in the ground, cap mkd.	
	T10N R14W $\frac{1}{4}$ S20 S21 1961	
	Deposit broken glass 6 ins. below the surface of the ground, no stone available for mound.	
42.00	Wash, 30 lks. wide, 3 ft. deep, drains NE.	
48.70	Wash, 10 lks. wide, 2 ft. deep, drains E.	
61.00	Wash, 20 lks. wide, 10 ft. deep, drains SE.	
68.60	Spur, slopes E.	
80.78	The cor. of secs. 16, 17, 20 and 21, monumented by an iron post as described in the official record.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/> <p>Land, rolling. Soil, clay and sand. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the south boundary of the township, monumented by an iron post as described in the official record.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land with N. to NW. drainage, through scattered cactus, catclaw, palo verde and greasewood.</p>
25.60	Wash, 50 lks. wide, 5 ft. deep, drains W.
40.00	Point for the ¼ sec. cor. of secs. 31 and 32.
	Set the post 18 ins. in the ground, mound with stone to top, cap mkd.
	<p>T10N R14W ½ S31 S32 1961</p>
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set the post 22 ins. in the ground, cap mkd.
	<p>T10N R14W S30 S29 S31 S32 1961</p>
	Erect a mound of stone 3 ft. high, 4 ft. base, west of post.
	Land, gently rolling. Soil, clay, sand and gravel. Timber, none; undergrowth, cactus, catclaw, palo verde and greasewood. <hr/>
	From the true point for the cor. of secs. 28, 29, 32 and 33.
	N. 89°56' W., bet. secs. 29 and 32.
	Over rolling land draining northerly into the Bill Williams River, through scattered cactus, palo verde and greasewood.
2.00	Leave wash, drains NE.
31.80	Road to Lincoln Ranch, graded, bears N. 10° E. and S. 20° W.
40.00	Point for the ¼ sec. cor. of secs. 29 and 32.
	Set the post 20 ins. in the ground, cap mkd.

26

CHAINS

T10N R14W

$\frac{1}{4}$ $\frac{S 29}{S 32}$

1961

Erect a mound of stone 3 ft. high, 4 ft. base, north of post.

46.70 Wash, 50 lks. wide, 4 ft. deep, drains N.

60.30 Road to Lincoln Ranch, graded, bears N. 70° W. and S. 70° E.

80.00 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.
Soil, sand, clay and gravel.
Timber, none; undergrowth, cactus, palo verde and greasewood.

N. 89°50' W., bet. secs. 30 and 31.

Over rolling land, through scattered desert vegetation.

4.50 Wash, 100 lks. wide, 4 ft. deep, drains N.

17.10 Road to Lincoln Ranch, graded, bears SW. and N. 70° E.

36.60 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 30 and 31.

Set the post 18 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W

$\frac{1}{4}$ $\frac{W S 30}{C S 31}$

1961

37.10 Wash, 500 lks. wide, 5 ft. deep, drains N.

40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31; impossible to perpetuate in this location.

51.70 Road to Lincoln Ranch, graded, bears N. 10° W. and SE.

79.53 The cor. of secs. 25, 30, 31 and 36, monumented by an iron post as described in the official record.

Land, rolling and low hills.
Soil, sandy clay.
Timber, none; undergrowth, cactus, palo verde and greasewood.

From the cor. of secs. 29, 30, 31 and 32.

N. 0°03' W., bet. secs. 29 and 30.

Over rolling land, through scattered cactus, palo verde and greasewood.

0.90 Road to Lincoln Ranch, graded, bears NE. and NW. on curve.

8.40 Wash, 100 lks. wide, 4 ft. deep, drains W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Set the post 22 ins. in the ground, cap mkd.

BOOK 4085
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion, Subdivision, T. 10 N., R. 14 W., Arizona</p> <hr/> <p style="text-align: center;">T10N R14W $\frac{1}{4}$ S30 S29 1961</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, west of iron post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T10N R14W S19 S20 S30 S29 1961</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.</p> <p>Land, rolling. Soil, sandy clay and gravel. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°57' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through scattered desert vegetation.</p>
11.00	<p>Wash, 200 lks. wide, 5 ft. deep, drains N. 10° E.</p>
33.50	<p>Low ridge, bears N. 20° E. and S. 20° W.</p>
40.03	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.</p> <p>Set the post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T10N R14W $\frac{1}{4}$ $\frac{S\ 20}{S\ 29}$ 1961</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, north of iron post.</p>
80.06	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, sandy clay and gravel. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>N. 89°48' W., bet. secs. 19 and 30.</p> <p>Over rolling land, through scattered desert vegetation.</p>
22.70	<p>Wash, 50 lks. wide, 3 ft. deep, drains N.</p>

CHAINS	
33.20	Wash, 200 lks. wide, 3 ft. deep, drains N.
37.40	Road, graded, to Johnston Ranch, bears N. and S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.
	Set the post 6 ins. in the ground, mound with stone to top, cap mkd.
	T10N R14W $\frac{1}{4}$ $\frac{S 19}{S 30}$ 1961
76.50	Clay knoll.
79.31	The cor. of secs. 19, 24, 25 and 30, monumented by an iron post, as described in the official record.
	Land, rolling. Soil, clay and gravel. Timber, none; undergrowth, cactus, palo verde and greasewood.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°07' W., bet. secs. 19 and 20.
	Over rolling land, through scattered desert vegetation.
13,70	Road, graded, bears irregularly E. and W.; asc. along SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
	Set the post 8 ins. in the ground, mound with stone to top, cap mkd.
	T10N R14W $\frac{1}{4}$ S19 S20 1961
43.90	Spur, projects SE.
54.10	Deep gully, drains SE.
80.87	The cor. of secs. 17, 18, 19 and 20, monumented by an iron post as described in the official record.
	Land, rolling. Soil, sandy clay and gravel. Timber, none; undergrowth, cactus, palo verde and greasewood.
	From the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township, monumented by an iron post as described in the official record.
	East, bet. secs. 18 and 19.
	Over rolling and broken land, through scattered cactus, palo verde and greasewood.
3.20	Wash, 40 lks. wide, drains NE.
6.90	Deep rocky canyon, drains N.; asc. broken S. slope.
30.40	Rocky Point.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Completion, Subdivision, T. 10 N., R. 14 W., Arizona
39.01	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.</p> <p>Set the post 12 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T10N R14W $\frac{1}{4}$ $\frac{S 18}{S 19}$ 1961</p>
79.01	<p>Point for the closing cor. of secs. 18 and 19 on the W. bdy. of sec. 20.</p> <p>Set the post 10 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T10N R14W CC $\frac{S18}{S19}$ S20 1961</p> <p>From this cor., the cor. of secs. 17, 18, 19 and 20 bears N. 0°07' W., 50 lks. dist. This cor. now functions as the cor. of secs. 17 and 20 only, therefore I remark the cap to read</p> <p style="text-align: center;">T10N R14W S18 $\frac{S17}{S20}$ 1913 1961</p> <p>Land, rolling to broken. Soil, shallow poor clay, sand and gravel. Timber, none; undergrowth, cactus, palo verde and greasewood.</p>
19.50	Deep ravine, drains N.
25.70	Natural gas pipeline, bears SE. and W.
26.10	Road, graded, along pipeline, bears SE. and W.
39.08	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>Set the post 12 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T10N R14W $\frac{1}{4}$ $\frac{S 7}{S 18}$ 1961</p>
49.60	Ridge, bears irregularly N. and S.; desc. broken E. slope.

CHAINS

77.10

Road to Johnston Ranch, graded, bears irregularly N. and S.

79.08

Point for the closing cor. of secs. 7 and 18, on the W. bdy. of sec. 17.

Set the post 22 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
 $\frac{S\ 7c}{S18c} | S17$
 1961

From this cor., the cor. of secs. 7, 8, 17 and 18 bears N. 0°03' W., 40 lks. dist. This cor. now functions as the cor. of secs. 8 and 17 only. I therefore remark the cap to read

T10N R14W
 $S\ 7 | \frac{S\ 8}{S17}$
 1913
 1961

Land, rolling.
 Soil, sand and clay.
 Timber, none; undergrowth, cactus, palo verde and greasewood.

The point for the East $\frac{1}{4}$ sec. cor. of sec. 18 is at mid-point between closing cors., on the E. bdy.

Set the post 5 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
 $\frac{1}{4} S\ 18 |$
 1961

From this cor., the $\frac{1}{4}$ sec. cor. of secs. 17 and 18 bears N. 0°03' W., 45 lks. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 17 only; I therefore remark the cap to read

$\frac{1}{4}$
 $| S17$
 1913
 1961

The point for the East $\frac{1}{4}$ sec. cor. of sec. 7 is at mid-point on the east bdy.

Set the post 22 ins. in the ground, mound with stone to top, cap mkd.

T10N R14W
 $\frac{1}{4} |$
 $S7 |$
 1961

Raise a mound of stone, 4 ft. base, 3 ft. high, west of iron post.

From this cor. the $\frac{1}{4}$ sec. cor. of secs. 7 and 8 bears N. 0°03' W., 20 lks. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 8 only; I therefore remark cap to read

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 10 North, Range 14 West, Arizona

$\frac{1}{4}$
| S8
1913
1961

General Description

Township 10 North, Range 14 West, is principally rolling and broken desert with some metamorphic extrusions. It has a general northerly exposure and drainage toward the Bill Williams River. Numerous deposits of minerals were noted in the extruded areas.

There were numerous prospect holes in the east tier and the west tier of sections which indicated mining activities are increasing in these areas.

The gas line maintenance road cuts nearly diagonally through the township from the SE. corner. Two other roads, the Lincoln Ranch road and the Johnston Ranch road enter the township in section 30 and bear generally toward the respective ranches.

The soil is principally a light shallow sandy clay, with numerous outcroppings of sandstone and lava, covered with a scattered undergrowth of cactus, palo verde and greasewood.

The only water noted was at the wells at both the Lincoln and Johnston ranches, which are on the south bank of the Bill Williams River.

LOOK 4005

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transitman
Dan V. Coleman	Notes
Douglas L. McInelly	Front Chainman
Jerald Brindley	Flagman
Neil R. Forsyth	Transitman
Jeddie J. Judd	Chainman
Max L. Sevy	Notekeeper
John D. Carter	Cornerman
Woodrow L. Jepson	Flagman

CERTIFICATE OF SURVEY

We, Horace G. Parker
X, Virgil E. Spratt

, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 20th day of March, 1961,

We, X, have retraced the east boundary, a portion of the south boundary, a portion of the subdivisional lines, and made a completion survey of the subdivisional lines of Township 10 North, Range 14 West

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~^{us} and under ~~my~~^{our} direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 24, 1962
(Date)

Horace G. Parker
(Cadastral Surveyor)
Horace G. Parker

October 24, 1962
(Date)

Virgil E. Spratt
(Cadastral Surveyor)
Virgil E. Spratt

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the retracement of the east boundary, a portion of the south boundary, a portion of the subdivisional lines, and completion survey of the subdivisional lines of Township 10 North, Range 14 West, Gila and Salt River Meridian, Arizona,

executed by Horace G. Parker and Virgil E. Spratt, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

Washington, D. C.

AUG 27 1963
(Date)

E. E. Livingston
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)