

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

DEPENDENT RESURVEY

of the

First Standard Parallel South

through Range 27 East

and the

DEPENDENT RESURVEY

of a Portion of the

Subdivisional Lines

and a

COMPLETION SURVEY

of the

Subdivisional Lines

of

Township 6 South, Range 27 East

Of the Gila and Salt River Meridian,

In the State of Arizona

## EXECUTED BY

Dell Cazier, Cadastral Surveyor

Glen B. Hatch, Surveying Technician

Eldon W. Sibley, Surveying Technician

Under special instructions dated August 10, 19 59, which provided for the surveys  
included under Group Number 338, approved August 24, 1959,  
and assignment instructions dated Mar. 9 and Nov. 23, 19 60.

Survey commenced April 12, 19 60

Survey completed December 19, 19 60

1A

BOOK 4687

# INDEX DIAGRAM

		Township 6 South				Range 27 East			
		6	5	4	3	2			
8	7								
	65( $\frac{1}{4}$ )	65( $\frac{1}{4}$ )	34( $\frac{1}{4}$ )	27( $\frac{1}{4}$ )	20( $\frac{1}{4}$ )	14( $\frac{1}{4}$ )			
	6 64	5 33 ( $\frac{1}{4}$ ) 62	4 26	3 19	2 13	1		66	
	63	62	32 ( $\frac{1}{4}$ )60	24 60( $\frac{1}{4}$ )	18 56( $\frac{1}{4}$ )	13			
66	7 60	8 31	9 58	10 56	11 12	12			
	45	44		57	55	10			
	18 43	17	16	( $\frac{1}{4}$ ) 58 15 54	14 49	13			
	42	41		52	52	48			
	19 40	20 30	21 23	( $\frac{1}{4}$ ) 53 22 51	23 47	24		66	
	39	38	30	23	50	47			
	30 37	29 29	28 22	27 17	26 46	25		66	
	36	35	28	21	16	9			
	31 34	32 27	33 20	34 15	35 8	36			

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

1. B

CHAINS

Township 6 South, Range 27 East  
Gila and Salt River Meridian, Arizona

The north boundary, First Standard Parallel South, was originally surveyed by P. Contzen in 1895. The portion of the line between the standard corner of sections 31 and 32, T5S, R27E and the standard corner of sections 35 and 36, T5S, R26E was retraced and partly dependently resurveyed by Kimmell and Veal in 1916-19. The east boundary was surveyed by P. Contzen in 1895. The S $\frac{1}{2}$  of the line between sections 31 and 36 was dependently resurveyed by C. E. Hunter in 1931. The north five and one-half miles were dependently resurveyed by Phil D. Smith in 1958. The south boundary was originally surveyed by T. F. White in 1875 and dependently resurveyed by P. Contzen in 1895. The corner of sections 1, 2, 35 and 36 and the southeast corner of the township were reestablished by C. E. Hunter in 1931. The line between the southwest corner of the township and the corner of sections 1, 2, 35 and 36 was dependently resurveyed by D. E. Harding in 1957. The west boundary was surveyed by P. Contzen in 1895 and concurrently dependently resurveyed by Eldon W. Sibley under group 338, the record of which appears in the field notes of the dependent resurvey of the east boundary of T6S, R26E.

The resurvey was initiated on the official request of the State Supervisor for Arizona to perpetuate the original corner locations and to provide identification of the boundaries of the public lands to facilitate administration under appropriate public land laws.

The following field notes are those of the dependent resurvey of the north boundary, First Standard Parallel South, and a portion of the subdivisional lines and the completion survey of T6S, R27E.

The identified evidence of the original corners consisted of the monuments and/or the remains of the bearing trees or objects. About 95 per cent of the original corner locations were identified. The original survey was faithfully and carefully executed. Before restoring the corners the lines were retraced and a diligent search made for any evidence of the original corners, bearing objects and any other calls of the original field note record. When duly identified, the corner positions were remonumented and new accessories established. After completing the necessary retracements to connect with the identified corner locations, and after exhausting every reasonable possibility of finding direct evidence for the control of each particular corner, the rules of proportionate measurement were applied in order to ascertain the position of lost corners. The true lines thus adjusted to the identified original evidence were then marked on the ground.

This survey was executed with two W. and L. E. Gurley transits, serial numbers 491037 and 580158, both constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition prior to the beginning of the survey and were maintained in proper adjustment throughout the progress of the survey.

## CHAINS

The direction of the lines of the survey were determined by observations on Polaris at elongation and carried forward by sustained angulation and checked throughout the progress of the survey with altitude observations on the sun for azimuth.

Measurements were made with narrow steel tapes, 8 chains in length graduated in tenths for the first link, in links for the next 99 links and thereafter at intervals of 10 links. The tapes were tested by comparison with a standard 1-chain steel tape and found to be correct. All measurements were made on the slope and the vertical angle of each interval ascertained by a clinometer in good adjustment; the horizontal equivalents alone are entered in the field notes. All lines of this survey were run by direct method where the lines were accessible; lines inaccessible were run by triangulation or traverse. The topography calls along inaccessible lines were scaled from USGS preliminary sheets.

The triangulation, traverse and retracement data were checked and verified prior to conclusion of the field work and in order to simplify the record the true line notes are supplied herewith, which refer to the completed survey.

The geographic position for the southeast corner of T6S, R27E, is in latitude  $32^{\circ}51'35''$  North and longitude  $109^{\circ}31'38''$  West, as determined by section line ties to USC&GS triangulation station BONIT, which is situated in the NW $\frac{1}{4}$  of section 7, T6S, R28E.

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be  $13^{\circ}$  East.

---

Dependent Resurvey  
of the First Standard Parallel South  
through Range 27 East, G&SRM, Arizona

---

Reestablishment of the Survey  
Executed by Philip Contzen  
Under Contract Number 29, dated June 17, 1893

---

Beginning at the standard  $\frac{1}{4}$  sec. cor. of sec. 36, T. 5 S., R. 27 E., which is mkd. by an iron post,  $2\frac{1}{2}$  ins. diam., set mkd. and witnessed as described in the field notes of the dependent resurvey of the W. bdy. of T. 6 S., R. 28 E.

S.  $89^{\circ}53'$  W., along the S. bdy. of sec. 36.

Over rolling land, with general SE. drainage, through scattered shrubs.

Desc. 30 ft. over SW. slope.

6.50 Wash, 20 lks. wide, 2 ft. deep, drains SE., asc. 50 ft. over NE. slope.

20.00 Spur slopes SE.; desc. 35 ft. over SW. slope.

33.50 Wash, near head, drains S.; asc. 30 ft. over E. slope.

39.60 Jeep road, bears N. and S., on spursloping S.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Dependent Resurvey, 1st Stan. Par. S., R27E, Arizona

39.95

The 1/4 sec. cor. of sec. 1, T. 6 S., R. 27 E., hereinafter described.

40.14

The standard cor. of secs. 35 and 36, which is mkd. by a malpais stone, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E  
SC  
S35 | S36

T6S  
1960

Deposit the original cor. stone alongside iron post.

Land, rolling.

Soil, gravelly sandy clay.

Timber, none; undergrowth, creosote, cacti and catclaw.

---

S. 89°58' W., along the S. bdy. of sec. 35.

Over rolling land, with general SE. drainage; through scattered undergrowth.

Desc. 30 ft. over SW. slope.

10.90

Wash, 40 lks. wide, 3 ft. deep, drains SE.; asc. 100 ft. over E. slope.

29.00

Spur, slopes S. 10° E.; asc. 40 ft. along S. slope.

39.97

The closing cor. of sec. 1 and 2, T. 6 S., R. 27 E.; hereinafter described.

40.16

The standard 1/4 sec. cor. of sec. 35, which is mkd. by a malapis stone, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E  
SC  
1/4 S35

T6S  
1960

Deposit the original cor. stone alongside of iron post.

---

S. 89°55' W., beginning new measurement.

CHAINS	
	Desc. 50 ft. along SW. slope.
14.00	Wash, 60 lks. wide, 4 ft. deep, drains SE.; asc. 30 ft. along E. slope.
20.00	Slope changes; asc. 40 ft. along N. slope.
39.84	The ¼ sec. cor. of sec. 2, T. 6 S., R. 27 E., hereinafter described.
39.96	The standard cor. of secs. 34 and 35, which is mkd. by a malpais stone, set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;">T5SR27E SC <u>S34   S35</u> T6S 1960</p>
	Deposit the original cor. stone alongside iron post.
	Land, rolling.
	Soil, gravelly and rocky sandy clay.
	Timber, none; undergrowth, creosote, catclaw and cacti.
	<hr/>
	S. 89°54' W., along the S. bdy. of sec. 34.
	Over rolling land, on N. slope; through scattered brush.
	Asc. 40 ft. along N. slope.
10.00	Dim track road, bears N. and S.; asc. 120 ft. along N. slope.
39.91	The closing cor. of secs. 2 and 3, T. 6 S., R. 27 E., hereinafter described.
40.13	The standard ¼ sec. cor. of sec. 34, which is mkd. by a malpais stone, set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;">T5SR27E SC <u>¼ S34</u> T6S 1960</p>
	Deposit the original cor. stone alongside iron post.
	<hr/>
	S. 89°53' W., beginning new measurement.
	Desc. 30 ft. along SW. slope.
8.50	Fence, barbed wire, bears N. 20° E. and S. 20° W.
10.50	Dirt road, bears S. 50° E. and N. 50° W., thence over gently rolling land.

CHAINS	
38.00	Dirt road, bears NE. and SW.
39.79	The ¼ sec. cor. of sec. 3, T. 6 S., R. 27 E., hereinafter described.
40.08	The standard cor. of secs. 33 and 34, which is mkd. by a malpais stone, set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	T5SR27E SC S33 S34 T6S 1960
	Deposit the original cor. stone alongside iron post.
	Land, rolling. Soil, gravel and rocky, sandy clay. Timber, none; undergrowth, thinly scattered brush.
	S. 89°53' W., along the S. bdy. of sec. 33.
	Over rolling land, through thinly scattered catclaw and mesquite.
	Desc. 20 ft. along S. slope.
12.00	Wash, 30 lks. wide, 6 ft. deep, drains S. 80° E.; asc. 100 ft. over E. slope.
25.00	Slope changes; asc. 60 ft. along S. slope.
39.71	The closing cor. of secs. 3 and 4, T. 6 S., R. 27 E. hereinafter described.
39.97	The standard ¼ sec. cor. of sec. 33, which is mkd. by a malpais stone, 18"x16"x10", set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	T5SR27E SC <u>¼ S33</u> T6S 1960
	Deposit the original cor. stone alongside of iron post.

6

CHAINS

S. 89°49' W., beginning new measurement.

Asc. 360 ft. along boulder strewn S. slope.

25.00 Slope changes; asc. 140 ft. over steep E. slope.

31.00 Spur, projecting S. 20° E.; desc. 10 ft. along SW. slope.

39.39 The ¼ sec. cor. of secs. 4; hereinafter described.

39.67 The standard cor. of secs. 33 and 32, which is mkd. by a malpais stone, 18"x15"x8", set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E  
SC  
S32 | S33  
T6S  
1960

Deposit the original cor. stone alongside iron post.

Land, rolling to mountainous.  
Soil, gravelly rocky sandy clay.  
Timber, none; undergrowth, none.

West along the S. bdy. of sec. 32.

Over mountainous land, no timber or undergrowth.

By triangulation desc. about 400 ft. along steep, boulder strewn, ledgy SW. slope.

26.00 Wash, near head, drains S. 40° E.; asc. about 40 ft. over E. slope.

27.34 Intersect line 2-3 of M.S. No. 4457, Red Cap No. 19 lode at a point from which Cor. No. 2 bears N. 10°37' 57" W., 4.45 chs. dist. and Cor. No. 3 bears S. 10°37' 57" E., 4.64 chs. dist.

29.20 Dirt road, bears N. and S.

29.50 End of triangulation; asc. 200 ft. over boulder strewn E. slope.

39.38 The closing cor. of secs. 4 and 5, hereinafter described.

39.68 The standard ¼ sec. cor. of sec. 32, which is mkd. by a malpais stone, 14 x 10 x 8 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E  
SC  
¼ S32  
T6S  
1960

Deposit the original cor. stone alongside iron post.



TRAIL POST

Dependent Resurvey, 1st Stan. Par. S., R27E, Arizona 7.

CHAINS	
	West, beginning new measurement.
	Asc. 360 ft. over ledgy E. slope.
20.00	Top of spur; desc. 160 ft. over W. slope.
26.45	Dirt road, bears N. 30° E. and S. 80° W., on spur sloping S. 85° W.; desc. 60 ft. along N. slope.
37.84	The ¼ sec. cor. of sec. 5, hereinafter described.
39.91	The standard cor. of secs. 31 and 32, which is mkd. by a malpais stone, 12x10x6 ins., set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock and in a mound of stone to top, with brass cap mkd.
	T5SR27E SC <u>S31 S32</u> T6S 1960
	Deposit the original cor. stone alongside iron post.
	Land, mountainous. Soil, boulder-strewn, sandy clay. Timber, none; undergrowth, scattered mesquite and catclaw.
	<hr/>
	S. 89°58' W., along the S. bdy. of sec. 31.
	Over mountainous land, no timber; through thinly scattered brush.
	Desc. 80 ft. along N. slope.
11.00	Old fence, bears N. 30° E. and S. 30° W.; desc. 100 ft. along N. slope.
16.00	Wash, near head, drains N.; asc. 100 ft. over steep E. slope.
20.00	Dirt road, bears S. 80° E. and N. 80° W.; asc. 160 ft. over boulder-strewn, steep E. slope.
25.00	Spur, sloping steeply NE.; asc. 80 ft. along steep N. slope.
37.93	The closing cor. of secs. 5 and 6, hereinafter described.
39.91	The standard ¼ cor. of sec. 31, which is mkd. by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record.
	<hr/>
	N. 89°57' W., beginning new measurement.
	Desc. 60 ft. along N. slope.
8.55	Wash, 25 lks. wide, 4 ft. deep, drains N.; asc. 140 ft. over NE. slope.

CHAINS	
18.78	Intersect line 2-3 of M.S. No. 4456, Johnny lode at a point from which Cor. No. 2 bears S. 38°24'07" W., 9.68 chs. dist. and Cor. No. 3 bears N. 38°24'07" W., 13.05 chs. dist.
20.00	Spur, slopes N.; desc. 80 ft. along NW. slope.
25.50	Wash, 20 lks. wide, 3 ft. deep, drains N.; asc. 290 ft. over steep E. slope.
36.00	Spur, sloping N.; desc. 20 ft. along N. slope.
38.02	The $\frac{1}{4}$ sec. cor. of sec. 6, hereinafter described.
40.05	The standard township cor. of T. 5 S., Rs. 26 and 27 E., which is mkd. by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, mountainous. Soil, boulder-strewn, rocky, sandy clay. Timber, none; undergrowth thinly scattered mesquite and catclaw.
	N. 89°54' W., along the S. bdy. of sec. 36, R. 26 E.
	Over mountainous land, no timber or undergrowth.
	Asc. 80 ft. along N. slope.
7.40	Spur, sloping N., thence over series of spurs and washes.
24.40	Ridge, bears N. 45° W. and S. 70° E.; desc. 150 ft. over steep W. slope.
37.06	The closing cor. of sec. 1 and 6, T. 6 S., Rs. 26 and 27 E., which is mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of T. 6 S., R. 26 E., concurrent with this survey.
39.96	The standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 5 S., R. 26 E., which is mkd. by an iron post, 1 inch diam., firmly set, mkd. and witnessed as described in the official record.
	Dependent Resurvey Portion, Subdivisional Lines, T6S, R27E Gila and Salt River Meridian, Arizona
	Reestablishment of the Survey Executed by Philip Contzen Under Contract Number 29, dated June 17, 1893
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy., mkd. by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record.
	N. 0°06' E., bet. secs. 35 and 36.
	Over nearly level land, through scattered mesquite.
5.10	Cement irrigation ditch, slopes SW.
5.20	Track road, bears E. and W.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS									
	Dependent Resurvey, Portion, T6S, R27E, Arizona								
6.65	Cement canal, 40 lks. wide, 4 ft. deep, slopes W.								
11.15	S. bank of the Gila River, bearing N. 70° W. and S. 70° E.								
17.70	N. bank of the Gila River.								
23.70	Road, bears N. 40° W. and S. 40° E.								
40.06	Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.  The cor. point falls on private land, which is under cultivation and is not monumented.								
55.50	Fence, barbed wire, bears N. 75° W. and S. 75° E.								
56.20	Graveled road, bears S. 75° E. and N. 75° W.; leave river bottom, thence over rolling hills.								
58.95	SE. cor. of old log shed.								
60.90	Wash, 20 lks. wide, 1 ft. deep, drains E.; asc. 40 ft. over S. slope.								
68.55	Dirt road, bears SE. and NW.								
70.00	Wash, 15 lks. wide, 2 ft. deep, drains SE.; asc. 60 ft. over S. slope.								
80.12	The cor. of secs. 25, 26, 35 and 36, which is mkd. by a malpais stone 19x15x4 ins. set, mkd. and witnessed as described in the official record.  At the cor. point  Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T6SR27E</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2">1960</td></tr> </table> </div> Deposit the original cor. stone alongside iron post.  Land, nearly level river bottom. Soil, river alluvium. Timber, none; undergrowth, none.	T6SR27E		S26	S25	S35	S36	1960	
T6SR27E									
S26	S25								
S35	S36								
1960									
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. which is mkd. by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record.  N. 89°41' W., bet. secs. 25 and 36.  Over rolling land, no timber or undergrowth.  Desc. 60 ft. along NW. slope.								

CHAINS		
6.80	Wash, 20 lks. wide, 2 ft. deep, drains SW.; asc. 80 ft. over SE. slope.	
15.00	Spur, slopes SW.; desc. 60 ft. over NW. slope.	
18.10	Wash; 30 lks. wide, 2 ft. deep, drains SW.; asc. 80 ft. over SE. slope.	
27.50	Spur, slopes SW.; desc. 60 ft. over NW. slope.	
34.50	Wash, 80 lks. wide, 4 ft. deep, drains SW.	
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, to solid rock and in a mound of stone to top, with brass cap mkd.	
	<p>T6SR27E  <math>\frac{1}{4}</math> <math>\frac{S\ 25}{S\ 36}</math>                      1960</p>	
41.42	Dirt road, bears SW. and NE.; asc. 100 ft. over SE. slope.	
50.10	Dirt road, bears S. 40° W. and N. 40° E.	
56.10	Dirt road, bears N. and S.; on spur sloping S.; desc. 50 ft. over W. slope.	
58.60	Wash, 35 lks. wide, 2 ft. deep, drains S. 15° E.; asc. 120 ft. along SE. slope.	
70.00	Spur, sloping S.; desc. 120 ft. over steep W. slope.	
73.00	Wash, 20 lks. wide, 2 ft. deep, drains S.; asc. 40 ft. along S. slope.	
78.80	Wash, 20 lks. wide, 2 ft. deep, drains S.	
79.94	The cor. of secs. 25, 26, 35 and 36.	
	Land, rolling. Soil, rocky, sandy clay. Timber, none; undergrowth, mesquite and catclaw.	
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. which is mkd. by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.	
	S. 89°03' W., bet. secs. 12 and 13.	
	Over mountainous land, no timber.	
	Asc. 30 ft. over E. slope.	
4.50	Flat topped spur, projecting S.; desc. 220 ft. over W. slope.	
15.00	Bottom of canyon, drains S. 30° E., asc. 120 ft. over steep E. slope.	
25.00	Top of steep ascent, thence asc. 100 ft. over rolling E. slope.	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Dependent Resurvey, Portion, T6S, R27E, Arizona

39.76 The 1/4 sec. cor. of sec. 13, hereinafter described.

41.40 The 1/4 sec. cor. of secs. 12 and 13, which is mkd. by a malpais stone, 20x12x8 ins. set, mkd. and witnessed as described in the official record.

At the cor. point

Set and iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

1/4 S12

1960

Deposit the original cor. stone alongside iron post.

This cor. now functions as the 1/4 sec. cor. for sec. 12 only.

N. 89°54' W., beginning new measurement.

Asc. 100 ft. over E. slope.

10.00 Spur, slopes S. 30° E.; desc. 30 ft. along S. slope.

26.00 Wash, near head, drains S. 30° E.; asc. 160 ft. over E. slope.

33.00 Slope changes; asc. 60 ft. along N. slope.

38.12 The closing cor. of secs. 13 and 14, hereinafter described.

39.97 The original cor. of secs. 11, 12, 13 and 14, which is mkd. by a mound of stone and the apparent remains of the original cor. stone.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

S14 S12

1960

Deposit the original cor. stone alongside iron post.

This cor. will now function as the SW. cor. of sec. 12 only.

Land, mountainous.

Soil, gravelly sandy clay.

Timber, none; undergrowth, none.

CHAINS

N. 0°36' E., along the W. bdy. of sec. 12.  
Over mountainous land, no timber, sparse undergrowth.

.68 The closing cor. of secs. 11 and 14; hereinafter described.

Desc. 260 ft. over grassy N. slope.

13.20 Wash, 60 lks. wide, 10 ft. deep, drains E.; asc. 30 ft. over S. slope.

15.00 Small spur slopes E.; desc. 40 ft. over N. slope.

21.10 Wash, 70 lks. wide, 6 ft. deep, drains S. 80° E.; asc. 200 ft. over SW. slope.

40.48 The 1/4 sec. cor. of secs. 11 and 12, which is mkd. by a malpais stone, 12x12x6 ins. set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam. 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

1/4  
S11 | S12  
1960

Deposit the original cor. stone alongside iron post.

N. 0°17' E., beginning new measurement.

Asc. 20 ft. over slight SW. slope.

5.00 Flat topped spur, slopes SE.; desc. 120 ft. along NE. slope.

20.00 Enter wash bottom, drains SE.

33.00 Leave wash bottom; asc. 40 ft. over SW. slope.

40.22 The cor. of secs. 1, 2, 11 and 12, which is mkd. by a malpais stone, 12x12x5 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

S 2 | S 1  
S11 | S12  
1960

Deposit the original cor. stone alongside iron post.

Land, mountainous.  
Soil, gravelly sandy clay.  
Timber, none; undergrowth, scattered catclaw along the drainage.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Dependent Resurvey, Portion, T6S, R27E, Arizona
	<p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. which is mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>S. 89°36' W., bet. secs. 1 and 12.</p> <p>Over mountainous land, no timber; scattered brush.</p>
2.70	Wash, 30 lks. wide, 5 ft. deep, drains S. 40° E.; asc. 100 ft. over NE. slope.
12.00	Land becomes rolling; asc. 60 ft. over slight SE. slope.
37.00	Dirt road, bears S. 70° E. and N. 70° W.
40.33	<p>The ¼ sec. cor. of secs. 1 and 12, which is mkd. by a malpais stone 18x10x4 ins. set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E</p> <p>¼ <math>\frac{S 1}{S 12}</math></p> <p>1960</p> </div> <p>Deposit the original cor. stone alongside iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°52' W., beginning new measurement.</p> <p>Over nearly level land.</p>
14.50	Dirt road, bears N. and S.
36.20	Canyon rim, bears NW. and SE.; desc. 20 ft. over SW. slope.
40.09	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, nearly level to rolling. Soil, gravelly sandy clay. Timber, none; undergrowth, scattered mesquite and catclaw.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land, no timber.</p> <p>Asc. 50 ft. over slight SW. slope.</p>
14.10	Dirt road, bears N. 30° W., and S. 80° E.
36.00	Top of ascent on spur sloping SE.; desc. 20 ft. over N. slope.

CHAINS

40.07

The 1/4 sec. cor. of secs. 1 and 2, which is mkd. by a malpais stone 14x8x6 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

1/4  
S 2 | S 1  
1960

Deposit the original cor. stone alongside iron post.

N. 0°02' W., beginning new measurement.

22.00

Wash, 50 lks. wide, 2 ft. deep, drains S. 70° E.

28.00

Dirt road, bears E. and W.; asc. 100 ft. over slight SW. slope.

39.00

Intersect the First Standard Parallel South at the closing cor. of secs. 1 and 2, which is mkd. by a malpais stone, 16x10x6 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E

S 2 | S 1  
CC  
T6S  
1960

Deposit the original cor. stone alongside iron post.

From this cor. the standard 1/4 sec. cor. of sec. 35, previously described bears S. 89°58' W., 19 lks. dist.

Land, rolling.

Soil, rocky, sandy clay.

Timber, none; undergrowth, scattered catclaw and mesquite.

The point for the N. 1/4 sec. cor. of sec. 1 is at mid-point and on the N. bdy. of the township.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E

1/4 S 1  
T6S  
1960

From this cor. the standard cor. of secs. 35 and 36, T. 5 S., R. 27 E., bears S. 89°53' W., 19 lks. dist.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Dependent Resurvey, Portion, T6S, R27E, Arizona
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy., which is mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>N. 0°18' E., bet. secs. 34 and 35.</p> <p>Over nearly level land.</p>
.09	Fence, barbed wire, bears E. and W.; thence over cultivated field.
6.40	Leave field, at fence bearing E. and W.
7.50	Irrigation ditch, 15 lks. wide, 2 ft. deep, drains S. 45° E.
11.00	Fence, barbed wire, bears E. and W.; leave cultivated land.
11.65	Gravelled road, bears S. 80° W. and N. 80° E.; asc. 150 ft. along rolling E. slope.
33.60	Edge of spur, sloping N. 5° W.; desc. 30 ft. along E. slope.
39.92	<p>The ¼ sec. cor. of secs. 34 and 35, which is mkd. by a malpais stone, 22x14x4 ins., set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E</p> <p>¼</p> <p>S34   S35</p> <p>1960</p> </div> <p>Deposit the original cor. stone alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' E., beginning new measurement.</p> <p>Desc. 40 ft. along E. slope.</p>
3.40	Wash, 35 lks. wide, 3 ft. deep, drains S. 45° E.; asc. 40 ft. along E. slope.
9.60	Wash, 150 lks. wide, 3 ft. deep, drains S. 30° E.; asc. 360 ft. over ledgy SW. slope.
20.00	Rim of mesa, bears NW. and SE., thence over nearly level land.
39.78	<p>The cor. of secs. 26, 27, 34 and 35, which is mkd. by a malpais stone, 15x8x7 ins., set, mkd. and witnessed as described in the official record.</p> <p>At the corner point</p>

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T6SR26E  
 $\frac{S27}{S34} | \frac{S26}{S35}$   
 1960

Deposit the original cor. stone alongside iron post.

Land, rolling to nearly level.  
 Soil, gravelly sandy clay.  
 Timber, none; undergrowth, creosote brush and catclaw.

From the cor. of secs. 25, 26, 35 and 36.

S. 89°35' W., bet. secs. 26 and 35.

Over rolling land, through scattered creosote brush and catclaw.

Asc. 50 ft. over E. slope.

- 5.00 Spur, slopes S., desc. 100 ft. over SW. slope.
- 9.40 Wash, 40 lks. wide, 3 ft. deep, drains S.; asc. 60 ft. over E. slope.
- 17.40 Dirt road, bears S. 20° E. and N. 20° W.; desc. 40 ft. over W. slope.
- 20.90 Wash, 20 lks. wide, 1 ft. deep, drains S.; asc. 160 ft. over E. slope.
- 26.00 Spur, sloping S.; desc. 120 ft. over W. slope.
- 33.30 Wash, 30 lks. wide, 2 ft. deep, drains SW.
- 36.40 Wash, 100 lks. wide, 3 ft. deep, drains S.; asc. 80 ft. along NE. slope.
- 39.89 The ¼ sec. cor. of secs. 26 and 35, which is mkd. by a malpais stone, 20x14x10 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
 $\frac{1}{4} \frac{S26}{S35}$   
 1960

Deposit the original cor. stone alongside iron post.

S. 89°53' W., beginning new measurement.

Asc. 90 ft. over NE. slope.

- 4.00 Spur, slopes SE.; desc. 60 ft. over SW. slope.
- 5.60 Wash, 90 lks. wide, 2 ft. deep, drains SE.; asc. 200 ft. over steep E. slope.
- 19.00 Rim of mesa, bears N. 30° W. and S. 30° E.; thence over nearly level land.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Dependent Resurvey, Portion, T6S, R27E, Arizona</p> <hr/>
28.60	<p>Fence, barbed wire, bears N. and S.</p>
40.14	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling to nearly level. Soil, gravelly sandy clay. Timber, none; undergrowth, creosote brush and catclaw.</p> <hr/>
	<p>N. 0°09' E., bet. secs. 26 and 27.</p>
	<p>Over nearly level land, through scattered creosote brush.</p>
7.00	<p>Wash, 20 lks. wide, 2 ft. deep, drains N. 10° W.</p>
12.80	<p>Wash, 35 lks. wide, 2½ ft. deep, drains S. 20° W.</p>
19.50	<p>Wash, 30 lks. wide, 3 ft. deep, drains SW.</p>
39.80	<p>The ¼ sec. cor. of secs. 26 and 27, which is mkd. by a malpais stone, 14x10x8 ins., set, mkd. and witnessed as described in the official record.</p>
	<p>At the cor. point</p>
	<p>Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.</p>
	<p style="text-align: center;">T6SR27E       ½ S27   S26       1960</p>
	<p>Deposit the original cor. stone alongside iron post.</p> <hr/>
	<p>N. 0°09' E., beginning new measurement.</p>
	<p>By triangulation; asc. 680 ft. over boulder strewn, ledgy S. slope.</p>
40.00	<p>The cor. position for the cor. of secs. 22, 23, 26 and 27 as determined by the remaining mound of stone and its relationship to identified original corners in the area.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6SR27E S22   S23 S27   S26       1960</p>
	<p>Land, S. ½ mile rolling, N. ½ mile mountainous. Soil, rocky, sandy clay. Timber, none; undergrowth, creosote brush and catclaw.</p> <hr/>

CHAINS	
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°59' W., bet. secs. 2 and 11.
	Over rolling land, through scattered creosote and catclaw.
	Desc. 50 ft. over SW. slope.
7.20	Wash, 40 lks. wide, 4 ft. deep, drains S. 50° E.; asc. 100 ft. over NE. slope.
17.00	Spur, sloping SE.; desc. 20 ft. over SW. slope.
24.30	Wash, 20 lks. wide, 4 ft. deep, drains SE.; asc. 80 ft. along SE. slope.
38.49	The $\frac{1}{2}$ sec. cor. of sec. 11 hereinafter described.
39.94	The $\frac{1}{2}$ sec. cor. of secs. 2 and 11, which is monumented by a malpais stone, 18x18x8 ins., set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	T6SR27E $\frac{1}{2}$ S 2 ----- 1960
	Deposit the original cor. alongside the iron post.
	This cor. will now function as the cor. of sec. 2 only.
	-----
	S. 89°54' W., beginning new measurement.
.20	Spur, slopes SE.; desc. 30 ft. over SW. slope.
9.40	Wash, 30 lks. wide, 2 ft. deep, drains S. 70° E.; asc. 90 ft. over NE. slope.
20.00	Spur, slopes SE.; thence along slight S. slope.
36.00	Track road, bears N. 70° W. and S. 70° E.
38.55	The closing cor. of secs. 10 and 11, hereinafter described; thence bet. secs. 2 and 10.
40.39	The cor. of secs. 2, 3, 10 and 11, which is monumented by a malpais stone, 16x10x4 ins., set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	T6SR27E S 3   S 2 ----- S 10 1960
	Deposit the original cor. stone alongside the iron post.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Dependent Resurvey, Portion, T6S, R27E, Arizona
	<p>This cor. now functions as the cor. of secs. 2 and 3, only.</p> <p>Land, rolling. Soil, gravelly sandy clay. Timber, none; undergrowth, scattered creosote brush and catclaw.</p>
	<p>N. 0°25' W., bet. secs. 2 and 3.</p> <p>Over hilly land, through undergrowth.</p> <p>Asc. 140 ft. over S. slope.</p>
19.60	E. side of hill, approx. 5.00 chains E. of crest; desc. 220 ft. over N. slope.
38.70	Graded road, bears N. 40° E. and S. 60° W.
39.46	The W.C. ¼ sec. cor. of secs. 2 and 3, which is monumented by a malpais stone, 24x8x6 ins., set, mkd. and witnessed as described in the official record.
	<p>At the witness cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E WC ¼ S 3   S 2 1960</p> </div> <p>Deposit the original cor. stone alongside the iron post.</p>
40.66	True point for the ¼ sec. cor. of secs. 2 and 3 falls in wash, 125 lks. wide, 4 ft. deep, draining S. 80° E., where the cor. monument cannot be perpetuated.
	<p>N. 0°30' E., beginning new measurement.</p> <p>Asc. 80 ft. over SW. slope.</p>
12.00	Spur, sloping SE.; desc. 30 ft. over NE. slope.
17.00	Wash, 20 lks. wide, 3 ft. deep, drains S. 50° E.; asc. 100 ft. over SW. slope.
37.10	Dirt road, bears S. 80° E. and S. 80° W.
38.17	Intersect the First Standard Parallel South, at the closing cor. of secs. 2 and 3, which is monumented by a malpais stone, 24x24x12 ins., set, mkd. and witnessed as described in the official record.
	<p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone to top, with brass cap mkd.</p>

CHAINS

T5SR27E

S 3 | S 2

CC

T6S

1960

Deposit the original cor. stone alongside iron post.

From this cor. the standard  $\frac{1}{4}$  sec. cor. of sec. 34, previously described, bears S.  $89^{\circ}54'$  W., 22 lks. dist.

Land, rolling.

Soil, gravelly sandy clay.

Timber, none; undergrowth, creosote brush and catclaw.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 2 is at mid-point and on the N. bdy. of the township.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E

$\frac{1}{4}$  S 2

T6S

1960

From this cor. the standard cor. of secs. 34 and 35, previously described, bears S.  $89^{\circ}55'$  W., 12 lks. dist.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township, which is monumented by an iron post  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the official record.

N.  $0^{\circ}13'$  E., bet. secs. 33 and 34.

Over nearly level land; through creosote brush.

4.00 Road, bears S.  $75^{\circ}$  W. and N.  $75^{\circ}$  E.

10.00 Rim of mesa, bears NW. and SE.; desc. 120 ft. over steep boulder-strewn NE. slope.

13.20 Wash, 2.00 chs. wide, 10 ft. deep, drains E.; asc. 280 ft. over steep boulder-strewn SE. slope.

19.00 Edge of mesa, bears SW. and NE.; thence over nearly level mesa top.

32.71 Wash, 20 lks. wide, 2 ft. deep, drains S.  $80^{\circ}$  W.; asc. 20 ft. over S. slope.

39.81 The  $\frac{1}{4}$  sec. cor. of secs. 33 and 34, which is monumented by a malpais stone, 15x10x5 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

$\frac{1}{4}$   
S33 | S34

1960

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Dependent Resurvey, Portion, T6S, R27E, Arizona
40.07	<p>Deposit the original cor. stone alongside the iron post.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 27, 28, 33 and 34, which is monumented by a malpais stone, 15x7x6 ins., set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set the iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E  <math>\frac{S28}{S33}   \frac{S27}{S34}</math>            1960</p> </div> <p>Deposit the original cor. stone alongside the iron post.</p> <p>Land, nearly level.            Soil, gravelly sandy clay.            Timber, none; undergrowth, creosote brush and catclaw.</p>
9.30	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°55' W., bet. secs. 27 and 34.</p> <p>Over nearly level land, through creosote brush.</p> <p>Rim of mesa, bears NE. and SW.; desc. 50 ft. over NW. slope.</p>
15.20	<p>Wash, 2.00 chs. wide, 6 ft. deep, drains S. 45° W.; asc. 50 ft. over SE. slope.</p>
20.00	<p>Rim of mesa, bears NE. and SW.; thence over mesa land.</p>
32.00	<p>Mesa rim, bears irregularly N. and S.; desc. 160 ft. over steep W. slope.</p>
37.00	<p>Thence over bottom land.</p>
39.88	<p>The ¼ sec. cor. of secs. 27 and 34, which is monumented by a malpais stone, 15x10x4 ins. set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set the iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E  <math>\frac{1}{4} \frac{S 27}{S 34}</math>            1960</p> </div> <p>Deposit the original cor. stone alongside the iron post.</p> <hr/>

CHAINS

N. 89°49' W., beginning new measurement.

Over bottom land.

2.00 Leave bottom land; asc. 150 ft. over S. slope.

6.40 Point of spur, sloping from NW.; desc. 40 ft. over SW. slope.

10.50 Wash, 1.00 chain wide, 15 ft. deep, drains S. 75° E.; asc. 30 ft. over slight SE. slope.

39.76 The cor. of secs. 27, 28, 33 and 34.

Land, nearly level.

Soil, gravelly sandy clay.

Timber, none; undergrowth, creosote brush and catclaw.

N. 0°04' E., bet. secs. 27 and 28.

Over nearly level land, through creosote brush and catclaw.

Asc. 10 ft. over slight SE. slope.

21.25 Road, bears S. 35° W. and N. 40° E.

29.10 Bulldozed trail, bears E. and W.

40.03 The 1/4 sec. cor. of secs. 27 and 28, which is monumented by a malpais stone, 20x10x4 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.

T6SR27E

1/4  
S28 | S27  
1960

Deposit the original cor. stone alongside iron post.

N. 0°02' E., beginning new measurement.

Asc. 40 ft. over S. slope.

15.40 Wash, 30 lks. wide, 2 ft. deep, drains SW.; asc. 200 ft. over S. slope.

38.00 Wash, 40 lks. wide, 2 ft. deep, drains S. 20° W.

40.63 Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

S21 | S22  
S28 | S27  
1960



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

CHAINS	
	<p>Dependent Resurvey, Portion, T6S, R27E, Arizona</p> <hr/> <p>Land, nearly level in S<math>\frac{1}{2}</math>, rolling in N<math>\frac{1}{2}</math>. Soil, gravelly sandy clay. Timber, none; undergrowth, creosote bush and catclaw.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27. N. 89°12' W., bet. secs. 22 and 27. Over mountainous land, through creosote brush and catclaw. Along boulder-strewn S. slope.</p>
20.00	Slope changes; desc. 300 ft. over steep boulder-strewn SW. slope.
39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;">T6SR27E <math>\frac{1}{4}</math> <math>\frac{S\ 22}{S\ 27}</math> 1960</p>
	Desc. 160 ft. over steep boulder-strewn SW. slope.
53.46	Spur, slopes S.; desc. 80 ft. over SW. slope.
62.86	Wash, 40 lks. wide, 4 ft. deep, drains S.; asc. 40 ft. over SE. slope.
70.00	Spur, slopes S.; desc. 80 ft. over SW. slope.
79.92	The cor. of secs. 21, 22, 27 and 28.
	<p>Land, mountainous and rolling. Soil, boulder-strewn gravelly sandy clay. Timber, none; undergrowth, creosote brush and catclaw.</p> <hr/> <p>N. 0°02' E., bet. secs. 21 and 22. Over mountainous land, through creosote brush and catclaw. Asc. 720 ft. over steep boulder-strewn S. slope.</p>
30.00	Crest of mountain, bears N. 85° E. and S. 85° W.; desc. 100 ft. over N. slope.
38.25	Wash, 20 lks. wide, 2 ft. deep, drains N. 65° E.; asc. 10 ft. over S. slope.
38.88	The W. $\frac{1}{4}$ sec. cor. of sec. 22 hereinafter described.

CHAINS

40.63

The 1/4 sec. cor. of secs. 21 and 22, which is monumented by a malapis stone, 12x12x5 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
1/4 |  
S21 |  
1960

Deposit the original cor. stone alongside iron post.

This cor. now functions as the cor. of sec. 21, only.

N. 0°05' E., beginning new measurement.

Asc. 180 ft. over S. slope.

11.40

Spur, slopes N. 10° E.; desc. 160 ft. over N. slope.

20.35

Wash, 30 lks. wide, 2 ft. deep, drains N. 75° E.; asc. 100 ft. over S. slope.

25.65

Spur, slopes E.; desc. 320 ft. over steep boulder-strewn N. slope.

32.30

Track road, bears E. and W.

34.90

Wash, 35 lks. wide, 2 ft. deep, drains N. 75° W.; asc. 30 ft. over S. slope.

37.10

Bulldozed road, bears S. 45° E. and N. 45° W.

38.25

The closing cor. of secs. 15 and 22 hereinafter described thence bet. secs. 15 and 21.

39.14

The cor. of secs. 15, 16, 21 and 22, which is monumented by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of sec. 16, T6S, R27E.

I remark the brass cap

T6SR27E  
S16 |  
S21 | S15  
1955  
1960

This cor. now functions as the cor. of secs. 16 and 21, only.

Land, mountainous.  
Soil, boulder-strewn, gravelly sandy clay.  
Timber, none; undergrowth, creosote brush and catclaw.

From the cor. of secs. 2 and 3, previously described.

West, bet. secs. 3 and 10.

Over rolling land, through creosote brush.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Dependent Resurvey, Portion, T6S, R27E, Arizona

Asc. 20 ft. along S. slope.

- 12.60 Track road, bears S. 20° E. and N. 20° W.; asc. 20 ft. along S. slope.
- 17.30 Wash, 30 lks. wide, 4 ft. deep, drains S. 30° E.; asc. 10 ft. along S. slope.
- 22.60 Fence, barbed wire, bears S. 50° W.; asc. 50 ft. along S. slope.
- 38.17 The ¼ sec. cor. of sec. 10, hereinafter described.
- 40.12 The ¼ sec. cor. of secs. 3 and 10, which is monumented by a malpais stone, 18x6x6 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
¼ S 3  
-----  
1960

Deposit the original cor. stone alongside iron post.

This cor. now functions as the cor. of sec. 3, only.

West, beginning new measurement.

Over rolling land.

- 12.80 Fence, barbed wire, bears N. 35° E. and S. 35° W.; asc. 30 ft. along S. slope.
- 20.60 Graded road, bears N. 50° E. and S. 50° W.
- 30.60 Graded road, bears N. 5° E. and S. 5° W.
- 38.06 The closing cor. of secs. 9 and 10, hereinafter described; thence bet. secs. 3 and 9.
- 40.02 The cor. of secs. 3, 4, 9 and 10, which is monumented by a malpais stone, 16x8x8 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
S 4 | S 3  
S 9  
-----  
1960

CHAINS		
	<p>Deposit the original cor. stone alongside iron post.</p> <p>This cor. now functions as the cor. of secs. 3 and 4, only.</p> <p>Land, rolling. Soil, gravelly, sandy clay. Timber, none; undergrowth, creosote brush.</p> <hr/> <p>N. 0°52' W., bet. secs. 3 and 4.</p> <p>Over rolling land, through creosote brush.</p> <p>Along E. slope.</p>	
7.55	Wash, 20 lks. wide, 4 ft. deep, drains E.; asc. 30 ft. over S. slope.	
11.95	Spur, sloping E.; desc. 100 ft. over N. slope.	
23.00	Wash, 2.00 chs. wide, 4 ft. deep, drains N. 80° E.; asc. 20 ft. over S. slope.	
28.10	Graded road, bears N. 75° W. and S. 75° E.; asc. 40 ft. over S. slope.	
39.99	<p>The ¼ sec. cor. of secs. 3 and 4, which is monumented by a malpais stone, 14x10x8 ins., set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E ¼ S 4   S 3 1960</p>	
	<p>Deposit the original cor. stone alongside iron post.</p> <hr/> <p>N. 1°03' E., beginning new measurement.</p>	
1.00	Base of steep boulder-strewn slope; asc. 240 ft. over S. slope.	
11.80	Spur, N. 80° E.; desc. 100 ft. over N. slope.	
18.30	Wash, 40 lks. wide, 2 ft. deep, drains N. 70° E.; asc. 30 ft. over S. slope.	
23.60	Spur, slopes NE.; desc. 100 ft. over N. slope.	
34.95	Wash, 25 lks. wide, 4 ft. deep, drains S. 70° E.; asc. 20 ft. over S. slope.	
38.75	<p>Intersect the First Standard Parallel South at the closing cor. of secs. 3 and 4, which is monumented by a malpais stone, 16x10x6 ins., set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.</p>	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Dependent Resurvey, Portion, T6S, R27E, Arizona

T5SR27E

S 4 | S 3

CC

T6S

1960

Deposit the original cor. stone alongside iron post.

From this cor. the standard  $\frac{1}{4}$  sec. cor. of sec. 33, previously described, bears S.  $89^{\circ}53'$  W., 26 lks. dist.

Land, rolling.

Soil, gravelly sandy clay.

Timber, none; undergrowth, creosote brush.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 3 is at mid-point and on the N. bdy. of the township.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E

$\frac{1}{4}$  S 3

T6S

1960

From this cor. the standard cor. of secs. 33 and 34, T5S, R27E, bears S.  $89^{\circ}53'$  W., 29 lks. dist.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, which is monumented by an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the official record.

N.  $0^{\circ}07'$  E., bet. secs. 32 and 33.

Over nearly level land, through creosote brush and catclaw.

Asc. 80 ft. over slight S. slope.

17.00 Spur, slopes S.  $30^{\circ}$  W.; desc. 120 ft. along NW. slope.

33.60 Wash, 70 lks. wide, 5 ft. deep, drains S.  $80^{\circ}$  W.; asc. 60 ft. over boulder-strewn SE. slope.

40.01 The  $\frac{1}{4}$  sec. cor. of secs. 32 and 33, which is monumented by a malpais stone, 17x10x5 ins. set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

CHAINS

T6SR27E

$\frac{1}{4}$   
S32|S33  
1960

Deposit the original cor. stone alongside the iron post.

N. 0°06' E., beginning new measurement.

Asc. 60 ft. over SE. slope.

10.90

Rim of mesa bears irregularly NE. and SW., thence over nearly level land.

17.70

Wash, 25 lks. wide, 2 ft. deep, drains E.; asc. 30 ft. over S. slope.

23.00

Point projecting from mesa; desc. 30 ft. along NE. slope.

31.00

Wash, 80 lks. wide, 10 ft. deep, drains E.; asc. 40 ft. over S. slope.

40.04

The cor. of secs. 28, 29, 32 and 33, which is monumented by a malpais stone, 15x7x7 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

S29|S28  
S32|S33  
1960

Deposit the original cor. stone alongside the iron post.

Land, nearly level.

Soil, gravelly sandy clay.

Timber, none; undergrowth, creosote brush and catclaw.

From the cor. of secs. 27, 28, 33 and 34.

N. 89°41' W., bet. secs. 28 and 33.

Over nearly level land, through creosote brush and catclaw.

9.20

Track road, bears N. 10° E. and S. 10° W.

39.81

The ¼ sec. cor. of secs. 28 and 33, which is monumented by a malpais stone, 18x10x6 ins., set mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T6SR27E

$\frac{1}{4}$  S28  
S33  
1960

Deposit the original cor. stone alongside the iron post.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Dependent Resurvey, Portion, T6S, R27E, Arizona
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
	_____
	N. 89°51' W., beginning new measurement.
	Over nearly level land.
24.00	Wash, 70 lks. wide, 5 ft. deep, drains S. 20° W.
40.07	The cor. of secs. 28, 29, 32 and 33.
	Land, nearly level. Soil, gravelly sandy clay. Timber, none; undergrowth, creosote brush and catclaw.
	_____
	N. 0°04' E., bet. secs. 28 and 29.
	Over rolling land, through creosote brush and catclaw.
	Asc. 60 ft. over slight S. slope.
40.10	The ¼ sec. cor. of secs. 28 and 29, which is monumented by a malapis stone, 18x7x6 ins., set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	T6SR27E ¼ S29   S28 1960
	Deposit the original cor. stone alongside the iron post.
	_____
	North, beginning new measurement.
	Asc. 40 ft. over slight S. slope.
18.20	Track road, bears E. and W.; asc. 80 ft. over slight S. slope.
40.02	The cor. of secs. 20, 21, 28 and 29, which is monumented by a malpais stone, 20x8x9 ins., set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mka.
	T6SR27E S20   S21 S29   S28 1960

## CHAINS

Deposit the original cor. stone alongside iron post.

Land, nearly level on slight S. slope.

Soil, gravelly sandy clay.

Timber, none, undergrowth, creosote brush and catclaw.

---

From the cor. of secs. 21, 22, 27 and 28.

S. 89°04' W., bet. secs. 21 and 28.

Over mountainous land, through creosote brush and catclaw.

Desc. 200 ft. over boulder strewn SW. slope.

39.98 The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, which is monumented by a malpais stone, 23x8x5 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

$\frac{1}{4}$   $\frac{S\ 21}{S\ 28}$

1960

Deposit the original cor. stone alongside the iron post.

---

N. 89°29' W., beginning new measurement.

Over rolling land.

11.70 Wash, 60 lks. wide, 5 ft. deep, drains S. 20° W.

25.85 Track road, bears S. 70° E. and N. 70° W.

39.97 The cor. of secs. 20, 21, 28 and 29.

Land, rolling and mountainous.

Soil, gravelly sandy clay.

Timber, none; undergrowth, creosote brush and catclaw.

---

N. 0°03' E., bet. secs. 20 and 21.

Over rolling land, through creosote brush and catclaw.

4.20 Track road, bears E. and W.; asc. 40 ft. over SW. slope.

21.30 Wash, 50 lks. wide, 6 ft. deep, drains S. 20° W.; asc. 30 ft. along SE. slope.

30.70 Prospect hole, 12x8x5 ft.; asc. 60 ft. along SE. slope.

40.06 The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, which is monumented by a malpais stone, 12x10x8 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Dependent Resurvey, Portion, T6S, R27E, Arizona

T6SR27E

$\frac{1}{4}$   
S20 | S21  
1960

Deposit the original cor. stone alongside iron post.

N. 0°09' E., beginning new measurement.

Asc. 50 ft. along SE. slope.

- 17.00 Spur, slopes SW.; desc. 20 ft. along NW. slope.
- 20.00 Wash, 1.50 chs. wide, 3 ft. deep, drains SW.; asc. 20 ft. over SE. slope.
- 24.70 Wash, 50 lks. wide, 2 ft. deep, drains SW.
- 35.15 Gravelled road, bears S. 40° W. and N. 40° E.
- 40.10 The cor. of secs. 16, 17, 20 and 21, which is monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.  
Soil, gravelly sandy clay.  
Timber, none; undergrowth, creosote brush and catclaw.

From the cor. of secs. 8, 9, 16 and 17, which is monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°46' W., bet. secs. 8 and 9.

Over mountainous land; through scattered undergrowth.

Asc. 600 ft. over ledgy S. slope.

- 16.50 Ridge, bears E. and approx. 8.00 chs. W. to knob; by triangulation desc. about 440 ft. over steep N. slope.
- 32.00 Wash, 40 lks. wide, 2 ft. deep, drains E.; asc. about 200 ft. over steep S. slope.
- 39.84 Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

$\frac{1}{4}$   
S8 | S9  
1960

Asc. about 180 ft. over steep S. slope.

CHAINS		
49.90	Ridge, bears E. and W., end of triangulation; desc. 470 ft. over steep N. slope.	
69.20	Wash, 1.00 chain wide, 3 ft. deep, drains E.; asc. 250 ft. over steep S. slope.	
77.36	Intersect line 2-3 of M.S. 4457, Lone Star No. 60 lode at a point from which Cor. No. 2 bears N. 79°24'06" E., 1.95 chs. dist., and Cor. No. 3 bears S. 79°24'06" W., 20.78 chs. dist.	
79.68	The cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the original corner.	
	At the cor. point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.	
	T6SR27E S 8   S 4   S 9 1960	
	This cor. will now function as the cor. of secs. 4 and 9 only.	
	Land, mountainous. Soil, rocky, sandy clay. Timber, none; undergrowth, cresotebush, catclaw and cacti.	
	From the cor. of secs. 3 and 4.	
	N. 89°53' W., bet. secs. 4 and 9.	
	Over mountainous land, through creosote brush and catclaw.	
	Asc. 240 ft. along S. slope.	
17.00	Top of ascent on S. side of hill; desc. 100 ft. along S. slope.	
38.04	The ¼ sec. cor. of sec. 9 hereinafter described.	
39.47	The point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.	
	Set the iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.	
	T6SR27E ¼ S 4 1960	
	This cor. now functions as the cor. of sec. 4, only.	
	Asc. 320 ft. along S. slope.	
66.76	Intersect line 3-4 of M.S. No. 4457, Lone Star No. 59 lode at a point from which Cor. No. 3 bears N. 79°15'45" E., 12.32 chs. dist. and Cor. No. 4 bears S. 79°15'45" W., 10.41 chs. dist.	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Dependent Resurvey, Portion, T6S, R27E, Arizona</p> <hr/>
<p>78.94</p>	<p>The cor. of secs. 4 and 9.</p> <p>Land, mountainous. Soil, rocky sandy clay. Timber, none; undergrowth, creosote brush and catclaw.</p> <hr/>
	<p>N. 0°46' W., bet. secs. 4 and 8.</p> <p>Over mountainous land, through scattered creosote brush and catclaw.</p>
<p>1.07</p>	<p>The closing cor. of secs. 5 and 8, hereinafter described, thence bet. secs. 4 and 5.</p> <p>Asc. 400 ft. over ledgy S. slope.</p>
<p>13.00</p>	<p>Crest of the Gila Mountains, bears irregularly NW. and SE.; desc. 600 ft. over steep ledgy N. slope.</p>
<p>38.54</p>	<p>Graded road, bears E. and W.</p>
<p>39.84</p>	<p>The ¼ sec. cor. of secs. 4 and 5, which is monumented by a malpais stone, 14x9x6 ins., set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E</p> <p>       ½</p> <p>       S 4</p> <p>       1960</p> </div> <p>Deposit the original cor. stone alongside the iron post.</p> <p>This cor. now functions as the cor. of sec. 4, only.</p> <hr/> <p>N. 0°11' E., beginning new measurement.</p>
<p>1.23</p>	<p>The ¼ sec. cor. of sec. 5, hereinafter described.</p>
<p>1.40</p>	<p>Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 100 ft. over S. slope.</p>
<p>10.70</p>	<p>Track road, bears E. and W.; on spur sloping E.; desc. 80 ft. over N. slope.</p>
<p>20.80</p>	<p>Wash, 70 lks. wide, 3 ft. deep, drains S. 70° E.; asc. 40 ft. over S. slope.</p>
<p>23.60</p>	<p>Track road, bears E. and W.; asc. 160 ft. along E. slope.</p>
<p>38.73</p>	<p>Intersect the First Standard Parallel South, at the closing cor. of secs. 4 and 5, which is monumented by a malpais stone, 15x12x8 ins., set, mkd. and witnessed as described in the official record.</p>

## CHAINS

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E

S 5 | S 4  
CC

T6S  
1960

Deposit the original cor. stone alongside the iron post.

From this cor. the standard  $\frac{1}{4}$  sec. cor. of sec. 32, T5S, R27E, bears West 30 lks. dist.

Land, mountainous.

Soil, rocky gravelly clay.

Timber, none; undergrowth, creosote brush and catclaw.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 4 is at mid-point and on the N. bdy. of the township.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T5SR27E

$\frac{1}{4}$  S 4

T6S  
1960

From this cor. the Standard cor. of secs. 32 and 33 bears S.  $89^{\circ}49'$  W., 28 lks. dist.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the township, monumented by an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the official record.

N.  $0^{\circ}01'$  E., bet. secs. 31 and 32.

Over rolling land on slight S. slope, through scattered to medium undergrowth; asc. 10 ft.

9.35 Dirt road, bears E. and W.; asc. 90 ft. over S. slope.

24.00 Spur, slopes S.  $70^{\circ}$  W.; desc. 40 ft. over NW. slope.

30.60 Wash, 30 lks. wide, 1 ft. deep, drains S.  $70^{\circ}$  W.; asc. 60 ft. over S. slope.

37.70 Spur, projects S.  $80^{\circ}$  W.; desc. 30 ft. over N. slope.

39.98 The  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, monumented by a malapis stone, 20x10x8 ins., set 14 ins. in the ground, marked  $\frac{1}{4}$  on N. face. There is a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of the corner.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Dependent Resurvey, Portion, T6S, R27E, Arizona

T6SR27E

$\frac{1}{2}$   
S31|S32

1960

Deposit the original cor. stone at base of iron post.

There are no other suitable accessories available.

N. 0°17' E., beginning new measurement.

Desc. 30 ft. over N. slope.

2.90 Wash, 100 lks. wide, 8 ft. deep, drains S. 80° W.;  
asc. 40 ft. over S. slope.

10.90 Small wash, drains S. 20° W.; asc. 120 ft. over S.  
slope.

16.00 Spur, projects W.; asc. 10 ft. along gentle W. slope.

28.50 Spur, projects N. 60° W.; desc. 30 ft. over NE. slope.

37.50 Wash, 20 lks. wide, 10 ft. deep, drains N. 60° W.

38.70 Wash, 35 lks. wide, 3 ft. deep, drains W. about 2 chs.  
to junction with wash from SE.

40.00 The cor. of secs. 29, 30, 31, and 32, monumented by  
a malpais stone, 20x12x8 ins., set 8 ins. in the ground,  
marked with 5 notches on the east face, 1 notch on  
the south face, T6S on the NE., and R27E on the SE.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T6SR27E

S30|S29

S31|S32

1960

Deposit original cor. stone alongside of iron post.

Raise a mound of stone, 3½ ft. base, 2½ ft. high,  
W. of cor.

Land, rolling.

Soil, gravelly clay.

Undergrowth, creosote brush, palo verde, and catclaw.

Timber, none.

From the cor. of secs. 28, 29, 32 and 33.

S. 89°59' W., bet. secs. 29 and 32.

Over nearly level land draining S., through scattered  
to medium undergrowth.

CHAINS		
14.60	Wash, 25 lks. wide, 3 ft. deep, drains S. for about 5 chs., then S. 70° W.	
32.30	Dirt road, bears N. and S.	
39.81	The ¼ sec. cor. of secs. 29 and 32, monumented by a malpais stone, 15x10x5 ins., set 8 ins. in the ground, marked ¼ on north face. There is a mound of stone, 3 ft. base, 2 ft. high, N. of cor.	
	At the cor. point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.	
	T6SR27E ¼ $\frac{S\ 29}{S\ 32}$ 1960	
	Deposit the original cor. stone at base of iron post.	
	There are no other suitable accessories.	
	_____	
	N. 89°55' W., beginning new measurement.	
	Desc. 70 ft. over gently rolling land, drains W.	
17.20	Wash, 35 lks. wide, 2 ft. deep, drains S. 60° W.	
26.40	Low spur, slopes S. 70° W.	
36.60	Wash, 40 lks. wide, 3 ft. deep, drains W.	
39.99	The cor. of secs. 29, 30, 31 and 32.	
	Land, gently rolling. Soil, gravelly clay. Undergrowth, creosote brush, catclaw, and palo verde. Timber, none.	
	_____	
	N. 89°57' W., bet. secs. 30 and 31.	
	Over rolling land, through scattered to medium undergrowth.	
1.00	Wash, 100 lks. wide, 2 ft. deep, drains N. 70° W.; asc. 30 ft. along N. slope.	
10.90	Top of ascent, slopes N.; desc. 50 ft. along rolling N. slope.	
27.30	Recross wash, 50 lks. wide, 7 ft. deep, drains S. 20° W.; continue over nearly level land.	
39.97	The ¼ sec. cor. of secs. 30 and 31, monumented by a malpais stone, 15x6x5 ins., set in a small mound of stone, marked ¼ on north face.	
	At the cor. point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.	
	T6SR27E ¼ $\frac{S\ 30}{S\ 31}$ 1960	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Dependent Resurvey, Portion, T6S, R27E, Arizona
	<p>Deposit the original cor. stone at base of iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of iron post.</p> <hr/> <p>N. 89°46' W., beginning new measurement.</p> <p>Continue over nearly level land.</p>
3.80	Dirt road, bears N. and S.
9.90	Gravel road, bears NE. and SW.
14.70	Water check, 6 ft. high, 8 ft. wide, across wash; wash is 2 chs. wide, and drains SW.; asc. 60 ft. over SE. slope.
34.00	Spur, projects S.; desc. 40 ft. over SW. slope.
38.67	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township; monumented by an iron post, 2½ ins. diam., set, marked and witnessed as described in the official record.
	<p>Land, rolling. Soil, gravelly clay. Undergrowth, creosote brush and catclaw. Timber, none.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°02' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through medium to scattered undergrowth; asc. 30 ft. over SW. slope.</p>
9.50	Spur, slopes W.; desc. 10 ft. over NW. slope.
12.10	Wash, 50 lks. wide, 3 ft. deep, drains S. 80° W.; asc. 20 ft. over gently rolling land, draining S.
40.10	The ¼ sec. cor. of secs. 29 and 30, monumented by a malpais stone, 15x10x8 ins., set 8 ins. in the ground, marked ¼ on west face.
	<p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6SR26E ¼ S30   S29 1960</p>
	<p>Deposit the original cor. stone alongside iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <hr/>

CHAINS

N. 0°01' W., beginning new measurement.

Through scattered to medium undergrowth, over gently rolling land, draining S.

6.30 Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.

26.25 Gravelled road, bears NE. and SW.

30.85 Track road, bears N. 80° W. and S. 80° E. about 4 chs. to junction with NE.-SW. road.

35.10 Dirt road, bears N. 30° E. and S. 30° W.

39.40 Wash, 70 lks. wide, 3 ft. deep, drains S. 30° W.

40.11 The cor. of secs. 19, 20, 29 and 30, monumented by a malpais stone, 20x7x6 ins., set 9 ins. in the ground, marked with 5 notches on the east face, 2 notches on the south face, T6S on the NE., and R27E on the SE.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap marked

T6SR27E  
S19 | S20  
S30 | S29  
1960

Deposit the original cor. stone alongside iron post.

There are no other suitable accessories available.

Land, gently rolling.  
Soil, gravelly clay.  
Undergrowth, creosote brush, catclaw, and palo verde.  
Timber, none.

From the cor. of secs. 20, 21, 28 and 29.

N. 89°55' W., bet. secs. 20 and 29.

Through scattered to medium undergrowth, over gently rolling, slight SW. slope.

11.05 Wash, 40 lks. wide, 8 ft. deep, drains SW.; desc. 20 ft.

29.35 Wash, 40 lks. wide, 10 ft. deep, drains S.; desc. 10 ft.

39.70 Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.

39.94 Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T6SR27E  
¼ S 20  
S 29  
1960

There are no other suitable accessories.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Dependent Resurvey, Portion, T6S, R27E, Arizona
40.15	Wash, 30 lks. wide, 4 ft. deep, drains S.; along S. slope; desc. 10 ft.
43.55	Wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.; desc. 10 ft.
56.15	Dirt road, bears N. 70° W. and S. 70° E.; desc. 10 ft.
66.45	Concrete dam 4 ft. high, 1 ft. wide, 3 chs. long, bears NW. and SE.
67.25	Gravelled road, bears NE. and SW.; desc. 10 ft.
72.75	Dirt road, bears N. and S.; desc. 10 ft.
79.35	Wash, 70 lks. wide, 3 ft. deep, drains S. 30° W.
79.88	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, gravelly clay. Undergrowth, creosote brush, catclaw, and palo verde. Timber, none.</p>
	N. 89°45' W., bet. secs. 19 and 30.
	Through scattered to medium undergrowth; over gently rolling land; desc. 10 ft.
8.70	Wash, 20 lks. wide, 1 ft. deep, drains SW.; desc. 10 ft.
20.00	Two prospect holes, each about 10x10x8 ft.; desc. 20 ft.
40.11	The ¼ sec. cor. of secs. 19 and 30, monumented by a malpais stone, 15x10x6 ins., set 6 ins. in the ground, marked ¼ on north face.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;">T6SR27E ¼ <math>\frac{S\ 19}{S\ 30}</math> 1960</p>
	Deposit the original cor. stone in mound around iron post.
	There are no other suitable accessories.
	S. 89°39' W., beginning new measurement.
	Continue over gentle SW. slope.
8.90	Wash, 50 lks. wide, 4 ft. deep, drains S. 20° W.

CHAINS		
22.80	Wash, 15 lks. wide, 2 ft. deep, drains SW.	
28.70	Wash, 10 lks. wide, 1 ft. deep, drains S.	
38.05	Wash, 10 lks. wide, 2 ft. deep, drains S.	
38.50	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the township, monumented by an iron post, 2½ ins. diam., set, marked and witnessed as described in the official record.	
	Land, rolling. Soil, gravelly clay. Undergrowth, creosote brush, catclaw, palo verde, and cacti. Timber, none.	
	From the cor. of secs. 19, 20, 29 and 30.	
	N. 0°04' E., bet. secs. 19 and 20.	
	Through scattered to medium undergrowth, over gently rolling, slight SW. slope; asc. 10 ft.	
8.85	Dirt road, bears NW. and S.	
9.70	Wash, 10 lks. wide, 2 ft. deep, drains SW.	
11.90	Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.; asc. 50 ft.	
40.07	The ¼ sec. cor. of secs. 19 and 20, monumented by a malpais stone, 10x10x5 ins., set 6 ins. in the ground, marked ¼ on north face.	
	At the cor. point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.	
	T6SR27E ¼ S19 S20 1960	
	Deposit the original cor. stone in mound around iron post.	
	There are no other suitable accessories.	
	N. 0°02' W., beginning new measurement.	
	Continue along gentle SW. slope; asc. 70 ft.	
26.70	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 20 ft.	
33.00	Wash, 15 lks. wide, 1 ft. deep, drains SW.; asc. 75 ft.	
39.98	The cor. of secs. 17, 18, 19 and 20, monumented by a malpais stone, 15x12x10 ins., set 6 ins. in the ground, marked with 5 notches on the east edge, 3 notches on the south edge, T6S on the NE. face, and R27E on the SE. face.	
	At the cor. point	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Dependent Resurvey, Portion, T6S, R27E, Arizona
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E S18   S17 S19   S20 1960</p> <p>Deposit the original cor. stone in mound around iron post.</p> <p>There are no other suitable accessories.</p> <p>Land, gently rolling. Soil, gravelly clay. Undergrowth, creosote brush, catclaw, palo verde and cacti. Timber, none.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°51' W., bet. secs. 17 and 20.</p> <p>Through scattered to medium undergrowth, over rolling land, draining S.; desc. 10 ft.</p> <p>8.30 Dirt road, bears NE. and SW.; desc. 40 ft.</p> <p>25.90 Wash, 25 lks. wide, 2 ft. deep, drains S. 20° W.</p> <p>32.25 Wash, 80 lks. wide, 6 ft. deep, drains S. 20° W.; asc. 10 ft.</p> <p>36.55 Wash, 10 lks. wide, 2 ft. deep, drains S.</p> <p>39.73 The ¼ sec. cor. of secs. 17 and 20, monumented by a malpais stone, 18x10x8 ins., set 10 ins. in the ground, marked ¼ on north face.</p> <p>There is a mound of stone, N. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E ¼ S 17 S 20 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>There are no other suitable accessories.</p> <hr/> <p>S. 89°58' W., beginning new measurement.</p> <p>Continue over gently rolling land, draining S.; desc. 30 ft.</p>

## CHAINS

- 8.30 Wash, 10 lks. wide, 3 ft. deep, drains SW.
- 13.50 Wash, 20 lks. wide, 4 ft. deep, drains SE.
- 15.80 Dirt road, bears N. and S.; asc. 10 ft.
- 21.40 Dirt road, bears N. and SE.
- 22.60 Wash, 30 lks. wide, 8 ft. deep, drains S.; asc. 50 ft.
- 35.50 Spur, slopes S. 60° E.; desc. 20 ft.
- 40.16 The cor. of secs. 17, 18, 19 and 20.
- Land, gently rolling.  
Soil, gravelly clay.  
Undergrowth, creosote brush, catclaw, and palo verde.  
Timber, none.
- 
- S. 89°40' W., bet. secs. 18 and 19.
- Through scattered to medium undergrowth, over rolling land; desc. 120 ft. over SW. slope.
- 12.10 Wash, 50 lks. wide, 4 ft. deep, drains SW. from the N.; desc. 50 ft. along rolling S. slope.
- 38.70 Wash, 50 lks. wide, 3 ft. deep, drains SE.; asc. 5. ft. over E. slope.
- 39.96 The  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, monumented by a malpais stone, 22x7x6 ins., set 8 ins. in the ground, marked  $\frac{1}{4}$  on north face.
- There is a mound of stone, N. of cor.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
- T6SR27E  
 $\frac{1}{4}$   $\frac{S\ 18}{S\ 19}$   
1960
- Deposit the original cor. stone in mound around iron post.
- There are no other suitable accessories.
- 
- N. 89°57' W., beginning new measurement
- Continue along gently rolling S. slope; asc. 10 ft.
- 4.30 Fence, barbed wire, bears N. and S.
- 6.60 Wash, 45 lks. wide 3 ft. deep, drains S. from NW.
- 14.35 Wash, 20 lks. wide, 3 ft. deep, drains S.
- 18.50 Track road, bears N. and S.
- 23.20 Wash, 20 lks. wide, 4 ft. deep, drains S.
- 38.66 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township, monumented by an iron post, 2 $\frac{1}{2}$  ins. diam., set, marked and witnessed as described in the official record.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Dependent Resurvey, Portion, T6S, R27E, Arizona
	<p>Land, gently rolling. Soil, gravelly clay. Undergrowth, creosote brush, palo verde, ocotillo, and cacti. Timber, none.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p>
	<p>N. 0°12' E., bet. secs. 17 and 18.</p>
	<p>Through scattered to medium undergrowth, over rolling land; asc. 210 ft. over SW. slope.</p>
10.30	<p>Slope changes, asc. 10 ft. along W. slope.</p>
12.60	<p>Top of ascent on NW. shoulder of knoll, on a spur projecting SE.; desc. 140 ft. over NE. slope.</p>
24.80	<p>Ravine, drains SE.; asc. 50 ft. over SE. slope.</p>
38.85	<p>Wash, 30 lks. wide, 3 ft. deep, drains SE. for 2 chs. thence S.; asc. 10 ft. over W. slope.</p>
40.35	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 18, monumented by a malpais stone, 20x12x12 ins., set 6 ins. in the ground, mkd. <math>\frac{1}{4}</math> on W. face.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 16 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>
	<p>T6S R27E <math>\frac{1}{4}</math> S18 S17 1960</p>
	<p>Deposit the original cor. stone in the mound of stone around iron post.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>_____</p>
	<p>N. 0°08' E., beginning new measurement.</p>
10.90	<p>Spur, slopes S. 15° E.; asc. 60 ft. along E. slope.</p>
22.20	<p>Small ravine, 30 lks. wide, 8 ft. deep, drains E.; asc. 70 ft. along E. slope.</p>
40.10	<p>The cor. of secs. 7, 8, 17 and 18, monumented by a malpais stone, 20x10x8 ins., set 12 ins. in the ground, mkd. with 5 notches on the east edge, 4 notches on the south edge, T6S on the northeast face and R27 on the southeast face.</p>
	<p>At the cor. point</p>

## CHAINS

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
 $\frac{S 7}{S 18} | \frac{S 8}{S 17}$   
 1960

Deposit the original cor. stone alongside iron post.

Land, rolling.

Soil, rocky, sandy clay.

Timber, none; undergrowth, palo verde, catclaw, creosotebush and cactus.

From the cor. of secs. 8, 9, 16 and 17, monumented by an iron post  $2\frac{1}{2}$  ins. diam., firmly set, mkd. and witnessed as described in the official record.

N.  $88^{\circ}56'$  W., bet. secs. 8 and 17.

Over mountainous land, through scattered undergrowth.

Asc. 30 ft. over E. slope.

11.80 Spur, slopes S.; desc. 290 ft. along steep S. slope.

35.76 Intersect line 4-1 of M.S. No. 2585, Pearson's lode at a point from which Cor. No. 1 bears N.  $41^{\circ}41'$  E., 6.53 chs. dist., and Cor. No. 4 bears S.  $41^{\circ}41'$  W., 16.20 chs. dist.

37.10 Wash, 20 lks. wide, 2 ft. deep, drains SW.; asc. 10 ft. over SE. slope.

39.59 The  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, monumented by a malpais stone, 20x14x8 ins., set 8 ins. in the ground, mkd.  $\frac{1}{4}$  on north face, with a mound of stone to N.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
 $\frac{1}{4} \frac{S 8}{S 17}$   
 1960

Deposit the original cor. stone alongside iron post.

From this cor., Corner No. 1 of "Everybody's" mining claim bears N.  $52^{\circ}37'$  W., 1.51 chs. dist.

Note: These mining claims are shown as being in secs. 17 and 20 on plat of Mineral Survey No. 2585.

N.  $89^{\circ}54'$  W., beginning new measurement.

Desc. 280 ft. over SW. slope.

15.30 Wash, 20 lks. wide, 3 ft. deep, drains SW.; desc. 160 ft. over SW. slope.

17.74 Intersect line 2-3 of M.S. No. 2585, Everybody's lode at a point from which Cor. No. 2 bears N.  $54^{\circ}$  E., 15.21 chs. dist. and Cor. No. 3 bears S.  $54^{\circ}$  W., 7.52 chs. dist.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

CHAINS	Dependent Resurvey, Portion, T6S, R27E, Arizona
34.30	Wash, 20 lks. wide, 4 ft. deep, drains SW.
36.10	Wash, 20 lks. wide, 3 ft. deep, drains S. about 2½ chs. to junction with a wash from the NE.; asc. 40 ft. over E. slope.
39.89	The cor. of secs. 7, 8, 17 and 18.  Land, mountainous. Soil, rocky, sandy clay. Timber, none; undergrowth, creosotebrush, catclaw and cactus.
6.90	S. 89°39' W., bet. secs. 7 and 18.  Over rolling land, through scattered undergrowth.  Asc. 170 ft. over E. slope.  Spur, projects S. 30° W.; desc. 350 ft. over steep rocky NW. slope.
39.35	Point selected for the witness ¼ sec. cor. of sec. 7.  Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.  T6SR27E W ¼ S 7 C 1960
40.00	True point for the ¼ sec. cor. of sec. 7, at 40.00 chs. in westing from the cor. of secs. 7, 8, 17 and 18, falls in wash, 80 lks. wide, 3 ft. deep, where the monument cannot be perpetuated. (drains SW.)
40.47	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.  At the cor. point  Set the iron post, 30 ins. long, 2½ ins. diam, 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.  T6SR27E ¼ S 18 1960
54.05	This cor. now functions as the cor. of sec. 18 only.  Desc. 40 ft. over rolling SW. slope.  Dirt road, bears NE. and SW.
58.15	Wash, 50 lks. wide, 3 ft. deep, drains SW.; asc. 20 ft. over gently rolling land.

CHAINS	
78.95	<p>The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township, monumented by an iron post, 30 ins. long, 2½ ins. diam., set, marked and witnessed as described in the official record.</p> <p>Land, rolling. Soil, rocky sandy clay. Undergrowth, creosote bush, catclaw, palo verde and cacti. Timber, none.</p>
<p>Completion Survey of the Subdivisional Lines T6S, R27E, Gila and Salt River Meridian, Arizona</p>	
<p>From the cor. of secs. 25, 26, 35 and 36.</p>	
<p>North, bet. secs. 25 and 26, with the establishment of a Sectional Guide Meridian.</p>	
<p>Over rolling land, through scattered undergrowth.</p>	
1.10	<p>Wash, 10 lks. wide, 3 ft. deep, drains SW., asc. 110 ft. along SE. slope.</p>
10.20	<p>Spur, slopes SW.; desc. 110 ft. along W. slope.</p>
18.00	<p>Ravine, 50 lks. wide, drains W.; asc. 20 ft. over S. slope.</p>
20.00	<p>Spur, slopes W.; desc. 40 ft. along NW. slope.</p>
25.60	<p>Thence over series of small washes draining W.</p>
33.50	<p>Main wash, 30 lks. wide, 5 ft. deep, drains SW.; asc. 40 ft. over S. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 25 and 26.</p>
<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>	
<p>T6SR27E ¼ S26   S25 1960</p>	
<p>Asc. 40 ft. over SW. slope.</p>	
47.20	<p>Wash, 40 lks. wide, 6 ft. deep, drains SW.; asc. 200 ft. over steep boulder-strewn SE. slope.</p>
54.20	<p>Bulldozed road, bears NE. and SW.; asc. 80 ft. over SE. slope.</p>
57.80	<p>Same road, bears E. and W.; asc. 120 ft. along SE. slope.</p>
65.00	<p>Top of ascent on E. side of spur projecting S.; thence along steep E. slope.</p>
79.35	<p>Intersect the Sectional Correction Line; point for the cor. of secs. 23, 24, 25 and 26.</p>
<p>At the point of intersection</p>	
<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>	



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions, T6S, R27E, Arizona

T6SR27E  
S23 | S24  
S26 | S25  
1960

Land, rolling.  
Soil, rocky gravelly sandy clay.  
Timber, none; undergrowth, creosotebush, catclaw and cacti.

From the true point for the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township, as described in the official record.

West, bet. secs. 24 and 25, with the establishment of a Sectional Correction Line.

Over nearly level land, through medium dense creosotebush, catclaw and cacti.

14.00 Wash, 2.20 chs. wide, 5 ft. deep, drains SW.; asc. 180 ft. over steep rocky S. slope.

39.86 Point for the  $\frac{1}{4}$  sec. cor. of secs. 24 and 25.

Set the iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
 $\frac{1}{4}$  S 24  
S 25  
1960

Asc. 20 ft. along S. slope.

45.90 Top of ascent on S. side of spur which projects E.; desc. 50 ft. along S. slope.

53.80 Wash, 30 lks. wide, 6 ft. deep, drains S.; asc. 340 ft. over steep boulder-strewn E. slope.

68.10 Ridge, bears N.  $30^\circ$  W. and S.  $30^\circ$  E.; desc. 180 ft. over steep boulder-strewn SW. slope.

79.50 Wash, 10 lks. wide, 2 ft. deep, drains S.  $30^\circ$  E.

79.72 The cor. of secs. 23, 24, 25 and 26.

Land, nearly level to rolling.  
Soil, rocky gravelly sandy clay.  
Timber, none; undergrowth, creosotebush, catclaw and cacti.

North, bet. secs. 23 and 24, with the Sectional Guide Meridian.

Over mountainous land, through scattered creosote and catclaw.

CHAINS		
	Asc. 360 ft. over steep S. slope.	
16.40	Spur, slopes S. 40° E.; asc. 160 ft. along SE. slope.	
31.80	Spur, slopes S. 65° E.; desc. 30 ft. along E. slope.	
35.70	Ravine, drains E.; asc. 60 ft. over SE. slope.	
40.00	Point for the 1/2 sec. cor. of secs. 23 and 24.  Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.  T6SR27E 1/2 S23 S24 1960	
	Asc. 20 ft. along SE. slope.	
41.60	Spur, slopes NE.; desc. 320 ft. over steep, boulder-strewn N. slope.	
57.50	Wash, 50 lks. wide, 3 ft. deep, drains E.; asc. 400 ft. over steep boulder-strewn N. slope.	
76.50	Ridge, bears S. 55° W. and N. 55° E.; desc. 70 ft. over steep NW. slope.	
80.00	Point for the cor. of secs. 13, 14, 23 and 24.  Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock and in a mound of stone to top, with brass cap mkd.  T6SR27E S14 S13 S23 S24 1960	
	Land, mountainous. Soil gravelly sandy clay. Timber, none; undergrowth, creosotebush, catclaw and cacti.	
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, which is marked by an iron post, 2 1/2 ins. diam., set, marked and witnessed as described in the official record.  N. 89°57' W., bet. secs. 13 and 24.  Over rolling land, through scattered undergrowth.	
.50	Track road, bears N. and S.; desc. 30 ft. over W. slope.	
3.10	Wash, 10 lks. wide, 2 ft. deep, drains S.; asc. 50 ft. over E. slope.	
10.80	Spur, slopes S.; desc. 20 ft. over W. slope.	
14.70	Wash, 30 lks. wide, 3 ft. deep, drains S. 20° E.; asc. 160 ft. over NE. slope.	
26.00	Spur, sloping SE.; desc. 60 ft. over SW. slope.	
35.20	Wash, 40 lks. wide, 4 ft. deep, drains S. 40° E.; asc. 100 ft. over E. slope on N. side of spur.	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

X chains	Completion Survey, Subdivisions, T6S, R27E, Arizona
39.81	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E <math>\frac{1}{4}</math> <math>\frac{S\ 13}{S\ 24}</math> 1960</p> <p>Asc. 465 ft. along steep N. slope of spur sloping E.</p>
67.20	Crest of spur; asc. 100 ft. along steep S. slope.
72.90	Ridge, bears S. $60^\circ$ W. and N. $35^\circ$ E.; desc. 140 ft. over ledgy NW. slope.
79.62	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling and mountainous. Soil, rocky sandy clay. Timber, none; undergrowth, creosotebrush, catclaw, ocotillo and cacti.</p> <hr/> <p>North, bet. secs. 13 and 14, with the establishment of the Sectional Guide Meridian.</p> <p>Over mountainous land, through scattered undergrowth.</p> <p>By triangulation desc. about 500 ft. over ledgy NW. slope.</p>
27.50	Wash, 60 lks. wide, 4 ft. deep, drains E.; asc. about 100 ft. along SE. slope.
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E <math>\frac{1}{4}</math> S14   S13 1960</p> <p>Asc. about 20 ft. along SE. slope.</p>
43.50	Spur, slopes N. $50^\circ$ E.; desc. about 100 ft. over N. slope.
48.50	Wash, 30 lks. wide, 3 ft. deep, drains E.; asc. about 500 ft. over steep S. slope.
70.00	End of triangulation on crest of mountain; desc. 140 feet over steep N. slope.
79.21	Intersect the S. bdy. of sec. 12, point for the C.C. of secs. 13 and 14.

~~XXXX~~  
chains

At the point of intersection

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
S12  
-----  
S14 | S13  
CC  
1960

From this cor. the SW. cor. of sec. 12, previously described, bears N. 89°54' W., 1.85 chs. dist.

Land, mountainous.  
Soil, rocky, sandy clay.  
Timber, none; undergrowth, creosotebush, catclaw, ocotillo and cacti.

The point for the N. ¼ sec. cor. of sec. 13 is at mid-point and on the N. bdy. of the sec.

At the cor. point

Set the iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
-----  
¼ S13  
1960

From this cor. the ¼ sec. cor. of sec. 12, previously described, bears S. 89°03' W., 1.64 chs. dist.

From the cor. of secs. 23, 24, 25 and 26.

West, between secs. 23 and 26, with the continuation of the Sectional Correction Line.

Over mountainous land, through scattered undergrowth.

Asc. 110 ft. over steep E. slope.

6.80 Spur, slopes S.; thence by triangulation desc. about 360 ft. over steep ledgy W. slope.

30.00 Wash, 40 lks. wide, 3 ft. deep, drains S.; asc. about 150 ft. over E. slope.

38.00 Track road, bears N. and S. on a spur which slopes S.

39.84 Point for the ¼ sec. cor. of secs. 23 and 26.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
¼  $\frac{S\ 23}{S\ 26}$   
1960

Asc. about 100 ft. along SE. slope.

53.00 Wash, 20 lks. wide, 3 ft. deep, drains SE.; asc. about 520 ft. along ledgy SE. slope.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Completion Survey, Subdivisions, T6S, R27E, Arizona
79.68	<p>End of triangulation at the cor. of secs. 22, 23, 26 and 27.</p> <p>Land, mountainous. Soil, rocky, sandy clay. Timber, none; undergrowth, creosotebush, ocotillo, catclaw and cacti.</p>
	<p>N. 0°01' W. bet. secs. 22 and 23.</p> <p>Over mountainous land, through scattered undergrowth.</p> <p>Asc. 280 ft. over ledgy S. slope.</p>
6.30	<p>Spur, projects E. from crest of Gila Mountains, approximately 10.00 chs. W.; desc. 100 ft. over N. slope.</p>
11.30	<p>Ravine, drains E.; asc. 100 ft. along SE. slope.</p>
18.70	<p>Spur, slopes E. from Gila Mountains; desc. 50 ft. along E. slope.</p>
23.20	<p>Ravine, drains E.; desc. 30 ft. along steep E. slope.</p>
38.00	<p>Spur, slopes NE.; desc. 20 ft. over NW. slope.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6SR27E <math>\frac{1}{4}</math> S22   S23 1960</p>
	<p>Desc. 160 ft. over steep N. slope.</p>
45.00	<p>Base of steep slope, bears NE. and SW.; desc. 150 ft. over rolling N. slope.</p>
63.20	<p>Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. 150 ft. over S. slope.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.</p>
	<p style="text-align: center;">T6SR27E S15   S14 S22   S23 1960</p> <p>Land, mountainous and rolling. Soil, rocky, sandy clay. Timber, none; undergrowth, creosotebush, ocotillo, catclaw and cacti.</p>

CHAINS	
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°56' W., bet. secs. 14 and 23.</p> <p>Over mountainous land, through scattered undergrowth.</p> <p>Desc. 200 ft. over ledgy NW. slope.</p>
14.70	Ravine, drains N.; asc. 20 ft. over E. slope.
18.70	Spur, slopes N.; desc. 60 ft. over W. slope.
27.10	Wash, 30 lks. wide, 3 ft. deep, drains NE. approximately 2.50 chs. to stock pond.
32.00	Same wash, drains SE.; asc. 10 ft. over NE. slope.
32.90	Jeep trail, bears NW. and SE.; asc. 40 ft. over SE. slope.
35.00	Spur, slopes NE.; desc. 20 ft. over NW. slope.
39.88	<p>Point for the ¼ sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E  <math>\frac{1}{4} \begin{array}{l} S \ 14 \\ S \ 23 \end{array}</math>            1960</p> <p>Desc. 20 ft. over NW. slope.</p>
43.20	Jeep trail bears NE. and SW.; desc. 20 ft. over NW. slope.
46.40	Wash, 40 lks. wide, 3 ft. deep, drains NE.; thence along bottom.
50.00	Leave bottom; asc. 40 ft. over NE. slope.
53.60	Jeep road, NW. and S. 70° E.; asc. 20 ft. over E. slope.
55.30	Spur, slopes N.; desc. 20 ft. over W. slope.
57.70	Jeep road, bears NE. and SW.; desc. 20 ft. over W. slope.
60.30	Wash, 50 lks. wide, 4 ft. deep, drains NE. from stock pond, approximately 2.00 chs. SW.; asc. 180 ft. along SE. slope.
79.76	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, mountainous.            Soil, rocky, sandy clay.            Timber, none; undergrowth, creosotebush, catclaw, ocotillo and cacti.</p> <hr/> <p>West, bet. secs. 15 and 22.</p> <p>Over mountainous land, through scattered undergrowth.</p> <p>Desc. 20 ft. along S. slope.</p>
13.10	Small wash, near head, drains S. 20° W.; asc. 70 ft. over SE. slope.
19.50	Ravine, drains S. 60° E.; asc. 150 ft. over E. slope.

CHAINS	
24.90	Spur, sloping NE. from top of mountain approximately 5.00 chs. SW.; desc. 140 ft. over NW. slope.
39.97	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6SR27E  <math>\frac{1}{4}</math> <math>\frac{S\ 15}{S\ 22}</math>                      1960</p>
	Desc. 80 ft. over NW. slope.
52.70	Wash, 20 lks. wide, 2 ft. deep, drains NE., thence along bottom land.
56.30	Jeep trail, bears NE. and SW., asc. 100 ft. over E. slope.
65.50	Spur, slopes S.; desc. 100 ft. along steep SW. slope.
79.94	Point for the C.C. of secs. 15 and 22 on the E. bdy. of sec. 21.
	At the cor. point
	<p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6SR27E                      S21 <math>\frac{S15\ C}{S22\ C}</math>                      1960</p>
	<p>From this cor. the cor. of secs. 16 and 21 bears N. <math>0^{\circ}05'</math> E., 0.89 chs. dist.</p>
	<p>Land, mountainous.                      Soil, rocky, sandy clay.                      Timber, none; undergrowth, creosote bush, ocotillo, catclaw and cacti.</p>
	<p>The point for the W. <math>\frac{1}{4}</math> sec. cor. of sec. 22 is 40.00 chs. in southing from closing cor. of secs. 15 and 22 and on the line bet. secs. 21 and 22.</p>
	At the cor. point
	<p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p>

CHAINS	
	<p>T6SR27E  <math>\frac{1}{2}</math>                      S22                      1960</p> <p>From this cor. the E. <math>\frac{1}{2}</math> sec. cor. of sec. 21, previously described, bears N. 0°02' E., 1.75 chs. dist.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.                      N. 0°01' W., bet. secs. 14 and 15.                      Over mountainous land, through scattered undergrowth.                      Asc. 250 ft. over steep S. slope.</p>
10.60	Top of hill, by triangulation desc. about 400 ft. over steep N. slope.
27.50	Wash, 20 lks. wide, 2 ft. deep, drains east. There is a jeep road along the bottom of the wash, bears E. and W.; asc. about 200 ft. over steep S. slope.
36.85	End of triangulation; asc. 90 ft. over steep S. slope.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 14 and 15.  Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	<p>T6SR27E  <math>\frac{1}{2}</math>                      S15   S14                      1960</p>
	Asc. 110 ft. over ledgy S. slope.
44.70	Ridge, bears NW. and E.; thence by triangulation desc. about 200 ft. over steep N. slope.
55.00	Wash, 20 lks. wide, 2 ft. deep, drains E.; asc. about 100 ft. over S. slope.
60.00	Spur, slopes E.; desc. about 100 ft. over N. slope.
66.00	Wash, 20 lks. wide, 2 ft. deep, drains E.; asc. about 220 ft. over steep S. slope.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.  Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.



400  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion Survey, Subdivisions, T6S, R27E, Arizona</p> <hr/> <p style="text-align: center;">T6SR27E S10   S11 S15   S14 1960</p> <p>Land, mountainous. Soil, rocky, sandy clay. Timber, none; undergrowth, creosote bush, catclaw, ocotillo and cacti.</p> <hr/> <p>East, bet. secs. 11 and 14.</p> <p>Over mountainous land; through scattered undergrowth.</p> <p>Desc. 380 ft. along steep boulder-strewn SE. slope.</p> <p>25.00 Ravine, drains S.; asc. 220 ft. over steep, boulder-strewn SW. slope.</p> <p>37.00 Spur, slopes SE.; desc. 30 ft. over steep NE. slope.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14, 40.00 chs. in easting from the cor. of secs. 10, 11, 14 and 15.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E <math>\frac{1}{4}</math> <math>\frac{S 11}{S 14}</math> 1960</p> <p>Desc. 160 ft. over steep NE. slope.</p> <p>53.00 Slope changes; desc. 200 ft. along steep S. slope.</p> <p>67.50 Wash, 20 lks. wide, 3 ft. deep, drains N. <math>20^\circ</math> E.</p> <p>67.50 Fence, barbed wire, bears N. <math>85^\circ</math> W. and S. <math>85^\circ</math> E.; asc. 160 ft. along NW. slope.</p> <p>77.80 Point for the C.C. of secs. 11 and 14 on the W. bdy. of sec. 12.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T6SR27E S11 C   S 12 S14 C   1960</p> <p>From this cor. the SW. cor. of sec. 12, previously described, bears S. <math>0^\circ 36'</math> W., 68 lks. dist.</p> <p>Land, mountainous. Soil, rocky, sandy clay. Timber, none; undergrowth, creosote bush, catclaw, ocotillo and cacti.</p> <hr/>

## CHAINS

From the cor. of secs. 10, 11, 14 and 15.

N.  $0^{\circ}01'$  W., bet. secs. 10 and 11.

Over mountainous land, through scattered undergrowth.

Asc. 40 ft. over SE. slope.

2.00 Ridge, bears W. and NE., thence by triangulation;  
desc. about 360 ft. over steep NW. slope.

19.00 Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc.  
about 160 ft. over SE. slope.

39.30 End of triangulation on spur, sloping NE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 10 and 11.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins.  
in the ground to solid rock and in a mound of stone  
to top, with brass cap mkd.

T6SR27E

$\frac{1}{4}$   
S10|S11  
1960

Desc. 230 ft. over NW. slope.

55.00 Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. 50 ft.  
over S. slope.

58.50 Fence, barbed wire, bears NE. and SW.

60.60 Spur, slopes E.; desc. 20 ft. over N. slope.

64.70 Bulldozed trail, bears NW. and E.; desc. 20 ft. over  
N. slope.

66.20 Wash, 40 lks. wide, 3 ft. deep, drains N.  $80^{\circ}$  E.;  
asc. 120 ft. over S. slope.

79.91 Point for the C.C. of secs. 10 and 11, on the S. bdy.  
of sec. 2.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T6SR27E

S2  
S10|S11

CC  
1960

From this cor. the cor. of secs. 2 and 3, previously  
described, bears S.  $89^{\circ}54'$  W., 1.84 chs. dist.

Land, mountainous.

Soil, rocky, sandy clay.

Timber, none; undergrowth, creosotebush, catclaw,  
ocotillo and cacti.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 11 is 40.00  
chs. in easting from the closing cor. of secs. 10 and  
11 and on the line bet. secs. 2 and 11.

At the cor. point

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions, T6S, R27E, Arizona

Set the iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

½ S11  
T6SR27E  
1961

From this cor., the S. ¼ sec. cor. of sec. 2, previously described, bears N. 89°59' W., 1.45 chs. dist.

From the cor. of secs. 10, 11, 14 and 15.

West, bet. secs. 10 and 15.

Over mountainous land, through scattered undergrowth.

Asc. 20 ft. along S. slope of ridge, bearing E. and W.

14.00 Base of steep slope, bears NE. and SW.; asc. 400 ft. over boulder-strewn, steep SE. slope.

35.50 Spur, slopes SE. from mountain top, approximately 15.00 chs. NW.; desc. 100 ft. over boulder-strewn S. slope.

40.00 Point for the ¼ sec. cor. of secs. 10 and 15.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E  
¼  $\frac{S\ 10}{S\ 15}$   
1961

Desc. 40 ft. along boulder-strewn S. slope.

53.00 Wash, near head, drains S.; asc. 250 ft. over steep boulder-strewn SE. slope.

64.00 Ridge, bears NE. and SW.; desc. 290 ft. over NW. slope.

77.00 Slope is broken by ledges, bearing N. and S.; desc. 150 ft. over W. facing ledges.

80.00 Point for the C.C. of secs. 10 and 15 on the W. bdy. of sec. 16, falls on a ledge where it is impracticable to set a monument.

At the point selected for the W.C., secs. 10 and 15, S. 0°02' E., 0.26 chs. dist. from the C.C.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

## CHAINS

T6SR27E

WC

S16 |  $\frac{S10 \ C}{S15 \ C}$ 

1960

From the true point for the closing cor. of secs. 10 and 15, the cor. of secs. 9, 10, 15 and 16, monumented by an iron post, 2½ ins. diam., set, marked and witnessed as described in the official record, bears N. 0°02' W., 0.79 chs. dist.

This cor. now functions as the cor. of secs. 9 and 16 only, and the brass cap is therefore remarked

T6SR27E

S9 | S10  
S16 |

1955

1960

Land, mountainous.  
Soil, rocky, sandy clay.  
Timber, none; undergrowth, creosote bush, palo verde, catclaw and cacti.

The point for the W. ¼ sec. cor. of sec. 15 is at mid-point and on the W. bdy. of the section.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

¼ |  
S15 |

1961

From this cor. the ¼ sec. cor. of secs. 15 and 16, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears N. 0°02' W., 0.84 chs. dist.

This cor. now functions as the cor. of sec. 16 only, and the brass cap is therefore remarked

T6SR27E

¼ |  
S16 |

1955

1961

From the cor. of secs. 9 and 16.

N. 0°02' W., bet. secs. 9 and 10.

Over mountainous land, through scattered undergrowth.

Asc. 20 ft. along W. facing ledges.

7.70 Top of ascent; desc. 240 ft. over steep, boulder-strewn NW. slope.

22.20 Wash, near head, drains N. 30° E.; asc. 40 ft. along SE. slope.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion Survey, Subdivisions, T6S, R27E, Arizona</p> <hr/>
39.21	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 10 only; 40.00 chs. in northing from the closing cor. of secs. 10 and 15.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E</p> <p>  <math>\frac{1}{4}</math></p> <p>  S10</p> <p>1960</p> </div>
40.00	<p>True point for the <math>\frac{1}{4}</math> sec. cor. of sec. 9 falls in gravelled road which is being rebuilt; considered unsafe for cor. monument.</p>
41.00	<p>Point selected for the witness <math>\frac{1}{4}</math> sec. cor. of sec. 9.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E</p> <p>  <math>\frac{1}{4}</math></p> <p>  S 9</p> <p>WC</p> <p>1960</p> </div>
	<p>Asc. 20 ft. over SE. slope.</p>
45.00	<p>Spur, slopes NE.; desc. 20 ft. over NW. slope.</p>
47.60	<p>Fence, bears N. <math>45^\circ</math> E., and S. <math>45^\circ</math> W.; desc. 20 ft. over NW. slope.</p>
51.30	<p>Wash, 1.50 chs. wide, 4 ft. deep, drains E.; asc. 30 ft. over SE. slope.</p>
54.00	<p>Bulldozed road, bears E. and W.; asc. 20 ft. over SE. slope.</p>
60.50	<p>Spur, slopes E.; desc. 60 ft. over N. slope.</p>
67.80	<p>Wash, 2.00 chs. wide, 4 ft. deep, drains E.; stock pond, bears W. approximately 4.00 chs.; asc. 40 ft. over S. slope.</p>
75.10	<p>Fence, barbed wire, bears S. <math>35^\circ</math> E. and N. <math>35^\circ</math> W.; asc. 10 ft. over S. slope.</p>
79.35	<p>Point for the C.C. of secs. 9 and 10 on the S. bdy. of sec. 3.</p> <p>Set an iron post 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6SR27E</p> <p>S3</p> <hr/> <p>S 9   S10</p> <p>CC</p> <p>1960</p> </div>

## CHAINS

From this cor. the cor. of secs. 3 and 4, previously described, bears West, 1.96 dist.

Land, mountainous.

Soil, rocky, sandy clay.

Timber, none; undergrowth, creosotebush, catclaw and cactus.

The N.  $\frac{1}{4}$  sec. cor. of sec. 10 is at mid-point bet. the closing cors. of secs. 9 and 10 and 10 and 11, and on the line bet. secs. 3 and 10.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S10  
T6SR27E  
1961

From this cor. the S.  $\frac{1}{4}$  sec. cor. of sec. 3, previously described, bears West, 1.95 chs. dist.

The N.  $\frac{1}{4}$  sec. cor. of sec. 9 is 40.00 chs. in westing from the closing cor. of secs. 9 and 10 and on the line bet. secs. 4 and 9.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S 9  
T6SR27E  
1960

From this cor. the S.  $\frac{1}{4}$  sec. cor. of sec. 4, previously described, bears N.  $89^{\circ}53'$  W., 1.43 chs. dist.

From the cor. of secs. 7, 8, 17 and 18.

N.  $0^{\circ}03'$  W., bet. secs. 7 and 8.

Over mountainous land, through scattered undergrowth.

Desc. 10 ft. along E. slope.

- 8.10 Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 80 ft. along SE. slope.
- 15.70 Fence, barbed wire, bears N.  $30^{\circ}$  E. and S.  $30^{\circ}$  W.; asc. 80 ft. along SE. slope.
- 19.30 Spur, slopes S.  $30^{\circ}$  W.; desc. 110 ft. along NW. slope.
- 27.35 Wash, 100 links wide, 10 ft. deep, drains S.  $40^{\circ}$  W.; asc. 10 ft. over S. slope.
- 31.00 Enter wash, 20 lks. wide, drains S.  $5^{\circ}$  E.; thence in bottom of wash.
- 33.00 Leave bottom; asc. 110 ft. over SE. slope.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Completion Survey, Subdivisions, T6S, R27E, Arizona
36.20	Spur, slopes S. 40° W.; desc. 20 ft. over NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 7 and 8.  Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;">                     T6SR27E                      ¼                      S 7   S 8                      1960                 </div>
	Desc. 40 ft. along NW. slope.
45.00	Small wash, near head, drains W.; asc. 50 ft. along S. slope.
48.00	Spur, slopes SW.; desc. 20 ft. along W. slope.
51.00	Small wash near head, drains SW.; asc. 50 ft. over S. slope.
52.60	Spur, slopes W.; desc. 20 ft. along W. slope.
56.88	Intersect line 2-3 of M.S. No. 4475, Copper Hill No. 7 lode, at a point from which Cor. No. 3 bears S. 79°24' 06" W., 2.67 chs. dist., and Cor. No. 2 bears N. 79° 24'06" E., 6.39 chs. dist.
60.00	Wash, 20 lks. wide, 3 ft. deep, drains W.; 20 ft. over SE. slope.
62.50	Spur, slopes SW.; thence along NW. slope.
67.70	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 140 ft. over SE. slope.
73.50	Spur, slopes SW.
73.60	Road, bears NE. and SW.; desc. 20 ft. along NW. slope.
78.00	Wash, 10 lks. wide, 2 ft. deep, drains S. 70° W.; asc. 30 ft. over S. slope.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.  Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;">                     T6SR27E                      S 6   S 5                      S 7   S 8                      1960                 </div>
	From this cor. Cor. No. 4, Survey No. 4457, Copper Hill No. 1 Lode, identical with Cor. No. 1, Survey No. 4454, Consolidated Metals No. 24 Lode and Cor. No. 1, Survey No. 4475, Copper Hill No. 7 Lode, bears N. 79°06' E., 2.13 chs. dist.

## CHAINS

Land, mountainous.  
Soil, rocky, sandy clay.  
Timber, none; undergrowth, creosote bush, catclaw  
and cacti.

East, bet. secs. 5 and 8.

Over mountainous land, through scattered undergrowth.

By triangulation; desc. 20 ft. along SE. slope.

2.50 Shallow wash, drains SW.; asc. about 240 ft. over  
steep SW. slope.

23.00 Bulldozed road, bears NW. and SE. approximately 1.00  
chain to junction with graded road; asc. about 650 ft.  
over ledgy SW. slope.

35.90 End of triangulation on ridge, which bears NW. and  
drops sharply SE.; desc. 150 ft. over steep NE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 8, 40 chs.  
in easting from the cor. of secs. 5, 6, 7 and 8.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins.  
in the ground to solid rock and in a mound of stone  
to top, with brass cap mkd.

T6SR27E

$$\frac{1}{4} \frac{S \ 5}{S \ 8}$$

1960

By triangulation desc. about 360 ft. over steep N.  
slope on N. side of spur sloping E.

56.00 Graded road, bears N.  $35^\circ$  W. and S.  $35^\circ$  E.; desc.  
about 150 ft. over NE. slope.

60.00 Wash, 30 lks. wide, 3 ft. deep, drains S.  $40^\circ$  E.; asc.  
about 120 ft. along steep SW. slope.

78.35 Point for the C.C. of secs. 5 and 8 on the line bet.  
secs. 4 and 5.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins.  
in the ground to solid rock and in a mound of stone  
to top, with brass cap mkd.

T6SR27E

$$\frac{S5 \ C}{S8 \ C} S4$$

1960

From this cor. the cor. of secs. 4 and 9, previously  
described, bears S.  $0^\circ 46'$  E., 1.07 chs. dist.

Land, mountainous.  
Soil, rocky, sandy clay.  
Timber, none; undergrowth, creosote bush, catclaw  
and cacti.

The point for the E.  $\frac{1}{4}$  sec. cor. of sec. 5 is 40.00 chs.  
in northing and on the line bet. secs. 4 and 5.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins.  
in the ground to solid rock and in a mound of stone to  
top, with brass cap mkd.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions, T6S, R27E, Arizona

T6SR27E

$\frac{1}{4}$  |  
S 5 |  
1960

From this cor. the W.  $\frac{1}{4}$  sec. cor. of sec. 4, previously described, bears S.  $0^{\circ}11'$  W., 1.23 chs. dist.

From the cor. of secs. 5, 6, 7 and 8.

S.  $89^{\circ}41'$  W., bet. secs. 6 and 7.

Over mountainous land, through scattered undergrowth.

Desc. 30 ft. along SE. slope.

- 8.50 Spur, slopes SW.; desc. 120 ft. over NW. slope.
- 13.70 Wash, 20 lks. wide, 2 ft. deep, drains S.; asc. 20 ft. over E. slope.
- 14.80 Bulldozed road, bears N. and S. along spur, which slopes S.; desc. 20 ft. over W. slope.
- 17.70 Wash, near head, drains S.; jeep trail follows along bottom of wash bearing N. and S.; asc. 40 ft. over E. slope.
- 22.50 Spur, slopes S.; desc. 100 ft. over W. slope.
- 29.30 Wash, 20 lks. wide, 2 ft. deep, drains S.  $25^{\circ}$  E.; asc. 80 ft. over E. slope.
- 34.80 Jeep trail, bears NW. and SE.
- 35.00 Spur, slopes S.  $30^{\circ}$  E.; desc. 70 ft. over W. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T6SR27E

$\frac{1}{4}$   $\frac{S\ 6}{S\ 7}$   
1960

Desc. 80 ft. over rocky, steep W. slope.

- 41.40 Wash, 50 lks. wide, 3 ft. deep, drains S.; asc. 20 ft. over E. slope.
- 43.00 Spur, slopes S.; desc. 30 ft. over W. slope.
- 45.40 Wash, 30 lks. wide, 2 ft. deep, drains S.  $10^{\circ}$  W.; asc. 110 ft. over E. slope.
- 53.40 Spur, slopes S.; desc. 160 ft. over W. slope.
- 68.80 Road, bears NE. and S.

64

CHAINS	
69.50	Wash, 50 lks. wide, 3 ft. deep, drains SW.; asc. 30 ft. over E. slope.
71.90	Road, bears N. and S.
72.40	Spur, slopes SW.; desc. 80 ft. over NW. slope.
77.60	Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. 20 ft. over SE. slope.
78.92	The cor. of secs. 1, 6, 7 and 12, which is monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, mountainous. Soil, rocky sandy clay. Timber, none; undergrowth, creosotebush, catclaw and cacti.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Over mountainous land, through scattered undergrowth.
	By triangulation, asc. about 200 ft. steep SE. slope.
6.00	Spur, slopes SW.; desc. about 30 ft. over steep NW. slope.
10.00	Wash, near head, drains SW.; asc. about 680 ft. over ledgy SW. slope.
31.50	End of triangulation.
31.80	Bulldozed trail, bears N. 10° W. and S. 10° E.; asc. 40 ft. over SW. slope.
36.00	Spur, projects W. from mountain top; desc. 10 ft. along steep W. slope.
40.00	Point for the ¼ sec. cor. of secs. 5 and 6.  Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.
	T6SR27E ¼ S 6   S 5 1960
	By triangulation desc. about 200 ft. over steep ledgy N. slope.
50.00	Wash, near head, drains NE.; asc. about 300 ft. over steep SE. slope.
68.00	End of triangulation on spur, sloping NE.; desc. 540 ft. over steep ledgy NW. slope.
77.57	Point for the C.C. of secs. 5 and 6 on the First Standard Parallel South.  Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions, T6S, R27E, Arizona

T5SR27E  
S31  
S 6 | S 5  
T6S  
1960

From this cor., the standard  $\frac{1}{4}$  sec. cor. of sec. 31, previously described, bears S.  $89^{\circ}58'$  W., 1.98 chs. distant.

Land, mountainous.  
Soil, rocky, sandy clay.  
Timber, none; undergrowth, creosotebush, catclaw and cacti.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 5 is 40.00 chs. in easting from the C.C. of secs. 5 and 6, and on the N. bdy. of the township.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S 5  
T6SR27E  
1960

From this cor. the standard cor. of secs. 31 and 32, previously described, bears West, 2.07 chs. dist.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 6 is 40.00 chs. in westing from the C.C. of secs. 5 and 6, and on the N. bdy. of the township.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S 6  
T6SR27E  
1961

From this cor. the standard cor. of T. 5 S., Rs. 26 and 27 E., bears N.  $89^{\circ}57'$  W., 2.03 chs. dist.

Retracement, W. Bdy., Sec. 7, T6S, R27E, Arizona  
as surveyed in 1960 by Dell Cazier

The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township is monumented by an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the official record.

CHAINS

N. 0°02' E., bet. secs. 7 and 12.

39.97 The 1/4 sec. cor. of secs. 7 and 12, monumented by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record.

North, beginning new measurement.

39.95 The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record.

Retracement, Portion, E. Bdy., T6S, R27E, Arizona as surveyed in 1958 by Phil D. Smith

The 1/4 sec. cor. of secs. 25 and 30, monumented by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°10' W., bet. secs. 25 and 30.

39.88 True point for the cor. of secs. 19, 24, 25 and 30, falls in an unsafe place.

N. 0°11' W., bet. secs. 19 and 24.

0.50 The original W.C. for secs. 19, 24, 25 and 30, monumented by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record.

The cor. was remonumented during the 1958 resurvey but was not designated as a witness corner; additionally marked the brass cap to read as follows:

T6S  
R27E | R28E  
S24 | S19  
-----  
S25 | S30  
WC  
1958

40.05 The 1/4 sec. cor. of secs. 19 and 24, monumented by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record.

The cor. of secs. 1, 6, 7 and 12 is monumented by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°06' W., bet. secs. 1 and 6.

39.78 The 1/4 sec. cor. of secs. 1 and 6, monumented by an iron post, set, mkd. and witnessed as described in the official record.

General Description

The southeast corner of the township is located approximately 11 air miles northeast of the city of Safford and in Graham County, Arizona

The land is both mountainous and rolling. A spur of the Gila Mountains extends through the township from

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 6 South, Range 27 East, Arizona

the northwest corner to the southeast corner. The land lying on the northeast flank of the mountains is mostly precipitous slopes, while the land lying on the southwest flank is a well developed southwest slope. The elevation of the township ranges from about 3000 feet along the Gila River in the southeast corner to about 6000 feet above sea level on Weber Mountain, which is situated in the extreme northwest corner.

The drainage system is composed of intermittent streams and numerous tributary washes. The Gila Mountains form a drainage divide within the township. The land lying on the northeast flank of the mountains drains east and southeast, while the land on the southwest side of the mountains is drained to the southwest. The drainage from both sides of the mountain empties into the Gila River, which flows southwest at the very edge of the southeast corner of the township.

The soil found is both residual and alluvial. Both have about the same general characteristics, but vary in depth and development. They are both grayish, rocky to gravelly, sandy clay lacking in humus, of the desert soil type. Depending on the amount of rainfall these soils will support a luxuriant vegetative cover consisting of creosotebush, ocotillo, palo verde, catclaw, acacia and several species of cacti and grasses. The size and number vary with elevation, available moisture, topography and exposure. Generally the trees and shrubs are found along the drainage; the creosotebush, cacti and grasses cover the entire township.

The main road comes from Safford, Arizona, and crosses the township from the southwest corner to the northeast corner. This is a gravelled, well maintained road. There are also numerous bulldozed roads and jeep trails throughout the township.

There is a windmill in section 16 at Anderson's Ranch, and numerous stock ponds and water tanks throughout the township, but there was no apparent source of permanent surface water.

There is considerable evidence of the existence of copper and its related metals within the township. There are, however, no producing mines within the township, although the land shows a long history of mineral exploration, as evidenced by the numerous remains of mine dumps, tunnels, shafts, buildings and other traces of past activity. With the sinking of an explorer shaft now under way in section 5, there has been a renewal of the interest in the land and it appears that at least 70 per cent of the land will be covered by mineral claims. The only other apparent interest or utilization of the land is in grazing of livestock.

4-680  
(Feb., 1960)

BOOK 4007

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Eldon W. Sibley	Crew Chief
William R. Savage	Principal Assistant
La Vern Griffin	Notekeeper
Parley Pratt	Front Chainman
P. Gordon Shurtz	Flagman
Dan Coleman	Cornerman
Glen B. Hatch	Crew Chief
Neil Forsyth	Principal Assistant
Wallace R. Ott	Notekeeper
Gary T. Oviatt	Front Chainman
Jerry Lee Thomas	Flagman
Douglas Haycock	Cornerman

### CERTIFICATE OF CADASTRAL ENGINEER

WE, Eldon W. Sibley, Survey Technician  
Glen B. Hatch, Survey Technician  
~~by~~ Dell Cazier, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in

pursuance of special instructions bearing date of the 10th day of August, 1959,

WE ~~have surveyed~~ dependently resurveyed the First Standard Parallel South, through  
Range 27 East, and dependently resurveyed a portion of the subdivisional lines,  
and surveyed a portion of the subdivisional lines in Township 6 South, Range 27 East

of the Gila & Salt River Meridian, in the State of Arizona, which are  
represented in the foregoing field notes as having been executed by ~~me~~<sup>us</sup> and under ~~my~~<sup>our</sup> direction; and that  
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the  
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing  
field notes.

September 28, 1961

Phoenix, Arizona

*Dell Cazier*  
Cadastral Surveyor  
*Eldon W. Sibley*  
Survey Technician  
*Glen B. Hatch*  
Survey Technician

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., JAN 17 1964, 19

The foregoing field notes of the ~~survey of~~ dependent resurvey of the First Standard Parallel  
South, through Range 27 East and dependent resurvey of a portion of the subdivisional  
lines, T. 6 S., R. 27 E., Gila and Salt River Meridian, Arizona

executed by Dell Cazier, Cadastral Surveyor, Glen B. Hatch, Survey Technician, and  
Eldon W. Sibley, Survey Technician  
having been critically examined and found correct, are hereby approved.

*E. Remington*  
Cadastral Engineering Staff Officer.  
Chief, Division of Engineering

### CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in  
is a true copy of the original field notes.~~

~~Cadastral Engineering Staff Officer.~~