

BOOK 4009

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

West Boundary

(First Guide Meridian East)

SURVEY

of the

East and North Boundaries

and

Sections 4 thru 9, 16 thru 21 and 29 thru 30

TOWNSHIP 6 NORTH, RANGE 5 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Gary W. Rutledge, Surveying Technician

Under special instructions dated April 22, 19 63, which provided for the surveys
included under Group Number 399, approved April 22, 1963,
and assignment instructions dated April 22, 19 63.

Survey commenced April 30, 19 63

Survey completed June 21, 19 63

1A

INDEX DIAGRAM

Township 6 North, Range 5 East,

	17	16	15	14	13	12
7	($\frac{1}{2}$)37 ₆ 37	5 26	4 20	3	2	1 11
6	36	35	25			
6	($\frac{1}{2}$)36 ₇ 34	8 24	9 19	10	11	12 11
5	33	32	23			
5	($\frac{1}{4}$)34 ₁₈ 31	17 22	16 18	15	14	13 10
4	30	29	22			
4	($\frac{1}{4}$)3 ₁₉ 28	20 21	21 18	22	23	24 9
3	27	26				
2	30 28	29	28	27	26	25 8
1	31	32	33	34	35	36 8

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

1. B

CHAINS

Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

The west boundary was surveyed in 1910 by R. C. Ham and the south one-half mile dependently resurveyed in 1959 by H. G. Parker. The south boundary was surveyed in 1919 by S. E. Blout. Sections 28, 31, 32 and 33 and some of the subdivisions of section 28 were surveyed in 1959 by H. G. Parker. Several exchange surveys, homestead surveys and mineral surveys have been made and are in the township.

The following notes are those of a dependent resurvey of the north five and one-half miles of the west boundary (East boundary, Township 6 North, Range 4 East) and the survey of the east boundary, north boundary and sections 4 through 9, 16 through 21 and 29 through 30 of Township 6 North, Range 5 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated April 22, 1963.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top. Original corner monuments were deposited alongside the new monuments, unless described otherwise.

The geographic position of the southeast corner of the township is: Latitude, 33°48'50" North and Longitude 111°47'10.5" West.

The magnetic declination was found to be 14½° East.

Dependent Resurvey of the North Five and one-half Miles of the East Boundary, Township 6 North, Range 4 East

Reestablishment of the Survey
Executed by R. C. Ham in 1910

From the ¼ sec. cor. of secs. 31 and 36 on the E. bdy. of the township, monumented by an iron post as described in the official record. This cor. is identical with Cor. No. 1, Exchange Survey No. 658.

From the cor.

U. S. Coast and Geodetic Survey triangulation station LINE bears S. 0°09' W., 15.81 chs. dist., as verified by double chaining. Distance as originally recorded, 14.82 chs., is in error.

Fence, barbed wire, bearing N. and S., bears East, 05½ lks. dist.

N. 0°02' W., along the E. bdy. of sec. 36.

CHAINS

Asc. over gently rolling hills through scattered to moderate undergrowth.

18.90 Wash, 100 lks. wide, 2 ft. deep, drains W.

31.00 Wash, 50 lks. wide, 1 ft. deep, drains S. 70° W.

40.02 The cor. of secs. 25, 30, 31 and 36, monumented by a stone 16 x 10 x 6 ins., set, mkd. and witnessed as described in the official record.

At the cor. point.

Set the iron post 24 ins. in the ground, cap mkd.

T6N	
R4E	R5E
S25	S30
S36	S31
10	
1963	

This cor. is identical with Cor. No. 2, Exchange Survey No. 658.

The cor. is located under fence bearing West and East .05 lks. dist. to fence bearing N. and S.

Land, gently rolling.

Soil, gravelly.

No timber; undergrowth, palo verde, brush and cactus.

North, along the E. bdy. of sec. 25.

Over rolling hills through scattered undergrowth.

18.00 Graded dirt road, bears E. and W.; road forks 0.50 chs. West, bears N. and SW.

28.30 Small wash, drains W.; asc. over rocky S. slope.

34.81 Cor. No. 3 of Exchange Survey No. 658 bears West, 0.01 chs. dist., monumented by a stone as described in the official record.

Desc. over N. slope.

38.20 Wash, 20 lks. wide, 3 ft. deep, drains S. 80° W.

40.03 The 1/4 sec. cor. of secs. 25 and 30, monumented by a stone, 15 x 10 x 6 ins., set, mkd. and witnessed as described in the official record.

At the cor. point

Set the iron post 11 ins. in the ground, mound with stones to top, cap mkd.

T6N	
R4E	R5E
1/4	
S25	S30
10	
1963	

Original mound of stone W. of the cor.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS							
	Resurvey, E. Bdy., T. 6 N., R. 4 E., Arizona						
	N. 0°04' W., along the E. bdy. of sec. 25, beginning new measurement.						
	Asc. over rolling hills through scattered undergrowth.						
3.70	Top of ascent; desc. over NW. slope.						
9.90	Wash, 40 lks. wide, 2 ft. deep, drains SW.; asc. over rocky S. slope.						
26.60	Top of ridge, bears N. 70° E. and S. 70° W.; desc. over NW. slope.						
35.88	Concrete water tank in fence bearing N. and S.; located near small wash draining S. 70° W.; asc. over S. slope.						
39.54	Fence bears W.						
39.56	The cor. of secs. 19, 24, 25 and 30, monumented by a stone, 18 x 8 x 8 ins., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 24 and 25 only.						
	At the cor. point						
	Set the iron post 12 ins. in the ground, mound with stone to top, cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T6N</td></tr> <tr><td>R4E R5E</td></tr> <tr><td>S24 S30</td></tr> <tr><td>S25 </td></tr> <tr><td>10</td></tr> <tr><td>1963</td></tr> </table>	T6N	R4E R5E	S24 S30	S25	10	1963
T6N							
R4E R5E							
S24 S30							
S25							
10							
1963							
	The cor. is located 0.02 chs. W. of fence bearing N. and S.						
	Land, rolling and broken.						
	Soil, gravelly and rocky.						
	No timber; undergrowth, palo verde, brush and cactus.						
	N. 0°01' W., along the E. bdy. of sec. 24.						
	Asc. over SE. slope.						
3.30	Top of ascent; desc. over N. slope.						
6.40	S. bank of wash draining W.						
9.00	N. bank of wash; asc. over rolling S. slope.						
26.40	Top of ascent, bears E. and W.; desc. over N. slope.						
32.70	Wash, 100 lks. wide, 2 ft. deep, drains S. 70° W.						
39.63	The witness ¼ sec. cor. of secs. 19 and 24, monumented by a stone, 14 x 8 x 4 ins., set, mkd. and witnessed as described in the official record. This cor. now functions as the witness ¼ sec. cor. of sec. 24 only.						
	At the witness point						

CHAINS

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

WC
 T6N
 R4E R5E
 1/4
 S24
 10
 1963

39.88 True point for the 1/4 sec. cor. falls in wash.

N. 0°04' W., beginning new measurement.

Asc. over broken land facing S.

12.80 Graded road, bears N. 80° E. and S. 80° W.

17.10 Graded road, bears N. 80° E. and S. 80° W.

20.00 Top of ascent, bears E. and W.; desc. over steep NW. slope.

31.00 Oriental Wash, 170 lks. wide, 4 ft. deep, drains SW.; asc. along steep broken E. slope.

39.86 The cor. of secs. 13, 18, 19 and 24, monumented by a (X) on a stone in place, 14 x 12 x 12 ins. above the ground, marked and witnessed as described in the official record. This cor. now functions as the cor. of secs. 13 and 24 only.

At the cor. point

Set the iron post over the original (X) and in a mound of stone to top cap mkd.

T6N
 R4E R5E
 S13
 S24 | S19
 10
 1963

Land, mountainous.

Soil, rocky.

No timber; undergrowth, palo verde, mesquite and cactus.

N. 0°01' W., along the E. bdy. of sec. 13.

Over steep, broken mountainous land.

By triangulation, topography as taken from original notes.

9.00 Oriental Wash, 30 lks. wide, drains SE.; asc. steep slope.

12.25 Top of W. slope; desc. steep slope.

14.10 Oriental Wash, 25 lks. wide, drains W. circling to SE.

14.25 Begin steep ascent of 800 ft. to Oriental Peak.

18.00 Oriental Mine, bears East, 6.00 chs. dist.

30.49 Shaft, 100 ft. deep, on line.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Resurvey, E. Bdy., T. 6 N., R. 4 E., Arizona

31.50 End of triangulation on spur sloping SW.; thence along broken W. slope.

38.69 The 1/4 sec. cor. of secs. 13 and 18, monumented by a stone, 14 x 10 x 8 ins., set, mkd. and witnessed as described in the official record. This cor. now functions as the 1/4 sec. cor. of sec. 13 only.

At the cor. point

Set the iron post 22 ins. in the ground, cap mkd.

T6N
R4E R5E
1/4 |
S13 |
10
1963

Original mound of stone W. of the cor.

N. 0°03' E., beginning new measurement.

Along broken W. slope through scattered undergrowth.

11.30 Asc. over S. slope.

16.10 Spur, projects E.; thence, along rolling, rocky E. slope.

20.70 Rocky ravine, 20 lks. wide, 1 ft. deep, drains E.

27.40 Spur, slopes E.; desc. over steep NE. slope.

40.38 The cor. of secs. 7, 12, 13 and 18, monumented by a stone, 20 x 10 x 8 ins., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 12 and 13 only.

At the cor. point

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T6N
R4E R5E
S12 | S18
S13 |
10
1963

Original mound of stone W. of the cor.

Land, mountainous.

Soil, rocky.

No timber; undergrowth, scattered brush, palo verde and cactus.

N. 0°23' E., along the E. bdy. of sec. 12.

Over steep mountainous land through scattered undergrowth.

6

CHAINS	
1.70	By triangulation, begin ascent over steep, ledgy SW. slope of Continental Mountain.
39.01	The 1/4 sec. cor. of secs. 7 and 12, monumented by a "X" chiseled on a stone in place, mkd. and witnessed as described in the official record. This cor. now functions as the 1/4 sec. cor. of sec. 12 only.
	At the cor. point
	Set the iron post over the "X" and in a large mound of stones to top, cap mkd.
	<p>T6N R4E R5E 1/4 S12 10 1963</p>
	N. 0°01' W., beginning new measurement.
	Asc. over steep SW. slope.
5.40	Top of Continental Mountain, bears N. 60° W. and S. 60° E.; desc. over NE. slope.
12.20	Spur, slopes NE.; by triangulation desc. over steep N. side of Continental Mountain.
40.55	The cor. of secs. 1, 6, 7 and 12, monumented by a stone, 20 x 6 x 4 ins., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 1 and 12 only.
	At the cor. point
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	<p>T6N R4E R5E S 1 S12 S 7 10 1963</p>
	Land, mountainous. Soil, rocky. No timber; undergrowth, mountain laurel, oak, mesquite and cactus.
	N. 0°09' E., along the E. bdy. of sec. 1.
	By triangulation, topography as taken from original notes.
	Over mountainous land, desc. to the foot of Continental Mountain.
6.00	Draw, drains NW.
24.80	Bottom of descent, wash 45 lks. wide, course SE.; asc.
26.00	Top of ascent, bears E. and W.; desc.
28.18	Bottom of descent; wash 50 lks. wide, drains W.; asc. steeply for 200 ft.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS																						
	Resurvey, E. Bdy., T. 6 N., R. 4 E., Arizona																					
37.00	Top of ascent, bears E. and W.; desc. 100 ft. on W. slope.																					
40.28	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented by a stone 15 x 12x6 ins., set, mkd. and witnessed as described in the official record. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 1 only.																					
	At the cor. point																					
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.																					
	<table border="0"> <tr><td></td><td>T6N</td><td></td></tr> <tr><td></td><td>R4E R5E</td><td></td></tr> <tr><td></td><td>$\frac{1}{4}$ </td><td></td></tr> <tr><td></td><td>S 1 </td><td></td></tr> <tr><td></td><td>10</td><td></td></tr> <tr><td></td><td>1963</td><td></td></tr> </table>		T6N			R4E R5E			$\frac{1}{4}$			S 1			10			1963				
	T6N																					
	R4E R5E																					
	$\frac{1}{4}$																					
	S 1																					
	10																					
	1963																					
	N. 0°03' E., beginning new measurement.																					
	Over mountainous land, by triangulation; topography as taken from original notes.																					
3.20	Draw, drains SW.; asc. 250 ft.																					
8.25	Top of ridge, rhyolite dyke, bears N. 51½° E. and S. 51½° W.; desc. 40 ft.																					
9.50	Bottom of draw, asc. 150 ft.																					
15.20	Top of ascent, ridge bears SW. and NE.; desc. 150 ft. through dense scrub oak.																					
22.75	Bottom of draw, drains W.; asc. 100 ft.																					
30.00	Top of ridge, bears E. and W.; desc. 50 ft.																					
31.50	Bottom of descent; draw, drains SW.; asc. 100 ft.																					
34.25	Top of ascent, bears SW. and NE.; desc. 100 ft.																					
38.15	Draw, drains SW.; asc. 75 ft.																					
39.90	The cor. of Townships 6 and 7 North, Ranges 4 and 5 East, monumented by a stone, 14 x 10 x 10 ins., set, mkd. and witnessed as described in the official record.																					
	At the cor. point																					
	Set the iron post 24 ins. in the ground, cap mkd.																					
	<table border="0"> <tr><td></td><td>T7N</td><td></td></tr> <tr><td></td><td>R4E R5E</td><td></td></tr> <tr><td></td><td>S36 S31</td><td></td></tr> <tr><td></td><td>S 1 S 6</td><td></td></tr> <tr><td></td><td>T6N</td><td></td></tr> <tr><td></td><td>10</td><td></td></tr> <tr><td></td><td>1963</td><td></td></tr> </table>		T7N			R4E R5E			S36 S31			S 1 S 6			T6N			10			1963	
	T7N																					
	R4E R5E																					
	S36 S31																					
	S 1 S 6																					
	T6N																					
	10																					
	1963																					
	Original mound of stone S. of the cor.																					

CHAINS

Land, mountainous.
Soil, rocky.
No timber; undergrowth, scrub oak, mountain laurel,
cactus and mesquite.

Survey of the East Boundary
Township 6 North, Range 5 East, Arizona

From the cor. of Ts. 5 and 6 N., Rs. 5 and 6 E.,
monumented by an iron post set, mkd. and witnessed
as described in the official record.

North, bet. secs. 31 and 36.

Asc. over rolling hills, through scattered undergrowth
and cactus.

15.90 Unimproved road, bears NW. and SE.

17.60 Wash, 10 lks. wide, 1 ft. deep, drains SE.

38.00 Top of small knoll.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set the iron post 24 ins. in ground, cap mkd.

T6N
R5E R6E
1/4
S36|S31
1963

No accessories available.

Cor. falls on N. slope of small knoll.

44.60 Wash, 30 lks. wide, 4 ft. deep, drains SE.; track road
in wash.

66.30 Wash, 50 lks. wide, 1 ft. deep, drains SE.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set the iron post 24 ins. in ground, cap mkd.

T6N
R5E R6E
S25|S30
S36|S31
1963

Raise a mound of stone 3 ft. base, 2 ft. high, W.
of post.

Land, rolling.
Soil, rocky and gravelly.
Timber, none.
Undergrowth, mesquite, catclaw, palo verde, black brush
and cactus.

North, bet. secs. 25 and 30.

Over rolling hills, through scattered undergrowth
and cactus.

00.90 Small wash, drains N. 75° E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Survey, E. Bdy., T. 6 N., R. 5 E., Arizona
14.90	Wash, 10 lks. wide, 2 ft. deep, drains S. 60° E.
38.90	Enter large wash area.
40.00	Point for the ¼ sec. cor. of secs. 25 and 30. Set the iron post 24 ins. in ground, cap mkd.
	T6N R5E R6E ¼ S25 S30 1963
	Raise a small mound of stone W. of post. Cor. falls in a wash area.
42.00	Leave wash area.
52.10	Ridge, bears S. 75 E. and N. 75° W.; desc. N. slope.
61.40	Enter wash, drains E.
69.60	Leave wash; asc. S. slope.
71.80	Ridge, bears E. and W.; desc. N. slope to cor.
80.00	Point for the cor. of secs. 19, 24, 25 and 30. Set the iron post 22 ins. in ground, cap mkd.
	T6N R5E R6E S24 S19 S25 S30 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post. Cor. falls in flat sloping NE. Land, rolling. Soil, decomposed granite. Timber, none. Undergrowth, palo verde, mesquite, catclaw and cactus.
	North, bet. secs. 19 and 24. By triangulation, asc. over nearly level land, through medium undergrowth; topography estimated.
30.00	Improved road to Bartlett Dam, bears E. and W.
40.00	Point for the ¼ sec. cor. of secs. 19 and 24. Set the iron post 24 ins. in ground, cap mkd.
	T6N R5E R6E ¼ S24 S19 1963

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Cor. falls on S. edge of Camp Creek Wash.

45.10 End of triangulation at Camp Creek Wash, drains S. 30° E.; track road in wash.

47.50 N. bank of Camp Creek Wash, 5 ft. high; by triangulation asc. S. slope of ridge bearing NE.

61.30 Crest of ridge, bears NE.; end of triangulation; desc. N. slope.

78.20 Wash, 100 lks. wide, drains SW.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set the iron post 24 ins. in ground, cap mkd.

T6N
R5E R6E
S13 | S18
S24 | S19
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.

Cor. falls on S. slope about 1.50 chs. N. of large wash.

Land, broken and rolling.

Soil, decomposed granite.

Timber, none.

Undergrowth, palo verde, black brush and cactus.

North, bet. secs. 13 and 18.

Over rolling hills; asc. S. slope.

40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.

Set the iron post 24 ins. in ground, cap mkd.

T6N
R5E R6E
S13 | S18
1963

No accessories available.

Cor. falls in flat on gentle W. slope.

71.00 Wash, 50 lks. wide, 2 ft. deep, drains SW.

80.00 Point for the cor. of secs. 7, 12, 13 and 18.

Set the iron post 24 ins. in ground, cap mkd.

T6N
R5E R6E
S12 | S7
S13 | S18
1963

Raise a mound of stone W. of post.

Cor. falls on gentle S. slope at head of a small draw.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Survey, E. Bdy., T. 6 N., R. 5 E., Arizona
	<p>Land, rolling. Soil, decomposed granite. Timber, none. Undergrowth, palo verde, catclaw, blackbrush and cactus.</p>
	<p>North, bet. secs. 7 and 12.</p>
	<p>Over rolling hills, through scattered undergrowth.</p>
18.55	<p>Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.</p>
	<p>Set the iron post 22 ins. in ground, cap mkd.</p>
	<p style="text-align: center;">T6N R5E R6E $\frac{1}{4}$ S12 S7 1963</p>
	<p>No accessories available.</p>
	<p>Cor. falls on gentle SW. slope.</p>
48.00	<p>Wash, 30 lks. wide, 3 ft. deep, drains SW.</p>
68.30	<p>Wash, 20 lks. wide, 3 ft. deep, drains W.</p>
78.80	<p>Wash, 20 lks. wide, 3 ft. deep, drains S. 75° W.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p>
	<p>Set the iron post 24 ins. in ground, cap mkd.</p>
	<p style="text-align: center;">T6N R5E R6E S1 S6 S12 S7 1963</p>
	<p>Raise a mound of stone 3 ft. base, 2 ft. high, W. of post.</p>
	<p>Land, rolling. Soil, decomposed granite. Timber, none. Undergrowth, palo verde, catclaw, blackbush and cactus.</p>
	<p>North, bet. secs. 1 and 6.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
14.70	<p>Wash, 100 lks. wide, 1 ft. deep, drains W.</p>
19.90	<p>Unimproved road, bears irregularly E. and W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.</p>
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>

CHAINS

T6N
R5E R6E
 $\frac{1}{4}$
S 1 | S 6
1963

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of post.

Cor. falls on S. slope, on S. side of a small ravine draining W.

By triangulation, asc. over rolling land, through scattered undergrowth; topography estimated.

68.00 Crest of spur, slopes steeply SE.

75.00 Draw, drains E.

77.22 Point for the cor. of Ts. 6 and 7 N., Rs. 5 and 6 E., at a point E. of the cor. of Ts. 6 and 7 N., R. 4 and 5 E.

Set the iron post 24 ins. in ground, cap mkd.

T7N
R5E R6E
S36 | S31
S 1 | S 6
T6N
1963

Raise a mound of stone S. of post.

Land, rolling.

Soil, rocky.

Timber, scattered juniper.

Undergrowth, scattered cactus, blackbrush and mountain laurel.

Survey of the North Boundary
Township 6 North, Range 5 East, Arizona

From the cor. of Ts. 6 and 7 N., Rs. 5 and 6 E.

West, bet. secs. 1 and 36.

Asc. over mountainous land, through scattered undergrowth.

18.60 Crest of spur, slopes NW.; desc. W. slope.

27.80 Wash, 30 lks. wide, 3 ft. deep, drains SW.

36.70 Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. SE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36.

Set the iron post 22 ins. in ground, cap mkd.

T7N R5E
 $\frac{1}{4}$ S 36
S 1
T6N
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS							
	Survey, N. Bdy., T. 6 N., R. 5 E., Arizona						
	Cor. falls on gentle E. slope.						
47.60	Ravine, 10 lks. wide, 2 ft. deep, drains S.; asc. SE. slope.						
56.40	Small spur, slopes South; thence along S. slope.						
63.70	Crest of spur, slopes S.; desc. SW. slope.						
80.00	Point for the cor. of secs. 1, 2, 35 and 36.						
	Set the iron post 20 ins. in ground, collar of stone to top, cap mkd.						
	<table border="0"> <tr><td>T7N</td><td>R5E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td>S2</td><td>S1</td></tr> </table>	T7N	R5E	S35	S36	S2	S1
T7N	R5E						
S35	S36						
S2	S1						
	T6N						
	1963						
	Raise a mound of stone, W. of post.						
	Cor. falls on small bench on the W. slope of a large hill.						
	Land, rolling mountains.						
	Soil, sandstone formation, rocky.						
	Timber, scattered juniper.						
	Undergrowth, black brush, catclaw, palo verde, mountain laurel and cactus.						
	West, bet. secs. 2 and 35.						
	By triangulation, desc. SW. slope over rocky and broken land.						
29.10	Power line on N. bank of Camp Creek Wash, bears SE.; end of triangulation.						
29.80	Graded road, follows N. bank of Camp Creek, bears SE. and NW.						
31.40	Camp Creek Wash, 2 chs. wide, 2 ft. deep, drains SE.; asc. steep NE. slope.						
39.20	Crest of spur, slopes N.						
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35.						
	Set the iron post 10 ins. in ground, mound of stone to top, cap mkd.						
	<table border="0"> <tr><td>T7N</td><td>R5E</td></tr> <tr><td>$\frac{1}{4}$</td><td>S 35</td></tr> <tr><td></td><td>S 2</td></tr> </table>	T7N	R5E	$\frac{1}{4}$	S 35		S 2
T7N	R5E						
$\frac{1}{4}$	S 35						
	S 2						
	T6N						
	1963						
42.40	Small draw, drains N.						
58.46	Power line, bears N. $88^{\circ}47'$ E. and S. $88^{\circ}47'$ W.						

CHAINS

63.90 Crest of ridge, bears NW. and SE.

68.90 Graded road, bears NW. and SE.

79.00 Draw, drains S.

80.00 Point for the cor. of secs. 2, 3, 34 and 35.

Set the iron post 24 ins. in ground, cap mkd.

T7N R5E
S34 | S35
S 3 | S 2
T6N
1963

Raise a mound of stone, W. of post.

Cor. falls on E. slope of a spur.

Land, broken and mountainous.
Soil, gravelly with boulders.
Timber, scattered juniper with sycamore and willow growth along Camp Creek.
Undergrowth, oak brush, blackbrush, laurel, catclaw, and cactus.

West, bet. secs. 3 and 34.

Asc. over rolling mountain land.

1.90 Spur, bears N. 15° W.

12.10 Graded road to Seven Springs, bears S. and NW.; about 70 lks. N. road forks to E.

13.60 Point selected for a witness point.

Set the iron pipe 24 ins. in ground, cap mkd.

T7N R5E
WP
S34
S3
T6N
1963

19.90 Crest of ridge, bears SE. and NW.; asc. steep E. slope.

33.80 Crest of spur, bears N.

38.30 Ravine, 20 lks. wide, 2 ft. deep, drains N. 15° W.

40.00 Point for the ¼ sec. cor. of secs. 3 and 34.

Set the iron post 24 ins. in ground, cap mkd.

T7N R5E
¼ S 34
S 3
T6N
1963

Cor. falls on N. slope.

Thence along broken N. slope.

47.70 Crest of spur, bears N.

51.70 Ravine, 20 lks. wide, 2 ft. deep, drains N.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS																
	Survey, N. Bdy., T. 6 N., R. 5 E., Arizona															
57.10	Spur, bears N.; thence along N. slope.															
65.90	Spur, bears NW.															
73.40	Wash, 30 lks. wide, 2 ft. deep, drains irregularly N.; asc. E. slope.															
79.90	Point for the witness corner for secs. 3, 4, 33 and 34. Set the iron post 12 ins. in ground, mound of stone with 3½ ft. base to top, cap mkd. <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>T7N</td> <td>R5E</td> </tr> <tr> <td>WC</td> <td><u>S33</u></td> <td><u>S34</u></td> </tr> <tr> <td></td> <td>S4</td> <td>S3</td> </tr> <tr> <td></td> <td>T6N</td> <td></td> </tr> <tr> <td></td> <td>1963</td> <td></td> </tr> </table> </div> <p>W.C. falls N. of wash on rocky ledge.</p>		T7N	R5E	WC	<u>S33</u>	<u>S34</u>		S4	S3		T6N			1963	
	T7N	R5E														
WC	<u>S33</u>	<u>S34</u>														
	S4	S3														
	T6N															
	1963															
80.00	Point for the cor. of secs. 3, 4, 33 and 34 falls in wash 20 lks. wide, steep sloping sides, drains irregularly East. Land, broken and mountainous. Soil, rocky shale. Timber, scattered juniper. Undergrowth, oak brush, mountain laurel, blackbrush, catclaw and cactus.															
	West, bet. secs. 4 and 33. Over broken mountainous land, through scattered undergrowth.															
17.60	Crest of spur, bears S.															
18.40	Barbed wire fence, bears SW. and NE.; thence along S. slope.															
29.50	Crest of spur, bears irregularly SE.; thence along SW. slope to cor.															
40.00	Point for the ¼ sec. cor. of secs. 4 and 33. Set the iron post 16 ins. in ground, mound of stone to top, cap mkd. <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>T7N</td> <td>R5E</td> </tr> <tr> <td>¼</td> <td><u>S 33</u></td> <td></td> </tr> <tr> <td></td> <td>S 4</td> <td></td> </tr> <tr> <td></td> <td>T6N</td> <td></td> </tr> <tr> <td></td> <td>1963</td> <td></td> </tr> </table> </div> <p>from which Cor. No. 1 of the Fort Worth mining claim, M.S. No. 2916A, bears N. 49°51' W., 11.70 chs. dist., monumented by a 4 x 4 in. redwood post, 3 ft. exposed and in a mound of stone.</p>		T7N	R5E	¼	<u>S 33</u>			S 4			T6N			1963	
	T7N	R5E														
¼	<u>S 33</u>															
	S 4															
	T6N															
	1963															

CHAINS

Entrance to mine shaft bears N. 62°19' W.,
14.57 chs. dist.

S.E. cor. of a miner's cabin bears N. 59°04' W.,
24.20 chs. dist., cabin is 20 x 8 ft., long side
facing North.

Improved seep bears N. 69°11' W., 24.80 chs. dist.,
consists of covered shaft 5 x 5 ft. and 10 ft.
to water.

Cor. falls on NW. slope.

40.20 Small draw, drains S. 75° W.; desc. SW. slope.

45.40 Wash, 20 lks. wide, 4 ft. deep, drains NW.

52.40 Road to shaft from the Fisk mill site, approximately
7 chs. North.

59.40 Large spur, bears N.; thence along steep N. slope.

66.30 Wash, 20 lks. wide, 3 ft. deep, drains N.

80.00 Point for the cor. of secs. 4, 5, 32 and 33.

Set the iron post 24 ins. in ground, collar of stone
with 3 ft. base to top, cap mkd.

T7N R5E
S32 | S33
S 5 | S 4
T6N
1963

Land, broken mountainous.
Soil, rocky shale.
Timber, scattered juniper.
Undergrowth; oak brush, Spanish bayonet, cactus and
thick mountain laurel on north slopes.

West, bet. secs. 5 and 32.

Over rolling mountains, through medium thick undergrowth.

00.10 Ravine, drains N.; asc. along N. slope.

8.10 Crest of spur, bears N.; desc. steep SW. slope.

22.60 Ravine, 10 lks. wide, 1 ft. deep, drains N. 30° W.

27.50 Spur, bears N.; desc. N. slope.

36.80 Spur, bears N.

39.30 Wash, 15 lks. wide, 1 ft. deep, drains NW.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 32.

Set the iron post 22 ins. in ground, cap mkd.

T7N R5E
1/4 S 32
S 5
T6N
1963

Raise a small mound of stone, W. of post.

48.20 Wash, 30 lks. wide, 2 ft. deep, drains irregularly N.;
thence along broken N. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Survey, N. Bdy., T. 6 N., R. 5 E., Arizona
77.80	Ridge, bears SE. and NW.; desc. SSW. slope to cor.
80.00	Point for the cor. of secs. 5, 6, 31 and 32.
	Set the iron post 15 ins. in ground, mound of stone with 3 ft. base to top, cap mkd.
	<p style="text-align: center;">T7N R5E $\frac{S31}{S6} \frac{S32}{S5}$ T6N 1963</p>
	Cor. falls on S. slope of Butte Peak.
	<p>Land, broken mountains. Soil, rocky shale. Timber, scattered juniper. Undergrowth, oak brush, mountain laurel and cactus.</p>
	West, bet. secs. 6 and 31.
	Over broken mountainous land, along S. slope of Butte Peak.
4.90	Steep rocky draw, drains S.
10.40	Spur, slopes SSW. from Butte Peak; thence by triangulation desc. SW. slope.
34.40	Spur, slopes SW.; thence along spur that bears W. to cor.; end of triangulation.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.
	Set the iron post 10 ins. in ground, mound of stone with 3 ft. base and 2 ft. high to top, cap mkd.
	<p style="text-align: center;">T7N R5E $\frac{1}{4} \frac{S31}{S6}$ T6N 1963</p>
	Cor. falls in small saddle on spur.
	Thence by triangulation desc. steep W. slope; topography estimated.
74.00	Small saddle on ridge bearing N. and S.
79.53	The cor. of Ts. 6 and 7 N., Rs. 4 and 5 E.
	<p>Land, rolling mountains. Soil, rocky shale. Timber, scattered juniper. Undergrowth scattered mountain laurel, black brush and cactus.</p>

CHAINS

From the cor. of secs. 21, 22, 27 and 28, monumented
by an iron post as described in the official record.

N. 0°02' W., bet. secs. 21 and 22.

Asc. over gently rolling hills, through scattered
undergrowth.

17.91 Improved blacktop road, Cave Creek to Seven Springs
and Bartlett Dam, bears N. 52°20' E. and S. 52°20' W.

19.16 Graded road, bears E. and W.

30.80 Power line, bears N. 52° E. and S. 52° W.

40.00 Point for the 1/4 sec. cor. of secs. 21 and 22.

Set the iron post 24 ins. in the ground, cap mkd.

T6N R5E

1/4
S21|S22
1963

from which

U.S.G.S. triangulation station WILDCAT bears
S. 58°19' E., 17.12 chs. dist.

74.00 Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.

78.78 Graded road, bears S. 30° E. and N. 40° W.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set the iron post 24 ins. in ground, cap mkd.

T6N R5E

S16|S15
S21|S22
1963

from which

A windmill bears N. 46°19'45" W., 53.068 chs. dist.

Land, gently rolling.

Soil, sandy.

Timber, scattered mesquite.

Undergrowth, catclaw, palo verde, cactus and black
brush.

N. 0°02' W., bet. secs. 15 and 16.

Over rolling hills, through scattered undergrowth.

8.90 Barbed wire fence, bears N. 80° E. and S. 80° W.

13.30 Barbed wire fence, bears NW. and SE.; and road bears
irregularly E. and W.

40.00 Point for the 1/4 sec. cor. of secs. 15 and 16.

Set the iron post 24 ins. in ground cap mkd.

T6N R5E

1/4
S16|S15
1963

BOOK 4089
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Survey, Subdivision, T. 6 N., R. 5 E., Arizona
80.00	<p>No accessories available.</p> <p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set the iron post 24 ins. in ground, cap mkd.</p> <div style="text-align: center;"> <p>T6N R5E $\frac{S9}{S16} \frac{S10}{S15}$ 1963</p> </div> <p>from which</p> <p style="padding-left: 40px;">A water tank 8 ft. high, 15 ft. diameter, bears N. 1°21' E., 25.33 chs. dist.</p> <p>Cor. falls on slight S. slope at head of small valley.</p> <p>Land, rolling. Soil, decomposed granite. Timber, none. Undergrowth, catclaw, palo verde, black brush and cactus.</p>
18.72	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Asc. over rolling hills, through scattered undergrowth.</p> <p>Thence along E. slope of rolling hills.</p>
21.22	<p>Intersect line 1-2 of E.S. No. 659.</p> <p>Point for the C.C. of secs. 9 and 10.</p> <p>Set the iron post 22 ins. in ground, cap mkd.</p> <div style="text-align: center;"> <p>T6N R5E ES 659 $\frac{C}{S9} \frac{C}{S10}$ 1963</p> </div> <p>from which</p> <p style="padding-left: 40px;">Cor. No. 1 bears S. 25°41' E., 46.54 chs. dist., and Cor. No. 2 bears N. 25°41' W., 4.45 chs. dist., both of E.S. No. 659.</p>
27.60	<p>Intersect line 2-3 of E.S. No. 659.</p> <p>Point for the C.C. of secs. 9 and 10.</p> <p>Set the iron post 24 ins. in ground, cap mkd.</p> <div style="text-align: center;"> <p>T6N R5E $\frac{C}{S9} \frac{C}{S10}$ ES 659 1963</p> </div>

CHAINS		
	<p>from which</p> <p>Cor. No. 3 bears N. 39°01' E., 23.21 chs. dist. and Cor. No. 2 bears S. 39°01' W., 3.06 chs. dist., both of E.S. No. 659.</p>	
40.00	<p>Point for the ½ sec. cor. of secs. 9 and 10.</p> <p>Set the iron post 12 ins. in ground, mound of stone to top, cap mkd.</p> <p style="text-align: center;">T6N R5E ½ S 9 S10 1963</p> <p>Boulder, 2 ft. high and 2 ft. wide, W. of post.</p> <p>Cor. falls near wash draining SE.</p>	
54.10	<p>Desc. N. slope of broken mountains.</p>	
56.00	<p>Wash, 40 lks. wide, 3 ft. deep, drains E.</p>	
63.26	<p>Graded road, bears SE. and NW.</p>	
78.20	<p>Graded road, bears NW. and SE. to abandoned mine.</p>	
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set the iron post 24 ins. in ground, cap mkd.</p> <p style="text-align: center;">T6N R5E S 4 S 3 S 9 S10 1963</p> <p>from which</p> <p>A water tank, 3 ft. high, 8 ft. diameter, bears S. 68°43' E., 7.711 chs. dist.</p> <p>A chimney bears S. 73°55' E., 8.334 chs. dist.</p> <p>A seep bears N. 78°18' E., 8.662 chs. dist., flow is about 1 gal. per hour.</p> <p>Raise a mound of stone 2 ft. high, 3 ft. base, W. of post.</p> <p>Land, broken mountains. Soil, rocky shale. Timber, very scattered juniper. Undergrowth, mountain laurel, catclaw, oak brush and mesquite.</p> <hr/> <p>N. 0°07' E., bet. secs. 3 and 4.</p> <p>Over high rolling mountainous land.</p>	
0.55	<p>Ravine, drains SE.; asc. steep S. slope.</p>	
24.10	<p>Top of ridge, bears SE.; thence along E. slope.</p>	
29.00	<p>Desc. NE. slope.</p>	
34.10	<p>Spur, slopes E.</p>	
37.00	<p>Desc. steep N. slope.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Survey, Subdivision, T. 6 N., R. 5 E., Arizona
38.80	Small spur, slopes NNE.; desc. W. slope to cor.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. Set the iron post 22 ins. in ground, cap mkd.
	<p style="text-align: center;">T6N R5E $\frac{1}{4}$ S4 S3 1963</p> <p>Raise a mound of stone, 2 ft. high, 3 ft. base, W. of post.</p> <p>Cor. falls on steep W. slope.</p> <p>By triangulation, desc. steep mountainous land, through dense undergrowth and scattered juniper; topography estimated.</p>
65.00	Wash, drains SE.; asc. steep S. slope.
74.10	Spur, slopes SE.; desc. steep NNE. slope; end of triangulation.
77.60	Wash, 20 lks. wide, 2 ft. deep, drains E.
77.71	The true point for the cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the township.
	<p>Land, rolling mountains. Soil, decomposed sandstone and granite. Timber, scattered juniper. Undergrowth, oak brush, mountain laurel, mesquite, catclaw and cactus.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29, monumented by an iron post set, mkd. and witnessed as described in the official record.</p> <p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Asc. over rolling hills, through scattered undergrowth.</p>
18.30	Enter wash, drains SW.
21.20	Leave wash.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21. Set the iron post 22 ins. in ground, cap mkd.
	<p style="text-align: center;">T6N R5E $\frac{1}{4}$ S20 S21 1963</p> <p>No accessories available.</p> <p>Cor. falls just S. of small ravine draining W.</p>

CHAINS	
64.60	Wash, 50 lks. wide, 3 ft. deep, drains S. 75° W.
78.90	Wash, 15 lks. wide, 2 ft. deep, drains S. 30° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 18 ins. in ground, mound of stone with 2 ft. base to top, cap mkd.
	<p style="text-align: center;">T6N R5E <u>S17</u> <u>S16</u> <u>S20</u> <u>S21</u> 1963</p>
	Land, rolling. Soil, decomposed granite. Timber, none. Undergrowth, catclaw, palo verde, black brush and cactus.
	<hr/>
	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°53' W., bet. secs. 16 and 21.
	Over gently rolling hills, through scattered undergrowth.
0.54	Graded road, bears NW. and SE.
23.40	Unimproved road, bears SW. and NE.
24.40	Barbed wire fence, bears SW. and NE.
40.00	Point for the ¼ sec. cor. of secs. 16 and 21.
	Set the iron post 6 ins. in ground, mound of stone to top, cap mkd.
	<p style="text-align: center;">T6N R5E ¼ S 16 S 21 1963</p>
	Cor. falls on S. edge of wash, 30 lks. wide, draining S. 75° W.
44.30	Barbed wire fence, bears N. and S.
51.10	Wash, 50 lks. wide, 1 ft. deep, drains S. 30° W.
78.90	Wash, 15 lks. wide, 2 ft. deep, drains S. 30° W.
80.00	The cor. of secs. 16, 17, 20 and 21.
	Land, gently rolling. Soil, sand and gravel, decomposed granite. Timber, none. Undergrowth, palo verde, cactus, catclaw and black brush.
	<hr/>
	N. 0°02' W., bet. secs. 16 and 17.
	Over rolling land, through scattered undergrowth; small washes with general SW. drainage.
18.30	Wash, 100 lks. wide, 1 ft. deep, drains irregularly SSW.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Survey, Subdivision, T. 6 N., R. 5 E., Arizona
27.10	Small wash, drains SSE.
32.00	Same wash, drains irregularly S.
35.80	Same wash.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. Set the iron post 20 ins. in ground, collar of stone with 4 ft. base to top, cap mkd. <div style="text-align: center;"> T6N R5E $\frac{1}{4}$ S17 S16 1963 </div> Cor. falls near wash which drains irregularly S.
40.50	Wash, drains irregularly SSW.
68.50	Wash, 20 lks. wide, 1 ft. deep, drains SE.
73.30	Crest of spur, slopes W.; desc. along W. slope.
79.20	Point selected as witness to cor. of secs. 8, 9, 16 and 17. Set the iron post 18 ins. in ground, collar of stone with 4 ft. base to top, cap mkd. <div style="text-align: center;"> T6N R5E W C S8 S9 S17 S16 1963 </div>
80.00	Point for the cor. of secs. 8, 9, 16 and 17, falls in wash. <hr/> From the cor. of secs. 9, 10, 15 and 16. S. 89°49' W., bet. secs. 9 and 16. Over rolling hills, through moderate undergrowth.
16.85	Wash, 35 lks. wide, 2 ft. deep, drains S.
27.66	Barbed wire fence, bears N. and S.
37.89	Wash, 10 lks. wide, 3 ft. deep, drains S.; asc. moderate SE. slope.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set the iron post 10 ins. in ground, mound of stone with 4 ft. base to top, cap mkd. <div style="text-align: center;"> T6N R5E $\frac{1}{4}$ S9 S16 1963 </div>

CHAINS

- 42.50 Desc. a moderate SW. slope.
- 46.27 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 51.70 Spur, bears S.
- 57.79 Wash, 15 lks. wide, 1½ ft. deep, drains S. for one chain then SE.
- 62.40 Top of ascent; desc. short W. slope.
- 64.30 Asc. moderate SE. slope.
- 67.40 Spur, slopes SW. from N.; desc. steep NW. slope.
- 76.95 Desc. abrupt W. slope.
- 78.00 East bank of wash, 2 ft. high, bears N. and S.
- 80.08 True point for the cor. of secs. 8, 9, 16 and 17.

Land, high foothills.
 Soil, rocky.
 Timber, none.
 Undergrowth, palo verde, mesquite and cactus.

N. 0°02' W., bet. secs. 8 and 9.

Over high mountainous rolling land, through undergrowth.

- 5.02 Crest of small spur; thence by triangulation asc. steep S. slope; topography estimated.
- 20.00 Spur, bears S. from ridge to N.; asc. progressively steeper slope to cor.
- 40.00 Point for the ¼ sec. cor. of secs. 8 and 9.

Set the iron post 16 ins. in ground, mound of stone to top, cap mkd.

T6N R5E
 ½
 S8 | S9
 1963

Cor. falls about half way up on N. slope of spur.

End of triangulation.

- 60.30 Ridge, bears irregularly WSW. and ENE.; by triangulation desc. steep, brushy N. slope to cor.
- 67.00 Crest of long spur, slopes WNW.
- 80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set the iron post 16 ins. in ground, mound of stone to top, cap mkd.

T6N R5E
 S5 | S4
 S8 | S9
 1963

from which

U.S.L.M. No. 1131 bears N. 2°53' E., 14.98 chs. dist.

CHAINS	
	<p>Cor. falls on steep N. slope. Land, rolling mountains. Soil, rocky. Timber, scattered juniper Undergrowth, catclaw, mesquite, mountain laurel and cactus.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10. S. 89°59' W., bet. secs. 4 and 9. Over mountainous land, through medium dense undergrowth.</p>
2.80	Spur, bears SE. and road bearing N. 60° W. and S. 60° E.
7.00	Asc. steep NE. slope.
13.50	Spur, bears S. 60° E.
16.40	Desc. steep SW. slope.
20.20	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. steep E. slope.
23.00	Asc. SE. slope.
29.50	Spur, bears S. 15° W.; desc. W. slope.
32.43	Wash, 10 lks. wide, 1 ft. deep, drains S. 15° E.; asc. steep SE. slope.
37.50	Spur, slopes S.; desc. SW. slope.
39.51	Barbed wire fence, bears N. 24° E. and S. 24° W.
40.03	Point for the ¼ sec. cor. of secs. 4 and 9. Set the iron post 20 ins. in ground, collar of stone with 2 ft. base to top, cap mkd. <div style="text-align: center;"> T6N R5E $\frac{1}{4} \begin{matrix} S & 4 \\ S & 9 \end{matrix}$ 1963 </div>
42.90	Spur, bears S. 15° W.; thence by triangulation desc. SW. slope; topography estimated.
53.00	Wash, 25 lks. wide, 2 ft. deep, drains N. 60° W.; asc. NE. slope.
67.26	Intersect line 6-1 of the Lyon lode, M.S. No. 1295, at a point from which Cor. No. 6 bears S. 38°18' E., 2.05 chains dist.
78.87	Intersect line 3-4 of the Lyon lode, M.S. No. 1295, at a point from which Cor. No. 4 bears S. 38°18' E., 9.85 chs. dist.
80.07	<p>The cor. of secs. 4, 5, 8 and 9. Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, moderately dense oak brush, mountain laurel, catclaw, palo verde, Spanish bayonet and cactus.</p> <hr/> <p>N. 0°11' E., bet. secs. 4 and 5. By triangulation, over rolling mountainous land, through dense undergrowth; topography estimated.</p>
1.52	Intersect line 3-4 of the Lyon lode, M.S. No. 1295, at a point from which Cor. No. 3 bears N. 38°18' W., 10.94 chs. dist.

CHAINS	
4.30	Wash, drains irregularly W.
8.60	Trail, bears N. 75° W. and S. 75° E.
16.16	Intersect line 6-1 of the Lyon lode, M.S. No. 1295, at a point from which Cor. No. 1 bears N. 38°18' W., 0.08 chs. dist.
21.00	Top of Gold Hill; desc. steep and broken N. slope.
39.80	Small draw, drains SW.; asc. SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 4 and 5. Set the iron post 20 ins. in ground, collar of stone with 3½ ft. base to top, cap mkd.
	T6N R5E ¼ S 5 S 4 1963
	Cor. falls on SW. slope.
47.70	Top of ridge, bears WNW. and ESE.; desc. steep NW. slope.
57.10	Wash, drains SE.
63.60	Spur, slopes ESE.; desc. W. slope.
69.00	Desc. steep NW. slope to cor.
78.00	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the township. Land, rolling mountains. Soil, rocky. Timber, scattered juniper. Undergrowth, buckbrush, mountain laurel, catclaw and cactus.
	From the cor. of secs. 20, 21, 28 and 29.
	S. 89°54' W., bet. secs. 20 and 29.
	Over rolling land.
1.00	Small wash, drains SW.
20.41	Wash, 90 lks. wide, 1 ft. deep, drains SW.
40.00	Point for the ¼ sec. cor. of secs. 20 and 29. Set the iron post 22 ins. in ground, cap mkd.
	T6N R5E ¼ S 20 S 29 1963
	Raise a small mound of stone to the N. of post.
40.50	Small wash, drains S. 15° W.
44.20	Desc. along gentle NNW. slope.
62.90	Wash, drains irregularly SSW.; asc. SE. slope.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Survey, Subdivision, T. 6 N., R. 5 E., Arizona

Set the iron post 24 ins. in ground, cap mkd.

T6N R5E
S19 | S20
S30 | S29
1963

from which

A windmill bears S. 9°08' W., 21.45 chs. dist.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Cor. falls on SE. slope.

Land, rolling.

Soil, gravelly.

Timber, none.

Undergrowth, creosote, saguaro, ocotillo and other cacti.

West, bet. secs. 19 and 30.

By triangulation asc. along steep rocky SE. slope; topography estimated.

4.00 Small spur, slopes S.

7.50 Ravine, drains S.

18.00 End of triangulation.

18.70 Crest of rocky hill, slopes S.; thence along S. slope.

Through large saguaro cacti.

30.00 Desc. steep W. slope.

40.00 Point for the ¼ sec. cor. of secs. 19 and 30.

Set the iron post 8 ins. in ground, mound of stone with 3½ ft. base to top, cap mkd.

T6N R5E
¼ S 19
S 30
1963

Cor. falls on W. slope.

52.80 Wash, 15 lks. wide, 1 ft. deep, drains SW.

58.60 Low ridge, bears SW. and NE.

69.40 Wash, 20 lks. wide, 6 ins. deep, drains SW.; asc. SE. slope.

77.50 Small wash.

79.72 Intersect E. bdy. of T. 6 N., R. 4 E.

CHAINS

Point for the C.C. of secs. 19 and 30.

Set the iron post 13 ins. in ground, mound of stone to top, cap mkd.

T6N
R4E R5E
S24 | S19 C
 | S20 C
1963

From this cor., the cor. of secs. 24 and 25, T. 6 N., R. 4 E., bears S. 0°01' E., 0.48 chs. dist.

Land, high, broken and rolling.
Soil, large lava rock and gravel.
Timber, none.
Undergrowth, thick cactus and palo verde, Spanish bayonet and scrub oak.

From the cor. of secs. 19, 20, 29 and 30.

S. 0°03' E., bet. secs. 29 and 30.

Over rolling land.

19.40 Wash, drains irregularly SSW.

34.29 Intersect N. bdy. of E.S. No. 658.

Point for the C.C. of secs. 29 and 30.

Set the iron post 24 ins. in ground, cap mkd.

T6N R5E
C C
S30 | S29
ES 658

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.

From the C.C., a stake in mound of stone as described at 101.70 chs. on line 3-4 in the official record of E.S. No. 658 bears N. 82°09' E., 21.29 chs. distance.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°03' W., bet. secs. 19 and 20.

Asc. E. slope of Lone Mountain.

8.70 Along E. slope of Lone Mountain.

16.60 Desc. NE. slope of Lone Mountain.

38.10 Wash, drains W.

40.00 Point for the ¼ sec. cor. of secs. 19 and 20.

Set the iron post 24 ins. in ground, cap mkd.

T6N R5E
¼
S19 | S20
1963

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Survey, Subdivision, T. 6 N., R. 5 E., Arizona

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.

Cor. falls on gentle SSW. slope.

50.90 Wash, drains irregularly SW.

80.00 Point for the cor. of secs. 17, 18, 19 and 20.

Set the iron post 24 ins. in ground, cap mkd.

T6N R5E
S18 | S17
S19 | S20
1963

from which

A windmill bears S. 35°12' W., 66.36 chs. dist.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.

Cor. falls on W. slope.

Land, rolling.

Soil, rocky.

Timber, none.

Undergrowth, catclaw, palo verde and cactus.

From the cor. of secs. 16, 17, 20 and 21.

S. 89°51' W., bet. secs. 17 and 20.

Over rolling land, through scattered undergrowth.

33.00 Small knoll; desc. NW. slope.

37.50 Wash, drains SW.

40.07 Point for the 1/4 sec. cor. of secs. 17 and 20.

Set the iron post 24 ins. in ground, cap mkd.

T6N R5E
1/4 S 17
S 20
1963

No accessories available.

Cor. falls on level land.

40.80 Wash, drains SSW.

50.90 Wash, drains SSW.

70.30 Unimproved road, bears N. and S.

80.14 The cor. of secs. 17, 18, 19 and 20.

CHAINS

Land, rolling.
Soil, rocky.
Timber, none.
Undergrowth, cactus and palo verde.

West, bet. secs. 18 and 19.

Over rolling hills and small washes with general drainage SSW.

- 5.40 Wash, drains SSW.
- 12.70 Wash, drains SSW.
- 32.20 Wash, drains SSW.; asc. over small spur sloping S.
- 37.70 Small draw, drains SE.; asc. along NNE. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
Set the iron post 8 ins. in ground, collar of stone to top, cap mkd.

T6N R5E
 $\frac{1}{4}$ $\frac{S 18}{S 19}$
1963

Cor. falls on NNE. slope, 40 lks. S. of a draw draining SW.

- 46.10 Spur, slopes SW.; desc. steep NW. slope.
- 53.60 Graded road, leads to mine, bears N. and S.
- 55.90 Draw, drains S.
- 70.84 Road, leads to mine, bears N. and S.; desc. NW. slope.
- 72.10 Fence line, bears N. and S.
- 79.10 Rocky wash, drains irregularly S.; asc. steep rocky NE. slope to cor.
- 79.63 Intersect E. bdy. of T. 6 N., R. 4 E.

Point for the C.C. of secs. 18 and 19.

Set the iron post 4 ins. in ground, mound of stone with 4 ft. base to top, cap mkd.

T6N
R4E R5E
S13 $\frac{S18 C}{S19 C}$
1963

From this cor. the cor. of secs. 13 and 24, T. 6 N., R. 4 E., bears S. 0°01' E., 0.91 chs. dist.

Land, rolling and broken.
Soil, decomposed granite with large boulders.
Timber, none.
Undergrowth, catclaw, palo verde and cactus.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Survey, Subdivision, T. 6 N., R. 5 E., Arizona

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 19 is at mid-point bet. C.Cs. and on the W. bdy. of the township.

Set the iron post 6 ins. in the ground, mound of stone to top, cap mkd.

T6N
R4E R5E
| $\frac{1}{4}$ S19
1963

From this cor. the $\frac{1}{4}$ sec. cor. of sec. 24, T. 6 N., R. 4 E., bears S. $0^{\circ}04'$ E., 0.68 chs. dist.

From the cor. of secs. 17, 18, 19 and 20.

N. $0^{\circ}03'$ W., bet. secs. 17 and 18.

Over rolling land, through scattered undergrowth.

2.40

Wash, drains W.

20.80

Wash, 50 lks. wide, 1 ft. deep, drains irregularly SSW.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Set the iron post 12 ins. in ground, collar of stone to top, cap mkd.

T6N R5E
 $\frac{1}{4}$
S18 | S17
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of post.

Cor. falls on E. slope, approximately 1 chain W. of a wash draining S.

46.80

Wash, drains irregularly S.

57.40

Same wash, drains irregularly S.

59.90

Same wash, drains irregularly S.

73.40

Crest of small spur, slopes SW.; desc. along W. slope.

77.10

Wash, drains irregularly S.; asc. spur sloping S.

80.00

Point for the cor. of secs. 7, 8, 17 and 18.

Set the iron post 13 ins. in ground, collar of stone to top, cap mkd.

T6N R5E
S7 | S8
S18 | S17
1963

from which

Cor. No. 3 of mining claim "Blue Boy" bears S. $74^{\circ}30'$ W., 8.85 chs. dist.

CHAINS

U.S.L.M. No. 2920 bears S. 36°11'30" W., 43.988 chs. dist.

A well being drilled bears S. 58°33' W., 43.86 chs. dist.

Cor. falls on crest of spur sloping S.

Land, rolling.

Soil, rocky.

Timber, none.

Undergrowth, palo verde and cactus.

From the true point for the cor. of secs. 8, 9, 16 and 17.

S. 89°51' W., bet. secs. 8 and 17.

Over high rolling foothills, through moderate undergrowth; along wash 150 lks. wide, 2 ft. deep, drains S. from E.

- 1.00 Leave wash.
- 5.10 Spur, slopes SW.; asc. moderate steep SE. slope.
- 10.80 Track road, bears irregularly NE. and SW.
- 13.00 Wash, 20 lks. wide, 2 ft. deep, drains S. for 50 lks. thence S. 60° W.; asc. moderate SE. slope.
- 15.70 Wash, 10 lks. wide, 1 ft. deep, drains S. for 2 chains, thence SW.
- 19.30 Bladed road, bears NE. and SW.
- 20.00 Desc. moderate SW. slope.
- 31.80 Wash, 50 lks. wide, 2 ft. deep, drains W. from NE.
- 34.50 Wash described at 31.80, drains W.
- 37.20 Leave wash; asc. SE. slope.
- 40.07 Point for the ¼ sec. cor. of secs. 8 and 17.
Set the iron post 16 ins. in ground, mound of stone to top, cap mkd.

T6N R5E

¼ $\frac{S \ 8}{S \ 17}$

1963

- 45.80 Wash, 10 lks. wide, 3 ft. deep, drains W. for 1 chain, thence S.
- 46.80 Asc. NE. slope.
- 50.00 Top of small knoll; desc. W. slope.
- 54.10 Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. E. slope.
- 62.40 Top of small hill; desc. W. slope.
- 69.56 Wash, 10 lks. wide, 1 ft. deep, drains S. from NE.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Survey, Subdivision, T. 6 N., R. 5 E., Arizona
73.50	Spur bears SW.; desc. NW. slope.
77.26	Wash, 20 lks. wide, 1 ft. deep, drains SW.; asc. SE. slope.
80.14	The cor. of secs. 7, 8, 17 and 18. Land, high hills. Soil, rocky. Timber, none. Undergrowth, catclaw, palo verde and cactus.
	West, bet. secs. 7 and 18. Over high rolling hills, through moderate undergrowth.
3.50	Small spur, slopes S. from NW.
5.80	Small spur, slopes S.
8.50	Small spur, slopes S. from N. 15° E.
10.20	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° E.; asc. E. slope.
16.00	Ridge, bears irregularly N. and S.
18.70	Spur, slopes S. 10° W.; desc. W. slope.
21.40	Bladed road, bears N. and S.
21.60	E. bank of wash, bears N. and S.
24.80	Bladed road, bears N. 30° E. and S. 30° W.
26.80	W. bank of wash, bears N. and S.; asc. E. slope.
30.30	Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.
35.00	Small spur, slopes SE.
35.90	Draw, 5 lks. wide, 2 ft. deep, drains irregularly SE.; asc. E. slope of spur sloping E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18. Set the iron post 15 ins. in ground, mound of stone with 3 ft. base to top, cap mkd. T6N R5E $\frac{1}{4}$ $\frac{S 7}{S 18}$ 1963
41.60	Spur, slopes N. 20° W. from S. 20° W.
45.00	Wash, 10 lks. wide, 18 ins. deep, drains irregularly S.; Asc. SE. slope over small spurs and draws.
64.40	High spur, slopes SE.

CHAINS	
66.60	High spur, slopes S.
67.90	Gully, 30 lks. wide, 10 ft. deep, drains S. 20° E. from NW.
78.70	Wash, 10 lks. wide, 1 ft. deep; drains S. 60° E. from NW.
79.53	Barbed wire fence, bears N. and S.
79.61	Intersect E. bdy. of T. 6 N. R. 4 E. Point for C.C. of secs. 7 and 18. Set the iron post 20 ins. in ground, cap mkd.
	T6N R4E R5E S12 S 7 C S 18C 1963
	From this cor. the cor. of secs. 12 and 13, T. 6 N., R. 4 E., bears S. 0°23' W., 1.71 chs. dist. Land, rolling. Soil, gravelly. Timber, none. Undergrowth, catclaw, manzanita and cactus.
	<hr/>
	The point for the W. ¼ sec. cor. of sec. 18 is at mid-point bet. the C.Cs. and on the W. bdy. of the township. At the cor. point Set the iron post 10 ins. in ground, mound of stone to top, cap mkd.
	T6N R4E R5E ¼ S 18 1963
	From this cor. the ¼ sec. cor. of sec. 13, T. 6 N., R. 4 E., bears S. 0°03' W., 2.15 chs. dist.
	<hr/>
	From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling hills, through scattered undergrowth.
9.60	Crest of spur, slopes SW.
13.00	Wash, drains SW.
27.90	Draw, drains S. 30° E.
33.30	Crest of spur, slopes W.
35.30	Draw drains S. 80° W.; asc. SSE. slope.
38.80	Crest of small spur, slopes SW.; thence along W. slope.
40.00	Point for the ¼ sec. cor. of secs. 7 and 8.

CHAINS	
	<p>Set the iron post 12 ins. in ground, collar of stone to top, cap mkd.</p> <p style="text-align: center;">T6N R5E $\frac{1}{4}$ S7 S8 1963</p> <p>Cor. falls on W. slope.</p>
45.10	Draw, drains S. 80° W.
56.40	Crest of spur, slopes N. 75° W.; desc. steep NNW. slope.
62.60	Wash, 40 lks. wide, 1 ft. deep, drains S. 75° W.
72.00	Crest of spur, slopes S. 30° W. to main wash which drains irregularly SSW.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	<p>Set the iron post 24 ins. in ground, cap mkd.</p> <p style="text-align: center;">T6N R5E S6 S5 S7 S8 1963</p> <p>from which</p> <p style="padding-left: 40px;">Cor. No. 3 of mining claim "Catherine" bears N. 42°53' E., 2.90 chs. dist.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of post.</p> <p>Land, high rolling hills. Soil, rocky. Timber, none. Undergrowth, catclaw, palo verde and cactus.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°48' W., bet. secs. 5 and 8.</p> <p>By triangulation over rolling mountains, through dense undergrowth.</p>
12.00	Small spur, slopes N.; end of triangulation.
23.00	Desc. W. slope.
40.06	Point for the ¼ sec. cor. of secs. 5 and 8.
	<p>Set the iron post 18 ins. in ground, cap mkd.</p> <p style="text-align: center;">T6N R5E $\frac{1}{4}$ $\frac{S 5}{S 8}$ 1963</p>
48.75	Thence by triangulation, topography estimated.
64.77	Intersect line 1-2 of the Catherine lode, M.S. No. 1984 at a point from which Cor. No. 2 bears N. 39°08' W., 10.44 chs. dist.
72.00	Desc. steep W. slope to cor.
76.43	Intersect line 3-4 of the Catherine lode, M.S. No. 1984 at a point from which Cor. No. 3 bears N. 39°08' W., 2.72 chs. dist.
80.12	The cor. of secs. 5, 6, 7 and 8.
	<p>Land, mountainous. Soil, rocky. Timber, none; undergrowth, dense mountain laurel on N. slopes, cactus, palo verde and oakbrush.</p>

CHAINS

West, bet. secs. 6 and 7.

By triangulation, over fairly level land first 1/3 mile, then over rolling mountains, through undergrowth; topography estimated.

0.80 Asc. steep E. bank of wash.

3.00 Edge of bank, bears N. and S.

18.00 Desc. WNW. slope to wash.

26.00 Wash, drains irregularly S.; track road in wash.

30.00 Crest of spur, slopes S.; desc. steep SW. slope.

36.00 Wash, drains SE., track road in wash.

40.00 Point for the 1/4 sec. cor. of secs. 6 and 7.

Set the iron post 6 ins. in ground, collar of stone to top, cap mkd.

T6N R5E
 1/4 S 6
 S 7
 1963

Cor. falls on steep rocky NNE. slope.

End of triangulation.

47.50 By triangulation, asc. NE. slope, through dense mountain laurel; topography estimated.

72.00 Desc. NW. slope.

79.41 Intersect E. bdy. T. 6 N., R. 4 E.

Point for the C.C. of secs. 6 and 7.

Set the iron post 4 ins. in ground, collar of stone with 3 1/2 ft. base to top, cap mkd.

T6N
 R4E R5E
 S 1 | S 6 C
 S 7 C
 1963

From this cor. the cor. of secs. 1 and 2, T. 6 N., R. 4 E., bears S. 0°09' W., 2.12 chs. dist.

Land, rolling mountains.

Soil, shale.

Timber, scattered juniper.

Undergrowth, dense mountain laurel on N. slopes, scrub oak and cactus.

The point for the W. 1/4 sec. cor. of sec. 7 is at mid-point bet. the C.Cs. and on the W. bdy. of the township.

At the cor. point

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Survey, Subdivision, T. 6 N., R. 5 E., Arizona

Set the iron post 10 ins. in the ground, mound of stone to top, cap mkd.

T6N
R4E R5E
| 1/4 S7
1963

From this cor. the 1/4 sec. cor. of sec. 12, T. 6 N., R. 4 E., bears S. 0°01' E., 2.68 chs. dist.

The point for the W. 1/4 sec. cor. of sec. 6, is 40.00 chs. in northing from the C.C. of secs. 6 and 7.

Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.

T6N
R4E R5E
| 1/4 S6
1963

From this cor. the 1/4 sec. cor. of sec. 1, T. 6 N., R. 4 E., bears S. 0°03' W., 1.84 chs. dist.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°14' E., bet. secs. 5 and 6.

By triangulation over high rolling land, through scattered undergrowth; topography estimated.

- 1.00 Asc. N. bank of wash.
- 17.00 Crest of spur, slopes SW.
- 19.00 Draw, drains SW.; asc. SW. slope.
- 27.00 Crest of spur, slopes S. 75° E.
- 32.00 Head of draw, drains S. 75° E.; asc. steep S. slope to cor.
- 40.00 Point for the 1/4 sec. cor. of secs. 5 and 6.

Set the iron post 12 ins. in ground, mound of stone with 2 1/2 ft. base to top, cap mkd.

T6N R5E
1/4
S6 | S5
1963

Cor. falls on steep S. slope.

End of triangulation.

- 43.20 Crest of spur, slopes SW.; by triangulation desc. steep NW. slope; topography estimated.

CHAINS

68.00 Draw, drains SW.; asc. steep SW. slope to cor.

78.16 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the township.

Land, rolling mountains.

Soil, rocky.

Timber, scattered juniper.

Undergrowth, catclaw, sage, mountain laurel and cactus.

General Description

Township 6 North, Range 5 East has two main types of land. The northern part of the township is predominately high rolling mountains broken by many steep, sloping spurs and deep ravines and washes. The vegetation in this area consists mostly of catclaw, palo verde and cactus. However, farther north there is no palo verde and very little cactus. Along the north boundary there is a heavy growth of mountain laurel and oak brush on the north slopes. Spanish bayonet is also found in this area. The soil is of a rocky nature and is mostly decomposed granite. The southern part of the township is low rolling land broken by many small washes. There is a heavy growth of palo verde in spots and medium growth throughout. The undergrowth consists of catclaw, mesquite and cactus with cholla and saguaro the prevailing cacti. The soil ranges from sandy to gravelly.

Elevation in the township ranges from 4,535 feet above sea level on Continental Mountain, which is at the quarter section corner on the west boundary of section 7, to 3,259 feet above sea level at Wildcat Hill in section 27.

The west half of the township has a general southwest drainage with some south drainage in the northern part. The east half of the township drains south or southeast into Camp Creek. There was no running water in the township and only two places have permanent water sources; one is a well by Camp Creek in section 2 and the other is a large storage tank which is part of the Tonto Hills Real Estate development in the southeast quarter of section 9.

The paved highway from Cave Creek to Bartlett Dam and Seven Springs cuts across sections 31, 32, 28, 22 and 15. In section 22 the highway forks and a dirt road goes east to Bartlett Dam. The paved road goes north to Seven Springs where in section 15 the pavement ends and a graded road commences.

The most important development at the present time is real estate. The Tonto Hills Company has land in sections 10 and 15. One home has been built in section 10 and is now occupied. There are no other homes being built at this time. There are a number of mineral claims in the township but no mining activity was noticed. Most of the township is being used for limited grazing of livestock.

BOOK 4000

Form 4-680
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Wallace R. Ott	Transit
Alan R. Crockett	Notes
Phil G. Bowler	Chainman
Harold V. Merideth	Cornerman
Larry L. Carson	Flagman
Jack R. Bowker	Notes
Kenneth D. Herman	Axeman and Notes
Tom D. Carter	Chainman
Clarence Bell, Jr.	Flagman and Cornerman
Fred R. Coe	Flagman and Cornerman
Alfonso Cardenas, Jr.	Cornerman
Henry A. Guerrero	Cornerman

40

CERTIFICATE OF SURVEY

WE, Boyd S. Owens, Gary W. Rutledge, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 22 day of April, 19 63,

WE have dependently resurveyed the west boundary, and surveyed the east and north boundaries, sections 4 through 9, 16 through 21, and 29 through 30 of Township 6 North, Range 5 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 21, 1963 (Date)

Boyd S. Owens (Cadastral Surveyor) Boyd S. Owens

June 21, 1963 (Date)

Gary W. Rutledge (Cadastral Surveyor) Surveying Technician Gary W. Rutledge

CERTIFICATE OF APPROVAL Bureau of Land Management

The foregoing field notes of the dependent resurvey of the west boundary, survey of the east and north boundaries, and of sections 4 through 9, 16 through 21, and 29 through 30, of Township 6 North, Range 5 East of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens, Cadastral Surveyor, and Gary W. Rutledge, Surveying Technician having been critically examined and found correct, are hereby approved.

Washington, D. C. MAR 13 1964 (Date)

[Signature] (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)