

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

North, South, East and West Boundaries

and the

Subdivisional Lines

of

Township 15 North, Range 28 East

Of the _____ Gila and Salt River _____ Meridian,

In the State of _____ Arizona _____.

EXECUTED BY

Leonard W. Murphy, Cadastral Surveyor

Wallace R. Ott, Survey Technician

Under special instructions dated _____ March 14 _____, 1963 _____, which provided for the surveys
included under Group Number _____ 390 _____, approved _____ March 18, 1963 _____,
and assignment instructions dated _____ July 2 _____, 19 63 _____.

Survey commenced _____ July 10 _____, 19 63 _____

Survey completed _____ August 21 _____, 19 63 _____

14

4000

INDEX DIAGRAM

Township 15 North, Range 28 East

	6	5	4	3	3	1	
19	6 54 53	5 45 53	4 38 44	3 32 38	2 26 31	1 25 25	15
18	7 52 52	8 43 51	9 37 43	10 31 36	11 24 30	12 24 24	14
18	18 50 50	17 42 49	16 36 42	15 30 35	14 23 29	13 23 23	14
17	19 48 48	20 41 47	21 35 40	22 28 34	23 22 28	24 22 22	13
16	30 47 46	29 40 46	28 33 39	27 27 33	26 21 27	25 20 20	12
16	31 45	32 38	33 32	34 26	35 20	36 12	12
	11	10	9	8	8	7	

CHAINS

The north boundary was surveyed in 1882 by H. A. Coe. The east boundary was surveyed in 1882 by M. Santee. The south boundary was surveyed in 1875 by C. B. Foster. The south boundary was dependently resurveyed and west boundary and subdivisional lines surveyed in 1882 by A. P. Johnson.

The following field notes are those of the dependent resurvey of the township exteriors and the subdivisional lines of Township 15 North, Range 28 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 14, 1963.

An extensive retracement was necessary to positively identify the corners as only a very small percentage of the corners was found.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top. The original corner monument is buried alongside the iron post unless otherwise described.

The geographic position of the southeast corner of the township as computed from U.S.C. & G.S. Triangulation Station WITCH is: Latitude 34°39'35" N. and Longitude 109°18'50" W.

The average magnetic declination was found to be 13°30' East.

Dependent Resurvey, North Boundary, T15N, R28E, Arizona

Reestablishment of the Survey executed in 1882
by Henry A. Coe

Point for the cor. of Ts. 15 and 16 N., R. 28 and 29 E., at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N	
R28E	R29E
S36	S31
S 1	S 6
T15N	
1963	

from which

USC&GS Triangulation Station WITCH, a standard disk set in concrete, bears N. 31°27' E., 107.90 chains dist.

CHAINS

The cor. of secs. 25, 30, 31 and 36, T16N, Rs. 28 and 29 E., bears N. $1^{\circ}11'$ E., 80.18 chs. dist., described in current resurvey of Township 16 North, Range 28 East under this same group.

The cor. of secs. 2, 3, 34 and 35, Ts. 15 and 16 N., R. 29 E., monumented by a basalt stone, 11x6x3 ins., loosely set, marked with 4 notches on the W. and 2 notches on the E. edges, bears N. $89^{\circ}55'$ E., 328.96 chs. dist.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R29E
 $\frac{S34}{S3} | \frac{S35}{S2}$
 T15N
 1963

from which

Raise a small mound of stone N. of cor.

The centerline of U.S. Highway No. 666 bears West, 18.60 chs. dist.

Thence from the cor. of Ts. 15 and 16 N., Rs. 28 and 29 E.

N. $89^{\circ}54'$ W., bet. secs. 1 and 36.

Over level land, through sparse timber.

40.18 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E
 $\frac{1}{4} \frac{S36}{S1}$
 T15N
 1963

Raise a small mound of stone N. of cor. deposit glass bottle at base of post.

75.20 Barbed wire fence, bears irregularly NW. and SE.

78.35 Unimproved road, bears N. and S.

80.36 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E
 $\frac{S35}{S2} | \frac{S36}{S1}$
 T15N
 1963

CHAINS					
	<p>from which</p> <p style="padding-left: 40px;">A windmill bears N. 7°19' W., 14.27 chs. dist.</p> <p>Raise a small mound of stone N. of cor.; deposit glass at base of post.</p> <p>Land, level. Soil, sandy clay. Timber, scattered cedar; undergrowth, blue sage and grasses.</p> <hr/> <p>N. 89°54' W., bet. secs. 2 and 35.</p> <p>Over level land, through scattered timber.</p>				
33.10	Enter into area of dense timber, bears NE. and SW.				
35.00	Unimproved road, bears NE. and SW.				
40.18	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R28E</p> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 35</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 2</td> </tr> </table> <p>T15N 1963</p> </div> <p>Raise a small mound of stone N. of cor.; deposit glass bottle at base of post.</p>	1/4	S 35		S 2
1/4	S 35				
	S 2				
80.36	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R28E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S34</td> <td style="padding: 0 5px;">S35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> </table> <p>T15N 1963</p> </div> <p>Raise a small mound of stone N. of cor.; no bearing trees available.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered cedar; undergrowth, low sage and grasses.</p> <hr/> <p>N. 89°54' W., bet. secs. 3 and 34.</p> <p>Over gently rolling sand hills.</p>	S34	S35	S 3	S 2
S34	S35				
S 3	S 2				
20.90	<p>Low sandy ridge, bears N. and S.; desc. to gently rolling grassland.</p>				

CHAINS	
40.18	<p>Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E $\frac{1}{4} \frac{S \ 34}{S \ 3}$ T15N 1963</p> <p>Raise a small mound of stone N. of cor.</p>
80.36	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E $\frac{S33}{S4} \mid \frac{S34}{S3}$ T15N 1963</p> <p>Deposit glass bottle at base of post; no bearing trees available.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered cedar; undergrowth, blue sage and grasses.</p>
<p>N. 89°54' W., bet. secs. 4 and 33.</p>	
<p>Over gently rolling land.</p>	
8.20	<p>Enter into moderate stand of cedar, bears NE. and SW.</p>
24.10	<p>Descend gentle W. slope of sand hill.</p>
40.18	<p>Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E $\frac{1}{4} \frac{S \ 33}{S \ 4}$ T15N 1963</p> <p>Deposit glass bottle at base of post.</p>
46.40	<p>South end of dam for earthen reservoir, bears approx. N. 80° W.; also unimproved road, bears N. 60° W., and S. 60° E.</p>
50.20	<p>Wash, 200 lks. wide, 2 ft. deep, drains S. from dam.</p>
71.50	<p>Unimproved road, bears N. 45° E. and S. 45° W.; asc. gentle E. slope.</p>

CHAINS					
80.36	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td>S5</td> <td>S4</td> </tr> </table> <p>T15N 1963</p> </div> <p>Deposit glass bottle at base of post.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered cedar; undergrowth, low sage.</p> <hr/>	S32	S33	S5	S4
S32	S33				
S5	S4				
4.15	<p>Wash, 20 lks. wide, 2 ft. deep, drains SE., from N.</p>				
40.18	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>$\frac{1}{4}$ S 32</td> <td></td> </tr> <tr> <td>S 5</td> <td></td> </tr> </table> <p>T15N 1963</p> </div> <p>Raise a small mound of earth and stone N. of cor.; deposit glass at base of post.</p>	$\frac{1}{4}$ S 32		S 5	
$\frac{1}{4}$ S 32					
S 5					
49.00	<p>Wash, 30 lks. wide, 1 ft. deep, drains S.</p>				
62.20	<p>Unimproved road, bears N. 10° W. and S.</p>				
62.60	<p>Wash, 30 lks. wide, 2 ft. deep, drains S.</p>				
80.36	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td>S6</td> <td>S5</td> </tr> </table> <p>T15N 1963</p> </div> <p>Raise a small mound of stone N. of cor.; deposit glass at base of post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none; undergrowth, blue sage and grasses.</p> <hr/>	S31	S32	S6	S5
S31	S32				
S6	S5				

6

CHAINS

N. 89°54' W., bet. secs. 6 and 31.

Over nearly level land, through sparse timber.

- .40 South end of earthen reservoir, bears NW. and SE.
- 2.00 Wash, 80 lks. wide, 4 ft. deep, drains S.
- 7.00 Wash, 100 lks. wide, 1 ft. deep, drains SE.
- 37.10 Wash, 50 lks. wide, 2 ft. deep, drains SE.

40.18 The ¼ sec. cor. of secs. 6 and 31, monumented by petrified wood 12x10x6 ins. lying loosely on the ground, dimly marked with ¼ on one side. This point accepted as the original position of the ¼ sec. cor.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

¼ $\frac{S\ 31}{S\ 6}$

T15N

1963

Deposit glass at base of post.

N. 89°54' W., bet. secs. 6 and 31, beginning new measurement.

- 39.76 The cor. of secs. 1, 6, 31 and 36, Ts. 15 and 16 N., Rs. 27 and 28 E., monumented by a sandstone, 18x12x6 ins., loosely set and faintly marked. This is the only sandstone in area and is at intersection of fences extending N., S. and generally W.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N
R27E R28E

$\frac{S36\ | \ S31}{S\ 1\ | \ S\ 6}$

T15N

1963

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.; deposit glass at base of post.

Land, nearly level.

Soil, clay.

Timber, scattered cedar; undergrowth, sparse sage.

Dependent Resurvey, South Boundary, T15S, R28E, Arizona

Reestablishment of the Survey in 1882

by A. P. Johnson

CHAINS

Point for the cor. of Ts. 14 and 15 N., Rs. 28 and 29 E. monumented by a large mound of stone set in corner of fences bearing generally N., S., E. and W. This mound is accepted locally as the cor. and was verified by Mr. Charles R. Jarvis, adjacent property owner since 1907.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T15N
R28E R29E
S36 | S31
S 1 | S 6
T14N
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of corner.

N. 89°59' W., along the S. bdy. of sec. 36.

Over rolling land, through scattered timber and undergrowth.

Asc. gentle slope along the N. side of a barbed wire fence.

35.00 Leave rolling sand hills; thence across level grass land.

41.11 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground with cap mkd.

T15N R28E
1/4 S 36
S 1
T14N
1963

Raise a small mound of earth and stone N. of cor.

Continue over level grass land.

82.21 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T15N R28E
S35 | S36
S 2 | S 1
T14N
1963

Raise a small mound of earth and stone W. of cor.

Land, mostly level.

Soil, sandy.

Timber, sparse cedar; undergrowth, sagebrush and grasses.

8

CHAINS

N. 89°59' W., bet. secs. 2 and 35.

Over level grass land.

41.11

The ¼ sec. cor. of secs. 2 and 35, monumented by a sandstone, 14x10x4 ins., loosely set, marked ¼ on one side.

At the corner point.

Set the post 20 ins. in the ground, cap mkd.

T15N R28E

¼ S 35
S 2

T14N

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.; cor. falls on level land.

West, bet. secs. 2 and 35, beginning new measurement.

Over gently rolling land.

23.70

Unimproved road, bears irregularly NW. and SE.

25.70

Asc. gentle slope and enter into moderate growth of cedars.

33.00

Cross rocky N. slope.

40.43

The cor. of secs. 2, 3, 34 and 35, monumented by a sandstone 14x12x3 ins., firmly set, marked with 4 notches on W. and 2 notches on E. edges, set in mound of earth.

At the corner point

Set the post 4 ins. in the ground on solid rock, and in a mound of stone to top, cap mkd.

T15N R28E

S34 | S35
S 3 | S 2

T14N

1963

Cor. falls on gentle N. slope.

Land, level E. 65 chains, gently rolling W. 15 chains.
Soil, sandy and rocky.
Timber, scattered cedars; undergrowth, sagebrush and grasses.

S. 89°57' W., bet. secs. 3 and 34.

Over broken sand hills.

1.05

Barbed wire fence, bears N. and S.

1.35

Sandstone bluff, bears N. and S. 15° E.; thence over small, broken sandstone hills.

CHAINS	
6.80	Desc. 20 ft. over SW. slope, thence over level ground.
30.50	Asc. gentle NE. slope and enter into moderate growth of cedars.
39.90	Desc. 10 ft. over W. slope.
40.45	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate distance, there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	T15N R28E $\frac{1}{4}$ $\frac{S\ 34}{S\ 3}$ T14N 1963
	Raise a small mound of earth and stone N. of cor.; cor. falls on level land.
42.15	Wash, 10 lks. wide, 1 ft. deep, drains N. from S. 10° E.
60.05	Wash, 30 lks. wide, 1 ft. deep, drains N. 15° E.
62.00	Asc. 12 ft. over sandstone ledge, bears NE. and SW.
64.65	Wash, 5 lks. wide, 1 ft. deep, drains irregularly NE.
69.75	Small wash, drains NE.
77.90	Sandstone bluff, bears NE. and SW.; desc. 25 ft. to cor.
80.90	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 22 ins. in the ground, cap mkd.
	T15N R28E $\frac{S33\ S34}{S4\ S3}$ T14N 1963
	Raise small mound of earth and stone W. of cor.
	Land, broken sandstone hills. Soil, sandy. Timber, scattered cedars; undergrowth, sagebrush and grasses.
	S. 89°57' W., bet. secs. 4 and 33.
	Over nearly level grass land.
1.45	Unimproved road, bears N. 80° E. and S. 80° W.
16.40	Barbed wire fence, bears N. 30° E. and S. 30° W.
29.80	Gulley, 15 lks. wide, 4 ft. deep, drains NW. into Zuni River.

10

CHAINS

40.45 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 10 ins. in the ground and in a collar of stone to top, cap mkd.

T15N R28E

$\frac{1}{4} \frac{S \ 33}{S \ 4}$

T14N
1963

Cor. falls on level land.

44.79 Zuni River, 40 lks. wide, 4 ft. deep, drains S. 10° W. for 2 chs., then S. 60° W.

53.30 Wash, 25 lks. wide, 3 ft. deep, drains SW.

80.55 Barbed wire fence, bears N. and S.

80.90 Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 20 ins. in the ground, cap mkd.

T15N R28E

$\frac{S32 \ S33}{S \ 5 \ S \ 4}$

T14N
1963

Deposit glass; cor. falls 35 lks. W. of N. and S. fence.

Land, nearly level.

Soil, sandy.

Timber, none; undergrowth, dense growth of salt cedar along banks of Zuni River.

S. 89°57' W., bet. secs. 5 and 32.

Over level land, no timber.

21.55 Dim truck road, bears N. 20° E. and S.

40.45 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

$\frac{1}{4} \frac{S \ 32}{S \ 5}$

T14N
1963

Deposit glass.

54.00 Arroyo, 30 lks. wide, 3 ft. deep, drains SW.

80.90 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

CHAINS		
	<p>Set the post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{S31}{S6} \frac{S32}{S5}$ T14N 1963</p> <p>Deposit glass; raise small mound of earth and stone N. of corner.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, sagebrush and shadscale.</p>	
<p>10.40</p> <p>34.10</p> <p>40.45</p>	<p>S. 89°57' W., bet. secs. 6 and 31.</p> <p>Over level grass land, no timber.</p> <p>Wash, 30 lks. wide, 1 ft. deep, drains SW.</p> <p>Small arroyo, 10 lks. wide, 3 ft. deep, drains SW.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p>	
<p>58.60</p>	<p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{1}{4} \frac{S31}{S6}$ T14N 1963</p> <p>Deposit glass; E. and W. fenceline bears S., 20 lks. distant.</p> <p>Arroyo, 30 lks. wide, 3 ft. deep, drains SW.</p>	
<p>79.89</p>	<p>The cor. of Ts. 14 and 15 N., Rs. 27 and 28 E., monumented by a mound of stone set in fence cor. from which fences extend N., E. and W. This fence cor. is accepted locally as the corner.</p> <p>At the corner point</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R27E R28E $\frac{S36}{S1} \frac{S31}{S6}$ T14N 1963</p> <p>Raise a mound of earth and stone S. of cor.</p> <p>Land, level. Soil, sandy. Timber, none; undergrowth, shadscale and grasses.</p>	

12

CHAINS

Dependent Resurvey, East Boundary, T15N, R28E, Arizona

Reestablishment of the Survey in 1882 by M. Santee

From the cor. of Ts. 14 and 15 N., Rs. 28 and 29 E.

N. 0°28' W., bet. secs. 31 and 36.

Over gently rolling land, through low vegetations, no timber.

Desc. gentle N. slope.

40.08 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N
R28E R29E
½
S36 | S31
1963

Deposit glass at base of post.

80.16 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T15N
R28E R29E
S25 | S30
S36 | S31
1963

Raise a small mound of earth and stone W. of cor.

Land, gently rolling.

Soil, sandy loam.

Timber, none; undergrowth, sagebrush and grasses.

N. 0°28' W., bet. secs. 25 and 30.

Over gently rolling land, no timber.

31.65 Barbed wire fence, bears irregularly NE. and SW.

36.65 S. bank of Zuni River, 10 ft. high, bears N. 85° E. and S. 75° W.

38.85 N. bank of Zuni River, 4 ft. high, same general bearing; asc. gentle slope.

40.08 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

CHAINS		
	<p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E R29E $\frac{1}{4}$ S25 S30 1963</p> <p>from which</p> <p style="padding-left: 40px;">A windmill bears S. 32° E., 18.35 chs. dist.</p> <p>Deposit glass at base of post.</p>	
75.70	<p>Barbed wire fence, bears N. 80° W. and S. 80° E.</p>	
80.16	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E R29E S24 S19 S25 S30 1963</p> <p>Deposit glass at base of post.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, none; undergrowth, sagebrush and grasses.</p>	
	<p>N. 0°28' W., bet. secs. 19 and 24.</p> <p>Over nearly level land.</p>	
24.00	<p>Asc. gentle S. slope.</p>	
40.08	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E R29E $\frac{1}{4}$ S24 S19 1963</p> <p>Deposit glass at base of post.</p>	
61.00	<p>Over level land.</p>	
80.16	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>	

CHAINS

T15N
R28E R29E
S13 | S18
S24 | S19
1963

Deposit glass at base of post.

Land, nearly level.

Soil, sandy.

Timber, none; undergrowth, sagebrush and grasses.

N. 0°28' W., bet. secs. 13 and 18.

Over gently rolling land, no timber.

27.65 Old track road, bears generally SW. and NE.

37.00 Track road, bears NE. and SW.

40.08 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N
R28E R29E
1/4
S13 | S18
1963

Deposit charcoal at base of post.

80.16 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N
R28E R29E
S12 | S7
S13 | S18
1963

Deposit charcoal at base of post.

Land, gently rolling.

Soil, sandy loam.

Timber, none; undergrowth, sagebrush.

N. 0°28' W., bet. secs. 7 and 12.

Over gently rolling land, through scattered timber.

40.08 Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

CHAINS	
	<p style="text-align: center;">T15N R28E R29E $\frac{1}{4}$ S12 S7 1963</p> <p>Deposit charcoal at base of post.</p> <p>45.10 Barbed wire fence, bears E. and W.</p> <p>45.70 Track road, bears W. and E. for one chain, thence S.</p> <p>80.16 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R28E R29E S 1 S6 S12 S7 1963</p> <p>Deposit charcoal at base of post.</p> <p>Land, gently rolling. Soil, sandy. Timber, scattered cedar; undergrowth, sagebrush.</p>
	<hr/> <p>N. 0°28' W., bet. secs. 1 and 6.</p> <p>Asc. gentle S. slope, through scattered timber.</p> <p>4.00 Barbed wire fence, bears NW. and SE.</p> <p>37.30 Over gently rolling hills.</p> <p>40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R28E R29E $\frac{1}{4}$ S 1 S6 1963</p> <p>Deposit glass at base of post.</p> <p>80.16 The cor. of Ts. 15 and 16 N., Rs. 28 and 29 E.</p> <p>Land, gently rolling hills. Soil, sandy. Timber, scattered cedar; undergrowth, moderate sagebrush and grasses.</p>
	<hr/> <p>Dependent Resurvey, West Boundary, T15N, R28E, Arizona</p> <hr/>

16

CHAINS

Reestablishment of the Survey in 1882 by A. P. Johnson

From the cor. of Ts. 14 and 15 N., Rs. 27 and 28 E.

N. 0°09' E., bet. secs. 31 and 36.

Along a fenceline.

8.00 Asc. gentle SE. slope.

13.10 Dim track road, bears N. 70° W. and E.

30.00 Over level land.

39.00 Desc. gentle N. slope of hill.

40.16 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N
R27E R28E
¼
S36 | S31
1963

Deposit glass at base of post; cor. falls in N. and S. fenceline.

43.00 Over level land.

71.50 Enter gently rolling land.

80.32 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N
R27E R28E
S25 | S30
S36 | S31
1963

Deposit glass at base of post; cor. set in N. and S. fenceline.

Land, gently rolling hills.

Soil, sandy.

Timber, none; undergrowth, grass.

N. 0°09' E., bet. secs. 25 and 30.

Over gently rolling land, no timber.

40.16 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

CHAINS	
	<p style="text-align: center;">T15N R27E R28E $\frac{1}{4}$ S25 S30 1963</p> <p>Deposit glass at base of post; N. and S. fenceline bears W. 4 lks. dist.</p>
80.32	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R27E R28E S24 S19 S25 S30 1963</p> <p>Deposit glass at base of post; cor. set in N. and S. fenceline.</p> <p>Land, gently rolling hills. Soil, sandy. Timber, none; undergrowth, grass and sagebrush.</p>
	<p>N. 0°09' E., bet. secs. 19 and 24.</p> <p>Over gently rolling hills, no timber.</p>
1.50	<p>Track road, bears E. and SW.</p>
40.16	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R27E R28E $\frac{1}{4}$ S24 S19 1963</p> <p>Raise a small mound of stone W. of cor.; cor. set 9 lks. E. of N. and S. fenceline.</p>
49.50	<p>Asc. rocky S. slope of ridge bearing generally E. and W.</p>
60.80	<p>Rim of mesa top, bears N. 85° E. and S. 80° W.</p>
80.32	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 15 ins. in the ground to bedrock, and in a mound of stone to top, cap mkd.</p>
	<p style="text-align: center;">T15N R27E R28E S13 S18 S24 S19 1963</p>

CHAINS

Deposit glass at base of post; cor. set 7 lks. E. of N. and S. fenceline.

Land, gently rolling.
Soil, rocky.
Timber, none; undergrowth, sagebrush and grasses.

N. 0°09' E., bet. secs. 13 and 18.

Over gently rolling land, through moderate growth of low grass.

40.16 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N
R27E R28E
1/4
S13 | S18
1963

Deposit glass at base of post; cor. set 8 lks. E. of N. and S. fenceline.

80.32 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground and in a small collar of stone to top, cap mkd.

T15N
R27E R28E
S12 | S7
S13 | S18
1963

Deposit glass at base of post; cor. set 11 lks. E. of N. and S. fenceline.

Land, gently rolling hills.
Soil, sandy.
Timber, none; undergrowth, sagebrush and grasses.

N. 0°09' E., bet. secs. 7 and 12.

Over gently rolling land, no timber.

14.45 Track road, bears SW. and E.

40.16 The 1/4 sec. cor. of secs. 7 and 12, monumented by a sandstone, badly weathered but firmly set in mound of stone, charcoal at base of stone.

At the corner point

Set the post 22 ins. in the ground, cap mkd.

CHAINS	
	<p style="text-align: center;">T15N R27E R28E $\frac{1}{4}$ S12 S7 1963</p> <p>Deposit glass at base of post; cor. falls on gentle ridge bearing E. and W.; E. and W. fence bears S. 20 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°17' W., bet. secs. 7 and 12, beginning new measurement.</p> <p>Desc. over gentle N. slope of mesa.</p> <p>20.40 Wash, 100 lks. wide, 3 ft. deep, drains SE.</p> <p>21.70 Wash, 60 lks. wide, 2 ft. deep, drains SE.</p> <p>27.35 Wash, 120 lks. wide, 3 ft. deep, drains SE.</p> <p>40.31 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R27E R28E <u>S 1 S 6</u> S12 S7 1963</p> <p>Deposit glass at base of post; raise a small mound of stone W. of cor.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, none; undergrowth, sagebrush.</p>
	<hr/> <p>N. 0°17' W., bet. secs. 1 and 6.</p> <p>Over rolling land, no timber.</p> <p>1.30 Wash, 100 lks. wide, 4 ft. deep, drains SE. into a wash draining S.</p> <p>21.70 Asc. S. slope over clay hills.</p> <p>40.31 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 14 ins. in the ground to hardpan and in a mound of stone, 2 ft. base to top, cap mkd.</p> <p style="text-align: center;">T15N R27E R28E $\frac{1}{4}$ S 1 S 6 1963</p> <p>Deposit glass at base of post.</p>

CHAINS

- 76.30 Desc. gentle N. slope to the corner.
- 80.31 The cor. of Ts. 15 and 16 N., Rs. 27 and 28 E.
Land, gently rolling.
Soil, sandy clay.
Timber, none; undergrowth, sagebrush and grasses.

- Dependent Resurvey, Subdivisional Lines, T15N, R28E
Arizona

- Reestablishment of the Survey in 1882 by A. P. Johnson

- From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township.
N. 0°35' E., bet. secs. 35 and 36.
Over gently rolling grassland, no timber.
- 40.14 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
Set the post 24 ins. in the ground, cap mkd.

T15N R28E
1/4
S35|S36
1963

Deposit glass at base of post; raise a small mound of stone W. of corner.
- 57.00 Barbed wire fence, bears irregularly E. and W.
- 58.75 Zuni River, 75 lks. wide, 5 ft. deep, drains S. 70° W.
- 76.60 Wash, 80 lks. wide, 1 ft. deep, drains SW. into Zuni River.
- 80.28 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
Set the post 24 ins. in the ground, cap mkd.

T15N R28E
S26|S25
S35|S36
1963

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.; deposit glass at base of post.

Land, gently rolling hills.
Soil, sandy.
Timber, none; undergrowth, low sagebrush and grasses.

- From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the township.
N. 89°55' W., bet. secs. 25 and 36.

CHAINS	
	Over low rolling hills, no timber.
9.60	Wash, 10 lks. wide, 3 ft. deep, drains N. 10° W. into Zuni River.
28.60	Barbed wire fence, bears N. and S. for 1 chain, then S. 45° W.
38.90	East bank of Zuni River, 4 ft. high, bears S. 40° W.
40.39	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner. Corner position falls in center of Zuni River where point cannot be monumented.
40.90	West bank of Zuni River, 3 ft. high, bears S. 40° W.
41.39	Point selected for the witness ¼ sec. cor. of secs. 25 and 36. Set the post 24 ins. in the ground, cap mkd. <div style="text-align: center;"> T15N R28E WC ¼ $\frac{S\ 25}{S\ 36}$ 1963 </div>
80.78	Deposit glass at base of post. The cor. of secs. 25, 26, 35 and 36. Land, nearly level. Soil, sandy. Timber, none; undergrowth, dense sagebrush and grasses.
40.14	N. 0°33' W., bet. secs. 25 and 26. Over nearly level land, through dense low undergrowth. Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd. <div style="text-align: center;"> T15N R28E ¼ S26 S25 1963 </div>
79.28	Deposit glass at base of post. Barbed wire fence, bears E. and W.
80.28	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd. <div style="text-align: center;"> T15N R28E S23 S24 S26 S25 1963 </div>

CHAINS		
	<p>Raise a small mound of earth and stone W. of cor.; deposit glass at base of post.</p> <p>Land, nearly level. Soil, sandy. Timber, none; undergrowth, sagebrush.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township.</p> <p>N. 89°50' W., bet. secs. 24 and 25.</p> <p>Over gently rolling hills, no timber.</p>	
25.10	Top of small ridge, bears N. 15° W. and S. 10° E.; desc. gentle slope.	
38.60	Middle of small dry pond, 80 lks. wide, and 80 lks. long.	
40.47	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.	
	Set the post 24 ins. in the ground, cap mkd.	
	<p>T15N R28E</p> <p>¼ $\frac{S\ 24}{S\ 25}$</p> <p>1963</p>	
	Raise a small mound of earth and stone N. of corner.	
60.40	Top of low spur, bears N. 35° W. and S. 15° E.	
80.94	The cor. of secs. 23, 24, 25 and 26.	
	Land, nearly level. Soil, sandy. Timber, none; undergrowth, low sagebrush and grasses.	
	N. 0°53' W., bet. secs. 23 and 24.	
	Over gently rolling hills.	
16.00	Top of low spur, slopes W.; desc. N. slope.	
28.65	Wash, 75 lks. wide, 3 ft. deep, drains irregularly SW.	
40.14	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.	
	Set the post 24 ins. in the ground, cap mkd.	
	<p>T15N R28E</p> <p>¼ $\frac{S23}{S24}$</p> <p>1963</p>	
	Raise a small mound of stone W. of the corner.	
80.28	The cor. of secs. 13, 14, 23 and 24, monumented by the original sandstone, 15x10x4 ins., firmly set, dimly mkd.	

CHAINS

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
 $\frac{S14}{S23} | \frac{S13}{S24}$
 1963

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.; deposit glass at base of post.

Land, gently rolling hills.
 Soil, sandy.
 Timber, none; undergrowth, sagebrush.

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township.

N. 89°44' W., bet. secs. 13 and 24.

Over nearly level land, through low vegetation, no timber.

40.78 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
 $\frac{1}{4} \frac{S 13}{S 24}$
 1963

from which

A windmill bears N. 29° E., 8.19 chs. dist.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.; deposit glass at base of post.

68.90 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.

70.80 Asc. gentle E. slope to cor.

81.56 The cor. of secs. 13, 14, 23 and 24.

Land, nearly level.
 Soil, sandy loam.
 Timber, none; undergrowth, moderate growth of sagebrush.

N. 0°06' E., bet. secs. 13 and 14.

Over low rolling hills, no timber.

5.80 Track road, bears N. 40° E. and S. 75° W.

40.14 Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

CHAINS

T15N R28E

$\frac{1}{4}$
S14 | S13
1963

Deposit glass at base of post; raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

80.28 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

S11 | S12
S14 | S13
1963

Deposit glass at base of post; raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, low rolling hills.

Soil, sandy.

Timber, none; undergrowth, sage brush.

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township.

N. 89°40' W., bet. secs. 12 and 13.

Over nearly level land, no timber.

40.38 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

$\frac{1}{4}$ $\frac{S 12}{S 13}$
1963

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

62.80 Track road, bears N. 5° E. and S. 5° W.

80.76 The cor. of secs. 11, 12, 13 and 14.

Land, nearly level.

Soil, sandy loam.

Timber, none; undergrowth, blue sage and grasses.

N. 0°14' W., bet. secs. 11 and 12.

Over nearly level rangeland, through sparse timber.

40.14 Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

CHAINS	
	<p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{1}{4}$ S11 S12 1963</p> <p>Deposit glass at base of post; raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p>
43.85	Barbed wire fence, bears E. and W.
44.05	Track road, bears E. and W.
80.28	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{S\ 2}{S11} \frac{S\ 1}{S12}$ 1963</p> <p>Deposit glass at base of post; raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy. Timber, scattered cedar; undergrowth, grasses and sagebrush.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the township.</p> <p>N. 89°36' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through sparse timber.</p>
30.80	Top of low ridge, bears NE. and SW.
40.22	<p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{1}{4} \frac{S\ 1}{S\ 12}$ 1963</p> <p>Deposit glass at base of post; raise a small mound of earth and stone N. of cor.</p>
54.60	A reservoir, approximately 4 chs. wide and 4 chs. long, bears N., 3.50 chs. dist.
57.00	Track road, bears irregularly NW. and SE.
80.43	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar; undergrowth, sagebrush and grasses.</p>

CHAINS

N. 0°23' W., bet. secs. 1 and 2.

Over nearly level land, through scattered timber.

15.40 Track road, bears N. 80° W. and S. 80° E.

37.50 Wash, 20 lks. wide, 1 ft. deep, drains N. 75° E. toward reservoir.

40.14 Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

1/4
S 2 | S 1
1963

Deposit glass at base of post; raise a small mound of earth and stone W. of cor.

65.35 Track road, bears N. 70° E. and S. 45° W.

79.88 The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the township.

Land, nearly level.

Soil, sandy, clay.

Timber, sparse cedar; undergrowth, blue and yellow sage and grasses.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the township.

N. 0°39' E., bet. secs. 34 and 35.

Over gently rolling land, no timber.

8.40 Track road, bears irregularly SE. and W. toward St. Johns Stake Welfare Ranch.

11.85 Track road, bears N. 30° E. and S. 45° W.

25.35 Barbed wire fence, bears N. 30° E. and S. 45° W.

36.55 Wash, 80 lks. wide, 3 ft. deep, drains irregularly NW. into Zuni River.

37.15 Barbed wire fence, bears E. and W.

40.16 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T15N R28E

1/4
S34 | S35
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

CHAINS	
41.35	Zuni River, 120 lks. wide, 3 ft. deep, drains irregularly SW.
80.32	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T15N R28E $\frac{S27}{S34} \frac{S26}{S35}$ 1963</p>
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
	Land, gently rolling. Soil, sandy. Timber, none; undergrowth, sagebrush and salt cedar along river bank.
<hr/>	
	From the cor. of secs. 25, 26, 35 and 36.
	West bet. secs. 26 and 35.
	Over level land, through low undergrowth, no timber.
3.55	Barbed wire fence, bears N. and S.
40.74	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T15N R28E $\frac{1}{4} \frac{S 26}{S 35}$ 1963</p>
	Deposit glass at base of post; raise a small mound of earth and stone N. of cor.
80.18	Barbed wire fence, bears N. and S.
81.48	The cor. of secs. 26, 27, 34 and 35.
	Land, level. Soil, clay hardpan. Timber, none; undergrowth, sagebrush.
<hr/>	
	N. 0°26' W., bet. secs. 26 and 27.
	Over level land, no timber.
40.16	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.

CHAINS

T15N R28E

$\frac{1}{4}$
S27 | S26
1963

Deposit glass at base of post.

52.05 Wash, 30 lks. wide, 1 ft. deep, drains S. 74° W.

80.32 Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

S22 | S23
S27 | S26
1963

Deposit glass at base of post.

Land, level.

Soil, sandy clay.

Timber, none; undergrowth, blue sage and grasses.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°57' W., bet. secs. 23 and 26.

Over nearly level land, no timber.

40.66 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

$\frac{1}{4}$ S 23
S 26
1963

Deposit glass at base of post; raise a small mound of stone and earth N. of cor.

44.00 Wash, 30 lks. wide, 1 ft. deep, drains S. 70° W.

48.65 Barbed wire fence, bears irregularly E. and W.

56.65 Top of low ridge, bears N. 45° E. and S. 10° E.

80.90 Barbed wire fence, bears S. and N. for 30 lks.

81.32 The cor. of secs. 22, 23, 26 and 27.

Land, nearly level.

Soil, clay hardpan.

Timber, none; undergrowth, dense sagebrush.

N. 0°35' W., bet. secs. 22 and 23.

Over nearly level land, no timber.

CHAINS	
.30	Barbed wire fence, bears E. and W.
24.00	Asc. gentle S. slope.
26.85	Dim track road, bears NE. and SW.
40.16	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T15N R28E $\frac{1}{4}$ S22 S23 1963</p>
	Deposit glass at base of post; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.32	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T15N R28E S15 S14 S22 S23 1963</p>
	Deposit glass at base of post; raise a small mound of earth and stone W. of cor.
	<p>Land, nearly level. Soil, sandy. Timber, none; undergrowth, sagebrush.</p>
	<hr/>
	From the cor. of secs. 13, 14, 23 and 24.
	N. $89^{\circ}55'$ W., bet. secs. 14 and 23.
	Over level land, through sparse undergrowth and no timber.
40.45	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T15N R28E $\frac{1}{4}$ S 14 S 23 1963</p>
	Deposit glass at base of post; raise a mound of stone 2 ft. base, 2 ft. high, N. of cor.
56.20	Low spur, bears N. and S. 10° W.
80.90	The cor. of secs. 14, 15, 22 and 23.

CHAINS

Land, level.
Soil, sandy.
Timber, none; undergrowth, sparse sagebrush and grasses.

N. 0°07' E., bet. secs. 14 and 15.

Over nearly level land, through sparse undergrowth, no timber.

40.16 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T15N R28E
 $\frac{1}{4}$
S15 | S14
1963

Raise a small mound of stone W. of cor.

41.80 Track road, bears irregularly NW. and SE.

80.32 Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 18 ins. in the ground and in a collar of stone to top, cap mkd.

T15N R28E
S10 | S11
S15 | S14
1963

Deposit glass at base of post; raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, nearly level.
Soil, sandy laom.
Timber, none; undergrowth, sagebrush.

From the cor. of secs. 11, 12, 13 and 14.

N. 89°54' W., bet. secs. 11 and 14.

Over nearly level land, no timber.

21.60 Low ridge, bears N. 20° E. and S. 45° W.

40.45 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
 $\frac{1}{4}$ $\frac{S 11}{S 14}$
1963

Deposit glass at base of post; raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

CHAINS	
80.90	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, nearly level. Soil, sandy. Timber, none; undergrowth, sagebrush and grasses.</p>
	<p>N. 0°16' W., bet. secs. 10 and 11.</p> <p>Over nearly level land, no timber.</p>
15.00	<p>Track road, bears NE. and SW.</p>
40.16	<p>Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E ¼ S10 S11 1963</p> <p>Deposit glass at base of post; raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p>
41.98	<p>Barbed wire fence, bears E. and W.</p>
44.60	<p>Track road, bears E. and W.</p>
80.32	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E S 3 S 2 S10 S11 1963</p> <p>Deposit glass at base of post; raise a small mound of stone W. of cor.</p> <p>Land, nearly level. Soil, sandy. Timber, none; undergrowth, low sagebrush.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°52' W., bet. secs. 2 and 11.</p> <p>Over level land, through sparse undergrowth and timber.</p>
32.45	<p>Track road, bears N. 20° E. and S. 30° W.</p>
40.48	<p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>

CHAINS	
80.96	<p style="text-align: center;">T15N R28E $\frac{1}{4}$ $\frac{S \ 2}{S \ 11}$ 1963</p> <p>Deposit glass at base of post; raise a small mound of stone N. of cor.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, level. Soil, sandy loam. Timber, scattered cedar; undergrowth, sparse sagebrush.</p>
40.16	<p style="text-align: center;">N. 0°02' E., bet. secs. 2 and 3.</p> <p>Over nearly level land, through sparse timber.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
64.50	<p style="text-align: center;">T15N R28E $\frac{1}{4}$ S 3 S 2 1963</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears S. 82°30' E., 190 lks. distant, mkd. $\frac{1}{4}$ S 2 BT</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 58°30' W., 121 lks. dist., mkd. T15N R28E $\frac{1}{4}$ S 3 BT</p> <p>Deposit glass at base of post; raise a small mound of stone W. of cor.</p>
64.50	<p>Track road, bears N. 80° E. and S. 80° W.</p>
79.77	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the township.</p> <p>Land, nearly level. Soil, sandy. Timber, scattered cedar; undergrowth, sagebrush and grasses.</p>
23.28	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township.</p> <p>N. 0°31' E., bet. secs. 33 and 34.</p> <p>Over gently rolling rangeland, no timber.</p>
27.55	<p>Barbed wire fence, bears N. 75° E. and S. 75° W.</p>
27.55	<p>Zuni River, 140 lks. wide, 5 ft. deep, drains S. 60° W.</p>
40.13	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p>

CHAINS	
	<p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{1}{4}$ S33 S34 1963</p> <p>Deposit glass at base of post; raise a small mound of stone W. of cor.</p>
<p>80.26</p>	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E S28 S27 S33 S34 1963</p> <p>Deposit glass at base of post; raise a small mound of stone W. of cor.</p> <p>Land, gently rolling. Soil, clay. Timber, none; undergrowth, sagebrush, shadscale and grasses.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°56' W., bet. secs. 27 and 34.</p> <p>Over level rangeland, through sparse undergrowth, no timber.</p>
<p>17.00</p>	<p>Middle of old dry lake, approximately 250 lks. wide, 300 lks. long.</p>
<p>40.52</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{1}{4}$ $\frac{S 27}{S 34}$ 1963</p>
<p>81.04</p>	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, low sagebrush.</p>
	<p>N. 0°07' W., bet. secs. 27 and 28.</p> <p>Over level land, through low undergrowth, no timber.</p>

CHAINS

- 40.13 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
- Set the post 24 ins. in the ground, cap mkd.
- T15N R28E
 $\frac{1}{4}$
S28|S27
1963
- Deposit glass at base of post; raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
- 59.00 Wash, 40 lks. wide, 2 ft. deep, drains S. 85° W.
- 80.26 Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance, there is no remaining evidence of the original corner.
- Set the post 24 ins. in the ground, cap mkd.
- T15N R28E
S21|S22
S28|S27
1963
- Deposit glass at base of post; raise a small mound of earth and stone W. of cor.
- Land, level.
Soil, sandy.
Timber, none; undergrowth, dense sagebrush and grasses.
-
- From the cor. of secs. 22, 23, 26 and 27.
- S. $89^\circ 54'$ W., bet. secs. 22 and 27.
- Over level rangeland, no timber and dense low undergrowth.
- 40.27 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.
- Set the post 24 ins. in the ground, cap mkd.
- T15N R28E
 $\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$
1963
- Deposit glass at base of post; raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
- 64.30 Asc. gentle E. slope to cor.
- 80.54 The cor. of secs. 21, 22, 27 and 28.
- Land, level.
Soil, clay hardpan.
Timber, none; undergrowth, sagebrush and grasses.
-

CHAINS	
	<p>N. 0°43' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land, no timber.</p>
.60	<p>Barbed wire fence, bears E. and W.</p>
40.13	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E</p> <p>$\frac{1}{4}$</p> <p>S21 S22</p> <p>1963</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
80.27	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E</p> <p>S16 S15</p> <p>S21 S22</p> <p>1963</p> </div> <p>Raise a small mound of stone to W. of cor.</p> <p>Land, gently rolling. Soil, sandy. Timber, none; undergrowth, blue sage and grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°51' W., bet. secs. 15 and 22.</p> <p>Over gently rolling hills, no timber.</p>
40.34	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E</p> <p>$\frac{1}{4}$ S 15</p> <p>S 22</p> <p>1963</p> </div> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p>
80.68	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, gently rolling. Soil, sandy. Timber, none; undergrowth, blue and yellow sage.</p> <hr/>

CHAINS		
	<p>N. 0°10' E., bet. secs. 15 and 16.</p>	
	<p>Over level land, through low undergrowth, no timber.</p>	
34.94	<p>Track road, bears N. 80° E. and S. 80° W.</p>	
40.13	<p>Point for the ¼ sec. cor. of secs. 15 and 16 at proportionate distance; there is no remaining evidence of the original corner.</p>	
	<p>Set the post 24 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T15N R28E ¼ S16 S15 1963</p>	
	<p>Deposit glass at base of post; raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
80.26	<p>Point for the cor. of secs. 9, 10, 15 and 16 at proportionate distance; there is no remaining evidence of the original corner.</p>	
	<p>Set the post 24 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T15N R28E S 9 S10 S16 S15 1963</p>	
	<p>Deposit glass at base of post; raise a small mound of earth and stone W. of cor.</p>	
	<p>Land, level.</p>	
	<p>Soil, sandy.</p>	
	<p>Timber, none; undergrowth, sagebrush and grasses.</p>	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>	
	<p>S. 89°51' W., bet. secs. 10 and 15.</p>	
	<p>Over nearly level land, through low undergrowth.</p>	
11.95	<p>Track road, bears N. 35° E. and S. 15° W.</p>	
40.31	<p>Point for the ¼ sec. cor. of secs. 10 and 15 at proportionate distance; there is no remaining evidence of the original corner.</p>	
	<p>Set the post 24 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T15N R28E ¼ S 10 S 15 1963</p>	
	<p>Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p>	
57.80	<p>Track road, bears irregularly NW. and SE.</p>	
80.62	<p>The cor. of secs. 9, 10, 15 and 16.</p>	

CHAINS	
	<p>Land, nearly level. Soil, sandy. Timber, none; undergrowth, sagebrush.</p> <hr/> <p>N. 0°22' W., bet. secs. 9 and 10. Over nearly level land, no timber.</p>
7.30	Track road, bears W. and S. 80° E.
40.13	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E 1/4 S 9 S 10 1963</p> </div> <p>Raise a small mound of stone W. of cor.</p>
42.30	Barbed wire fence, bears E. and W.
51.42	Track road, bears N. 65° W. and S. 70° E.
60.00	Enter scattered cedar trees, generally bears E. and W.
80.26	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 26 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E S 4 S 3 S 9 S 10 1963</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 45° E., 47 lks. dist., mkd. S 3 BT</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam, bears S. 69° E., 121 lks. dist., mkd. S 10 BT</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 56°45' W., 58 lks. dist., mkd. T15N R 28 E S 9 BT</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 29° W., 57 lks. dist., mkd. T 15 N R 28 E S 4 BT</p> <p>Deposit glass at base of post; raise a small mound of earth and stone W. of cor.</p> <p>Land, nearly level. Soil, sandy. Timber, N. 20 chs. only; undergrowth, sagebrush and grasses.</p> <hr/>

CHAINS	
<p>40.38</p>	<p>From the cor. of secs. 2, 3, 10 and 11. S. 89°48' W., bet. secs. 3 and 10. Over gently rolling land, through scattered timber. Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E ¼ $\frac{S\ 3}{S\ 10}$ 1963</p> <p>Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p>
<p>54.80</p>	<p>Enter moderately dense stand of cedar, bears irregularly NE. and SW.</p>
<p>80.75</p>	<p>The cor. of secs. 3, 4, 9 and 10.</p>
	<p>Land, gently rolling. Soil, sandy loam. Timber, cedar; undergrowth, sagebrush.</p>
	<hr/>
<p>40.13</p>	<p>N. 0°19' E., bet. secs. 3 and 4. Over gently rolling land, through scattered timber. Point for the ¼ sec. cor. of secs. 3 and 4 at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E ¼ $\frac{S\ 4}{S\ 3}$ 1963</p> <p>Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p>
<p>55.00</p>	<p>Track road, bears generally E. and W.</p>
<p>69.90</p>	<p>Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.</p>
<p>75.15</p>	<p>Wash, 15 lks. wide, 2 ft. deep, drains S. 75° W.</p>
<p>80.14</p>	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the township.</p>
	<p>Land, gently rolling. Soil, sandy. Timber, scattered cedar; undergrowth, sagebrush.</p>
	<hr/>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the township.</p>
	<p>N. 0°09' E., bet. secs. 32 and 33.</p>

4690

Resurvey, Subdivision, T15N, R28E, Arizona

39.

CHAINS	
	Over level land, through low undergrowth.
33.25	Wash, 40 lks. wide, 2 ft. deep, drains S. 75° W.
37.50	Track road, bears E. and S. 80° W.
39.20	Wash, 30 lks. wide, 1 ft. deep, drains S. 65° W.
40.14	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	T15N R28E ¼ S32 S33 1963
	from which
	A windmill bears S. 87°30' E., 34.07 chs. dist.
	Deposit glass at base of post; raise a small mound of stone W. of cor.
45.95	Track road, bears N. 49° E. and S. 40° W.
77.30	Wash, 20 lks. wide, 2 ft. deep, drains S. 50° W. toward Zuni River.
80.28	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	T15N R28E S29 S28 S32 S33 1963
	Deposit glass at base of post; raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
	Land, level.
	Soil, sandy.
	Timber, none; undergrowth, dense sagebrush and sparse grass.
From the cor. of secs. 27, 28, 33 and 34. S. 89°58' W., bet. secs. 28 and 33. Over nearly level land, no timber.	
21.00	Wash, 30 lks. wide, 2 ft. deep, drains irregularly SW.
40.41	Barbed wire fence, bears N. and S.
40.67	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

CHAINS

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
 $\frac{1}{4}$ $\frac{S 28}{S 33}$
1963

Deposit glass at base of post; raise a small mound of stone N. of cor.

58.80 Dry pond, 80 lks. wide, 200 lks. long.

75.85 Track road, bears N. 10° E. and S. 10° E.

81.34 The cor. of secs. 28, 29, 32 and 33.

Land, nearly level.
Soil, sandy.
Timber, none; undergrowth, sagebrush.

N. 0°21' W., bet. secs. 28 and 29.

Over level land, through sparse undergrowth and no timber.

40.14 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
 $\frac{1}{4}$
S29 | S28
1963

Deposit glass at base of post; raise a small mound of stone W. of cor.

80.28 Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
S20 | S21
S29 | S28
1963

Land, level.
Soil, sandy.
Timber, none; undergrowth, sagebrush and grasses.

From the cor. of secs. 21, 22, 27 and 28.

S. 89°58' W., bet. secs. 21 and 28.

Over level land, no timber.

6.45 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° E.

35.50 Barbed wire fence, bears N. 70 lks. and S.

CHAINS

40.82

Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

$\frac{1}{4}$ $\frac{S\ 21}{S\ 28}$

1963

Raise a small mound of stone N. of cor.

45.75

Windmill, bears N. 1.60 chs. dist.

48.70

Track road, bears N. 25° E. and S. 25° W.

81.64

The cor. of secs. 20, 21, 28 and 29.

Land, level.

Soil, sandy.

Timber, none; undergrowth, blue sage.

N. 0°15' W., bet. secs. 20 and 21.

Over nearly level land, through sparse undergrowth, no timber.

.55

Track road, bears E. and W.

1.02

Barbed wire fence, bears E. and W.

40.14

Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

$\frac{1}{4}$ S20|S21

1963

Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

61.47

Wash, 50 lks. wide, 1 ft. deep, drains S. 80° W.

80.05

Barbed wire fence, bears E. and W.

80.28

Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

S17|S16
S20|S21

1963

Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

42

CHAINS

Land, level.
Soil, sandy.
Timber, none; undergrowth, sagebrush and grasses.

From the cor. of secs. 15, 16, 21 and 22.

West, bet. secs. 16 and 21.

Over gently rolling land, no timber.

38.00 Track road, bears N. 5° W. and S. 10° E.

40.48 Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
¼ $\frac{S\ 16}{S\ 21}$
1963

from which

The windmill at the ranch called Bird Place,
bears N. 9°34' W., 27.74 chs. dist.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

61.45 Barbed wire fence, bears N. 10° E. and S. 10° W.

80.96 The cor. of secs. 16, 17, 20 and 21.

Land, gently rolling.
Soil, sandy loam.
Timber, none; undergrowth, sparse sagebrush.

N. 0°25' E., bet. secs. 16 and 17.

Over nearly level land, through low undergrowth, no timber.

21.64 Fence corner bears E. 45 lks. dist.; from this intersection fences extend E. and S.

27.30 Track road, bears N. 45° E. and S. 50° W.

40.14 Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E
¼ $\frac{S17}{S16}$
1963

Deposit glass at base of post; raise a mound of stone 2½ ft. base, 2 ft. high, W. of cor.

CHAINS					
80.28	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table> <p>1963</p> </div> <p>Raise a small mound of earth and stone W. of cor.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none; undergrowth, sagebrush, grasses.</p>	S 8	S 9	S 17	S 16
S 8	S 9				
S 17	S 16				
	<hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°57' W., bet. secs. 9 and 16.</p> <p>Over nearly level land, no timber.</p>				
13.70	<p>Track road, bears N. 25° E. and S. 10° W.</p>				
40.29	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>$\frac{1}{4}$ S 9</td> <td></td> </tr> <tr> <td>S 16</td> <td></td> </tr> </table> <p>1963</p> </div> <p>Deposit glass at base of post; raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.</p>	$\frac{1}{4}$ S 9		S 16	
$\frac{1}{4}$ S 9					
S 16					
79.20	<p>Top of small malpai ridge, bears N. 10° E. and S. 20° W.</p>				
80.58	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy, rocky. Timber, none; undergrowth, sagebrush and grasses.</p>				
	<hr/> <p>N. 0°12' W., bet. secs. 8 and 9.</p> <p>Over nearly level land, no timber.</p>				
23.26	<p>Wash, 30 lks. wide, 2 ft. deep, drains S. 80° W.</p>				
40.14	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 26 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T15N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>$\frac{1}{4}$ S 8</td> <td>S 9</td> </tr> </table> <p>1963</p> </div>	$\frac{1}{4}$ S 8	S 9		
$\frac{1}{4}$ S 8	S 9				

44

CHAINS

Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

40.70 Barbed wire fence, bears E. and W.

45.52 Wash, 70 lks. wide, 3 ft. deep, drains irregularly SW.

80.28 Point for the cor. of sections 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

S 5	S 4
S 8	S 9

1963

Deposit glass at base of post; raise a small mound of stone W. of cor.

Land, nearly level.

Soil, sandy and clay.

Timber, none; undergrowth, sparse sagebrush.

From the cor. of secs. 3, 4, 9 and 10.

West, bet. secs. 4 and 9.

Over level land, through scattered timber.

7.30 Leave timber, enter open, level land.

14.65 Track road, bears N. and S.

40.15 Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

¼	S 4
	S 9

1963

Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

44.10 Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.

63.65 Small wash, drains S. 5° W.

80.29 The cor. of secs. 4, 5, 8 and 9.

Land, level.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, sparse sagebrush and grasses.

CHAINS	
	<p>N. 0°14' E., bet. secs. 4 and 5.</p>
	<p>Over level grassland, no timber.</p>
40.14	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R28E</p>
	<p style="text-align: center;"> $\frac{1}{4}$ S 5 S 4 1963 </p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
57.42	<p>Dim track road, bears S. 20° W. and N. 20° E.</p>
80.33	<p>The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the township.</p>
	<p>Land, level.</p>
	<p>Soil, sandy.</p>
	<p>Timber, none; undergrowth, sparse sagebrush and grasses.</p>
	<hr/>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the township.</p>
	<p>N. 0°08' E., bet. secs. 31 and 32.</p>
	<p>Over level grassland, no timber.</p>
.15	<p>Track road, bears N. 70° W. and N. 75° E.</p>
26.60	<p>Wash, 40 lks. wide, 4 ft. deep, drains S. 45° W.</p>
40.46	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R28E</p>
	<p style="text-align: center;"> $\frac{1}{4}$ S 31 S 32 1963 </p>
	<p>Deposit glass at base of post; raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p>
80.92	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T15N R28E</p>
	<p style="text-align: center;"> S 30 S 29 S 31 S 32 1963 </p>
	<p>Deposit glass at base of post; raise a small mound of stone W. of corner.</p>

CHAINS	
	<p>Land, level. Soil, clay hardpan. Timber, none; undergrowth, sparse sagebrush and grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33. N. 89°32' W., bet. secs. 29 and 32. Over nearly level rangeland, no timber.</p>
8.20	SW. end of small ridge, bears NE. and SW.; desc. W. gentle slope.
28.00	Wash, 20 lks. wide, 2 ft. deep, drains S. 10° E.
40.48	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd.
	<p>T15N R28E ¼ $\frac{S\ 29}{S\ 32}$ 1963</p>
	Deposit glass at base of post; raise a small mound of earth and stone N. of cor.
54.77	Hardscrabble Wash, 60 lks. wide, 4 ft. deep, drains S. 5° E.
80.96	The cor. of secs. 29, 30, 31 and 32. Land, nearly level. Soil, clay hardpan. Timber, none; undergrowth, blue and yellow sage.
	<hr/> <p>S. 89°29' W., bet. secs. 30 and 31. Over level land, through sparse undergrowth, no timber.</p>
40.59	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd.
	<p>T15N R28E ¼ $\frac{S\ 30}{S\ 31}$ 1963</p>
	Deposit glass at base of post; raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
61.00	Track road, bears N. 20° E. and S. 30° W.
79.91	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township. Land, level. Soil, sandy loam. Timber, none; undergrowth, dense sagebrush, sparse grasses.

CHAINS	
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°08' W., bet. secs. 29 and 30.</p> <p>Over level land, no timber.</p>
12.75	<p>SE. end of dike, 4 ft. high, bears E., 0.60 chs. and irregularly W.</p>
40.46	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{1}{4}$ S30 S29 1963</p> <p>Deposit glass at base of post; raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
55.05	<p>SW. end of dike, 15 lks. wide, 4 ft. high, bears NE. and SW.</p>
55.65	<p>Wash, 20 lks. wide, 2 ft. deep, drains S. 75° E.</p>
76.85	<p>Track road, bears N. 80° E. and N. 80° W.</p>
80.92	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E S19 S20 S30 S29 1963</p> <p>from which</p> <p style="padding-left: 40px;">A windmill bears S. 36° E., 38.22 chs. dist.</p> <p>Deposit glass at base of post; raise a small mound of stone W. of cor.; cor. falls 8 lks. S. of E-W barbed wire fence.</p> <p>Land, level. Soil, clay hardpan. Timber, none; undergrowth, sparse sagebrush.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°04' W., bet. secs. 20 and 29.</p> <p>Over level rangeland, through sparse undergrowth, no timber.</p>
7.65	<p>Desc. NW. gentle slope.</p>
29.00	<p>Over level land.</p>

CHAINS	
36.44	Track road, bears irregularly E. and SW.
40.33	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd.
	T15N R28E $\frac{1}{4} \frac{S 20}{S 29}$ 1963
	Deposit glass at base of post; raise a small mound of stone N. of cor.
51.40	Barbed wire fence, bears N. 5° E. and S. 5° W.
52.05	Hardscrabble Wash, 120 lks. wide, 3 ft. deep, drains S. 32° W., into reservoir.
80.66	The cor. of secs. 19, 20, 29 and 30. Land, level. Soil, clay hardpan. Timber, none; undergrowth, sagebrush and grasses.
	<hr/> S. 89°05' W., bet. secs. 19 and 30. Over gently rolling land, through low undergrowth, no timber.
3.40	Track road, bears N. 85° W. and S. 75° E.
13.05	Track road, bears N. 10° E. and S. 45° W.
14.15	Asc. E. gentle slope.
40.58	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd.
	T15N R28E $\frac{1}{4} \frac{S 19}{S 30}$ 1963
	Deposit glass at base of post; raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
79.46	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the township. Land, gently rolling. Soil, sandy loam. Timber, none; undergrowth, sagebrush and sparse grass.
	<hr/> From the cor. of secs. 19, 20, 29 and 30. N. 0°27' W., bet. secs. 19 and 20. Over level land, through sparse undergrowth, no timber.

CHAINS	
.08	Barbed wire fence, bears E. and W.
7.70	E. edge of small mesa, projects E. for 3 chs., bears E. and W.
40.46	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd. T15N R28E $\frac{1}{4}$ S19 S20 1963 Deposit glass at base of post; raise a small mound of stone W. of cor.
80.04	Intersection of fences extending E., S. 5° W. and N. 8° W.
80.92	The cor. of secs. 17, 18, 19 and 20, monumented by a basalt stone, 24x14x6 ins., marked with 3 notches on S. and 5 notches on E. faces, firmly set in mound of stone. At the corner point Set the post 22 ins. in the ground, cap mkd. T15N R28E S18 S17 S19 S20 1963 Deposit glass at base of post and reconstruct mound of stone to W. of cor. Land, level. Soil, clay hardpan. Timber, none; undergrowth, sagebrush and grasses.
	From the cor. of secs. 16, 17, 20 and 21. N. 88°38' W., bet. secs. 17 and 20. Over level land, through sparse undergrowth, no timber.
1.25	Barbed wire fence, bears N. 3° E. and S. 3° W.
40.45	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set the post 24 ins. in the ground, cap mkd. T15N R28E $\frac{1}{4}$ S 17 S 20 1963 Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

CHAINS

- 65.12 Hardscrabble Wash, 350 lks. wide, 8 ft. deep, drains S. 10° E.
- 70.00 Small wash, drains S. 20° W.
- 80.90 The cor. of secs. 17, 18, 19 and 20.
Land, level.
Soil, clay hardpan.
Timber, none; undergrowth, sparse sagebrush.
-
- S. 88°40' W., bet. secs. 18 and 19.
Over rolling and broken land, no timber.
- .60 Asc. steep and broken E. slope of Malpai ridge.
- 15.20 Top of ridge, bears irregularly NE. and W.
- 40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
Set the post 24 ins. in the ground, cap mkd.
- T15N R28E
 $\frac{1}{4}$ $\frac{S\ 18}{S\ 19}$
1963
- 78.65 Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.
The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township.
Land, rolling and broken.
Soil, rocky.
Timber, none; undergrowth, sparse sagebrush.
-
- From the cor. of secs. 17, 18, 19 and 20.
N. 0°31' E., bet. secs. 17 and 18.
Over gently rolling land, no timber, asc. gentle S. slope.
- 18.09 Track road, bears N. 35° W. and S. 15° E.
- 24.14 Wash, 30 lks. wide, 3 ft. deep, drains N. 85° E.
- 35.95 Track road, bears N. 20° E. and S. 30° W.
- 39.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.
Set the post 24 ins. in the ground, cap mkd.
- T15N R28E
 $\frac{1}{4}$
S18|S17
1963

CHAINS					
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.				
43.00	Desc. gentle N. slope.				
55.90	Wash, 20 lks. wide, 2 ft. deep, drains S. 85° E.				
79.80	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.				
	Set the post 24 ins. in the ground, cap mkd.				
	T15N R28E <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> 1963	S 7	S 8	S 18	S 17
S 7	S 8				
S 18	S 17				
	Deposit glass at base of post; raise a small mound of earth and stone W. of cor.				
	Land, gently rolling. Soil, sandy, rocky. Timber, none; undergrowth, sparse sagebrush and grasses.				
	From the cor. of secs. 8, 9, 16 and 17.				
	N. 89°00' W., bet. secs. 8 and 17.				
	Over rolling and broken land, no timber.				
13.80	Asc. steep E. slope of Malpai ridge.				
18.65	Top of Malpai ridge, bears N. 30° E. and S. 5° W.; desc. W. slope.				
31.45	Hardscrabble Wash, 75 lks. wide, 11 ft. deep, drains S. 2° W.				
37.00	Branch of same major wash, 40 lks. wide, 6 ft. deep, drains S.				
40.40	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.				
	Set the post 24 ins. in the ground, cap mkd.				
	T15N R28E <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1/4 S 8</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> 1963	1/4 S 8	S 17		
1/4 S 8	S 17				
54.37	Wash, 90 lks. wide, 4 ft. deep, drains S. 30° E.				
62.45	Wash, 95 lks. wide, 5 ft. deep, drains S. 25° E.				
80.25	Wash, 40 lks. wide, 4 ft. deep, drains S. 15° E.				
80.80	The cor. of secs. 7, 8, 17 and 18.				
	Land, gently rolling. Soil, sandy, rocky. Timber, none; undergrowth, sparse sagebrush and grasses.				

52

CHAINS

S. 89°04' W., bet. secs. 7 and 18.
 Over nearly level land, through low undergrowth, no timber.

13.15 Asc. gentle E. slope.

13.55 Track road, bears N. 15° W. and S. 5° E.

40.44 Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.
 Set the post 24 ins. in the ground, cap mkd.

T15N R28E
 ¼ $\frac{S\ 7}{S\ 18}$
 1963

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of corner.

79.08 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the township.
 Land, nearly level.
 Soil, sandy loam.
 Timber, none; undergrowth, sparse sagebrush and grasses.

From the cor. of secs. 7, 8, 17 and 18.
 N. 0°16' W., bet. secs. 7 and 8.
 Over gently rolling land, through sparse undergrowth, no timber.

3.65 Wash, 90 lks. wide, 4 ft. deep, drains S. 25° E.

7.35 Wash, 30 lks. wide, 1 ft. deep, drains S. 35° E.

31.05 Asc. SE. slope of clay ridge.

33.20 Top of ridge, bears NW. and SE.

39.40 Barbed wire fence, bears E. and W.

39.90 Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.
 Set the post 24 ins. in the ground, cap mkd.

T15N R28E
 ¼ $\frac{S\ 7}{S\ 8}$
 1963

Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

62.35 W. edge of clay ridge.

74.70 Desc. gentle N. slope to sec. cor.

CHAINS	
79.80	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\begin{array}{c c} S6 & S5 \\ \hline S7 & S8 \end{array}$ 1963</p> <p>Deposit glass at base of post; raise a small mound of earth and stone W. of cor.</p> <p>Land, gently rolling. Soil, clay. Timber, none; undergrowth, dense sagebrush and sparse grass.</p>
	<hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°20' W., bet. secs. 5 and 8.</p> <p>Over nearly level land, through sparse undergrowth, no timber.</p>
34.26	<p>Wash, 45 lks. wide, 3 ft. deep, drains S. 30° E.</p>
40.44	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T15N R28E $\frac{1}{4} \begin{array}{c} S 5 \\ \hline S 8 \end{array}$ 1963</p> <p>Deposit glass at base of post; raise a small mound of stone N. of corner.</p>
41.80	<p>Wash, 50 lks. wide, 1 ft. deep, drains S. 40° E.</p>
52.30	<p>Small wash, drains S. 5° E.</p>
61.90	<p>Asc. gentle NE. slope to sec. cor.</p>
80.88	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, nearly level. Soil, sandy. Timber, none; undergrowth, sagebrush and grasses.</p>
	<hr/> <p>S. 89°36' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land, through sparse undergrowth, no timber.</p>
2.90	<p>N. edge of small spur, bears N. and S.</p>
8.80	<p>Top of small clay ridge, bears N. and S.</p>

CHAINS

40.36

Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

$\frac{1}{4}$ $\frac{S 6}{S 7}$

1963

Deposit glass at base of post; raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

53.65

N. edge of small clay ridge, bears NW. and SW.

76.87

Wash, 35 lks. wide, 1 ft. deep, drains S. 10° E.

78.77

The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township.

Land, gently rolling.

Soil, clay.

Timber, none; undergrowth, sparse sagebrush and grasses.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°36' E., bet. secs. 5 and 6.

Over nearly level land, no timber.

8.45

Wash, 10 lks. wide, 1 ft. deep, drains irregularly E.

35.65

Wash, 10 lks. wide, 1 ft. deep, drains S. 50° E.

39.90

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T15N R28E

$\frac{1}{4}$
S 6 | S 5

1963

Deposit glass at base of post; raise a small mound of earth and stone W. of cor.

49.05

Wash, 30 lks. wide, 2 ft. deep, drains S. 60° E.

55.55

Wash, 10 lks. wide, 1 ft. deep, drains S. 85° E.

58.20

Wash, 70 lks. wide, 4 ft. deep, drains S. 80° E.

79.53

The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township.

Land, nearly level.

Soil, sandy loam.

Timber, none; undergrowth, sagebrush.

CHAINS

General Description

The land within Township 15 North, Range 28 East, is level to gently rolling, varying from 5500 feet to 5850 feet above sea level. The soil of the bottom land along the Zuni River is very sandy; much of the soil in the central part is of clay. There are ridges of Malpai stone in secs. 17, 18, and 19. The only trees are cedars in sections 1 and 2.

The Zuni River crosses the southeastern portion of the township, the river being dry except during the rainy summer months. All of the washes in this township drain southerly into the Zuni River.

Most of this township is privately owned. The principle landowner is Mr. Clair Platt, who resides in St. Johns, Arizona. The land is used only for stock grazing and none of the land is under cultivation. There are numerous track roads throughout the township, all leading to windmills and stock tanks. The best track road exits in section 12, which is 5 miles west of U.S. Highway No. 666.

The only settlement is in section 16 and is known locally as the Bird Place. It is not normally occupied the year around.

BOOK 4690
CERTIFICATE OF SURVEY

~~WE~~ Wallace R. Ott
~~XX~~ Leonard W. Murphy , HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 14 day of March , 19 63 ,
~~WE~~
~~XX~~have dependently resurveyed the North, East, South and West boundaries
and the Subdivisional Lines of Township 15 North, Range 28 East,

of the Gila and Salt River Meridian, in the State of Arizona , which
are represented in the foregoing field notes as having been executed by ~~me~~ ^{us} and under ~~my~~ ^{our} direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

September 16, 1963
(Date)

Leonard W. Murphy
(Cadastral Surveyor)
Leonard W. Murphy

September 16, 1963
(Date)

Wallace R. Ott
Surveying ~~(Cadastral Surveyor)~~ Technician
Wallace R. Ott

CERTIFICATE OF APPROVAL
Bureau of Land Management

The foregoing field notes of the dependent resurvey of the North, South, East
and West Boundaries and Subdivisional Lines of Township 15 North, Range
28 East, Gila and Salt River Meridian, Arizona,

executed by Leonard W. Murphy, Cadastral Surveyor
Wallace R. Ott, Surveying Technician
having been critically examined and found correct, are hereby approved.

Washington, D. C.
MAR 24 1964
(Date)

[Signature]
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)