

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

North Boundary

(the Fourth Standard Parallel North)

East and West Boundaries

Subdivisional Lines

Township 16 North, Range 28 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Leonard W. Murphy, Cadastral Surveyor

Paul G. Bauer, Surveying Technician

Under special instructions dated March 14, 19 63, which provided for the surveys included under Group Number 390, approved March 18, 1963, and assignment instructions dated July 2, 19 63.

Survey commenced July 10, 19 63

Survey completed August 30, 19 63

1A

BOOK 4691

# INDEX DIAGRAM

Township 16 North, Range 28 East,  
 2                    2                    3                    4                    4                    5

	( $\frac{1}{4}$ )51	( $\frac{1}{4}$ )51	( $\frac{1}{4}$ )41	( $\frac{1}{4}$ )35	( $\frac{1}{4}$ )28	( $\frac{1}{4}$ )22	
15	6 50 50	5 41 50	4 34 40	3 28 34	2 22 28	1 21	10
14	7 49 48	8 40 48	9 33 39	10 27 33	11 20 27	12 20	9
13	18 47 46	17 39 46	16 32 39	15 26 32	14 19 26	13 19	9
12	19 45 45	20 38 44	21 31 37	22 25 30	23 18 25	24 18	8
11	30 43 43	29 36 42	28 30 36	27 24 29	26 17 23	25 16	7
11	31 41	32 35	33 29	34 22	35 16	36	6

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

1. B

CHAINS

Township 16 North, Range 28 East, G&amp;SRM, Arizona

The north boundary, the Fourth Standard Parallel North, and the east, south and west boundaries and the subdivisional lines were surveyed in 1882 by H. A. Coe.

The following field notes are those of the dependent resurvey of the east, north and west boundaries and the subdivisional lines of Township 16 North, Range 28 East.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 14, 1963.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top. The original corner monuments are buried alongside the iron post unless described otherwise.

The geographic position of the corner of Townships 15 and 16 North, Ranges 28 and 29 East, is: Latitude 34°44'49" North and Longitude 109°18'53" West. This position was calculated from a direct tie to U. S. Coast and Geodetic Survey Triangulation Station WITCH located in section 30, Township 16 North, Range 29 East.

The mean magnetic declination was found to be: 13°30' East.

Dependent Resurvey, North Boundary  
(The Fourth Standard Parallel North)  
T. 16 N., R. 28 E., Arizona

Reestablishment of the Survey in 1882  
by H. A. Coe

Beginning at the Standard Cor. of Ts. 17 N., Rs. 27 and 28 E., monumented by a post 4½ ft. long, 4 ins. sq., markings faintly visible. This post had been tied into a fence corner from which fences extend E., W. and N., and is accepted locally as the original cor. position.

At the corner point

Set the post 20 ins. in the ground, cap mkd.

SC  
T17N  
R27E R28E  
S36 | S31  
1963

Raise a small mound of stone N. of cor.

CHAINS

S. 89°41' E., along the S. bdy. of sec. 31.

Over gently rolling land, through dense timber.

41.10

Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

SC  
T17N R28E  
 $\frac{1}{4}$  S31  
-----  
1963

from which

A cedar, 5 ins. diam., bears N. 4° E., 39 lks.  
dist., mkd.  $\frac{1}{4}$  S 31 SC BT

A cedar, 7 ins. diam., bears N. 47°30' E., 90 lks.  
dist., mkd.  $\frac{1}{4}$  S 31 SC BT.

61.40

Leave dense stand of cedar, bears NE. and SW.; asc. gentle W. slope.

75.70

Track road, bears N. 10° W. and S. 5° E.

82.20

Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

SC  
T17N R28E  
S 31 | S 32  
-----  
1963

from which

A cedar, 4 ins. diam., bears N. 32° E., 71 lks.  
dist., mkd. BT

A cedar, 4 ins. diam., bears N. 52° W., 15 lks.  
dist., mkd. BT

Deposit glass at base of post.

Land, gently rolling.

Soil, sandy.

Timber, cedar; undergrowth, sparse sagebrush.

S. 89°41' E., along the S. bdy. of sec. 32.

Over nearly level land, through scattered timber.

20.80

Track road, bears N. and S.

41.10

Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

SC  
T17N R28E  
 $\frac{1}{4}$  S32  
-----  
1963

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Fourth Stan. Par. N., R. 28 E., Arizona
	<p>from which</p> <p>A cedar, 12 ins. diam., bears N. 9°45' E., 99 lks. dist., mkd. <math>\frac{1}{4}</math> SC S32 BT</p> <p>A cedar, 5 ins. diam., bears N. 64°15' E., 156 lks. dist., mkd. <math>\frac{1}{4}</math> SC S 32 BT</p>
53.50	Enter area of dense cedar.
82.20	Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 22 ins. in the ground, cap mkd.
	SC T17N R28E <u>S32   S33</u> 1963
	Deposit glass at base of post; there are no suitable bearing trees available.
	Land, nearly level. Soil, sandy clay. Timber, cedar; undergrowth, sagebrush.
	S. 89°41' E., along the S. bdy. of sec. 33.
	Over nearly level land, through scattered timber.
31.00	Leave level land, asc. gentle E. slope.
41.10	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 22 ins. in the ground, cap mkd.
	SC T17N R28E <u><math>\frac{1}{4}</math> S33</u> 1963
	Deposit glass at base of post; no bearing trees available.
64.40	Wash, 40 lks. wide, 1 ft. deep, drains generally E.
73.30	Same wash, 20 lks. wide, drains E.
75.85	Same wash, 20 lks. wide, 3 ft. deep, drains SE.
81.47	Track road, bears irregularly NE. and SW.
82.20	Point for the standard cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.

4

CHAINS

SC  
T17N R28E  
S33|S34  
1963

from which

A metal water tank bears N. 79° E., 3.42 chs. distant.

Deposit glass at base of post; set a redwood post 4 ft. long, 4 ins. square, alongside the post as a guard stake.

Land, gently rolling.

Soil, sandy.

Timber, cedar; undergrowth, dense sagebrush, and grasses.

S. 89°41' E., along the S. bdy. of sec. 34.

Over gently rolling land, through scattered timber.

25.80

Track road, bears N. 82° W. and S. 82° E.

41.10

Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

SC  
T17N R28E  
 $\frac{1}{4}$  S34  
1963

Raise a small mound of earth and stone N. of cor.

53.50

Enter scattered cedars; desc. gentle E. slope.

82.20

Point for the standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

SC  
T17N R28E  
S34|S35  
1963

from which

A cedar, 8 ins. diam., bears N. 15°45' E., 233 lks. dist., mkd. SC S 35 BT

A cedar, 10 ins. diam., bears N. 9°15' W., 184 lks. dist., mkd. SC S 34 BT

Deposit glass at base of post.

Land, gently rolling.

Soil, sandy clay.

Timber, scattered cedar; undergrowth, sagebrush.

S. 89°41' E., along the S. bdy. of sec. 35.

Over gently rolling land; asc. gentle W. slope.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Fourth Stan. Par. N., R. 28 E., Arizona
11.00	Top of low ridge, bears N. and SW.; desc. gentle E. slope.
38.70	Shallow draw, drains SW.; asc. gentle W. slope.
41.10	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.  Set the post 24 ins. in the ground, cap mkd.  <div style="text-align: center;">                     SC                      T17N R28E  <math>\frac{1}{4}</math> S35  <hr style="width: 50px; margin: 0 auto;"/>                     1963                 </div> Raise a small mound of stone N. of corner.
67.70	Begin desc. gentle E. slope.
72.00	Shallow draw, drains S.; asc. gentle W. slope.
82.20	Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.  Set the post 20 ins. in the ground, cap mkd.  <div style="text-align: center;">                     SC                      T17N R28E                      S35   S36  <hr style="width: 50px; margin: 0 auto;"/>                     1963                 </div> Raise a small mound of stone N. of the cor.; cor. falls on low ridge bearing N. and S.  Land, gently rolling. Soil, sandy clay. Timber, scattered cedar; undergrowth, sagebrush and grasses.
	S. 89°41' E., along the S. bdy. of sec. 36.
	Over gently rolling land, through sparse low undergrowth.
3.50	Desc. gentle E. slope of ridge.
30.00	Over level land.
41.10	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.  Set the post 24 ins. in the ground, cap mkd.  <div style="text-align: center;">                     SC                      T17N R28E  <math>\frac{1}{4}</math> S36  <hr style="width: 50px; margin: 0 auto;"/>                     1963                 </div> from which  A cedar, 14 ins. diam., bears N. 78° E., 188 lks.

CHAINS

dist., mkd. T17N R28E ¼ SC S 36 BT (only bearing tree available)

Raise a small mound of stone N. of cor.

55.70 Unimproved road, bears NE. to windmill and SW.

72.70 Hardscrabble Wash, 35 lks. wide, 3 ft. deep, drains irregularly SW.

82.20 The standard cor. of Ts. 17 N., Rs. 28 and 29 E., monumented by the remains of the original wood post, 4 ins. sq., markings faintly visible.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

SC  
T17N  
R28E R29E  
S36|S31  
1963

Deposit glass at base of post; raise a small mound of stone N. of corner; no bearing trees available.

Land, gently rolling.

Soil, sandy clay.

Timber, cedar; undergrowth, sagebrush and grasses.

Dependent Resurvey, East Boundary  
T. 16 N., R. 28 E., Arizona

Reestablishing the Survey in 1882 by H. A. Coe

From the cor. of Ts. 15 and 16 N., Rs. 28 and 29 E., an iron post as described in the field notes of T. 15 N., R. 28 E., concurrently being surveyed under this same group number.

N. 1°11' E., bet. secs. 31 and 36.

Over nearly level land, through scattered timber.

33.80 Barbed wire fence, bears N. 76°50' E. and S. 76°50' W.

40.09 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N  
R28E R29E  
¼  
S36|S31  
1963

from which

A cedar, 12 ins. diam., bears S. 87°45' W.,  
159 lks. dist., mkd. ¼ S 36 BT (no other bearing trees available within limits)

Deposit glass at base of post; raise a small mound of stone W. of cor.



BOOK 4691  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Resurvey, E. Bdy., T. 16 N., R. 28 E., Arizona</p>
50.00	<p>Enter dense timber, bears NE. and SW.</p>
74.00	<p>Gentle desc.; continue through dense timber.</p>
80.18	<p>The cor. of secs. 25, 30, 31 and 36, monumented by the original wood post, 3½ ft. long, 4 ins. square, firmly set and properly marked. All four bearing trees still in evidence and correct as noted in official record.</p> <p>At the corner point</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E R29E S25 S30 S36 S31 1963</p> </div> <p>Deposit glass at base of post; destroy original post.</p> <p>Land, nearly level. Soil, sandy. Timber, cedar; undergrowth, sage brush and range grasses.</p>
	<p>N. 1°02' E., bet. secs. 25 and 30.</p>
	<p>Over nearly level land, through dense timber.</p>
12.00	<p>Barbed wire fence, bears irregularly N. and S.; enter recently cleared land.</p>
38.70	<p>Track road, bears irregularly SW. and E.</p>
40.18	<p>Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set the post 24 ins. in the ground, cap mkd.</p>
	<div style="text-align: center;"> <p>T16N R28E R29E ¼ S25 S30 1963</p> </div>
	<p>from which</p> <p>A cedar, 10 ins. diam., bears S. 11° E., 64 lks. dist., mkd. ¼ S 30 BT</p> <p>A cedar, 12 ins. diam., bears N. 71° W., 130 lks. dist., mkd. ¼ S 25 BT</p>
	<p>Raise a small mound of stone W. of cor.</p>
80.36	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p>

CHAINS

Set the post 24 ins. in the ground, cap mkd.

T16N  
R28E R29E  
S24 | S19  
S25 | S30  
1963

Raise a small mound of stone W. of cor.; no bearing trees available within limits.

Land, nearly level.

Soil, sandy.

Timber, cedar; undergrowth, sagebrush.

N. 1°02' E., bet. secs. 19 and 24.

Over gently rolling land, through sparse undergrowth.

19.00 Enter dense timber.

40.18 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 18 ins. in the ground, cap mkd.

T16N  
R28E R29E  
 $\frac{1}{4}$   
S24 | S19  
1963

from which

A cedar, 6 ins. diam., bears S. 59°15' E.,  
249 lks. dist., mkd.  $\frac{1}{4}$  S 19 BT

A cedar, 6 ins. diam., bears N. 22° W., 48 lks.  
dist., mkd.  $\frac{1}{4}$  S 24 BT.

Deposit glass at base of post; raise a small mound of stone W. of corner.

53.40 Desc. gentle N. slope of ridge.

65.00 Enter dense timber and almost level land.

80.36 Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T16N  
R28E R29E  
S13 | S18  
S24 | S19  
1963

from which

A cedar, 6 ins. diam., bears N. 22° E., 102 lks.  
dist., mkd. S 18 BT

A cedar, 10 ins. diam., bears N. 57°30' W.,  
57 lks. dist.; mkd. S 13 BT

Deposit glass at base of post; raise a small mound of stone W. of cor.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Resurvey, E. Bdy., T. 16 N., R. 28 E., Arizona
40.18	<p>Land, gently rolling. Soil, sandy. Timber, cedar; undergrowth, sagebrush and grasses.</p> <hr/> <p>N. 1°02' E., bet. secs. 13 and 18. Over level land, through dense timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E R29E <math>\frac{1}{4}</math> S13 S18 1963</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 43°30' E., 146 lks. dist., mkd. <math>\frac{1}{4}</math> S 18 BT</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 74°30' W., 68 lks. dist., mkd. <math>\frac{1}{4}</math> S 13 BT</p>
80.36	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E R29E <math>\frac{1}{4}</math> S12 S7 S13 S18 1963</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears N. 59° E., 58 lks. dist., mkd. T16N R29E S7 BT</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears S. 70° W., 14 lks. dist., mkd. S 13 BT</p> <p>Raise a small mound of earth and stone W. of corner.</p> <p>Land, nearly level. Soil, sandy. Timber, cedar; undergrowth, sparse sagebrush and range grasses.</p> <hr/> <p>N. 1°02' E., bet. secs. 7 and 12.</p> <p>Over level land, through scattered timber and sparse undergrowth.</p>

## CHAINS

- 19.00 Enter cleared off area.
- 40.18 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
- Set the post 24 ins. in the ground, cap mkd.
- T16N  
R28E R29E  
 $\frac{1}{4}$   
S12 | S7  
1963
- Raise a small mound of stone W. of cor.; no bearing trees available.
- 67.50 Cont. desc. over gentle N. slope.
- 80.36 The cor. of secs. 1, 6, 7 and 12, monumented by a wooden post  $3\frac{1}{2}$  ft. long, 3 ins. square, firmly set and faintly marked.
- At the corner point
- Set the post 22 ins. in the ground, cap mkd.
- T16N  
R28E R29E  
S1 | S6  
S12 | S7  
1963
- Deposit glass at base of post.
- Land, nearly level.  
Soil, sandy clay.  
Timber, scattered cedar; undergrowth, sagebrush.
- 
- N.  $0^{\circ}38'$  W., bet. secs. 1 and 6.
- Over gently rolling land, no timber.
- 4.11 Point for the closing corner of secs. 1 and 6, on the N. bdy. of the township, at proportionate distance; there is no remaining evidence of the original corner.
- Set the post 24 ins. in the ground, cap mkd.
- S1 | S6  
R28E | R29E  
T16N  
CC  
1963
- from which
- The standard cor. of T. 17 N., Rs. 28 and 29 E.,  
bears S.  $89^{\circ}41'$  E., 2.91 chs. dist.
- Raise a small mound of stone S. of cor.
- Land, gently rolling.  
Soil, sandy clay.  
Timber, cedar; undergrowth, sagebrush.
-

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS		
	Dependent Resurvey, West Boundary, T. 16 N., R. 28 E., Arizona	
	<hr/> Reestablishing the Survey in 1882 by H. A. Coe	
	From the cor. of Ts. 15 and 16 N., Rs. 27 and 28 E., an iron post as described in the field notes of T. 15 N., R. 28 E., concurrently surveyed under this same group number.	
	N. 0°30' W., bet. secs. 31 and 36.	
	Over gently rolling land, through sparse vegetation, along a fence.	
4.25	Wash, 25 lks. wide, 3 ft. deep, drains E.	
30.10	Wash, 10 lks. wide, 2 ft. deep, drains SE.	
34.00	Small wash, drains irregularly SE.	
40.20	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at pro- portionate distance; there is no remaining evidence of the original corner.	
	Set the post 20 ins. in the ground, cap mkd.	
	T16N R27E R28E $\frac{1}{4}$ S36 S31 1963	
	No bearing trees available.	
48.70	Wash, 50 lks. wide, 1 ft. deep, drains SE.	
70.60	Wash, 20 lks. wide, 1 ft. deep, drains SE.	
80.40	Point for the cor. of secs. 25, 30, 31 and 36, at pro- portionate distance; there is no remaining evidence of the original corner.	
	Set the post 15 ins. in the ground and in a collar of petrified wood to top, cap mkd.	
	T16N R27E R28E S25 S30 S36 S31 1963	
	Deposit glass at base of post.	
	Land, $S\frac{1}{2}$ mile level; $N\frac{1}{2}$ slopes gently to S. Soil, sandy clay. Timber, scattered cedar; undergrowth, sagebrush.	
	<hr/> N. 0°30' W., bet. secs. 25 and 30.	
	Over gently rolling land, through scattered timber.	

CHAINS

10.30 Asc. S. slope of ridge.

18.20 End major asc.; over nearly level land.

30.00 Enter dense timber.

40.20 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T16N  
R27E R28E  
 $\frac{1}{4}$   
S25|S30  
1963

from which

A cedar, 9 ins. diam., bears S. 30°15' E., 37 lks. dist., mkd.  $\frac{1}{4}$  S 30 BT

A cedar, 8 ins. diam., bears N. 61° W., 53 lks. dist., mkd.  $\frac{1}{4}$  S 25 BT

80.40 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N  
R27E R28E  
S24 | S19  
S25 | S30  
1963

from which

A cedar, 10 ins. diam., bears S. 56°30' E., 51 lks. dist., mkd. S 30 BT

A cedar, 10 ins. diam., bears N. 50°15' W., 31 lks. dist., mkd. S 24 BT

Raise a mound of stone W. of corner.

Land, gently rolling.  
Soil, sandy clay.  
Timber, cedar; undergrowth, sagebrush and grasses.

---

N. 0°30' W., bet. secs. 19 and 24.

Over level land, through dense timber and sparse undergrowth.

19.50 Barbed wire fence, bears irregularly E. and W.

40.20 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N  
R27E R28E  
 $\frac{1}{4}$   
S24|S19  
1963

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Resurvey, W. Bdy., T. 16 N., R. 28 E., Arizona</p> <hr/> <p>from which</p> <p>A cedar, 10 ins. diam., bears S. 18° W., 79 lks. dist., mkd. ¼ S 24 BT</p> <p>A cedar, 8 ins. diam., bears N. 28°30' W., 24 lks. dist., mkd. ¼ S 24 BT</p> <p>Deposit glass at base of post; raise a small mound of stone W. of corner.</p> <p>80.40 Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R27E R28E S13 S18 S24 S19 1963</p> <p>from which</p> <p>A cedar, 8 ins. diam., bears S. 15°30' W., 42 lks. dist., mkd. S 24 BT</p> <p>A cedar, 10 ins. diam., bears N. 18°15' W., 250 lks. dist., mkd. T16N R27E S13 BT</p> <p>Deposit glass at base of post; raise a small mound of stone W. of corner.</p> <p>Land, nearly level. Soil, sandy. Timber, cedar; undergrowth, sagebrush and range grasses.</p>
	<p>N. 0°30' W., bet. secs. 13 and 18.</p> <p>Over level land, through scattered timber.</p>
	<p>8.50 Track road, bears N. 80° E. and S. 80° W.</p>
	<p>40.20 Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R27E R28E ¼ S13 S18 1963</p> <p>from which</p> <p>A cedar, 15 ins. diam., bears S. 77°15' E., 204 lks. dist., mkd. ¼ S 18 BT (only bearing tree available within limits)</p>

CHAINS

Deposit glass at base of post; raise a mound of stone, 2½ ft. base, 2 ft. high, W. of corner.

60.65 Barbed wire fence, bears S. 80°23' E. and N. 80°23' W.

80.40 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N  
R27E R28E  
S12 | S7  
S13 | S18  
1963

from which

A cedar, 9 ins. diam., bears S. 50°15' E., 36 lks. dist., mkd. S 18 BT

A cedar 10 ins. diam., bears N. 89°45' W., 62 lks. dist., mkd. S 12 BT

Raise a small mound of earth and stone W. of corner.

Land, level.

Soil, sandy clay.

Timber, cedar; undergrowth, blue sage.

N. 0°30' W., bet. secs. 7 and 12.

Over level land, through dense timber.

3.30 Track road, bears N. 60° W. and S. 60° E.

40.20 Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N  
R27E R28E  
¼  
S12 | S7  
1963

from which

A cedar, 7 ins. diam., bears S. 43° E., 28 lks. dist., mkd. ¼ S 7 BT

A cedar, 10 ins. diam., bears N. 60°30' W., 20 lks. dist., mkd. ¼ S 12 BT

76.00 Asc. gentle S. slope to cor.

80.40 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N  
R27E R28E  
S1 | S6  
S12 | S7  
1963



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Resurvey, W . Bdy., T. 16 N., R. 28 E., Arizona

Raise a small mound of stone W. of corner.

Land, nearly level.

Soil, sandy.

Timber, cedar.

Undergrowth, yellow top sage and bunch grass.

N. 0°30' W., bet. secs. 1 and 6.

Over level land, through dense timber.

5.53

Point for the closing corner of secs. 1 and 6, on the N. bdy. of the township, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

S 1	S 6
R27E	R28E
T16N	
CC	
1963	

from which

The standard cor. of T. 17 N., Rs. 27 and 28 E. bears S. 89°36' E., 2.08 chs. dist.

The standard cor. of T. 17 N., Rs. 26 and 27 E. bears N. 89°36' W., 480.32 chs. dist., monumented by a large mound of stone set in corner of fences bearing generally N., E. and W. This mound is accepted locally as the corner.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

SC	
T17N	
R26E	R27E
S36	S31
1963	

Reconstruct mound of stone N. of corner.

Land, nearly level.

Soil, sandy.

Timber, cedar.

Undergrowth, sagebrush and grasses.

16

CHAINS

## Reestablishment of the Survey in 1882 by H. A. Coe

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the township, an iron post as described in the field notes of T. 15 N., R. 28 E., being surveyed under this group number.

N.  $1^{\circ}34'$  E., bet. secs. 35 and 36.

Over gently rolling land, through sparse timber.

- 4.90 Track road, bears N.  $75^{\circ}$  W. and S.  $50^{\circ}$  E.  
 5.18 Barbed wire fence, bears S.  $47^{\circ}09'$  E. and N.  $47^{\circ}09'$  W.  
 14.30 Barbed wire fence, bears N.  $76^{\circ}49'$  E. and S.  $76^{\circ}49'$  W.  
 40.25 Point for the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   
 S35|S36  
 1963

Deposit glass at base of post.

- 59.70 Track road, bears N.  $60^{\circ}$  E. and S.  $60^{\circ}$  W.  
 80.50 The cor. of secs. 25, 26, 35 and 36, monumented by a wooden post,  $3\frac{1}{2}$  ft. long, 3 ins. square, well marked, loosely set.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 S26|S25  
 S35|S36  
 1963

All original bearing trees in evidence and correct as noted in official record.

Land, gently rolling.

Soil, sandy.

Timber, scattered cedar; undergrowth, yellow and blue top sage.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the township.

N.  $89^{\circ}44'$  W., bet. secs. 25 and 36.

Over nearly level land, through scattered timber.

- 39.88 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   $\frac{S\ 25}{S\ 36}$   
 1963

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona</p> <hr/> <p>Deposit glass at base of post.</p>
50.50	Track road, bears N. 20° E. and S. 45° W.
79.76	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, nearly level. Soil, sandy. Timber, cedar; undergrowth, sagebrush and grasses.</p> <hr/> <p>N. 0°21' E., bet. secs. 25 and 26.</p> <p>Over gently rolling land, through dense timber.</p> <p>Asc. gentle S. slope.</p>
33.50	Crest of low ridge, bears NE. and SW.; desc. gentle N. slope.
40.12	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented by the original wooden post, 3 ft. long, 3 ins. square, dimly marked and firmly set. All original bearing trees in evidence and correct as in official record.</p> <p>At the corner point</p> <p>Set the post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E 1/4 S26   S25 1963</p> <p>Deposit glass at base of post.</p> <hr/> <p>N. 0°28' E., beginning new measurement.</p>
39.94	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E S23   S24 S26   S25 1963</p> <p>from which</p> <p>A cedar, 5 ins. diam., bears S. 41°30' E., 19 lks. dist., mkd. S 25 BT</p> <p>A cedar, 6 ins. diam., bears S. 38°30' W., 120 lks. dist., mkd. T16N R28E S26 BT</p> <p>A cedar, 6 ins. diam., bears N. 31° W., 77 lks. dist., mkd. S 23 BT</p> <p>Land, gently rolling. Soil, sandy. Timber, cedar; undergrowth, yellow top sage and grasses.</p> <hr/>

CHAINS

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the township.

N. 89°57' W., bet. secs. 24 and 25.

Over gently rolling land, through dense timber.

2.40 Barbed wire fence, bears N. and S.

40.29 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

1/4 S 24

S 25

1963

from which

A cedar, 7 ins. diam., bears S. 80°45' W., 61 lks. dist., mkd. 1/4 S 25 BT

A cedar, 7 ins. diam., bears N. 12° W., 35 lks. dist., mkd. 1/4 S 24 BT

80.58 The cor. of secs. 23, 24, 25 and 26.

Land, gently rolling.

Soil, sandy loam.

Timber, cedar; undergrowth, sagebrush and grasses.

N. 0°12' E., bet. secs. 23 and 24.

Over gently rolling land, through scattered timber.

35.50 Crest of low ridge, bears NE. and SW.; desc. gentle NW. slope.

39.94 Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

1/4 S23 | S24

1963

from which

A cedar, 6 ins. diam., bears S. 64°45' E., 57 lks. dist., mkd. 1/4 S 24 BT

A cedar, 6 ins. diam., bears N. 15° W., 12 lks. dist., mkd. 1/4 S 23 BT

57.80 Barbed wire fence, bears N. 83° W. and S. 83° E.

79.88 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona

T16N R28E  
S14 | S13  
S23 | S24  
1963

from which

A cedar, 12 ins. diam., bears S. 36° W., 83 lks. dist., mkd S 23 BT

A cedar, 7 ins. diam., bears N. 2°30' W., 46 lks. dist., mkd. S 14 BT

Land, gently rolling.

Soil, sandy.

Timber, cedar; undergrowth, sagebrush and bunchgrass.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the township.

S. 89°45' W., bet. secs. 13 and 24.

Over nearly level land, through moderate growth of timber.

6.65 Barbed wire fence, bears N. and S.

40.88 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
1/4 S 13  
S 24  
1963

from which

A cedar, 9 ins. diam., bears S. 22° E., 188 lks. dist., mkd. 1/4 S 24 BT

A cedar, 8 ins. diam., bears S. 20°45' W., 191 lks. dist., mkd. 1/4 S 24 BT

81.75 The cor. of secs. 13, 14, 23 and 24.

Land, nearly level.

Soil, sandy loam.

Timber, cedar; undergrowth, sagebrush and grasses.

N. 1°26' E., bet. secs. 13 and 14.

Over gently rolling land, through scattered timber.

16.00 Asc. gentle S. slope.

29.00 Crest of low ridge, bears NE. and SW.; gentle desc.

CHAINS

39.95 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 20 ins. in the ground, cap mkd.

T16N R28E  
1/4  
S14 | S13  
1963

44.00 Desc. NW. slope of ridge.

79.00 Leave timber, over nearly level land.

79.90 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
S11 | S12  
S14 | S13  
1963

Land, gently rolling.  
Soil, sandy clay.  
Timber, scattered cedar; undergrowth, sagebrush and bunch grass.

---

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the township.

S. 89°27' W., bet. secs. 12 and 13.

Over nearly level land, through low undergrowth, no timber.

6.00 Barbed wire fence, bears irregularly N. and S.

40.60 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
1/4 S 12  
S 13  
1963

Continue over nearly level grassland.

81.20 The cor. of secs. 11, 12, 13 and 14.

Land, nearly level.  
Soil, sandy.  
Timber, sparse cedar; undergrowth, yellow and blue top sage.

---

N. 0°18' E., bet. secs. 11 and 12.

Over nearly level grassland, through sparse timber.

4.30 Wash, 30 lks. wide, 4 ft. deep, drains N. 75° W.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona
39.94	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E <math>\frac{1}{4}</math> S11 S12 1963</p>
43.45	<p>Hardscrabble Wash, 40 lks. wide, 3 ft. deep, drains S. 45° W.</p>
65.50	<p>Track road, bears N. 65° E. and W.</p>
79.88	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E S 2   S 1 S11 S12 1963</p> <p>Land, nearly level. Soil, sandy clay. Timber, sparse cedar; undergrowth, sage brush and bunch grass.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the township.</p> <p>S. 89°06' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through scattered timber.</p>
11.00	<p>Hardscrabble Wash, 30 lks. wide, 2 ft. deep, drains irregularly SW.</p>
28.10	<p>Track road, bears irregularly NE. and SW.</p>
41.13	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R28E <math>\frac{1}{4}</math> <math>\frac{S 1}{S 12}</math> 1963</p> <p>Raise a small mound of stone N. of corner.</p>
82.26	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, cedar; undergrowth, yellow sage and bunch grass.</p>

22

## CHAINS

N. 3°21' E., bet. secs. 1 and 2.

Over nearly level land, through scattered timber.

5.83

Point for the closing corner of secs. 1 and 2 on the N. bdy. of the township, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

$\frac{S 2}{T16N R28E}$  |  $\frac{S 1}{CC}$   
 1963

From this C.C. the Stan. cor. of secs. 35 and 36, T. 17 N., R. 28 E., bears S. 89°41' E., 2.57 chs. dist.

Land, nearly level.

Soil, sandy.

Timber, cedar; undergrowth, sagebrush and grasses.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 1 is on the N. bdy. of the township and mid-point bet. the C.Cs.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

$\frac{1}{4} S 1$   
 $\frac{T16N R28E}{1963}$

Deposit glass at base of post.

From this cor. the Stan.  $\frac{1}{4}$  sec. cor. of sec. 36, T. 17 N., R. 28 E., bears S. 89°41' E., 2.74 chs. dist.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, an iron post as described in the field notes of T. 15 N., R. 28 E., being surveyed under this group number.

N. 1°41' E., bet. secs. 34 and 35.

Over nearly level land, through scattered timber.

Asc. gentle S. slope.

16.10

Crest of low ridge, bears NW. and SE.; desc. gentle N. slope.

40.04

Point for the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 26 ins. in the ground, cap mkd.

$\frac{T16N R28E}{\frac{1}{4}}$   
 $\frac{S34}{1963}$  |  $\frac{S35}{BT}$

from which

A cedar, 8 ins. diam., bears S. 42°30' E., 32 lks. dist., mkd.  $\frac{1}{4}$  S 35 BT



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS					
	<p>Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona</p>				
80.08	<p>A cedar, 12 ins. diam., bears S. 23° W., 71 lks. dist., mkd. <math>\frac{1}{4}</math> S 34 BT</p> <p>Deposit glass at base of post; raise small mound of earth and stone W. of cor.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> </table> <p>1963</p> </div> <p>from which</p> <p>A cedar, 8 ins. diam., bears N. 86° E., 100 lks. dist., mkd. S 26 BT</p> <p>A cedar, 8 ins. diam., bears S. 41°15' E., 35 lks. dist., mkd. S. 35 BT</p> <p>Deposit glass at base of post; raise a small mound of stone W. of corner.</p> <p>Land, nearly level. Soil, sandy. Timber, cedar; undergrowth, sagebrush.</p>	S27	S26	S34	S35
S27	S26				
S34	S35				
11.50	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°53' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Desc. gentle W. slope.</p>				
24.00	<p>Shallow draw, drains SW.</p>				
39.90	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35, monumented by the original wooden post, 3 ft. long, 3 ins. square, plainly marked and firmly set.</p> <p>At the corner point</p> <p>Set the post 20 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E</p> <table border="1" style="margin: auto;"> <tr> <td><math>\frac{1}{4}</math> S 26</td> </tr> <tr> <td>S 35</td> </tr> </table> <p>1963</p> </div> <p>from which</p> <p>A cedar, 12 ins. diam., bears S. 45°45' E., 102 lks. dist., mkd. <math>\frac{1}{4}</math> S 35 BT</p>	$\frac{1}{4}$ S 26	S 35		
$\frac{1}{4}$ S 26					
S 35					

CHAINS

A cedar, 10 ins. diam., bears N. 21°30' W., 27 lks. dist., mkd. ¼ S 26 BT

S. 89°29' W., beginning new measurement.

Desc. along gentle NW. slope through scattered timber.

40.36 The cor. of secs. 26, 27, 34 and 35.

Land, gently rolling.  
Soil, sandy.  
Timber, cedar; undergrowth, sagebrush and grasses.

N. 0°26' E., bet. secs. 26 and 27.

Over gently rolling land, through scattered timber.

39.40 Low spur, bears irregularly NE. and SW.

40.03 Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

¼  
S27|S26  
1963

from which

A cedar, 9 ins. diam., bears S. 40°45' E., 97 lks. dist., mkd. ¼ S 26 BT

A cedar, 12 ins. diam., bears S. 82°15' W., 109 lks. dist., mkd. T16N R28E ¼ S 27 BT

54.30 Wash, 20 lks. wide, 3 ft. deep, drains S. 85° W.

80.05 Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

S22|S23  
S27|S26  
1963

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, gently rolling.  
Soil, sandy.  
Timber, cedar; undergrowth, sagebrush and grasses.

From the cor. of secs. 23, 24, 25 and 26.

S. 89°47' W., bet. secs. 23 and 26.

Over nearly level land, through sparse timber and undergrowth.

40.13 Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

BOOK 4691  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona
	Set the post 24 ins. in the ground, cap mkd.
	T16N R28E $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ 1963
	Raise a small mound of earth and stone N. of corner.
75.25	Cross series of small washes, drain generally S. 15° W.
80.26	The cor. of secs. 22, 23, 26 and 27.
	Land, nearly level. Soil, sandy loam. Timber, cedar; undergrowth, sagebrush and grasses.
	N. 1°01' W., bet. secs. 22 and 23.
	Over gently rolling land, no timber.
	Desc. gentle NW. slope.
27.70	Wash, 25 lks. wide, 4 ft. deep, drains S. 75° W.
30.30	Wash, 20 lks. wide, 4 ft. deep, drains S. 85° W.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	T16N R28E $\frac{1}{4}$ S22 S23 1963
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of corner.
59.55	Barbed wire fence, bears N. 80° E. and S. 80° W.
72.35	Wash, 30 lks. wide, 2 ft. deep, drains N. 85° W.
80.06	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	T16N R28E S15 S14 S22 S23 1963
	Land, gently rolling. Soil, sandy loam. Timber, none; undergrowth, sagebrush and grasses.

## CHAINS

From the cor. of secs. 13, 14, 23 and 24.

S. 89°56' W., bet. secs. 14 and 23.

Over gently rolling land, through scattered timber.

25.00 Desc. gentle W. slope.

40.98 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$   $\frac{S 14}{S 23}$

1963

Cor. falls on gentle W. slope.

51.34 Barbed wire fence, bears N. 7° E. and S. 7° W.

81.95 The cor. of secs. 14, 15, 22 and 23.

Land, gently rolling.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, sagebrush and range grasses.

N. 1°35' E., bet. secs. 14 and 15.

Over level land, through low undergrowth, no timber.

25.10 Hardscrabble Wash, 20 lks. wide, 2 ft. deep, drains S. 75° W.

40.04 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$   
S15 | S14

1963

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Asc. gentle N. slope from valley floor.

80.08 The cor. of secs. 10, 11, 14 and 15, monumented by the original wooden post, 4 ft. long, 3 ins. square, dimly marked, firmly set.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

S10 | S11  
S15 | S14

1963

Raise a small mound of stone W. of corner.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona
	Land, nearly level. Soil, sandy. Timber, none; undergrowth, sagebrush and range grasses.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°55' W., bet. secs. 11 and 14. Over gently rolling land; desc. gentle W. slope.
40.56	Barbed wire fence, bears N. 12° E. and S. 12° W.
40.84	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.  Set the post 24 ins. in the ground, cap mkd.  T16N R28E ¼ $\frac{S 11}{S 14}$ 1963
	Cor. falls on level bottom land.
44.00	Hardscrabble Wash, 45 lks. wide, 2 ft. deep, drains S. 40° W.; asc. gentle E. slope.
81.68	The cor. of secs. 10, 11, 14 and 15.  Land, gently rolling. Soil, sandy loam. Timber, sparse cedar; undergrowth, dense sagebrush and grasses.
	N. 0°36' W., bet. secs. 10 and 11.  Over gently rolling land.
40.27	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.  Set the post 22 ins. in the ground, cap mkd.  T16N R28E ¼ S10   S11 1963
66.70	End asc.; over level land, through medium growth of timber.
80.54	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.  Set the post 20 ins. in the ground and in a collar of stone to top, cap mkd.  T16N R28E S3   S2 S10   S11 1963

CHAINS

Land, gently rolling.  
Soil, sandy loam.  
Timber, sparse cedar; undergrowth, sagebrush.

41.45

From the cor. of secs. 1, 2, 11 and 12.  
N. 89°26' W., bet. secs. 2 and 11.  
Over gently rolling land, through scattered timber.  
Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.  
Set the post 20 ins. in the ground and in a collar of stone to top, cap mkd.

T16N R28E  
1/4 S 2  
S 11  
1963

82.90

The cor. of secs. 2, 3, 10 and 11.  
Land, gently rolling.  
Soil, sandy loam.  
Timber, cedar; undergrowth, sagebrush and bunchgrass.

5.56

N. 8°53' E., bet. secs. 2 and 3.  
Over level land, through scattered timber.  
Point for the closing corner of secs. 2 and 3, on the N. bdy. of the township, at proportionate distance; there is no remaining evidence of the original corner.  
Set the post 24 ins. in the ground, cap mkd.

S 3 | S 2  
T16N R28E  
CC  
1963

Raise a small mound of stones S. of cor; deposit glass at base of post.  
From this C.C. the Stan. cor. of secs. 34 and 35 bears S. 89°41' E., 2.75 chs. dist.  
Land, nearly level.  
Soil, sandy loam.  
Timber, cedar; undergrowth, sparse sagebrush and grasses.

The point for the 1/4 sec. cor. of sec. 2 is on the N. bdy. of the township and at mid-point bet. the C.Cs.  
At the corner point  
Set the post 24 ins. in the ground, cap mkd.

1/4 S 2  
T16N R28E  
1963

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona

from which

A cedar, 6 ins. diam., bears S. 61°30' W., 192  
lks. dist., mkd.  $\frac{1}{4}$  S 2 BT

From this cor. the Stan.  $\frac{1}{4}$  sec. cor. of sec. 35 bears  
S. 89°41' E., 2.66 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy.  
of the township, an iron post as described in the field  
notes of T. 15 N., R. 28 E., being surveyed under this  
group number.

N. 1°36' E., bet. secs. 33 and 34.

Over rolling land, through scattered timber.

14.50 Desc. gentle NW. slope.

19.70 Wash, 20 lks. wide, 3 ft. deep, drains S. 75° W.;  
asc. gentle S. slope.

40.27 Point for the  $\frac{1}{4}$  sec. cor. of secs. 33 and 34, at pro-  
portionate distance; there is no remaining evidence  
of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   
S33|S34  
1963

Deposit glass at base of post; raise a mound of stone,  
3 ft. base, 2 ft. high, W. of cor.

80.54 The cor. of secs. 27, 28, 33 and 34, monumented by a  
wooden post, 3 ft. long, 4 ins. square, clearly mkd.  
loosely set.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
S28|S27  
S33|S34  
1963

Land, rolling.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, yellow top sage  
and grasses.

From the cor. of secs. 26, 27, 34 and 35.

N. 89°35' W., bet. secs. 27 and 34.

Desc. gentle W. slope.

40.23 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 34, at pro-  
portionate distance; there is no remaining evidence of  
the original corner.

## CHAINS

Set the post 25 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$   $\frac{S 27}{S 34}$

1963

Deposit glass at base of post; raise a small mound of earth and stone N. of corner.

65.40 Asc. gentle E. slope to cor.

80.45 The cor. of secs. 27, 28, 33 and 34.

Land, gently rolling.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, bunch grass and sagebrush.

N. 0°20' E., bet. secs. 27 and 28.

Over nearly level land, through sparse timber and undergrowth.

Asc. gentle S. slope.

3.00 Crest of low ridge, bears NE. and SW.; desc. gentle N. slope.

31.10 Wash, 20 lks. wide, 3 ft. deep, drains irregularly SW. into Hardscrabble Wash.

40.18 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$   
S28 | S27

1963

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the corner.

66.85 Barbed wire fence, bears N. 36° E. and S. 36° W.

80.36 The cor. of secs. 21, 22, 27 and 28, monumented by a wooden post, 3 ft. long, 3 ins. square, dimly mkd., loosely set.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

S21 | S22  
S28 | S27

1963

Land, gently rolling.

Soil, sandy.

Timber, scattered cedar; undergrowth, bunch grass and shadscale.

From the cor. of secs. 22, 23, 26 and 27.

N. 89°23' W., bet. secs. 22 and 27.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

CHAINS	
	Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona
	Desc. gentle W. slope through sparse timber and undergrowth.
40.32	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R28E <math>\frac{1}{4}</math> <math>\frac{S\ 22}{S\ 27}</math> 1963</p>
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.
71.18	Barbed wire fence, bears N. 15° E. and S. 15° W.
80.64	The cor. of secs. 21, 22, 27 and 28.
	<p>Land, nearly level. Soil, clay hardpan. Timber, scattered cedar; undergrowth, grama and bunch grass.</p>
	N. 1°44' W., bet. secs. 21 and 22.
	Over nearly level land, no timber.
19.20	Hardscrabble Wash, 40 lks. wide, 3 ft. deep, drains S. 70° W.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R28E <math>\frac{1}{4}</math> S21 S22 1963</p>
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the corner.
42.50	Leave level land; asc. gentle S. slope.
80.07	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R28E S16 S15 S21 S22 1963</p>
	<p>Land, level S<math>\frac{1}{2}</math> mile; gently rolling N<math>\frac{1}{2}</math> mile. Soil, sandy. Timber, none; undergrowth, yellow top sage and bunch grass.</p>

CHAINS

From the cor. of secs. 14, 15, 22 and 23.

N. 89°23' W., bet. secs. 15 and 22.

Over gently rolling land, through scattered timber.

21.00 Hardscrabble Wash, 20 lks. wide, 4 ft. deep, drains S. 18° W.

40.81 Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   $\frac{S\ 15}{S\ 22}$   
 1963

Deposit glass at base of post.

48.20 Asc. gentle E. slope.

64.20 Crest of ridge, bears N. 30° E. and S. 30° W.

81.62 The cor. of secs. 15, 16, 21 and 22.

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, scattered cedar; undergrowth, sagebrush and grasses.

N. 1°37' E., bet. secs. 15 and 16.

Asc. gentle S. slope through scattered timber.

40.03 Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   $\frac{S16}{S15}$   
 1963

Deposit glass at base of post.

56.15 Wash, 15 lks. wide, 3 ft. deep, drains E.

60.00 Slope changes from S. to SE.

75.45 Wash, 10 lks. wide, 3 ft. deep, drains SE.

80.06 Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{S9}{S16}$  |  $\frac{S10}{S15}$   
 1963

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, sparse cedar; undergrowth, yellow top sage and grasses.

BOOK 4681  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°38' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land, through sparse timber and undergrowth.</p>
40.78	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 15, monumented by the original wooden post, 3 ft. long, 2 ins. square, dimly mkd. and loosely set.</p> <p>At the corner point</p> <p>Set the post 25 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E</p> <p><math>\frac{1}{4}</math> <math>\frac{S 10}{S 15}</math></p> <p>1963</p> </div> <p>Raise a small mound of stone N. of the corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 88°27' W., beginning new measurement.</p>
12.30	Wash, 30 lks. wide, 3 ft. deep, drains S.
40.79	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling.</p> <p>Soil, sandy loam.</p> <p>Timber, scattered cedar; undergrowth, sagebrush.</p> <hr style="width: 80%; margin: auto;"/> <p>N. 1°15' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Continue along NE. slope.</p>
21.40	Desc. gentle NE. slope.
25.00	Wash, 10 lks. wide, 2 ft. deep, drains E.
40.03	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R28E</p> <p><math>\frac{1}{4}</math> S9   S10</p> <p>1963</p> </div>
64.15	Wash, 45 lks. wide, 2 ft. deep, drains SE.
68.80	Same wash, 45 lks. wide, 2 ft. deep, drains S.
80.05	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p>

CHAINS

Set the post 20 ins. in the ground, collar with stone to top, cap mkd.

T16N R28E  
 $\frac{S\ 4}{S\ 9} \mid \frac{S\ 3}{S\ 10}$   
 1963

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, scattered cedar; undergrowth, dense sagebrush.

---

From the cor. of secs. 2, 3, 10 and 11.

N. 89°45' W., bet. secs. 3 and 10.

Over gently rolling land, through scattered timber.

41.19 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 20 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4} \frac{S\ 3}{S\ 10}$   
 1963

Raise a small mound of earth and stone N. of corner.

82.38 The cor. of secs. 3, 4, 9 and 10.

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, cedar; undergrowth, low sagebrush and bunch grass.

---

N. 7°08' E., bet. secs. 3 and 4.

Over nearly level land, through scattered timber.

2.70 Barbed wire drift fence, bears N. 55° E. and S. 55° W.

5.63 Point for the closing corner of secs. 3 and 4 on the N. bdy. of the township, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

$\frac{S\ 4}{T16N\ R28E} \mid \frac{S\ 3}{CC}$   
 1963

Deposit glass at base of post.

From this C.C., the Stan. cor. of secs. 33 and 34 bears S. 89°41' E., 3.08 chs. dist.

Land, nearly level.  
 Soil, sandy loam.  
 Timber, cedar; undergrowth, sagebrush and range grasses.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

## CHAINS

Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona

The point for the  $\frac{1}{4}$  sec. cor. of sec. 3 is on the N. bdy. of the township and at mid-point bet. the C.Cs.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

$\frac{1}{4}$  S3  
T16N R28E  
1963

Raise a small mound of stone S. of cor.; deposit glass at base of post.

From this cor. the Stan.  $\frac{1}{4}$  sec. cor. of sec. 34 bears S.  $89^{\circ}41'$  E., 2.92 chs. dist.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the township, an iron post as described in the field notes of T. 15 N., R. 28 E., being surveyed under this group number.

N.  $1^{\circ}05'$  E., bet. secs. 32 and 33.

Over level land, no timber.

16.40 Track road, bears S.  $60^{\circ}$  E. and N.  $60^{\circ}$  W.

40.55 Point for the  $\frac{1}{4}$  sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 25 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   
S32|S33  
1963

Deposit glass at base of post; raise a small mound of stone W. of corner.

52.15 Hardscrabble Wash, 25 lks. wide, 4 ft. deep, drains irregularly SW.

59.05 Track road, bears N.  $70^{\circ}$  E. and S.  $80^{\circ}$  W.

62.00 Asc. gentle SE. slope.

81.10 The cor. of secs. 28, 29, 32 and 33, monumented by the original wooden post, 3 ft. long, 2 ins. square, dimly marked and loosely set.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
S29|S28  
S32|S33  
1963

CHAINS

Raise a small mound of stone W. of the corner.  
 Land, level.  
 Soil, sandy loam.  
 Timber, none; undergrowth, sparse sagebrush and grasses.

From the cor. of secs. 27, 28, 33 and 34.

N. 89°28' W., bet. secs. 28 and 33.

Over gently rolling land, through scattered timber.

6.50 Crest of low ridge, bears NE. and SW.; desc. gentle W. slope.

30.15 Hardscrabble Wash, 40 lks. wide, 2 ft. deep, drains S. 20° W.

40.57 Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 25 ins. in the ground, cap mkd.

T16N R28E  
 ¼  $\frac{S\ 28}{S\ 33}$   
 1963

Deposit glass at base of post; raise a small mound of stone N. of the corner.

41.40 Track road, bears N. 15° E. and S. 15° W.

81.14 The cor. of secs. 28, 29, 32 and 33.

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, cedar; undergrowth, yellow top sage and bunch grass.

N. 0°47' E., bet. secs. 28 and 29.

Over nearly level land, through sparse timber and undergrowth.

19.35 Wash, 20 lks. wide, 3 ft. deep, drains S. 80° E.

40.24 Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 ¼  $\frac{S29}{S28}$   
 1963

Raise a small mound of stone W. of the corner.

51.60 Wash, 70 lks. wide, 4 ft. deep, drains S. 55° E.

74.00 Top of low ridge, bears E. and W.; desc. gentle N. slope.

77.90 Wash, 15 lks. wide, 3 ft. deep, drains irregularly E.

80.48 The cor. of secs. 20, 21, 28 and 29, monumented by

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona

the original wooden post, 3 ft. long, 3 ins. square, dimly marked and firmly set.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
S20|S21  
S29|S28  
1963

from which

A cedar, 10 ins. diam., bears N. 48°45' E.,  
41 lks. dist., mkd. S 21 BT

A cedar, 12 ins. diam., bears S. 22°45' E.,  
77 lks. dist., mkd. S 28 BT

Land, nearly level.

Soil, sandy loam.

Timber, cedar; undergrowth, blue sage and grasses.

From the cor. of secs. 21, 22, 27 and 28.

N. 89°21' W., bet. secs. 21 and 28.

Over gently rolling land, through scattered timber.

7.65 Hardscrabble Wash, 30 lks. wide, 2 ft. deep, drains S.  
10° W.; asc. gentle E. slope.

17.00 Track road, bears N. 5° E. and S. 10° W.

40.24 Point for the 1/4 sec. cor. of secs. 21 and 28, at pro-  
portionate distance; there is no remaining evidence  
of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
1/4 S 21  
S 28  
1963

Raise a mound of stone, 2 ft. base, 2 ft. high, N.  
of the corner.

55.30 Wash, 10 lks. wide, 1 ft. deep, drains S. 5° E.

58.40 Barbed wire fence, bears N. 45° W. and S. 45° E.

80.48 The cor. of secs. 20, 21, 28 and 29.

Land, gently rolling.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, grama grass and  
sagebrush.

CHAINS

N. 2°29' W., bet. secs. 20 and 21.

Over level land, through scattered timber.

7.45 Barbed wire fence, bears N. 71° W. and S. 71° E.

40.03 Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

¼  
 S20 | S21  
 1963

from which

A cedar, 6 ins. diam., bears N. 5° E., 147 lks. dist., mkd. ¼ S 21 BT

A cedar, 20 ins. diam., bears S. 3°45' W., 119 lks. dist., mkd. ¼ S 20 BT

80.06 Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

S17 | S16  
 S20 | S21  
 1963

Deposit glass at base of post.

Land, level.  
 Soil, sandy loam.  
 Timber, cedar; undergrowth, low sagebrush and grasses.

From the cor. of secs. 15, 16, 21 and 22.

N. 89°24' W., bet. secs. 16 and 21.

Over gently rolling land, through scattered timber and low undergrowth.

6.15 Top of small ridge, bears N. and S.

38.80 Track road, bears N. 14° W. and S. 8° E.

40.75 Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 22 ins. in the ground, cap mkd.

T16N R28E

¼ S 16  
 S 21  
 1963

68.10 Wash, 30 lks. wide, 3 ft. deep, drains S. 30° E.

81.50 The cor. of secs. 16, 17, 20 and 21.

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, scattered cedar; undergrowth, dense sagebrush.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

## CHAINS

Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona

N. 1°07' E., bet. secs. 16 and 17.

Over nearly level land, through scattered timber and dense undergrowth.

6.90 Wash, 25 lks. wide, 5 ft. deep, drains S. 50° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S17} | \text{S16} \\ \hline 1963 \end{array}$$

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of corner.

64.00 Track road, bears N. 35° W. and S. 35° E.

80.00 Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$$\begin{array}{c} \text{S8} | \text{S9} \\ \hline \text{S17} | \text{S16} \\ \hline 1963 \end{array}$$

from which

A cedar, 10 ins. in diam., bears S. 74° E.,  
78 lks. dist., mkd. S 16 BTA cedar, 6 ins. diam., bears S. 5°30' W., 83  
lks. dist., mkd. S 17 BT

Land, nearly level.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, sagebrush and range grasses.

From the cor. of secs. 9, 10, 15 and 16.

S. 87°42' W., bet. secs. 9 and 16.

Over gently rolling land, through scattered timber.

Asc. along gentle S. slope.

22.50 Top of low spur, bears NE. and SW.; desc. over SW. slope.

40.63 The  $\frac{1}{4}$  sec. cor. of secs. 9 and 16, monumented by the original wooden post, 3 ft. long, 3 ins. square, dimly marked and loosely set.

CHAINS

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4} \frac{S 9}{S 16}$   
 1963

Raise a small mound of earth and stone N. of the corner.

---

N. 86°44' W., beginning new measurement.

41.67 The cor. of secs. 8, 9, 16 and 17.

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, sparse cedar.  
 Undergrowth, dense blue sagebrush.

---

N. 1°32' W., bet. secs. 8 and 9.

Over gently rolling land, through scattered timber.

26.00 Barbed wire fence, bears N. 60° E. and S. 60° W.

26.40 Track road, parallels fenceline.

40.01 Point for the  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   
 S 8 | S 9  
 1963

80.02 Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 S 5 | S 4  
 S 8 | S 9  
 1963

Land, gently rolling.  
 Soil, sandy loam.  
 Timber, cedar.  
 Undergrowth, yellow-top sage, blue sage and bunchgrass.

---

From the cor. of secs. 3, 4, 9 and 10.

N. 89°28' W., bet. secs. 4 and 9.

Over level land, through scattered timber and sparse undergrowth.

41.32 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona</p>
	<p>Set the post 20 ins. in the ground, collar with stone to top, cap mkd.</p> <p style="text-align: center;">T16N R28E <math>\frac{1}{4} \frac{S \ 4}{S \ 9}</math> 1963</p>
82.64	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, nearly level. Soil, sandy loam. Timber, scattered cedar. Undergrowth, blue sage and bunchgrass.</p>
	<p>N. 7°41' E., bet. secs. 4 and 5.</p> <p>Over level land, through scattered timber.</p>
5.32	<p>Point for the closing corner of secs. 4 and 5, on the N. bdy. of the township, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;"><u>S 5   S 4</u> T16N R28E CC 1963</p> <p>From this C.C. the Stan. cor. of secs. 32 and 33 bears S. 89°41' E., 3.51 chs. dist.</p> <p>Land, level. Soil, sandy loam. Timber, cedar. Undergrowth, sagebrush.</p>
	<p>The point for the <math>\frac{1}{4}</math> sec. cor. of sec. 4 is on the N. bdy. of the township and at mid-point bet. the C.Cs.</p> <p>At the corner point</p> <p>Set the post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;"><u><math>\frac{1}{4}</math> S 4</u> T16N R28E 1963</p> <p>Deposit glass at base of post.</p> <p>From this cor. the Stan. <math>\frac{1}{4}</math> sec. cor. of sec. 33 bears S. 89°41' E., 3.29 chs. dist.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the township, an iron post as described in the field notes of T. 15 N., R. 28 E., being surveyed under this group number.</p> <p>N. 0°31' E., bet. secs. 31 and 32.</p>

CHAINS

Over level land, through low undergrowth, no timber.

25.70 Wash, 75 lks. wide, 5 ft. deep, drains irregularly SE.

40.20 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   
 S31|S32  
 1963

Deposit glass at base of post; raise a small mound of stone W. of the corner.

Asc. gentle S. slope.

80.41 Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 S30|S29  
 S31|S32  
 1963

Deposit glass at base of post; raise a small mound of earth and stone W. of the corner.

Land, level.  
 Soil, sandy loam.  
 Timber, scattered cedar.  
 Undergrowth, sagebrush.

From the cor. of secs. 28, 29, 32 and 33.

N. 89°57' W., bet. secs. 29 and 32.

Over gently rolling land, through sparse timber and undergrowth.

8.00 Low spur, bears N. and S.; desc. along SW. slope.

17.15 Wash, 10 lks. wide, 1 ft. deep, drains S.

37.30 Wash, 10 lks. wide, 1 ft. deep, drains S.

39.33 The  $\frac{1}{4}$  sec. cor. of secs. 29 and 32, monumented by the original wooden post, 3 ft. long, 3 ins. square, markings plainly visible, loosely set.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4}$   $\frac{S\ 29}{S\ 32}$   
 1963

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona
	Raise a small mound of stone N. of the corner.
	_____
	S. 89°11' W., beginning new measurement.
3.40	Wash, 20 lks. wide, 3 ft. deep, drains S.
6.10	Track road, bears N. 30° W. and S. 30° E.
41.82	The cor. of secs. 29, 30, 31 and 32.
	Land, gently rolling. Soil, sandy loam. Timber, scattered cedar; undergrowth, sagebrush.
	_____
	N. 89°54' W., bet. secs. 30 and 31.
	Over nearly level land, through sparse timber and undergrowth.
32.50	Wash, 30 lks. wide, 4 ft. deep, drains S.
41.95	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set the post 25 ins. in the ground, cap mkd.
	T16N R28E 1/4 <u>  S 30</u> <u>  S 31</u> 1963
	Deposit glass at base of post; raise a small mound of stone N. of the corner.
62.00	Wash, 30 lks. wide, 3 ft. deep, drains S. 15° E.
69.40	Wash, 15 lks. wide, 2 ft. deep, drains irregularly SE.
81.37	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the township.
	Land, nearly level. Soil, sandy. Timber, cedar; undergrowth, bunchgrass, sagebrush and shadscale.
	_____
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°56' W., bet. secs. 29 and 30.
	Over gently rolling hills.
1.95	Track road, bears N. 80° E. and S. 85° W.
15.45	Wash, 80 lks. wide, 4 ft. deep, drains S. 35° E.
19.05	Wash, 30 lks. wide, 4 ft. deep, drains S. 80° E.

44

CHAINS

- 29.35 Wash, 15 lks. wide, 3 ft. deep, drains S. 35° W.
- 31.90 Enter moderately dense stand of timber, bears NE. and SW.
- 40.21 Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.  
  
Set the post 24 ins. in the ground, cap mkd.  
  

T16N R28E  
 $\frac{1}{4}$   
 S30|S29  
 1963

from which

A cedar, 5 ins. diam., bears N. 40°30' E., 131 lks. dist., mkd. ¼ S 29 BT

A cedar, 6 ins. diam., bears S. 7° W., 60 lks. dist., mkd. ¼ S 30 BT
- 54.70 Leave timber.
- 60.90 Track road, bears N. 85° W. and S. 45° E.
- 80.42 Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.  
  
Set the post 22 ins. in the ground, cap mkd.  
  

T16N R28E  
 $\frac{1}{4}$   
 S19|S20  
 S30|S29  
 1963

from which

A cedar, 16 ins. diam., bears S. 33° E., 168 lks. dist., mkd. S 29 BT

A cedar, 11 ins. diam., bears N. 76° W., 76 lks. dist., mkd. S 19 BT

Land, gently rolling hills.  
 Soil, sandy loam.  
 Timber, cedar; undergrowth, sagebrush and grasses.

---

From the cor. of secs. 20, 21, 28 and 29.  
 S. 89°31' W., bet. secs. 20 and 29.  
 Over gently rolling hills.
- 26.00 Top of low ridge, bears N. 15° E. and S. 25° W.
- 31.30 Small wash, drains irregularly S.
- 41.78 Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.  
  
Set the post 24 ins. in the ground, cap mkd.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

## CHAINS

Resurvey, Subdivision, T. 16 N , R. 28 E., Arizona

T16N R28E

 $\frac{1}{4} \frac{S 20}{S 29}$ 

1963

from which

A cedar, 5 ins. diam., bears S. 32°30' W., 92  
lks. dist., mkd.  $\frac{1}{4}$  S 29 BT

No other bearing trees available within limits.

83.55 The cor. of secs. 19, 20, 29 and 30.

Land, gently rolling hills.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, sagebrush and  
grasses.

N. 89°53' W., bet. secs. 19 and 30.

Over nearly level land.

13.40 Track road, bears N. 25° W. and S. 20° E.

41.70 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, at pro-  
portionate distance; there is no remaining evidence  
of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

 $\frac{1}{4} \frac{S 19}{S 30}$ 

1963

from which

A cedar, 12 ins. diam., bears S. 56° W., 108 lks.  
dist., mkd.  $\frac{1}{4}$  S 30 BTA cedar, 16 ins. diam., bears N. 16°45' W., 25  
lks. dist., mkd. BT80.76 The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of  
the township.

Land, nearly level.

Soil, sandy loam.

Timber, cedar; undergrowth, sagebrush and range grasses.

From the cor. of secs. 19, 20, 29 and 30.

N. 1°26' W., bet. secs. 19 and 20.

Over nearly level land, through scattered timber.

13.90 Asc. gentle S. slope of ridge.

19.70 Barbed wire fence, bears E. and W.

40.22 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, at pro-  
portionate distance; there is no remaining evidence  
of the original corner.

46

CHAINS

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$   
S19|S20  
1963

from which

A cedar, 6 ins. diam., bears S. 89°45' W., 166 lks. dist., mkd.  $\frac{1}{4}$  S 19 BT (only bearing tree within limits).

59.75 Top of small ridge, bears N. 65° E. and S. 80° W.

80.43 Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

S18|S17  
S19|S20  
1963

Land, nearly level.  
Soil, sandy loam.  
Timber, cedar; undergrowth, sagebrush.

From the cor. of secs. 16, 17, 20 and 21.

S. 89°47' W., bet. secs. 17 and 20.

Over gently rolling land.

29.85 Barbed wire fence, bears N. and S.

41.04 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$   $\frac{S 17}{S 20}$   
1963

Deposit glass at base of the post.

Asc. gentle E. slope.

64.60 Top of ridge, bears N. 40° E. and S. 40° W.

82.07 The cor. of secs. 17, 18, 19 and 20.

Land, gently rolling.  
Soil, sandy loam.  
Timber, scattered cedar; undergrowth, sagebrush and grasses.

N. 89°53' W., bet. secs. 18 and 19.

Over level land.

18.95 Barbed wire fence, bears N. and S. 20° W.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona</p> <hr/>
33.35	Track road, bears generally N. and S.
40.89	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p>
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R28E <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{18}{19}</math> 1963</p>
	from which
	<p style="text-align: center;">A cedar, 10 ins. diam., bears N. 58°30' W., 116 lks. dist., mkd. <math>\frac{1}{4}</math> S 18 BT (no other bearing trees available).</p>
79.45	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township.
	<p>Land, level. Soil, sandy loam. Timber, scattered cedar; undergrowth, low sagebrush and grasses.</p> <hr/>
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°17' E., bet. secs. 17 and 18.
	Over gently rolling hills.
35.80	Enter dense stand of timber, bears NE. and SW.
40.21	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p>
	Set the post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R28E <math>\frac{1}{4}</math> S18 S17 1963</p>
	from which
	<p style="text-align: center;">A cedar, 6 ins. diam., bears N. 52°45' E., 49 lks. dist., mkd. <math>\frac{1}{4}</math> S 17 BT</p>
	<p style="text-align: center;">A cedar, 6 ins. diam., bears N. 50°15' W., 33 lks. dist., mkd. T16N R28E <math>\frac{1}{4}</math> S 18 BT</p>
55.90	Barbed wire fence, bears irregularly E. and W.
59.40	Track road, bears N. 80° E. and S. 80° W.
80.41	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p>

CHAINS

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{S 7}{S 18} | \frac{S 8}{S 17}$   
 1963

from which

A cedar, 6 ins. diam., bears N. 57°15' E.,  
 232 lks. dist., mkd. S 8 BT

A cedar, 12 ins. diam., bears S. 50°15' E.,  
 266 lks. dist., mkd. T16N R28E S17 BT

Raise a mound of stone, 3 ft. base, 2½ ft. high, W.  
 of the corner.

Land, gently rolling.

Soil, sandy loam.

Timber, dense cedar; undergrowth, sagebrush and sparse  
 grasses.

From the cor. of secs. 8, 9, 16 and 17.

N. 89°59' W., bet. secs. 8 and 17.

Over level land, through dense timber.

41.58 Point for the ¼ sec. cor. of secs. 8 and 17, at pro-  
 portionate distance; there is no remaining evidence  
 of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
 $\frac{1}{4} \frac{S 8}{S 17}$   
 1963

from which

A cedar, 6 ins. diam., bears S. 84°45' W.,  
 69 lks. dist., mkd. ¼ S 17 BT

A cedar, 9 ins. diam., bears N. 23° W., 24 lks.  
 dist., mkd. T16N R28E ¼ S 8 BT

45.08 Barbed wire fence, bears N. 58° E. and S. 58° W.

83.16 The cor. of secs. 7, 8, 17 and 18.

Land, level.

Soil, sandy loam.

Timber, cedar; undergrowth, sparse sagebrush.

N. 89°51' W., bet. secs. 7 and 18.

Over gently rolling land.

3.40 Track road, bears irregularly NE. and SW.

7.00 Same road, bears N. 35° W. and S. 35° E.

41.64 Point for the ¼ sec. cor. of secs. 7 and 18, at pro-  
 portionate distance; there is no remaining evidence  
 of the original corner.

BOOK 4691  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$   $\frac{S 7}{S 18}$

1963

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the corner.

80.53 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the township.

Land, gently rolling.

Soil, sandy loam.

Timber, scattered cedar; undergrowth, sagebrush.

From the cor. of secs. 7, 8, 17 and 18.

N. 1°08' W., bet. secs. 7 and 8.

Over gently rolling land.

3.35 Track road, bears N. 45° E. and S. 45° W.

4.80 Asc. gentle S. slope of ridge.

40.21 Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E

$\frac{1}{4}$  S 7 | S 8

1963

from which

A cedar, 6 ins. diam., bears N. 85°15' E., 90 lks. dist., mkd. ¼ S 8 BT

A cedar, 12 ins. diam., bears S. 14°45' W., 151 lks. dist., mkd. ¼ S 7 BT

53.00 Top of ridge, bears N. 60° W. and S. 80° E.

74.10 Track road, bears N. 10° W. and S. 10° E.

80.42 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 20 ins. in the ground, collar with stone to top, cap mkd.

T16N R28E

S 6 | S 5  
S 7 | S 8

1963

CHAINS

Land, gently rolling.  
Soil, sandy loam.  
Timber, cedar; undergrowth, sagebrush and range grasses.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°44' W., bet. secs. 5 and 8.

41.29 Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

T16N R28E  
¼  $\frac{S \ 5}{S \ 8}$   
1963

57.90 Track road, bears N. and S.

82.58 The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling.  
Soil, sandy loam.  
Timber, scattered cedar; undergrowth, sagebrush and grasses.

N. 89°49' W., bet. secs. 6 and 7.

Over gently rolling land.

0.80 Track road, bears N. 5° W. and S. 5° E.

41.21 Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 20 ins. in the ground, cap mkd.

T16N R28E  
¼  $\frac{S \ 6}{S \ 7}$   
1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the corner.

79.65 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the township.

Land, gently rolling.  
Soil, sandy loam.  
Timber, cedar; undergrowth, sagebrush and range grasses.

From the cor. of secs. 5, 6, 7 and 8.

N. 5°33' E., bet. secs. 5 and 6.

5.37 Point for the closing corner of secs. 5 and 6 on the N. bdy. of the township, at proportionate distance; there is no remaining evidence of the original corner.

Set the post 24 ins. in the ground, cap mkd.

$\frac{S \ 6}{S \ 5}$   
T16N | R28E  
CC  
1963

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTE PAPER

## CHAINS

Resurvey, Subdivision, T. 16 N., R. 28 E., Arizona

From this C.C., the Stan. cor. of secs. 31 and 32 bears S. 89°41' E., 4.09 lks. dist.

Land, nearly level.  
Soil, sandy loam.  
Timber, cedar; undergrowth, sagebrush.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 5 is on the N. bdy. of the township and at mid-point bet. the C.Cs.

At the corner point

Set the post 24 ins. in the ground, cap mkd.

$\frac{1}{4}$  S 5  
T16N R28E  
1963

Deposit glass at base of post.

From this cor. the Stan.  $\frac{1}{4}$  sec. cor. of sec. 32 bears S. 89°41' E., 3.80 chs. dist.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 6 is on the north boundary of the township, at proportionate distance based upon the theoretical position indicated by the lotting as shown on the plat approved March 14, 1883.

Set the post 24 ins. in the ground, cap mkd.

$\frac{1}{4}$  S 6  
T16N R28E  
1963

From this cor. the Stan.  $\frac{1}{4}$  sec. cor. of sec. 31 bears S. 89°41' E., 4.09 chs. dist.

General Description

Township 16 North, Range 28 East is nearly level to gently rolling, varying from 5560 feet to 5900 feet above sea level. The soil is mostly sandy to sandy loam. There are dense stands of cedar on all the ridges and a moderately dense growth of cedars throughout the north portion of the township.

Most of the washes drain into Hardscrabble Wash, which in turn drains into the Zuni River. Hardscrabble Wash, usually dry, enters the township at the very northeast corner of the township and drains generally southwest.

None of the land is under cultivation but is used extensively for stock grazing. Under normal conditions there is an abundance of native grasses and sagebrush.

52

## CHAINS

There are numerous track roads throughout the township, all leading to windmills and stock tanks. There are also many barbed wire fences, most of the fences having no relation to cardinal directions or section lines and serving only as trap fences.

There are no settlements in this township and also no mineral activity.

BOOK 4691

Form 4-680  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Gary P. Bowler	Chainman
Ralph J. Brown, Jr.	Flagman
David B. Hill	Axeman
Charles J. Kriz	Cornerman
Dennis L. Twitchell	Notekeeper

CERTIFICATE OF SURVEY

WE, Paul G. Bauer  
xx Leonard W. Murphy , HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 14 day of March , 1963 ,

We  
xx have dependently resurveyed the North Boundary, Fourth Standard  
Parallel North, the east and west boundaries and subdivisional lines  
of Township 16 North, Range 28 East,

of the Gila and Salt River Meridian, in the State of Arizona , which  
are represented in the foregoing field notes as having been executed by ~~me~~<sup>us</sup> and under ~~my~~<sup>our</sup> direction;  
and that said survey has been made in strict conformity with said special instructions, the Manual  
of Instructions for the Survey of the Public Lands of the United States, and in specific manner  
described in the foregoing field notes.

October 10, 1963  
(Date)

*Leonard W. Murphy*  
(Cadastral Surveyor)

October 10, 1963  
(Date)

*Paul G. Bauer*  
Surveying ~~(Cadastral Surveyor)~~ Technician

CERTIFICATE OF APPROVAL  
Bureau of Land Management

The foregoing field notes of the dependent resurvey of the north boundary, the  
Fourth Standard Parallel North, the east and west boundaries and the  
subdivisional lines of T. 16 N., R. 28 E., Gila and Salt River Meridian,  
Arizona

executed by Paul G. Bauer, Surveying Technician  
Leonard W. Murphy, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

Washington, D. C.  
MAR 24 1964  
(Date)

*E. L. Summitt*  
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)