

Form 4-679

(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

Portion, Sections 26 and 27

and

SURVEY

Portion of the Subdivisions

Sections 26 and 27

Township 7 North, Range 2 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Paul G. Bauer, Surveying Technician

Under special instructions dated February 20, 19 63, which provided for the surveys
included under Group Number 395, approved March 4, 1963,
and assignment instructions dated May 20, 19 63.

Survey commenced May 31, 19 63

Survey completed June 7, 19 63

BOOK 4694
INDEX DIAGRAM

Township 7 North, Range 2 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivisions of sections 26 and 27 Pages 5 through 16

CHAINS	
	<p>The boundaries of sections 26 and 27, T7N, R2E, G&SRM, Arizona, were surveyed in 1918 by H. L. Baldwin. Portions of the section lines were resurveyed and a portion of the subdivisions in both sections were surveyed in 1951 by White and Warner.</p> <p>The following field notes are those of a dependent resurvey of a portion of the boundaries of sections 26 and 27, and a survey of subdivisions in the north half of section 26 and in the east half of the northeast quarter of section 27.</p> <p>This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated February 20, 1963.</p> <p>Only the true line bearings and distances for the surveyed lines are given in these notes. The Bathey markers are "T" iron stakes, 24 inches long, with aluminum caps.</p> <p>The magnetic declination was found to be 14°30' East.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion, Section 26, T7N, R2E</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey executed in 1918 by H. L. Baldwin</p> <hr/> <p>Beginning at the true point for the $\frac{1}{4}$ cor. of secs. 25 and 26, originally established by H. L. Baldwin in 1918 and presently marked by a wooden hub in the center of a road under construction by the Maricopa County Road Commission, from which an original bearing tree, a palo verde, 12 ins. in diam., bears S. 8°45' W., 143 lks. dist., conforming to the record. This corner point is to be later monumented by the Maricopa County Road Commission with a 1-inch diam. reinforcing rod set in concrete in a recessed iron receptacle. This corner setting has been checked and verified as to precise location.</p> <p>N. 0°01'30" W., bet. secs. 25 and 26.</p> <p>Over rolling hills, along a bladed road, 27th Avenue.</p> <p>.380 Power line, bears E. and W.</p> <p>2.600 Wash, 45 lks. wide, 3 ft. deep, drains NW. from S. 65° E.</p> <p>5.700 Bladed road, bears easterly.</p> <p>19.975 Point for the N. 1/16 cor. of secs. 25 and 26 falls in bladed road bearing N. and S.</p> <p>Set a copperweld survey marker, a copper-coated iron rod 24 ins. long, 5/8 ins. diam., 6 ins. below the surface of the road, cap mkd.</p>

CHAINS

N $\frac{1}{16}$
S26 | S25
1963

from which

An iron post 30 ins. long, 2½ ins. diam., set 15 ins. in the ground, in a mound of stone to top, 3 ft. base, for a reference monument, bears N. 45° E., 0.645 chs. dist., with brass cap mkd. RM S25 42.57 ft. 1963, and an arrow pointing to the true corner.

An iron post 30 ins. long, 2½ ins. diam., set 15 ins. in the ground, in a mound of stone to top, 3 ft. base, for a reference monument, bears S. 45° E., 0.645 chs. dist., with brass cap mkd. RM S25 42.57 ft. 1963, and an arrow pointing to the true corner.

- 23.400 Buckskin trail, a bladed road bearing irregularly NE. from 27th Avenue.
- 26.300 Wash, 25 lks. wide, 2 ft. deep, drains W.
- 39.950 The cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., set in a mound of stone 2 ft. high, 3½ ft. base, with brass cap mkd.

T7N R2E
S23 | S24
S26 | S25
1918

Land, gently rolling.
Soil, gravelly.
Timber, scattered mesquite and palo verde.
Undergrowth, sagebrush, greasewood and cactus.

From the ¼ cor. of secs. 26 and 27, monumented by an iron post 1 inch diam., set in a mound of stone, 3 ft. base, with brass cap mkd.

¼
S27 | S26
L12 L7
1918

Remarked the cor. to show

Lot	Lot
46	53
¼	
S27 S26	
L12 L7	
1963	
1918	

N. 0°02' W., bet. secs. 26 and 27.

Over rolling hills.

CHAINS																		
4.996	Point for the S-S-N 1/256 cor. of secs. 26 and 27. Set a Bathey marker 20 ins. in the ground, cap mkd.																	
	$\begin{array}{r l} 45 & 52 \\ \hline 46 & 53 \end{array}$																	
9.992	Point for the S-N 1/64 cor. of secs. 26 and 27. Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, 3 ft. base, cap marked																	
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>Lot</td><td>Lot</td></tr> <tr><td>44</td><td>49</td></tr> <tr><td colspan="2" style="text-align: center;">S-N $\frac{1}{64}$</td></tr> <tr><td>Lot</td><td>Lot</td></tr> <tr><td>45</td><td>52</td></tr> <tr><td colspan="2" style="text-align: center;">1963</td></tr> </table>	Lot	Lot	44	49	S-N $\frac{1}{64}$		Lot	Lot	45	52	1963						
Lot	Lot																	
44	49																	
S-N $\frac{1}{64}$																		
Lot	Lot																	
45	52																	
1963																		
14.988	Point for the N-S-N 1/256 cor. of secs. 26 and 27. Set a Bathey marker 20 ins. in the ground, cap mkd.																	
	$\begin{array}{r l} 43 & 48 \\ \hline 44 & 49 \end{array}$																	
19.984	The N 1/16 cor. of secs. 26 and 27, monumented by an iron post, 2½ ins. diam., set in a mound of stone to top, 4 ft. base, brass cap mkd.																	
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">N $\frac{1}{16}$</td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td colspan="2" style="text-align: center;">1951</td></tr> </table>	N $\frac{1}{16}$		S27	S26	1951												
N $\frac{1}{16}$																		
S27	S26																	
1951																		
	Remarkd the cor. to show																	
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>Lot</td><td>Lot</td></tr> <tr><td>42</td><td>45</td></tr> <tr><td colspan="2" style="text-align: center;">N $\frac{1}{16}$</td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td colspan="2" style="text-align: center;">1963</td></tr> <tr><td>Lot</td><td>Lot</td></tr> <tr><td>43</td><td>48</td></tr> <tr><td colspan="2" style="text-align: center;">1951</td></tr> </table>	Lot	Lot	42	45	N $\frac{1}{16}$		S27	S26	1963		Lot	Lot	43	48	1951		
Lot	Lot																	
42	45																	
N $\frac{1}{16}$																		
S27	S26																	
1963																		
Lot	Lot																	
43	48																	
1951																		
	<hr style="width: 20%; margin: auto;"/> N. 0°03' E., beginning new measurement.																	
2.000	South edge of mesa, bears NE. and SW., thence over gently rolling mesa.																	
4.999	Point for the S-N-N 1/256 cor. of secs. 26 and 27. Set a Bathey marker 20 ins. in the ground, cap mkd.																	
	$\begin{array}{r l} 41 & 44 \\ \hline 42 & 45 \end{array}$																	
9.998	Point for the N-N 1/64 cor. of secs. 26 and 27. Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, 2½ ft. base, cap mkd.																	

4

CHAINS

Lot Lot
40 41

$N-N\frac{1}{64}$

S27|S26

Lot Lot
41 44

1963

14.997 Point for the N-N-N 1/256 cor. of secs. 26 and 27.
Set a Bathey marker 20 ins. in the ground, cap mkd.

$\frac{39|40}{40|41}$

19.996 The cor. of secs. 22, 23, 26 and 27, monumented by an iron post 2 ins. in diam., set in a mound of stone 2 ft. high, 4 ft. base, cap mkd.

T7N R2E

$\frac{S22|S23}{S27|S26}$

1918

Remarked the cor. to show

T7N R2E

$\frac{S22|S23}{S27|S26}$

1963

Lot 1918 Lot

39 40

Land, rolling hills.
Soil, rocky.
Timber, scattered palo verde.
Undergrowth, sagebrush, greasewood and cacti.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°52'30" W., bet. secs. 23 and 26.

Over rolling land.

.250 Center of 27th Avenue, a bladed road bearing N. and S.

3.600 Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W. for 1 chain, thence drains SE.

7.800 Track road, bears NE. and SW.

9.500 Track road, bears N. 30° E. and S. 30° W.

19.988 Point for the E. 1/16 cor. of secs. 23 and 26.

Set an iron post 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone to top, 2½ ft. base, cap mkd.

$E\frac{1}{16}\frac{S23}{S26}$

1963

CHAINS	
23.500	Dim track road, bears NE. and SW.
25.200	Wash, 40 lks. wide, 3 ft. deep, drains S. 15° W.
29.100	Dim bladed road, bears SE. and NW.
31.100	Wash, 10 lks. wide, 1 ft. deep, drains S. from NW.
39.976	The ¼ cor. of secs. 23 and 26, monumented by an iron post, 1 inch diam., projecting 18 ins. above ground, mound of stone to the N.
<hr/> <p>N. 89°55' W., beginning new measurement.</p> <p>Over rolling land.</p>	
2.515	Power line, bears N. 20°38' E. and S. 20°38' W.
2.700	Track road, bears SE. and NW.
3.700	Wash, 15 lks. wide, 2 ft. deep, drains SE.
4.700	Bladed road bears S. 15° E. and N. 15° W.; thence asc. moderate E. slope.
13.300	East edge of mesa, bears N. and S.
19.968	Point for the W 1/16 cor. of secs. 23 and 26. Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, 2½ ft. base, cap mkd.
$W \frac{1}{16} \frac{S23}{S26}$ <p>Lot 39 1963</p>	
29.952	Point for the W-W 1/64 cor. of secs. 23 and 26. Set an iron post 30 ins. long, 2½ ins. diam., 15 ins. in the ground, mound of stone to top, 2 ft. base, cap mkd.
$W-W \frac{1}{64} \frac{S23}{S26}$ <p>Lot 40 Lot 39 1963</p>	
39.936	The cor. of secs. 22, 23, 26 and 27. Land, rolling E. portion, gently rolling mesa W. portion. Soil, gravelly. Timber, scattered mesquite and palo verde. Undergrowth, sagebrush, greasewood and cacti.
<hr/> <p>Resurvey of a Portion of the Subdivision Executed in 1951 by White and Warner</p> <hr/>	
<p>From the ¼ cor. of secs. 25 and 26. N. 89°55'30" W., on the E. and W. centerline of sec. 26.</p>	

6

CHAINS	
	Over a county road in the process of construction and paving.
15.000	Bladed dirt road, bears NE.
19.985	Point for the C-E 1/16 cor. of sec. 26 cannot be monumented because of road construction.
	from which
	A railroad spike driven flush in a power pole, 18 ins. above ground level, for a reference marker, bears N. 65° W., 0.905 chs. dist., head of spike mkd. RM 59.7 ft.
	An iron post 30 ins. long, 2½ ins. diam., set 26 ins. in the ground for a reference monument, bears N. 0°02' W., 1.053 chs. dist., with brass cap mkd. RM S26 69.5 ft. 1963 and an arrow pointing to the true cor.
20.400	Wash, 40 lks. wide, 3 ft. deep, drains SW.
24.981	Point for the C-E-W-E 1/256 cor. cannot be monumented because of road construction.
	from which
	A railroad spike driven flush in a power pole, 18 ins. above ground level, for a reference marker, bears NW., 0.577 chs. dist., head of spike mkd. RM 38.1 ft.
	An iron post 30 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 0°03' W., 1.000 chs. dist., with brass cap mkd. RM S26 66.0 ft. 1963, and an arrow pointing to the true cor.
29.500	New county road begins curve to the SW.
29.977	Point for the C-W-E 1/64 cor. of sec. 26; cannot be monumented because of road construction.
	from which
	A railroad spike driven flush in a power pole, 18 ins. above ground level for a reference marker, bears N. 9°10' W., 0.422 chs. dist., head of spike mkd. RM 27.9 ft.
	An iron post 30 ins. long, 2½ ins. diam., set 12 ins. in the ground, in a mound of stone to top, 2½ ft. base, bears NE. 0.857 chs. dist., cap mkd. RM S26 56.6 ft. 1963, and an arrow pointing to the true cor.
	A temp for B.M. No. 14 bears S. 2°31' E., 0.979 chs. distant.
32.500	Leave road construction area.
33.400	Wash, 70 lks. wide, 5 ft. deep, drains S. 20° W.
34.800	Power line, bears N. 80° E. and S. 80° W.

CHAINS	
39.970	<p>The C$\frac{1}{4}$ cor. of sec. 26, monumented by an iron post 2$\frac{1}{2}$ ins. in diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C $\frac{1}{4}$ S26 L1 1951</p> </div> <p>The cor. is set on the S. edge of a bladed road bearing E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., beginning new measurement.</p> <p>Over rolling land, along the S. edge of an E-W bladed road.</p>
9.993	<p>Point for the C-E-W $\frac{1}{64}$ cor. of sec. 26, falls in an intersection of bladed roads bearing E-W and N.</p> <p>Set an iron post 30 ins. long, 2$\frac{1}{2}$ ins. diam., 6 ins. below the surface of the road, cap mkd.</p> <div style="text-align: center;"> <p>E-W $\frac{1}{64}$ C ——— C S26 1963</p> </div> <p>from which</p> <p>A railroad spike driven flush in a power pole, 18 ins. above ground level for a reference marker, bears S. 84°35' W., 0.53 chs. dist., head of spike mkd. RM 35 ft.</p> <p>A railroad spike driven flush in a power pole, 18 ins. above ground level for a reference marker, bears N. 22°45' W., 1.245 chs. dist., head of spike mkd. RM 82.2 ft.</p>
13.600	<p>Wash, 15 lks. wide, 1 ft. deep, drains S. for 2 chs., thence drains SE.</p>
15.086	<p>Fall 15 lks. N. of a cor. of fences bearing S. and W.</p>
17.100	<p>Fall 20 lks. S. of junction of bladed roads bearing E., S. 10° E., W. and N. 10° W.</p>
18.540	<p>Power line, bears N. 22°30' E., and S. 22°30' W.</p>
19.986	<p>The C-W $\frac{1}{16}$ cor. of sec. 26, monumented by an iron post, 2$\frac{1}{2}$ ins. diam., projecting 6 ins. above ground level, in a mound of stone to top, 2$\frac{1}{2}$ ft. base, brass cap mkd.</p> <div style="text-align: center;"> <p>C-W $\frac{1}{16}$ S25 L5 L4 1951</p> </div>

8

CHAINS

Remarked the cor. to show

C-W
 $\frac{1}{16}$
 Lot 16
 54 S25⁶
 L5|L4
 1963

from which

A cor. of fences bearing E. and S. bears S. 20°
 E., 16 lks. dist.

N. 89°55' W., beginning new distance.

- .150 Bladed road, bears N. and S.
- .332 Fall .024 chs. N. of cor. of fences bearing S. and W.
- 3.807 Fall .022 chs. N. of cor. of fences bearing E., S.
and W.
- 9.998 The C-W-W 1/64 cor. of sec. 26, monumented by a
2x2-inch fir post, conforming to the record.

Remonumented the cor. with an iron post 30 ins. long,
 2½ ins. diam., set 24 ins. in the ground, in a collar
 of stone 1½ ft. base, cap mkd.

Lot Lot
 53 54
 C-W-W $\frac{1}{64}$
 +
 S26
 1963

from which

A cor. of fences, bearing E., S. and W., bears
 S. 23°30' W., .027 chs. dist.

N. 89°55' W., beginning new distance.

- 1.720 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 7.900 Fall .020 chs. N. of cor. of fences bearing E. S. and W.
- 9.998 The ¼ cor. of secs. 26 and 27.

From the C¼ cor. of sec. 26.

N. 0°03' W., on the N. and S. center line of sec. 26.

Over rolling hills, through moderate brush and cacti.

- .150 Bladed road bears E. and W.; thence along west edge
of track road.
- 7.500 Power line, bears E. and W. 4 chs. to well.
- 9.995 Point for the C-S-N 1/64 cor. of sec. 26.

CHAINS	
	<p>Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, small mound of stone to W., 1 ft. high, 1 ft. base, cap of post mkd.</p>
	$\begin{array}{c} C \\ S-N\frac{1}{64} \left \begin{array}{l} S26 \\ C \\ 1963 \end{array} \right. \end{array}$
10.100	Junction of track roads, bearing E., S. and N.
14.992	Point for the C-N-S-N 1/256 cor. of sec. 26.
	Set a Bathey marker 20 ins. in the ground, cap mkd.
	$\overline{57} \left \right.$
19.990	Point for the C-N 1/16 cor. of sec. 26.
	Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, 2½ ft. base, cap mkd.
	$\begin{array}{c} C \\ N\frac{1}{16} \left \begin{array}{l} S26 \\ C \\ 1963 \end{array} \right. \end{array}$
25.400	Wash, 8 lks. wide, 1 ft. deep, drains SE.
30.000	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° E. from N. 20° E.
31.000	Roughly bladed road, bears SE. and NW.
35.50	Wash, 15 lks. wide, 1 ft. deep, drains SE. for 1.50 chs., thence S. 20° W.
38.050	Track road, bears S. 60° E. and N. 60° W.
39.980	Intersect the ¼ cor. of secs. 23 and 26.
<p>Survey of a Portion of the Subdivisions Section 26, T7N, R2E, Arizona</p>	
	From the true point for the C-E 1/16 cor. of sec. 26.
	N. 0°02'15" W., on the N. and S. center line of the NE¼ of sec. 26.
	Over rolling hills, through moderate brush.
.380	Wash, 40 lks. wide, 3 ft. deep, drains SW.
.380	Power line, bears E. and W.
1.053	Intersect a RM for the C-E 1/16 cor. of sec. 26, hereinbefore described.
1.720	Power line to a church, bears NE. and SW.
3.350	Bladed road to a church, bears NE. and S. 60° W.
9.991	Point for the C-S-NE 1/64 cor. of sec. 26.
	Set an iron post 30 ins. long, 2½ ins. diam., 26 ins. in the ground, mound of stone to top, 1½ ft. base, cap mkd.

CHAINS

C-S-NE $\frac{1}{64}$
+
S26
Lot
61
1963

14.600 Dim track road, bears irregularly SE. and NW.

19.982 Point for the NE 1/16 cor. of sec. 26.

Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

NE $\frac{1}{16}$
+
S26
1963

39.965 Intersect the E 1/16 cor. of secs. 23 and 26.

From the N 1/16 cor. of secs. 25 and 26.

N. 89°54' W., on the E. and W. center line of the NE¼ of sec. 26.

Over rolling hills, through moderate brush, cacti and palo verde.

19.987 Intersect the NE 1/16 cor. of sec. 26.

21.800 Bladed road, bears NE. and SW.

23.700 Wash, 10 lks. wide, 1 ft. deep, drains SW.

24.984 Point for the C-E-W-NE 1/256 cor. of sec. 26.

Set a Bathey marker, 20 ins. in the ground, cap mkd.

59

25.050 Wash, 5 lks. wide, 1 ft. deep, drains SE. for 150 chs., thence SW.

29.981 Point for the C-W-NE 1/64 of sec. 26.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, mound of stone to top, 2 ft. base, cap mkd.

C-W-NE $\frac{1}{64}$
+
S26 Lot
1963 59

30.70 E. bank of wash, 3 ft. deep, drains S. 10° E., from N.

32.000 W. bank of same wash, bears S. 10° E. and NW.

38.800 Bladed road, bears irregularly NE. and SW.

39.973 Intersect the C-N 1/16 cor. of sec. 26.

CHAINS															
	From the C-W 1/16 cor. of sec. 26.														
	N. 0°02' W., on the N. and S. center line of the NW¼ of sec. 26.														
	Over rolling land.														
.200	Junction of bladed roads, SW. and N.														
4.996	Point for the C-S-S-NW 1/256 cor. of sec. 26.														
	Set a Bathey marker 20 ins. in the ground, in a small collar of stone, cap mkd.														
	$\begin{array}{r l} 51 & 58 \\ \hline 54 & \end{array}$														
9.993	Point for the C-S-NW 1/64 cor. of sec. 26.														
	Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>Lot</td> <td>Lot</td> </tr> <tr> <td>50</td> <td>56</td> </tr> <tr> <td>C-S-NW</td> <td>$\frac{1}{64}$</td> </tr> <tr> <td style="text-align: center;">+</td> <td></td> </tr> <tr> <td>Lot</td> <td>Lot</td> </tr> <tr> <td>51</td> <td>58</td> </tr> <tr> <td colspan="2" style="text-align: center;">1963</td> </tr> </table>	Lot	Lot	50	56	C-S-NW	$\frac{1}{64}$	+		Lot	Lot	51	58	1963	
Lot	Lot														
50	56														
C-S-NW	$\frac{1}{64}$														
+															
Lot	Lot														
51	58														
1963															
11.700	Bladed road, bears N. 20° E. and S.														
14.990	Point for the C-N-S-NW 1/256 cor. of sec. 26.														
	Set a Bathey marker 20 ins. in the ground, cap mkd.														
	$\begin{array}{r l} 47 & 55 \\ \hline 50 & 56 \end{array}$														
15.400	Dim track road, bears E. and W. 1 chain, thence NW.														
18.700	Wash, 10 lks. wide, 1 ft. deep, drains SE.; thence over moderate S. slope.														
19.987	Point for the NW 1/16 cor. of sec. 26.														
	Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>Lot</td> <td></td> </tr> <tr> <td>46</td> <td></td> </tr> <tr> <td>NW</td> <td>$\frac{1}{16}$</td> </tr> <tr> <td style="text-align: center;">+</td> <td></td> </tr> <tr> <td>Lot</td> <td>Lot</td> </tr> <tr> <td>47</td> <td>55</td> </tr> <tr> <td colspan="2" style="text-align: center;">1963</td> </tr> </table>	Lot		46		NW	$\frac{1}{16}$	+		Lot	Lot	47	55	1963	
Lot															
46															
NW	$\frac{1}{16}$														
+															
Lot	Lot														
47	55														
1963															
24.985	Point for the C-S-N-NW 1/256 cor. of sec. 26.														
	Set a Bathey marker, 20 ins. in the ground, cap mkd.														
	$\begin{array}{r l} 43 & \\ \hline 46 & \end{array}$														

CHAINS

- 29.000 S. edge of mesa, bears E. and W.
- 29.983 Point for the C-N-NW 1/64 cor. of sec. 26.
 Set an iron post 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone to top, 2 ft. base, cap mkd.

Lot
 42
 C-N-NW $\frac{1}{64}$
 +
 Lot S26
 43
 1963

from which

A malpai stone, 16x24x30 ins., marked with Indian picture writings, bears S. 8°30' E., 1.76 chs. dist.

A granite stone 24x30 ins. x 4½ ft., marked with Indian picture writings, bears S. 15°30' E., 1.88 chs. dist.
- 34.981 Point for the C-N-N-NW 1/256 cor. of sec. 26.
 Set a Bathey marker 20 ins. in the ground, cap mkd.

$\frac{39}{42}$
- 39.980 Intersect the W 1/16 cor. of secs. 23 and 26.

From the C-N 1/16 cor. of sec. 26.

N. 89°55' W., on the E. and W. center line of the NW¼ of sec. 26.

Over rolling hills, through moderate brush and cacti.
- 9.988 Point for the C-E-NW 1/64 cor. of sec. 26.
 Set an iron post 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, 2½ ft. base, cap mkd.

C-E-NW $\frac{1}{64}$
 +
 Lot S26
 55
 1963
- 10.260 Power line, bears N. 22°30' E. and S. 22°30' W.
- 15.100 Wash, 5 lks. wide, 1 ft. deep, drains S. 20° W.
- 15.700 Bladed road, bears NE. and SW.
- 16.700 Rough bladed road, bears S. 60° E. and N. 60° W.
- 19.977 Intersect the NW 1/16 cor. of sec. 26.

CHAINS

21.300 Wash, 15 lks. wide, 1 ft. deep, drains SE.

24.700 Dim track road, bears SE. and NW.

29.975 Point for the C-W-NW 1/64 cor. of sec. 26.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, cap mkd.

Lot Lot
45 46

C-W-NW $\frac{1}{64}$
+

Lot S26 Lot
48 1963 47

39.973 Intersect the N 1/16 cor. of secs. 26 and 27.

Dependent Resurvey, Portion of North Boundary
Section 27, T7N, R2E

From the cor. of sections 22, 23, 26 and 27.

West, bet. secs. 22 and 27.

Desc. over steep W. slope.

6.500 Begin desc. over gentle W. slope.

10.000 Point for E-E 1/64 cor. of secs. 22 and 27.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, 1½ ft. base, cap mkd.

E-E $\frac{1}{64}$ $\frac{S22}{S27}$

Lot
1963³⁹

11.800 E. edge of New River basin, bears N. and S.; thence over sandy bottom land.

20.000 The E 1/16 cor. of secs. 22 and 27, monumented by an iron post 2½ ins. diam., projecting 15 ins. above ground, brass cap mkd.

E $\frac{1}{16}$ $\frac{S22}{S27}$
1951

Build a mound of stone to top, 4 ft. base.

Dependent Resurvey
Subdivision of a Portion of Section 27, T7N, R2E

Reestablishment of the Survey
Executed in 1951 by White and Warner

CHAINS

From the $\frac{1}{4}$ cor. of secs. 26 and 27.
 N. $89^{\circ}59'$ W., on the E. and W. center line of sec. 27.
 Over rolling hills, asc. SE. slope.


4.998 The C-E-E-E $\frac{1}{256}$ cor. of sec. 27, monumented by a 2x2-inch fir post, conforming to the record and set in a saddle of a ridge bearing N. 30° E. and S. 30° W.

N. $89^{\circ}59'$ W., beginning new measurement.

Desc. steep NW. slope.

4.998 The C-E-E $\frac{1}{64}$ cor. of sec. 27, monumented by a 2x2-inch fir post, conforming to the record.

Remonumented the cor. with an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.



N. $89^{\circ}59'$ W., beginning new measurement.

.600 Base of slope; thence over nearly level sandy bottom land.

6.050 E. bank of New River, 6 ft. high, bears N. and S.

9.150 W. bank of New River, 4 ft. high, bears N. and S.

9.400 Old fence line, originally 4-strand barbed wire, bears N. 20° E. and S. 20° W.

10.026 The C-E $\frac{1}{16}$ cor. of sec. 27, monumented by an iron post as described in the official record.


From the C-E $\frac{1}{16}$ cor. of sec. 27.

N. $0^{\circ}02'$ E., on the N. and S. center line of the $NE\frac{1}{4}$ of sec. 27.

3.500 Remains of old fence line, bears SE. and NW.

9.991 Point for the C-S-NE $\frac{1}{64}$ cor. of sec. 27. Find no evidence of the original corner post.

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with glass at base of post, cap mkd.



16.100 Thence over rocky wash bottom.

CHAINS	
19.600	W. bank of New River wash area, 6 ft. high, bears N. 30° E. and S. 30° W.
19.983	The NE 1/16 cor. of sec. 27, monumented by an iron post, 2½ ins. diam., projecting 8 ins. above the ground, cap mkd.
	NE 1/16 S27 1951
	<hr/> From the NE 1/16 cor. of sec. 27. N. 0°02' E., beginning new distance.
9.996	Point for the C-N-NE 1/64 cor. of sec. 27. Set an iron post 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with glass at base of post, cap mkd.
	C-N-NE $\frac{1}{64}$ + S27 1963
18.100	Right bank of New River, 4 ft. high, bears SE. and NW.
19.200	Left bank of New River, 3 ft. high, bears SE. and NW.
19.992	The E 1/16 cor. of secs. 22 and 27.
	<hr/> From the N 1/16 cor. of secs. 26 and 27. N. 89°59'30" W., on the E. and W. center line of the NE¼ of sec. 27. Over nearly level land on mesa.
7.000	Begin desc. over steep W. slope.
9.997	Point for the C-E-NE 1/64 cor. of sec. 27. Set an iron post 30 ins. long, 2½ ins. diam., 15 ins. in the ground, mound of stone to top, cap mkd.
	Lot 42 C-E-NE $\frac{1}{64}$ + S27 Lot 43 1963
	The cor. point falls at the base of a 10-foot rocky ledge.
12.700	Thence over level bottom land.
15.000	Left bank of New River, 4 ft. high, bears N. 10° E. and S. 10° W.

16

CHAINS	
19.700	Right bank of New River, 6 ft. high, bears N. 30° E. and S. 30° W.
19.995	The NE 1/16 cor. of sec. 27.
<hr/> <p>The remaining subdivisions as shown on the plat of this survey were surveyed and the corner monuments set. The plat gives the true bearings and distances and the legend indicates the kind of marker set at the corners.</p> <hr/>	
<p>General Description</p> <hr/>	
<p>The area in this survey is a flat-topped mesa approximately 100 feet higher than the area to the west, which consists of river bottom land. The soil varies from sandy to rocky, with drainage to the south. There is a medium growth of cholla and saguaro cacti on the mesa and palo verde and mesquite on the bottom land.</p>	

2

CERTIFICATE OF SURVEY

I, Paul G. Bauer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20 day of February, 1963, I have dependently resurveyed a portion of Sections 26 and 27 and surveyed a portion of the subdivisions of Sections 26 and 27, T7N, R2E of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 11, 1963
 (Date)

Paul G. Bauer
 Surveying (Cadastral Surveyor) Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL
 Bureau of Land Management

The foregoing field notes of the dependent resurvey of a portion of Sections 26 and 27 and survey of a portion of the subdivisions of Sections 26 and 27, T7N, R2E, of the Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer, Surveying Technician,

having been critically examined and found correct, are hereby approved.
 Washington, D.C.

APR 23 1964
 (Date)

E. J. Pennington
 (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)