

BOOK 4705

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

Portion of the West Boundary

Township 4 South, Range 25 East

DEPENDENT RESURVEY

South Boundary, Portion of West Boundary

Portion of Subdivisional Lines

and

COMPLETION SURVEY

East Boundary and Subdivisional Lines

Township 4 South, Range 24 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Paul G. Bauer, Cadastral Surveyor

Under special instructions dated August 12, 1959, which provided for the surveys included under Group Number 340, approved September 14, 1959, and assignment instructions dated February 11, 1963.

Survey commenced February 18, 1963

Survey completed April 3, 1963

1A

BOOK 4705 INDEX DIAGRAM

Township 4 South, Range 24 East,

	($\frac{1}{4}$)58	($\frac{1}{4}$)58	($\frac{1}{4}$)45	($\frac{1}{4}$)38			
12	($\frac{1}{4}$)57 ⁶ 57 55	5 45 54	4 37 44	16 37($\frac{1}{4}$) 36	2 14 15	($\frac{1}{4}$)21 ¹ 21	9
					($\frac{1}{4}$)29	($\frac{1}{4}$)23	
	($\frac{1}{4}$)56 ⁷ 54 53	8 43 52	9 35 42	10 28 35	11 22 28	12 20	8
	18 52 51	17 42 50	16 34 41	15 27 33	14 19 26	13 19	7
	19 49 49	20 40 48	21 33 39	22 25 32	23 18 25	24 18	6
11	($\frac{1}{4}$)49 ⁸ 47 46	29 39	28 31 38	27 24 29	26 17 23	25 13	5
10	($\frac{1}{4}$)47 ¹ 46	32	33 30 ($\frac{1}{4}$)31	34 24 ($\frac{1}{4}$)31	35 14	36	
	4	3	3	2	2	1	

CHAINS

The north boundary was surveyed in 1955 by D. E. Harding, and dependently resurveyed in 1962 by Boyd S. Owens and Paul G. Bauer. The west boundary of Township 4 South, Range 25 East, which is the east boundary of Township 4 South, Range 24 East, was surveyed in 1921 by Thorn and Kinsey. The south boundary was originally surveyed in 1875 by T. F. White and dependently resurveyed in 1955 by F. R. Chappell. The west boundary was surveyed in 1875 by T. F. White and partly resurveyed in 1958 by H. G. Parker. Sections 2, 32 and 36 were surveyed in 1955 by D. E. Harding and F. R. Chappell.

The following field notes are those of a dependent resurvey of the west boundary of Township 4 South, Range 25 East and the establishment of the east boundary of Township 4 South, Range 24 East; the dependent resurvey of the south boundary of the township, a dependent resurvey of a portion of the west boundary of the township; a dependent resurvey of sections 2 and 36 and a completion survey of the subdivisional lines.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions, 1947, and the Special Instructions dated August 12, 1959.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top. Original corner monuments were desposited alongside the new monuments, unless described otherwise.

The geographic position of the southeast corner of the township is: Latitude, 33°02'05" North and Longitude 109°49'31" West.

The magnetic declination was found to be 14½° East.

Dependent Resurvey of the North Boundary
Township 5 South, Range 24 East

Reestablishment
Survey in 1875 by T. F. White
Resurvey in 1955 by F. R. Chappell

Beginning at the corner of secs. 1 and 36, Ts. 4 and 5 S., R. 24 E., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record.

N. 89°39' W., bet. secs. 1 and 36.

Over rolling land, through creosote brush and cactus.

Desc. gentle W. slope.

12.80 Wash, 60 lks. wide, 2 ft. deep, drains S. 20° W.

39.90 The ¼ sec. cor. of secs. 1 and 36, monumented by an iron post as described in the official record.

BOOK 4705

2

Dependent Resurvey, N. Bdy., T5S, R24E, Arizona

2.

CHAINS

N. 89°44' W., beginning new measurement.

16.40 Wash, 60 lks. wide, 3 ft. deep, drains SW.

32.70 Old road, bears NE. and SW.

40.02 The cor. of secs. 1, 2, 35 and 36, monumented by an iron post as described in the official record.

Land, rolling.

Soil, rocky.

Timber, none.

Undergrowth, creosote brush and cactus.

S. 89°47' W., bet. secs. 2 and 35.

Over rolling land, through medium creosote brush.

.70 Wash, 20 lks. wide, 6 ft. deep, drains SW.

1.70 Wash, 50 lks. wide, 6 ft. deep, drains SW.

30.70 Wash, 20 lks. wide, 2 ft. deep, drains SW.

39.88 The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented by an iron post as described in the official record.

N. 88°46' W., beginning new measurement.

15.65 Wash, 1 chain wide, 2 ft. deep, drains SW.

26.80 Wash, 20 lks. wide, 1 ft. deep, drains SW.

37.00 Wash, 10 lks. wide, 1 ft. deep, drains S.

40.23 The cor. of secs. 2, 3, 34 and 35, monumented by an iron post as described in the official record.

Land, rolling.

Soil, rocky.

Timber, none.

Undergrowth, creosote brush and scattered ocotillo.

S. 89°27' W., bet. secs. 3 and 34.

Over rolling land.

12.90 Wash, 140 lks. wide, 1 ft. deep, drains S. 30° W.

28.00 Wash, 100 lks. wide, with 10 ft. banks, drains S. 30° W.

40.16 Point for the $\frac{1}{4}$ sec. cor. of sec. 3, at proportionate distance; there is no remaining evidence of the original corner.

Set the iron post 10 ins. in the ground, mound with stone to top, 3 $\frac{1}{2}$ ft. base, cap mkd.

T4S

$\frac{1}{4}$ S 3

T5SR24E

1963

BOOK 4705

Dependent Resurvey, N. Bdy., T5S, R24E, Arizona

3.

CHAINS	
	S. 89°26' W., beginning new measurement.
0.30	No trace of the original $\frac{1}{4}$ sec. cor. of sec. 34.
20.60	Small spur, slopes S. 30° W.
31.70	Wash, 25 lks. wide, 4 ft. deep, drains S. 20° W.
39.99	Point for the cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.
	Set the iron post 6 ins. in the ground, mound with stone to top, 3 $\frac{1}{2}$ ft. base, cap mkd.
	<hr style="width: 50px; margin: auto;"/> S4 S3 T5SR24E 1963
	Land, rolling. Soil, sandy clay. Timber, none; undergrowth, creosote brush and scattered cacti.
	<hr/>
	S. 89°15' W., on the north bdy. of sec. 4.
	Over rolling land.
0.77	No trace of the original cor. of secs. 33 and 34.
36.20	Spur, slopes S. 10° W.
40.22	The $\frac{1}{4}$ sec. cor. of sec. 4, monumented by an iron post as described in the official record.
	<hr/>
	N. 89°59' W., beginning new measurement.
1.01	No trace of the original $\frac{1}{4}$ sec. cor. of sec. 33.
4.70	Small spur, slopes S. for 2 chs., then SW.
15.80	Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.
24.70	E. bank of wash, drains S.
28.70	W. bank of wash.
39.04	The cor. of secs. 4 and 5, monumented by an iron post as described in the official record.
	Land, rolling. Soil, rocky and sandy loam. Timber, none; undergrowth, creosote brush and cactus.
	<hr/>
	West on the N. bdy. of sec. 5.
	Over rolling hills, through creosote brush.
0.85	The cor. of secs. 32 and 33, monumented by an iron post as described in the official record.
3.45	Wash, 70 lks. wide, 6 ft. banks, drains SW.

CHAINS	
21.80	Bladed road, bears N. and S.
24.10	Track road, bears NE. and SW.
30.30	Wash, 15 lks. wide, 1 ft. deep, drains S. 30° W.
39.92	The $\frac{1}{4}$ sec. cor. of sec. 5, monumented by a stone as described in the official record of the survey of 1875 by T. F. White. There is no evidence of the iron post as described in the official resurvey of 1955 by Harding and Chappell.
	At the cor. point
	Set the iron post 6 ins. in the ground, mound with stone to top, $3\frac{1}{2}$ ft. base, cap mkd.
	<hr style="width: 10%; margin: auto;"/> $\frac{1}{4}$ S 5 T5SR24E 1963
	West, beginning new measurement.
0.93	The $\frac{1}{4}$ sec. cor. of sec. 34, monumented by an iron post as described in the official record.
14.10	Wash, 30 lks. wide, 2 ft. deep, drains S. 30° W.
18.30	Spur, slopes SW.
39.82	The cor. of secs. 5 and 6, monumented by an iron post as described in the official record.
	Land, rolling. Soil, rocky with some clay. Timber, none; undergrowth, scattered mesquite, creosote brush and cactus.
	N. 89°22' W., on the N. bdy. of sec. 6.
	Over rolling land and washes.
1.10	The cor. of secs. 31 and 32, monumented by an iron post as described in the official record.
11.00	Wash, 200 lks. wide, 3 ft. deep, drains SW.
38.50	The $\frac{1}{4}$ sec. cor. of sec. 6, monumented by an iron post as described in the official record.
	N. 89°55' W., beginning new measurement.
2.16	The $\frac{1}{4}$ sec. cor. of sec. 31, monumented by an iron post as described in the official record.
22.30	Wash, 200 lks. wide, 2 ft. left bank, 15 ft. right bank, drains SW.
40.99	The cor. of secs. 1, 6, 31 and 36, Ts4&5S, Rs23&24E, monumented by an iron post as described in the official record.

CHAINS	
	<p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, mesquite, creosote brush and cactus.</p> <hr/> <p>Dependent Resurvey, Portion, West Boundary Township 4 South, Range 25 East, Arizona</p> <hr/> <p>Reestablishment of the Survey in 1921 by Thorn and Kinsey</p> <p>Establishment of the East Boundary of T4S, R24E, by placing the one-quarter corners and the section corners at 40.00 and 80.00 chains in latitude from the north-east corner of section 36.</p> <hr/> <p>From the corner of secs. 30 and 31, T4S, R25E. N. 0°02' W., along the W. bdy. of sec. 30. Over high rolling land, covered with lava rock, creosote brush and cactus.</p>
2.22	The cor. of secs. 25 and 36, T4S, R24E, monumented by an iron post conforming to the record.
6.70	Spur, slopes W.
13.40	Ridge, bears E. and W.
20.80	Wash, 15 lks. wide, 3 ft. deep, drains W.
29.30	Spur, slopes W.
36.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 75° W.
39.92	The $\frac{1}{4}$ sec. cor. of sec. 30, T4S, R25E, monumented by an iron post conforming to the record.

6

CHAINS

N. 0°02' W., beginning new measurement.

2.30

Point for the $\frac{1}{4}$ sec. cor. of sec. 25, T4S, R24E; falls on the S. bank of a wash 25 lks. wide, 4 ft. deep, draining SW.

Set the iron post 6 ins. in the ground, in a mound of stone to top, $4\frac{1}{2}$ ft. base, cap mkd.

T4S
R24E $\frac{1}{4}$ R25E
S25 |
1963

2.60

Wash, 25 lks. wide, 4 ft. deep, drains SW.; asc. steep S. slope.

34.80

Top of 75 ft. ledge, bears S. 75° E. and N. 75° W.; asc. over top of high hill.

39.56

The cor. of secs. 19 and 30, T4S, R25E, monumented by an iron post conforming to the record.

Land, rolling and mountainous.
Soil, rocky.
Timber, none.
Undergrowth, scattered creosote brush and cactus.

N. 0°08' W., along the W. bdy. of sec. 19.

Over steep N. slope, through scattered cedar, pinon, palo verde and yucca.

2.74

Point for the cor. of secs. 24 and 25.

Set the iron post 6 ins. in the ground, in a mound of stone to top, $4\frac{1}{2}$ ft. base, cap mkd.

T4S
S24 |
S25 |
R24E |
1963

CHAINS											
	<p>from which</p> <p style="text-align: center;">Triangulation Station SEEP bears N. 76°25'30" W., 27.64 chs. dist.</p>										
20.95	Wash, 15 lks. wide, 1 ft. deep, drains NE.										
36.80	Small spur, slopes N. 70° E.										
40.05	The ¼ sec. cor. of sec. 19, monumented by an iron post conforming to the record.										

	N. 0°05' W., beginning new measurement.										
0.05	Wash, 10 lks. wide, 1 ft. deep, drains E.										
2.69	Point for the ¼ sec. cor. of sec. 24, T4S, R24E; falls on the E. slope of a small knoll.										
	Set the iron post 2 ins. in the ground, in a mound of stone to top, 3½ ft. base, cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T4S</td><td> </td></tr> <tr><td>R24E</td><td> </td></tr> <tr><td> ½</td><td> </td></tr> <tr><td>S24</td><td> </td></tr> <tr><td>1963</td><td></td></tr> </table>	T4S		R24E		½		S24		1963	
T4S											
R24E											
½											
S24											
1963											
10.80	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E., asc. S. slope.										
23.90	Ridge, bears N. 75° E. and S. 75° W., desc. N. slope.										
37.30	Begin desc. over steep N. slope, through cedar and pinon.										
39.93	The cor. of secs. 18 and 19, monumented by an iron post conforming to the record.										
	Land, rolling and broken. Soil, rocky. Timber, scattered cedar and pinon. Undergrowth, creosote brush.										

	N. 0°06' W., along the W. bdy. of sec. 18, T4S, R25E.										
	Desc. over steep N. slope.										
2.76	Point for the cor. of secs. 13 and 24, T4S, R24E.										
	Set the iron post 6 ins. in the ground in a mound of stone to top, 3½ ft. base, cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T4S</td><td> </td></tr> <tr><td>S13</td><td> </td></tr> <tr><td>S24</td><td> </td></tr> <tr><td>R24E</td><td> </td></tr> <tr><td>1963</td><td></td></tr> </table>	T4S		S13		S24		R24E		1963	
T4S											
S13											
S24											
R24E											
1963											
4.90	Wash, 30 lks. wide, 3 ft. deep, drains N. 45° W.; asc. steep S. slope.										
13.60	High knoll, desc. steep N. slope.										

CHAINS	
28.50	Wash, 50 lks. wide, 5 ft. deep, drains E. with a small flow of water; asc. SE. slope.
39.91	The $\frac{1}{4}$ sec. cor. of sec. 18, T4S, R25E, monumented by an iron post conforming to the record.
	<hr/> N. 0°02' W., beginning new measurement; asc. SE. slope.
2.85	Point for the $\frac{1}{4}$ sec. cor. of sec. 13, T4S, R24E. Set the iron post over a + chiseled on solid rock, mound of stone to top, 6 ft. base, cap mkd.
	<pre style="text-align: center;"> T4S 1/4 S13 R24E 1963 </pre>
8.10	Spur, slopes E. for 4 chs., then projects SE.
22.20	Small ridge, bears E. and NW.; desc. N. slope.
35.60	Wash, 110 lks. wide, with walls 75 ft. high, drains S. 80° E.; asc. steep S. slope.
39.97	The cor. of secs. 7 and 18, T4S, R25E, monumented by an iron post conforming to the record.
	Land, rolling and broken. Soil, rocky. Timber, scattered cedar and pinon. Undergrowth, creosote brush.
	<hr/> N. 0°01' W., along the W. bdy. of sec. 7.
	Over rocky SW. slope.
2.88	Point for the cor. of secs. 12 and 13, T4S, R24E.
	Set the iron post over a + chiseled on solid rock, mound of stone to top, 4½ ft. base, cap mkd.
	<pre style="text-align: center;"> T4S S12 S13 R24E 1963 </pre>
14.40	Ridge, bears E. and N. 60° W.; desc. N. slope through trees.
23.70	Wash, 50 lks. wide, 1½ ft. deep, drains N. 75° E.; asc. N. slope.
29.40	Spur, slopes SE.; desc. NE. slope.
40.00	The $\frac{1}{4}$ sec. cor. of sec. 7, monumented by an iron post conforming to the record.
	<hr/> N. 0°04' W., beginning new measurement.
	Desc. over NE. slope.

CHAINS		
.70	Spur, slopes S. 50° E.; desc. steep NE. slope.	
2.88	Point for the ¼ sec. cor. of sec. 12, T4S, R24E.	
	Set the iron post over a + on solid rock, mound of stone to top, 3½ ft. base, cap mkd.	
	<p>T4S ¼ S12 R24E 1963</p>	
3.40	Fence, barbed wire, bears E. and W.	
17.30	Ravine, 20 lks. wide, 6 ft. deep, drains E.	
32.90	Left fork of Markham Creek, 150 lks. wide, 2 ft. deep, with some flowing water, drains E.	
35.30	Bladed road, bears SE. and NW.	
37.70	Low spur, slopes W.	
40.01	Record distance for the true point for the cor. of secs. 6 and 7, T4S, R25E, which was not monumented.	
	<p>Land, mountainous. Soil, rocky. Timber, scattered cedar and pinon. Undergrowth, scattered cacti.</p>	
	N. 0°04' W., beginning new measurement.	
	Asc. over SE. slope.	
.30	Left fork of Markham Creek, 150 lks. wide, 2 ft. deep, with some flowing water, drains S., circling E.	
1.50	Record distance for the witness sec. cor. of secs. 6 and 7, T4S, R25E, originally set 1.50 chs. N. of the true point. Find the iron post, 36 ins. long, 2 ins. diam., properly mkd., washed out and lying loose on the ground.	
1.50	Point for the witness sec. cor. of secs. 6 and 7 at proportionate distance.	
	Reset the iron post 30 ins. in the ground, mound of stone to E., 3 ft. high, 4 ft. base.	
2.87	Point for the cor. of secs. 1 and 12, T4S, R24E.	
	Set the iron post 12 ins. in the ground, mound of stone to top, 5 ft. base, cap mkd.	
	<p>T4S R24E S 1 S12 1963</p>	
25.10	Left fork of Markham Creek, 100 lks. wide, 3 ft. deep, with some flowing water, drains S. 30° E.	

CHAINS	
26.20	Bladed road in wash, bears S. 30° E. and N. 30° W.
27.07	Fence, barbed wire, bears SE. and NW.; asc. over SW. slope.
36.90	Ravine, drains W.
40.01	The ¼ sec. cor. of sec. 6, monumented by an iron post conforming to the record.
	N. 0°05' W., beginning new measurement.
	Asc. over rocky SW. slope.
2.86	Point for the ¼ sec. cor. of sec. 1, T4S, R24E.
	Set the iron post 10 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.
	T4S R24E ¼ S 1 1963
8.90	Begin gentle asc. over W. slope.
17.70	Deep ravine, drains W.
39.97	The cor. of secs. 1, 6, 31 and 36, Ts3&4S, Rs24&25E., monumented by an iron post conforming to the record.
	Land, rolling and mountainous. Soil, rocky. Timber, scattered cedar and pinon. Undergrowth, scattered cacti.
<hr/> Dependent Resurvey, Portion, West Boundary Township 4 South, Range 24 East	
<hr/> Reestablishment of the Survey in 1875 by T. F. White	
	<hr/> From the cor. of secs. 1, 6, 31 and 36, Ts4&5S, Rs23&24E, previously described.
	N. 0°19' E., bet. secs. 31 and 36.
	Over rolling land.
9.00	Wash, 15 lks. wide, 1 ft. deep, drains SW., circling S.
21.70	Wash, 10 lks. wide, 1 ft. deep, drains SW, circling S.
32.90	Wash, 30 lks. wide, 1 ft. deep, drains SW. into George Canyon Wash.
40.31	The ¼ sec. cor. of secs. 31 and 36, monumented by a mound of stone 2 ft. high, with pieces of rotted wood alongside. This point is accepted as the best remaining evidence of the original cor. This cor. now functions as the ¼ sec. cor. of sec. 36, only.

CHAINS		
	<p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, build a mound of stone to W., 2½ ft. high, 3½ ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4S R23E ¼ S36 1963</p> </div> <hr/> <p>N. 0°07' W., beginning new measurement.</p> <p>Over rolling land.</p>	
6.40	George Canyon Wash, 400 lks. wide, 3 ft. deep, drains SW.	
12.00	Wash, 40 lks. wide, 1 ft. deep, drains S. into George Canyon Wash.	
28.20	Wash, 10 lks. wide, 1 ft. deep, drains SW.	
35.10	Wash, 40 lks. wide, 1 ft. deep, drains SW.	
39.77	<p>The cor. of secs. 25, 30, 31 and 36, monumented by an old mound of stone, 2 ft. high. This point is accepted as the best remaining evidence of the original cor. This cor. now functions as the cor. of secs. 25 and 36 only.</p> <p>At the cor. point</p> <p>Set an iron post 12 ins. in the ground, mound of stone to top, 2½ ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4S R23E S25 S36 1963</p> </div> <p>Land, rolling. Soil, rocky. Timber, scattered mesquite along washes. Undergrowth, scattered cacti and grass.</p> <hr/> <p>N. 0°05' W., bet. secs. 25 and 30.</p> <p>Over rolling hills and washes.</p>	
9.40	Spur, slopes S. 40° W.	
17.70	Wash, 30 lks. wide, 1 ft. deep, drains SW.	
28.00	Wash, 10 lks. wide, 1 ft. deep, drains SW.	
34.40	Old road, bears NE. and SW.	
39.91	<p>The ¼ sec. cor. of secs. 25 and 30, monumented by a volcanic stone, 14x10x9 ins., plainly mkd. This cor. now functions as the ¼ sec. cor. of sec. 25, only.</p> <p>At the cor. point</p> <p>Set the iron post 8 ins. in the ground, mound of stone</p>	

CHAINS

to top, 3½ ft. base, cap mkd.

	T4S	
R23E		R24E
¼		
S25		
	1963	

bury the original cor. stone alongside.

N. 0°06' W., beginning new measurement.

8.90 Wash, 30 lks. wide, 1 ft. deep, drains S. 40° W.

17.20 Spur, slopes S. 35° W.

22.30 Small draw, drains SW.

27.00 Clay Mine Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.

39.83 The cor. of secs. 19, 24, 25 and 30, monumented by an iron post 2½ ins. diam., conforming to the record.

Land, rolling.
Soil, rocky.
Timber, none.
Undergrowth, scattered cacti.

From the cor. of secs. 1, 6, 7 and 12, T4S, Rs23&24E, monumented by an iron post 2½ ins. diam., conforming to the record.

N. 0°08' W., bet. secs. 1 and 6.

Over high hills, through scattered creosote brush; asc. along E. slope.

7.80 Wash, 30 lks. wide, 2 ft. deep, drains S. 10° E.

10.20 Same wash, 30 lks. wide, 2 ft. deep, drains S. 25° W.; asc. S. slope.

19.40 Spur, projects SW. 3 chs., then slopes S.

24.20 Wash, 20 lks. wide, 2 ft. deep, drains S. 75° W.; asc. steep SW. slope.

31.90 Spur, slopes W., desc. N. slope.

39.54 The ¼ sec. cor. of secs. 1 and 6, monumented by an old mound of stone 2 ft. high, with traces of old post. This point is accepted as the best remaining evidence of the original corner, and now functions as the ¼ sec. cor. of sec. 1 only.

At the cor. point

Set the iron post 6 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

	T4S	
	¼	
S 1		
R23E		
	1963	

CHAINS	
	N. 0°04' W., beginning new measurement.
18.50	Begin desc. over steep N. slope.
36.20	Burton Wash, 130 lks. wide, 2 ft. deep, drains S. 75° W. from E., asc. SW. slope.
39.16	The cor. of secs. 1, 6, 31 and 36, Ts3&4S, Rs23&24W, monumented by an iron post 2½ ins. diam., conforming to the record.
	Land, rolling and mountainous. Soil, rocky. Timber, scattered palo verde, cedar and pinon. Undergrowth, scattered creosote brush and cacti.
<hr/> <p>Resurvey of a Portion of the Subdivision Township 4 South, Range 24 East, G&SRM, Arizona</p> <hr/>	
<p>Reestablishment of the Survey in 1955 by Donald E. Harding and Fred R. Chappell</p> <hr/>	
	From the cor. of secs. 25 and 36, on the east boundary of the township, previously described.
	N. 89°40' W., bet. secs. 25 and 36.
	Over rolling S. slope, through scattered creosote brush.
1.00	Small draw, drains S. 10° W.
19.60	Wash, 10 lks. wide, 1 ft. deep, drains SW., asc. SE. slope.
26.40	Low ridge, bears NE. and S.
32.40	Head of small draw.
39.93	The ¼ sec. cor. of secs. 25 and 36, monumented by an iron post as described in the official record.
	S. 89°50' W., beginning new measurement.
12.70	Crest of low ridge, bears NE. and SW.; desc. along NW. slope.
20.50	Wash, 40 lks. wide, 1 ft. deep, drains S. from N. 10° E.; desc. along gentle S. slope.
23.50	Jeep road, bears N. and S.
34.60	Low spur, slopes SW.; desc. gentle NW. slope.
40.12	The cor. of secs. 25, 26, 35 and 36, monumented by an iron post as described in the official record.
	Land, rolling. Soil, sandy and rocky clay. Timber, none. Undergrowth, creosote brush and cacti.

CHAINS

S. 0°05' E., bet. secs. 35 and 36.

Over rolling land, through scattered creosote brush.

1.80 Low spur, slopes S. 80° W.; desc. S. slope.

8.70 Small draw, drains S. 85° W.; asc. gentle N. slope.


11.90 Low spur, slopes S. 85° W.

22.00 Low spur, slopes SW.; desc. gentle S. slope.

27.60 Jeep road, bears N. 4° E. and S. 4° W.

36.10 Small wash, drains E.


39.42 The 1/4 sec. cor. of secs. 35 and 36, monumented by an iron post as described in the official record. This cor. now functions for sec. 36 only and is remarked to show



S. 0°05' E., beginning new measurement.

.58 Point for the 1/4 sec. cor. of sec. 35 only at 40.00 chs. in latitude from the north.

Set the iron post 24 ins. in the ground, build a mound of stone to the W., 2 1/2 ft. high, 3 ft. base, cap mkd.



8.10 Wash, 30 lks. wide, 2 ft. deep, drains S. 2° E. from N. 4° E.

26.20 Same wash, drains S. 5° W. from N.; asc. SW. slope.

30.60 Spur, slopes S. 10° W.; desc. S. slope.

40.18 The cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township, previously described.

Land, rolling.
Soil, rocky and sandy clay.
Timber, none.
Undergrowth, scattered creosote brush and cacti.

From the cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the township, monumented by an iron post as described in the official record.

S. 0°22' W., bet. secs. 1 and 2.

Over high rolling hills; asc. rocky N. slope.

BOOK 4705

Resurvey, Portion, Subdivision, T4S, R24E, Arizona 15.

CHAINS	
10.70	Small spur, slopes E.
21.70	Rocky wash, 40 lks. wide, 5 ft. deep, drains E.
25.20	Small rocky spur, slopes E.
34.70	Spur, slopes S. 55° E.
40.04	The ¼ sec. cor. of secs. 1 and 2, monumented by an iron post as described in the official record. This cor. now functions for sec. 2 only and is remarked to show
<p>T4SR24E ¼ S2 1963 1955</p>	
<p>S. 0°19' W., beginning new measurement; desc. rocky S. slope.</p>	
.90	Wash, 20 lks. wide, 2 ft. deep, drains E.; asc. N. slope.
4.10	Spur, slopes S. 80° E.; desc. broken S. slope.
10.40	Wash, 40 lks. wide, 3 ft. deep, drains E.; asc. NW. slope.
40.06	The cor. of secs. 1, 2, 11 and 12, monumented by an iron post as described in the official record. This cor. now functions for sec. 2 only, and is remarked to show:
<p>R24E S2 T4S 1963 1950</p>	
<p>Land, mountainous. Soil, rocky. Timber, scattered pinon pine and cedar. Undergrowth, scrub oak.</p>	
<p>N. 89°43' W., bet. secs. 2 and 11; by triangulation, topography taken from original record.</p>	
<p>Desc. 60 ft. over W. slope.</p>	
6.40	Bottom of desc.; asc. 110 ft. over SE. slope.
15.00	Spur, slopes NE.; desc. 30 ft. along NW. slope.
20.20	Bottom of desc.; asc. 270 ft. over broken NE. slope.
39.50	Spur, slopes NW.
39.91	The ¼ sec. cor. of secs. 2 and 11, monumented by an iron post as described in the official record. This cor. now functions for sec. 2 only, and is remarked to show

CHAINS

T4SR24E

 $\frac{1}{4}$ S 2

1963

1955

N. 89°49' W., beginning new measurement.

- 4.10 Begin desc. over steep W. slope.
- 15.40 Wash, 20 lks. wide, 2 ft. deep, drains N. 20° E. from SW.; asc. steep SE. slope.
- 37.60 Ridge, bears NE. and SW. for 2 chs.; thence S. 30° W.
- 40.08 The cor. of secs. 2, 3, 10 and 11, monumented by an iron post as described in the official record. This cor. now functions for sec. 2 only and is remarked to

T4S

R24E

| S2

1963

1955

Land, mountainous.
Soil, rocky.
Timber, scattered pinon and cedar.
Undergrowth, scrub oak.

From the cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the township, monumented by an iron post as described in the official record.

S. 0°16' E., bet. secs. 2 and 3.

Along gentle rolling E. slope.

- 26.10 Spur, slopes SE.; desc. S. slope.
- 39.95 The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented by an iron post as described in the official record. This cor. now functions for sec. 2 only and is remarked to show

 $\frac{1}{4}$

| S2

T4SR24E

1963

S. 0°12' W., beginning new measurement.

- 2.40 Wash, 40 lks. wide, 1 ft. deep, drains N. 80° E.; asc. rocky N. slope.
- 9.10 Saddle of ridge bearing N. 66° E. and West; desc. over rolling S. slope.
- 30.00 Small draw, drains N. 80° E.
- 39.58 The cor. of sec. 2 only, previously described.

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and clay. Timber, pinon and cedar. Undergrowth, scrub oak and cacti.</p> <hr/> <p style="text-align: center;">Completion Survey of the Subdivisions Township 4 South, Range 24 East, G&SRM, Arizona</p> <hr/> <p>In the retracement and resurvey of the west boundary of Township 4 South, Range 25 East, and the survey of the north five miles of the east boundary of Township 4 South, Range 24 East, it was found necessary to establish a sectional guide meridian north from the corner of sections 25, 26, 35 and 36 at regular intervals of 40.00 and 80.00 chains.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, previously described.</p> <p>North, bet. secs. 25 and 26.</p> <p>Over rolling land.</p> <p>2.90 Wash, 10 lks. wide, 1 ft. deep, drains SW.</p> <p>16.70 Wash, 40 lks. wide, 1 ft. deep, drains SW.</p> <p>23.80 Wash, 15 lks. wide, 4 ft. deep, drains S. 30° E. from N.; begin asc. over steep and rocky SW. slope.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p style="text-align: center;">T4SR24E 1/4 S26 S25 1963</p> <p>60.00 Spur, slopes S. 10° E.; asc. along E. side of top of Oliver Knoll.</p> <p>69.70 Begin desc. over steep N. slope of Oliver Knoll.</p> <p>80.00 Point for the cor. of secs. 23, 24, 25 and 26.</p> <p style="text-align: center;">T4SR24E S23 S24 S26 S25 1963</p> <p>from which</p> <p style="text-align: center;">The head of Oliver Springs bears N. 35° 11' E., 44.07 chs. dist.</p>

CHAINS	
	<p>Land, mountainous. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.</p> <hr/> <p>S. 89°56' E., bet. secs. 24 and 25.</p> <p>Over rough and mountainous land.</p>
4.50	Small draw, drains N, heads 4 chs. S.; asc. along NW. slope.
30.60	A black knob 15 ft. high bears N. 15 lks. dist.; asc. along backbone of a black ridge.
37.60	Small black ridge bears NE. and SW.
40.00	Point for the ¼ sec. cor. of secs. 24 and 25; falls on a rocky S. slope under a 100-ft. cliff.
	<p>Set the iron post over an X chiseled on solid rock, mound of stone to top, 3½ ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E ¼ $\frac{S\ 24}{S\ 25}$ 1963</p>
	Desc. over rocky SW. slope.
65.00	Begin asc. over steep west slope.
75.20	Rim on top of steep slope, bears SE. and NW.; asc. along gentle N. slope of a rounded knoll.
79.88	The cor. of secs. 24 and 25 on the E. bdy. of the township, previously described.
	<p>Land, mountainous and broken. Soil, rocky. Timber, scattered palo verde, pinon and cedar. Undergrowth, scattered yucca, spanish bayonet and cacti.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>North, bet. secs. 23 and 24.</p> <p>Over steep N. slope through scattered palo verde and cacti.</p>
25.10	Wash, 40 lks. wide, 3 ft. deep, drains W.
25.60	Oliver Spring Wash, 70 lks. wide, 4 ft. deep, drains W. from NE.; asc. broken and rocky S. slope.
40.00	Point for the ¼ sec. cor. of secs. 23 and 24.
	<p>Set the iron post over an X chiseled on solid rock, mound of stone to top, 4 ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E ¼ S23 S24 1963</p>

BOOK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona 19.

CHAINS	
	Asc. over rocky and ledgy S. slope by triangulation, topography taken from USGS quadrangle.
44.50	Draw, drains S. 70° W. from N. 15° E.
47.00	Spur, slopes S. 15° W.; asc. steep and rocky SW. slope.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set the iron post 6 ins. in the ground, mound of stone to top, 4½ ft. base, cap mkd. <div style="text-align: center;"> T4SR24E S14 S13 S23 S24 1963 </div>
	Land, mountainous. Soil, rocky. Timber, scattered palo verde. Undergrowth, scattered cacti.
	S. 89°57' E., bet. secs. 13 and 24. Over steep SW. slope.
4.20	Rim of high plateau, bears SE. and NW.
33.10	Small spur, slopes N. 15° E.
40.00	Point for the ¼ sec. cor. of secs. 13 and 24. Set the iron post 4 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd. <div style="text-align: center;"> T4SR24E ¼ S 13 S 24 1963 </div>
54.80	Wash, 20 lks. wide, 1 ft. deep, drains E., then NE.
64.30	High spur, slopes N. 75° E.
73.50	Wash, 30 lks. wide, 1 ft. deep, drains N.
79.78	The cor. of secs. 13 and 24 on the E. bdy. of the township, previously described. Land, high rolling. Soil, rocky clay. Timber, scattered pinon, palo verde and cedar. Undergrowth, scattered cacti.
	From the cor. of secs. 13, 14, 23 and 24. North, bet. secs. 13 and 14. Asc. steep rocky SW. slope.
2.30	Base of nearly vertical cliff, 110 ft. high.
6.40	S. rim of high plateau, bears S. 75° E. and N. 30° W.; thence over rolling and broken land through scattered pinon and cedar.

CHAINS	
38.40	Bottom deep canyon, drains E. from SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, falls on steep S. slope. Set the iron post 6 ins. in the ground, mound of stone to top, 5 ft. base, cap mkd. T4SR24E $\frac{1}{4}$ S14 S13 1963
47.80	Rocky spur slopes E.; desc. over broken ground along E. slope.
65.50	Wash, 20 lks. wide, 3 ft. deep, drains E.; asc. S. slope.
70.80	Rocky spur, slopes S. 75° E.; desc. along NE. slope.
80.00	Point for the cor. of secs. 11, 12, 13 and 14, falls on E. slope. Set the iron post over an X on solid rock, mound of stone to top, 4 ft. base, cap mkd. T4SR24E S11 S12 S14 S13 1963 Land, broken. Soil, rocky. Timber, scattered cedar and pinon. Undergrowth, scattered black brush and cacti.
	East, bet. secs. 12 and 13. Desc. E. slope over rolling and broken land.
1.90	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° E.; asc. steep W. slope.
16.20	Top of high knoll, bears SE. and NW.
34.40	Head of draw, drains S. 30° E.; asc. steep SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13. Set the iron post over an X chiseled in solid rock, mound of stone to top, 4 ft. base, cap mkd. T4SR24E $\frac{1}{4}$ S 12 S 13 1963
43.70	Top of high knoll, bears SE. and NW.; desc. steep NE. slope, through dense cedar and pinon trees.
75.60	Wash, 120 lks. wide, with 40-ft. walls, drains S. 20° E., then circles to E.
79.60	The cor. of secs. 12 and 13, on the E. bdy. of the township, previously described.

CHAINS	
	<p>Land, high and broken. Soil, rocky clay. Timber, scattered to medium pinon and cedar. Undergrowth, scattered sagebrush and cacti.</p> <hr/> <p>From the cor. of secs. 1 and 12 on the E. bdy. of the township, previously described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rough rolling land; asc. E. slope.</p>
6.10	Spur, slopes SE.; asc. along S. slope.
16.40	Draw, drains SE.
25.30	Spur, slopes SE.; desc. along S. slope.
39.35	Wash, 10 lks. wide, 1 ft. deep, drains S. from NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only.
	<p>Set the iron post over an X chiseled on solid rock, mound of stone to top, 4 ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E $\frac{1}{4}$ S 1 ----- 1963</p>
	Asc. along E. slope.
49.70	Spur, slopes S.
57.70	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.; asc. steep E. slope.
69.60	Spur, slopes S.; desc. over SW. slope.
78.30	Spur, slopes S. 70° W.; desc. along gentle NW. slope.
81.16	Intersect the E. bdy. of sec. 2.
	<p>Point for the closing cor. of secs. 1 and 11.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E S 2 C S 1 C S 11 ----- 1963</p>
	<p>From this cor. the SE. cor. of sec. 2 only, bears S. 0°19' W., 0.94 chs. dist.</p> <p>Land, rough and mountainous. Soil, rocky clay. Timber, scattered pinon and cedar. Undergrowth, scattered cacti.</p> <hr/> <p>The point for the W. $\frac{1}{4}$ sec. cor. of sec. 1 is on the W. bdy. at 40.00 chs. in northing from the closing corner of secs. 1 and 11.</p>

CHAINS

Set the iron post 6 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

T4SR24E
|
½
|
S 1
1963

from which

The E. ¼ sec. cor. of sec. 2 only, previously described, bears S. 0°22' W., 0.88 chs. dist.

From the cor. of secs. 11, 12, 13 and 14.

North, bet. secs. 11 and 12.

Over mountainous land; asc. rolling S. slope.

4.40 Wash, 10 lks. wide, 1 ft. deep, drains SE.

11.80 Spur, slopes SW.; desc. steep N. slope.

20.60 Wash, 30 lks. wide, 2 ft. deep, drains N. 75° E.

26.50 Rocky spur, slopes S. 50° E.

32.70 Wash, 20 lks. wide, 1 ft. deep, drains S. 40° E.; asc. steep S. slope.

40.00 Point for the ¼ sec. cor. of secs. 11 and 12.

Set the iron post over an X chiseled on solid rock, mound of stone to top, 4 ft. base, cap mkd.

T4SR24E
¼
S11 | S12
1963

52.50 High spur, slopes NW.; desc. steep N. slope.

66.20 Wash, 30 lks. wide, 1 ft. deep, drains SE.; asc. steep SW. slope.

74.20 Ravine, drains S. 20° W.

79.90 Spur, slopes W.

79.92 Intersect the S. bdy. of sec. 1.

Point for the closing cor. of secs. 11 and 12.

Set the iron post over an X chiseled on solid rock, mound of stone to top, 4 ft. base, cap mkd.

T4SR24E
S1

S11 | S12
C C
1963

From this cor. the closing cor. of secs. 1 and 11 bears W., 1.58 chs. dist.

CHAINS	
	<p>Land, steep, broken hills. Soil, rocky clay. Timber, scattered pinon and cedar. Undergrowth, scattered cacti.</p> <hr/> <p>The point for the $\frac{1}{4}$ sec. cor. of sec. 12 is on the N. bdy. at 40.00 chs. in easting from the closing corner of secs. 11 and 12 and falls on precipitous E. slope where corner cannot be perpetuated.</p> <p>At a point East, 0.13 chs. dist., is the point selected for the witness corner.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4SR24E WC ← $\frac{1}{4}$ S12 1963</p> </div> <p>From the true point for the $\frac{1}{4}$ sec. cor. of sec. 12, the $\frac{1}{4}$ sec. cor. of sec. 1 bears West 0.42 chs. dist.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>West, on a sectional correction line, bet. secs. 26 and 35.</p> <p>Over rolling land; desc. gentle W. slope.</p> <p>12.40 Dim road, bears N. 55° E. and S. 55° W.</p> <p>17.80 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.</p> <p>29.80 Wash, 30 lks. wide, 4 ft. deep, drains SW. from N.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p> <p>Set the iron post 12 ins. in the ground, collar of stone to top, 2 ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4SR24E $\frac{1}{4}$ $\frac{S\ 26}{S\ 35}$ 1963</p> </div> <p>47.50 Spur, slopes SW. from E.</p> <p>63.20 Wash, 40 lks. wide, 2 ft. deep, drains S. for 2 chs., then SW.</p> <p>77.20 Wash, 90 lks. wide, 2 ft. deep, drains S.</p> <p>80.00 Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T4SR24E $\frac{S27}{S34}$ $\frac{S26}{S35}$ 1963</p> </div> <p>Build a mound of stone to the West; 2½ ft. high, 3 ft. base.</p>

CHAINS	
	<p>Land, rolling. Soil, rocky clay. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.</p> <hr/> <p>S. 0°01' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
14.00	Left bank of a large wash, bears NE. and SW.
16.30	Center of same wash, 60 lks. wide, 2 ft. deep, drains SW.
32.00	Wash, 100 lks. wide, 2 ft. deep, drains SW.
40.00	Point for the ¼ sec. cor. of secs. 34 and 35.
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E ¼ S34 S35 1963</p>
41.20	Wash, 20 lks. wide, 1 ft. deep, drains SW.
48.10	Wash, 10 lks. wide, 2 ft. deep, drains W.
63.50	Wash, 40 lks. wide, 1 ft. deep, drains S. 60° W.
78.91	The cor. of secs. 34 and 35 on the S. bdy. of the township, previously described.
	<p>Land, rolling. Soil, gravelly clay. Timber, none. Undergrowth, scattered creosote brush and cacti.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
8.20	Wash, 30 lks. wide, 1 ft. deep, drains S. 10° E.
34.30	Top of low knoll.
40.00	Point for the ¼ sec. cor. of secs. 26 and 27.
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T4SR24E ¼ S27 S26 1963</p> <p>Build a mound of stone to the west, 2 ft. high, 2½ ft. base.</p>
56.80	Wash, 15 lks. wide, 1 ft. deep, drains irregularly S.

CHAINS	
61.20	Same wash, drains irregularly S.
62.60	Same wash, drains irregularly S.; asc. SE. slope.
76.20	Ridge, bears NE. and SW.; desc. along W. slope.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 4 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.
	<p>T4SR24E $\frac{S22}{S27} \frac{S23}{S26}$ 1963</p>
	<p>Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.</p>
	<hr/> From the cor. of secs. 23, 24, 25 and 26.
	N. 89°57' W., bet. secs. 23 and 26.
	Desc. over rolling N. slope of Oliver Knoll.
1.80	Draw, drains N.
7.70	Begin desc. over rolling and broken W. slope.
23.30	Ravine, drains N.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	Set the iron post 19 ins. in the ground, in a collar of stone, cap mkd.
	<p>T4SR24E $\frac{1}{4} \frac{S 23}{S 26}$ 1963</p>
	Build a mound of stone to the north, 2 ft. high, 2½ ft. base.
51.80	Wash, 20 lks. wide, 2 ft. deep, drains S.
61.00	Rocky spur, slopes S.
69.10	Wash, 30 lks. wide, 2 ft. deep, drains S. 30° W.
76.80	Small spur, slopes SW.; desc. W. slope.
79.98	The cor. of secs. 22, 23, 26 and 27.
	<p>Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, scattered cacti.</p>
	<hr/> N. 0°01' W., bet. secs. 22 and 23.
	Over high rolling land; asc. SW. slope.

CHAINS		
3.40	Top of asc.; desc. over NW. slope.	
14.80	Wash, 50 lks. wide, with 10-ft. banks, drains W.; asc. broken S. slope.	
17.40	Bladed road, bears NE. and W.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, falls in a small draw, draining NW.	
	Set the iron post 4 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.	
	T4SR24E	
	$\frac{1}{4}$	
	S22 S23	
	1963	
43.00	Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.	
56.60	Draw, 15 lks. wide, drains SW.; asc. steep rocky S. slope.	
63.50	High rocky spur, slopes S. 80° W.; desc. NW. slope.	
66.90	Wash, 40 lks. wide, 3 ft. deep, drains SW.; asc. S. slope.	
76.00	Spur, slopes SW.; desc. over rocky NE. slope.	
80.00	Point for the cor. of secs. 14, 15, 22 and 23.	
	Set the iron post 8 ins. in the ground, mound of stone to top, 5 ft. base, cap mkd.	
	T4SR24E	
	S15 S14	
	S22 S23	
	1963	
	Land, rolling and broken.	
	Soil, rocky clay.	
	Timber, scattered palo verde and cedar.	
	Undergrowth, scattered creosote brush and cacti.	
	From the cor. of secs. 13, 14, 23 and 24.	
	N. 89°54' W., bet. secs. 14 and 23.	
	Over broken land, desc. steep SW. slope.	
18.10	Draw, drains SW.; asc. SE. slope.	
24.70	Small rocky spur, projects SW.; desc. W. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.	
	Set the iron post 6 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.	
	T4SR24E	
	$\frac{1}{4}$ $\frac{S 14}{S 23}$	
	1963	

BOOK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona 27.

CHAINS	
	Desc. Steep, rocky W. slope.
43.20	Wash, 30 lks. wide, 2 ft. deep, drains S.; asc. steep E. slope.
61.50	Spur, slopes S.; desc. W. slope.
75.10	Draw, drains SW.
79.30	Draw, drains S., circles to SW.
80.00	The cor. of secs. 14, 15, 22 and 23.
	Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, scattered cacti.
<hr/>	
	N. 0°01' W., bet. secs. 14 and 15.
	Over broken, mountainous land.
1.70	Wash, 40 lks. wide, 1 ft. deep, drains S. 30° E.
3.90	Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W., circles to S. 30° E.
35.50	Spur, slopes S. 70° E.
40.00	Point for the ¼ sec. cor. of secs. 14 and 15.
	Set the iron post 6 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.
	T4SR24E ¼ S15 S14 1963
47.00	Spur, slopes E.; thence along broken E. slope.
61.80	Base of cliff.
63.00	Top of cliff, about 120 ft. high; continue along broken E. slope.
69.70	Spur, slopes E.
77.00	Rocky spur, slopes E.
80.00	Point for the cor. of secs. 10, 11, 14 and 15, falls on the N. side of a rocky outcropping.
	Set the iron post 12 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.
	T4SR24E S10 S11 S15 S14 1963
	Land, broken. Soil, rocky. Timber, scattered cedar and pinon. Undergrowth, scattered cacti.

CHAINS	
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89°56' W., bet. secs. 11 and 14.
	Over broken, mountainous land.
6.40	Spur, slopes NE.
21.70	Spur, slopes N. 40° E.
31.60	Wash, 10 lks. wide, 1 ft. deep, drains NE.
39.70	Wash, 10 lks. wide, 1 ft. deep, drains S. 50° E.
39.98	Point for the ¼ sec. cor. of secs. 11 and 14.
	Set the iron post 5 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.
	T4SR24E ¼ $\frac{S\ 11}{S\ 14}$ 1963
62.80	Rim of mesa, bears S. 45° E. and N. 15° W.; desc. steep SW. slope.
77.50	Wash, 15 lks. wide, 2 ft. deep, drains S. 25° E.
79.96	The cor. of secs. 10, 11, 14 and 15.
	Land, broken. Soil, rocky. Timber, medium to scattered pinon and cedar. Undergrowth, scattered cacti.
	N. 0°01' W., bet. secs. 10 and 11.
	Over steep SW. slope.
26.50	Rim of mesa, bears S. 45° E. and N. 60° W.; desc. gentle N. slope.
40.00	Point for the ¼ sec. cor. of secs. 10 and 11.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, 5 ft. base, cap mkd.
	T4SR24E ¼ S10 S11 1963
43.50	Desc. steep NW. slope.
49.80	Wash, 10 lks. wide, 6 ins. deep, drains NE.; asc. SE. slope.
57.00	Spur, slopes NE.; desc. steep N. slope.
63.40	Wash, 10 lks. wide, 6 ins. deep, drains NE. 6 chs., then N.
65.20	Small spur, projects E. for 5 chs.; desc. NE. slope.

CHAINS	
67.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° E.; asc. steep SE. slope.
78.70	Saddle of ridge, bears NE. and S. 30° W.
79.24	Intersect the S. bdy. of sec. 2.
	Point for the C.C. of secs. 10 and 11.
	At the cor. point
	Set the iron post 4 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.
	T4SR24E S2 <hr style="width: 50px; margin: 0 auto;"/> S10 S11 CC 1963
	From this cor., the SW. cor. of sec. 2 bears N. 89°49' W., 1.63 chs. dist.
	Land, broken and rolling. Soil, rocky. Timber, medium pinon and cedar. Undergrowth, scattered catclaw and scrub oak.
	The point for the ¼ sec. cor. of sec. 11 is on the N. bdy. at midpoint bet. the CCs.
	Set the iron post 4 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.
	T4SR24E <hr style="width: 50px; margin: 0 auto;"/> ¼ S11 1963
	From this cor., the ¼ sec. cor. of sec. 2 bears N. 89°43' W., 1.52 chs. dist.
	From the cor. of secs. 26, 27, 34 and 35.
	West, on a sectional correction line, bet. secs. 27 and 34.
	Over rolling land.
17.00	Ridge, bears N. 40° E. and S. 40° W.
22.40	Ravine, drains SW.
27.80	Spur, slopes S. 25° W.
40.00	Point for the ¼ sec. cor. of secs. 27 and 34.
	Set the iron post 18 ins. in the ground, cap mkd.
	T4SR24E ¼ S 27 S 34 1963

CHAINS

Build a mound of stone to the N. of post, 2½ ft. high, 2½ ft. base.

41.20 Wash, 40 lks. wide, 2 ft. deep, drains SW.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set the iron post 5 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

T4SR24E
S28|S27
S33|S34
1963

Land, rolling.
Soil, rocky clay.
Timber, none.
Undergrowth, scattered creosote brush and cacti.

S. 0°01' E., bet. secs. 33 and 34.

Over rolling land.

26.60 Wash, 100 lks. wide, 1 ft. deep, drains S. for 4 chs., then SW.

35.10 Wash, 400 lks. wide, 3 ft. deep, drains SW.

40.00 Point for the ¼ sec. cor. of secs. 33 and 34.

Set the iron post 12 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

T4SR24E
¼
S33|S34
1963

58.10 Wash, 20 lks. wide with 5-ft. banks, drains SW.

63.00 Low spur, slopes S. 40° W.

70.30 High rocky spur, slopes SW.; desc. broken S. slope.

79.70 Intersect the S. bdy. of the township.

Point for the C.C. of secs. 33 and 34.

At the cor. point

Set the iron post 15 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

T4SR24E
CC
S33|S34
1963

From this cor. the cor. of secs. 3 and 4; previously described, bears S. 89°26' W., 0.15 chs. dist.

Land, rolling.
Soil, rocky clay.
Timber, none.
Undergrowth, scattered creosote brush and cacti.

BOOK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona 31.

CHAINS	
	<p>The point for the S. $\frac{1}{4}$ sec. cor. of sec. 34 is on the S. bdy. at mid-point bet. the CCs.</p> <p>At the cor. point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, $3\frac{1}{2}$ ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E <u>$\frac{1}{4}$ S34</u> T5S 1963</p> <p>From this cor., the $\frac{1}{4}$ sec. cor. of sec. 3 bears S. 89° 27' W., 0.16 chs. dist., previously described.</p> <hr/> <p>The point for the S. $\frac{1}{4}$ sec. cor. of sec. 33 is on the S. bdy., at mid-point bet. the CC for secs. 33 and 34 and the cor. of secs. 32 and 33.</p> <p>At the cor. point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, $3\frac{1}{2}$ ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E <u>$\frac{1}{4}$ S33</u> T5S 1963</p> <p>From this cor. the $\frac{1}{4}$ sec. cor. of sec. 4, previously described, bears N. $89^{\circ}15'$ W., 0.24 chs. dist.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. $0^{\circ}01'$ W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p> <p>2.60 Wash, 15 lks. wide, 1 ft. deep, drains S. 50° W.</p> <p>3.90 Wash, 20 lks. wide, 1 ft. deep, drains S. 50° W.</p> <p>20.90 Low ridge, bears E. and S. 20° W.</p> <p>24.20 Wash, 40 lks. wide, 1 ft. deep, drains W.</p> <p>32.00 Low ridge, bears E. and W.</p> <p>38.50 Wash, 20 lks. wide, 1 ft. deep, drains SW.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.</p> <p>Set the iron post 16 ins. in the ground in a collar of stone, cap mkd.</p> <p style="text-align: center;">T4SR24E $\frac{1}{4}$ S28 S27 1963</p> <p>Build a mound of stone to the W., 3 ft. high, 3 ft. base.</p>

CHAINS		
49.75	Bladed road, bears NE. and SW.	
50.40	Spur, bears SW.; desc. NW. slope.	
59.60	Fence, barbed wire, bears NE. and SW.	
60.20	2-in. water pipe line, bears NE. and SW.	
60.30	Wash, 40 lks. wide, 2 ft. deep, drains SW.	
63.20	Fence, barbed wire, bears E. and W.	
63.90	Bladed road, bears NE. and SW.	
80.00	Point for the cor. of secs. 21, 22, 27 and 28.	
	Set the iron post 14 ins. in the ground, mound of stone to top, cap mkd.	
	<p>T4SR24E $\frac{S21}{S28} \frac{S22}{S27}$ 1963</p>	
	from which	
	Teague Spring bears S. 10°21' E., 18.73 chs. dist.	
	<p>Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, medium creosote brush and scattered cacti.</p>	
	From the cor. of secs. 22, 23, 26 and 27.	
	N. 89°58' W., bet. secs. 22 and 27.	
	Over rolling and broken land; desc. W. slope.	
8.20	Wash, 60 lks. wide, 1 ft. deep, drains SW.	
20.70	Wash, 20 lks. wide, 1 ft. deep, drains S.	
35.40	Bladed road, bears NE. and SW.; desc. W. slope.	
39.30	Small draw, drains S. 45° W.	
39.98	Point for the ¼ sec. cor. of secs. 22 and 27.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	<p>T4SR24E $\frac{1}{4} \frac{S22}{S27}$ 1963</p>	
	Build a mound of stone to the N., 2½ ft. high, 2½ ft. base.	
42.80	Ridge, bears N. 20° E. and SW.	
57.00	Wash, 20 lks. wide, 1 ft. deep, drains SW.	
60.40	Wash, 10 lks. wide, 6 ins. deep, drains SW.	

CHAINS	
65.20	Bladed road, bears N. 20° E. and SW.
77.00	Wash, 40 lks. wide, 1 ft. deep, drains S.
79.96	The cor. of secs. 21, 22, 27 and 28.
	Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, medium creosote brush and scattered cacti.
	N. 0°01' W., bet. secs. 21 and 22.
	Over rolling land, through medium creosote brush and scattered cacti.
40.00	Point for the ½ sec. cor. of secs. 21 and 22.
	Set the iron post 6 ins. in the ground, mound of stone to top, 5 ft. base, cap mkd.
	T4SR24E ½ S21 S22 1963
47.10	Wash, 15 lks. wide, 1 ft. deep, drains S. 25° E.
76.00	Spur, slopes S. 70° E.
80.00	Point for the cor. of secs. 15, 16, 21 and 22, falls on a NE. slope.
	Set the iron post 6 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.
	T4SR24E S16 S15 S21 S22 1963
	Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°56' W., bet. secs. 15 and 22.
	Over rolling land.
7.20	Crest of rocky ridge, bears N. and S.
15.80	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.
24.80	Spur, slopes N. A rocky knoll bears S., 0.60 chs. dist.
39.97	Point for the ½ sec. cor. of secs. 15 and 22, falls on a SE. slope.

CHAINS

Set the iron post 12 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.

T4SR24E
 $\frac{1}{4}$ $\frac{S 15}{S 22}$
 1963

from which

Walnut Spring, with a 3/4-in. pipe through which water flows into a cement trough 2 ft. by 2 ft. by 10 ft. long, bears S. 6°08' W., 15.32 chs. dist.

46.90 Wash, 10 lks. wide, 1 ft. deep, drains S.

57.10 Wash, 20 lks. wide, 1 ft. deep, drains S.

58.70 Dirt road, bears S. 35° E. and N. 70° W.

75.30 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° E.

79.94 The cor. of secs. 15, 16, 21 and 22.

Land, rolling and broken.
 Soil, rocky.
 Timber, none.
 Undergrowth, scattered creosote brush and cacti.

N. 0°01' W., bet. secs. 15 and 16.

Over rolling land.

9.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.

22.10 Small rocky knoll.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

Set the iron post 10 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.

T4SR24E
 $\frac{1}{4}$
 S16|S15
 1963

from which

An unnamed pond bears S. 84°42' E., 12.44 chs. dist.

40.70 Wash, 10 lks. wide, 1 ft. deep, drains W.

52.30 Wash, 25 lks. wide, 2 ft. deep, drains W.

61.30 Spur, slopes S. 50° E.

80.00 Point for the cor. of secs. 9, 10, 15 and 16, falls on a SE. slope.

Set the iron post 10 ins. in the ground, mound of stone to top, 5 ft. base, cap mkd.

CHAINS		
	T4SR24E $\frac{S9}{S16} \frac{S10}{S15}$ 1963	
	Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.	
	<hr/>	
	From the cor. of secs. 10, 11, 14 and 15. N. 89°57' W., bet. secs. 10 and 15. Over rough and broken land; asc. E. slope.	
17.00	Rim of mesa, bears S. 6° E. and N. 31° W.; desc. steep SW. slope.	
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15. Set the iron post 8 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.	
	T4SR24E $\frac{1}{4} \frac{S10}{S15}$ 1963	
	Desc. broken SW. slope.	
68.00	East fork of George Canyon, 100 lks. wide, 2 ft. deep, drains S. 20° E.; asc. broken E. slope.	
79.94	The cor. of secs. 9, 10, 15 and 16. Land, broken. Soil, rocky. Timber, scattered pinon and cedar on top of mesa. Undergrowth, scattered creosote brush and cacti.	
	<hr/>	
	N. 0°01' W., bet. secs. 9 and 10. Over broken land.	
22.00	Spur, slopes SE.	
32.90	Wash, 15 lks. wide, 1 ft. deep, drains S. 10° E.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10 falls on the E. edge of a small draw draining S. 15° W. Set the iron post 4 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.	
	T4SR24E $\frac{1}{4}$ $\frac{S9}{S10}$ 1963	
	Asc. broken S. slope.	
66.00	Spur, projects E. 4 chs.	

CHAINS	
78.80	Small spur, slopes E.
80.00	Point for the cor. of secs. 3, 4, 9 and 10 falls on a NE. slope.
	Set the iron post 15 ins. in the ground, mound of stone to top, 2½ ft. base, cap mkd.
	<p>T4SR24E $\frac{S4}{S9} \frac{S3}{S10}$ 1963</p>
	Land, steep and broken. Soil, rocky. Timber, scattered cedar. Undergrowth, scattered catclaw and cacti.
	East, bet. secs. 3 and 10.
	Over steep and broken land; desc. steep E. slope.
11.00	Wash, 20 lks. wide, 1 ft. deep, drains S.; asc. steep SW. slope.
37.90	Rim of mesa, bears S. and NW.; asc. gentle SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 3 and 10 falls on gentle E. slope.
	Set the iron post 12 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.
	<p>T4SR24E $\frac{1}{4} \frac{S3}{S10}$ 1963</p>
61.90	Wash, 20 lks. wide, 1 ft. deep, drains S. 80° E. for 3 chs. then N. 75° E.
69.30	Same wash, 30 lks. wide, 2 ft. deep, drains NE.
78.29	Intersect the W. bdy. of sec. 2.
	Point for the C.C. of secs. 3 and 10.
	At the cor. point
	Set the iron post 6 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.
	<p>T4SR24E $\frac{C S3}{C S10} S2$ 1963</p>
	From this cor. the SW. cor. of sec. 2 bears S. 0°12' W., 0.90 chs. dist.
	Land, west ½ mile steep and broken, east ½ mile, rolling. Soil, rocky. Timber, scattered pinon and cedar. Undergrowth, scattered scrub oak and cacti.

CHAINS	
	<p>The point for the E. $\frac{1}{4}$ sec. cor. of sec. 3 is on the E. bdy. at 40.00 chs. in northing from the closing cor. of secs. 3 and 10.</p> <p>At the cor. point</p> <p>Set the iron post over an X on solid rock, mound of stone to top, 4 ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4SR24E</p> <p>$\frac{1}{4}$ </p> <p>S 3 </p> <p>1963</p> </div> <p>From this cor. the $\frac{1}{4}$ sec. cor. of sec. 2 bears S. $0^{\circ}16'$ W., 1.32 chs. dist.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10</p> <p>N. $0^{\circ}01'$ W., bet. secs. 3 and 4.</p> <p>Over broken land.</p>
8.00	Spur, slopes E.
14.90	Wash, 20 lks. wide, 1 ft. deep, drains SE.; asc. broken S. slope.
34.90	Rim of mesa, bears E. and N. 75° W.
39.00	Wash, 15 lks. wide, 1 ft. deep, drains SE. 2 chs., then E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, $3\frac{1}{2}$ ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4SR24E</p> <p>$\frac{1}{4}$ </p> <p>S 4 S 3</p> <p>1963</p> </div>
59.00	Ridge, bears N. 75° E. and N. 80° W.
77.19	Intersect the N. bdy. of the township.
	<p>Point for the C.C. of secs. 3 and 4.</p> <p>At the cor. point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T3SR24E</p> <p>S 4 S 3</p> <p>CC</p> <p>T4S</p> <p>1963</p> </div> <p>From this cor. the original cor. of secs. 3, 4, 33 and 34, an iron post as described in the official record, bears N. $89^{\circ}53'$ W., 1.48 chs. dist. This cor. now functions for secs. 33 and 34 only and is remarked to show</p>

CHAINS

T3SR24E
S33 | S34
 T4S
 63
 1955

Land, steep and broken.
 Soil, rocky.
 Timber, scattered pinon and cedar.
 Undergrowth, scattered scrub oak and cacti.

The point for the $\frac{1}{4}$ sec. cor. of sec. 3 is on the N. bdy. at 40.00 chs. in easting from the closing corner of secs. 3 and 4.

Set the iron post 6 ins. in the ground, mound of stone to top, 5 ft. base, cap mkd.

T3S
 $\frac{1}{4}$ S 3
 T4SR24E
 1963

From this cor. the original $\frac{1}{4}$ sec. cor. of secs. 3 and 34, an iron post as described in the official record, bears S. $87^{\circ}49'$ W., 1.40 chs. dist. This cor. now functions for sec. 34 only and is remarked to show

T3SR24E
 $\frac{1}{4}$ S34
 T4S
 63
 1955

From the cor. of secs. 27, 28, 33 and 34.

S. $89^{\circ}47'$ W., bet. secs. 28 and 33.

Over rolling land.

6.90 Enter wash, 30 lks. wide, 2 ft. deep, drains W.

11.50 Leave same wash, drains SW.

40.19 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.

Set the iron post 10 ins. in the ground, mound of stone to top, $3\frac{1}{2}$ ft. base, cap mkd.

T4SR24E
 $\frac{1}{4}$ S 28
 S 33
 1963

51.40 Wash, 40 lks. wide, 2 ft. deep, drains SW.

56.40 Bladed road, bears N. 20° E. and S.

63.10 Aqueduct from Teague Spring, bears NE. and S. 20° W.

78.20 Wash, 40 lks. wide, 2 ft. deep, drains W. 4 chs., then S.

80.38 The cor. of secs. 28, 29, 32 and 33, monumented by an iron post as described in the official record.

BOOK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona 39.

CHAINS	
	<p>Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
13.10	Low ridge, bears NE. and SW.
19.60	Wash, 5 lks. wide, 6 ins. deep, drains S. 40° W.
24.30	Low ridge, bears NE. and SW.
33.80	Wash, 10 lks. wide, 6 ins. deep, drains S. 20° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
	<p>Set the iron post 5 ins. in the ground, mound of stone to top, 3$\frac{1}{2}$ ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E $\frac{1}{4}$ S29 S28 1963</p>
49.90	Small wash, drains S. 40° W.
54.90	Small wash, drains S. 20° W.
64.30	Small wash, drains S. 30° W.
75.90	Small wash, drains S. 20° W.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, 3$\frac{1}{2}$ ft. base, cap mkd.</p> <p style="text-align: center;">T4SR24E S20 S21 S29 S28 1963</p> <p>Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, scattered creosote brush and cacti.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°47' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
11.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W. 5.00 chs., then S. 35° W.
21.90	Wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.
24.40	Wash, 20 lks. wide, 1 ft. deep, drains S. 20° E.

CHAINS

- 34.60 High spur, slopes S. 40° W.
- 40.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 10° W.
- 40.20 Point for the 1/4 sec. cor. of secs. 21 and 28.
Set the iron post 4 ins. in the ground, mound of stone to top, 4 1/2 ft. base, cap mkd.

T4SR24E
 1/4 S 21
 S 28
 1963

- 52.40 Saddle in ridge, bearing N. 35° E. and S. 35° W.
- 58.80 Wash, 15 lks. wide, 1 ft. deep, drains SW.
- 63.00 Wash, 15 lks. wide, 2 ft. deep, drains S. 15° E.
- 69.20 Spur, slopes N.
- 76.70 Wash, 25 lks. wide, 1 ft. deep, drains S. 25° W.
- 80.40 The cor. of secs. 20, 21, 28 and 29.

Land, rolling.
 Soil, rocky.
 Timber, none.
 Undergrowth, scattered creosote brush and cacti.

N. 0°02' W., bet. secs. 20 and 21.
 Over rolling land; asc. SE. slope.

- 6.80 Ridge, bears NE. and SW.
- 15.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.
- 23.80 Spur, slopes S. 40° W. from N.
- 31.90 Spur, slopes S. 35° W. from S.; desc. NW. slope.
- 39.00 Small draw, drains W.
- 40.00 Point for the 1/4 sec. cor. of secs. 20 and 21.
Set the iron post 24 ins. in the ground, cap mkd.

T4SR24E
 1/4
 S20 | S21
 1963

- Build a mound of stone to W. 2 ft. high, 2 1/2 ft. base.
- 42.80 Small draw, drains S. 75° W.; asc. rocky S. slope.
- 51.90 Small draw, drains W. from NE.
- 58.40 Rocky spur, slopes SW.; desc. rocky N. slope.
- 64.20 Draw, drains W. from NE.; asc. steep and rocky SW. slope.

BOOK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona 41.

CHAINS	
79.00	Top of ledge 75 ft. high; desc. NW. slope.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 18 ins. in the ground in a collar of stone, cap mkd.
	T4SR24E $\frac{S17}{S20} \frac{S16}{S21}$ 1963
	Build a mound of stone to W. 2 ft. high, 3 ft. base.
	Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°44' W., bet. secs. 16 and 21.
	Over rolling land.
4.30	Spur, slopes SE.
12.30	Spur, slopes S.
21.40	Small rocky spur, slopes SW.
28.00	Draw, drains S.
37.40	Fork in Ridge, bears N. 10° E. and S. 20° W.; desc. NW. slope.
40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.
	Set the iron post 16 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.
	T4SR24E $\frac{1}{4} \frac{S 16}{S 21}$ 1963
47.50	Small wash, drains S. 20° W.
55.00	Low spur, slopes S. 20° W.; desc. NW. slope.
69.30	Draw, drains N. 65° W.; asc. E. slope.
76.60	Top of ledge 20 ft. high; desc. along N. slope.
80.44	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling and broken. Soil, rocky clay. Timber, none. Undergrowth, scattered creosote brush, catclaw and cacti.

CHAINS	
	N. 0°02' W., bet. 16 and 17.
	Desc. over N. slope.
7.30	Left bank of wash in George Canyon, bears N. 40° E. and S. 40° W.
8.60	An old rock house bears E., 1.00 chain dist.
9.30	Road in George Canyon Wash, bears N. 40° E. and S. 40° W.
11.25	Right bank of same wash; asc. ledgy S. slope.
23.10	Rocky spur, slopes SW.
34.80	Small wash, drains S. 35° W.; asc. S. slope.
40.00	Point for the ¼ sec. cor. of secs. 16 and 17.
	Set the iron post 6 ins. in the ground, mound of stone to top, 4½ ft. base, cap mkd.
	T4SR24E ¼ S17 S16 1963
40.10	Small draw, drains S. 35° E.
47.40	Spur, slopes SW.
59.90	Small wash, drains S. 20° W.; asc. SE. slope.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set the iron post 12 ins. in the ground, mound of stone to top, 2½ ft. base, cap mkd.
	T4SR24E S8 S9 S17 S16 1963
	Land, broken. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush, catclaw and cacti.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 89°43' W., bet. secs. 9 and 16.
	Over broken mountainous land.
4.80	Ridge, bears N. and S.
16.80	Spur, slopes SW.
22.70	West fork of George Canyon, 25 lks. wide, 2 ft. deep, drains S. 80° W.
25.50	Wash, 30 lks. wide, 2 ft. deep, drains S. 70° W.

CHAINS		
36.00	Spur, slopes S. 10° W.	
38.40	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 9 and 16.	
	Set the iron post over an X chiseled on solid rock, mound of stone to top, 3 $\frac{1}{2}$ ft. base, cap mkd.	
	T4SR24E $\frac{1}{4}$ ← $\begin{matrix} S9 \\ S16 \end{matrix}$ WC 1963	
38.50	E. rim of a canyon, bears N. and S. 5° E.; desc. nearly vertical W. slope.	
40.25	True point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16 cannot be perpetuated.	
41.95	Bottom of narrow canyon, drains S.; asc. steep E. slope.	
46.50	Spur, slopes S.; desc. SW. slope.	
64.50	Draw, drains S. 20° E.; asc. E. slope.	
80.50	The cor. of secs. 8, 9, 16 and 17.	
	Land, broken and mountainous. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush, catclaw and cacti.	
	N. 0°02' W., bet. secs. 8 and 9.	
	Over mountainous land.	
3.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 75° E.; asc. S. slope.	
10.00	Low spur, slopes S. 75° E.; desc. NE. slope.	
15.10	Wash, 15 lks. wide, 1 ft. deep, drains S. 40° E.; asc. SW. slope.	
20.00	Spur, projects SE. 4.00 chs., then S. 25° E.; desc. steep NE. slope.	
26.20	Wash, 20 lks. wide, 1 ft. deep, drains S. 75° E. 2 chs., thence SE.; asc. S. slope.	
37.60	Spur, slopes SE.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9 fall at the head of a small gully draining SE.	
	Set the iron post 5 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.	
	T4SR24E $\frac{1}{4}$ S8 S9 1963	

CHAINS		
45.50	Ridge, bears N. 35° E. and S. 35° W.; desc. steep NW. slope.	
54.00	Enter wash area draining SW.	
63.30	Leave wash area; asc. steep, rocky S. slope.	
67.30	Mouth of small canyon, drains SE. 4.00 chs., then SW.; asc. steep and broken S. slope.	
80.00	Point for the cor. of secs. 4, 5, 8 and 9 falls on an E. slope, 20 lks. W. of a small draw draining SE.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	<p>T4SR24E $\frac{S5}{S8} \frac{S4}{S9}$ 1963</p>	
	Build a mound of stone to the W., 3 ft. high, 3 ft. base.	
	<p>Land, broken and mountainous. Soil, rocky. Timber, scattered cedar. Undergrowth, scattered scrub oak, catclaw and cacti.</p>	
	From the cor. of secs. 3, 4, 9 and 10.	
	S. 89°41' W., bet. secs. 4 and 9.	
	Over rough and mountainous land; asc. steep E. slope.	
17.00	Rim of mesa, bears N. 5° E. and S. 10° E.; asc. E. slope.	
38.30	Begin desc. over steep W. slope.	
40.25	Point for the ¼ sec. cor. of secs. 4 and 9.	
	Set the iron post 6 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.	
	<p>T4SR24E $\frac{1}{4} \frac{S4}{S9}$ 1963</p>	
42.20	Wash in bottom of canyon, 20 lks. wide, 2 ft. deep, drains S.; asc. broken SE. slope.	
54.50	Rim of mesa, bears SE. and NW.; desc. nearly vertical SW. slope.	
65.50	Begin desc. over steep SW. slope.	
80.50	The cor. of secs. 4, 5, 8 and 9.	
	<p>Land, steep slopes and ledges. Soil, rocky. Timber, scattered pinon and cedar. Undergrowth, scrub oak and cacti.</p>	

BOOK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona 45.

CHAINS	
	N. 0°02' W., bet. secs. 4 and 5.
	Over mountainous land; asc. steep SW. slope.
26.00	Ridge, bears S. 80° E. and NW. 5.00 chs., then W.; descend N. slope.
40.00	Point for the ¼ sec. cor. of secs. 4 and 5 falls on the S. edge of a wash.
	Set the iron post 10 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.
	T4SR24E ¼ S 5 S 4 1963
40.10	Wash, 20 lks. wide, 1 ft. deep, drains N. 75° W.; asc. steep SW. slope.
58.00	Spur, slopes S. 10° E. and S. 30° W.; asc. along W. slope.
62.20	Small wash, drains S. 35° W.; asc. SW. slope.
77.72	Intersect the N. bdy. of the township.
	Point for the C.C. of secs. 4 and 5.
	At the cor. point
	Set the iron post 6 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.
	T3S <hr style="width: 50px; margin: auto;"/> S 5 S 4 CC T4SR24E 1963
	From this cor. the original cor. of secs. 4, 5, 32 and 33, monumented by an iron post as described in the official record, bears West, 0.77 chs. dist. This cor. now functions for secs. 32 and 33 only and is remarked to show
	T3SR24E S32 S33 T4S 63 1955
	Land, mountainous. Soil, rocky. Timber, scattered pinon and cedar. Undergrowth, scattered creosote, scrub oak and cacti.
	The point for the N. ¼ sec. cor. of sec. 4 is at mid-point between the CCs.
	At the cor. point

ECCOCK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona

46.

46

CHAINS

Set the iron post over an X chiseled on solid rock, mound of stone to top, 4 ft. base, cap mkd.

T3S

$\frac{1}{2}$ S 4
T4SR24E
1963

From this cor. the original $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented by an iron post as described in the official record, bears N. 89°52' W., 1.13 chs. dist. This cor. now functions for sec. 33 only and is remarked to show

T3SR24E
 $\frac{1}{2}$ S33
T4S
63
1955

From the cor. of secs. 29, 30, 31 and 32.

West on a ~~sectional correction~~ line bet. secs. 30 and 31.

Over rolling land.

- 5.20 Spur, slopes SW.
 - 13.10 Wash, 10 lks. wide, 2 ft. deep, drains S.
 - 18.30 Spur, slopes SW.
 - 38.80 Wash, 300 lks. wide, 2 ft. deep, drains SW.
 - 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31 falls W. side of wash bottom.
- Set the iron post 20 ins. in the ground in a collar of stone, cap mkd.

T4SR24E
 $\frac{1}{2}$ $\frac{S\ 30}{S\ 31}$
1963

Build a mound of stone to the N., 3 ft. high, 3 $\frac{1}{2}$ ft. base.

- 53.50 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 71.40 Wash, 15 lks. wide, 1 ft. deep, drains SW.
- 78.24 Intersect the W. bdy. of the township.

Point for the C.C. of secs. 30 and 31.

At the cor. point

Set the iron post 10 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.

CHAINS

T4S
S30 C
S31 C
R24E
1963

From this cor. the cor. of secs. 25 and 36, T4S, R23E, previously described, bears N. 0°07' W., 0.58 chs. dist.

Land, rolling.
Soil, rocky clay.
Timber, none.
Undergrowth, scattered creosote brush and cacti.

The point for the W. ¼ sec. cor. of sec. 31 is on the W. bdy. of the township at 40.00 chs. in southing from the closing corner of secs. 30 and 31.

At the cor. point

Set the iron post 12 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

T4S
R24E
¼
S31
1963

From this cor. the ¼ sec. cor. of sec. 36, T4S, R23E, previously described, bears N. 0°19' E., 0.81 chs. dist.

From the cor. of secs. 29, 30, 31 and 32.

N. 0°02' W., bet. secs. 29 and 30.

Over rolling land.

32.40 Wash, 100 lks. wide, 2 ft. deep, drains W.

37.00 Wash, 20 lks. wide, 1 ft. deep, drains S. 40° W.; asc. S. slope.

40.00 Point for the ¼ sec. cor. of secs. 29 and 30.

Set the iron post 24 ins. in the ground, cap mkd.

T4SR24E
¼
S30|S29
1963

Build a mound of stone to the W., 2½ ft. high, 2 ft. base.

41.10 Low spur, slopes SW.

52.50 Wash, 10 lks. wide with 4-ft. banks, drains W. 1.50 chs., then S.

56.90 Spur, slopes S. 30° W.

BOOK 4705

48

Completion Survey, Subdivision, T4S, R24E, Arizona

48.

CHAINS	
65.70	Small draw, drains S. 30° W.
73.00	Spur, slopes S. 30° W.
79.90	Wash, 40 lks. wide, 1 ft. deep, drains S. 75° W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set the iron post 20 ins. in the ground in a collar of stone, cap mkd.
	T4SR24E <u>S19 S20</u> <u>S30 S29</u> 1963
	Build a mound of stone to the W., 3 ft. high, 3 ft. base.
	Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, scattered creosote brush, catclaw and cacti.
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°59' W., bet. secs. 20 and 29.
	Over rolling land.
3.20	Spur, slopes S. 30° W.
18.10	Wash, 30 lks. wide, 1 ft. deep, drains S. 35° W.
21.80	Spur, slopes S.
31.10	Wash, 40 lks. wide, 2 ft. deep, drains S. 20° W.
36.50	Wash in George Canyon, 50 lks. wide, 2 ft. deep, drains S. 10° W.
40.01	Point for the ¼ sec. cor. of secs. 20 and 29.
	Set the iron post 20 ins. in the ground in a collar of stone, cap mkd.
	T4SR24E ¼ <u>S 20</u> S 29 1963
	Build a mound of stone to the N., 2½ ft. high, 2 ft. base.
40.90	Spur, slopes S. 33° W.
45.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.
65.50	Wash, 50 lks. wide, 1 ft. deep, drains SW.
80.02	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, scattered creosote brush, catclaw and cacti.

CHAINS	
	<p>N. 89°44' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
11.80	Wash, 40 lks. wide, 2 ft. deep, drains S. 20° E.
13.80	Jeep road, bears N. 5° E. and SW.
18.20	Jeep road, bears N. and S.
29.00	Wash, 10 lks. wide, 1 ft. deep, drains SW.
37.80	Spur, slopes S.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30 falls on a W. slope.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4SR24E</p> <p>$\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$</p> <p>1963</p> </div>
42.20	Wash, 10 lks. wide, 1 ft. deep, drains S.
45.00	Spur, slopes S.
56.80	Wash, 30 lks. wide, 1 ft. deep, drains S. 10° E.
64.50	Wash, 10 lks. wide, 1 ft. deep, drains S.
78.32	<p>The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.</p> <hr/> <p>The point for the W. $\frac{1}{4}$ sec. cor. of sec. 30 is on the W. bdy. of the township and at mid-point between the CC for secs. 30 and 31 and the cor. of secs. 19, 24, 25 and 30.</p> <p>At the cor. point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4S</p> <p>R23E R24E</p> <p> $\frac{1}{4}$</p> <p> S30</p> <p>1963</p> </div> <p>From this cor. the $\frac{1}{4}$ sec. cor. of sec. 25, T4S, R23E, previously described, bears N. 0°05' W., 0.33 chs. dist.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°02' W., bet. secs. 19 and 20.</p>

CHAINS	
	Over rolling land.
2.20	Small wash, drains S. 40° W.
8.00	Wash, 20 lks. wide, 1 ft. deep, drains S. 25° W.
40.00	Point for the ¼ sec. cor. of secs. 19 and 20. Set the iron post 24 ins. in the ground, cap mkd. T4SR24E ½ S19 S20 1963 from which A dry, abandoned well bears N. 77°25' E., 6.04 chs. dist. Build a mound of stone to the W., 3 ft. high, 3 ft. base.
44.20	Wash, 80 lks. wide, 1 ft. deep, drains S. 30° W.
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set the iron post 18 ins. in the ground, mound of stone to top, 2½ ft. base, cap mkd. T4SR24E S18 S17 S19 S20 1963 Land, rolling. Soil, gravelly clay. Timber, none. Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over rolling land.
7.30	E. bank of wash area.
9.80	Center of wash area in George Canyon, drains S. 5° W. from NE.
12.30	W. bank of wash area; asc. over rolling E. slope.
21.00	Ridge, bears NE. and SW.
25.70	Wash, 20 lks. wide, 1 ft. deep, drains S. 2.00 chs., then SW.
27.30	Jeep road, bears N. 20° E. and S. 70° W.
38.50	Same jeep road, bears SE. and NW.
39.95	Point for the ¼ sec. cor. of secs. 17 and 20. Set the iron post 6 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

CHAINS		
	T4SR24E $\frac{1}{4} \frac{S 17}{S 20}$ 1963	
41.70	Wash, 20 lks. wide, 1 ft. deep, drains S. 3.00 chs., then SW.	
46.10	Same jeep road, bears N. and S.	
51.50	Wash, 40 lks. wide, 2 ft. deep, drains S.	
60.50	Draw, drains S.	
65.90	Spur, slopes S.	
72.80	Wash, 30 lks. wide, 1 ft. deep, drains S. 15° W.; asc. E. slope.	
79.00	Ridge, bears N. and S.; desc. W. slope.	
79.90	The cor. of secs. 17, 18, 19 and 20.	
	Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush, catclaw and cacti.	
	West, bet. secs. 18 and 19.	
	Over rolling land.	
3.80	Draw, drains S.	
9.20	Ridge, bears S. 15° E. and N.	
16.50	E. bank of wash area, bears N. and S.	
20.80	W. bank of same wash, bears N. and S.	
25.50	Jeep road on top of ridge, bears N. and S.	
32.40	Ravine, drains S. 15° W.	
36.70	Spur, slopes S. 20° W.	
39.70	Head of small draw, drains S.; asc. E. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.	
	Set the iron post 12 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.	
	T4SR24E $\frac{1}{4} \frac{S 18}{S 19}$ 1963	
43.70	Ridge, bears NE. and SW.	
50.80	Wash, 30 lks. wide, 1 ft. deep, drains irregularly W.	
56.90	Same wash, drains SW.; asc. SE. slope.	

CHAINS		
60.50	Wash, 10 lks. wide, 6 ins. deep, drains S. 10° W.	
78.34	<p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.</p>	
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°02' W., bet. secs. 17 and 18.</p> <p>Over high rolling land.</p>	
9.90	Spur, slopes SW.	
35.90	Wash, 10 lks. wide, 6 ins. deep, drains S. 30° W.; asc. SE. slope.	
40.00	<p>Point for the ¼ sec. cor. of secs. 17 and 18.</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, cap mkd.</p>	
	<p>T4SR24E ¼ S18 S17 1963</p>	
	Build a mound of stone to the W., 3½ ft. high, 3½ ft. base.	
44.10	High spur, slopes SW.; desc. NW. slope.	
52.50	Wash, 80 lks. wide, 2 ft. deep, drains SW.	
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18 falls on the S. side of a wash.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.</p>	
	<p>T4SR24E S7 S8 S18 S17 1963</p>	
	<p>Land, high rolling hills. Soil, rocky clay. Timber, none. Undergrowth, scattered creosote brush and cacti.</p>	
	From the cor. of secs. 8, 9, 16 and 17.	
	N. 89°57' W., bet. secs. 8 and 17.	
	Over steep and broken mountainous land.	
13.50	Spur, slopes S.	

BOOK 4705

Completion Survey, Subdivision, T4S, R24E, Arizona 53.

CHAINS	
20.70	Spur, slopes S.
31.70	Rocky spur, slopes S. 25° W.; desc. steep W. slope.
39.92	Point for the ¼ sec. cor. of secs. 8 and 17 falls on a W. slope.
	Set the iron post 10 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.
	T4SR24E $\frac{1}{4} \begin{array}{l} S \ 8 \\ S \ 17 \end{array}$ 1963
48.60	Wash, 25 lks. wide, 1 ft. deep, drains S. 10° E.
62.00	Rocky spur, slopes SW.
65.90	Wash, 25 lks. wide, 1 ft. deep, drains S.
74.50	Ridge, bears N. and S. 25° W.
79.84	The cor. of secs. 7, 8, 17 and 18.
	Land, broken E ½ mile, rolling W ½ mile. Soil, rocky. Timber, scattered palo verde. Undergrowth, scattered cacti.
	S. 89°43' W., bet. secs. 7 and 18.
	Over rolling land.
.30	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
7.60	Draw, drains S.
9.90	Spur, slopes S.
14.30	Wash, 10 lks. wide, 1 ft. deep, drains S. 55° E.
15.00	Jeep road, bears N. and S.
16.20	Spur, slopes S. 40° E.
21.10	Wash, 15 lks. wide, 2 ft. deep, drains S. 35° E.
26.30	Spur, slopes S. 15° W.
35.20	Ridge, bears N. and SW.
39.30	Wash, 10 lks. wide, 2 ft. deep, drains SW.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18 falls on E. slope.
	Set the iron post 4 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.
	T4SR24E $\frac{1}{4} \begin{array}{l} S \ 7 \\ S \ 18 \end{array}$ 1963

CHAINS	
57.20	Wash in Box Canyon, 100 lks. wide, 2 ft. deep, drains SW.
71.50	Low ridge, bears N. 35° E. and S. 35° W.
78.50	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township, monumented by an iron post as described in the official record. Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°02' W., bet. secs. 7 and 8.
	Over broken and rolling land.
.10	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.; asc. steep and rocky SE. slope.
26.10	Saddle of a rocky ridge, bears NE. and SW.; asc. steep and rocky SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 7 and 8. Set the iron post on an X chiseled on solid rock, mound of stone to top, 4½ ft. base, cap mkd. T4SR24E ¼ S 7 S 8 1963 Asc. along E. slope.
53.50	Begin desc. over steep NE. slope.
69.50	Begin desc. over steep N. slope.
74.00	Rocky wash, 30 lks. wide, 1 ft. deep, drains NW. 4.00 chs., then S. 70° W.; asc. along steep W. slope.
80.00	Point for the cor. of secs. 5, 6, 7 and 8 falls on the S. side of a low spur, sloping SW. Set the iron post 6 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd. T4SR24E S 6 S 5 S 7 S 8 1963 Land, mountainous. Soil, rocky. Timber, scattered palo verde and cedar. Undergrowth, scattered creosote brush, catclaw and cacti.
	From the cor. of secs. 4, 5, 8 and 9.
	N. 89°59' W., bet. secs. 5 and 8.

CHAINS	
	Over broken, mountainous land.
9.00	Begin desc. over steep SW. slope.
22.30	Wash, 30 lks. wide, 1 ft. deep, drains SE.
27.00	Spur, slopes S. from NW.; desc. steep SW. slope.
39.74	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 5 and 8. Set the iron post 6 ins. in the ground, mound of stone to top, $3\frac{1}{2}$ ft. base, cap mkd. <div style="text-align: center;"> T4SR24E $\frac{1}{4}$ $\begin{matrix} \leftarrow S & 5 \\ S & 8 \end{matrix}$ WC 1963 </div>
39.94	True point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8 falls on ledgy ground and cannot be perpetuated.
42.80	Wash, 10 lks. wide, 1 ft. deep, drains S.
47.00	Low spur, slopes S.; desc. W. slope.
47.20	Wash, 20 lks. wide, 2 ft. deep, drains S. 10° E.; asc. steep E. slope.
64.00	Ridge, bears N. 25° E. and S. 25° W.; desc. steep W. slope.
79.88	The cor. of secs. 5, 6, 7 and 8. Land, mountainous. Soil, rocky. Timber, scattered palo verde and cedar. Undergrowth, scrub oak, catclaw and cacti.
	West, on a sectional correction line bet. secs. 6 and 7. Over low mountainous land. Desc. steep W. slope.
8.00	Wash, 20 lks. wide, 1 ft. deep, drains S. 15° W.; asc. steep SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7 falls on top of a high ridge. Set the iron post 6 ins. in the ground, mound of stone to top, $3\frac{1}{2}$ ft. base, cap mkd. <div style="text-align: center;"> T4SR24E $\frac{1}{4}$ $\begin{matrix} S & 6 \\ S & 7 \end{matrix}$ 1963 </div>
40.40	Ridge, bears N. and S. 5.00 chs., then S. 25° E.; desc. over steep SW. slope.
62.00	Wash, 20 lks. wide, 1 ft. deep, drains SW.; asc. SE. slope.

CHAINS

67.00 Spur, slopes S. 10° W.; desc. over steep SW. slope.

75.00 Wash, 45 lks. wide, 2 ft. deep, drains S.; asc. E. slope.

78.63 Intersect the W. bdy. of the township.

Point for the C.C. of secs. 6 and 7.

At the cor. point

Set the iron post 6 ins. in the ground, mound of stone to top, 3½ ft. base, cap mkd.

$$\begin{array}{r|l} \text{T4S} & \\ \text{R24E} & \\ \hline \text{S 1} & \frac{\text{S 6}}{\text{S 7}} \text{ C} \\ \hline & \text{1963} \end{array}$$

From this cor. the cor. of secs. 1, 6, 7 and 12, monumented by an iron post as described in the official record, bears S. 0°08' E., 0.58 chs. dist. This cor. now functions for secs. 1 and 12 only, and is remarked to show

$$\begin{array}{r} \text{T4S} \\ \text{R23E R24E} \\ \hline \text{S 1} \\ \hline \text{S 12} \end{array} \left| \begin{array}{l} \\ \\ \\ \text{S 7} \end{array} \right.$$

63
1958

Land, mountainous.
Soil, rocky.
Timber, scattered cedar.
Undergrowth, scattered creosote brush, morman tea and cacti.

The point for the W. ¼ sec. cor. of sec. 7 is at mid-point bet. the C.C. of secs. 6 and 7 and the cor. of secs. 7, 12, 13 and 18.

At the cor. point

Set the iron post 7 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.

$$\begin{array}{r} \text{T4S} \\ \text{R23E R24E} \\ \hline \frac{1}{4} \\ \hline \text{S 7} \\ \hline \text{1963} \end{array}$$

From this cor. the ¼ sec. cor. of secs. 7 and 12, monumented by an iron post as described in the official record, bears S. 0°05' E., 0.21 chs. dist. This cor. now functions for sec. 12 only and is remarked to show

$$\begin{array}{r} \text{T4S} \\ \text{R23E R24E} \\ \hline \frac{1}{4} \\ \hline \text{S 12} \\ \hline \text{63} \\ \hline \text{1958} \end{array}$$

BOOK 4705
Completion Survey, Subdivision, T4S, R24E, Arizona 57.

CHAINS	
	<p>The point for the W. $\frac{1}{4}$ sec. cor. of sec. 6 is at 40.00 chs. in northing from the C.C. of secs. 6 and 7, and on the W. bdy. of the township.</p> <p>At the cor. point</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4S $\frac{1}{4}$ S 6 R24E 1963</p> </div> <p>From this cor. the $\frac{1}{4}$ sec. cor. of sec. 1, previously described, bears S. $0^{\circ}04'$ E., 1.04 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. $0^{\circ}02'$ W., bet. secs. 5 and 6.</p> <p>Over mountainous land.</p>
2.00	Low spur, slopes SW.
4.20	Wash, 10 lks. wide, 1 ft. deep, drains W.; thence over several small spurs sloping S.
20.00	Wash, 100 lks. wide, with 3 ft. banks, drains SW.; asc. steep SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6 falls on a S. slope.
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, $3\frac{1}{2}$ ft. base, cap mkd.</p> <div style="text-align: center;"> <p>T4SR24E $\frac{1}{4}$ S 6 S 5 1963</p> </div>
45.60	Ridge, bears S. 75° E. and N. 75° W.; desc. steep N. slope.
51.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 75° W.; asc. steep S. slope.
59.00	Ridge, bears S. 70° E. and N. 75° W.; desc. steep NE. slope.
70.70	Left bank of wash, 3 ft. high, bears SE. and NW.
71.80	Right bank of same wash, 3 ft. high, bears SE. and NW.
78.00	Intersect the N. bdy. of the township.
	<p>Point for the C.C. of secs. 5 and 6.</p> <p>At the cor. point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.</p>

CHAINS

T3SR24E

S 6 | S 5
CC
T4S
1963

From this cor. the cor. of secs. 5, 6, 31 and 32, Ts3&4, R24E, monumented by an iron post as described in the official record, bears N. 89°48' W., 1.01 chs. dist. This cor. now functions for secs. 31 and 32 only and is remarked to show

T3SR24E
S31 | S32
T4S
63
1955

Land, mountainous.
Soil, rocky.
Timber, scattered pinon and cedar.
Undergrowth, scattered creosote brush and cacti.

The point for the N. ¼ sec. cor. of sec. 5 is on the N. bdy. of the township at mid-point between the CCs.

At the cor. point

Set the iron post 5 ins. in the ground, mound of stone to top, 4 ft. base, cap mkd.

T3SR24E
¼ S 5
T4S
1963

From this cor. the original ¼ sec. cor. of secs. 5 and 32, on the N. bdy. of the township, monumented by an iron post as described in the official record, bears N. 89°49' W., 0.96 chs. dist. This cor. now functions for sec. 32 only and is remarked to show

T3SR24E
¼ S 32
T4S
63
1955

The point for the N. ¼ sec. cor. of sec. 6 is on the N. bdy. of the township at 40.00 chs. in westing from the C.C. of secs. 5 and 6.

At the cor. point

Set the iron post 6 ins. in the ground, mound of stone to top, 3 ft. base, cap mkd.

T3S
¼ S 6
T4SR24E
1963

CHAINS

From this cor. the original $\frac{1}{4}$ sec. cor. of secs. 6 and 31, on the N. bdy. of the township, monumented by an iron post as described in the official record, bears N. $89^{\circ}43'$ W., 0.92 chs. dist. This cor. now functions for sec. 31 only and is remarked to show

T3SR24E
 $\frac{1}{4}$ S31

T4S
63
1955

General Description

The general elevation of the township is from about 2850 feet in the southwest corner to a high point of 6100 on the north boundary. The southwest three quarters is rolling land and the northeast one quarter consists of high mountain land. The soil is rocky and gravelly clay. The southwest portion drains to the southwest and the northeast portion drains to the east. Both drainages eventually find their way into the Gila River. There is a scattered growth of palo verde trees along the wash areas in the southwest portion and the higher northeast portion has a scattered to medium growth of cedar and pinon trees. The whole township is utilized for grazing, although the higher land has more grass than the lower portions.

61

BOOK 4705
CERTIFICATE OF SURVEY

I, Paul G. Bauer, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 12 day of August, 1959,
I have dependently resurveyed a portion of the west boundary of Township 4
South, Range 25 East, dependently resurveyed the south boundary and
portions of the west boundary and subdivisional lines, and made a
completion survey of the east boundary and subdivisional lines of
Township 4 South, Range 24 East
of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

April 3, 1963
(Date)

Paul G. Bauer
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL
Bureau of Land Management

The foregoing field notes of the dependent resurvey of a portion of the west
boundary of Township 4 South, Range 25 East, dependent resurvey of the
south boundary and portions of the west boundary and subdivisional lines,
and completion survey of the east boundary and subdivisional lines of
Township 4 South, Range 24 East, of the Gila and Salt River Meridian,
Arizona,

executed by Paul G. Bauer, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.
Washington, D.C.

AUG 31 1964
(Date)

E. Pennington
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)