

Form 4-679  
(January 1963)

BOOK 4710  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of

REMONUMENTATION

in

Township 25 North, Range 4 East

Of the Gila & Salt River Meridian,

In the State of Arizona.

### EXECUTED BY

Lester S. Mann, Cadastral Surveyor

Under special instructions dated June 22, 19 64, which provided for the surveys included under Group Number 417, approved June 22, 1964, and assignment instructions dated June 22, 19 64.

Survey commenced July 21, 19 64

Survey completed September 4, 19 64

1A

BOOK 4710

# INDEX DIAGRAM

Township 25 North, Range 4 East

6	5	5	4	4	3	3	2	2	1	1
6		8		4		8		2		1
									7	8
7		8		9		10		11	7	12
									6	7
18		17		16		15		14		13
19		20		21		22		23		24
					9	9	8			
30		29		28	10	27	12	26		25
					10	11	11			
31		32		33		34		35		36

BOOK 4710

Township 25 North, Range 4 East  
Gila & Salt River Meridian, Arizona

18

CHAINS

The north boundary and the subdivisional lines were surveyed in 1903 by M. Caudle. The west boundary was surveyed in 1902 by Caudle and Caudle. The south boundary was surveyed in 1883 by A. E. Shoemaker, resurveyed in 1894 by Oury Perkins and again resurveyed in 1903 by M. Caudle. The east boundary was surveyed in 1894 by Oury Perkins, resurveyed in 1903 by M. Caudle and again resurveyed in 1944-1945 by White-Warner-Wakeman.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 22, 1964 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54, dated April 21, 1954.

The assistants furnished by the Forest Service, remonumented the original corner positions after verification. An open site Dietzen compass was used to obtain the bearings and a standard steel tape was used to measure the distances.

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, Ts. 25 and 26 N., R. 4 E., is monumented by a malpais stone, 6 X 10 X 14 ins., firmly set in a collar of stones, mkd. with  $\frac{1}{4}$  on the N., from which the original bearing trees

A juniper, 14 ins. diam., bears N. 54° E., 41 lks. dist., mkd.  $\frac{1}{4}$ S36BT

A juniper, 12 ins. diam., bears S. 59° E., 75 lks. dist., mkd.  $\frac{1}{4}$ S1BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T26NR4E

$\frac{1}{4}$  S36  
S I

T25N

1964

from which

A pinon, 16 ins. diam., bears S. 20° E., 193 lks. dist., mkd.  $\frac{1}{4}$ S1BT

A pinon, 16 ins. diam., bears N. 65° W., 134 lks. dist., mkd.  $\frac{1}{4}$ S36BT

Bury the original corner stone alongside the iron post.

Cor. is on a gentle E. slope, in an E. and W. fence.

The cor. of secs. 1, 2, 35 and 36, Ts. 25 and 26 N., R. 4 E., is monumented by a malpais stone, 10 X 14 X 20 ins., firmly set, mkd. with 1 notch on the E. and 5 notches on the W., from which the original bearing trees

A pinon, 14 ins. diam., bears N. 50° E., 197 lks. dist., mkd. with an over grown blaze.

CHAINS

A juniper, 12 ins. diam, bears S. 85° E., 116 lks.  
mkd. T25NR4ES1BT

A pinon, 8 ins. diam., bears S. 61° W., 213 lks.  
dist., mkd. with an overgrown blaze.

A pinon, 16 ins. diam., bears N. 51° W., 106 lks.  
dist., mkd. with faint scribe marks.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins.  
in the ground, with a collar of stones to the top, with  
brass cap mkd.

T26NR4E	
S35	S36
S 2	S 1
T25N	
1964	

from which

A juniper, 7 ins. diam., bears N. 56° E., 177 lks.  
dist., mkd. T26NR4ES36BT

A pinon, 6 ins. diam., bears S. 66° W., 105 lks.  
dist., mkd. T25NR4ES2BT

A pinon, 12 ins. diam., bears N. 84° W., 120 lks.  
dist., mkd. T26NR4ES35BT

Bury the original corner stone alongside the iron post.

Cor. is on a gentle E. slope in an E. and W. fence.

The ¼ sec. cor. of secs. 2 and 35, Ts. 25 and 26 N., R.  
4 E., is monumented by a malpais stone, 10 X 14 X 16 ins.,  
firmly set, mkd. ¼ on the N., from which the remains of  
an original bearing tree

A pinon, 20 ins. diam., bears S. 76° E., 145 lks.  
dist., blaze almost grown over with parts of scribe  
marks visible.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.  
in the ground, with brass cap mkd.

T26NR4E	
¼ S35	
¼ S 2	
T25N	
1964	

from which

A juniper, 12 ins. diam., bears S. 34° E., 171 lks.  
dist., mkd. ¼S2BT

Raise a mound of stones to the N. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is in almost level area and in an E. and W. fence.

The cor. of secs. 2, 3, 34 and 35, Ts. 25 and 26 N., R.  
4 E., is monumented by a malpais stone, 12 X 14 X 18 ins.  
firmly set, mkd. with 2 notches on the E. and 4 notches  
and the W.

BOOK 4710

Township 25 North, Range 4 East, Arizona

3.

CHAINS

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T26NR4E  
 $\frac{S34}{S3}$  |  $\frac{S35}{S2}$   
 T25N  
 1964

No original bearing trees given and no new bearing trees are available.

Bury the original corner stone alongside the iron post.

Cor. is in a level area at a fence corner from which fences bear N., E. and W.

The cor. of secs. 3, 4, 33 and 34, Ts. 25 and 26 N., R. 4 E., is monumented by a malpais stone, 10 X 12 X 14 ins. firmly set, mkd. with 3 notches on the E. and W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T26NR4E  
 $\frac{S33}{S4}$  |  $\frac{S34}{S3}$   
 T25N  
 1964

from which

A juniper, 6 ins. diam., bears S.  $76^\circ$  E., 120 lks. mkd. T25NR4ES3BT

A pinon, 5 ins. diam., bears S.  $26^\circ$  W., 181 lks. dist., mkd BT

Bury the original corner stone alongside the iron post.

Cor. is in nearly level area and in an E. and W. fence.

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, Ts. 25 and 26 N., R. 4 E., is monumented by a malpais stone, 8 X 10 X 14 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., with a mound of stones to the N.

At the cor. point.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T26NR4E  
 $\frac{1}{4} \frac{S33}{S4}$   
 T25N  
 1964

from which .

A pinon, 18 ins. diam., bears S.  $33^\circ$  E., 148 lks. dist., mkd.  $\frac{1}{4}$ S4BT

A pinon, 18 ins. diam., bears N.  $61^\circ$  E., 142 lks. dist., mkd.  $\frac{1}{4}$ S33BT

Bury the original corner stone alongside the iron post.

CHAINS

Cor. is in a nearly level area and in an E. and W. fence.

The cor. of secs. 4, 5, 32 and 33, Ts. 25 and 26 N., R. 4 E., is monumented by a sandstone, 5 X 15 X 18 ins., firmly set, mkd. with 4 notches on the E. and 2 notches on the W., from which the remains of the original bearing trees

A juniper, 16 ins. diam., bears N. 56° E., 18 lks. dist., mkd. with an over grown blaze.

A juniper, 12 ins. diam., bears S. 78° E., 125 lks. dist., mkd. with faint scribe marks.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, with a collar of stone to the top, with brass cap mkd.

T26NR4E  
 S32 | S33  
 S 5 | S 4  
 T25N  
 1964

from which

A pinon, 10 ins. diam., bears N. 14° E., 106 lks. dist., mkd. T26NR4ES33BT

A juniper, 18 ins. diam., bears S. 55° E., 145 lks. dist., mkd. T25NR4ES4BT

A pinon, 6 ins. diam., bears S. 71° W., 124 lks. dist., mkd. S5BT

A pinon, 14 ins. diam., bears N. 51° W., 258 lks. dist., mkd. T26NR4ES32BT

Bury the original corner stone alongside the iron post.

Cor. is in almost level area about 8 chs. S. of Arizona State Highway 180 and in an E. and W. fence.

The ¼ sec. cor. of secs. 5 and 32, Ts. 25 and 26 N., R. 4 E., is monumented by a malpais stone, 8 X 10 X 12 ins., firmly set, mkd. ¼ on the N., with a mound of stones to the W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26NR4E  
 ¼ S32  
 S 5  
 T25N  
 1964

from which

A juniper, 8 ins. diam., bears N. 1° W., 126 lks. dist., mkd. ¼S32BT

A pinon, 5 ins. diam., bears S. 56° E., 163 lks. dist., mkd. BT

Bury the original corner stones alongside the iron post.

Cor. is on a gentle E. slope in an E. and W. fence.

17001 4710

Township 25 North, Range 4 East, Arizona

5.

CHAINS

The cor. of secs. 5, 6, 31 and 32, Ts. 25 and 26 N., R. 4 E., is monumented by a malpais stone, firmly set, mkd. with 5 notches on the E. and 1 notch on the W., 8 X 12 X 14 ins., from which the remains of the original bearing trees

A juniper, 6 ins. diam., bears S. 26° W., 124 lks. dist., mkd. on a limb T25NR4ES6BT

A juniper, 8 ins. diam., bears N. 70° W., 146 lks. dist., mkd. T26NR4ES3LBT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T26NR4E  
S31 | S32  
S 6 | S 5  
T25N  
1964

from which

A pinon, 12 ins. diam., bears N. 79° E., 128 lks. dist., mkd. T26NR4ES32BT

A juniper, 6 ins. diam., bears S. 31° W., 136 lks. dist., mkd. BT

A pinon, 14 ins. diam., bears N. 46° W., 139 lks. dist., mkd. T26NR4ES3LBT

Bury the original corner stone alongside the iron post.

Cor. is in nearly level area and in an E. and W. fence.

The ¼ sec. cor. of secs. 6 and 31, Ts. 25 and 26 N., R. 4 E., is monumented by a limestone, 6 X 10 X 18 ins., firmly set, mkd. ¼ on the N., from which the remains of the original bearing trees

A juniper, 16 ins. diam., bears N. 24° E., 91 lks. dist., mkd. ¼S36BT

A juniper, 16 ins. diam., bears S. 71° E., 101 lks. dist., mkd. with an over grown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T26NR4E  
¼ S31  
S 6  
T25N  
1964

from which

A pinon, 8 ins. diam., bears N. 77° E., 60 lks. dist., mkd. ¼S31BT

A juniper, 16 ins. diam., bears S. 71° E., 101 lks. dist., mkd. BT (Remarked original bearing tree)

Bury the original corner stone alongside the iron post.

Cor. is in a level area and in an E. and W. fence.

CHAINS

The cor. of secs. 1, 6, 31 and 36, Ts. 25 and 26 N., Rs. 3 and 4 E., is monumented by a sandstone, 6 X 10 X 20 ins., firmly set, mkd. with 6 notches on the N., S., E. and W., from which the remains of the original bearing trees

A juniper, 14 ins. diam., bears N. 52° E., 318 lks. dist., mkd. with an over grown blaze.

A juniper, 12 ins. diam., bears S. 32° E. 45 lks. dist., mkd. T25NR4ES6BT.

A pinon, 12 ins. diam., bears S. 32° W., 78 lks. dist., mkd. with an over grown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T26N
R3E R4E
S36   S31
S 1   S 6
T25N
1964

from which

A juniper, 14 ins. diam., bears N. 76° E., 176 lks. dist., mkd. T26NR4ES31BT

A pinon, 14 ins. diam., bears S. 3° E., 108 lks. dist., mkd. T25NR4ES6BT

A pinon, 8 ins. diam., bears S. 54° W., 124 lks. dist., mkd. T25NR3ES1BT

A juniper, 12 ins. diam., bears N. 27° W., 42 lks. dist., mkd. T26NR3ES36BT

Bury the original corner stone alongside the iron post.

Cor. is in nearly level area at a fence corner from which fences bear E., W. and S.

The cor. of secs. 11, 12, 13 and 14, is monumented by a malpais stone, 6 X 12 X 18 ins., firmly set, mkd. with 4 notches on the S. and 1 notch on the E., from which the remaining bearing trees

A pinon, 12 ins. diam., bears N. 2° E., 147 lks. dist., mkd. T25NR4ES12BT

A pinon, 14 ins. diam., bears S. 57° W., 268 lks. dist., mkd. T25NR4ES14BT

A pinon, 16 ins. diam., bears N. 42° W., 103 lks. dist., mkd. T25NR4ES11BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E
S11   S12
S14   S13
1964

from which

A pinon, 12 ins. diam., bears N. 37° W., 114 lks. dist., mkd. T25NR4ES11BT



CHAINS

A pinon, 6 ins. diam., bears N. 51° E., 119 lks.  
dist., mkd. S12BT

A juniper, 14 ins. diam., bears S. 30° E., 110 lks.  
dist., mkd. T25NR4ES13BT

A pinon, 8 ins. diam., bears S. 38° W., 136 lks.  
dist., mkd. S14BT

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, is monumented by a malpais stone, 10 X 14 X 20 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., from which the original bearing trees

A pinon, 16 ins. diam., bears N. 6° W., 114 lks.  
dist., mkd.  $\frac{1}{4}$ S12BT

A pinon, 16 ins. diam., bears S. 38° W., 30 lks.  
dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T25NR4E

$\frac{1}{4}$  S12  
S13

from which

1964

A juniper, 16 ins. diam., bears S. 80° E., 52 lks.  
dist., mkd.  $\frac{1}{4}$ S13BT

A pinon, 12 ins. diam., bears N. 19° E., 147 lks.  
dist., mkd.  $\frac{1}{4}$ S12BT

Cor. is on a steep N. slope in pinon and juniper trees.

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, is monumented by a malpais stone, loosely set in a collar of stones, mkd.  $\frac{1}{4}$  on the W., with a mound of stones to the W., from which the remains of the original bearing trees

A pinon, 10 ins. diam., bears N. 53° E., 104 lks.  
dist., tree is dead and has fallen, mkd.  $\frac{1}{4}$ S12BT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T25NR4E

$\frac{1}{4}$  S11  
S12

from which

1964

A juniper, 16 ins. diam., bears S. 41° E., 89 lks.  
dist., mkd.  $\frac{1}{4}$ S12BT

A pinon, 4 ins. diam., bears S. 71° W., 30 lks.  
dist., mkd. BT

Build a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

The cor. of secs. 1, 2, 11 and 12, is monumented by a malpais stone, 6 X 10 X 18 ins., firmly set, mkd. with 5 notches on the S. and 1 notch on the E., from which the original bearing trees

A pinon, 16 ins. diam., bears N. 72° E., 175 lks.  
dist., mkd. with an over grown blaze.

CHAINS

A juniper, 8 ins. diam., bears S. 71° E., 57 lks. dist., mkd. T25NR4ES12BT

A pinon, 16 ins. diam., bears S. 41° W., 223 lks. dist., mkd. T25NR4ES11BT

A pinon, 14 ins. diam., bears N. 71° W., 141 lks. dist., mkd. T25NR4ES2BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25NR4E  
S 2 | S 1  
S11 | S12

from which

1964

A juniper, 12 ins. diam., bears N. 55° E., 188 lks. dist., mkd. S1BT

A juniper, 6 ins. diam., bears S. 13° E., 96 lks. dist., mkd. S12BT

A pinon, 14 ins. diam., bears S. 88° W., 136 lks. dist., mkd. T25NR4ES11BT

A juniper, 10 ins. diam., bears N. 26° W., 136 lks. dist., mkd. T25NR4ES2BT

Bury the original corner stone alongside the iron post.

Cor. is about 10 chs. S. of State Hwy. 180.

The ¼ sec. cor. of secs. 1 and 12, is monumented by a malpais stone, 10 X 10 X 26 ins., firmly set in a collar of stones, mkd. ¼ on the N., from which the remains of the original bearing trees

A pinon, 18 ins. diam., bears N. 82° E., 115 lks. dist., tree is dead and fallen, parts of the scribe marks are visible.

A pinon, 14 ins. diam., bears S. 64° E., 86 lks. dist., tree is dead and fallen, no marks found.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E  
¼ S 1  
¼ S12

from which

1964

A pinon, 20 ins. diam., bears N. 82° E., 214 lks. dist., mkd. ¼S1BT

A pinon, 14 ins. diam., bears S. 24° E., 70 lks. dist., mkd. ¼S12BT

Bury the original corner stone alongside the iron post.

The cor. of secs. 22, 23, 26 and 27, is monumented by a malpais stone, firmly set, mkd. with 2 notches on the

CHAINS

S. and E., with a mound of stones to the W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E.  
S22|S23  
S27|S26  
1964

No original bearing trees given and no new bearing trees available.

Bury the original corner stone alongside the iron post.

Cor. is in open grass land.

The  $\frac{1}{4}$  sec. cor. of secs. 22 and 27, is monumented by a malpais stone, 10 X 12 X 16 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., with a small mound of stones to the N.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E  
 $\frac{1}{4}$  S22  
S27  
1964

No original bearing trees given and no new bearing trees available.

Bury the original corner stone alongside the iron post.

Cor. is in open grass land.

The cor. of secs. 21, 22, 27 and 28, is monumented by a malpais stone, 12 X 14 X 18 ins., firmly set, mkd. with 2 notches on the S. and 3 notches on the E., with a mound of stones to the W., from which the original bearing trees

A pinon, 14 ins. diam., bears N.  $55^\circ$  E., 159 lks. dist., mkd. T25NR4ES22BT

A pinon, 16 ins. diam., bears S.  $44^\circ$  E., 229 lks. dist., mkd. T25NR4ES27BT

A pinon, 16 ins. diam., bears N.  $21^\circ$  W., 195 lks. dist., mkd., T25NR4ES21BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T25NR4E  
S21|S22  
S28|S27  
1964

from which

CHAINS

A pinon, 8 ins. diam., bears N. 80° E., 153 lks.  
dist., mkd. T25NR4ES22BT

A pinon, 14 ins. diam., bears S. 89° E., 170 lks.  
dist., mkd. T25NR4ES27BT

A juniper, 12 ins. diam., bears N. 11° W., 255 lks.  
dist., mkd. T25NR4ES21BT

A pinon, 4 ins. diam., bears S. 34° W., 59 lks.  
dist., mkd. BT

Bury the original corner stone alongside the iron post.

Cor. is on a SW. slope.

The  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, is monumented by a malpais stone, 4 X 10 X 18 ins., firmly set, mkd. with  $\frac{1}{4}$  on the W., with a mound of stones to the W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E

$\frac{1}{4}$   
S28 | S27

from which

1964

A pine, 10 ins. diam., bears N. 81° E., 413 lks.  
dist., mkd.  $\frac{1}{4}$ S27BT

Bury the original corner stone alongside the iron post.

Cor. is in open grass land.

The cor. of secs. 27, 28, 33 and 34, is monumented by a malpais stone, 12 X 12 X 14 ins., firmly set, mkd. with 1 notch on the S. and 3 notches on the E., from which the remains of the original bearing trees

A juniper, .6 ins. diam., bears S. 7° W., 99 lks.  
dist., mkd. T25NR4ES33BT

A juniper, 16 ins. diam., bears N. 61° W., 33 lks.  
dist., mkd. T25NR4ES28BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E

S28 | S27  
S33 | S34

from which

1964

A juniper, 8 ins. diam., bears N. 55° E., 46 lks.  
dist., mkd. T25NR4ES27BT

A pinon, 8 ins. diam., bears S. 56° E., 134 lks.  
dist., mkd. S34BT

A juniper, 6 ins. diam., bears S. 19° W., 26 lks.  
dist., mkd. T25NR4ES33BT

CHAINS

A pinon, 4 ins. diam., bears N. 34° W., 22 lks.  
dist., mkd. BT

Build a mound of stones to the W. of the iron post.  
Bury the original corner stone alongside the iron post.  
Cor. is in a level area and among large trees.

The  $\frac{1}{4}$  sec. cor. of secs. 27 and 34, is monumented by a malpais stone, 8 X 10 X 14 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., from which the remains of the original bearing trees

A pinon, 8 ins. diam., bears N. 78° W., 282 lks.  
dist., tree has fallen and has faint scribe marks.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T25NR4E

$\frac{1}{4}$  S27  
S34

from which

1964

A pinon, 8 ins. diam., bears S. 37° W., 471 lks.  
dist., mkd.  $\frac{1}{4}$ S34BT

Build a mound of stones to the N. of the iron post.  
Bury the original corner stone alongside the iron post.  
Cor. is in an open valley.

The cor. of secs. 26, 27, 34 and 35, is monumented by a malpais stone, 14 X 18 X 24 ins., firmly set in a collar of stones, mkd. with 1 notch on the S. and 2 notches on the E., from which the original bearing trees

A pinon, 12 ins. diam., bears N. 77° E., 43 lks.  
dist., mkd. T25NR4ES26BT

A pine, 24 ins. diam., bears S. 34° E., 95 lks.  
dist., mkd. with an overgrown blaze.

A pinon, 14 ins. diam., bears S. 26° W., 14 lks.  
dist., mkd. T25NR4ES34BT

A pinon, 16 ins. diam., bears N. 3° W., 21 lks.  
dist., mkd. T25NR4ES27BT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 12 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E

S27 | S26  
S34 | S35

from which

1964

A pinon, 14 ins. diam., bears N. 57° E., 28 lks.  
dist., mkd. T25NR4ES26BT

A pinon, 6 ins. diam., bears S. 64° E., 11 lks.  
dist., mkd. S35BT

CHAINS

A pinon, 22 ins. diam., bears S. 41° W., 76 lks. dist., mkd. T25NR4ES34BT

A pinon, 16 ins. diam., bears N. 54° W., 52 lks. dist., mkd. T25NR4ES27BT

Bury the original corner stone alongside the iron post.

Cor. is on a gentle NW. slope among large trees.

The  $\frac{1}{4}$  sec. cor. of secs. 26 and 27, is monumented by a malpais stone, 8 X 14 X 24 ins., firmly set, mkd.  $\frac{1}{4}$  on the W., from which the remains of the original bearing trees

A pine, 24 ins. diam., bears S. 52° E., 112 lks. dist., mkd. with a grown over blaze, tree is partly dead.

A pine, 20 ins. diam., bears S. 9° W., 91 lks. dist., mkd. with a grown over blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T25NR4E

$\frac{1}{4}$   
S27 | S26

from which

1964

A pine, 6 ins. diam., bears N. 60° E., 148 lks. dist., mkd.  $\frac{1}{4}$ S26BT

A juniper, 18 ins. diam., bears N. 81° W., 176 lks. dist., mkd.  $\frac{1}{4}$ S27BT

Bury the original corner stone alongside the iron post.

Cor. is on a gentle NE. slope, on edge of open grass land.

The official record was found to be in error for many of the bearings and distances given for the bearing trees. A few of the trees were misnamed as to specie. A ring growth count was made on several trees which proved they were marked at the time of the original survey.

Where the original corner monument appeared to be undisturbed, it was accepted as the true point for the corner.



14

BOOK 4710

CERTIFICATE OF SURVEY

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day of June, 1964, I have remonumented a portion of the cadastral survey corners in cooperation with the U. S. Forest Service in T. 25 N., R. 4 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Oct. 29, 1964 (Date)

Lester S. Mann (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date NOV 2 1964

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in T. 25 N., R. 4 E., G. & S. R. Meridian, Arizona,

executed by Lester S. Mann, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

APR 20 1965 (Date)

[Signature] (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)