

Form 4-679  
(January 1963)

BOOK 4715  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of

REMONUMENTATION

in

Township 22 North, Range 1 West

Of the Gila & Salt River Meridian,

In the State of Arizona.

### EXECUTED BY

Lester S. Mann, Cadastral Surveyor

Under special instructions dated June 22, 19 64, which provided for the surveys included under Group Number 417, approved June 22, 1964, and assignment instructions dated June 22, 19 64.

Survey commenced July 21, 19 64

Survey completed September 4, 19 64

111

# BOOK 4715 INDEX DIAGRAM

Township 22 North, Range 1 West,

|    |    |    |    |    |    |    |    |    |    |   |
|----|----|----|----|----|----|----|----|----|----|---|
|    | 9  | 8  | 17 | 8  | 7  | 7  | 6  | 6  |    |   |
| 10 | 6  | 5  | 4  | 3  | 2  | 1  |    | 5  |    |   |
| 10 |    |    |    |    |    |    |    | 5  |    |   |
| 11 | 7  | 8  | 9  | 10 | 11 | 12 |    | 4  |    |   |
| 11 |    |    |    |    |    | 19 | 20 | 4  |    |   |
|    | 18 | 17 | 16 | 24 | 15 | 14 | 19 | 18 | 3  |   |
| 11 |    | 28 | 29 |    | 23 | 24 | 21 | 21 | 3  |   |
|    | 19 | 28 | 20 | 24 | 21 | 23 | 22 | 28 | 3  |   |
|    |    | 27 | 27 |    | 22 |    |    |    | 2  |   |
| 12 | 30 | 26 | 29 | 28 | 22 | 27 | 26 | 18 | 25 | 2 |
| 12 | 26 | 25 |    |    |    |    | 21 | 18 |    | 1 |
|    | 31 | 25 | 32 | 33 | 34 | 20 | 35 | 17 | 36 |   |
| 13 | 13 | 13 | 14 | 15 | 15 | 15 | 16 | 16 |    | 1 |

BOOK 4715

Township 22 North, Range 1 West  
Gila & Salt River Meridian, Arizona

113

CHAINS

The boundaries and the subdivisional lines of Township 22 North, Range 1 West, Gila & Salt River Meridian, Arizona, were surveyed in 1883 by J. T. Smith. The following field notes are those of remonumented cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 22, 1964 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54, dated April 21, 1954.

The assistants furnished by the Forest Service, remonumented the original corner positions after verification. An open site Dietzen compass was used to obtain the bearings and a standard steel tape was used to measure the distances.

The cor. of secs. 1, 6, 31 and 36, Ts. 21 and 22 N., Rs. 1 E. and 1 W., is monumented by a mound of stones and verified by the remains of the original bearing tree

A hole where the original tree, a juniper, 16 ins. diam., stood, bears N. 71° E., 226 lks. dist., tree has been pushed but scribed marks are visible.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with a collar of stones to top, with brass cap mkd.

|           |
|-----------|
| T22N      |
| RLW R1E   |
| S36   S31 |
| S1   S6   |

from which

T21N  
1964

A juniper, 4 ins. diam., bears N. 16° E., 135 lks. dist., mkd. S31BT

A juniper, 10 ins. diam., bears S. 61° W., 135 lks. dist., mkd. S1BT

A juniper, 6 ins. diam., bears N. 62° W., 150 lks. dist., mkd. S36BT

Cor. is in a nearly level area and about 1.50 chs. E. of a N. and S. fence.

The cor. of secs. 25, 30, 31 and 36, T. 22 N., Rs. 1 E. and 1 W., is monumented by the remains of the original wood post, parts of scribe mks. visible, in a mound of stones, from which the original bearing tree

An alligator juniper, 2¼ ins. diam., bears S. 10° E., 18 lks. dist., mkd. T22NR1ES31BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., on bed rock and over a +, mounded with stone to top, with brass cap mkd.

BOOK 4715

Township 22 North, Range 1 West, Arizona

2

2.

CHAINS

T22N  
RLW R1E  
S25|S30  
S36|S31

from which

1964

A juniper, 12 ins. diam., bears N. 68° E., 59 lks. dist., mkd. T22NRLES30BT

A juniper, 6 ins. diam., bears S. 60° W., 94 lks. dist., mkd. S36BT

A pinon, 12 ins. diam., bears N. 75° W., 52 lks. dist., mkd. T22NRLWS25BT

Cor. is on a gentle S. slope.

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, T. 22 N., Rs. 1 E. and 1 W., is monumented by a malpais stone, 6 X 14 X 18 ins., firmly set, mkd.  $\frac{1}{4}$  on the W., with a mound of stones to the SE., from which the remains of the original bearing tree

A hole where the original tree, a juniper, 16 ins. diam., stood, bears N. 8° E., 34 lks. dist., tree has been pushed but parts of scribe mks. are visible.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, with a collar of stones to top, with brass cap mkd.

T22N  
RLW R1E  
 $\frac{1}{4}$   
S25|S30  
1964

from which

A pine, 6 ins. diam., bears S. 88° E., 219 lks. dist., mkd.  $\frac{1}{4}$ S30BT

A juniper, 6 ins. diam., bears S. 68° W., 99 lks. dist., mkd.  $\frac{1}{4}$ S25BT

Bury the original corner stone alongside the iron post.

Cor. is in an area where trees have been pushed.

The cor. of secs. 19, 24, 25 and 30, T. 22 N., Rs. 1 E. and 1 W., is monumented by a malpais stone, 10 X 10 X 12 ins., firmly set, mkd. with 2 notches on the S. and 4 notches on the N., with a mound of stones to the SE.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T22N  
RLW R1E  
S24|S19  
S25|S30  
1964

from which

A juniper, 6 ins. diam., bears N. 77° E., 7 lks. dist., mkd. BT

A juniper, 6 ins. diam., bears S. 45° E., 28 lks. dist., mkd. BT

A juniper, 6 ins. diam., bears S. 26° W., 65 lks. dist., mkd. BT

A juniper, 10 ins. diam., bears N. 86° W., 30 lks. dist., mkd. S24 BT

CHAINS

Bury the original corner stone alongside the iron post.  
Cor. is in fairly level area among young juniper trees.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, T. 22 N., Rs. 1 E. and 1 W., is monumented by a red malpais stone, 6 X 10 X 16 ins., firmly set, mkd.  $\frac{1}{4}$  on the W. and with a mound of stone to the SE., from which an original bearing tree

A juniper, 14 ins. diam., bears N. 60° E., 20 lks. dist., mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22N  
RLW R1E  
 $\frac{1}{4}$   
S24|S19  
1964

from which

A juniper, 8 ins. diam., bears N. 68° W., 21 lks. dist., mkd.  $\frac{1}{4}$ S24BT

Bury the original corner stone alongside the iron post.

Cor. is on a fairly steep NE. slope..

The cor. of secs. 13, 18, 19 and 24, T. 22 N., Rs. 1 E. and 1 W., is monumented by a malpais stone, 5 X 7 X 14 ins., firmly set in a small collar of stone, mkd. with 3 notches on the N. and S., from which an original bearing tree

A pine, 18 ins. diam., bears N. 87° W., 112 lks. dist., blaze has grown over, add mks. S13BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22N  
RLW R1E  
S13|S18  
S24|S19  
1964

from which

A juniper, 6 ins. diam., bears N. 10° E., 32 lks. dist., mkd. S18BT

A pine, 6 ins. diam., bears S. 70° E., 96 lks. dist., mkd. S19BT

A juniper, 12 ins. diam., bears S. 16° W., 120 lks. dist., mkd. T22NRLWS24BT

Bury the original corner stone alongside the iron post.

Cor. is 70 lks. S. of a wash, 10 lks. wide, course W.

The  $\frac{1}{4}$  Sec. cor. of secs. 13 and 18, T. 22 N., Rs. 1 E.

CHAINS

and 1 W., is monumented by a malpais stone, 9 X 9 X 14 ins., loosely set in a mound of stone, mkd.  $\frac{1}{4}$  on the W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22N  
RLW R1E

$\frac{1}{4}$   
S13 | S18  
1964

from which

A juniper, 10 ins. diam., bears S.  $34^\circ$  E., 52 lks. dist., mkd.  $\frac{1}{4}$ S18BT

A juniper, 6 ins. diam., bears S.  $42^\circ$  W., 18 lks. dist., mkd.  $\frac{1}{4}$ S13BT

Bury the original corner stone alongside the iron post.

Cor. is in an almost flat area of stones and juniper.

The cor. of secs. 7, 12, 13 and 18, T. 22 N., Rs. 1 E. and 1 W., is monumented by a juniper, 16 ins. diam. which is one of several trees growing from one stump. Tree is blazed and scribed T22NR1ES7 on the NE. and 18 on the SE. Ring growth to blaze on the NE. shows it to be 56 years old. Original bearing trees

A dead juniper, 8 ins. diam., bears N.  $64^\circ$  E., 40 lks. dist., mkd. T22NR1ES, other mks. rotted off.

A dead juniper, 8 ins. diam., bears S.  $69^\circ$  E., 14 lks. dist., mkd. T22NR1ES18BT

At a point 10 lks. N. of the cor. tree

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, with a collar of stone to top, with brass cap, mkd.

WC  
T22N

RLW R1E  
S12 | S7  
S13 | S18  
1964

from which

A juniper, 8 ins. diam., bears N.  $68^\circ$  E., 28 lks. dist., mkd. T22NR1ES7WCBT

A juniper, 10 ins. diam., bears S.  $40^\circ$  E., 68 lks. dist., mkd. T22NR1ES18WCBT

A juniper, 4 ins. diam., bears S.  $59^\circ$  W., 25 lks. dist., mkd. WCBT

A juniper, 12 ins. diam., bears N.  $60^\circ$  W., 72 lks. dist., mkd. S12WCBT

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, T. 22 N., Rs. 1 E. and 1 W., is monumented by a malpais stone, 6 X 8 X 10 ins., firmly set, mkd.  $\frac{1}{4}$  on the W., with a small mound of stone to the S.

At the cor. point

CHAINS

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with collar of stone to top, with brass cap mkd.

T22N  
RLW R1E  
 $\frac{1}{4}$   
S12 | S7  
1964

from which

A juniper, 6 ins. diam., bears N.  $71^\circ$  E., 51 lks. dist., mkd.  $\frac{1}{4}$ S7BT

A juniper, 8 ins. diam., bears N.  $66^\circ$  W., 16 lks. dist., mkd.  $\frac{1}{4}$ S12BT

Bury the original corner stone alongside the iron post.  
Cor. is on a very gentle N. slope.

The cor. of secs. 1, 6, 7 and 12, T. 22 N., Rs. 1 E. and 1 W., is monumented with a malpais stone, 6 X 12 X 16 ins., firmly set, mkd. with 5 notches on the S. and 1 notch on the N. and with a mound of stone to the N.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22N  
RLW R1E  
S1 | S 6  
S12 | S 7  
1964

No bearing trees available.

Raise a mound of stone to the W.

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, T. 22 N., Rs. 1 E. and 1 W., is monumented by a malpais stone, 6 X 7 X 12 ins., firmly set, mkd.  $\frac{1}{4}$  on the W. with a mound of stone to the SE.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22N  
RLW R1E  
 $\frac{1}{4}$   
S 1 | S 6  
1964

from which

A juniper, 8 ins. diam., bears S.  $73^\circ$  E., 34 lks. dist., mkd. BT

A juniper, 6 ins. diam., bears S.  $65^\circ$  W., 53 lks. dist., mkd. BT

Bury the original corner stone alongside the iron post.

CHAINS

The cor. of secs. 1, 6, 31 and 36, Ts. 22 and 23 N., Rs. 1 E. and 1 W., is monumented by a malpais stone, 10 X 16 X 20 ins., firmly set in a collar of stone, mkd. with 6 notches on the S. and faint marks on the E., W. and N., from which the original bearing trees

A dead and fallen pinon, 6 ins. diam., bears N. 58° E., 130 lks. dist., mkd. T23NRLES31BT

A dead and fallen pinon, 6 ins. diam., bears S. 46° E., 154 lks. dist., mkd. T22NRLES6BT

A dead and fallen pinon, 10 ins. diam., bears S. 67° W., 94 lks. dist., mkd. T22NRLWS1BT

A dead juniper, 10 ins. diam., bears N. 3° W., 99 lks. dist., mkd. T23NRLWS36BT

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with collar of stone to top, with brass cap mkd.

|      |     |
|------|-----|
| T23N |     |
| RLW  | R1E |
| S36  | S31 |
| S 1  | S 6 |

from which

T22N  
1964

A juniper, 6 ins. diam., bears N. 29° E., 92 lks. dist., mkd. S31BT

A juniper, 6 ins. diam., bears S. 80° E., 60 lks. dist., mkd. T22NRLES6BT

A juniper, 6 ins. diam., bears S. 54° E., 93 lks. dist., mkd. T22NRLWS1BT

A juniper, 12 ins. diam., bears N. 51° W., 150 lks. dist., mkd. T23NRLWS36BT

Bury the original corner stone alongside the iron post.

Cor is on a gently N. slope in rocky area.

The cor. of secs. 1, 2, 35 and 36, Ts. 22 and 23 N., R. 1 W., is monumented by a granite stone, 6 X 8 X 14 ins. firmly set, mkd. with 5 notches on the W. and 1 notch on the E. and with a mound of stone to the N., from which the original bearing trees

A juniper, 10 ins. diam., bears S. 34° E., 130 lks. dist., mkd. TXX11NRLWS1BT

A juniper, 24 ins. diam., bears N. 6° W., 86 lks. dist., mkd. TXX111NRLWS35BT

Both trees have been pushed over.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, with collar of stone to top, with brass cap mkd.



CHAINS

T23NRLW  
 S35 | S36  
 S2 | S1  
 T22N

from which 1964

A pinon, 14 ins. diam., bears N. 83° E., 200 lks. dist., mkd. T23NRLWS36BT

A juniper, 16 ins. diam., bears S. 84° W., 216 lks. dist., mkd. T22NRLWS2 BT

Bury the original corner stone alongside the iron post.

Cor. if 5 lks. SW. of a fence corner.

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, Ts. 22 and 23 N., R. 1 W., is monumented by a malpais stone, 8 X 8 X 16 ins., firmly set, mkd.  $\frac{1}{4}$  on the N. and with a small mound of stone to the W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T23NRLW  
 $\frac{1}{4}$  S35  
 $\frac{1}{4}$  S2

from which 1964

A juniper, 6 ins. diam., bears S. 39° W., 38 lks. dist., mkd.  $\frac{1}{4}$ S2BT

A juniper, 6 ins. diam., bears N. 32° W., 15 lks. dist., mkd.  $\frac{1}{4}$ S35BT

Bury the original corner stone alongside the iron post.

Cor. is in flat area and rocky ground.

The cor. of secs. 2, 3, 34 and 35, Ts. 22 and 23 N., R. 1 W., monumented by a malpais stone, 10 X 12 X 24 ins., firmly set, mkd. with 4 notches on the W. and 2 notches on the E. and with a mound of stone on the SE., from which the original bearing trees

A juniper limb, 12 ins. diam., bears S. 20° E., 90 lks. dist., blazed with faint scribe marks. Add mks. S2BT on base of tree.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T23NRLW  
 S34 | S35  
 S3 | S2  
 T22N

from which 1964

A juniper, 10 ins. diam., bears S. 16° W., 77 lks. dist., mkd. S3BT

Bury the original corner stone alongside the iron post.

8

CHAINS

Cor. is in rocky ground and an area where the trees have been pushed.

The cor. of secs. 3, 4, 33 and 34, Ts. 22 and 23 N., R. 1 W., is monumented by a malpais stone, 7 X 9 X 16 ins., firmly set, mkd. with 3 notches on the E. and W., and with a mound of stones to the N., from which the original bearing trees

A juniper, 12 ins. diam., bears S. 28° E., 100 lks. dist., mkd. TXX11NRLWS111BT on a limb of tree.

A juniper, 18 ins. diam., bears N. 71° W., 58 lks. dist., mkd. TXX111NRLWSXXX111BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

|           |
|-----------|
| T23NRLW   |
| S33   S34 |
| S4   S3   |

T22N

1964

from which

A juniper, 16 ins. diam., bears N. 6° E., 61 lks. dist., mkd. T23NRLWS34BT

A juniper, 4 ins. diam., bears S. 51° W., 58 lks. dist., mkd. S4BT

Bury the original corner stone alongside the iron post.

Cor. is 30 lks. N. of a small drain, course W.

The cor. of secs. 5, 6, 31 and 32, Ts. 22 and 23 N., R. 1 W., is monumented by a sandstone, 10 X 12 X 14 ins., firmly set in a collar of stone, mkd. with 1 notch on the W. and 5 notches on the E., from which the original bearing trees

A juniper, 16 ins. diam., bears S. 48° E., 103 lks. dist., mkd. TXX11NRLWSVBT

A juniper, 12 ins. diam., bears S. 33° W., 112 lks. dist., mkd. on a limb TXX11NRLWSV1BT

A juniper, 12 ins. diam., bears N. 46° W., 76 lks. dist., mkd. TXX111NRLWSXXX1BT

NOTE: All three of these trees were marked at the time of the original survey but were never recorded.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

|           |
|-----------|
| T23NRLW   |
| S31   S32 |
| S6   S5   |

T22N

1964

from which

A juniper, 8 ins. diam., bears N. 45° E., 56 lks. dist., mkd. S32BT

CHAINS

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, Ts. 22 and 23 N., R. 1 W., is monumented by a sandstone, 5 X 8 X 14 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., from which the original bearing trees

A dead pinon, 8 ins. diam., bears N. 15° W., 61 lks. dist., mkd.  $\frac{1}{4}$  SBT

A juniper, 4 ins. diam., bears S. 7° E., 44 lks. dist., mkd.  $\frac{1}{4}$  SBT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T23NR1W

$\frac{1}{4}$  S31  
S6

T22N

from which

1964

A juniper, 6 ins. diam., bears N. 19° W., 51 lks. dist., mkd.  $\frac{1}{4}$  S31BT

Bury the original corner stone alongside the iron post.

Cor. is in level area about 5 chs. S. of a road.

The cor. of secs. 1, 6, 31 and 36, Ts. 22 and 23 N., Rs. 1 and 2 W., is monumented by a limestone, 10 X 12 X 30 ins., firmly set, mkd. with 6 notches on all four sides, with a mound of stone to the S., from which the original bearing trees

A juniper, 16 ins. diam., bears EAST, 68 lks. dist., mkd. TXX11NR1WSV1BT

A juniper stump, 12 ins. diam., bears N. 6° W., 38 lks. dist.

A juniper, 14 ins. diam., bears S. 17° W., 20 lks. dist., mkd. TXX11NR11WS1BT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N

R2W R1W

S36 | S31

S1 | S6

T22N

from which

1964

A pinon, 10 ins. diam., bears N. 79° E., 56 lks. dist., mkd. T23NR1WS31BT

A juniper, 8 ins. diam., bears S. 3° E., 18 lks. dist., mkd. T22NR1WS6BT

A juniper, 10 ins. diam., bears N. 85° W., 71 lks. dist., mkd. T23NR2WS36BT

10

CHAINS

Bury the original corner stone alongside the iron post.

Cor. is on a NE. slope, 2.00 chs. S. and 1.50 chs. W. of a drain, course S. 60° W.

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, T. 22 N., Rs. 1 and 2 W., is monumented by a sandstone, 8 X 10 X 14 ins., firmly set, mkd.  $\frac{1}{4}$  on W., with mound of stone to W., from which the original bearing trees

A dead pinon, 12 ins. diam., bears N. 78° W., 31 lks. dist., mkd.  $\frac{1}{4}$ SBT

A pinon stump, badly rotted, bears S. 57° E., 25 lks. dist., fallen tree is mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22N  
R2W RLW  
 $\frac{1}{4}$   
S1 | S6  
1964

from which

A juniper, 16 ins. diam., bears S. 62° W., 33 lks. dist., mkd.  $\frac{1}{4}$ SLBT

A pinon, 5 ins. diam., bears N. 35° E., 27 lks. dist., mkd.  $\frac{1}{4}$ S6BT

Bury the original corner stone alongside the iron post.

Cor. is on a NW. slope.

The cor. of secs. 1, 6, 7 and 12, T. 22 N., Rs. 1 and 2 W., is monumented by a limestone, 10 X 12 X 28 ins., loosely set, mkd. with 1 notch on the N. and 5 notches on the S., from which the original bearing trees

A juniper, 10 ins. diam., bears S. 42° E., 23 lks. dist., mkd. TXXLNRLWSV11BT

A juniper, 10 ins. diam., bears N. 68° W., 36 lks. dist., mkd. TXXL1NR, other marks too faint to read.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 15 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22N  
R2W RLW  
S1 | S6  
S12 | S7  
1964

from which

A juniper, 12 ins. diam., bears S. 29° W., 31 lks. dist., mkd. T22NR2WS12BT

A juniper, 12 ins. diam., bears N. 6° E., 24 lks. dist., mkd. S6BT

Bury the original corner stone alongside of the iron post.

BOOK 4715

Township 22 North, Range 1 West, Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, T. 22 N., Rs. 1 and 2 W., is monumented by a sandstone, 3 X 16 X 16 ins., firmly set in a small collar of stone, mkd.  $\frac{1}{4}$  on the W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, with collar of stone to top, with brass cap mkd.

T22N  
R2W R1W  
 $\frac{1}{4}$   
S12 | S7  
1964

from which

A juniper, 5 ins. diam., bears S.  $58^\circ$  E., 12 lks. dist., mkd. BT

A juniper, 8 ins. diam., bears N.  $30^\circ$  W., 90 lks. dist., mkd.  $\frac{1}{4}$ S12BT

Bury the original corner stone alongside the iron post.

Cor. is on a long spur sloping SW. and near a sharp break on the S. side of the spur.

The cor. of secs. 7, 12, 13 and 18, T. 22 N., Rs. 1 and 2 W., is monumented by a sandstone, 7 X 12 X 24 ins., firmly set in a mound of stone, mkd. with 4 notches on the S. and 2 notches on the N.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22N  
R2W R1W  
S12 | S7  
S13 | S18  
1964

No bearing trees available.

Bury the original corner stone alongside the iron post.

Cor. is on a steep and rocky SE. slope about 1.20 chs. N. of a draw, course SW.

The cor. of secs. 13, 18, 19 and 24, T. 22 N., Rs. 1 and 2 W., is monumented by a sandstone, 5 X 14 X 24 ins., firmly set in a collar of stone, mkd. with 3 notches on the N. and S.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, with collar of stone to top, with brass cap mkd.

T22N  
R2W R1W  
S13 | S18  
S24 | S19  
1964

from which

A juniper, 12 ins. diam., bears S.  $22^\circ$  E., 104 lks. dist., mkd. BT

12

CHAINS

A juniper, 8 ins. diam., bears S. 40° W., 35 lks. dist., mkd. BT

A juniper, 6 ins. diam., bears N. 35° W., 25 lks. dist., mkd. BT

Bury the original corner stone alongside the iron post.

Cor. is on a rocky SW. slope.

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, T. 22 N., Rs. 1 and 2 W., is monumented by a malpais stone, 4 X 8 X 14 ins., firmly set, mkd.  $\frac{1}{4}$  on the W., with a mound of stone to W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22N  
R2W R1W  
 $\frac{1}{4}$   
S25 | S30  
1964

Build a mound of stone to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is 50 lks. N. of a dirt road, bearing E. and W.

The cor. of secs. 25, 30, 31 and 36, T. 22 N., Rs. 1 and 2 W., is monumented by a malpais stone, 6 X 8 X 18 ins., firmly set, mkd. with 1 notch on the S. and 5 notches on the N., with a mound of stone to the W., from which the original bearing trees

Limb on juniper, 16 ins. diam., bears N. 50° E., 31 lks. dist., mkd. TXX1LNRLWSXXXBT

A juniper, 12 ins. diam., bears S. 70° W., 18 lks. dist., mkd. TXX1LNRL1WSXXXV1BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with collar of stone to top, with brass cap mkd.

T22N  
R2W R1W  
S25 | S30  
S36 | S31  
1964

from which

A juniper, 8 ins. diam., bears N. 9° E., 15 lks. dist., mkd. S30 BT

A juniper, 6 ins. diam., bears S. 88° E., 52 lks. dist., mkd. S31BT

A juniper, 24 ins. diam., bears S. 12° W., 76 lks. dist., mkd. S36BT

A juniper, 4 ins. diam., bears N. 31° W., 77 lks. dist., mkd. BT

Bury the original cor. stone alongside the iron post.

CHAINS

Cor. is on a spur sloping gently to the SW.

The cor. of secs. 1, 6, 31 and 36, Ts. 21 and 22 N., Rs. 1 and 2 W., is monumented by a malpais stone, 8 X 12 X 18 ins., firmly set, mkd. with 6 notches on the N., S., E. and W., with a collar of stone.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, with collar of stone to top, with brass cap mkd.

T22N  
R2W RLW  
S36 | S31  
S1 | S6  
T21N  
1964

from which

A juniper, 10 ins. diam., bears N. 24° E., 18 lks. dist., mkd. T22NRLWS31BT

A juniper, 6 ins. diam., bears S. 26° E., 41 lks. dist., mkd. S6BT

A juniper, 6 ins. diam., bears S. 29° W., 90 lks. dist., mkd. BT NOTE: This tree has a limb blazed and scribed TXX1NR11WS1BT which appears to have been marked during the original survey.

A juniper, 12 ins. diam., bears N. 43° W., 23 lks. dist., mkd. S36BT

Bury the original corner stone alongside the iron post.

Cor. is in a flat area.

The  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, Ts. 21 and 22 N., R. 1 W., is monumented by a malpais stone, 8 X 12 X 16 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., with small collar of stone.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW  
 $\frac{1}{4}$  S31  
S6  
T21N  
1964

from which

A juniper, 8 ins. diam., bears N. 25° W., 40 lks. dist., mkd. BT

A juniper, 10 ins. diam., bears S. 23° W., 79 lks. dist., mkd. S6BT

Bury the original corner stone alongside the iron post.

Cor. is in a flat area about 3.50 chs. E. of a drain, course S. and about 4 chs. E. of a dim road, bearing N. and S.

The cor. of secs. 5, 6, 31 and 32, Ts. 22 and 21 N.,

## CHAINS

R. 1 W., is monumented by a malpais stone, 10 X 14 X 18 ins., firmly set, mkd. with 5 notches on the E. and 1 notch on the W., with a mound of stone to the N., from which the original bearing tree.

A juniper, 24 ins. diam., bears S. 30° W., 130 lks. dist., mkd. on a limb VLB, other marks are gone.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone to top, with brass cap mkd.

|         |     |
|---------|-----|
| T22NRLW |     |
| S31     | S32 |
| S6      | S5  |
| T21N    |     |
| 1964    |     |

from which

A juniper, 5 ins. diam., bears N. 14° E., 16 lks. dist., mkd. BT

A juniper, 8 ins. diam., bears S. 33° E., 28 lks. dist., mkd. S5BT

A juniper, 4 ins. diam., bears S. 32° W., 67 lks. dist., mkd. BT

A juniper, 6 ins. diam., bears N. 8° W., 51 lks. dist., mkd. BT

Bury the original corner stone alongside the iron post.

Cor. is on a gentle E. slope.

The cor. of secs. 4, 5, 32 and 33, Ts. 21 and 22 N., R. 1 W., is monumented by a malpais stone, 6 X 10 X 12 ins., firmly set, mkd. with 4 notches on the E. and 2 notches on the W., with a mound of stone to the N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

|         |     |
|---------|-----|
| T22NRLW |     |
| S32     | S33 |
| S5      | S4  |
| T21N    |     |
| 1964    |     |

from which

A juniper, 4 ins. diam., bears N. 76° E., 14 lks. dist., mkd. BT

A juniper, 5 ins. diam., bears S. 40° W., 6 lks. dist., mkd. BT

A juniper, 4 ins. diam., bears N. 71° W., 40 lks. dist., mkd. BT

Build a mound of stone to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a ridge with gentle slope to the S.



BOOK 4710

Township 22 North, Range 1 West, Arizona

15.

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, Ts. 21 and 22 N., R. 1 W., is monumented by a malpais stone, 10 X 12 X 20 ins., firmly set in a small collar of stone, mkd.  $\frac{1}{4}$  on the N., from which the original bearing trees

A juniper, 8 ins. diam., bears N. 16° E., 47 lks. dist., mkd.  $\frac{1}{4}$ SBT, add small blaze chest high.

A juniper, 8 ins. diam., bears S. 1° W., 43 lks. dist., mkd.  $\frac{1}{4}$ SBT, add small blaze chest high.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   $\frac{S33}{S4}$

T21N

1964

Bury the original corner stone alongside of the iron post.

Cor. is on a NW. slope, about 7 chs. S. of the S. one of two large pipe lines.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, Ts. 21 and 22 N., R. 1 W., is monumented by a malpais stone, 5 X 5 X 24 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., from which the original bearing trees

A juniper, 20 ins. diam., bears N. 24° W., 61 lks. dist., mkd.  $\frac{1}{4}$ SBT

A pinon, 20 ins. diam., bears S. 13° E., 71 lks. dist., blazed has grown over.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground and between two rocks, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   $\frac{S34}{S3}$

T21N

1964

from which

A juniper, 16 ins. diam., bears S. 47° W., 116 lks. dist., mkd.  $\frac{1}{4}$ S3BT

A juniper, 18 ins. diam., bears N. 81° W., 57 lks. dist., mkd.  $\frac{1}{4}$ S34BT

Bury the original corner stone alongside the iron post.

Cor. is about 1 ch. N. of the N. rim of a canyon.

The cor. of secs. 2, 3, 34 and 35, Ts. 21 and 22 N., R. 1 W., is monumented by a malpais stone, 14 X 18 X 24 ins., firmly set in a collar of stone, mkd. with 2 notches on the E. and 4 notches on the W., from which the original bearing trees

A dead juniper, 20 ins. diam., bears S. 60° E., 71 lks. dist., mkd. TXXLNRLWSL1BT

CHAINS

A juniper stump, 12 ins. diam., bears N. 44° W., 36 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW  
 S34 | S35  
 S3 | S2  
 T21N  
 1964

from which

A juniper, 6 ins. diam., bears N. 12° E., 58 lks. dist., mkd. BT

A pine, 24 ins. diam., bears S. 26° W., 142 lks. dist., mkd. T21NRLWS3BT

Bury the original corner stone alongside the iron post.

Cor. is on a SW. slope, about 1.50 chs. N. of a drain, course NW.

The cor. of secs. 1, 2, 35 and 36, Ts. 21 and 22 N., R. 1 W., is monumented by a malpais stone, 10 X 12 X 18 ins., firmly set, mkd. with 1 notch on the E. and 5 notches on the W., with a mound of stone to the N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22NRLW  
 S35 | S36  
 S2 | S1  
 T21N  
 1964

from which

A juniper, 6 ins. diam., bears N. 13° E., 23 lks. dist., mkd. BT

A juniper, 6 ins. diam., bears S. 51° E., 42 lks. dist., mkd. SLBT

A juniper, 10 ins. diam., bears S. 50° W., 71 lks. dist., mkd. T21NRLWS2BT

A juniper, 6 ins. diam., bears N. 64° W., 111 lks. dist., mkd. BT

Bury the original corner stone alongside the iron post.

Cor. is on a W. slope among young juniper trees and about 10 chs. N. of an old stone quarry.

The ¼ sec. cor. of secs. 1 and 36, Ts. 21 and 22 N., R. 1 W., is monumented by a malpais stone, 8 X 12 X 18 ins., loosely set, mkd. ¼ on the N., from which the original bearing trees

A juniper, 10 ins. diam., bears S. 28° E., 87 lks. dist., mkd. ¼SBT

BOOK 4715

Township 22 North, Range 1 West, Arizona

17.

CHAINS

A juniper, 10 ins. diam., bears N. 23° W., 35 lks. dist., mkd.  $\frac{1}{4}$ SBT

At the corner point

Set an iron post, 30 ins. long.,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22NR1W

$\frac{1}{4}$  S36  
 $\frac{1}{4}$  S1

T21N

from which

1964

A juniper, 8 ins. diam., bears S. 78° E., 49 lks. dist., mkd.  $\frac{1}{4}$ S1BT

Bury the original corner stone alongside the iron post.

Cor. is about 1 ch. E. of the top of a steep slope which bears NW. and SE.

The cor. of secs. 4, 5, 32 and 33, Ts. 22 and 23 N., R. 1 W., is monumented by a sandstone, 5 X 14 X 20 ins., firmly set, mkd. with 4 notches on the E. and 2 notches on the W. and with a mound of stone to the E., from which the original bearing trees

A dead juniper, 24 ins. diam., bears N. 82° E., 115 lks. dist., mkd. TXX111NR1WSXXX111BT

A juniper, 24 ins. diam., bears S. 65° W., 149 lks. dist., mkd. TXX11NR1WSVBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with collar of stone to top, with brass cap mkd.

T23NR1W

S32 | S33  
S5 | S4

T22N

from which

1964

A juniper, 6 ins. diam., bears N. 52° E., 51 lks. dist., mkd. S33BT

A juniper, 30 ins. diam., bears S. 56° E., 60 lks. dist., mkd. S4BT

A juniper, 6 ins. diam., bears S. 21° W., 42 lks. dist., mkd. S5BT

A pinon, 10 ins. diam., bears N. 41° W., 29 lks. dist., mkd. T23NR1WS32BT

Bury the original corner stone alongside the iron post.

Cor. is 15 lks. W. of a drain, 5 lks. wide, course S. and in a flat area about 4 chs. W. of a dirt road.

The  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, is monumented by a malpais stone, 4 X 14 X 18 ins., loosely set in a collar stone, mkd.  $\frac{1}{4}$  on the W., with mound of stone to the W.,

CHAINS

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   
S35|S36  
1964

from which

A juniper, 6 ins. diam., bears N.  $46^\circ$  W., 27 lks. dist., mkd.  $\frac{1}{4}$ S35BT

A juniper, 5 ins. diam., bears S.  $34^\circ$  E., 13 lks. dist., mkd.  $\frac{1}{4}$ S36BT

Bury the original corner stone alongside the iron post.

Cor. is on a steep W. slope.

The cor. of secs. 25, 26, 35 and 36, is monumented by a conglomerate stone, 6 X 12 X 20 ins., loosely set, old mound of stone to the W.; from which an original bearing tree

A dead juniper, 20 ins. diam., bears N.  $2^\circ$  E., 93 lks. dist., mkd. TXXL1RLWSXXVBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, with collar of stones to top, with brass cap mkd.

T22NRLW

S26|S25  
S35|S36  
1964

from which

A juniper, 6 ins. diam., bears N.  $52^\circ$  E., 101 lks. dist., mkd. S25BT

A juniper, 4 ins. diam., bears S.  $77^\circ$  E., 51 lks. dist., mkd. BT

A juniper, 8 ins. diam., bears S.  $28^\circ$  W., 55 lks. dist., mkd. BT

Bury the original corner stone alongside the iron post.

Cor. is on a spur sloping W.

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, is monumented by a malpais stone, 6 X 10 X 14 ins., firmly set, mkd.  $\frac{1}{4}$  on the W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   
S26|S25  
1964

No bearing trees available.

## CHAINS

Build a mound of stones to the W.

Bury the original corner stone alongside the iron post.

Cor. is about 2 chs. N. of a drain, 10 lks. wide, course W., and in an area of pushed trees.

The  $\frac{1}{4}$  sec. cor. of secs. 13 and 14, is monumented by a sandstone, 10 X 10 X 24 ins., loosely set, mkd.  $\frac{1}{4}$  on the W., with small mound of stones to the W., from which the remains of the original bearing trees

A hole where the original tree stood, bears N. 68° W. 139 lks. dist., tree has been pushed and is dead but scribe marks  $\frac{1}{4}$  SBT are visible.

A hole where the original tree stood, bears S. 43° E. 168 lks. dist., tree has been pushed and is dead but scribe mks.  $\frac{1}{4}$  SBT are visible.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   
S14 | S13

1964

from which

A pinon, 5 ins. diam., bears N. 25° W., 78 lks. dist., mkd.  $\frac{1}{4}$  S14BT.

Bury the original corner stone alongside the iron post.

Cor. is 55 lks. S. of a draw, course NW.

The cor. of secs. 11, 12, 13 and 14, is monumented by a limestone, 9 X 12 X 14 ins., firmly set, mkd. with 4 notches on the S. and 1 notch on the E., with a mound of stones to the N., from which the original bearing trees

A pinon, 14 ins. diam., bears N. 43° E., 53 lks. dist., blaze has grown over.

A juniper, 10 ins. diam., bears S. 87° E., 22 lks. dist., mkd. TXX11NRLWSX111BT

A juniper, 14 ins. diam., bears S. 38° W., 120 lks. dist., mkd. TXX11NRLWSX1VBT

A juniper, 12 ins. diam., bears N. 30° W., 108 lks. dist., mkd. TXX11NRLWSX1BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T22NRLW

S11 | S12  
S14 | S13

1964

from which

Remark the original tree to the NE., T22NRLWS12BT

CHAINS

A juniper, 5 ins. diam., bears S. 43° E., 42 lks. dist., mkd. BT

A pinon, 8 ins. diam., bears S. 22° W., 9 lks. dist., mkd. S14BT

A juniper, 10 ins. diam., bears N. 16° W., 104 lks. dist., mkd. S11BT

Bury the original corner stone alongside of the iron post.

Cor. in on a SW. slope.

The 1/4 sec. cor. of secs. 12 and 13, is monumented by a sandstone, 4 X 12 X 18 ins., loosely set, mkd. 1/4 on the N., with a mound of stone to the N., from which the original bearing tree

A juniper, 28 ins. diam., bears N. 9° E., 41 lks. dist., mkd. 1/4 SBT

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T22NRLW

1/4 S12  
1/4 S13

from which

1964

A pinon, 12 ins. diam., bears S. 14° W., 37 lks. dist., mkd. 1/4 S13BT

A pinon, 9 ins. diam., bears N. 32° W., 44 lks. dist., mkd. 1/4 S12BT

Bury the original corner stone alongside the iron post.

Cor. is on a NW. slope, about 1 ch. E. of a small drain, course N.

The 1/4 sec. cor. of secs. 34 and 35, is monumented by a malpais stone, 4 X 10 X 15 ins., firmly set, mkd. 1/4 on the W., with a mound of stones to the W., from which the original bearing tree

A juniper, 14 ins. diam., bears S. 42° E., 74 lks. dist., mkd. 1/4 SBT

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, with collar of stones to top, with brass cap mkd.

T22NRLW

1/4 S34 | S35

from which

1964

A juniper, 8 ins. diam., bears N. 89° E., 136 lks. dist., mkd. 1/4 S35BT

A juniper, 8 ins. diam., bears N. 16° W., 90 lks. dist., mkd. 1/4 S34BT

Bury the original corner stone alongside the iron post.

CHAINS

Cor. is in almost level area, about 5 chs. S. of a rail-road bearing E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, is monumented by a malpais stone, 8 X 8 X 20 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., with a mound of stones to the N., from which an original bearing tree

A juniper stump, 18 ins. diam., bears S. 11° E., 35 lks. dist., has bottom of blaze but no marks.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, with a collar of stones to top, with brass cap mkd.

T22NRLW

$\frac{1}{4}$  S26  
 $\frac{1}{4}$  S35

from which

1964

A juniper, 10 ins. diam., bears S. 18° W., 37 lks. dist., mkd.  $\frac{1}{4}$ S35BT

A juniper, 10 ins. diam., bears N. 36° W., 63 lks. dist., mkd.  $\frac{1}{4}$ S26BT

Bury the original corner stone alongside the iron post.

Cor. is on a gentle E. slope.

The cor. of secs. 14, 15, 22 and 23, is monumented by a malpais stone, loosely set in a small mound of stones, mkd. with 3 notches on the S. and 2 notches on the E., from which the remaining bearing trees

A juniper, 28 ins. diam., bears S. 52° E., 76 lks. dist., mkd. TXX11NRLWSXX111BT

A juniper, 28 ins. diam., bears S. 16° W., 84 lks. dist., mkd. TXX11NRLWSXX11BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T22NRLW

S15 | S14  
S22 | S23

from which

1964

A juniper, 10 ins. diam., bears N. 14° E., 58 lks. dist., mkd. S14BT

A juniper, 14 ins. diam., bears N. 55° W., 15 lks. dist., mkd. S15BT

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, is monumented by a malpais stone, 10 X 12 X 14 ins., loosely set, mkd.  $\frac{1}{4}$  on the N., with a mound of stones to the N., from which a remaining bearing tree

A juniper, 14 ins. diam., bears N. 11° E., 82 lks.

CHAINS

Cor. dist., mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   $\frac{S14}{S23}$

from which

1964

A juniper, 8 ins. diam., bears S.  $12^{\circ}$  E., 32 lks. dist., mkd.  $\frac{1}{4}$ S23BT

Raise a mound of stone to the N. of the iron post.

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, is monumented by a malpais stone, 3 X 10 X 30 ins., firmly set in a collar of stones, mkd.  $\frac{1}{4}$  on the W., from which a remaining bearing tree

A juniper, 16 ins. diam., bears S.  $82^{\circ}$  W., 43 lks. dist., mkd. on a limb  $\frac{1}{4}$ SBT

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   $\frac{S28}{S27}$

from which

1964

A juniper, 10 ins. diam., bears S.  $77^{\circ}$  E., 92 lks. dist., mkd.  $\frac{1}{4}$ S27BT

A juniper, 10 ins. diam., bears N.  $74^{\circ}$  W., 40 lks. dist., mkd.  $\frac{1}{4}$ S28BT

Build a mound of stone to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is about 3 chs. N. of the N. edge of a blow hole.

The cor. of secs. 21, 22, 27 and 28, is monumented by a malpais stone, 8 X 12 X 16 ins., firmly set in a collar of stones, mkd. with 3 notches on the E. and 2 notches on the S., from which the remaining original bearing trees

A juniper, 14 ins. diam., bears N.  $40^{\circ}$  E., 111 lks. dist., mkd. SXX11BT, other mks. not visible

A juniper, 12 ins. diam., bears S.  $61^{\circ}$  W., 86 lks. dist., mkd. SXXV111BT, other mks. not visible.

A pinon, 12 ins. diam., bears N.  $10^{\circ}$  W., 32 lks. dist., mkd. SXX1BT, other mks. not visible.

At the cor. point



CHAINS

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, with a collar of stones to top, with brass cap mkd.

T22NR1W  
S21|S22  
S28|S27

from which

1964

A juniper, 10 ins. diam., bears N.  $61^\circ$  E., 106 lks. dist., mkd. T22NR1WS22BT

A juniper, 8 ins. diam., bears S.  $11^\circ$  E., 55 lks. dist., mkd. S27BT

A juniper, 10 ins. diam., bears S.  $44^\circ$  W., 134 lks. dist., mkd. T22NR1WS28BT

A pinon, 8 ins. diam., bears N.  $32^\circ$  W., 24 lks. dist., mkd. T22NR1WS21BT

Bury the original corner stone alongside the iron post.

Cor. is on a flat spur.

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, is monumented by a malpais stone, 6 X 12 X 14 ins., loosely set, mkd.  $\frac{1}{4}$  on the W., with a small mound of stones to the W., from which the original bearing trees

A juniper, 12 ins. diam., bears S.  $37^\circ$  E., 42 lks. dist., mkd.  $\frac{1}{4}$ SBT

A juniper, 12 ins. diam., bears S.  $22^\circ$  E., 57 lks. dist., mdk.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NR1W  
 $\frac{1}{4}$   
S21|S22

from which

1964

A juniper, 6 ins. diam., bears S.  $80^\circ$  W., 9 lks. dist., mkd.  $\frac{1}{4}$  S21BT

A juniper, 8 ins. diam., bears S.  $59^\circ$  E., 31 lks. dist., mkd.  $\frac{1}{4}$ S22BT

Bury the original corner stone alongside of the iron post.

The cor. of secs. 15, 16, 21 and 22, is monumented by a malpais stone, 6 X 8 X 14 ins., loosely set along E. side of a malpais rock in place, mkd. with 3 notches on the E. and S.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, with a collar of stones to top, with brass cap mkd.

T22NR1W  
S16|S15  
S21|S22

1964

CHAINS

from which

A juniper, 6 ins. diam., bears N. 5° E., 32 lks.  
dist., mkd. BT

A juniper, 8 ins. diam., bears S. 62° E., 49 lks.  
dist., mkd. BT

A juniper, 4 ins. diam., bears S. 75° W., 65 lks.  
dist., mkd. BT

A juniper, 6 ins. diam., bears N. 36° W., 27 lks.  
dist., mkd. BT

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, is monumented by a malpais stone, 8 X 12 X 18 ins., lying on ground, mkd.  $\frac{1}{4}$ , from which an original bearing tree

A juniper, 14 ins. diam., bears S. 46° E., 38 lks.  
dist., mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$  S15

$\frac{1}{4}$  S22

from which

1964

A juniper, 6 ins. diam., bears N. 30° E., 23 lks.  
dist., mkd.  $\frac{1}{4}$ S15BT

Build a mound of stones to the N. of the iron post.

Bury the original corner stone alongside of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, is monumented by a malpais stone, 8 X 10 X 12 ins., firmly set, mkd.  $\frac{1}{4}$  on the W., with a small mound of stones to the E., from which the original bearing trees

A juniper, 10 ins. diam., bears N. 16° E., 25 lks.  
dist., mkd. with faint scribe marks.

A juniper, 10 ins. diam., bears N. 38° W., 81 lks.  
dist., mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with a collar of stones to top, with brass cap mkd.

T22NRLW

$\frac{1}{4}$  S16 | S15

1964

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, is monumented by a malpais stone, 4 X 12 X 12 ins., loosely set in a collar of stones, mkd.  $\frac{1}{4}$  on the W., from which the original bearing trees

CHAINS

A juniper, 12 ins. diam., bears S. 86° E., 35 lks. dist., has faint scribe marks.

A juniper, 20 ins. diam., bears S. 60° W., 88 lks. dist., mkd. on a limb  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NR1W

$\frac{1}{4}$   
S20 | S21

from which

1964

A juniper, 14 ins. diam., bears S. 42° E., 45 lks. dist., mkd.  $\frac{1}{4}$ S21BT

A juniper, 20 ins. diam., bears N. 68° W., 95 lks. dist., mkd.  $\frac{1}{4}$ S20BT

Bury the original corner stone alongside the iron post.

Cor. is on an E. slope, about 7 chs. W. of a road.

The  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, is monumented by a malpais stone, 5 X 10 X 15 ins., loosely set in a collar of stones, mkd.  $\frac{1}{4}$  on the W., from which an original bearing tree

A juniper, 20 ins. diam., bears N. 45° E., 56 lks. dist., mkd. on a limb  $\frac{1}{4}$ SBT

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, with a collar of stone to top, with brass cap mkd.

T22NR1W

$\frac{1}{4}$   
S31 | S32

from which

1964

A juniper, 10 ins. diam., bears N. 58° E., 105 lks. dist., mkd.  $\frac{1}{4}$ S32BT

A juniper, 8 ins. diam., bears S. 34° W., 82 lks. dist., mkd.  $\frac{1}{4}$ S31BT

Bury the original corner stone alongside the iron post.

The cor. of secs. 29, 30, 31 and 32, is monumented by a malpais stone, 8 X 12 X 14 ins., firmly set, mkd. with 1 notch on the south and 5 notches on the east, with a mound of stone to the W., from which the original bearing trees

A juniper, 10 ins. diam., bears N. 51° E., 108 lks. dist., mkd. TXX11NR1WSXX1XBT

A juniper, 8 ins. diam., bears S. 66° E., 27 lks. dist., mkd. TXX11NR1WSXXX11BT

A juniper, 14 ins. diam., bears S. 78° W., 51 lks. dist., mkd. TXX11NR1WSXXX1BT

26

CHAINS

A pinon, 10 ins. diam., bears N. 13° W., 21 lks. dist., mkd. TXXLINR1WSXXXBT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone to the top, with brass cap mkd.

T22NRIW  
S30|S29  
S31|S32

from which

1964

A juniper, 8 ins. diam., bears N. 64° E., 67 lks. dist., mkd. T22NRIWS29BT

A juniper, 12 ins. diam., bears S. 36° E., 34 lks. dist., mkd. T22NRIWS32BT

A juniper, 10 ins. diam., bears S. 37° W., 25 lks. dist., mkd. T22NRIWS31BT

A juniper, 10 ins. diam., bears N. 51° W., 38 lks. dist., mkd. T22NRIWS30BT

Bury the original corner stone alongside the iron post.

Cor. is on a sharp rocky spur, fairly sharp break-off is 1 ch. N.

The ¼ sec. cor. of secs. 30 and 31, is monumented by a malpais stone, 6 X 10 X 14 ins. firmly set in an old mound of stones, mkd. ¼ on the N., from which the original bearing trees

A juniper, 12 ins. diam., bears N. 57° E., 25 lks. dist., mkd. ¼SBT

A juniper, 16 ins. diam., bears S. 34° E., 30 lks. dist., mkd. ¼SBT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T22NRIW  
¼ S30  
¼ S31

from which

1964

A juniper, 10 ins. diam., bears S. 73° E., 60 lks. dist., mkd. ¼S31BT

A juniper, 8 ins. diam., bears N. 12° E., 13 lks. dist., mkd. ¼S30BT

Bury the original corner stone alongside the iron post.

Cor. is on a N. slope, about 8 chs. S. of a wash, course SW.

The ¼ sec. cor. of secs. 29 and 30, is monumented by a malpais stone, 6 X 10 X 12 ins., firmly set, mkd. ¼ on the W., with a mound of stones to the W., from which the original bearing trees

CHAINS

A juniper, 12 ins. diam., bears S. 61° E., 41 lks. dist., mkd.  $\frac{1}{4}$ SBT

A juniper, 12 ins. diam., bears N. 66° W., 42 lks. dist., mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$   
S30|S29

from which

1964

A juniper, 12 ins. diam., bears S. 89° E., 64 lks. dist., mkd.  $\frac{1}{4}$  S29BT

A juniper, 12 ins. diam., bears S. 50° W., 70 lks. dist., mkd.  $\frac{1}{4}$ S30BT

Build a mound of stone to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is in a fairly level area, about 8 chs. S. of a road bearing E. and W.

The cor. of secs. 19, 20, 29 and 30, is monumented by a sandstone, 3 X 12 X 24 ins., firmly set, mkd. with 2 notches on the S. and 5 notches on the E., with a small mound of stones to the N.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 18 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T22NRLW

S19|S20  
S30|S29

from which

1964

A pinon, 3 ins. diam., bears N. 69° E., 50 lks. dist., mkd. BT

A juniper, 12 ins. diam., bears S. 10° E., 17 lks. dist., mkd. S29BT

A juniper, 12 ins. diam., bears S. 89° W., 44 lks. dist., mkd. T22NRLWS30BT

A juniper, 8 ins. diam., bears N. 14° W., 81 lks. dist., mkd. S19BT

Bury the original stone corner alongside the iron post.

Cor. is on a steep SW. slope, among sandstones.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, is monumented by a sandstone, 3 X 16 X 20 ins., loosely set in a collar of stones, mkd.  $\frac{1}{4}$  on the N., with a small mound of stones to the N.

At the cor. point

CHAINS

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T22NRLW

$\frac{1}{4}$  S20

S29

from which

1964

A juniper,  $\frac{1}{4}$  ins. diam., bears S.  $43^\circ$  E., 22 lks. dist., mkd.  $\frac{1}{4}$ S29BT

A juniper,  $\frac{1}{4}$  ins. diam., bears N.  $34^\circ$  W., 94 lks. dist., mkd.  $\frac{1}{4}$ S20BT

Bury the original corner stone alongside the iron post.

Cor. is on a S. slope, about 1.20 chs. N. of a road bearing E. and W. with a hair-pin curve to the W.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, is monumented by a sandstone,  $\frac{1}{4}$  X 12 X 30 ins., mkd.  $\frac{1}{4}$ , lying on the ground, from which an original bearing tree

A pinon, 12 ins. diam., bears S.  $30^\circ$  E., 97 lks. dist., mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T22NRLW

$\frac{1}{4}$  S19

S20

from which

1964

A pinon, 12 ins. diam., bears S.  $88^\circ$  W., 97 lks. dist., mkd.  $\frac{1}{4}$ S19BT

Bury the original corner stone alongside the iron post.

The cor. of secs. 17, 18, 19 and 20, is monumented by a malpais stone, 6 X 10 X 18 ins., loosely set, mkd. with 3 notches on the S. and 5 notches on the E.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, with collar of stones to the top, with brass cap mkd.

T22NRLW

S18

S17

S19

S20

from which

1964

A pinon, 12 ins. diam., bears N.  $3^\circ$  E., 59 lks. dist., mkd. T22NRLWS17BT

A juniper,  $\frac{1}{4}$  ins. diam., bears S.  $56^\circ$  E., 34 lks. dist., mkd. BT

A juniper, 8 ins. diam., bears S.  $59^\circ$  W., 69 lks. dist., mkd. T22NRLWS19BT

A cedar, 8 ins. diam., bears N.  $28^\circ$  W., 22 lks. dist., mkd. S18BT

TRON 4715

Township 22 North, Range 1 West, Arizona

CHAINS

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, is monumented by a sandstone, 4 X 16 X 72 ins., firmly set, mkd.  $\frac{1}{4}$  on the N., with a collar of stones, from which the original bearing trees

A juniper, 10 ins. diam., bears S. 8° W., 32 lks. dist., mkd.  $\frac{1}{4}$ SBT

A juniper, 10 ins. diam., bears N. 39° E., 60 lks. dist., mkd.  $\frac{1}{4}$ SBT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam.,  $1\frac{1}{4}$  ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T22NRLW

$\frac{1}{4}$  S17

$\frac{1}{4}$  S20

from which

1964

A juniper, 10 ins. diam., bears N. 73° E., 54 lks. dist., mkd.  $\frac{1}{4}$ S17BT

A juniper, 12 ins. diam., bears S. 51° E., 95 lks. dist., mkd. BT

Place the large original corner stone alongside the iron post and in collar of stones.

Cor. is on gentle W. slope, among sandstones.

The official record was found to be in error for many of the distances and bearings for the original bearing trees and some of the bearing trees were misnamed as to specie. The trees were properly marked and the ring growth count on the few that were tested proved the marks were made during the year of the original survey.

In all places where the original corner monuments appeared to be undisturbed, it was accepted as the true point for the corner.

BOOK 4715

Form 4-680  
(June 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES        | CAPACITY              |
|--------------|-----------------------|
| Charley Doak | Cartographic Engineer |
| Joe Sisneros | Cadastral Surveyor    |
| Claud Harris | Surveying Aide        |
| Pete Castro  | Engineering Aide      |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |
|              |                       |



3

BOOK 4715

CERTIFICATE OF SURVEY

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day of June, 1964,

I have remonumented a portion of the cadastral survey corners in cooperation with the U. S. Forest Service, in T. 22 N., R. 1 W.,

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Oct. 9, 1964 (Date)

Lester S. Mann (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date NOV 2 1964

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in T. 22N., R. 1 W., G. & S. R. Meridian, Arizona,

executed by Lester S. Mann, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

APR 20 1965 (Date)

E. J. Huntington (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)