

Form 4-679
(January 1963)

BOOK 4724
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

REMONUMENTED

CADASTRAL SURVEY CORNERS

Township 15 North, Range 4 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated April 23, 19 64, which provided for the surveys included under Group Number 415, approved April 23, 1964, and assignment instructions dated May 15, 19 64.

Survey commenced May 18, 19 64

Survey completed June 26, 19 64

BOOK 4724

Township 15 North, Range 4 East
Gila and Salt River Meridian, Arizona

13

CHAINS

The north, south and west boundaries and a portion of the subdivisional lines were surveyed in 1877 by C. B. Foster. The east 2 miles of the north boundary were resurveyed in 1916 by W. H. Richards, Jr., and the remainder was resurveyed in 1938 by Ty White and F. Kennon. Part of the west boundary was resurveyed in 1917 by S. E. Blout. The east boundary was surveyed by W. B. Kimmel in 1918.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 23, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

The cor. of secs. 13, 18, 19 and 24, T. 15 N., Rs. 3 and 4 E., is monumented by a granite stone 8x8x8 ins., loosely set in a mound of stone, mkd. with 3 notches on N. and S.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound with stones to top, brass cap mkd.

T15N
R3E R4E
S13|S18
S24|S19
1964

Deposit the original cor. stone alongside the iron post.

Raise a mound of stone W. of the iron post.

The ¼ sec. cor. of secs. 13 and 18, T. 15 N., Rs. 3 and 4 E., is monumented by a granite stone 16x12x8 ins., firmly set, mkd. ¼ on W. face, with a mound of stones alongside.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound with stones to top, brass cap mkd.

T15N
R3E R4E
¼
S13|S18
1964

2

CHAINS

Bury the original cor. stone alongside the iron post.

Raise a mound of stone W. of the iron post.

A N-S fence line bears East, 22 lks. dist.

The cor. of secs. 1, 2, 11 and 12 is monumented by a limestone 24x14x6 ins., firmly set, mkd. with 5 notches on the S. and 1 notch on the E., with a mound of stone around the cor.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T15NR4E
S 2 | S 1
S11 | S12
 1964

Deposit the original cor. stone in a mound of stone W. of the iron post.

A N-S fence line bears W., 2½ lks. dist.

The cor. of secs. 10, 11, 14 and 15 is monumented by a cobblestone 18x14x8 ins., firmly set, mkd. with 4 notches on the S. and 2 notches on the E., with a mound of stone W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR4E
S10 | S11
S15 | S14
 1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone W. of the iron post.

The cor. of secs. 2, 3, 10 and 11 is monumented by a cobblestone 12x8x8 ins., firmly set, mkd. with 5 notches on the S. and 2 notches on the E.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T15NR4E
S 3 | S 2
S10 | S11
 1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stone W. of the iron post.

CHAINS

A utility pole bears S. $86\frac{1}{2}^\circ$ E., $46\frac{1}{2}$ lks. dist.

A utility pole bears S. 83° W., $37\frac{1}{2}$ lks. dist.

A Shell Oil Co. service station bears N. 20° W., about 5.00 chs. dist.

Road intersection bears North, 150 lks. dist., from which roads bear E., W. and N.

The cor. of secs. 15, 16, 21 and 22 is monumented by a cobblestone $16 \times 10 \times 8$ ins., firmly set in a mound of stone, mkd. with 3 notches on S. and E.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound with stones to top, brass cap mkd.

T15NR4E
 $\frac{S16}{S21} | \frac{S15}{S22}$
 1964

Deposit the original cor. stone alongside the iron post.

A fence cor. bears S. 15° E., 14 lks. dist., from which fences bear E. and S.

The cor. of secs. 9, 10, 15 and 16 is monumented by a schist stone $12 \times 8 \times 3$ ins., firmly set in a mound of stone, mkd. with 4 notches on the S. and 3 notches on the E.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR4E
 $\frac{S9}{S16} | \frac{S10}{S15}$
 1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stone W. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 10 and 15 is monumented by a broken sandstone $24 \times 14 \times 3$ ins., loosely set in a scattered mound of stone, mkd. $\frac{1}{4}$ on one of the pieces.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR4E
 $\frac{1}{4} \frac{S10}{S15}$
 1964

Bury the original cor. stone alongside the iron post.

BOOK 4724

Remonumentation, Township 15 North, Range 4 East, Arizona

4

4.

CHAINS

Raise a mound of stone N. of the iron post.

A fence cor. bears E., 5 lks. dist., from which fences bear N. and E.

The $\frac{1}{4}$ sec. cor. of secs. 3 and 10 is monumented by a granite stone 12x10x6 ins., firmly set, mkd. $\frac{1}{4}$ on S. face, with a mound of stone N.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, brass cap mkd.

T15NR4E
 $\frac{1}{4}$ $\frac{S\ 3}{S10}$
 1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone N. of the iron post.

The cor. is located on old fence line bearing E. and W.

The cor. of secs. 8, 9, 16 and 17 is monumented by a limestone 24x14x5 ins., firmly set with piece of old wooden stake alongside, mkd. with 4 notches on S. and E., with a mound of stone alongside.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR4E
 $\frac{S\ 8}{S17}$ | $\frac{S\ 9}{S16}$
 1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stone W. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 9 is monumented by a limestone 16x14x4 ins., firmly set, mkd. $\frac{1}{4}$ on N. face, with a mound of stone N.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, mound with stones to top, brass cap mkd.

T15NR4E
 $\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$
 1964

Deposit the original cor. stone alongside the iron post.

Rebuild the original mound of stone N. of the iron post.

The cor. is located under a utility line bearing E. and W.

CHAINS

The cor. of secs. 29, 30, 31 and 32 is monumented by a granite stone 14x10x6 ins., firmly set, mkd. with 1 notch on the S. and 5 notches on the E., with a mound of stone W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR4E
 S30|S29
 S31|S32
 1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone W. of the iron post.

The ¼ sec. cor. of secs. 19 and 20 is monumented by a cobblestone 16x12x8 ins., loosely set in a scattered mound of stone, mkd. ¼ on one face.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound with stones to top, brass cap mkd.

T15NR4E
 ¼
 S19|S20
 1964

Deposit the original cor. stone alongside the iron post.

The cor. is located 120 lks. south of the Verde River.

The cor. of secs. 17, 18, 19 and 20 is monumented by a granite stone 16x8x8 ins., firmly set, mkd. with 5 notches on E. and 3 notches on S., with a mound of stone W. of the cor.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR4E
 S18|S17
 S19|S20
 1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone W. of the iron post.

The cor. is located on a N-S fence line about 100 lks. N. of road bearing E. and W.; a power line parallels fence.

BOOK 4724

Remonumentation, Township 15 North, Range 4 East, Arizona

6

6.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 17 and 20 is monumented by a limestone 22x14x16 ins., firmly set, mkd. $\frac{1}{4}$ on N. face with a mound of stone and a steel fence post alongside.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR4E
 $\frac{1}{4}$ $\frac{S17}{S20}$
 1964

Bury the original cor. stone and set the steel fence post alongside the iron post.

Raise a mound of stone N. of the iron post.

The cor. of secs. 7, 8, 17 and 18 is monumented by a sandstone 18x14x4 ins., firmly set in a mound of stone, mkd. with 4 notches on the S. and 5 notches on the E.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, brass cap mkd.

T15NR4E
 $\frac{S7}{S18} | \frac{S8}{S17}$
 1964

Deposit the original cor. stone in a mound of stone W. of the iron post.

A fence bearing East and West bears North, $54\frac{1}{2}$ lks. dist.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17 is monumented by a limestone 16x12x8 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground, mound with stones to top, brass cap mkd.

T15NR4E
 $\frac{1}{4}$ $\frac{S8}{S17}$
 1964

Deposit the original cor. stone in the mound alongside the iron post.

8

BOOK 4724
CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 23 day of April, 19 64,
I have remonumented cadastral survey corners in Township 15 North, Range
4 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 24, 1965
(Date)

Boyd S Owens
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in
Township 15 North, Range 4 East, of the Gila and Salt River Meridian,
Arizona,

executed by Boyd S. Owens, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JUL 6 1965
(Date)

E. L. Huntington
(Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~_____~~, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)