

Form 4-679
(January 1963)

BOOK 4753
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

OF PORTIONS

OF

Sections 6 and 7

Township 9 North, Range 19 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer, Cadastral Surveyor

Under special instructions dated March 15, 19 65, which provided for the surveys
included under Group Number 422, approved March 16, 1965,
and assignment instructions dated March 16, 19 65.

Survey commenced March 23, 19 65

Survey completed March 25, 19 65

1A

BOOK 4753 INDEX DIAGRAM

Township 9N, Range 19W,

6	5	4	3	2	1
2	2				
7	1	8	9	10	11
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4753

Township 9 North, Range 19 West, G&SRM, Arizona

16

CHAINS

Township 9 North, Range 19 West, Gila & Salt River Meridian, Arizona, within the Colorado River Indian Reservation, was originally surveyed by G. P. Harrington as shown upon the plat approved November 24, 1913. These surveys closed upon and segregated from secs. 6 and 7, a portion of the Parker Townsite.

The following field notes are those of the N1/2 mile bet. secs. 7 and 8, the S1/2 mile bet. secs. 5 and 6, and, the line bet. secs. 6 and 7, designed to restore the corners thereof in accordance with the best available evidence of their original positions.

These resurveys were requested by the Superintendent, Bureau of Indian Affairs, Colorado River Agency, Parker, Arizona.

The resurveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 15, 1965.

Only the true line bearings and distances of the resurveyed lines are given in these notes.

Dependent Resurvey, Portions, Sections 6 and 7
T. 9 N., R. 19 W., Arizona

From the 1/4 sec. cor. of secs. 7 and 8, monumented by an iron post 1 inch in diam., set, marked and witnessed as described in the official record of the 1911-12 survey.

N. 0°07' W., bet. secs. 7 and 8.

Over gently rolling land, through scattered creosote brush.

39.50 Approximate location of an underground Public Service Co. pipeline, bears approximately E. and W.

40.02 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., falls in center of paved road bearing E. and W.

Set an iron post 30 ins. long, 2-1/2 ins. diam., 6 ins. below the surface of the road, with brass cap mkd.

T9NR19W
S 6 | S 5
S 7 | S 8
1965

from which

An iron post 30 ins. long, 2-1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 45° E., 0.45 chs. dist., with brass cap mkd. R M S5 29.7 FT 1965 and an arrow pointing to the cor.

BOOK 4753

Dependent Resurvey, Portions, Sections 6 and 7
T. 9 N., R. 19 W., Arizona

2

2.

CHAINS

An iron post 30 ins. long, 2-1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45° E., 0.45 chs. dist., with brass cap mkd. R M S8 29.7 FT 1965 and an arrow pointing to the cor.

The cor. of secs. 3, 4, 9 and 10, monumented by an iron post, 1 inch diam., set, marked and witnessed as described in the official record of the 1911-12 survey, bears E., 160.16 chs. dist.

N. 0°02' W., bet. secs. 5 and 6.

Over gently rolling land, through scattered undergrowth.

40.02 The 1/4 sec. cor of secs. 5 and 6, monumented by an iron post, 1 inch diam., set, marked and witnessed as described in the official record of the 1911-12 survey.

From the cor. of secs. 5, 6, 7 and 8.

N. 89°59' W., bet. secs. 6 and 7.

Along the center of a paved road, bearing E. and W., accepted as latitudinal control for the section line.

39.99 Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist. for longitudinal control. The original 1-inch iron post for the 1/4 sec. cor. of secs. 6 and 7 was reported found and destroyed by the Arizona Public Service Co. during construction of a pipeline in their right-of-way along the S. side of the paved road.

Set an iron post, 30 ins. long, 2-1/2 ins. diam., 4 ins. below the surface of the paved road, with brass cap mkd.

T9NR19W
S 6
1/4 ———
S 7
1965

from which

An iron post, 30 ins. long, 2-1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 45° E., 0.45 chs. dist., with brass cap mkd. R M S6 29.7 FT 1965 and an arrow pointing to the cor.

An iron post, 30 ins. long, 2-1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45° E., 0.45 chs. dist., with brass cap mkd. R M S7 29.7 FT 1965 and an arrow pointing to the corner.

55.48 Point for the closing cor. of secs. 6 and 7 at the intersection with the E. bdy. of the Parker Townsite, as described below.

Set the iron post, 30 ins. long, 2-1/2 ins. diam., 4 ins. below the surface of the paved road, with brass cap mkd.

T9NR19W
S 6 C
P T ———
S 7 C
1965

BOOK 4753

Dependent Resurvey, Portions, Sections 6 and 7
T. 9 N., R. 19 W., Arizona

CHAINS

from which

An iron post, 30 ins. long, 2-1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 45° E., 0.45 chs. dist., with brass cap mkd. R M S6 29.7 FT 1965 and an arrow pointing to the corner.

A length of iron railroad rail used as a guard post at the NE. cor. of pipeline valves, bears S. 5°40' E., 0.273 chs. dist., with top of the rail mkd. X R M 18 FT and an arrow pointing to the corner.

A rotted post, 8 ins. square, bears S. 0°29' E., 7.03 chs. dist. (record). This is the best available evidence of the original cor. of secs. 4, 5, 32 and 33, Ts. 2 and 3 N., R. 1 E., of the Colorado River Base and Meridian.

A row of several old wooden posts, each 4 ins. square, at varying distances along the E. bdy. of the Parker Townsite, bears N. 0°29' W.

Road bears E. and S. 60° W.

5

BOOK 4753
CERTIFICATE OF SURVEY

I, Paul G. Bauer, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 15th day of March, 1965,
I have dependently resurveyed and retraced portions of sections 6 and 7,
Township 9 North, Range 19 West

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

October 15, 1965
(Date)

Paul G. Bauer
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date OCT 20 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the resurvey and retracement of portions of
sections 6 and 7, Township 9 North, Range 19 West, of the Gila and
Salt River Meridian in the State of Arizona,

executed by Paul G. Bauer, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JAN 3 1966
(Date)

E. S. ...
(Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.
(Date) (Chief, Division of Engineering)~~