

1

Form 4-679
(January 1963)

BOOK 4754
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

COMPLETION SURVEY

of the

Subdivision

of

Township 36 North, Range 7 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated February 14, 19 63, which provided for the surveys included under Group Number 392, approved February 20, 1963, and assignment instructions dated June 29, 19 64.

Survey commenced August 10, 19 64

Survey completed September 2, 19 64

1A

BOOK 4754

INDEX DIAGRAM

Township 36 North, Range 7 West,

(38) 6 37 36	(38) 5 25 35	(27) 4 25	(21) 8 19 19	(20) 2 8 18	(9) 1 8
7 35 34	8 24 33	9	10 18 17	11 7 16	12 6
18 32 31	17 31	16	15 15 15	14 6 14	18 5
19 30 29	20 23 29	21 22	22 14 13	23 4 12	24 4
30 28 27	29 22	28 21	27 12 11	26 3 10	25 2
31	32	33	34 10	35 1	36

CHAINS

The north boundary, the Ninth Standard Parallel North, was surveyed in 1915 by T. B. Matthews. The south and west boundaries were surveyed in 1923-24 by Hiester and Hunter. The east boundary was surveyed in 1933 by W. H. Good. Sections 16 and 32 and the North-South center line of the township were surveyed in 1954 by H. G. Parker.

The following field notes are those of the survey completing the subdivisional lines of Township 36 North, Range 7 West, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions, dated February 14, 1963.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographical position of the southeast corner of the township is: Latitude, 36°28'11.6" North and Longitude 112°59'05.5" West, as computed from ties to U.S.C&G.S. triangulation stations.

The magnetic declination was found to be 15° E.

Survey of the Subdivisional Lines
Township 36 North, Range 7 West

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°01' W., bet. secs. 35 and 36.

Asc. over gently rolling land through scattered timber.

13.70 Desc. along NE. slope.

26.30 Draw, drains irregularly E.

33.40 Draw, drains SE.

34.40 Rocky ledge, bears E. and W.

40.00 Point for the ¼ sec. cor. of secs. 35 and 36.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W

¼

S35|S36

1964

from which

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

2

2.

CHAINS

A cedar, 8 ins. diam., bears N. $88\frac{3}{4}^{\circ}$ E., 60 lks. dist., mkd. $\frac{1}{4}$ S 36 B T

A cedar, 12 ins. diam., bears S. $15\frac{3}{4}^{\circ}$ W., 14 lks. dist., mkd. $\frac{1}{4}$ S 35 B T

Build a mound of stone W. of the iron post.

Continue over rolling land through scattered to moderate timber.

61.10 Bottom of draw, drains N. 65° E.; asc. over general S. slope.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 $\frac{S26}{S35}$ | $\frac{S25}{S36}$

from which

U.S.G.S. Triangulation station SAGE bears N. 53° $15\frac{1}{2}'$ W., 25.66 chs. dist.

Build a mound of stone W. of the iron post.

Land, low rolling hills.
 Soil, rocky clay loam.
 Timber, scattered to moderate pinon and cedar.
 Undergrowth, sagebrush.

From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

S. $89^{\circ}59'$ W., bet. secs. 25 and 36.

Desc. over gentle W. slope through scattered timber and moderate sagebrush.

8.70 Wash, 10 lks. wide, 2 ft. deep, drains N. 15° W.

9.90 Fence, barbed wire, bears N. 15° W. and S. 15° E.

10.00 Track road, parallels fence; asc. over E. slope.

27.00 Continue over gently rolling land.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$ $\frac{S25}{S36}$
 1964

from which

A cedar 18 ins. diam. bears N. $74\frac{3}{4}^{\circ}$ E., 13 lks. dist., mkd. $\frac{1}{4}$ S 25 B T

CHAINS	
	<p>A cedar 10 ins. diam. bears S. $7\frac{1}{2}^{\circ}$ W., 137 lks. dist., mkd. $\frac{1}{4}$ S 36 B T</p>
	<p>Raise a mound of stone N. of the iron post.</p>
66.80	<p>Asc. over SE. slope.</p>
79.96	<p>The cor. of secs. 25, 26, 35 and 36.</p>
	<p>Land, rolling. Soil, rocky clay loam. Timber, cedar and pinon. Undergrowth, sagebrush.</p>
	<p>N. $0^{\circ}01'$ W., bet. secs. 25 and 26.</p>
	<p>Over rolling land through scattered timber and heavy sagebrush.</p>
9.20	<p>Enter moderate timber.</p>
30.00	<p>Desc. over gentle N. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ S26 S25 1964</p>
	<p>from which</p>
	<p>A pinon 6 ins. diam., bears S. $40\frac{1}{4}^{\circ}$ E., 93 lks. dist., mkd. T 36 N R 7 W $\frac{1}{4}$ S 25 B T</p>
	<p>A pinon 10 ins. diam. bears S. $57\frac{1}{2}^{\circ}$ W., 21 lks. dist., mkd. T 36 N R 7 W $\frac{1}{4}$ S 26 B T</p>
56.70	<p>Desc. along W. slope,</p>
62.70	<p>Slope changes to N.; desc.</p>
63.20	<p>Draw, drains W.; asc. over gentle S. slope.</p>
67.10	<p>Fence, barbed wire, bears N. 75° W. and S. 75° E.</p>
70.50	<p>Ridge, bears E. and W.; desc. over steep N. slope.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T36NR7W S23 S24 S26 S25 1964</p>
	<p>from which</p>
	<p>A pinon 8 ins. diam. bears S. $64\frac{1}{2}^{\circ}$ E., 20 lks. dist., mkd. T 36 N R 7 W S 25 B T</p>
	<p>A cedar 13 ins. diam. bears S. 42° W., 33 lks. dist., mkd. T 36 N R 7 W S 26 B T</p>

BOOK 4754

Subdivision, T. 36 N, R. 7 W., Arizona

4

4.

CHAINS

A cedar 8 ins. diam. bears N. $48\frac{1}{2}^{\circ}$ W., 55 lks.
dist., mkd. T 36 N R 7 W S 23 B T

Raise a mound of stone W. of the iron post.

Land, low rolling mountains.
Soil, rocky clay loam.
Timber, moderate cedar and pinon.
Undergrowth, moderate sagebrush.

From the cor. of secs. 19, 24, 25 and 30 on the E. bdy.
of the Tp., an iron post 2 ins. diam., set, mkd. and
witnessed as described in the official record. This
cor. is located at fence cor.; fences bear E. and SW.

N. $89^{\circ}58'$ W., bet. secs. 24 and 25.

Asc. over E. slope through scattered timber.

6.10 Spur, slopes N.

14.30 Small wash, drains irregularly N.; thence, over rolling
land through moderate timber.

25.10 Asc. over NE. slope.

31.60 Top of ascent, bears NW. and SE.; continue over gently
rolling land through scattered timber.

40.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$ $\frac{S24}{S25}$
1964

Raise a mound of stone N. of the iron post.

54.10 Asc. through moderate to heavy timber.

66.50 Top of ascent, bears NE. and SW.; desc. over NW. slope.

74.00 Continue along base of N. slope.

80.06 The cor. of secs. 23, 24, 25 and 26.

Land, low rolling mountains.
Soil, rocky clay loam.
Timber, moderate cedars and pinons.
Undergrowth, moderate sagebrush.

N. $0^{\circ}01'$ W., bet. secs. 23 and 24.

Over rolling land through moderate timber.

8.70 Bladed road, bears N. 80° W. and S. 80° E.; asc. over
S. slope.

13.70 Top of ascent, bears E. and W.

23.20 Bottom of draw, drains irregularly E.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T36NR7W $\frac{1}{4}$ S23 S24 1964</p> <p>Raise a mound of stone W. of the iron post.</p> <p>Continue over gently rolling land through scattered timber.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T36NR7W S14 S13 S23 S24 1964</p> <p>from which</p> <p style="padding-left: 40px;">A pinon 10 ins. diam. bears N. $23\frac{3}{4}^{\circ}$ E., 107 lks. dist., mkd. T 36 N R 7 W S 13 B T</p> <p style="padding-left: 40px;">A cedar 8 ins. diam. bears S. $82\frac{3}{4}^{\circ}$ W., 103 lks. dist., mkd. T 36 N R 7 W S 23 B T</p> <p>Raise a mound of stone W. of the iron post.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, moderate to scattered cedar and pinon. Undergrowth, sagebrush and cacti.</p>
27.50	<p>Trail road, bears N. 10° E. and S. 10° W.; asc. E. slope.</p>
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T36NR7W $\frac{1}{4}$ S13 S24 1964</p> <p>Raise a mound of stone N. of the iron post.</p>
62.50	<p>Small spur, slopes N. 30° E.</p>

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

6.

6

CHAINS	
67.00	Draw, drains NE.; asc. E. slope.
72.60	Top of asc., bears N. and S.; thence over nearly level land.
80.08	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, gently rolling. Soil, clay loam. Timber, scattered cedar and pinon. Undergrowth, moderate to heavy sage brush.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p>
	<p>Over gently rolling land through scattered timber and moderate undergrowth.</p>
14.90	Draw, drains irregularly NE.
40.00	<p>Point for the ¼ sec. cor. of secs. 13 and 14.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T36NR7W ¼ S14 S13 1964</p>
	<p>Raise a mound of stone W. of the iron post.</p>
	<p>Continue over gently rolling land through heavy sage.</p>
57.20	Desc. over N. slope.
76.10	Small wash in bottom of draw, drains NW.; asc. over gentle SW. slope.
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T36NR7W S11 S12 S14 S13 1964</p>
	<p>Raise a mound of stone W. of the iron post.</p>
	<p>Land, gently rolling. Soil, clay loam and rocky. Timber, scattered to widely scattered cedar and pinon. Undergrowth, moderate to heavy sage brush.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.</p>
	<p>S. 89°58' W., bet. secs. 12 and 13.</p>
	<p>Over gently rolling range land.</p>
2.00	Head of small draw, drains N. curving to N. 60° E.

CHAINS	
6.00	Head of small draw, drains N. 60° E.; thence over nearly level land.
32.00	Desc. over gentle W. slope.
39.99	Point for the ¼ sec. cor. of secs. 12 and 13.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ $\frac{S12}{S13}$ 1964</p>
	Raise a mound of stone N. of the iron post.
45.80	Draw, drains N. 20° W.; enter scattered timber, mostly dead.
48.70	Track road, bears N. 30° W. and S. 30° E.; thence over gently rolling N. slope.
70.00	Desc. over gentle W. slope.
79.98	The cor. of secs. 11, 12, 13 and 14.
	<p>Land, gently rolling. Soil, clay loam and rocky. Timber, widely scattered juniper and pinon. Undergrowth, moderate sage.</p>
	N. 0°01' W., bet. secs. 11 and 12.
	Over nearly level land through heavy sagebrush and scattered timber.
8.00	Leave timber.
39.00	Enter scattered timber.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ S11 S12 1964</p>
	from which
	<p style="padding-left: 40px;">A cedar 12 ins. diam., bears S. 81½° E., 25 lks. dist., mkd. ¼ S 12 B T</p>
	<p style="padding-left: 40px;">A cedar 10 ins. diam. bears N. 51½° W., 51 lks. dist., mkd. ¼ S 11 B T</p>
	Desc. over N. slope.
46.70	Draw, drains W.
63.30	Draw, drains N. 70° W.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

8

8.

CHAINS		
70.60	Leave scattered timber, enter nearly level land.	
80.00	Point for the cor. of secs. 1, 2, 11 and 12.	
	Set the iron post, 20 ins. in the ground, cap mkd.	
	T36NR7W $\frac{S\ 2}{S11} \frac{S\ 1}{S12}$ 1964	
	Raise a mound of stone W. of the iron post.	
	Land, gently rolling. Soil, clay loam and rocky. Timber, scattered to widely scattered juniper and pinon. Undergrowth, sage and yellow brush.	
	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.	
	N. 89°54' W., bet. secs. 1 and 12.	
	Over nearly level range land.	
29.40	Asc. over NE. slope through scattered timber.	
37.90	Top of ascent, bears NW. and SE.; thence over nearly level land through moderate undergrowth.	
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.	
	Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.	
	T36NR7W $\frac{1}{4} \frac{S\ 1}{S12}$ 1964	
	Raise a mound of stone N. of the iron post.	
47.30	Desc. over NW. slope through moderate timber.	
53.90	Desc. over gentle W. slope through scattered timber.	
70.30	Small wash, drains irregularly N.	
74.10	Leave timber bearing NE. and SW.; continue over nearly level land.	
79.94	The cor. of secs. 1, 2, 11 and 12.	
	Land, rolling. Soil, clay loam. Timber, scattered to moderate cedar and pinon. Undergrowth, sage brush and yellow brush.	
	N. 0°01' W., bet. secs. 1 and 2.	
	Over gently rolling land through moderate undergrowth.	

CHAINS

- 3.40 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.
- 8.00 Asc. over gentle SE. slope.
- 30.50 Desc. over gentle NW. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.
- Set the iron post 22 ins. in the ground, cap mkd.
- T36NR7W
 $\frac{1}{4}$
S 2 | S 1
1964
- Deposit glass in the hole alongside the iron post.
- 49.70 Draw, drains N. 70° E.
- 55.30 Draw, drains SE.; asc. over S. slope.
- 61.30 Top of ascent, bears NE. and SW.
- 67.60 Draw, drains irregularly W.
- 74.50 Desc. over general N. slope.
- 78.36 Intersect the Ninth Standard Parallel North.
- Point for the closing cor. of secs. 1 and 2, T. 36 N., R. 7 W.
- Set the iron post 22 ins. in the ground, cap mkd.
- T37NR7W
S36
S 2 | S 1
T36NR7W
C C
1964
- Raise a mound of stone S. of the cor.
- From point of intersection the standard cor. of secs. 35 and 36, T. 37 N., R. 7 W., bears West, 12.51 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record.
- Land, gently rolling.
Soil, gravelly clay loam.
No timber; undergrowth, black brush, shadscale and grass.
-
- The point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.
- At the cor. point
- Set the iron post 22 ins. in the ground, cap mkd.
- $\frac{1}{4}$ S 1
T36NR7W
1964

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

10

10.

CHAINS

Raise a mound of stone S. of the iron post.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 37 N., R. 7 W., bears West, 12.50 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.

From the $\frac{1}{4}$ sec. cor. of sec. 1 an East-West fence bears North, 3 lks. dist.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°01' W., bet. secs. 34 and 35.

Over rolling mountainous land through moderate undergrowth and scattered timber.

36.00 Ravine, steep sides, drains irregularly W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set the iron post over an "X" cut in solid rock, mound with stones to top, cap mkd.

T36NR7W
 $\frac{1}{4}$
 S34|S35
 1964

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T36NR7W
 S27|S26
 S34|S35
 1964

Land, mountainous.
 Soil, rocky clay loam.
 Timber, scattered juniper and pinon.
 Undergrowth, moderate sagebrush, grass and shadscale.

From the cor. of secs. 25, 26, 35 and 36.

N. 89°55' W., bet. secs. 26 and 35.

Asc. over E. slope through scattered timber and heavy undergrowth.

4.00 Asc. over SE. slope.

18.00 Wide rolling spur, slopes S.; desc. along general S. slope.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.

Set the iron post 22 ins. in the ground, cap mkd.

CHAINS	
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ $\frac{S26}{S35}$ 1964</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 11° E., 57 lks. dist., mkd. $\frac{1}{4}$ S 26 B T</p> <p>Raise a mound of stone N. of the iron post.</p> <p>41.00 Small draw, drains S.; desc. over SW. slope.</p> <p>63.00 Asc. over NE. slope.</p> <p>66.00 Spur, slopes N.; desc. over W. slope.</p> <p>71.90 Enter draw draining W.</p> <p>78.50 Draw, curves to S.; asc. over E. slope.</p> <p>79.96 The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, low rolling hills. Soil, rocky clay loam. Timber, scattered pinon and junipers. Undergrowth, moderate to heavy sage and grass.</p> <hr/> <p>S. 89°57' W., bet. secs. 27 and 34.</p> <p>Over rolling rocky land through scattered timber and moderate undergrowth.</p> <p>Asc. over E. slope.</p> <p>1.30 Top of ascent, bears N. and S.; desc. over W. slope.</p> <p>12.40 Bladed road, bears N. and S.; continue over gently rolling land.</p> <p>39.00 Fence, barbed wire, bears N. 35° W. and S. 35° E.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T36NR7W $\frac{1}{4}$ $\frac{S27}{S34}$ 1964</p> <p>Raise a mound of stone N. of the iron post.</p> <p>80.00 The cor. of secs. 27, 28, 33 and 34, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, moderate sagebrush and grass.</p> <hr/>

CHAINS

From the cor. of secs. 26, 27, 34 and 35.

N. 0°01' W., bet. secs. 26 and 27.

Asc. along E. slope through scattered timber.

16.00 Top of ascent; continue over gently rolling land.

21.00 Desc. over N. slope.

31.20 Enter nearly level land; leave timber.

36.90 Bladed road from Fredonia to Tuweep, bears NE. and SW.

40.00 Point for the ¼ sec. cor. of secs. 26 and 27.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W

¼

S27|S26

1964

Raise a mound of stone W. of the iron post.

41.00 Asc. over S. slope.

46.00 Top of ascent, bears E. and W.; thence over gently rolling land through heavy undergrowth.

55.20 Track road, bears NE. and SW.

60.70 Fence, barbed wire, bears N. 65° E. and S. 65° W.

71.00 Enter moderate to heavy timber.

80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W

S22|S23

S27|S26

1964

from which

A cedar 15 ins. diam. bears N. 37¼° E., 59 lks. dist., mkd. T36N R7W S 23 B T

A cedar 13 ins. diam. bears S. 23¼° W., 93 lks. dist., mkd. T36N R7W S 27 B T

Raise a mound of stone W. of the iron post.

Land, rolling.

Soil, rocky clay loam.

Timber, scattered to heavy juniper.

Undergrowth, moderate sagebrush and grass.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°54' W., bet. secs. 23 and 26.

CHAINS	
	Asc. over NE. slope through moderate timber.
5.00	Spur, slopes N.; desc. over gentle W. slope.
11.70	Small wash, drains N.
23.50	Asc. over NE. slope through scattered timber.
31.10	Spur, slopes N.; thence, along N. slope.
36.00	Desc. over NW. slope.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	Set the iron post 22 ins. in the ground, cap mkd.
	T36NR7W $\frac{1}{4}$ $\frac{S23}{S26}$ 1964
	Raise a mound of stone N. of the iron post.
44.20	Fence, bears N. and S.; leave timber, continue over gently rolling land through moderate sagebrush.
48.80	Bladed road, from Fredonia to Tuweep, bears S. 60° W. and N. 60° E.
49.00	Fence, 4-strand barbed wire, bears N. 60° E. and S. 60° W.
75.90	Enter moderate timber, bears N. and S.
79.90	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling. Soil, clay loam and rocky. Timber, scattered to moderate juniper and pinon. Undergrowth, moderate sagebrush and grass.
	S. 89°56' W., bet. secs. 22 and 27.
	Desc. over rolling land through moderate to heavy timber.
3.30	Desc. over NW. slope.
15.30	Enter gently rolling land, scattered timber.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	Set the iron post 22 ins. in the ground, cap mkd.
	T36NR7W $\frac{1}{4}$ $\frac{S22}{S27}$ 1964
	Raise a mound of stone N. of the iron post.
	Continue over nearly level land.
80.00	The cor. of secs. 21, 22, 27 and 28, monumented by an iron post 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

14.

14

CHAINS	
	<p>Land, rolling to nearly level. Soil, clay loam and rocky. Timber, moderate to scattered cedar. Undergrowth, moderate sage, grass and cacti.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27. N. 0°01' W., bet. secs. 22 and 23. Over rolling land through moderate timber.</p>
22.30	Desc. over general N. slope.
29.20	Draw, drains N. 30° W.; asc. over SW. slope.
35.20	Desc. over NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23. Set the iron post 22ins. in the ground and in a collar of stone, cap mkd.
	<p>T36NR7W ¼ S22 S23 1964</p>
41.90	Leave timber; enter gently rolling land, moderate undergrowth.
47.60	Wash, 10 lks. wide, 4 ft. deep, drains irregularly N.
55.00	Wash curves to NE.; asc. over S. slope.
62.70	Slope changes to rolling E.; desc.
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set the iron post 22 ins. in the ground, cap mkd.
	<p>T36NR7W S15 S14 S22 S23 1964</p>
	<p>Raise a mound of stone W. of the iron post. Land, gently rolling. Soil, clay loam and rocky. Timber, heavy to scattered juniper. Undergrowth, moderate sagebrush and cacti.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24. N. 89°54' W., bet. secs. 14 and 23. Over rolling land through scattered timber and heavy undergrowth.</p>
5.40	Asc. over gentle NE. slope.
20.00	Top of ascent, bears N. 30° W. and S. 30° E.; continue over top of low hill.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

15.

CHAINS

- 39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
Set the iron post 22 ins. in the ground, cap mkd.
- T36NR7W
 $\frac{1}{4} \frac{S14}{S23}$
1964
- Raise a mound of stone N. of the iron post.
- 41.90 Fence, 4-strand barbed wire, bears N. and S.
- 48.40 Desc. over general W. slope.
- 57.60 Bottom of draw, drains N. 30° W.; asc. over E. slope.
- 60.70 Top of ascent, bears N. and S.; desc. over W. slope.
- 66.00 Bottom of draw, drains N. 20° E.; asc. over E. slope.
- 79.96 The cor. of secs. 14, 15, 22 and 23.
- Land, gently rolling.
Soil, clay loam and rocky.
Timber, scattered juniper.
Undergrowth, moderate sagebrush, grass and cacti.
-
- S. 89°59' W., bet. secs. 15 and 22.
- Asc. over E. slope through moderate undergrowth.
- 6.00 Top of ascent, bears N. 10° E. and S. 10° W.; continue over rolling land.
- 39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.
Set the iron post 22 ins. in the ground, cap mkd.
- T36NR7W
 $\frac{1}{4} \frac{S15}{S22}$
1964
- Raise a mound of stone N. of the iron post.
- 52.40 Reservoir bears North, 160 lks. dist.
- 79.88 The cor. of secs. 15, 16, 21 and 22, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
- Land, rolling.
Soil, clay loam and rocky.
Timber, widely scattered juniper.
Undergrowth, moderate sagebrush and grass.
-
- From the cor. of secs. 14, 15, 22 and 23.
- N. 0°01' W., bet. secs. 14 and 15.
- Over gently rolling land through heavy undergrowth and scattered timber.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

16.

16

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T36NR7W $\frac{1}{4}$ S15 S14 1964</p> <p>Raise a mound of stone W. of the iron post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T36NR7W S10 S11 S15 S14 1964</p> <p>from which</p> <p style="padding-left: 40px;">A cedar 14 ins. diam. bears N. $49\frac{3}{4}^{\circ}$ E., 16 lks. dist., mkd. T36N R7W S11 B T</p> <p style="padding-left: 40px;">A cedar 20 ins. diam. bears S. 36° W., 44 lks. dist., mkd. T36N R7W S15 B T</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, scattered cedars. Undergrowth, moderate to heavy sagebrush, grass and cacti.</p>
	<hr/>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p>
	<p>N. $89^{\circ}58'$ W., bet. secs. 11 and 14.</p>
	<p>Desc. over W. slope through scattered timber.</p>
3.60	<p>Bottom of draw, drains NW.; asc. over NE. slope.</p>
17.50	<p>Top of ascent, bears NW. and SE.; thence over top of spur projecting N.</p>
22.50	<p>Desc. over NW. slope.</p>
30.70	<p>Bottom of draw, drains NE.; continue over gently rolling land.</p>
39.98	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T36NR7W $\frac{1}{4}$ S11 S14 1964</p>
	<p>from which</p> <p style="padding-left: 40px;">A cedar 12 ins. diam. bears N. $44\frac{1}{2}^{\circ}$ E., 110 lks. dist., mkd. $\frac{1}{4}$ S11 B T</p>

CHAINS	
	<p>A cedar 6 ins. diam. bears S. 67° W., 76 lks. dist., mkd. $\frac{1}{4}$ S14 B T</p> <p>Raise a mound of stone N. of the iron post.</p> <p>Continue along gentle N. slope through scattered to moderate timber.</p>
41.60	Fence, 4-strand barbed wire, bears N. and S.
50.30	Small wash, drains N.
69.00	Desc. over gentle W. slope.
76.20	Wash, 15 lks. wide, 1 ft. deep, drains N.
79.96	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, rolling. Soil, rocky clay loam. Timber, scattered to moderate cedar and pinon. Undergrowth, sagebrush, grass and cactus.</p>
	<p>S. 89°58' W., bet. secs. 10 and 15.</p> <p>Asc. over SE. slope through widely scattered timber and moderate undergrowth.</p>
19.00	Continue along rolling S. slope.
22.90	Draw, drains S. 25° W.
28.60	Desc. over steep SW. slope.
39.00	Small wash, drains SW.; thence over gentle SW. slope.
39.87	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p>T36NR7W $\frac{1}{4}$ $\frac{S10}{S15}$ 1964</p>
	Raise a mound of stone N. of the iron post.
63.10	Track road, bears NW. and SE.; continue over nearly level land.
79.74	The cor. of secs. 9, 10, 15 and 16, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	<p>Land, nearly level on W 1/2 mile, south end of mountain on E 1/2 mile. Soil, rocky clay loam.</p>

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

18

18.

CHAINS

Timber, widely scattered junipers on extreme east portion, none on remainder.
Undergrowth, sagebrush, cactus and grass.

From the cor. of secs. 10, 11, 14 and 15.

N. 0°01' W., bet. secs. 10 and 11.

Over gently rolling land through moderate undergrowth.

18.20 Wash, 10 lks. wide, 2 ft. deep, drains SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$
S10|S11
1964

Raise a mound of stone W. of the iron post.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
S 3|S 2
S10|S11
1964

Raise a mound of stone W. of the iron post.

Land, gently rolling.
Soil, clay loam and rocky.
No timber; undergrowth, moderate sagebrush, cactus and grass.

From the cor. of secs. 1, 2, 11 and 12.

N. 89°58' W., bet. secs. 2 and 11.

Over gently rolling land.

30.00 Asc. over E. slope.

35.00 Top of ascent, bears N. 20° W. and S. 35° E.; thence over nearly level land.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$ S 2
S11
1964

CHAINS	
	Raise a mound of stone N. of the iron post.
42.20	Fence, 4-strand barbed wire, bears N. and S.
80.00	The cor. of secs. 2, 3, 10 and 11.
	Land, gently rolling. Soil, rocky and sandy clay loam. No timber; undergrowth, scattered brush, moderate grass.
	S. 89°57' W., bet. secs. 3 and 10.
	Over gently rolling land.
6.00	Desc. over gentle W. slope.
8.00	Enter swale draining N.
22.00	Asc. over gentle E. slope.
27.00	Continue over gently rolling land.
39.81	Point for the ¼ sec. cor. of secs. 3 and 10.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T36NR7W S 3 ¼ — S10 1964
	from which
	A stock pond bears N. 36° W., 60.50 chs. dist.
50.00	Desc. over NW. slope.
58.50	Small wash, drains irregularly N.
78.50	Draw, drains NE.
79.62	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, gently rolling. Soil, clay loam and rocky. No timber; undergrowth, moderate grass, sagebrush and cacti.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 0°01' W., bet. secs. 2 and 3.
	Over gently rolling land.
29.00	Desc. over N. slope through scattered timber.
34.20	Wash, 10 lks. wide, 4 ft. deep, drains N. 70° E.; asc. over S. slope.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

20

20.

CHAINS	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ S 3 S 2 1964</p>
	Raise a mound of stone W. of the iron post.
44.50	Continue along rolling E. slope.
49.00	Desc. over N. slope.
51.50	Draw, drains N. 60° E.; asc. over S. slope.
66.00	Top of ascent, bears E. and W.; thence over nearly level land.
78.44	Intersect the Ninth Standard Parallel North.
	Point for the closing cor. of secs. 2 and 3, T. 36 N., R. 7 W.
	Set the iron post 3 ins. in the ground to bedrock, mound with stones to top, cap mkd.
	<p style="text-align: center;">T37NR7W <u>S35</u> S 3 S 2 T36NR7W C C 1964</p>
	From the point of intersection the standard cor. of secs. 34 and 35, T. 37 N., R. 7 W., bears West, 12.46 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, gently rolling. Soil, clay loam and rocky. Timber, scattered juniper. Undergrowth, grass cacti and sagebrush.
	The point for the N. $\frac{1}{4}$ sec. cor. of secs. 2 is at mid-point and on the N. bdy. of the Tp.
	At the cor. point
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;"><u>$\frac{1}{4}$ S 2</u> T36NR7W 1964</p>
	Raise a mound of stone S. of the iron post.
	From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 37 N., R. 7 W., bears West, 12.48 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.

CHAINS

From the $\frac{1}{4}$ sec. cor. of sec. 2 an East-West fence bears North, 5 lks. dist.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3 is at mid-point and on the N. bdy. of the Tp.

At the cor. point

Set the iron post 20 ins. in the ground, cap mkd.

$\frac{1}{4}$ S 3
 T36NR7W
 1964

Raise a mound of stone S. of the iron post.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 37 N., R. 7 W., bears West, 12.67 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.

From the cor. of secs. 27, 28, 33 and 34.

N. $89^{\circ}57'$ W., bet. secs. 28 and 33.

Over gently rolling land through scattered timber and dense undergrowth.

- 8.00 Leave timber.
 - 15.30 Wash, 10 lks. wide, 3 ft. deep, drains NW.
 - 19.20 Track road, bears NW. and SE.
 - 21.90 Track road, bears NE. and SW.
 - 24.30 Wash, 30 lks. wide, 3 ft. deep, drains irregularly SE.
 - 28.20 Bladed road, bears N. and S.; enter widely scattered timber.
 - 38.60 Fence cor., fences bear N. 65° E. and W.
 - 40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.
- Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$ $\frac{S28}{S33}$
 1964

from which

A cedar 24 ins. diam. bears N. $31\frac{1}{4}^{\circ}$ E., 119 lks. dist., mkd. $\frac{1}{4}$ S28 B T

Raise a mound of stone N. of the iron post.

- 65.00 Center of reservoir bears North, 110 lks. dist.
- 70.00 Enter scattered timber.

CHAINS	
80.04	<p>The cor. of secs. 28, 29, 32 and 33, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record.</p>
	<p>Land, gently rolling. Soil, rocky clay loam. Timber, scattered to widely scattered cedar and pinon. Undergrowth, moderate sagebrush and cacti.</p>
	<hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p>
	<p>Over gently rolling land through scattered timber.</p>
6.50	<p>Small draw, drains S. 60° E.; asc. over S. slope.</p>
15.10	<p>Low spur, slopes S. 70° E.; thence over gently rolling land through moderate timber.</p>
35.60	<p>Small wash, drains S. 60° E.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 28 and 29. Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T36NR7W ¼ S29 S28 1964</p>
	<p>from which</p>
	<p style="text-align: center;">A cedar 14 ins. diam., bears N. 20¼° E., 61 lks. dist., mkd. ¼ S28 B T</p>
	<p>Raise a mound of stone W. of the iron post.</p>
53.00	<p>Leave timber, bears W. and NE.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T36NR7W S20 S21 S29 S28 1964</p>
	<p>Raise a mound of stone W. of the iron post.</p>
	<p>Land, gently rolling. Soil, clay loam and rocky. Timber, scattered to moderate cedar and pinon. Undergrowth, moderate sagebrush and grass.</p>
	<hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p>
	<p>S. 89°57' W., bet. secs. 21 and 28.</p>
	<p>Over rolling land through moderate undergrowth.</p>
10.30	<p>Bottom of volcanic crater about 3.00 chs. diam.</p>

CHAINS	
27.00	Enter timber bearing NE. and SW.
30.00	Small reservoir bears North about 10.00 chs. dist.; desc. over W. slope.
35.80	Draw, drains N. 15° E.
40.02	Point for the ¼ sec. cor. of secs. 21 and 28.
	Set the iron post 20 ins. in the ground, cap mkd.
	T36NR7W ¼ $\frac{S21}{S28}$ 1964
	from which
	The center of a reservoir bears S. 30° E., 2.50 chs. dist.
	Raise a mound of stone N. of the iron post.
42.70	Small wash, drains SE.
46.40	Bladed road, bears N. and S.; continue over nearly level land.
53.30	Asc. over gentle E. slope through moderate timber.
69.00	Leave timber bearing NW. and S.; thence over nearly level land through dense sagebrush.
80.04	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Soil, rocky clay loam. Timber, moderate to scattered cedar and pinon. Undergrowth, moderate sagebrush and grass.
	N. 0°01' E., bet. secs. 20 and 21.
	Over nearly level land through moderate undergrowth.
9.80	Desc. over N. slope.
15.60	Track road, bears E. and W.
17.80	Bottom of swale, drains E. curving to SE.; asc. over S. slope through scattered clumps of timber.
25.80	Top of ascent; continue over gently rolling land.
40.00	Point for the ¼ sec. cor. of secs. 20 and 21.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	T36NR7W ¼ S20 S21 1964
	from which

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

24.

24

CHAINS		
	<p>A cedar limb 8 ins. diam. bears N. $3\frac{3}{4}^{\circ}$ E., 79 lks. dist., mkd. $\frac{1}{4}$ S21 B T</p> <p>The center of a reservoir bears S. $36^{\circ}39'$ E., 32.70 chs. dist.</p> <p>Raise a mound of stone W. of the iron post.</p>	
43.00	Small draw, about 3.00 chs. from head, drains NE.	
50.70	Small draw, drains E. circling to N.	
53.70	Spur, slopes E. about 3.00 chs. to end.	
62.70	Small draw, drains N. 30° E.	
73.40	Small wash, drains E.	
76.70	Small wash, drains E.; asc. over gentle S. slope.	
80.00	<p>The cor. of secs. 16, 17, 20 and 21, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, scattered clumps of cedar and pinon. Undergrowth, moderate sagebrush and grass.</p>	
	<p>From the cor. of secs. 8, 9, 16 and 17, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>N. $0^{\circ}03'$ W., bet. secs. 8 and 9.</p> <p>Over rolling land through moderate sagebrush.</p>	
3.90	Wash, 15 lks. wide, 1 ft. deep, drains N. 30° E. from irregularly S.; asc. over S slope.	
12.00	Rocky spur, slopes E.	
14.60	Small draw, drains E.	
19.60	Spur, slopes E.; desc. over gently rolling land.	
35.90	Track road, bears NW. and SE.	
38.40	Wash, 20 lks. wide, 5 ft. deep, drains NW.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ S 8 S 9 1964</p>	
	<p>from which</p> <p>The center of a reservoir bears S. 38° E., 10 chs. dist.</p>	

BOOK 4754

Subdivision, T. 36 N., R 7 W., Arizona

CHAINS	
	Raise a mound of stone W. of the iron post.
60.30	The center of a reservoir bears West, 2.50 chs. dist.; desc. over rim bearing N. 15° E. and S. 15° W.
64.30	Same wash, 10 lks. wide, 6 ft. deep, drains N. 15° E.
76.00	Same wash, drains NW.
79.40	Rocky spur, slopes W.; desc. over N. slope.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set the iron post 22 ins. in the ground, cap mkd.
	T36NR7W S 5 S 4 S 8 S 9 1964
	Raise a mound of stone W. of the iron post.
	Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, moderate sagebrush and grass.
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°56' W., bet. secs. 4 and 9.
	Over gently rolling land through moderate undergrowth.
40.16	Point for the ¼ sec. cor. of secs. 4 and 9.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T36NR7W ¼ S 4 S 9 1964
	from which
	The center of a reservoir bears S. 24° E., 5.00 chs. dist.
73.40	Small draw, drains N.
76.40	Desc. over W. slope.
80.32	The cor. of secs. 4, 5, 8 and 9.
	Land, gently rolling. Soil, rocky clay loam. No timber; undergrowth, sagebrush, grass and snake weed.
	N. 0°03' W., bet. secs. 4 and 5.
	Desc. over N. slope.

CHAINS	
1.40	Bottom of narrow draw, near head, drains SW.; asc. over steep ledges of lava rock facing S.
2.50	Top of ledges, bears E. and W.; continue over gently rolling land.
10.80	Desc. over steep, rocky N. slope.
13.00	Enter canyon bottom, no definite channel, drains N. 25° E.
27.70	Asc. over steep, broken SE. slope.
38.30	Rocky point, projects E., 1.00 chain to end.
39.30	Desc. over N. slope through scattered timber.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ S 5 S 4 1964</p>
	from which
	<p style="text-align: center;">A pinon, 14 ins. diam., bears S. 12° E., 33 lks. dist., mkd. $\frac{1}{4}$ S4 B T</p>
	<p style="text-align: center;">A pinon, 8 ins. diam., bears N. 58$\frac{1}{2}$° W., 69 lks. dist., mkd. $\frac{1}{4}$ S5 B T</p>
	Raise a mound of stone W. of the iron post.
42.70	Enter rolling land.
58.40	Same canyon bottom as one given at 13.00 chs., drains W.; thence over rolling land, general W. drainage.
78.57	Intersect the Ninth Standard Parallel North.
	Point for the closing cor. of secs. 4 and 5, T. 36 N., R. 7 W.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T37NR7W <u>S33</u> S 5 S 4 T36NR7W C C 1964</p>
	Raise a mound of stone S. of the iron post.
	From the point of intersection the standard cor. of secs. 32 and 33, T. 37 N., R. 7 W., bears West, 12.46 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record.

CHAINS

Land, rolling and slightly broken.
Soil, rocky clay loam.
Timber, scattered pinon and cedar.
Undergrowth, moderate sagebrush and grass.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 4 is at mid-point and on the N. bdy. of the Tp.

At the cor. point

Set the iron post 22 ins. in the ground, cap mkd.

$\frac{1}{4}$ S 4
T36NR7W
1964

Raise a mound of stone S. of the iron post.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 37 N., R. 7 W., bears West, 12.67 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.

From the cor. of secs. 29, 30, 31 and 32, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. The cor. is located 8 lks. N. of E-W fence line.

S. $89^{\circ}55'$ W., bet. secs. 30 and 31.

Over gently rolling land through scattered timber.

22.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.

24.00 Asc. over steep E. slope.

29.50 Wash, 10 lks. wide, 2 ft. deep, drains SE.; continue steep ascent.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T36NR7W
 $\frac{1}{4}$ $\frac{S30}{S31}$
1964

from which

A pinon 8 ins. diam. bears N. $51\frac{3}{4}^{\circ}$ W., 66 lks. dist., mkd. $\frac{1}{4}$ S30 B T

An E-W fence bears South, 10 lks. dist.

48.20 Asc. along rolling S. slope.

53.20 Desc. over SW. slope.

74.50 Small wash, drains S.; asc. over gentle E. slope.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

28

28.

CHAINS

77.96

The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record. This cor. is located on E-W fence line.

Land, mountainous.
Soil, rocky clay loam.
Timber, moderate juniper and pinon.
Undergrowth, moderate sagebrush.

From the cor. of secs. 29, 30, 31 and 32.

N. 0°03' W., bet. secs. 29 and 30.

Over gently rolling land through scattered timber and moderate undergrowth, along W. side of N-S fence.

17.70

Small wash, drains E.; enter moderate timber.

26.10

Small wash, drains N. 60° E.

26.90

Small wash, drains E.

31.70

Small wash, drains E.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$
S30|S29
1964

from which

A cedar 6 ins. diam. bears S. 86 $\frac{3}{4}$ ° E., 34 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S29 B T

A pinon 8 ins. diam. bears S. 32 $\frac{1}{2}$ ° W., 43 lks. dist., mkd. $\frac{1}{4}$ S30 B T

Raise a mound of stone W. of the iron post.

40.10

Small wash, drains N. 70° E.

43.50

Small wash, drains E.

46.60

Wash, 10 lks. wide, steep sloping banks, drains E.

54.80

Wash, 10 lks. wide, steep sloping banks, drains N. 70° E.

65.80

Enter scattered timber.

80.00

Point for the cor. of secs. 19, 20, 29 and 30.

Set the iron post 20 ins. in the ground, cap mkd.

T36NR7W
S19|S20
S30|S29
1964

Raise a mound of stone W. of the iron post.

CHAINS	
	<p>Land, gently rolling E. slope. Soil, clay loam and rocky. Timber, moderate to scattered cedar and pinon. Undergrowth, moderate sage and grass.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29. S. 89°57' W., bet. secs. 20 and 29. Over gently rolling land, recently railed.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29. Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T36NR7W 1/4 $\frac{S20}{S29}$ 1964</p>
	<p>Raise a mound of stone N. of the iron post.</p>
43.70	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 60° E.; leave railed area.</p>
50.80	<p>Low spur, slopes S.; enter moderate timber bearing NE. and SW.</p>
53.80	<p>Draw, drains S. 15° E. curving to E.; asc. over gentle E. slope.</p>
60.30	<p>Top of ascent, bears N. and S.; thence over nearly level land.</p>
64.00	<p>Enter scattered timber.</p>
79.82	<p>Fence, 4-strand barbed wire, bears N. and S.</p>
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, clay loam and rocky. Timber, scattered to moderate on W 1/2 mile, none on E 1/2 mile. Undergrowth, moderate sagebrush and grass.</p> <hr/> <p>S. 89°52' W., bet. secs. 19 and 30. Over rolling land through scattered timber and moderate undergrowth.</p>
16.40	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 60° E</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30. Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T36NR7W 1/4 $\frac{S19}{S30}$ 1964</p>

CHAINS	
41.80	Small wash, drains N. 15° E.
45.10	Small wash, drains N. 15° E.
58.70	Wash, 40 lks. wide, 2 ft. deep, drains irregularly N. 15° E.; asc. over E. slope.
70.10	Continue along rolling N. slope through moderate timber.
77.88	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling.
	Soil, rocky clay loam.
	Timber, scattered clumps of juniper and pinon.
	Undergrowth, moderate to heavy sagebrush.
	<hr/>
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over gently rolling land through scattered timber and moderate sagebrush, along winding fence.
40.00	Point for the ¼ sec. cor. of secs. 19 and 20.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T36NR7W
	¼
	S19 S20
	1964
	from which
	A cedar 6 ins. diam. bears S. 86½° W., 18 lks. dist., mkd. ¼ S19 B T
	A N-S fence bears West, 2 lks. dist.
	Raise a mound of stone W. of the iron post.
53.20	Wash, 20 lks. wide, steep sloping banks, drains NE. from S. 30° W.
74.40	Desc. over rocky N. slope.
79.50	Small draw, drains NE.; thence along base of E. slope.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 22 ins. in the ground, cap mkd.
	T36NR7W
	S18 S17
	S19 S20
	1964
	Raise a mound of stone W. of the iron post.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

31.

CHAINS	
	<p>Land, gently rolling on S. 74.00 chs., slightly broken on the remainder. Soil, rocky clay loam. Timber, scattered cedar and pinon. Undergrowth, moderate sagebrush and grass.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21. S. 89°56' W., bet. secs. 17 and 20. Over rolling land through scattered to moderate timber.</p>
1.20	Small spur, slopes S.
3.50	Small draw, drains S. 30° E.; asc. over gentle E. slope through moderate timber.
16.00	Enter scattered timber.
32.00	Desc. over gently rolling W. slope.
40.01	Point for the ¼ sec. cor. of secs. 17 and 20. Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd. <div style="text-align: center;"> T36NR7W ¼ $\frac{S17}{S20}$ 1964 </div>
	Raise a mound of stone N. of the iron post.
51.10	Large draw, drains N. 15° E.; asc. over E. slope.
56.10	Top of ascent, bears N. and SW.; thence over gently rolling land.
62.60	Draw, near head, drains N. about 4.00 chs. thence NW.
67.90	Desc. over W. slope.
74.20	Draw, drains N.; continue over gently rolling land, N. drainage.
79.30	Small draw, drains N. 15° E. from SW.
80.02	The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, rocky clay loam. Timber, scattered to moderate cedar and pinon. Undergrowth, moderate sage and grass.
	<hr/> <p>S. 89°52' W., bet. secs. 18 and 19. Asc. over E. slope through moderate undergrowth.</p>
.25	Fence, 4-strand barbed wire, bears N. and S.
3.30	Rocky point, projects N.; desc. over W. slope.
10.60	Base of slope; thence across canyon bottom.

CHAINS	
13.50	Fence, 4-strand barbed wire, bears N. 70° E. and S. 70° W.
18.10	Wash in canyon bottom, 30 lks. wide, 1 ft. deep, drains N. 60° E.; asc. over SE. slope.
28.30	Small rocky spur, slopes S.
34.00	Asc. over E. slope through moderate timber.
40.00	Point for the ¼ sec. cor. of secs. 18 and 19.
	Set the iron post 22 ins. in the ground, cap mkd.
	T36NR7W $\frac{1}{4} \frac{S18}{S19}$ 1964
	from which
	A cedar, 16 ins. diam., bears N. 38½° E., 71 lks. dist., mkd. ¼ S18 B T
	A cedar, 10 ins. diam., bears S. 31¼° E., 72½ lks. dist., mkd. ¼ S19 B T
	An E-W fence, bears S., 11½ lks. dist.
	Raise a mound of stone N. of the iron post.
58.90	Top of low ridge, bears N. 20° E. and S. 20° W.; desc. over gently rolling land, N. drainage.
77.87	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record. This cor. is located on E-W fence line.
	Land, rolling and broken. Soil, rocky clay loam. Timber, moderate cedar and pinon on W 1/2 mile. Undergrowth, moderate sagebrush and grass.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over gently rolling E. slope through moderate brush.
13.80	Enter canyon bottom draining E. curving to NE.
19.60	Asc. over steep S. slope.
24.20	Rocky rim, bears NE. and W.; thence over gently rolling flat through heavy sagebrush.
36.10	Bottom of draw, drains N. 70° E.
39.00	Rocky rim, bears N. and SW.
40.00	Point for the ¼ sec. cor. of secs. 17 and 18.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

CHAINS

T36NR7W
 $\frac{1}{4}$
 S18 | S17
 1964

from which

A N-S fence, bears W., 44 lks. dist.

- 41.00 Rim bears to NE.
 - 44.50 Short draw, drains E.
 - 50.20 Enter moderate timber.
 - 67.20 Desc. over N. slope.
 - 70.10 Enter gently rolling land, scattered timber.
 - 80.00 Point for the cor. of secs. 7, 8, 17 and 18.
- Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W
 S 7 | S 8
 S18 | S17
 1964

from which

A fence cor. bears N. $34^{\circ}22'$ W., 118 lks. dist.; fences bear S. and N. 80° W.

Raise a mound of stone W. of the iron post.

Land, rolling and slightly broken.
 Soil, rocky clay loam.
 Timber, scattered to moderate cedar and pinon.
 Undergrowth, sagebrush and snake weed.

From the cor. of secs. 8, 9, 16 and 17.
 S. $89^{\circ}57'$ W., bet. secs. 8 and 17.
 Over gently rolling land through moderate undergrowth.

- 1.30 Wash, 20 lks. wide, 1 ft. deep, drains N. 15° E. curving to NE.
 - 5.80 Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.
 - 21.40 Bladed road, bears NW. and SE.
 - 29.40 N. end of low knoll, desc. over gentle W. slope.
 - 39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
- Set the iron post 20 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$ S 8
 S17
 1964

CHAINS		
	<p>from which</p> <p>A reservoir bears S. 69°08' E., 22.54 chs. dist.</p> <p>Raise a mound of stone N. of the iron post.</p> <p>Continue over nearly level land.</p>	
43.00	Asc. over gentle SE. slope.	
53.90	Top of ascent; thence over nearly level land.	
61.30	Desc. over gentle W. slope.	
71.70	Small wash, drains N. 15° W.; continue over gently rolling land.	
79.88	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling. Soil, clay loam and rocky. Timber, scattered juniper on W. 1/2 mile. Undergrowth, moderate sage, grass and snake weed.</p>	
	<p>S. 89°50' W., bet. secs. 7 and 18.</p> <p>Over rolling land through scattered timber and moderate brush.</p>	
.67	Fence, 4-strand barbed wire, bears N. and S.; asc. over E. slope.	
6.00	Top of ascent; thence over gently rolling land.	
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p style="text-align: center;">T36NR7W $\frac{1}{4}$ $\frac{S\ 7}{S18}$ 1964</p>	
	<p>from which</p> <p>The W. end of reservoir bears N. 38°53' E., 28.16 chs. dist.</p> <p>The center of dike on reservoir bears S. 67°26' W., 13.64 chs. dist.</p> <p>A fence cor., bears N. 53°21' W., 20.80 chs. dist.; fences bear about NW. and S. 78°30' E.</p> <p>The cor. is located on the W. edge of track road bearing N. 30° E. and S. 30° W.</p>	
52.30	Draw, drains N.	
54.70	Track road, bears N. and S. 30° E.	
77.76	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., set mkd. and witnessed as described in the official record.	

CHAINS

Land, gently rolling.
Soil, rocky clay loam.
Timber, widely scattered cedar.
Undergrowth, moderate sage, grass and snakeweed.

From the cor. of secs. 7, 8, 17 and 18.

N. 0°03' W., bet. secs. 7 and 8.

Over gently rolling land through moderate undergrowth and widely scattered timber.

15.00

Asc. over S. slope.

17.60

Rocky rim, bears N. 70° E. and S. 70° W.

23.10

Track road, bears NE. and SW.

23.30

Small wash, drains NE.

31.30

Continue along gently rolling E. slope.

40.00

Point for the ¼ sec. cor. of secs. 7 and 8.

Set the iron post 22 ins. in the ground, cap mkd.

T36NR7W

¼

S 7 | S 8

1964

Raise a mound of stone W. of the iron post.

44.80

Desc. over N. slope.

52.00

Enter clump of timber.

63.00

Small draw, drains NW. from S. 10° E.; thence over low rolling hills through widely scattered timber.

70.20

Bottom of swale, drains irregularly NE.

76.60

Low hill, bears E. and W.; desc. over N. slope.

80.00

Point for the cor. of secs. 5, 6, 7 and 8.

Set the iron post 20 ins. in the ground, cap mkd.

T36NR7W

S 6 | S 5

S 7 | S 8

1964

Raise a mound of stone W. of the iron post.

Land, rolling.

Soil, clay loam and rocky.

Timber, scattered to widely scattered cedar.

Undergrowth, moderate sagebrush, snake weed and grass.

From the cor. of secs. 4, 5, 8 and 9.

S. 89°57' W., bet. secs. 5 and 8.

BOOK 4754

Subdivision, T. 36 N., R. 7 W., Arizona

36

36.

CHAINS	
	Desc. over NW. slope.
2.00	Short rocky draw, drains SW.; asc. over SE. slope through large boulders.
5.20	S. end of rocky point, rim bears N. 70° E. and NW.; desc. over rocky W. slope.
8.90	Base of slope, bears N. and S.; thence over bottom of canyon draining N.
15.90	Asc. over rolling E. slope.
23.10	Top of ascent, bears N. and S.; continue over rolling land.
39.93	Point for the ¼ sec. cor. of secs. 5 and 8. Set the iron post 22 ins. in the ground, cap mkd. T36NR7W ¼ $\frac{S\ 5}{S\ 8}$ 1964 Raise a mound of stones N. of the iron post. Desc. along draw draining irregularly W.
51.20	Draw, drains NW.
58.20	Wash in bottom of draw, 10 lks. wide, 5 ft. deep, drains N.; asc. over E. slope.
61.40	Ridge, bears N. and S.; desc. over W. slope.
65.60	Base of ridge, bears N. and S.; thence over gently rolling land.
69.50	Bladed road, bears N. and S.
79.86	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, sandy clay loam and rocky. Timber, widely scattered cedars. Undergrowth, sagebrush, grass, cacti and snakeweed.
	S. 89°50' W., bet. secs. 6 and 7. Over gently rolling land through widely scattered timber.
9.20	Wash, 15 lks. wide, 2 ft. deep, drains irregularly NE.
18.30	Wash, 15 lks. wide, 3 ft. deep, drains N. 10° E.
21.50	Asc. over SE. slope.
27.90	Top of ascent, bears N. 20° E. and S. 20° W.; thence over gently rolling land through moderate undergrowth.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7.

CHAINS

Set the iron post 20 ins. in the ground, cap mkd.

T36NR7W
 $\frac{1}{4}$ $\frac{S 6}{S 7}$
 1964

Raise a mound of stone N. of the iron post.

- 46.10 Track road, bears NE. and SW.
- 68.00 Enter scattered timber.
- 71.00 Desc. over W. slope.
- 74.00 Bottom of draw, drains N. 10° E.; asc. over E. slope.
- 77.74 The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

Land, gently rolling.
 Soil, sandy clay loam and rocky.
 Timber, scattered to widely scattered cedar and pinon.
 Undergrowth, moderate sagebrush, grass and cacti.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°03' W., bet. secs. 5 and 6.

Over rolling land through widely scattered timber.

- 6.50 Wash in bottom of swale, 10 lks. wide, 4 ft. deep, drains N. 70° E.; asc. over S. slope.
- 13.10 Small spur, slopes E.
- 15.50 Small draw, drains E.; asc. over slightly broken SE. slope.
- 21.80 Low hill, bears NE. and SW.
- 31.90 Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. over steep, rocky S. slope.
- 36.80 Top of steep ascent, bears N. 80° E. and W.; thence over mesa top.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T36NR7W
 $\frac{1}{4}$
 S 6 | S 5
 1964

Raise a mound of stone W. of the iron post.

- 69.70 Desc. over steep N. slope.
- 72.90 Small wash, drains W. about 1.50 chs. to junction with wash draining N.; thence along E. side of wash.

38

CHAINS

78.68

Intersect the Ninth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6, T. 36 N., R. 7 W.

Set the iron post 22 ins. in the ground, cap mkd.

T37NR7W
S32
 S 6 | S 5
 T36NR7W
 C C
 1964

Raise a mound of stone S. of the iron post.

From the point of intersection the standard cor. of secs. 31 and 32, T. 37 N., R. 7 W., bears West, 12.56 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling and slightly broken.
 Soil, rocky clay loam.
 Timber, widely scattered juniper and pinon.
 Undergrowth, moderate sagebrush and snakeweed.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 5 is at mid-point and on the N. bdy. of the Tp.

At the cor. point

Set the iron post 4 ins. in the ground to bedrock, mound with stones to top, cap mkd.

T37N
 $\frac{1}{4}$ S 5
 T36NR7W
 1964

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 37 N., R. 7 W., bears West, 12.51 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.

The $\frac{1}{4}$ sec. cor. of sec. 5 is located on a steep, rocky E. slope, about 10.00 chs. West of road bearing N. and S.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 6 is 40.00 chs. West of the closing cor. of secs. 5 and 6 and on the N. bdy. of the Tp.

At the cor. point

Set the iron post 22 ins. in the ground, cap mkd.

$\frac{1}{4}$ S 6
 T36NR7W
 1964

Raise a mound of stone S. of the iron post.

BOOK 4754

Township 36 North, Range 7 West
Gila and Salt River Meridian, Arizona

39.

CHAINS

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 37 N., R. 7 W., bears West, 12.56 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.

General Description

The land in Township 36 North, Range 7 West, varies from high peaks and knolls to low rolling hills and nearly level mesas. There are numerous draws and gullies within the township with reservoirs and stock ponds built along them for water detention and erosion control.

The soil is mostly heavy clay loam with lava rock, which supports a fair growth of grass, sagebrush, cacti and snakeweed over most of the township, with moderate cedars and pinons in the southern part becoming scattered in the northern areas.

No minerals or mining activity was noted within the township which at present is used primarily for controlled grazing of livestock.

There are two good bladed roads cutting through the township and several track roads branching off to ponds and other points. One main road cuts north and south through the central part of the township from Tuweep to Colorado City, and the other bladed road cuts northeast and southwest through the southeast part of the township, from Tuweep to Fredonia, Arizona.

BOOK 4754

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert F. Johnson	Transitman
Lyman Polacca	Notekeeper
Vernon Masayesva	Front Chainman
Daniel R. Bauer	Cornerman and Axeman
David L. Sakiestewa	Flagman
Claud Clay	Axeman
Gerald Satala	Truck Driver

41

BOOK 4754
CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 14 day of February, 1963,
I have surveyed a portion of the subdivisinal lines, completing the
subdivision of Township 36 North, Range 7 West

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

March 16, 1965
(Date)

Boyd S Owens
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date SEP 27 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the survey of a portion of the subdivisinal lines
completing the subdivision of Township 36 North, Range 7 West, of the
Gila and Salt River Meridian in the State of Arizona,

executed by Boyd S. Owens, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JAN 7 1966
(Date)

E. J. Huntington
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)