

BOOK 4755

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

COMPLETION SURVEY

of the

Subdivisional Lines

Township 38 North, Range 7 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated February 18, 19 63, which provided for the surveys
Supplemental Special Instructions dated July 24, 1963
included under Group Number 393, approved February 20, 1963,
Supplemental Special Instructions approved July 25, 1963
and assignment instructions dated June 29, 19 64.

Survey commenced July 24, 19 64

Survey completed August 7, 19 64

1A

BOOK 4755 INDEX DIAGRAM

Township 38 North, Range 7 West

6 31 31	5 23 30	4 18 23	3 12 17	2 6 11	1 5
7 30 29	8 22 29	9 17 21	10 10 16	11 5 10	12 4
18 28 28	17 21 27	16 15 21	15 9 15	14 3 9	13 3
19 27 26	20 20 26	21 14 20	22 8 14	23 3 8	24 2
30 25 25	29 19 24	28 13 19	27 7 13	26 1 7	25
31 24	32 18	33 12	34 6	35	36

CHAINS

The east boundary was surveyed in 1924 by Hiester and Hunter. The south boundary was surveyed in 1934 by Procter and Hester. The west boundary was surveyed in 1937 by B. J. Kinsey. The north boundary and section 36 were surveyed in 1954 by D. E. Harding.

The following field notes are those of the completion survey of the subdivision of Township 38 North, Range 7 West.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated February 18, 1963, and Supplemental Special Instructions dated July 24, 1963.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 36°38'37" North, and Longitude 112°59'15.6" West, as determined from ties to U.S.G.S. triangulation stations RESERVOIR and MONUMENT ON LOW BUTTE.

The mean magnetic declination was found to be 16° East.

Completion of Subdivision, T. 38 N., R. 7 W., Arizona

Beginning at the cor. of secs. 25, 26, 35 and 36, monumented by an iron post 2½ ins. diam., as described in the official record, and situated at a cor. of fences bearing NE. and N. 75° W.

N. 0°01' W., bet. secs. 25 and 26.

Over nearly level land, through scattered undergrowth.

23.80 Dike, bears N. 56°40' E. and S. 56°40' W.

29.40 Wash, 20 lks. wide, 3 ft. deep, drains NW.

39.10 Bladed road, bears E. and W.

40.00 Point for the ¼ sec. cor. of secs. 25 and 26.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W

¼

S26|S25

1964

Deposit glass in the hole alongside the iron post.

52.70 Wash, 20 lks. wide, 3 ft. deep, drains irregularly NW.

63.30 Wash, 90 lks. wide, 6 ft. deep, drains irregularly W.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

2.

2

CHAINS

- 65.20 Gully, drains W.
- 67.30 Track road, bears irregularly E. and W.
- 80.00 Point for the cor. of secs. 23, 24, 25 and 26.
- Set the iron post 22 ins. in the ground, cap mkd.
- T38N R7W
 $\frac{S23}{S26} | \frac{S24}{S25}$
 1964
- Build a mound of stones W. of the iron post.
- Land, nearly level, with gullies.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, bunchgrass, scattered shadscale and cacti.
-
- From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.
- S. 89°59' W., bet. secs. 24 and 25.
- Over nearly level, eroded land.
- 5.00 Wash, 60 lks. wide, 4 ft. deep, drains irregularly SW.
- 7.00 Wash, 30 lks. wide, 4 ft. deep, drains S. 15° W.
- 12.80 Dike, bears S. 30° E. and N. 30° W.
- 16.00 Road, bears NE. and SW.
- 28.80 Bladed road, bears N. 60° E. and SW.
- 40.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.
- Set the iron post 22 ins. in the ground, cap mkd.
- T38N R7W
 $\frac{1}{4} \frac{S24}{S25}$
 1964
- Deposit glass in the hole alongside the iron post.
- 45.20 Dike, bears S. 57° E. and N. 57° W.
- 59.70 Fence, bears N. and S.
- 73.00 Road, track, bears SE. and NW.
- 73.80 N. end of a dike bearing S. 16° E.
- 80.06 The cor. of secs. 23, 24, 25 and 26.
- Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, bunchgrass, scattered shadscale and cacti.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

3.

CHAINS	
	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over nearly level land.</p>
4.30	<p>Road, track, bears SE. and NW.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W $\frac{1}{4}$ S23 S24 1964</p>
	<p>Deposit glass in the hole alongside the iron post.</p> <p>Continue over nearly level land.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W S14 S13 S23 S24 1964</p>
	<p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.</p>
	<hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p> <p>S. 89°57' W., bet. secs. 13 and 24.</p> <p>Over nearly level land.</p>
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W $\frac{1}{4}$ S13 S24 1964</p>
	<p>Deposit glass in the hole alongside the iron post.</p>
61.20	<p>Fence, bears N. and S.</p>
80.08	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.</p>
	<hr/> <p>N. 0°01' W., bet. secs. 13 and 14</p> <p>Over nearly level land.</p>

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

4

4.

CHAINS	
23.40	Gully, drains NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W $\frac{1}{4}$ S14 S13 1964
	Deposit glass in the hole alongside the iron post.
46.00	Gully, 80 lks. wide, 7 ft. deep, drains W.
78.40	Track road, bears NE. and SW.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W <u>S11 S12</u> <u>S14 S13</u> 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, shadscale and bunchgrass.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.
	S. 89°56' W., bet. secs. 12 and 13.
	Over nearly level land.
5.30	Wash, 90 lks. wide, 10 ft. deep, drains SW.
8.60	Gully, drains SW.
9.80	Gully, drains SW.
15.20	Wash, 80 lks. wide, 8 ft. deep, drains SW.
19.70	Gully, drains SW.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W $\frac{1}{4}$ <u>S12</u> <u>S13</u> 1964
	Deposit glass in the hole alongside the iron post.
62.70	Fence bears N. and S.
80.10	The cor. of secs. 11, 12, 13 and 14.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, shadscale and bunchgrass.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12. Over nearly level land.</p>
28.60	Gully, drains irregularly NW.
32.10	Wash, 30 lks. wide, 3 ft. deep, drains irregularly W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12. Set the iron post 22 ins. in the ground, cap mkd.
	<p>T38N R7W $\frac{1}{4}$ S11 S12 1964</p>
	Deposit glass in the hole alongside the iron post.
50.00	Fence, bears SE. and NW.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set the iron post 22 ins. in the ground, cap mkd.
	<p>T38N R7W S 2 S 1 S11 S12 1964</p>
	Build a mound of stones W. of the iron post.
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p> <p>S. 89°54' W., bet. secs. 1 and 12. Over nearly level land.</p>
8.30	Road, track, bears NE. and SW.
14.70	Fence, bears N. 55° E. and S. 55° W.
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12. Set the iron post 22 ins. in the ground, cap mkd.
	<p>T38N R7W $\frac{1}{4}$ S 1 S12 1964</p>
	Deposit glass in the hole alongside the iron post.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

6

6.

CHAINS		
	Continue over nearly level land.	
80.14	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, scattered bunchgrass, shadscale and blackbrush.</p>	
	N. 0°04' E., bet. secs. 1 and 2.	
	Over rolling land.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W $\frac{1}{4}$ S 2 S 1 1964</p> <p>Deposit glass in the hole alongside the iron post.</p>	
61.60	Road, bladed, bears SE. and NW.	
79.11	<p>The cor. of secs. 1 and 2 on the N. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., as described in the official record.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, shadscale, snakeweed, scattered grass.</p>	
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over nearly level land.</p>	
8.00	Gully, drains NW.	
12.10	Road, track, bears W. and E., curving to SE.	
19.20	Road, bladed, bears E. and W.	
38.20	Small wash, drains irregularly W.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W $\frac{1}{4}$ S34 S35 1964</p> <p>Deposit glass in the hole alongside the iron post.</p>	

CHAINS	
66.90	Track road, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W $\frac{S27}{S34} \frac{S26}{S35}$ 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.
	From the cor. of secs. 25, 26, 35 and 36. N. 89°55' W., bet. secs. 26 and 35. Over nearly level land.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35. Set the iron post 20 ins. in the ground, cap mkd.
	T38N R7W $\frac{1}{4} \frac{S26}{S35}$ 1964
	Deposit glass in the hole alongside the iron post.
40.50	Small wash, drains irregularly NW.
49.70	Track road, bears NE. and SW.
80.12	The cor. of secs. 26, 27, 34 and 35.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.
	N. 0°01' W., bet. secs. 26 and 27. Over nearly level land.
19.60	Fence, bears NW. and SE. for 60 lks., thence S. 75° E.
35.00	Wash, 100 lks. wide, 3 ft. deep, drains N. 70° W.
39.10	Gully, drains irregularly NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27. Set the iron post 20 ins. in the ground, cap mkd.
	T38N R7W $\frac{1}{4}$ $\frac{S27}{S26}$ 1964
	Deposit glass in the hole alongside the iron post.
62.70	Wash, 110 lks. wide, 6 ft. deep, drains N. 10° W. from SE.
68.50	Wash, 80 lks. wide, 6 ft. deep, drains W.
70.80	Wash, 90 lks. wide, 6 ft. deep, drains W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set the iron post 20 ins. in the ground, cap mkd.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

CHAINS

T38N R7W
S22 | S23
S27 | S26
 1964

Build a mound of stones W. of the iron post.

Land, nearly level.
 Soil, sandy clay loam.
 Timber, none.
 Undergrowth, shadscale.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°55' W., bet. secs. 23 and 26.

Over nearly level land.

- 6.40 Bladed road, bears S. 10° W. and N. 40° W.
- 9.10 Dike, bears S. 10° W. and N. 40° W.
- 33.10 Dike, bears S. 14° W. and N. 12° W.
- 40.02 Point for the 1/4 sec. cor. of secs. 23 and 26.
 Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 1/4 S23
S26
 1964

Deposit glass in the hole alongside the iron post.

- 40.40 Wash, 60 lks. wide, 3 ft. deep, drains irregularly NW.
- 46.90 Fence, bears S. 12° E. and N. 12° W.
- 52.10 Dike, bears N. 56° E. and S. 56° W.
- 61.00 Gully, drains NW.
- 72.10 Enter series of gullies and washes, draining NW.
- 80.04 The cor. of secs. 22, 23, 26 and 27.

Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, bunchgrass and shadscale.

N. 0°01' W., bet. secs. 22 and 23.

Over nearly level land.

- 2.90 Gully, drains irregularly W.
- 22.10 Wash, 40 lks. wide, 6 ft. deep, drains NW.
- 35.70 Gully, drains irregularly NW.
- 40.00 Point for the 1/4 sec. cor. of secs. 22 and 23.
 Set the iron post 20 ins. in the ground, cap mkd.

T38N R7W
 1/4 S22 | S23
 1964

Deposit glass in the hole alongside the iron post.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

9.

CHAINS	
72.00	Gully, drains SW.
76.40	Fence, bears E. and W.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p>T38N R7W $\frac{S15}{S22} \frac{S14}{S23}$ 1964</p>
	Build a mound of stones W. of the iron post.
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89°53' W., bet. secs. 14 and 23.
	Over nearly level land.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p>T38N R7W $\frac{1}{4} \frac{S14}{S23}$ 1964</p>
	Deposit glass in the hole alongside the iron post.
44.60	Road, bladed, bears irregularly S. and NW.
50.00	Dike, bears S. 20° E. and N. 30° W.
76.10	Dike, bears SE. and NW.
80.10	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, nearly level. Soil, sandy clay loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
	N. 0°01' W., bet. secs. 14 and 15.
	Over gently rolling land, through moderate brush and shadscale.
21.20	Road, bears SE. and NW.
23.20	Road, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
	Set the iron post 20 ins. in the ground, in a collar of stone, cap mkd.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

10

10.

CHAINS	
	T38N R7W $\frac{1}{4}$ S15 S14 1964
41.20	Dike, bears N. 15° E. and S. 15° W.
59.80	Same dike, bears S. 15° E. and N. 15° W.
66.40	Same dike, bears N. 31° E. and S. 31° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W S10 S11 S15 S14 1964
	Build a mound of stones W. of the iron post. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and black brush.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°53' W., bet. secs. 11 and 14. Over nearly level land.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W $\frac{1}{4}$ $\frac{S11}{S14}$ 1964
	Deposit glass in the hole alongside the iron post.
53.70	Dike, bears N. and S.
73.40	Dike, bears irregularly N. and S.
80.08	The cor. of secs. 10, 11, 14 and 15. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.
	N. 0°01' W., bet. secs. 10 and 11. Over nearly level land.
6.30	Dike, bears N. 11½° E. and S. 11½° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

11.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W $\frac{1}{4}$ S10 S11 1964</p> <p>Deposit glass in the hole alongside the iron post.</p>
49.30	Road, bears SE. and NW.
71.30	Road, bears NE. and SW.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W $\frac{S\ 3}{S10}$ $\frac{S\ 2}{S11}$ 1964</p> <p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale, snakeweed and black brush.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°53' W., bet. secs. 2 and 11.</p> <p>Over gently rolling land.</p>
24.20	Small wash, drains SW.
36.00	Series of small washes, drains SW.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W $\frac{1}{4}$ $\frac{S\ 2}{S11}$ 1964</p> <p>Deposit glass in the hole alongside the iron post.</p>
42.40	Fence, bears S. 65° E. and N. 65° W.
70.40	Road, track, bears irregularly N. and S.
80.06	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale, snakeweed and blackbrush.</p>

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

12

12.

CHAINS	
	<p>N. 0°12' E., bet. secs. 2 and 3.</p> <p>Over nearly level land.</p>
26.70	<p>Fence, bears approximately S. 60° E. and N. 60° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 2 and 3.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W ¼ S 3 S 2 1964</p>
	<p>Deposit glass in the hole alongside the iron post.</p>
53.50	<p>Wash, 20 lks. wide, 3 ft. deep, drains NW., circling SW.</p>
57.00	<p>Wash, 10 lks. wide, 1 ft. deep, drains W. 3.00 chs., thence SW.</p>
79.26	<p>The cor. of secs. 2 and 3, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the official record.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale, snakeweed and blackbrush.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p>
	<p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over nearly level land.</p>
20.00	<p>Asc. S. slope.</p>
27.20	<p>Low lava ridge, bears W. and E. about 6.00 chs. to end; desc. N. slope.</p>
38.80	<p>Track road, bears E. and W.; continue over nearly level land.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 33 and 34.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W ¼ S33 S34 1964</p>
	<p>Build a mound of stone W. of the iron post.</p> <p>From this corner a windmill bears S. 74°41' E., 6.02 chs. dist.</p>
42.10	<p>Track road, bears irregularly E. and W.; continue over eroded land.</p>

CHAINS	
52.20	Dike, bears NE. and SW.
58.40	Gully, drains NW.; thence over gently rolling land.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W <u>S28</u> <u>S27</u> <u>S33</u> <u>S34</u> 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level.
	Soil, sandy and gravelly loam.
	Timber, none.
	Undergrowth, bunchgrass, sage, shadscale and scattered cacti.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89°56' W., bet. secs. 27 and 34.
	Over nearly level land.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W $\frac{1}{4}$ <u>S27</u> <u>S34</u> 1964
	Deposit glass in the hole alongside the iron post.
80.04	The cor. of secs. 27, 28, 33 and 34.
	Land, nearly level.
	Soil, sandy clay loam.
	Timber, none.
	Undergrowth, bunchgrass, sage, shadscale and cacti.
	N. 0°02' W., bet. secs. 27 and 28.
	Over nearly level land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W $\frac{1}{4}$ <u>S28</u> <u>S27</u> 1964
	Deposit glass in the hole alongside the iron post.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set the iron post 22 ins. in the ground, cap mkd.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

14

14.

CHAINS

T38N R7W
 $\frac{S21}{S28} | \frac{S22}{S27}$
 1964

Build a mound of stone W. of the iron post.

Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, shadscale and bunchgrass.

From the cor. of secs. 22, 23, 26 and 27.

S. 89°59' W., bet. secs. 22 and 27.

Over nearly level land.

- 1.80 Wash, 100 lks. wide, 10 ft. deep, drains N. curving NW.
- 4.10 Series of gullies, drains irregularly NW.
- 24.30 Gully, drains N.
- 37.90 Wash, 80 lks. wide, 7 ft. deep, drains N.
- 40.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 $\frac{1}{4} \frac{S22}{S27}$
 1964

Deposit glass in the hole alongside the iron post.

- 44.10 Small wash, drains irregularly N.
- 56.00 Series of gullies, drains N.
- 64.94 Fence, bears S. 15° E. and N. 15° W.
- 80.06 The cor. of secs. 21, 22, 27 and 28.

Land, nearly level.
 Soil, sandy clay loam.
 Timber, none,
 Undergrowth, shadscale, bunchgrass and black brush.

N. 0°02' W., bet. secs. 21 and 22.

Over nearly level land.

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.
- Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 $\frac{1}{4} \frac{S21}{S22}$
 1964

Deposit glass in the hole alongside the iron post.

CHAINS	
46.60	Fence, bears S. 27° E. and N. 27° W.
68.00	Series of gullies, drains irregularly NE.
77.30	Wash, 100 lks. wide, 9 ft. deep, drains irregularly NW.
79.80	Point selected for a witness cor. for secs. 15, 16, 21 and 22.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W W C <u>S16 S15</u> <u>S21 S22</u> 1964
	Build a mound of stones W. of the iron post.
80.00	Point for the cor. of secs. 15, 16, 21 and 22 falls in a gully and cannot be perpetuated.
	From this corner a windmill bears N. 28°02' W., 20.70 chs. dist.
	Land, nearly level. Soil, sandy clay loam. Timber, none. Undergrowth, shadscale.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°57' W., bet. secs. 15 and 22.
	Over nearly level land.
31.80	Fence, bears S. 86°40' E. and N. 86°40' W.
40.03	Point for the ¼ sec. cor. of secs. 15 and 22.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W ¼ <u>S15</u> <u>S22</u> 1964
	Deposit glass in the hole alongside the iron post.
79.90	Wash, 10 lks. wide, 8 ft. deep, drains NW.
80.06	Point for the cor. of secs. 15, 16, 21 and 22.
	Land, nearly level. Soil, sandy clay loam. Timber, none. Undergrowth, shadscale and snakeweed.
	N. 0°02' W., bet. secs. 15 and 16.
	Over nearly level land.
0.40	Wash, 10 lks. wide, 8 ft. deep, drains NW.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

16.

16

CHAINS		
7.60	Series of gullies, drains NW.	
9.10	Wash, 30 lks. wide, 4 ft. deep, drains N. 75° W.	
17.50	Fence, bears approximately S. 30° E. and N. 30° W.	
40.00	Point for the ¼ sec. cor. of secs. 15 and 16.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T38N R7W ¼ S16 S15 1964	
	Deposit glass in the hole alongside the iron post.	
	Continue over nearly level land.	
80.00	Point for the cor. of secs. 9, 10, 15 and 16.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T38N R7W S 9 S10 S16 S15 1964	
	Build a mound of stones W. of the iron post.	
	Land, nearly level. Soil, sandy clay loam. Timber, none. Undergrowth, shadscale, cacti and black brush.	
	From the corner of secs. 10, 11, 14 and 15.	
	N. 89°57' W., bet. secs. 10 and 15.	
	Over nearly level land.	
2.00	Dike, bears S. 30° W. and N.	
10.20	Dike, bears S. 30° W. and N.	
20.20	Dike, bears N. 30° E. and S. 30° W.	
31.00	Dike, bears N. 30° E. and S. 30° W.	
39.60	Bladed road, bears SE. and NW.	
40.02	Point for the ¼ sec. cor. of secs. 10 and 15.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T38N R7W ¼ S10 S15 1964	
	Deposit glass in the hole alongside the iron post.	
	Build a mound of stones N. of the iron post.	
54.90	Gully, drains NW.	
80.04	The cor. of secs. 9, 10, 15 and 16.	

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, shadscale, snakeweed and cacti.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10. Over nearly level land.</p>
2.90	Gully, drains W.
19.90	Bladed road, bears SE. and NW.
25.50	Bladed road, bears S. 65° E. and N. 65° W.
40.00	Point for the ¼ sec. cor. of secs. 9 and 10. Set the iron post 22 ins. in the ground, cap mkd.
	<p>T38N R7W ¼ S 9 S10 1964</p>
	Deposit glass in the hole alongside the iron post.
46.40	Wash, 70 lks. wide, 10 ft. deep, drains N. 80° W.
52.70	Small wash, drains irregularly W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set the iron post 22 ins. in the ground, cap mkd.
	<p>T38N R7W S 4 S 3 S 9 S10 1964</p>
	Build a mound of stones W. of the iron post.
	<p>Land, nearly level. Soil, sandy clay loam. Timber, none. Undergrowth, shadscale, snakeweed and black brush.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. N. 89°57' W., bet. secs. 3 and 10. Over nearly level land.</p>
40.01	Point for the ¼ sec. cor. of secs. 3 and 10. Set the iron post 22 ins. in the ground, cap mkd.
	<p>T38N R7W ¼ S 3 S10 1964</p>
	Deposit glass in the hole alongside the iron post.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

18

18.

CHAINS

80.02 Continue over nearly level land.
The cor. of secs. 3, 4, 9 and 10.
Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, shadscale, snakeweed and black brush.

N. 0°09' E., bet. secs. 3 and 4.
Over nearly level land.

36.90 Fence, bears E. and W.

40.00 Point for the ¼ sec. cor. of secs. 3 and 4.
Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
¼
S 4 | S 3
1964

79.51 Deposit glass in the hole alongside the iron post.
The cor. of secs. 3 and 4, on the N. bdy. of the Tp.,
monumented by an iron post 2½ ins. diam., as described
in the official record.
Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, shadscale, snakeweed and black brush.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy.
of the Tp., monumented by an iron post 2 ins. diam.,
as described in the official record.
N. 0°03' W., bet. secs. 32 and 33.
Over gently rolling land.

40.00 Point for the ¼ sec. cor. of secs. 32 and 33.
Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
¼
S32 | S33
1964

78.90 Build a mound of stones W. of the iron post.
Track road, bears N. 65° W. and S. 65° E.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.
Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
S29 | S28
S32 | S33
1964

CHAINS	
	<p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, cacti and yucca.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>N. 89°56' W., bet. secs. 28 and 33.</p>
	<p>Over nearly level land.</p>
29.60	<p>Dike, bears NE. and SW.</p>
34.30	<p>Small wash, drains NW.</p>
34.70	<p>Small wash, drains NW.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W $\frac{1}{4}$ $\frac{S28}{S33}$ 1964</p>
	<p>Deposit glass in the hole alongside the iron post.</p>
80.00	<p>The cor. of secs. 28, 29, 32 and 33.</p>
	<p>Land, nearly level. Soil, sandy clay loam. Timber, none. Undergrowth, bunchgrass, cacti and yucca.</p>
	<p>N. 0°03' W., bet. secs. 28 and 29.</p>
	<p>Over nearly level land.</p>
33.60	<p>Small wash, drains irregularly NW.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W $\frac{1}{4}$ S29 S28 1964</p>
	<p>Deposit glass in the hole alongside the iron post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R7W S20 S21 S29 S28 1964</p>
	<p>Build a mound of stones W. of the iron post.</p>

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

20

20.

CHAINS

Land, nearly level.
Soil, sandy clay loam.
Timber, none.
Undergrowth, bunchgrass, tumbleweeds and cacti.

From the cor. of secs. 21, 22, 27 and 28.

N. 89°54' W., bet. secs. 21 and 28.

Over nearly level land.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 $\frac{1}{4}$ $\frac{S21}{S28}$
1964

Deposit glass in the hole alongside the iron post.

80.02 The cor. of secs. 20, 21, 28 and 29.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, bunchgrass, cacti and yucca.

N. 0°03' W., bet. secs. 20 and 21.

Over nearly level land.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 $\frac{1}{4}$
S20|S21
1964

Deposit glass in the hole alongside the iron post.

40.70 Wash, 15 lks. wide, 3 ft. deep, drains irregularly NE.

50.30 Wash, 15 lks. wide, 3 ft. deep, drains N. 65° E.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set the iron post 20 ins. in the ground, cap mkd.

T38N R7W
S17|S16
S20|S21
1964

Build a mound of stones W. of the iron post.

Land, nearly level.
Soil, gravel and clay.
Timber, none.
Undergrowth, shadscale and yellowbrush.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

CHAINS		
	<p>From the point for the cor. of secs. 15, 16, 21 and 22. N. 89°55' W., bet. secs. 16 and 21. Over nearly level land.</p>	
17.60	<p>Fence, bears S. 30° E. and N. 30° W.</p>	
40.02	<p>Point for the ¼ sec. cor. of secs. 16 and 21.</p>	
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T38N R7W ¼ $\frac{S16}{S21}$ 1964</p>	
	<p style="text-align: center;">Deposit glass in the hole alongside the iron post.</p>	
68.00	<p>Small wash, drains N.</p>	
69.40	<p>Wash, 12 lks. wide, 4 ft. deep, drains irregularly N.</p>	
80.04	<p>The cor. of secs. 16, 17, 20 and 21.</p>	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, cacti and yucca.</p>	
	<hr/>	
	<p>N. 0°03' W., bet. secs. 16 and 17.</p>	
	<p>Over nearly level land.</p>	
40.00	<p>Point for the ¼ sec. cor. of secs. 16 and 17.</p>	
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T38N R7W ¼ S17 S16 1964</p>	
	<p style="text-align: center;">Deposit glass in the hole alongside the iron post.</p>	
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p>	
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T38N R7W S 8 S 9 S17 S16 1964</p>	
	<p style="text-align: center;">Build a mound of stones W. of the iron post.</p>	
	<p>Land, nearly level. Soil, sandy loam with gravel. Timber, none. Undergrowth, shadscale and black brush.</p>	
	<hr/>	
	<p>From the cor. of secs. 9, 10, 15 and 16.</p>	
	<p>N. 89°55' W., bet. secs. 9 and 16.</p>	

CHAINS		
	Over nearly level land.	
14.55	Fence, bears N. and S.	
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set the iron post 22 ins. in the ground, cap mkd.	
	T38N R7W $\frac{1}{4}$ $\frac{S\ 9}{S\ 16}$ 1964	
	Build a mound of stones N. of the iron post.	
47.90	Wash, 80 lks. wide, 4 ft. deep, drains irregularly NW.	
80.04	The cor. of secs. 8, 9, 16 and 17. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, shadscale, yellowbrush.	
	<hr/>	
	N. 0°03' W., bet. secs. 8 and 9. Over gently rolling land; asc. SE. slope.	
2.10	South side of low mesa, bears NE. and SW.; desc. along gentle NE. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9. Set the iron post 22 ins. in the ground, cap mkd.	
	T38N R7W $\frac{1}{4}$ S 8 S 9 1964	
	Build a mound of stones W. of the iron post. Over nearly level land.	
46.70	Wash, 80 lks. wide, 6 ft. deep, drains irregularly NW.	
49.40	Bladed dirt road, bears E. and W.	
73.00	Wash, 70 lks. wide, 6 ft. deep, drains irregularly NW. from the E.	
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set the iron post 22 ins. in the ground, cap mkd.	
	T38N R7W S 5 S 4 S 8 S 9 1964	
	Build a mound of stone W. of the iron post. Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, shadscale.	
	<hr/>	

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

CHAINS	
	From the cor. of secs. 3, 4, 9 and 10.
	N. 89°57' W., bet. secs. 4 and 9.
	Over nearly level land.
16.40	Fence, bears N. and S.
40.02	Point for the ¼ sec. cor. of secs. 4 and 9.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T38N R7W $\frac{1}{4} \frac{S \ 4}{S \ 9}$ 1964</p>
	Deposit glass in the hole alongside the iron post.
80.04	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level.
	Soil, sandy loam and gravel.
	Timber, none.
	Undergrowth, shadscale, yellow brush.
	<hr/> N. 0°11' E., bet. secs. 4 and 5.
	Over nearly level land.
13.40	Wash, 80 lks. wide, 12 ft. deep, drains irregularly NW.
22.00	Wash, 15 lks. wide, 8 ft. deep, drains irregularly W.
22.70	Wash, 15 lks. wide, 8 ft. deep, drains irregularly SW.
40.00	Point for the ¼ sec. cor. of secs. 4 and 5.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T38N R7W $\frac{1}{4}$ S 5 S 4 1964</p>
	from which
	<p style="text-align: center;">Windmill at Clayhole Well bears N. 86°30' W., 39.51 chs. dist.</p>
	<p style="text-align: center;">Windmill at Clayhole Well bears N. 82°30' W., 38.82 chs. dist.</p>
	Deposit glass alongside the iron post.
68.50	Bladed dirt road, bears E. and W.
79.80	The cor. of secs. 4 and 5, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the official record.
	Land, nearly level.
	Soil, sandy clay.
	Timber, none.
	Undergrowth, bunchgrass, shadscale and cacti.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

24

24.

CHAINS

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.

N. 0°03' W., bet. secs. 31 and 32.

Over gently rolling land.

40.00

Point for the ¼ sec. cor. of secs. 31 and 32.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 ¼
 S31|S32
 1964

Deposit glass in the hole alongside the iron post.

Over nearly level land.

80.00

Point for the cor. of secs. 29, 30, 31 and 32.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 S30|S29
 S31|S32
 1964

Build a mound of stones W. of the iron post.

Land, nearly level.

Soil, sandy clay.

Timber, none.

Undergrowth, bunchgrass and scattered cacti.

From the cor. of secs. 28, 29, 32 and 33.

N. 89°53' W., bet. secs. 29 and 32.

Over nearly level land.

2.10

Track road, bears S. 5° E. and N. 10° W.

40.02

Point for the ¼ sec. cor. of secs. 29 and 32.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 ¼ S29
 S32
 1964

Build a mound of stones N. of the iron post.

46.70

Wash, 15 lks. wide, 3 ft. deep, drains N. 10° W.

54.00

Road, bears N. and S.

73.10

Track road, bears SE. and NW.

80.04

The cor. of secs. 29, 30, 31 and 32.

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, bunchgrass and scattered cacti.</p> <hr/> <p>N. 89°53' W., bet. secs. 30 and 31. Over nearly level land.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 30 and 31. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W ¼ S30 S31 1964</p>
49.20	<p>Build a mound of stones N. of the iron post. Track road, bears N. 35° E. and S. 35° W.</p>
79.28	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, shadscale and scattered cacti.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over nearly level land.</p>
7.30	Track road, bears SE. and NW.
21.80	Fence, bears S. 80° E. and N. 80° W.
31.00	Fence, bears N. 25° E. and S. 25° W.; enter salt cedar.
33.00	Low earthen bank on S. side of reservoir, approximately 10 chains diam.
40.00	Point for the ¼ sec. cor. of secs. 29 and 30 falls in reservoir where the cor. cannot be perpetuated.
49.00	Leave salt cedar.
52.50	Point selected for the witness ¼ sec. cor. of secs. 29 and 30. Set the iron post 22 ins. in the ground, cap mkd. <p style="text-align: center;">T38N R7W ¼ S30 S29 W C 1964</p>
	Build a mound of stones W. of the iron post.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

26

26.

CHAINS					
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T38N R7W</p> <table border="1" style="margin: auto;"> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> </table> <p>1964</p> </div> <p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, salt cedar, grass, sagebrush and tumbleweed.</p> <hr/>	S19	S20	S30	S29
S19	S20				
S30	S29				
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°57' W., bet. secs. 20 and 29.</p> <p>Over nearly level land.</p>				
40.02	<p>Point for the ¼ sec. cor. of secs. 20 and 29.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T38N R7W</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S20</td> </tr> <tr> <td>S29</td> </tr> </table> <p>1964</p> </div> <p>Deposit glass in the hole alongside the iron post.</p>	¼ S20	S29		
¼ S20					
S29					
48.90	<p>Bladed road, bears N. and S.</p>				
67.90	<p>Track road, bears N. 35° E. and S. 35° W.</p>				
80.04	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, shadscale, bunchgrass and cacti.</p> <hr/>				
	<p>N. 89°55' W., bet. secs. 19 and 30.</p> <p>Over nearly level land.</p>				
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 30.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T38N R7W</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S19</td> </tr> <tr> <td>S30</td> </tr> </table> <p>1964</p> </div> <p>Deposit glass in the hole alongside the iron post.</p>	¼ S19	S30		
¼ S19					
S30					
49.10	<p>Track road, bears N. 15° E. and S. 15° W.</p>				
79.28	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p>				

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, bunchgrass, shadscale and cacti.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30. N. 0°03' W., bet. secs. 19 and 20. Over nearly level land.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 20. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W ¼ S19 S20 1964</p>
45.50	<p>Build a mound of stones W. of the iron post. Track road, bears NE. and SW.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W S18 S17 S19 S20 1964</p>
	<p>from which Triangulation Station RESERVOIR bears N. 58°01' E., 49.50 chs. distant. Build a mound of stones W. of the iron post.</p>
	<p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, bunchgrass, shadscale.</p> <hr/>
40.02	<p>From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. Over nearly level land. Point for the ¼ sec. cor. of secs. 17 and 20. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W ¼ S17 S20 1964</p>
47.80	<p>Build a mound of stones N. of the iron post. Bladed road, bears N. and S.</p>

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

28

<p>CHAINS 63.30</p>	<p>Track road, bears N. 30° E. and S. 30° W.</p>
<p>80.04</p>	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, bunchgrass and shadscale.</p> <hr/> <p>N. 89°51' W., bet. secs. 18 and 19.</p> <p>Over nearly level land.</p>
<p>40.00</p>	<p>Point for the ¼ sec. cor. of secs. 18 and 19.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W ¼ $\frac{S18}{S19}$ 1964</p> <p>Deposit glass in the hole alongside the iron post.</p>
<p>79.18</p>	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, bunchgrass and shadscale.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over nearly level land.</p>
<p>16.50</p>	<p>Wash, 15 lks. wide, 2 ft. deep, drains irregularly W.</p>
<p>34.20</p>	<p>Top of rock ledge, 15 ft. high, bears NE. and SW.</p>
<p>40.00</p>	<p>Point for the ¼ sec. cor. of secs. 17 and 18.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R7W ¼ S18 S17 1964</p>
<p>47.40</p>	<p>Low, rocky ledge, bears S. 75° E. and N. 75° W.</p>
<p>64.50</p>	<p>Low rocky ledge, bears E. and W.</p>
<p>73.30</p>	<p>Low earthen mound.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R7W S 7 S 8 S18 S17 1964</p>

CHAINS

Build a mound of stones W. of the iron post.
 Land, gently rolling.
 Soil, sandy to stony.
 Timber, none.
 Undergrowth, shadscale, snakeweed and scattered grass.

From the cor. of secs. 8, 9, 16 and 17.

N. 89°54' W., bet. secs. 8 and 17.

Over nearly level land.

40.03 Point for the ¼ sec. cor. of secs. 8 and 17.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W

¼ $\frac{S 8}{S17}$
 1964

Build a mound of stones N. of the iron post.

44.20 Bladed road, bears N. and S.

60.60 E. edge of low mesa, bears N. and S.

68.20 W. edge of low mesa, bears N. and S.

80.06 The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling.
 Soil, sandy clay.
 Timber, none.
 Undergrowth, shadscale, snakeweed and scattered grass.

N. 89°48' W., bet. secs. 7 and 18.

Over gently rolling land.

40.00 Point for the ¼ sec. cor. of secs. 7 and 18.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W

¼ $\frac{S 7}{S18}$
 1964

Deposit glass in the hole alongside the iron post.

Over nearly level land.

79.13 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.

Land, nearly level.
 Soil, sandy clay.
 Timber, none.
 Undergrowth, shadscale, snakeweed and scattered grass.

BOOK 4755

Subdivision, T. 38 N., R. 7 W., Arizona

30

30.

CHAINS

From the cor. of secs. 7, 8, 17 and 18.

N. 0°03' W., bet. secs. 7 and 8.

Over nearly level land.

40.00

Point for the 1/4 sec. cor. of secs. 7 and 8.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 1/4
 S 7 | S 8
 1964

Build a mound of stones W. of the iron post.

80.00

Point for the cor. of secs. 5, 6, 7 and 8.

Set the iron post 22 ins. in the ground, cap mkd.

T38N R7W
 S 6 | S 5
 S 7 | S 8
 1964

Build a mound of stones W. of the iron post.

Land, nearly level.

Soil, sandy clay.

Timber, none.

Undergrowth, shadscale, snakeweed and scattered grass.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°55' W., bet. secs. 5 and 8.

Over gently rolling land.

9.20

Wash, 100 lks. wide, 8 ft. deep, drains irregularly NW.

11.10

Wash, 80 lks. wide, 4 ft. deep, drains N. to main wash.

40.03

Point for the 1/4 sec. cor. of secs. 5 and 8.

Set the iron post 24 ins. in the ground, cap mkd.

T38N R7W
 1/4 S 5
 S 8
 1964

Build a mound of stones N. of the iron post.

42.20

Bladed road, bears N. and S.

59.10

E. edge of low mesa, bears S. 20° E. and N. 20° W.

80.06

The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, shadscale, snakeweed and scattered grass and blackbrush.

CHAINS	
	N. 89°49' W., bet. secs. 6 and 7. Over gently rolling land.
3.30	Track road, bears SW. and NE.
15.20	Wash, 50 lks. wide, 6 ft. deep, drains irregularly N.
24.60	Road, track, bears SE. and NW.
31.00	S. point of low mesa, bears N. 10° E. and N. 10° W.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7. Set the iron post 8 ins. in the ground to bedrock, mound with stones to top, cap mkd.
	T38N R7W ¼ $\frac{S\ 6}{S\ 7}$ 1964
79.08	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record. Land, gently rolling. Soil, sandy clay. Timber, none. Undergrowth, shadscale, snakeweed, scattered grass and blackbrush.
	From the cor. of secs. 5, 6, 7 and 8. N. 0°13' E., bet. secs. 5 and 6. Over nearly level land.
2.90	Track road, bears N. 50° E. and S. 50° W.
40.00	Point for the ¼ sec. cor. of secs. 5 and 6. Set the iron post 22 ins. in the ground, cap mkd.
	T38N R7W ¼ S 6 S 5 1964
	Build a mound of stones W. of the iron post.
59.80	Left bank of wash, bears E. and W.
60.70	Center of wash, 15 ft. deep, drains W.
61.70	Right bank of same wash, bears E. and W.
80.00	The cor. of secs. 5 and 6, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the official record. Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, shadscale, snakeweed, scattered grass and black brush.

CHAINS

General Description

The elevation of Township 38 North, Range 7 West, ranges from about 5,000 feet above sea level at the southeast corner to about 4,800 feet above sea level at the northwest corner of the township. The general drainage is to the northwest. The soil is a fine sandy clay which has been subject to considerable erosion, and numerous water-spreading dikes and reservoir dams have been built throughout the township, which also contains several windmill wells. A major bladed dirt road from the Short Creek area to the Mt. Trumbull area cuts from north to south through Sections 5, 8, 17, 20, 29 and 32, with several track roads branching away to a large portion of the township.

There are no trees in the township. The south portion has a fair amount of grass, along with varied amounts of shadscale, sage and cacti. The north portion has scattered grass, sage, cacti, snakeweed and black brush.

No evidence of mineral deposits was noted during the course of the survey.

BOOK 4755
CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 18 day of February, 1963,
and supplemental special instructions dated July 24, 1963,
I have made a completion survey of the subdivisional lines of Township
38 North, Range 7 West,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 24, 1965
(Date)

Boyd S. Owens
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date OCT 20 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the completion survey of the subdivisional lines
of Township 38 North, Range 7 West, of the Gila and Salt River Meridian
in the State of Arizona,

executed by Boyd S. Owens, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JAN 6 1966
(Date)

[Signature]
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Engineering)~~