

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

RETRACEMENT

of the

East Boundary

for

Alignment Only

SURVEY

of the

Subdivisional Lines

Township 39 North, Range 7 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated February 18, 1963, which provided for the surveys
included under Group Number 393, approved February 20, 1963,
and assignment instructions dated June 29, 1963.

Survey commenced July 6, 19 64

Survey completed July 23, 19 64

1A

BOOK 4757 INDEX DIAGRAM

Township 39 North, Range 7 West

6 35 34	5 26 34	4 20 25	3 14 19	2 8 14	1 2 8	2
7 33 33	8 25 32	9 19 24	10 13 18	11 7 13	12 2 7	2
18 32 31	17 23 31	16 18 23	15 12 17	14 6 12	13 2 6	2
19 30 29	20 22 29	21 17 22	22 11 16	23 5 11	24 2 4	2
30 28 27	29 21 27	28 16 21	27 10 15	26 4 9	25 1 3	1
31 26	32 20	33 14	34 9	35 3	36 1	1

CHAINS

The north and east boundaries were surveyed in 1916 by Matthews and Nash. The west boundary was surveyed in 1937 by Kinsey, Muscott, Warner and Motoh. The south boundary was surveyed in 1954 by D. E. Harding.

The following field notes are those of a retracement of the east boundary for alignment only, and of the survey of the subdivisional lines of Township 39 North, Range 7 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated February 18, 1963.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 36°43'49.3" North, and Longitude 112°59'18.3" West, as determined from ties to the southeast corner of Township 38 North, Range 7 West, Gila and Salt River Meridian, Arizona.

The magnetic declination was found to be 15°45' East.

Retracement of the East Boundary of Township 39 North, Range 7 West, Arizona, for Alignment Only

The following retracement of the east boundary for alignment only, was performed to establish a mean course for the east boundary in order that the meridional section lines could be run parallel to the governing east boundary. The topography was found to be essentially the same as reported in the 1916 survey.

Beginning at the corner of Tps. 38 and 39 N., Rs. 6 and 7 W., monumented by an iron post 3 ins. diam., as described in the official record.

N. 0°10' W., bet. secs. 31 and 36.

40.00 Record dist. for the ¼ sec. cor. of secs. 31 and 36, monumented by an iron post 1 inch diam., as described in the official record.

80.00 Record dist. for the cor. of secs. 25, 30, 31 and 36, monumented by an iron post 2 ins. diam., as described in the official record.

N. 0°08' W., bet. secs. 25 and 30.

40.10 Record dist. for the witness ¼ sec. cor. of secs. 25 and 30, monumented by an iron post 1 inch diam., as described in the official record.

BOOK 4757

Retracement of the East Boundary of Township 39 North,
Range 7 West, Arizona, for Alignment Only

2

2.

CHAINS		
	Thence N. 0°06' W. from witness corner	
39.90	Record dist. for the cor. of secs. 19, 24, 25 and 30, monumented by an iron post 2 ins. diam., as described in the official record.	
	N. 0°11' W., bet. secs. 19 and 24.	
40.00	Record dist. for the ¼ sec. cor. of secs. 19 and 24, monumented by an iron post 1 inch diam., as described in the official record.	
	Thence N. 0°03' W.	
40.00	Record dist. for the cor. of secs. 13, 18, 19 and 24, monumented by an iron post 2 ins. diam., as described in the official record.	
	N. 0°08' W., bet. secs. 13 and 18.	
40.00	Record dist. for the ¼ sec. cor. of secs. 13 and 18, monumented by an iron post 1 inch diam., as described in the official record.	
	Thence N. 0°07' W.	
40.00	Record dist. for the cor. of secs. 7, 12, 13 and 18, monumented by an iron post 2 ins. diam., as described in the official record.	
	N. 0°04' W., bet. secs. 7 and 12.	
40.00	Record dist. for the ¼ sec. cor. of secs. 7 and 12, monumented by an iron post 1 inch diam., as described in the official record.	
	Thence N. 0°07' W.	
40.00	Record dist. for the cor. of secs. 1, 6, 7 and 12, monumented by an iron post 2 ins. diam., as described in the official record.	
	N. 0°05' W., bet. secs. 1 and 6.	
40.00	Record dist. for the ¼ sec. cor. of secs. 1 and 6, monumented by an iron post 1 inch diam., as described in the official record.	
	Thence N. 0°09' W.	
40.00	Record dist. for the cor. of Tps. 39 and 40 N., Rs. 6 and 7 W., monumented by an iron post 3 ins. diam., as described in the official record.	
	Subdivision, T. 39 N., R. 7 W., Arizona	

CHAINS	
	<p>The meridional lines, as surveyed in the subdivision of Tp. 39 N., R. 7 W., are parallel to the mean course of the E. bdy. of the Tp., which was found to be N. 0°07' W.</p> <p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the official record.</p> <p>N. 0°08' W., bet. secs. 35 and 36.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>4.50 Track road, bears E. and W.</p> <p>18.00 Draw, drains irregularly NW.</p> <p>26.80 Wash, 30 lks. wide, 4 ft. deep, drains N. 25° W.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 35 and 36.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ¼ S35 S36 1964</p>
	<p>Build a mound of stones W. of the iron post.</p> <p>Continue over nearly level land.</p> <p>80.00 Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S26 S25 S35 S36 1964</p> <p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and scattered cacti.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>N. 89°47' W., bet. secs. 25 and 36.</p> <p>Desc. gentle W. slope, through scattered undergrowth.</p> <p>39.97 Point for the ¼ sec. cor. of secs. 25 and 36.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S25 ¼ S36 1964</p> <p>Build a mound of stones N. of the iron post.</p>

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

4

4.

CHAINS		
40.60	Small swale, drains S. 80° W.	
60.20	Track road, bears SE. and NW.	
79.94	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and scattered cacti.</p>	
	<hr/> <p>N. 0°08' W., bet. secs. 25 and 26.</p>	
	Over nearly level land, through scattered undergrowth.	
0.50	Gully, drains irregularly SW.	
14.80	Wash, 15 lks. wide, 2 ft. deep, drains SW.	
16.60	Track road, bears irregularly SE. and NW.	
39.50	Low spur, slopes W.	
40.00	<p>Point for the ¼ sec. cor. of secs. 25 and 26.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ¼ S26 S25 1964</p>	
	Build a mound of stones W. of the iron post.	
	Thence over low, rolling hills.	
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S23 S24 S26 S25 1964</p>	
	Build a mound of stones W. of the iron post.	
	Land, low, rolling hills.	
	Soil, gravelly.	
	Timber, none.	
	Undergrowth, bunchgrass, shadscale, sage and cacti.	
	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, previously described, on the E. bdy. of the Tp.</p>	
	N. 89°48' W., bet. secs. 24 and 25.	
	Over nearly level land, through scattered undergrowth.	
15.60	Gully, drains SW.	
25.60	Wash, 30 lks. wide, 4 ft. deep, drains S. 75° W.	

CHAINS		
31.60	Gully, drains S. 75° W.	
39.98	Point for the ¼ sec. cor. of secs. 24 and 25.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T39N R7W ¼ $\frac{S24}{S25}$ 1964	
	Build a mound of stones N. of the iron post.	
	Desc. over gentle SW. slope.	
79.96	The cor. of secs. 23, 24, 25 and 26.	
	Land, gently rolling. Soil, gravelly. Timber, none. Undergrowth, bunchgrass, shadscale, sage and cacti.	
	N. 0°08' W., bet. secs. 23 and 24.	
	Over nearly level land, through scattered undergrowth.	
14.10	Wash, 30 lks. wide, 2 ft. deep, drains S. 25° W.	
40.00	Point for the ¼ sec. cor. of secs. 23 and 24.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T39N R7W ¼ S23 S24 1964	
	Build a mound of stones W. of the iron post.	
53.60	Wash, 40 lks. wide, 2 ft. deep, drains S. 15° W. from irregularly N.	
55.00	Bladed road, bears NE. and SW.	
58.50	Same wash, drains irregularly S. from N. 20° E.	
80.00	Point for the cor. of secs. 13, 14, 23 and 24.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T39N R7W S14 S13 S23 S24 1964	
	Build a mound of stones W. of the iron post.	
	Land, gentle SW. slope. Soil, gravelly. Timber, none. Undergrowth, bunchgrass, shadscale and cacti.	

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

6

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24, previously described, on the E. bdy. of the Tp.</p>
	<p>N. 89°50' W., bet. secs. 13 and 24.</p>
	<p>Over nearly level land, through scattered undergrowth.</p>
0.70	<p>Bladed road, bears irregularly NE. and SW.</p>
11.40	<p>Track road, bears SE. and NW.</p>
14.40	<p>Gully, drains irregularly NW.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 13 and 24.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ $\frac{S13}{S24}$ 1964</p>
	<p>Build a mound of stones N. of the iron post.</p>
61.90	<p>Wash, 70 lks. wide, 2 ft. deep, drains irregularly SW.</p>
80.00	<p>The cor. of secs. 13, 14, 23 and 24.</p>
	<p>Land, gently rolling. Soil, gravelly. Timber, none. Undergrowth, bunchgrass, shadscale and cacti.</p>
	<p>N. 0°08' W., bet. secs. 13 and 14.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
6.50	<p>Bladed road, bears S. 80° E. and N. 80° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 13 and 14.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S14 S13 1964</p>
	<p>Build a mound of stones W. of the iron post.</p>
40.12	<p>Fence, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p>
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S11 S12 S14 S13 1964</p>
	<p>Build a mound of stones W. of the iron post.</p>
	<p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>

CHAINS	
40.00	<p>From the cor. of secs. 7, 12, 13 and 18, previously described, on the E. bdy. of the Tp.</p> <p>N. 89°50' W., bet. secs. 12 and 13.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 12 and 13.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ¼ <u>S12</u> S13 1964</p> <p>Build a mound of stones N. of the iron post.</p>
78.10	<p>Gully, drains irregularly N.</p>
80.00	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p> <hr/> <p>N. 0°08' W., bet. secs. 11 and 12.</p> <p>Over nearly level land, through scattered undergrowth.</p>
3.30	<p>Gully, drains W., curving to NW.</p>
5.70	<p>Gully, drains SW.</p>
6.30	<p>Gully, drains SW.</p>
20.20	<p>Track road, bears NE. and SW.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 11 and 12.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ¼ S11 S12 1964</p> <p>Build a mound of stones W. of the iron post.</p> <p>Desc. over gentle NW. slope.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S 2 S 1 S11 S12 1964</p> <p>Build a mound of stones W. of the iron post.</p>

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

8

8.

CHAINS	
	<p>Land, gently rolling. Soil, gravelly. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, previously described, on the E. bdy. of the Tp.</p>
	<p>N. 89°50' W., bet. secs. 1 and 12.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
0.20	<p>Track road, bears N. and S.</p>
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ $\frac{S 1}{S12}$ 1964</p>
	<p>Build a mound of stones N. of the iron post.</p>
48.60	<p>Track road, bears S. 80° E. and N. 80° W.</p>
80.08	<p>The cor. of secs. 1, 2, 11 and 12.</p>
	<p>Land, gently rolling. Soil, gravelly. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
	<p>N. 0°02' W., bet. secs. 1 and 2.</p>
	<p>Over gentle NW. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S2 S1 1964</p>
	<p>Build a mound of stones W. of the iron post.</p>
79.72	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p>
	<p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, sage and shadscale.</p>
	<p>From the cor. of secs. 34 and 35 on the S. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., as described in the official record.</p>

CHAINS	
	N. 0°08' W., bet. secs. 34 and 35.
	Over gentle N. slope.
5.80	Track road, bears irregularly E. and W.
6.70	Gully, drains irregularly W.
36.50	Track road, bears SE. and NW.
40.00	Point for the ¼ sec. cor. of secs. 34 and 35.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ S34 S35 1964
	from which
	The top of a dike on the SW. side of "Big Warren" Reservoir bears N. 49°20' E., 20.30 chs. dist.
	Deposit broken glass at base of the iron post.
47.40	Wash, 90 lks. wide, 12 ft. deep, drains irregularly W.
50.40	Gully, drains irregularly W.
52.60	Wash, 40 lks. wide, 10 ft. deep, drains irregularly W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W S27 S26 S34 S35 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level.
	Soil, gravelly.
	Timber, none.
	Undergrowth, bunchgrass and shadscale.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°46' W., bet. secs. 26 and 35.
	Over nearly level land, through scattered undergrowth.
0.30	Gully, drains irregularly SW.
16.60	Gully, drains irregularly SW.
39.92	Point for the ¼ sec. cor. of secs. 26 and 35.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39NR7W ¼ S26 S35 1964

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

10

10.

CHAINS		
	Deposit broken glass at base of the iron post.	
53.50	Wash, 30 lks. wide, 3 ft. deep, drains irregularly S.	
55.30	Diversion dam, bears N. and S.	
59.00	Gully, drains irregularly S.	
74.30	Bladed road, bears SE. and NW.	
79.84	The cor. of secs. 26, 27, 34 and 35.	
	Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, bunchgrass and shadscale.	
	N. 0°08' W., bet. secs. 26 and 27.	
	Over nearly level land, through scattered undergrowth.	
8.60	Bladed road, bears SE. and NW.	
12.30	Track road, bears NE. and SW.	
25.20	Track road, bears SE. and NW.	
40.00	Point for the ¼ sec. cor. of secs. 26 and 27.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T39N R7W ¼ S27 S26 1964	
	from which	
	A stock pond bears N. 80°42' E., 47.80 chs. dist.	
	Deposit broken glass at base of the iron post.	
42.90	Gully, drains irregularly NW.	
52.00	Track road, bears irregularly E. and W.	
62.80	Bladed road, bears irregularly NE. and SW.	
80.00	Point for the cor. of secs. 22, 23, 26 and 27.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T39N R7W S22 S23 S27 S26 1964	
	Build a mound of stones W. of the iron post.	
	Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, scattered sage and snakeweed.	

CHAINS	
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°45' W., bet. secs. 23 and 26.</p> <p>Over nearly level land, through scattered undergrowth.</p>
18.20	Wash, 30 lks. wide, 2 ft. deep, drains S. 15° W.
20.90	Gully, drains irregularly S.
25.80	Track road, bears N. 15° E. and S. 15° W.
39.93	<p>Point for the ¼ sec. cor. of secs. 23 and 26.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ¼ $\frac{S23}{S26}$ 1964</p>
52.00	Bladed road, bears N. 60° E. and S. 60° W.
79.86	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, scattered sage and snakeweed.</p>
40.00	<p>N. 0°08' W., bet. secs. 22 and 23.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 23.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ¼ S22 S23 1964</p>
80.00	<p>Deposit broken glass at the base of the iron post.</p> <p>Continue over nearly level land.</p> <p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S15 S14 S22 S23 1964</p> <p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.</p>

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

12

12.

CHAINS

From the cor. of secs. 13, 14, 23 and 24.
 N. 89°45' W., bet. secs. 14 and 23.
 Over nearly level land, through scattered undergrowth.

39.93

Point for the 1/4 sec. cor. of secs. 14 and 23.
 Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 1/4 S14
 S23
 1964

Deposit broken glass at base of the iron post.
 Continue over nearly level land.

79.86

The cor. of secs. 14, 15, 22 and 23.
 Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, bunchgrass, shadscale and snakeweed.

N. 0°08' W., bet. secs. 14 and 15.
 Over nearly level land, through scattered undergrowth.

39.60

Bladed road, bears E. and W.

39.80

Fence, bears E. and W.

40.00

Point for the 1/4 sec. cor. of secs. 14 and 15.
 Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 1/4
 S15|S14
 1964

Deposit broken glass at base of the iron post.

70.60

Track road, bears N. 80° E. and S. 80° W.

80.00

Point for the cor. of secs. 10, 11, 14 and 15.
 Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 S10|S11
 S15|S14
 1964

Build a mound of stones W. of the iron post.

Land, nearly level.
 Soil, gravelly loam.
 Timber, none.
 Undergrowth, bunchgrass, shadscale, sage and cacti.

CHAINS	
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89°45' W., bet. secs. 11 and 14.
	Over nearly level land, through scattered undergrowth.
39.94	Point for the ¼ sec. cor. of secs. 11 and 14.
	Set the iron post 22 ins. in the ground, in a collar of stone, cap mkd.
	<p style="text-align: center;">T39N R7W $\frac{1}{4} \frac{S11}{S14}$ 1964</p>
	Deposit broken glass at base of the iron post.
53.70	Ditch, 20 lks. wide, 2 ft. deep, drains SW.
79.88	The cor. of secs. 10, 11, 14 and 15.
	Land, nearly level.
	Soil, gravelly loam.
	Timber, none.
	Undergrowth, bunchgrass, shadscale, sage and cacti.
	<hr/>
	N. 0°08' W., bet. secs. 10 and 11.
	Over nearly level land, through scattered undergrowth.
19.90	Track road, bears irregularly NE. and SW.
27.20	Begin desc. over gentle N. slope.
40.00	Point for the ¼ sec. cor. of secs. 10 and 11.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S10 S11 1964</p>
	Deposit broken glass at base of the iron post.
67.60	Track road, bears S. 15° E. and irregularly N.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W $\frac{S3}{S10} \frac{S2}{S11}$ 1964</p>
	Build a mound of stones W. of the iron post.
	Land, nearly level.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunchgrass and shadscale.
	<hr/>

BOOK 4757

Subdivision, T. 39 N., R. 7 W. Arizona

14

14.

CHAINS		
39.94	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°46' W., bet. secs. 2 and 11.</p> <p>Over gentle W. slope, through scattered undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stones, cap mkd.</p>	
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ $\frac{S 2}{S 11}$ 1964</p>	
42.00	<p>Gully, drains irregularly SW.</p>	
79.88	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>	
40.00	<p>N. 0°08' W., bet. secs. 2 and 3.</p> <p>Over gentle NW. slope, through scattered undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S 3 S 2 1964</p>	
51.10	<p>Deposit broken glass at base of the iron post.</p> <p>Track road, bears irregularly E. and W.</p>	
59.60	<p>Gully, drains W.</p>	
61.20	<p>Gully, drains SW.</p>	
79.36	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>	
	<p>From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., as described in the official record.</p> <p>N. 0°09' W., bet. secs. 33 and 34.</p> <p>Over nearly level land, through scattered undergrowth.</p>	

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

CHAINS	
7.30	Track road, bears SE. and NW.
7.60	Wash, 20 lks. wide, 8 ft. deep, drains W. 1 chain, thence SW.
19.90	Gully, drains irregularly W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S33 S34 1964</p>
	Deposit broken glass at base of the iron post.
62.00	Wash, 10 lks. wide, 2 ft. deep, drains irregularly W., curving S.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W S28 S27 S33 S34 1964</p>
	Build a mound of stones W. of the iron post.
	Land, nearly level.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunchgrass, shadscale, sage and snakeweed.
	<hr/> From the cor. of secs. 26, 27, 34 and 35.
	N. 89°45' W., bet. secs. 27 and 34.
	Over nearly level land, through scattered undergrowth.
10.90	Gully, drains irregularly W.
12.50	Wash, 20 lks. wide, 4 ft. deep, drains irregularly SW.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S27 S34 1964</p>
	Deposit broken glass at base of the iron post.
50.70	Wash, 10 lks. wide, 2 ft. deep, drains irregularly SW.
80.12	The cor. of secs. 27, 28, 33 and 34.
	Land, nearly level.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunchgrass, shadscale, sage and snakeweed.

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

16

16.

CHAINS	
	N. 0°09' W., bet. secs. 27 and 28.
	Over nearly level land, through scattered undergrowth.
5.70	Bladed road, bears NE. and SW.
7.40	Gully, drains irregularly W.
25.10	Wash, 10 lks. wide, 4 ft. deep, drains W., curving S.
25.50	Gully, drains SW.
40.00	Point for the ¼ sec. cor. of secs. 27 and 28.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ S28 S27 1964
	Deposit broken glass at base of the iron post.
46.80	Gully, drains S. 30° W.
69.80	Bladed road, bears S. 80° E. and N. 75° W.
75.20	Wash, 10 lks. wide, 3 ft. deep, drains irregularly W.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W S21 S22 S28 S27 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunchgrass, shadscale, sage and snakeweed.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°47' W., bet. secs. 22 and 27.
	Over nearly level land, through scattered undergrowth.
40.06	Point for the ¼ sec. cor. of secs. 22 and 27.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ S22 S27 1964
	Deposit broken glass at base of the iron post.
	Continue over nearly level land.
80.12	The cor. of secs. 21, 22, 27 and 28.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale, sage and snakeweed.</p> <hr/> <p>N. 0°09' W., bet. secs. 21 and 22.</p> <p>Over nearly level land, through scattered undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W $\frac{1}{4}$ S21 S22 1964</p>
	<p>Deposit broken glass at base of the iron post.</p> <p>Continue over nearly level land.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S16 S15 S21 S22 1964</p>
	<p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°47' W., bet. secs. 15 and 22.</p> <p>Over nearly level land, through scattered undergrowth.</p>
40.07	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W $\frac{1}{4}$ S15 S22 1964</p>
	<p>Deposit broken glass at base of the iron post.</p> <p>Continue over nearly level land.</p>
80.14	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p> <hr/>

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

18

18.

CHAINS	
	N. 0°09' W., bet. secs. 15 and 16.
	Over nearly level land, through scattered undergrowth.
37.40	Track road, bears NE. and SW.
38.50	Fence, bears S. 60° W. and N. 60° E. 4.00 chs. to cor.
40.00	Point for the ¼ sec. cor. of secs. 15 and 16.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ S16 S15 1964
	Deposit broken glass at base of the iron post.
43.10	Bladed road, bears SE. and NW.
66.00	Small spur, slopes W.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W S 9 S10 S16 S15 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, bunchgrass and shadscale.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89°48' W., bet. secs. 10 and 15.
	Over nearly level land, through scattered undergrowth.
40.07	Point for the ¼ sec. cor. of secs. 10 and 15.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ S10 S15 1964
	from which
	The center of a catch pond bears S. 86°14' W., 14.40 chs. dist.
	Deposit broken glass at base of the iron post.
79.30	Fence, bears N. and S.
80.14	The cor. of secs. 9, 10, 15 and 16.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, shadscale.</p> <hr/> <p>N. 0°09' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
21.40	Gully, drains irregularly W.
40.00	Point for the ¼ sec. cor. of secs. 9 and 10.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p>T39N R7W ¼ S 9 S10 1964</p>
	Deposit broken glass at base of the iron post.
47.10	Gully, drains irregularly W.
50.70	Gully, drains irregularly W.
52.10	Gully, drains irregularly W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p>T39N R7W S 4 S 3 S 9 S10 1964</p>
	Build a mound of stones W. of the iron post.
	<p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, shadscale.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°48' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
16.70	Gully, drains NW.
35.00	Track road, bears N. 15° E. and S. 15° W.
40.08	Point for the ¼ sec. cor. of secs. 3 and 10.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p>T39N R7W ¼ S 3 S10 1964</p>
	Deposit broken glass at base of the iron post.

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

20

20.

CHAINS	
52.00	Gully, drains irregularly W. from S.
57.80	Gully, drains irregularly NW.
72.40	Small wash, drains irregularly SW., curving W.
80.16	The cor. of secs. 3, 4, 9 and 10.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, shadscale.
	<hr/> N. 0°02' W., bet. secs. 3 and 4.
	Over nearly level land, through scattered undergrowth.
35.70	Gully, drains irregularly W.
40.00	Point for the ¼ sec. cor. of secs. 3 and 4.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W ½ S 4 S 3 1964</p>
	from which
	<p style="text-align: center;">A dike on the W. edge of a reservoir bears N. 84°20' E., 28.60 chs. dist.</p>
	Deposit broken glass at base of the iron post.
79.05	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, shadscale.
	<hr/> From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the official record.
	N. 0°10' W., bet. secs. 32 and 33.
	Over nearly level land, through scattered undergrowth.
18.00	Bladed road, bears N. 40° E. and S. 40° W.
40.00	Point for the ¼ sec. cor. of secs. 32 and 33.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W ½ S32 S33 1964</p>
	Deposit broken glass at base of the iron post.

CHAINS	
75.30	Wash, 10 lks. wide, 3 ft. deep, drains irregularly W.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W S29 S28 S32 S33 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89°46' W., bet. secs. 28 and 33.
	Over nearly level land, through scattered undergrowth.
8.00	Bladed road, bears N. 30° E. and S. 30° W.
39.99	Point for the ¼ sec. cor. of secs. 28 and 33.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ S28 S33 1964
	Deposit broken glass at base of the iron post.
76.00	Gully, drains NW.
79.98	The cor. of secs. 28, 29, 32 and 33.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.
	N. 0°10' W., bet. secs. 28 and 29.
	Over nearly level land, through scattered undergrowth.
33.40	Gully, drains irregularly W.
40.00	Point for the ¼ sec. cor. of secs. 28 and 29.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ S29 S28 1964
	Deposit broken glass at base of the iron post.

CHAINS

70.10 Bladed road, bears E. and W.

80.00 Point for the cor. of secs. 20, 21, 28 and 29.
Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
S20|S21
S29|S28
1964

Build a mound of stones W. of the iron post.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, bunchgrass and shadscale.

From the cor. of secs. 21, 22, 27 and 28.
N. 89°46' W., bet. secs. 21 and 28.
Over nearly level land, through scattered undergrowth.

28.38 Wash, 30 lks. wide, 13 ft. deep, drains irregularly W. from S. 65° E.

39.99 Point for the ¼ sec. cor. of secs. 21 and 28.
Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
¼ S21
S28
1964

Deposit broken glass at base of the iron post.

40.40 Bladed road, bears N. 20° W. and S. 20° E., curving S.

56.60 Drainage ditch, drains N. 20° W.

79.98 The cor. of secs. 20, 21, 28 and 29.
Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, bunchgrass and shadscale.

N. 0°10' W., bet. secs. 20 and 21.
Over nearly level land, through scattered undergrowth.

32.00 The NE. cor. of a fenced Experimental Range Plot, approximately 6.00 chs. sq., bears W., 0.54 chs. dist.

40.00 Point for the ¼ sec. cor. of secs. 20 and 21.
Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
¼
S20|S21
1964

CHAINS	
70.60 79.40 80.00	<p>Deposit broken glass at base of the iron post.</p> <p>Bladed road, bears N. 15° E. and S. 15° E. Bladed road, bears N. 70° E. and S. 70° W. Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set the iron post 20 ins. in the ground in a collar of stone, cap mkd.</p> <p style="text-align: center;">T39N R7W S17 S16 S20 S21 1964</p> <p>from which</p> <p style="padding-left: 40px;">A post on the W. end of a cattle guard bears N. 65°20' E., 2.04 chs. dist.</p> <p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
39.99	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°46' W., bet. secs. 16 and 21.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 21.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ¼ S16 S21 1964</p>
49.10 57.20 78.00 79.98	<p>Deposit broken glass at base of the iron post.</p> <p>Low ridge, bears N. and S.</p> <p>Small wash drains irregularly W.</p> <p>Junction of roads, bearing N. 10° E., S. 10° W. and S. 70° W.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
0.86	<p>N. 0°10' W., bet. secs. 16 and 17.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Fence, bears W. and E. for 2.50 chs., thence N. 70° E.</p>

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

24

24.

CHAINS

17.70 Bladed road, bears S. 15° E. and N. 15° W.

24.50 Gully, drains S. 60° W.

32.10 Gully, drains S. 20° W.

40.00 Point for the 1/4 sec. cor. of secs. 16 and 17.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W

1/4

S17|S16

1964

Deposit broken glass at base of the iron post.

41.50 Bladed road, bears N. 10° E. and S. 15° W.

43.80 Wash, 15 lks. wide, 3 ft. deep, drains irregularly W.

59.25 Fence, bears N. 11° E. and S. 11° W.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W

S 8|S 9

S17|S16

1964

Build a mound of stones W. of the iron post.

Land, nearly level.

Soil, sandy loam.

Timber, none.

Undergrowth, bunchgrass and shadscale.

From the cor. of secs. 9, 10, 15 and 16.

N. 89°45' W., bet. secs. 9 and 16.

Over nearly level land, through scattered undergrowth.

33.30 Bladed road, bears SE. and NW.

40.00 Point for the 1/4 sec. cor. of secs. 9 and 16.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W

1/4 S 9

S16

1964

Deposit broken glass at base of the iron post.

74.80 Bladed road, bears N. and S.

77.74 Fence, bears N. and S.

80.00 The cor. of secs. 8, 9, 16 and 17.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p> <hr/> <p>N. 0°10' W., bet. secs. 8 and 9. Over nearly level land, through scattered undergrowth.</p>
3.33	Fence, bears S. 27° E. and N. 27° W.
40.00	<p>Point for the ½ sec. cor. of secs. 8 and 9. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ½ S 8 S 9 1964</p> <p>Deposit broken glass at base of the iron post. Continue over nearly level land.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S 5 S 4 S 8 S 9 1964</p> <p>Build a mound of stones W. of the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass, shadscale and snakeweed.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10. N. 89°44' W., bet. secs. 4 and 9. Over nearly level land, through scattered undergrowth.</p>
40.00	<p>Point for the ½ sec. cor. of secs. 4 and 9. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W ½ S 4 S 9 1964</p> <p>Deposit broken glass at base of the iron post.</p>
66.40	Drainage ditch, drains N.
67.00	Bladed road, bears N. 10° E. and S. 10° W.
80.00	The cor. of secs. 4, 5, 8 and 9.

CHAINS

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, scattered bunchgrass and shadscale.

N. 0°02' W., bet. secs. 4 and 5.

Over gently rolling land, through scattered undergrowth.

10.50 Dike on S. edge of a reservoir.

14.24 Center of same reservoir.

18.08 Dike on N. edge of same reservoir.

40.00 Point for the ¼ sec. cor. of secs. 4 and 5.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
¼
S 5 | S 4
1964

Deposit broken glass at base of the iron post.

Continue over nearly level land.

78.65 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with the lower portion of a cement filled 2-inch iron post, with the remainder of the iron post and brass cap lying alongside.

At the same point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and over the lower portion of the original iron post, cap mkd.

T40N R7W
S32 | S33
S 5 | S 4
T39N
1964

Rebuild the mound of stones W. of the iron post.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, bunchgrass and shadscale.

From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the official record.

N. 0°10' W., bet. secs. 31 and 32.

Over gently rolling land, through scattered undergrowth.

29.60 Gully, drains irregularly W., curving to NW.

34.40 Track road, bears S. 30° E. and N. 30° W.

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W $\frac{1}{4}$ S31 S32 1964</p> <p>Deposit broken glass at base of the iron post.</p> <p>Thence over gently rolling land.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W S30 S29 S31 S32 1964</p> <p>Build a mound of stones W. of the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
17.70	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. $89^{\circ}45'$ W., bet. secs. 29 and 32.</p> <p>Over nearly level land, through scattered undergrowth.</p>
40.00	<p>Bladed road, bears N. and S.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W $\frac{1}{4}$ S29 S32 1964</p> <p>Deposit broken glass at base of the iron post.</p> <p>Continue over nearly level land.</p>
80.00	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, scattered bunchgrass and shadscale.</p>
5.00	<p>N. $89^{\circ}45'$ W., bet. secs. 30 and 31.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Gully, drains irregularly SE.</p>

BOOK 4757

Subdivision, T. 39 N., R. 7 W., Arizona

28

28.

CHAINS	
17.00	Wash, 30 lks. wide, 3 ft. deep, drains SE.
19.10	Gully, drains N.
36.00	Wash, 40 lks. wide, 3 ft. deep, drains irregularly W.
39.00	Same wash, drains S. 80° W.
40.00	Point for the ¼ sec. cor. of secs. 30 and 31.
	Set the iron post 22 ins. in the ground, cap mkd.
	T39N R7W ¼ $\frac{S30}{S31}$ 1964
	from which
	An alkali seep, bears S. 67°56' W., 4.40 chs. dist.
	Deposit broken glass at base of the iron post.
42.50	Bladed road, bears S. 20° E. and N. 20° W.
60.70	Wash, 30 lks. wide, 8 ft. deep, drains irregularly W.
75.84	True point for the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., (reported as the true point for secs. 25 and 36 only, in the 1937 survey of the E. bdy. of T. 39 N., R. 8 W.).
	from which
	The witness cor. of secs. 25, 30, 31 and 36 bears S. 2.50 chs. dist., monumented by an iron post 2 ins. diam., with brass cap mkd.
	W C T39N R8W R7W S25 S30 S36 S31 1937
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale..
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°10' W., bet. secs. 29 and 30.
	Over nearly level land, through scattered undergrowth.
11.70	Dike on S. edge of a reservoir.
17.70	Dike on N. edge of same reservoir.
23.80	Drainage ditch, drains E.
40.00	Point for the ¼ sec. cor. of secs. 29 and 30.
	Set the iron post 22 ins. in the ground, cap mkd.

CHAINS	
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S30 S29 1964</p> <p>Deposit broken glass at base of the iron post. Continue over nearly level land.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30. Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R7W $\frac{1}{4}$ S19 S20 S30 S29 1964</p> <p>Build a mound of stones W. of the iron post. Land, nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, moderate sage and shadscale.</p>
40.00	<p>From the cor. of secs. 20, 21, 28 and 29. N. 89°47' W., bet. secs. 20 and 29. Over nearly level land, through scattered undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29. Set the iron post 22 ins. in the ground, cap mkd.</p>
60.40	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S20 S29 1964</p> <p>Deposit broken glass at base of the iron post.</p>
67.90	<p>Track road, bears SE. and NW.</p>
80.00	<p>Bladed road, bears N. and S.</p> <p>The cor. of secs. 19, 20, 29 and 30.</p>
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p>
	<p>N. 89°46' W., bet. secs. 19 and 30. Over nearly level land, through scattered undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30. Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S19 S30 1964</p>

CHAINS											
	<p>Deposit broken glass at base of the iron post.</p> <p>Continue over nearly level land.</p>										
75.50	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., (reported as the cor. of secs. 24 and 25 only, in the 1937 survey of the E. bdy. of T. 39 N., R. 8 W.), monumented by an iron post 2 ins. diam., cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T39N</td></tr> <tr><td>R8W</td><td>R7W</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1937</td></tr> </table> </div> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and shadscale.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°10' W., bet. secs. 19 and 20.</p> <p>Over nearly level land, through scattered undergrowth.</p>	T39N		R8W	R7W	S24	S19	S25	S30	1937	
T39N											
R8W	R7W										
S24	S19										
S25	S30										
1937											
20.80	Gully, drains irregularly W.										
34.00	Bladed road, bears N. 75° E. and W.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T39N R7W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2">1964</td></tr> </table> </div>	T39N R7W		1/4		S19	S20	1964			
T39N R7W											
1/4											
S19	S20										
1964											
46.20	<p>Deposit broken glass at base of the iron post.</p> <p>Gully, drains irregularly W.</p>										
68.30	Gully, drains irregularly W.										
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T39N R7W</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2">1964</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">The center of a reservoir, bears S. 6°43' E., 21.60 chs. dist.</p> <p style="padding-left: 40px;">The center of an adjoining reservoir bears S. 6°02' E., 17.30 chs. dist.</p> <p>Build a mound of stones W. of the iron post.</p>	T39N R7W		S18	S17	S19	S20	1964			
T39N R7W											
S18	S17										
S19	S20										
1964											

CHAINS	
	<p>Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, bunchgrass, shadscale and cacti.</p>
	<p>From the cor. of secs. 16, 17, 20 and 21.</p>
	<p>N. 89°48' W., bet. secs. 17 and 20.</p>
	<p>Over nearly level land, through scattered undergrowth.</p>
7.80	<p>Wash, 10 lks. wide, 1 ft. deep, drains S.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 17 and 20.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W ¼ $\frac{S17}{S20}$ 1964</p>
	<p>Deposit broken glass at base of the iron post.</p>
	<p>Continue over nearly level land.</p>
80.00	<p>The cor. of secs. 17, 18, 19 and 20.</p>
	<p>Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, bunchgrass, shadscale and cacti.</p>
	<p>N. 89°48' W., bet. secs. 18 and 19.</p>
	<p>Over nearly level land, through scattered undergrowth.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 18 and 19.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R7W ¼ $\frac{S18}{S19}$ 1964</p>
	<p>Deposit broken glass at base of the iron post.</p>
48.00	<p>Track road, bears S. 85° E. and N. 85° W.</p>
75.19	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., (reported as the cor. of secs. 13 and 24 only, in the 1937 survey of the E. bdy. of T. 39 N., R. 8 W.), monumented by an iron post 2 ins. diam., cap mkd.</p>
	<p style="text-align: center;">T39N R8W R7W S13 S18 S24 S19 1937</p>

CHAINS

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, bunchgrass, shadscale and cacti.

From the cor. of secs. 17, 18, 19 and 20.
N. 0°10' W., bet. secs. 17 and 18.
Over nearly level land, through scattered undergrowth.

0.54 Fence, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 $\frac{1}{4}$
S18 | S17
1964

Deposit broken glass at base of the iron post.

58.80 Gully, drains irregularly SW.

60.60 Gully, drains S. 15° W.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
S 7 | S 8
S18 | S17
1964

Build a mound of stones W. of the iron post.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, bunchgrass, shadscale and cacti.

From the cor. of secs. 8, 9, 16 and 17.
N. 89°48' W., bet. secs. 8 and 17.
Over nearly level land, through scattered undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 $\frac{1}{4}$ S 8
S17
1964

Deposit broken glass at base of the iron post.

CHAINS	
	Continue over nearly level land.
80.00	The cor. of secs. 7, 8, 17 and 18.
	Land, nearly level.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunchgrass, shadscale and cacti.
	N. 89°45' W., bet. secs. 7 and 18.
	Over nearly level land, through scattered undergrowth.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ $\frac{S 7}{S 18}$ 1964</p>
	Deposit broken glass at base of the iron post.
	Continue over nearly level land.
74.86	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., (reported as the cor. of secs. 12 and 13 only, in the 1937 survey of the E. bdy. of T. 39 N., R. 8 W.), monumented by an iron post 2 ins. diam., cap mkd.
	<p style="text-align: center;">T39N R8W R7W <u>S12 S 7</u> S13 S18 1937</p>
	Land, nearly level.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunchgrass, shadscale and cacti.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°10' W., bet. secs. 7 and 8.
	Over nearly level land, through scattered undergrowth.
1.00	Gully, drains irregularly W.
26.80	Gully, drains N. 20° E.
40.00	Point for the ¼ sec. cor. of secs. 7 and 8.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R7W $\frac{1}{4}$ S 7 S 8 1964</p>
	Deposit broken glass at base of the iron post.

CHAINS

71.30 Gully, drains irregularly W.
 73.20 Wash, 15 lks. wide, 3 ft. deep, drains W.
 73.80 Gully, drains SW.
 80.00 Point for the cor. of secs. 5, 6, 7 and 8.
 Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 S 6 | S 5
 S 7 | S 8
 1964

Build a mound of stones W. of the iron post.
 Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, shadscale.

From the cor. of secs. 4, 5, 8 and 9.
 N. 89°49' W., bet. secs. 5 and 8.
 Over nearly level land, through scattered undergrowth.

39.19 Fence, bears SE. and NW.
 39.98 Point for the ¼ sec. cor. of secs. 5 and 8.
 Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 ¼ S 5
 S 8
 1964

Deposit broken glass at base of the iron post.
 Continue over nearly level land.

79.96 The cor. of secs. 5, 6, 7 and 8.
 Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, bunchgrass and shadscale.

N. 89°49' W., bet. secs. 6 and 7.
 Over nearly level land, through scattered undergrowth.

12.70 Gully, drains SW.
 14.60 Wash, 10 lks. wide, 2 ft. deep, drains N. 75° W.
 40.00 Point for the ¼ sec. cor. of secs. 6 and 7.
 Set the iron post 22 ins. in the ground, cap mkd.

CHAINS

T39N R7W
 $\frac{1}{4}$ $\frac{S 6}{S 7}$
 1964

Deposit broken glass at base of the iron post.

Continue over nearly level land.

74.51 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., (reported as the cor. of secs. 1 and 12 only, in the 1937 survey of the E. bdy. of T. 39 N., R. 8 W.), monumented by an iron post 2 ins. diam., cap mkd.

T39N
 R8W | R7W
 S 1 | S 6
 S12 | S 7
 1937

Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, bunchgrass and shadscale.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°06' W., bet. secs. 5 and 6.

Over nearly level land, through scattered undergrowth.

4.10 Gully, drains W.

39.50 Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R7W
 $\frac{1}{4}$
 S 6 | S 5
 1964

Deposit broken glass at base of the iron post.

52.10 Wash, 20 lks. wide, 4 ft. deep, drains S. through an outcropping of rock approximately 6 ft. high.

78.46 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.

Land, nearly level.
 Soil, sandy loam.
 Timber, none.
 Undergrowth, bunchgrass and shadscale.

CHAINS

General Description

The township is nearly level to gently rolling, with an elevation ranging from about 5,240 feet above sea level along the east boundary to about 4,880 feet above sea level along the west boundary. The general drainage is to the west and there are numerous reservoirs and stock tanks. A moderate stand of bunchgrass was found. There are several bladed roads throughout the township, with numerous track roads in the more remote portions.

BOOK 4757

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel R. Bauer	Transitman
Claud E. Clay	Notekeeper and Chainman
Vernon Masayesva	Chainman
Gerald Satala	Flagman
Michael Hall	Cornerman

BOOK 4757

CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of February, 1963, I have retraced the east boundary for alignment only, and surveyed the subdivisional lines of Township 39 North, Range 7 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 18, 1965
(Date)

Boyd S. Owens
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date OCT 15 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the retracement of the east boundary for alignment only, and survey of the subdivisional lines of Township 39 North, Range 7 West, of the Gila and Salt River Meridian in the State of Arizona,

executed by Boyd S. Owens, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 11 1966
(Date)

E. E. Livingston
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)