

BOOK 4763

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

COMPLETION SURVEY

of the

Subdivisional Lines

of

Township 40 North, Range 12 West

Of the _____ Gila and Salt River _____ Meridian,

In the State of _____ Arizona _____.

EXECUTED BY

_____ Boyd S. Owens, Cadastral Surveyor

_____ Paul G. Bauer, Cadastral Surveyor

Under special instructions dated _____ April 14 _____, 19 64 _____, which provided for the surveys

included under Group Number _____ 411 _____, approved _____ April 14, 1964 _____,

and assignment instructions dated _____ May 27 _____, 19 65 _____.

Survey commenced _____ May 28 _____, 19 65 _____

Survey completed _____ July 6 _____, 19 65 _____

BOOK 4763 INDEX DIAGRAM

Township 40 North, Range 12 West,

40($\frac{1}{4}$)	40($\frac{1}{4}$)	30($\frac{1}{4}$)	24($\frac{1}{4}$)	24($\frac{1}{4}$)	9($\frac{1}{4}$)
6 40 39	5 29 39	4 29	3 23 22	2 8 21	1 8
7 38 38	8 28 37	9	10 20 19	11 7 18	12 6
18 36 36	17 35	16	15 17 16	14 5 16	13 5
19 34 34	20 27 33	21 27	22 15 14	23 4 13	24 3
30 32 32	29 26 31	28 25	27 12 11	28 3 10	29 2
31 30	32 24	33	34 9	35 1	36

BOOK 4763

Township 40 North, Range 12 West
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The north boundary (Tenth Standard Parallel North) through Range 12 West was surveyed in 1921 by J. P. Davis. The Parallel through Range 11 West was surveyed in 1939 by Muscott, Warner and Motch. The south boundary was surveyed in 1926 by B. J. Kinsey. The east and west boundaries and a portion of the subdivisions were surveyed in 1955-56 by P. K. Russell.

The following notes are those of a completion survey of the subdivisional lines of Township 40 North, Range 12 West, Gila and Salt River Meridian.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated April 14, 1964.

Only the true line bearings and horizontal distances are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 36°49'07" North and Longitude 113°31'33.3" West as computed from a tie to U. S. Coast and Geodetic Survey triangulation Station RED BLUFF, located in section 33, Township 40 North, Range 11 West.

The magnetic declination was found to be 15°30' East.

Subdivision, T. 40 N., R. 12 W., Arizona

Beginning at the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1926 survey.

N. 0°01' W., bet. secs. 35 and 36.

Over nearly level land.

12.30 Small draw, drains NE.

40:00 Point for the ¼ sec. cor. of secs. 35 and 36.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W

¼
S35 | S36
1965

Desc. N. slope.

46.70 Rocky rim on Seegmuller Mountain, bears N. 35° E. and S. 35° W.; desc. NW. slope.

55.50 Spur, slopes N. 70° W., desc. NW. slope over a series of small spurs and washes.

74.20 Rocky spur, slopes N. 60° W.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

2

2.

CHAINS						
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.</p> <div style="text-align: center;"> <p>T40N R12W</p> <table border="0"> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> </table> <p>1965</p> </div> <p>from which</p> <p style="padding-left: 40px;">A dry catch pond bears N. 47°59' W., 35.23 chs. dist.</p> <p>Land, gently rolling in S. half, mountainous in N. half. Soil, shallow loam. Timber, dense juniper and pinon. Undergrowth, moderate sagebrush and grass.</p> <hr/> <p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the township, monumented by an iron post 2½ ins. diam. as described in the official record of the 1955-56 survey.</p> <p>from which</p> <p style="padding-left: 40px;">A dry catch pond bears S. 79°37' W., 10.46 chs. dist.</p> <p>N. 89°57' W., bet. secs. 25 and 36.</p> <p>Over nearly level land, through a railed and seeded area.</p>	S26	S25	S35	S36	
S26	S25					
S35	S36					
0.20	Track road, bears N. and S.					
6.00	Leave railed area, bears E. and W.; desc. W. slope through dense timber.					
24.50	W. rim of Seegmuller Mountain, bears N. and S.; desc. steep W. slope.					
39.96	<p>Point for the ¼ sec. cor. of secs. 25 and 36.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <div style="text-align: center;"> <p>T40N R12W</p> <table border="0"> <tr> <td>¼</td> <td>S25</td> </tr> <tr> <td></td> <td>S36</td> </tr> </table> <p>1965</p> </div>	¼	S25		S36	
¼	S25					
	S36					
43.50	Bottom of small canyon 100 lks. wide, with nearly vertical 70 ft. sides, drains N. 10° W.; asc. over broken N. slope.					
79.92	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling and mountainous. Soil, shallow and rocky clay loam. Timber, dense juniper and pinon. Undergrowth, sagebrush and cactus.</p> <hr/>					

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
	N. 0°01' W., bet. secs. 25 and 26.
	Over mountainous land, desc. NW. slope through moderate timber with some open areas.
10.10	Small wash, drains W.
17.60	Small wash, drains N. 80° W.
24.10	Small wash, drains irregularly W.
25.30	Wash, 20 lks. wide, 1 ft. deep, drains N. 80° W.
29.30	Small wash, drains irregularly W.
37.80	Low spur, slopes W.; desc. gentle N. slope.
40.00	Point for the ¼ sec. cor. of secs. 25 and 26.
	Set the iron post 13 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W $\frac{1}{4}$ S26 S25 1965</p>
48.40	Bladed road, bears irregularly E. and W.
52.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 70° W.; asc. S. slope.
54.20	Small draw, drains S. 70° W.
62.30	Old road, bears S. 30° E. and N. 50° W.
68.40	Bladed road, bears S. 50° E. and N. 50° W., curving to N.
78.90	Same road, on curve to irregularly E. and S.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W S23 S24 S26 S25 1965</p>
	<p>Land, rolling. Soil, shallow, gravelly loam. Timber, moderate juniper in S. half, scattered juniper in N. half. Undergrowth, sagebrush, grass and cactus.</p>
	<p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.</p>
	N. 89°55' W., bet. secs. 24 and 25.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

4

4.

CHAINS	
	Over rolling land, desc. gentle W. slope through scattered timber.
19.90	Enter railed area, bears N. and S.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25. Set the iron post 13 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W $\frac{1}{4}$ $\frac{S24}{S25}$ 1965
41.70	Track road, bears N. 15° E. and S. 15° W.; leave railed area, bears N. and S. Enter scattered timber.
44.80	Ridge, bears S. 20° E. and N. 20° W.; desc. W. slope.
47.70	Bladed road, bears S. 51° E. and N. 51° W.
56.60	Same road, bears N. 5° E. and S. 5° W., curving to W.
79.94	The cor. of secs. 23, 24, 25 and 26. Land, rolling and mountainous. Soil, shallow, gravelly loam. Timber, scattered patches of juniper. Undergrowth, sagebrush, grass and cactus.
	N. 0°01' W., bet. secs. 23 and 24. Over rolling land, asc. gentle SW. slope.
5.70	Begin desc. over NW. slope.
10.90	Draw, drains N. 70° W.; asc. SW. slope.
30.50	Spur, slopes E.
33.30	Draw, drains N. 60° W.
35.90	Draw, drains S. 70° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24. Set the iron post 20 ins. in the ground, cap mkd.
	T40N R12W $\frac{1}{4}$ S23 S24 1965
	Build a mound with stones W. of the corner.
46.90	Spur, slopes NW.; desc. NW. slope.
54.10	Draw, drains W.; asc. SW. slope.
64.20	Spur, slopes W.; desc. N. slope.
70.40	Draw, drains N. 60° W.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

5.

CHAINS	
75.00	Spur, slopes N. 60° W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set the iron post 20 ins. in the ground, cap mkd.
	T40N R12W S14 S13 S23 S24 1965
	Build a mound with stones W. of the corner.
	Land, rolling. Soil, shallow, rocky loam. Timber, scattered juniper. Undergrowth, blackbrush, grass and cactus.
	<hr/> From the cor. of secs. 13 and 24 only, on the E. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.
	N. 89°57' W., bet. secs. 13 and 24.
	Over rolling, mountainous land, through scattered timber.
	Desc. broken NW. slope.
25.30	Draw, drains N.; asc. NE. slope.
39.99	Point for the ¼ sec. cor. of secs. 13 and 24.
	Set the iron post 19 ins. in the ground, cap mkd.
	T40N R12W ¼ S13 S24 1965
	Build a mound with stones N. of the corner.
49.50	Spur, slopes N. 5° E.
57.60	Spur, slopes N.; desc. NW. slope.
79.98	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling. Soil, rocky, clay loam. Timber, scattered juniper and pinon. Undergrowth, blackbrush, grass and cactus.
	<hr/> N. 0°01' W., bet. secs. 13 and 14.
	Over rolling land.
10.50	Wash, 15 lks. wide, 1 ft. deep, drains N. 10° E.; asc. SE. slope.
16.00	Small spur, slopes E.; continue asc. over SE. slope.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

6

6.

CHAINS	
17.60	Draw, drains SE.
38.60	Top of small knoll, bears W. 100 lks. dist.; desc. NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
<p>T40N R12W $\frac{1}{4}$ S14 S13 1965</p>	
42.20	Bladed road, bears S. 80° E. and S. 80° W.
54.70	Draw, drains E.; asc. SE. slope, leave scattered timber. Enter open area.
72.00	Spur, slopes E.; desc. gentle N. slope.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set the iron post 18 ins. in the ground, cap mkd.
<p>T40N R12W S11 S12 S14 S13 1965</p>	
Build a mound with stones W. of the corner.	
<p>Land, rolling. Soil, rocky, clay loam. Timber, scattered juniper in S. half. Undergrowth, blackbrush, grass and cactus.</p>	
<p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the township, monumented by an iron post 2½ ins. diam. set, mkd. and witnessed as described in the official record of the 1955-56 survey.</p>	
West, bet. secs. 12 and 13.	
Over rolling land, through moderate undergrowth; asc. E. slope.	
6.50	Low ridge, bears NE. and SW.
8.70	Shallow draw, drains NE.
9.60	Bladed road, bears NE. and SW.
14.40	Small ridge, bears N. and S.
20.70	Begin asc. over SE. slope.
28.30	Spur, slopes S.; desc. SW. slope.
34.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.; asc. E. slope.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
	<p>Set the iron post 18 ins. in the ground, collar of stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{1}{4}$ $\frac{S12}{S13}$ 1965</p>
43.30	Spur, slopes S.; desc. W. slope.
51.80	Draw, drains SE.; asc. E. slope.
58.60	Spur, slopes S. 80° E.
62.80	Ridge, bears N. and S.; desc. W. slope.
65.90	Draw, drains S.; asc. E. slope.
75.50	Spur, slopes S.; desc. W. slope.
80.04	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, blackbrush, yellowbrush and cactus.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over broken, mountainous land; desc. NW. slope.</p>
4.60	E. rim of Quail Canyon, on Seegmuller Mountain, bears N. 25° E. and S. 25° W.; desc. steep NW. slope over a series of small spurs and draws.
36.20	Draw, drains S. 60° W.; asc. rocky S. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{1}{2}$ S11 S12 1965</p> <p>Asc. steep and rocky S. slope.</p>
56.90	E. rim of Quail Canyon, on Seegmuller Mountain, bears S. 50° E. and N. 50° W.
59.00	Spur, projects W. about 4.00 chs.
61.70	E. rim of Quail Canyon, bears N. 20° E. and S. 20° W.; desc. steep NW. slope.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set the iron post in a crack in a rock, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{S 2 S 1}{S11 S12}$ 1965</p>

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
	<p>Land, broken. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, blackbrush, grass and cactus.</p> <hr/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.</p> <p>N. 89°58' W., bet. secs. 1 and 12.</p> <p>Over rolling E. slope, through moderate blackbrush.</p>
2.00	Small spur, slopes S.; desc. W. slope.
4.80	Draw, drains SE.; asc. E. slope.
12.20	Draw, drains S. 30° E.; asc. E. slope.
18.10	Spur, slopes NE.
19.70	Draw, drains E.
23.70	Spur, slopes S. 20° E.
23.70	Spur, slopes S.; desc. W. slope.
31.90	Draw, drains SE.; asc. E. slope.
37.30	Spur, slopes S.
40.08	Point for the ¼ sec. cor. of secs. 1 and 12.
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{1}{4}$ $\frac{S 1}{S12}$ 1965</p>
69.00	E. rim of Quail Canyon, bears N. and S.; desc. W. slope.
70.50	Rocky rim, bears N. 20° E. and S. 20° W.; desc. steep W. slope.
80.16	The cor. of secs. 1, 2, 11 and 12.
	<p>Land, mountainous. Soil, rocky clay loam. Timber, none. Undergrowth, moderate blackbrush and cactus.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
2.60	Spur, slopes S. 70° W.; desc. NW. slope over a series of small spurs and draws.
39.85	Rocky spur, slopes NW.; desc. N. slope.
40.00	Point for the ¼ sec. cor. of secs. 1 and 2.
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p>

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
42.00	<p style="text-align: center;">T40N R12W $\frac{1}{4}$ S 2 S 1 1965</p> <p>Draw, drains SW.; asc. S. slope.</p>
51.10	<p>Spur, slopes S. 80° W.; desc. NW. slope.</p>
60.50	<p>Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.; asc. S. slope.</p>
65.77	<p>Intersect the S. bdy. of T. 41 N., R. 12 W., the Tenth Standard Parallel North.</p>
	<p>Point for the closing cor. of secs. 1 and 2.</p>
	<p>Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T41N R12W S36 ----- S 2 S 1 T40N R12W C C 1965</p>
	<p>From the closing cor., the Standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 41 N., R. 12 W., bears West, 11.70 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record of the 1921 survey.</p>
	<p>Land, rolling. Soil, shallow, rocky loam. Timber, none. Undergrowth, blackbrush, scattered grass and cactus.</p>
	<p>The point for the $\frac{1}{4}$ sec. cor. of sec. 1 is on the N. bdy. of the township, at mid-point bet. the closing corners.</p>
	<p>Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">----- $\frac{1}{4}$ S 1 T40N R12W 1965</p>
	<p>From this cor. the true point for the Standard closing cor. of the SW. cor. of T. 41 N., R. 11 W., bears West, 11.64 chs. dist., witnessed 1.83 chs. S. of the true point and monumented with an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post 2 ins. diam. set, mkd. and witnessed as described in the official record of the 1926 survey.</p>
	<p>N. 0°01' W., bet. secs. 34 and 35.</p>

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

10

10.

CHAINS	Over rolling and mountainous land, through dense juniper and pinon.
5.40	Spur, slopes E.; desc. N. slope.
12.10	Wash, 15 lks. wide, 1 ft. deep, drains E.; asc. S. slope.
24.80	Ridge, bears E. and W.; desc. N. slope.
34.40	Fence, bears E. and W.
38.10	Draw, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Set the iron post 20 ins. in the ground, cap mkd.
	T40N R12W $\frac{1}{4}$ S34 S35 1965
	Build a mound with stones W. of the cor.
43.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 80° E.
50.00	Road, bears S. 80° E. and N. 80° W.; asc. S. slope.
54.30	Spur, slopes S. 85° E.
55.80	Draw, drains N. 80° E.
58.80	Spur, slopes E.
60.80	Draw, drains SE.
65.00	Spur, slopes S. 80° E.
70.00	Ridge, bears E. and W.; desc. N. slope.
77.40	Draw, drains N. 35° W..
78.00	Spur, slopes NW.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W S27 S26 S34 S35 1965
	Land, rolling and mountainous. Soil, shallow loam with exposed limestone. Timber, dense juniper and pinon. Undergrowth, sagebrush, scattered grass and cactus.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°51' W., bet. secs. 26 and 35.
	Over mountainous land, desc. NW. slope through dense timber, by triangulation. Topography estimated.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
31.00	Small spur, slopes N.
33.00	Leave timbered area; enter open land.
39.10	Wash, 10 lks. wide, 2 ft. deep, drains irregularly N.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35 and end of triangulation.
	Set the iron post 24 ins. in the ground, cap mkd.
	T40N R12W $\frac{1}{4}$ $\frac{S26}{S35}$ 1965
	Build a mound with stones N. of the cor.
41.00	Road, bears N. 5° E. and S. 5° W.; thence by triangulation, topography by chaining.
42.20	Leave open area, enter dense timber.
52.40	Spur, slopes N. 20° E.
63.50	Spur, slopes N. 20° E.
67.80	Draw, drains N. 20° E.
76.30	Spur, slopes N.; end of triangulation. Desc. NW. slope.
80.08	The cor. of secs. 26, 27, 34 and 35.
	Land, mountainous. Soil, shallow and rocky. Timber, dense juniper and pinon with open areas. Undergrowth, sagebrush, scattered grass and cactus.
	N. 89°56' W., bet. secs. 27 and 34.
	Over mountainous land, by triangulation. Topography as estimated and by scaling from available maps.
1.00	Draw, drains N. 20° W.
5.00	Wash, 10 lks. wide, 1 ft. deep, drains NE.; asc. SE. slope.
14.50	Spur, slopes S.
16.80	Draw, drains SE.
24.30	Jeep trail, bears N. 10° E. and S. 10° W.
31.60	Spur, slopes N. 10° E., and end of triangulation; desc. steep W. slope.
33.20	Trail, bears N. 25° E. and S. 25° W.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	Set the iron post 22 ins. in the ground, cap mkd.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

12

12.

CHAINS		
	T40N R12W $\frac{1}{4} \frac{S27}{S34}$ 1965	
	Build a mound with stones N. of the cor.	
41.00	Cow trail, bears N. 10° E. and S. 10° W.	
42.60	East rim of Quail Canyon, bears S. 20° E. and N. 20° W.; desc. steep W. slope.	
48.50	Draw, drains SW. for 40 lks. thence drains W.	
50.57	Point for a witness point on the line bet. secs. 27 and 34. Set the iron post 20 ins. in the ground, cap mkd.	
	T40N R12W W P $\frac{S27}{S34}$ 1965	
	Build a mound with stones N. of the witness point.	
50.70	Bladed road, St. George to Mt. Trumbull, bears S. 5° E. and N. 5° W.	
51.60	Wash in Quail Canyon, 10 lks. wide, 1 ft. deep, drains N. 30° W.; asc. E. slope.	
56.80	Spur, slopes N. 20° E.	
58.90	Draw, drains N. 30° E.	
74.20	Spur, slopes NE.; desc. NW. slope.	
75.20	Trail to Quail Spring, bears N. 70° E. and S. 50° W.	
80.12	The true point for the cor. of secs. 27, 28, 33 and 34, witnessed 20 lks. S. 0°02' E. and monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey. from which Quail Spring bears S. 51°20' W., 7.03 chs. dist. Land, mountainous. Soil, shallow and rocky loam. Timber, dense juniper and pinon. Undergrowth, scattered sagebrush, grass and cactus.	
	From the cor. of secs. 26, 27, 34 and 35. N. 0°01' W., bet. secs. 26 and 27. Over mountainous land.	
2.80	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° E.	
5.30	Wash, 10 lks. wide, 2 ft. deep, drains S. 80° E.	

CHAINS	
10.10	Spur, slopes E.
12.80	Underground pipe line from Quail Spring, bears irregularly E. and W.
28.50	Draw, drains N. 40° E.
29.70	Spur, slopes E.
31.30	Draw, drains S. 80° E.; asc. S. slope.
35.40	Spur, slopes S. 80° E.; desc. NE. slope.
38.50	Draw, drains S. 75° E.; asc. SE. slope.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W $\frac{1}{4}$ S27 S26 1965
42.80	Spur, slopes E.; desc. N. slope.
48.80	Draw, drains N. 60° E.
51.70	Spur, slopes NE.
59.30	Low spur, slopes NW.
65.80	Draw, drains S. 80° E.; asc. S. slope.
74.00	Spur, slopes SW.; desc. N. slope.
75.50	Draw, drains NE.; asc. S. slope.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W S22 S23 S27 S26 1965
	Land, rolling. Soil, shallow loam in exposed limestone. Timber, dense juniper and pinon in south half, medium timber in north half. Undergrowth, scattered grass, sagebrush and cactus.
	From the cor. of secs. 23, 24, 25 and 26.
	N. 89°51' W., bet. secs. 23 and 26.
	Over rolling land.
17.20	Spur, slopes SW.
26.60	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° E.; asc. E. slope.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

14

14.

CHAINS		
31.70	Bladed road, bears N. 5° E. and S. 5° W.	
40.04	<p>Point for the ¼ sec. cor. of secs. 23 and 26.</p> <p>Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W ¼ $\frac{S23}{S26}$ 1965</p> <p>from which</p> <p style="text-align: center;">The center of a dry catch pond bears S. 60°45' E., 24.04 chs. dist.</p>	
51.00	Spur, slopes S. 70° E.	
60.40	Draw, drains S. 70° E.	
66.10	Spur, slopes S. 60° E.	
75.90	Draw, drains SE.	
77.30	Spur, slopes N. 50° E.	
77.90	Draw, drains N. 60° E.	
80.08	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, shallow loam with exposed limestone. Timber, scattered to medium juniper and pinon. Undergrowth, scattered sagebrush, grass and cactus.</p> <hr/> <p>N. 89°55' W., bet. secs. 22 and 27.</p> <p>Over rolling and mountainous land.</p>	
14.50	Ridge, bears S. and N. 10° W., with jeep trail on crest.	
24.70	Draw, drains N. 20° W.; asc. E. slope.	
35.00	Spur, slopes N.; desc. W. slope.	
39.10	Draw, drains NW.	
40.07	<p>Point for the ¼ sec. cor. of secs. 22 and 27.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W ¼ $\frac{S22}{S27}$ 1965</p>	
46.70	Fence, bears N. 15° E. and S. 15° W.	
47.20	Ridge, broken and rocky, bears N. 15° E. and S. 15° W.; desc. steep W. slope.	

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

15.

CHAINS	
49.00	East rim of Quail Canyon, bears N. 15° E. and S. 15° W.; continue steep desc. over W. slope.
60.90	Bladed road, St. George to Mt. Trumbull, bears irregularly N. and S.
66.00	Wash in bottom of Quail Canyon, 25 lks. wide, 1 ft. deep, drains N.; asc. E. slope.
74.40	Spur, slopes N.; desc. W. slope.
76.90	Wash, 10 lks. wide, 1 ft. deep, drains N.; asc. E. slope.
80.14	The cor. of secs. 21, 22, 27 and 28, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.
	Land, rolling and mountainous. Soil, shallow loam in exposed limestone. Timber, moderate juniper. Undergrowth, moderate sagebrush, grass and cactus.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling land; asc. S. slope.
1.30	Spur, slopes S. 10° E.
5.10	Draw, drains SE.; continue asc. over S. slope.
23.40	Spur, slopes S. 10° E.
33.40	Draw, drains S. 60° E.
35.70	Low spur, slopes W.
37.10	Draw, drains S. 80° E.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W ¼ S22 S23 1965
43.90	Dim jeep trail, bears NE. and S.
44.60	Spur, slopes NE.; desc. N. slope.
60.20	East rim of Quail Canyon, bears N. 25° E. and S. 25° W.; desc. steep NW. slope.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

16

16.

CHAINS	
	<p style="text-align: center;">T40N R12W $\frac{S15}{S22} \frac{S14}{S23}$ 1965</p> <p>Land, rolling and mountainous. Soil, shallow and rocky loam. Timber, scattered juniper in south half. Undergrowth, moderate sagebrush and grass.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24. N. 89°51' W., bet. secs. 14 and 23. Over rolling land, through scattered timber; desc. W. slope.</p>
13.80	Wash, 10 lks. wide, 1 ft. deep, drains N. for 1 chain, thence drains irregularly E.; asc. E. slope.
15.60	Spur, slopes SE.
17.40	Draw, drains S. 80° E.
25.00	Spur, slopes S. 85° E.
31.30	Draw, drains SE.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23. Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W $\frac{1}{4} \frac{S14}{S23}$ 1965</p>
40.70	Draw, drains S. 10° E.
42.10	Small spur, slopes S. 10° E.
47.70	Bladed road, bears N. and S. 5° W.
48.40	Ridge, bears N. and S.; desc. W. slope.
55.10	Draw, drains NW.
69.80	East rim of Quail Canyon, bears N. 30° E. and S. 30° W.; desc. steep W. slope.
80.06	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, shallow loam in exposed limestone. Timber, scattered juniper. Undergrowth, blackbrush and cactus.
	<hr/> <p>N. 89°55' W., bet. secs. 15 and 22. Over rolling land; desc. NW. slope.</p>
4.40	Draw, drains irregularly NW.

CHAINS	
5.90	Spur, slopes N. 25° W.
19.30	Draw, drains N. 5° E.
21.00	Spur, slopes N. 10° E.
23.80	Point for a witness point bet. secs. 15 and 22.
	Set the iron post 13 ins. in the ground, mound with stones to top, cap mkd.
	<p>T40N R12W W P <u>S15</u> S22 1965</p>
24.20	Bladed road, from St. George to Mt. Trumbull, bears N. 55° E. and S. 15° W.
27.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° E.; asc. E. slope.
30.10	Track road, bears N. and S.
33.60	Spur, slopes S. 30° E.; desc. SW. slope.
40.07	Point for the ¼ sec. cor. of secs. 15 and 22.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p>T40N R12W ¼ <u>S15</u> S22 1965</p>
	Build a mound with stones N. of the cor.
41.90	Spur, slopes S.; desc. SW. slope.
53.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° W.; asc. NE. slope.
58.00	Spur, slopes N. 20° W.
65.80	Draw, drains irregularly N.; asc. E. slope.
71.20	Spur, slopes S. 10° E.; desc. W. slope.
75.20	Draw, drains N.
80.14	The cor. of secs. 15, 16, 21 and 22, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.
	<p>Land, rolling. Soil, shallow loam with exposed limestone. Timber, none. Undergrowth, sagebrush, blackbrush, grass and cactus.</p>
	From the cor. of secs. 14, 15, 22 and 23.
	N. 0°01' W., bet. secs. 14 and 15.
	Over rolling land, desc. NW. slope.

CHAINS

- 2.70 Draw, drains NW.
- 5.00 Spur, slopes NW.
- 8.50 Track road, bears S. 15°30' E. for 6.10 chs. to end at a mining prospect and bears NW. to main road.
- 13.50 Draw, drains NW.
- 16.30 Spur, slopes NW.
- 20.30 Draw, drains NW.
- 27.20 Draw, drains N. 70° W. for 2 chs., thence drains irregularly N.
- 34.10 Begin gentle desc. over nearly level N. slope.
- 40.00 Point for the ¼ sec. cor. of secs. 14 and 15.
Set the iron post 20 ins. in the ground, cap mkd.

T40N R12W
¼
S15 | S14
1965

Build a mound with stones W. of the cor.

- 41.60 Wash, 20 lks. wide, with 5 ft. banks, drains N. 30° E. from S. 15° W.
- 43.40 Bladed road, St. George to Mt. Trumbull, bears N. 20° E., and S. 20° W.
- 48.00 Begin asc. over broken E. slope.
- 63.80 Begin desc. over N. slope.
- 66.30 Small draw, drains NE. for 1.50 chs., thence drains irregularly N.; desc. over broken NE. slope.
- 72.50 Draw, drains NW.; asc. broken SW. slope.
- 80.00 Point for the cor. of secs. 10, 11, 14 and 15.
Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W
S10 | S11
S15 | S14
1965

Land, rolling.
Soil, gravelly loam.
Timber, none.
Undergrowth, moderate sagebrush, scattered yellowbrush and cactus.

From the cor. of secs. 11, 12, 13 and 14.

N. 89°50' W., bet. secs. 11 and 14.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
	Over rolling land; asc. gentle E. slope.
3.00	East rim of Quail Canyon, bears N. 35° E. and S. 35° W.; desc. steep and broken W. slope.
40.02	Point for the ¼ sec. cor. of secs. 11 and 14. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd. T40N R12W ¼ $\frac{S11}{S14}$ 1965
47.50	Draw, drains N. 5° E.; asc. E. slope.
51.00	Spur, slopes S.; desc. W. slope.
54.30	Draw, drains NW.
57.00	Low ridge, bears N. and S. 30° E.
67.10	Wash, 15 lks. wide, 1 ft. deep, drains N. 20° E.; asc. E. slope.
68.60	Bladed road, St. George to Mt. Trumbull, bears N. 20° E. and S. 20° W.
74.80	Spur, slopes N.; desc. along W. slope.
80.04	The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, shallow loam. Timber, none. Undergrowth, blackbrush, yellowbrush and cactus.
	N. 89°54' W., bet. secs. 10 and 15.
	Over rolling land; desc. SW. slope.
6.20	Draw, drains irregularly NW.
12.80	Draw, drains N. 85° E.; asc. E. slope.
18.30	Low ridge, bears N. and S.; desc. W. slope.
28.00	Low ridge, bears N. and S.
30.90	Draw, drains N. 30° W.; asc. E. slope.
35.80	Spur, slopes N.; desc. W. slope.
40.07	Point for the ¼ sec. cor. of secs. 10 and 15. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd. T40N R12W ¼ $\frac{S10}{S15}$ 1965
41.90	Draw, drains irregularly NE.; asc. E. slope.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

20

20.

CHAINS		
51.00	Spur, slopes N.; desc. W. slope.	
63.40	Wash, 20 lks. wide, 1 ft. deep, drains N.; asc. E. slope.	
76.70	Draw, drains N. 5° E.; asc. SE. slope.	
80.14	The cor. of secs. 9, 10, 15 and 16, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.	
	from which	
	A dry catch pond bears S. 57°50' E., 12.00 chs. dist.	
	Land, rolling. Soil, shallow loam with exposed limestone. Timber, none. Undergrowth, blackbrush, scattered yellowbrush and cactus.	
	From the cor. of secs. 10, 11, 14 and 15.	
	N. 0°01' W., bet. secs. 10 and 11.	
	Over rolling land; asc. SW. slope.	
1.20	Ridge, bears S. 60° E. and N. 60° W.; desc. N. slope.	
7.20	Draw, drains NW.	
28.60	Wash; 30 lks. wide, 2 ft. deep, drains S. 70° W.	
29.50	Bladed road, St. George to Mt. Trumbull, bears S. 65° E. and NW.	
36.10	Stock Drive trail, bears N. 15° E. and S. 15° W.	
40.00	Point for the ¼ sec. cor. of secs. 10 and 11.	
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.	
	T40N R12W ¼ S10 S11 1965	
41.80	Bladed road, St. George to Mt. Trumbull, bears N. 30° E. and S. 30° W.	
50.80	Wash, 5 lks. wide, 1 ft. deep, drains irregularly N.	
53.80	Wash, 10 lks. wide, with 3 ft. banks, drains N. 60° W.	
55.30	Spur, slopes SW.	
57.40	Draw, drains SW.	
58.10	Spur, slopes SW.	
60.80	Draw, drains S. 20° W. from NE.; asc. along gentle E. slope.	

CHAINS	
70.40	Track road, bears irregularly E. and W.
74.70	Spur, slopes E.; desc. N. slope.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W $\frac{S\ 3}{S10} \frac{S\ 2}{S11}$ 1965</p>
	<p>Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, moderate sagebrush, scattered yellowbrush, grass and cactus.</p>
	<hr/>
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°50' W., bet. secs. 2 and 11.
	Over rolling and broken land; desc. SW. slope.
26.50	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.
	Set the iron post 16 ins. in the ground, cap mkd.
	<p style="text-align: center;">T40N R12W $\frac{1}{4} \frac{S\ 2}{S11}$ 1965</p>
	Build a mound with stones N. of the cor.
44.00	Draw, drains NW.
45.30	Small spur, slopes NE.
47.30	Draw drains N.; asc. E. slope.
50.30	Spur, slopes S. 10° W.; desc. W. slope.
55.80	Spur, slopes N.
63.00	Wash, 5 lks. wide, 1 ft. deep, drains irregularly N.; asc. E. slope.
65.20	Spur, slopes N.
68.00	Draw, drains N. 5° E.
71.10	Spur, slopes S. 10° W.; desc. W. slope.
74.90	Point for a witness point bet. secs. 2 and 11.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W W P $\frac{S\ 2}{S11}$ 1965</p>

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
75.20	Bladed road, St. George to Mt. Trumbull, bears N. and S.
80.04	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, blackbrush, scattered yellowbrush and cactus.
	N. 89°52' W., bet. secs. 3 and 10.
	Over rolling land.
0.20	Small draw, drains N. 10° E.; asc. E. slope.
16.00	Low ridge, bears N. and S.; desc. W. slope.
22.90	Draw, drains N. 10° E.; asc. E. slope.
27.00	Low ridge, bears N. and S.; desc. W. slope.
36.00	Spur, slopes N. 15° E.; continue desc. over W. slope.
40.07	Point for the ¼ sec. cor. of secs. 3 and 10.
	Set the iron post 20 ins. in the ground, cap mkd.
	T40N R12W ¼ $\frac{S\ 3}{S10}$ 1965
	Build a mound with stones N. of the cor.
46.20	East rim of a vertical walled canyon 140 ft. deep, bears N. and S.
47.50	Wash in bottom of Quail Canyon, 50 lks. wide, drains N.
49.20	West rim of same canyon, bears N. and S.; asc. E. slope.
54.20	Spur, slopes N.; desc. W. slope.
59.80	E. rim of canyon with 50 ft. vertical walls, bears NE. and SW.
61.10	Wash in bottom of canyon, 30 lks. wide, drains NE.
62.50	W. rim of same canyon, bears NE. and SW.; asc. E. slope.
73.70	Spur, slopes N.; desc. W. slope.
76.60	E. rim of small, deep canyon with 50 ft. vertical walls, bears NE. and SW.
77.00	Wash in bottom of canyon, 30 lks. wide, drains NE.
80.14	The true point for the cor. of secs. 3, 4, 9 and 10, witnessed 10 lks. S. 0°02' E. The witness cor. is monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.

CHAINS	
	<p>Land, rolling. Soil, shallow loam with exposed limestone. Timber, none. Undergrowth, blackbrush and scattered cactus.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. N. 0°01' W., bet. secs. 2 and 3. Over rolling land.</p>
1.50	Small draw, drains NW. for 1.00 chain, thence drains NE.
2.60	Spur, slopes W.
4.10	Same draw, drains NE.
9.50	Small draw, drains E.
13.80	Spur, slopes NE.
15.50	Draw, drains SW.; asc. S. slope.
20.10	Spur, slopes W. from top of knoll, 1.50 chs. E.
26.50	Road, bears N. 30° E. and SW.
28.00	Draw, drains NW. from S. 15° W.
32.20	Track road, bears SE. and NW.
34.50	Road, bears E. and N. 70° W.
40.00	Point for the ¼ sec. cor. of secs. 2 and 3. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd. T40N R12W ¼ S 3 S 2 1965
48.90	Bladed road, St. George to Mt. Trumbull, bears irregularly SE. and NW.
51.70	Wash, 20 lks. wide, 1 ft. deep, drains irregularly NW.
53.20	Spur, slopes W.
54.40	Draw, drains W. from NE.
61.80	Fence, bears N. 68°15' E. and S. 68°15' W.
65.30	Bladed road, St. George to Mt. Trumbull, bears N. 75° E. and S. 75° W.
65.54	Intersect the S. bdy. of T. 41 N., R. 12 W., the Tenth Standard Parallel North. Point for the closing cor. of secs. 2 and 3. Set the iron post 22 ins. in the ground, cap mkd.

CHAINS

T41N R12W

S35

S 3 | S 2
T40N | R12W

C C

1965

From the closing cor. the Standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 41 N., R. 12 W., bears West, 11.67 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

Land, rolling.

Soil, shallow loam with exposed limestone.

Timber, none.

Undergrowth, greasewood, yellowbrush and cactus.

The point for the $\frac{1}{4}$ sec. cor. of sec. 2 is on the N. bdy. at midpoint bet. the closing corners.

Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.

$\frac{1}{4}$ S 2

T40N R12W

1965

From this cor. the Standard sec. cor. of secs. 35 and 36, T. 41 N., R. 12 W., bears West, 11.68 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

The point for the $\frac{1}{4}$ sec. cor. of sec. 3 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 20 ins. in the ground, cap mkd.

$\frac{1}{4}$ S 3

T40N R12W

1965

Build a mound with stones S. of the cor.

From this cor. the Standard sec. cor. of secs. 34 and 35, T. 41 N., R. 12 W., bears West, 11.68 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. $0^{\circ}03'$ W., bet. secs. 32 and 33.

Over mountainous land; asc. steep S. slope of Wolf Hole Mountain through dense juniper.

4.20

S. rim of Wolf Hole Mountain, bears irregularly E. and NW.; asc. gentle S. slope.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
12.70	End of gentle S. slope; thence over nearly level land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W $\frac{1}{4}$ S32 S33 1965
	from which
	A juniper, 12 ins. diam., bears N. 84° E., 66 lks. dist., mkd. T40N R12W $\frac{1}{4}$ S33 B T
	A juniper, 18 ins. diam., bears S. 36°45' W., 67 lks. dist., mkd. T40N R12W $\frac{1}{4}$ S32 B T
50.60	Track road, bears N. 50° E. and S. 80° W.
55.50	Main road on Wolf Hole Mountain, bears N. 53° E. and S. 47° W.
60.40	Fence, bears irregularly E. and W.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W S29 S28 S32 S33 1965
	from which
	A juniper, 10 ins. diam., bears N. 42°45' E., 21 lks. dist., mkd. T40N R12W S28 B T
	A pinon, 8 ins. diam., bears N. 74°45' W., 75 lks. dist., mkd. T40N R12W S29 B T
	Land, nearly level. Soil, gravelly loam. Timber, dense juniper, scattered pinon. Undergrowth, sagebrush, oakbrush, scattered manzanita and cactus.
	<hr/> From the point for the cor. of secs. 27, 28, 33 and 34. N. 89°55' W., bet. secs. 28 and 33.
	Over mountainous land; asc. steep E. slope by triangulation.
0.00	Quail Canyon Wash, 20 lks. wide, 1 ft. deep, drains irregularly N. from S. 30° W.
0.20	Plastic pipe line, 2 ins. diam., from Quail Spring, bears irregularly N. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33. End of triangulation.

CHAINS		
	<p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{1}{4}$ $\frac{S28}{S33}$ 1965</p> <p>The cor. is set on a rocky rim bearing N. and SW.</p> <p>Asc. steep E. slope through an area of large volcanic boulders.</p>	
47.10	W. rim of Quail Canyon, bears irregularly N. and SW.; desc. gentle W. slope.	
49.30	Draw, drains S.; asc. gentle E. slope.	
80.00	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, steep and mountainous E. half, gently rolling W. half. Soil, shallow and rocky loam. Timber, dense juniper, scattered pinon. Undergrowth, sagebrush, brigham tea and cactus.</p>	
	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over nearly level land, through dense timber.</p>	
24.00	Wash, 5 lks. wide, 1 ft. deep, drains irregularly E.	
32.00	Spur, slopes W.; desc. N. slope.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.</p> <p>Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{1}{4}$ $\frac{S29}{S28}$ 1965</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears N. 81°40' E., 43 lks. dist., mkd. $\frac{1}{4}$ S28 B T</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 74°30' W., 51 lks. dist., mkd. T40N R12W $\frac{1}{4}$ S29 B T</p>	
44.80	Small draw, drains NE.	
52.10	West rim of Quail Canyon, bears irregularly E. and W.; desc. N. slope.	
70.50	Draw, drains NE.; asc. S. slope.	
73.80	Spur, slopes N. 80° E.; desc. N. slope.	
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p>	

CHAINS	
	<p style="text-align: center;">T40N R12W $\frac{S20}{S29} \frac{S21}{S28}$ 1965</p> <p>Land, rolling. Soil, shallow and rocky loam. Timber, moderate juniper, scattered pinon. Undergrowth, sagebrush, scattered yellowbrush, brigham tea and cactus.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28. N. 89°53' W., bet. secs. 21 and 28. Over rolling land.</p>
4.00	Stock driveway trail, bears irregularly N. and S.; asc. E. slope.
14.90	Spur, slopes N.; desc. NW. slope.
29.90	Draw, drains N.; asc. E. slope.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W $\frac{1}{4} \frac{S21}{S28}$ 1965</p> <p>from which</p> <p style="text-align: center;">Indian pictographs on large malpai boulders bear N. 55°19' W., 18.65 chs. dist.</p>
40.10	Spur, slopes N.; desc. W. slope.
61.90	Spur, slopes N.; desc. W. slope.
74.70	Draw, drains N. 25° W.
79.90	The cor. of secs. 20, 21, 28 and 29. Land, rolling. Soil, shallow and gravelly loam. Timber, moderate juniper, scattered pinon. Undergrowth, sagebrush, brigham tea, yellowbrush and cactus.
39.95	<p>N. 0°01' W., bet. secs. 20 and 21. Over rolling and broken N. slope by triangulation, through moderate timber.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21. End of triangulation. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p>

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

28

28.

CHAINS

T40N R12W

$\frac{1}{2}$

S20|S21

1965

- 45.90 Draw, drains NE.
- 50.00 Spur, slopes N. 50° E.
- 64.70 Spur, slopes E.; leave timbered area, enter open area.
- 79.60 Draw, drains NE.
- 79.90 The cor. of secs. 16, 17, 20 and 21, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.

Land, rolling and broken.
Soil, shallow loam.
Timber, moderate juniper S. three-quarters.
Undergrowth, blackbrush, sagebrush and cactus.

From the cor. of secs. 8, 9, 16 and 17, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°03' W., bet. secs. 8 and 9.

Over rolling land, through dense blackbrush.

- 13.80 Wash, 10 lks. wide, 1 ft. deep, drains irregularly E.; asc. S. slope.
- 16.40 Spur, slopes E.
- 18.40 Wash, 5 lks. wide, 1 ft. deep, drains E.
- 40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 8 and 9.
Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W

$\frac{1}{2}$

S 8|S 9

1965

- 41.00 Spur, slopes E.
- 51.00 Draw, drains SE.; asc. S. slope.
- 57.70 Spur, slopes S.; asc. along crest of spur.
- 80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W

S 5|S 4

S 8|S 9

1965

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS	
	<p>Land, rolling. Soil, shallow loam. Timber, none. Undergrowth, moderate blackbrush, scattered cactus.</p> <hr/> <p>From the point for the cor. of secs. 3, 4, 9 and 10. West, bet. secs. 4 and 9. Over mountainous land, asc. steep E. slope.</p>
6.30	Spur, slopes S. 20° W.; desc. W. slope.
9.30	Stock driveway trail, bears N. 10° E. and S. 10° W.; asc. E. slope.
19.70	Draw, drains irregularly SE.
34.00	Spur, slopes SE.; asc. SE. slope.
39.96	<p>Point for the ¼ sec. cor. of secs. 4 and 9.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W ¼ $\frac{S\ 4}{S\ 9}$ 1965</p> <p>Asc. steep SE. slope.</p>
42.00	W. rim of Quail Canyon, bears irregularly N. and S. 75° W.; asc. gentle E. slope.
57.20	Spur, slopes S.; continue asc. over gentle E. slope.
79.92	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, mountainous and rolling. Soil, shallow loam. Timber, none. Undergrowth, moderate blackbrush, scattered cactus.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5. Over gently rolling land.</p>
22.60	Spur, slopes NE.
40.00	<p>Point for the ¼ sec. cor. of secs. 4 and 5.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W ¼ S 5 S 4 1965</p> <p>Continue over gently rolling land.</p>
65.37	Intersect the S. bdy. of T. 41 N., R. 12 W., the Tenth Standard Parallel North.

CHAINS

Point for the closing cor. of secs. 4 and 5.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T41N R12W
S33
 S 5 | S 4
 T40N R12W
 C C
 1965

From the closing cor. the Standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 41 N., R. 12 W., bears West, 11.79 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

Land, gently rolling.

Soil, shallow loam.

Timber, none.

Undergrowth, moderate blackbrush, scattered cactus.

The point for the $\frac{1}{4}$ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

$\frac{1}{4}$ S 4
 T40N R12W
 1965

From this cor. the Standard cor. of secs. 33 and 34, T. 40 N., R. 12 W., bears West, 11.74 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1926 survey.

N. 0°03' W., bet. secs. 31 and 32.

Over rolling land, through moderate timber.

18.30 Main road on Wolf Hole Mountain, bears S. 73° E. and N. 73° W.

30.90 Fence, bears irregularly E. and W.

32.70 Draw, drains W.; asc. S. slope.

35.00 Spur, slopes W.; desc. gentle NW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W
 $\frac{1}{4}$
 S31 | S32
 1965

CHAINS

from which

A juniper, 6 ins. diam., bears N. 40°45' E., 45 lks. dist., mkd. $\frac{1}{4}$ S32 B T

A juniper, 12 ins. diam., bears S. 53° W., 39 lks. dist., mkd. T40N R12W $\frac{1}{4}$ S31 B T

A catch pond, bears S. 62°13' E., 34.00 chs. dist.

An earthen dam across a ravine bears S. 78°04' W., 6.20 chs. dist.

51.70 Track road, bears irregularly E. and W.

66.10 Spur, slopes W.; desc. NW. slope.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set the iron post 18 ins. in the ground, cap mkd.

T40N R12W
 $\frac{S30}{S31}$ | $\frac{S29}{S32}$
 1965

from which

A juniper, 10 ins. diam., bears S. 38°30' E., 29 lks. dist., mkd. T40N R12W S32 B T

A pinon, 8 ins. diam., bears S. 28°30' W., 38 lks. dist., mkd. T40N R12W S31 B T

Build a mound with stones W. of the cor.

Land, gently rolling.

Soil, shallow loam.

Timber, moderate juniper, scattered pinon.

Undergrowth, sagebrush, scattered yellowbrush and cactus.

From the cor. of secs. 28, 29, 32 and 33.

N. 89°59' W., bet. secs. 29 and 32.

Over nearly level land, through dense timber.

40.07 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W
 $\frac{1}{4}$ $\frac{S29}{S32}$
 1965

from which

A pinon, 15 ins. diam., bears S. 35°13' E., 10 lks. dist., mkd. $\frac{1}{4}$ S32 B T

A juniper, 8 ins. diam., bears N. 14°48' W., 25 lks. dist., mkd. T40N R12W $\frac{1}{4}$ S29 B T

CHAINS

64.00 Low ridge, bears N. and S.; desc. gentle W. slope.

70.20 Begin desc. over steep W. slope.

80.14 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.
Soil, shallow loam.
Timber, dense juniper, scattered pinon.
Undergrowth, scattered sagebrush and cactus.

N. 89°49' W., bet. secs. 30 and 31.

Over rolling land, desc. W. slope.

14.10 Road, bears irregularly N. and S.

40.00 Point for the ¼ sec. cor. of secs. 30 and 31.

Set the iron post 7 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W
¼ $\frac{S30}{S31}$
1965

from which

A pinon, 6 ins. diam., bears S. 45° W., 22 lks. dist., mkd. ¼ S31 B T

A juniper, 6 ins. diam., bears N. 10° W., 15 lks. dist., mkd. T40N R12W S30 B T

51.30 W. rim of Wolf Hole Mountain, bears S. 21° E. and N. 21° W.; desc. steep W. slope.

64.50 Wash, 10 lks. wide, 2 ft. deep, drains NW.; asc. NE. slope.

80.64 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.

Land, rolling E. half, mountainous W. half.
Soil, shallow loam.
Timber, dense juniper, scattered pinon.
Undergrowth, scattered sagebrush and cactus.

From the cor. of secs. 29, 30, 31 and 32.

N. 0°03' W., bet. secs. 29 and 30.

Over rolling land, through dense timber, desc. NW. slope.

16.00 Draw, drains W.; asc. SW. slope.

40.00 Point for the ¼ sec. cor. of secs. 29 and 30.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

CHAINS

T40N R12W

$\frac{1}{4}$
S30|S29
1965

from which

An Arizona Fish and Game metal rain trap bears
N. 82°19' W., 48 chs. dist.

There are no suitable bearing trees.

- 41.90 Spur, slopes W.; desc. NW. slope.
- 57.50 Small draw, drains W.; asc. SW. slope.
- 80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set the iron post 6 ins. in the ground, mound with
stones to top, cap mkd.

T40N R12W

S19|S20
S30|S29
1965

from which

A pinon, 10 ins. diam., bears S. 52°30' E.,
17 lks. dist., mkd. T40N R12W S29 B T

A pinon, 12 ins. diam., bears S. 37° W., 51
lks. dist., mkd. T40N R12W S30 B T

Land, rolling.
Soil, shallow loam.
Timber, dense juniper and pinon.
Undergrowth, scattered sagebrush, yellowbrush, brigham
tea and cactus.

From the cor. of secs. 20, 21, 28 and 29.
N. 89°57' W., bet. secs. 20 and 29.
Over mountainous land; asc. over broken NE. slope.

- 5.20 Draw, drains N. 20 E.
- 11.30 White topped spur, slopes N. 15° E.
- 13.10 Draw, drains N. 10° E.
- 22.20 Spur, slopes N. 20° E.
- 27.30 Draw, drains NE.; asc. steep E. slope.
- 35.40 W. rim of Quail Canyon, bears SE. and NW.
- 40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.

Set the iron post 7 ins. in the ground, mound with
stones to top, cap mkd.

T40N R12W

$\frac{1}{4}$ S20
S29
1965

CHAINS	
	<p>from which</p> <p>A juniper, 12 ins. diam., bears S. 57°20' E., 59 lks. dist., mkd. $\frac{1}{4}$ S29 B T</p> <p>A pinon, 15 ins. diam., bears N. 8°08' W., 21 lks. dist., mkd. $\frac{1}{4}$ S20 B T</p> <p>Asc. E. slope.</p>
45.60	Low ridge, bears N. and S.; desc. W. slope.
80.16	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, rolling. Soil, shallow loam. Timber, dense juniper, scattered pinon. Undergrowth, scattered sagebrush, yellowbrush, brigham tea and cactus.</p>
	<p>N. 89°47' W., bet. secs. 19 and 30.</p> <p>Over rolling land, through moderate timber; desc. W. slope.</p>
14.90	Draw, drains N. 20° W.; asc. E. slope.
24.80	Small spur, slopes N.; desc. gentle W. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{1}{4}$ $\frac{S19}{S30}$ 1965</p>
	There are no suitable bearing trees.
41.40	Wash, 5 lks. wide, 1 ft. deep, drains N. 30° W.; asc. E. slope.
48.10	Road, bears N. and S.
68.30	W. rim of Wolf Hole Mountain, bears S. and N. 10° W.; desc. steep W. slope.
74.60	Draw, drains NW.; continue steep desc.
80.50	<p>The cor. of secs. 19, 24, 25 and 30, ^{on the W. bdy. of the Tp}monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.</p> <p>Land, rolling. Soil, shallow loam. Timber, dense juniper, scattered pinon. Undergrowth, scattered sagebrush, yellowbrush, brigham tea and cactus.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p>

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

35.

CHAINS	
	Over rolling land, through moderate timber; desc. N. slope.
27.50	Draw, drains N. 60° W.; desc. along W. slope.
40.00	Point for the ¼ sec. cor. of secs. 19 and 20.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W ¼ S19 S20 1965</p>
	There are no suitable bearing trees.
50.20	Small spur, slopes W.; desc. N. slope.
75.00	Wash, 5 lks. wide, 1 ft. deep, drains NE.; asc. gentle SE. slope.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W S18 S17 S19 S20 1965</p>
	Land, rolling. Soil, shallow loam. Timber, moderate to scattered juniper and pinon. Undergorwth, sagebrush, yellowbrush and cactus.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89°49' W., bet. secs. 17 and 20.
	Asc. steep E. slope over open land.
19.20	Leave open land, enter timbered area.
22.20	Spur, slopes NE.; continue asc. over steep E. slope.
26.10	Draw, drains NE.; continue steep asc.
29.60	Spur, slopes N.; continue steep asc.
32.20	Draw, drains N. 20° E.; continue steep asc.
40.09	Point for the ¼ sec. cor. of secs. 17 and 20.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R12W ¼ S17 S20 1965</p>
	Continue steep asc. over E. slope.

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

36

36.

CHAINS	
45.23	W. rim of Quail Canyon and E. rim of Mokiatic Mountain, bears N. 30° E. and S. 30° W.; continue asc. over E. slope.
52.10	Large spur, slopes N. 20° E.; desc. W. slope.
80.18	The cor. of secs. 17, 18, 19 and 20. Land, mountainous. Soil, shallow loam. Timber, moderate juniper, scattered pinon in W. half. Undergrowth, blackbrush, yellowbrush and cactus.
	N. 89°40' W., bet. secs. 18 and 19.
	Over rolling land; asc. gentle E. slope.
40.00	Point for the ¼ sec. cor. of secs. 18 and 19. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W ¼ $\frac{S18}{S19}$ 1965
42.90	Road, bears SE. and NW.
47.90	Wash, 5 lks. wide, 1 ft. deep, drains N. 5° E.; asc. E. slope.
57.90	Spur, slopes N.; desc. W. slope.
63.50	W. rim of Mokiatic Mountain, bears N. and S. 30° W.; desc. steep W. slope.
80.34	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey. Land, rolling. Soil, shallow loam. Timber, moderate to scattered juniper. Undergrowth, sagebrush, blackbrush and cactus.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over gently rolling land.
24.60	Wash, 10 lks. wide, 1 ft. deep, drains NW.
40.00	Point for the ¼ sec. cor. of secs. 17 and 18. Set the iron post 7 ins. in the ground, mound with stones to top, cap mkd.
	T40N R12W ¼ $\frac{S18}{S17}$ 1965

CHAINS	
	<p>from which</p> <p>A dam on E. edge of a dry catch pond bears S. 76°46' W., 18.00 chs. dist.</p>
42.90	Draw, drains NE.
46.60	Draw, drains E.
48.80	Spur, slopes S. 30° E.
50.50	Draw, drains SE.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{S}{S18} \frac{7}{S17} \frac{S}{S8}$ 1965</p> <p>Land, gently rolling. Soil, shallow loam. Timber, moderate juniper S. half, scattered juniper N. half. Undergrowth, sagebrush, yellowbrush and cactus.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°49' W., bet. secs. 8 and 17.</p> <p>Over rolling land, asc. E. slope.</p>
13.50	Spur, slopes N. 10° E.; desc. NW. slope.
18.20	Wash, 15 lks. wide, 2 ft. deep, drains NE.; asc. E. slope.
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R12W $\frac{1}{4} \frac{S}{S17} \frac{S}{S8}$ 1965</p> <p>Asc. steep E. slope.</p>
54.70	E. rim of Mokiatic Mountain, bears N. and S.; asc. gentle E. slope through scattered juniper trees.
80.18	The cor. of secs. 7, 8, 17 and 18.
	<p>Land, rolling. Soil, shallow loam. Timber, scattered juniper in W. half. Undergrowth, blackbrush, sagebrush and cactus.</p> <hr/>

CHAINS	
	N. 89°41' W., bet. secs. 7 and 18. Over gently rolling land.
6.10	Small wash, drains irregularly S.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18. Set the iron post 9 ins. in the ground, mound with stones to top, cap mkd. <div style="text-align: center;"> T40N R12W ¼ $\frac{S\ 7}{S18}$ 1965 </div>
56.00	Road, bears SE. and N. 30° W.
56.90	Draw, drains N. 20° W.
61.90	Spur, slopes N. 10° W.
80.09	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey. Land, gently rolling. Soil, shallow loam. Timber, scattered juniper. Undergrowth, blackbrush, sagebrush and cactus.
40.00	From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over gently rolling land, through blackbrush and sagebrush. Point for the ¼ sec. cor. of secs. 7 and 8. Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd. <div style="text-align: center;"> T40N R12W ¼ S 7 S 8 1965 </div> from which A dry catch pond bears N. 56°57' W., 11.80 chs. dist.
49.40	Small wash, drains irregularly W. to a catch pond.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd. <div style="text-align: center;"> T40N R12W S 6 S 5 S 7 S 8 1965 </div>

CHAINS	
	<p>Land, gently rolling. Soil, shallow loam. Timber, none. Undergrowth, blackbrush, sagebrush and cactus.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>
	<p>N. 89°44' W., bet. secs. 5 and 8.</p>
	<p>Over gently rolling land, asc. E. slope.</p>
14.00	<p>Spur, slopes S. 20° E.</p>
40.10	<p>Point for the ¼ sec. cor. of secs. 5 and 8.</p>
	<p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T40N R12W $\frac{1}{4} \frac{S \ 5}{S \ 8}$ 1965</p>
68.90	<p>Draw, drains S. 30° E.</p>
80.20	<p>The cor. of secs. 5, 6, 7 and 8.</p>
	<p>Land, gently rolling. Soil, shallow loam. Timber, none. Undergrowth, blackbrush, sagebrush and cactus.</p>
	<p>N. 89°42' W., bet. secs. 6 and 7.</p>
	<p>Over gently rolling land.</p>
12.10	<p>Draw, drains S. for 1.00 chain, thence drains SE.</p>
21.50	<p>Spur, slopes S. 30° E.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 6 and 7.</p>
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T40N R12W $\frac{1}{4} \frac{S \ 6}{S \ 7}$ 1965</p>
	<p>Continue over nearly level land.</p>
79.88	<p>The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955-56 survey.</p>
	<p>Land, gently rolling. Soil, shallow loam. Timber, none. Undergrowth, sagebrush, yellowbrush and cactus.</p>

BOOK 4763

Subdivision, T. 40 N., R. 12 W., Arizona

40

40.

CHAINS

From the cor. of secs. 5, 6, 7 and 8.

N. 0°03' W., bet. secs. 5 and 6.

Over gently rolling land.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T40N R12W

$\frac{1}{4}$
S 6 | S 5
1965

47.10

Low ridge; bears NE. and SW.; desc. N. slope.

65.04

Intersect the S. bdy. of T. 41 N., R. 12 W., the Tenth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T41N R12W

S32

S 6 | S 5

T40N R12W

C C

1965

From the closing cor. the Standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 41 N., R. 12 W., bears West, 11.45 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

Land, gently rolling.

Soil, shallow loam.

Timber, none.

Undergrowth, blackbrush, sagebrush and cactus.

The point for the $\frac{1}{4}$ sec. cor. of sec. 5 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

$\frac{1}{4}$ S 5

T40N R12W

1965

From this cor. the Standard cor. of secs. 32 and 33 bears West, 11.62 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

The point for the $\frac{1}{4}$ sec. cor. of sec. 6 is on the N. bdy. at 40.00 chs. in westing from the closing cor. of secs. 5 and 6.

CHAINS

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

$\frac{1}{2}$ S 6
 T40N R12W
 1965

From this cor. the Standard sec. cor. of secs. 31 and 32 bears West, 11.45 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1921 survey.

General Description

Township 40 North, Range 12 West, Gila and Salt River Meridian, Arizona is in rough, mountainous country, and embraces Mokiatic Mountain and parts of Wolf Hole Mountain and Seegmuller Mountain. Quail Canyon drains northerly through the central portion of the township from its source near the south boundary. The elevation ranges from about 5,400 feet above sea level to a low of about 3,400 feet.

There is a heavy growth of juniper and pinon in the south two tiers of sections, gradually thinning into sagebrush, blackbrush and grass upon reaching the northerly slopes.

The main gravel road from St. George, Utah, to Wolf Hole Lake, Arizona, traverses southerly through the eastern half of the township. There are access roads along the south and west boundaries, ending at water reservoirs.

The township is primarily used for grazing of stock.

A few mining claim monuments were noted in the south-east and south-central portions of the township. No actual mining was noticed.

There are no permanent dwellings in this township.

BOOK 4763

CERTIFICATE OF SURVEY

I, Boyd S. Owens, Paul G. Bauer, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 14th day of April, 1964,

I have made a completion survey of the subdivisional lines of Township 40 North, Range 12 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 17, 1965 (Date)

Boyd S. Owens (Cadastral Surveyor)

November 17, 1965 (Date)

Paul G. Bauer (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date DEC 20 1965

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the completion survey of Township 40 North, Range 12 West, of the Gila and Salt River Meridian in the State of Arizona,

executed by Boyd S. Owens and Paul G. Bauer, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

FEB 7 1966 (Date)

E. L. Huntington (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)