

BOOK 4764

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of a

Portion of the North Boundary

and

SURVEY

of the

South Boundary

and

Subdivisional Lines

of

Township 39 North, Range 2 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Paul G. Bauer, Cadastral Surveyor

Under special instructions dated March 4, 19 64, which provided for the surveys included under Group Number 407, approved March 4, 1964, and assignment instructions dated April 2, 19 65.

Survey commenced April 8, 19 65

Survey completed May 7, 19 65

1A

BOOK 4764 INDEX DIAGRAM

Township 39 North, Range 2 West,
1

($\frac{1}{4}$) 52	6 52 50	5 37 49	4 30 36	3 23 29	2 16 23	1 15
($\frac{1}{4}$) 51	7 49 47	8 35 46	9 29 35	10 22 28	11 14 21	12 14
($\frac{1}{4}$) 48	18 46 44	17 34 44	16 27 34	15 21 27	14 13 20	13 12
($\frac{1}{4}$) 45	19 43 41	20 33 41	21 26 32	22 20 26	23 11 19	24 10
($\frac{1}{4}$) 42	30 40 39	29 32 38	28 25 31	27 18 25	26 9 18	25 9
($\frac{1}{4}$) 40	31 37	32 31	33 24	34 17	35 8	36
	7	6	5	4	3	2

CHAINS	
	<p>The west boundary of Township 39 North, Range 2 West, Gila and Salt River Meridian, Arizona, was surveyed in 1914 by J. C. Thoma as shown on the plat of Township 39 North, Range 3 West, accepted October 5, 1950. The east boundary was surveyed in 1916 by Mathews and Nash and shown on the plat of Township 39 North, Range 1 West, approved August 22, 1919. The north boundary was surveyed in 1954 by D. E. Harding and shown on the plat of Township 40 North, Range 2 West, accepted October 25, 1955.</p> <p>The following notes are those of a dependent resurvey of a portion of the north boundary, and survey of the south boundary and subdivisional lines of Township 39 North, Range 2 West, of the Gila and Salt River Meridian, Arizona.</p> <p>This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 4, 1964.</p> <p>Only the true line bearings and horizontal distances are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.</p> <p>The geographic position of the southeast corner of the township is: Latitude 36°43'45.2" North, and Longitude 112°26'55.3" West, as computed from a tie to U.S. Coast and Geodetic Survey triangulation station GRAVEL, located in Section 13, Township 39 North, Range 2 West.</p> <p>The mean magnetic declination was found to be 16°15' East.</p>
	<p style="text-align: center;">Dependent Resurvey, Portion, North Boundary Township 39 North, Range 2 West</p>
	<p style="text-align: center;">Reestablishment of the Survey executed by D. E. Harding in 1954</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1954 survey.</p> <p>N. 89°55' W., bet. secs. 6 and 31.</p> <p>Over rolling and broken land, desc. along S. slope.</p> <p>4.50 Wash, 20 lks. wide, with 5-ft. banks, drains N.; asc. steep E. slope.</p> <p>10.70 Rim of canyon; bears N. 30° E. and S.; asc. gentle E. slope.</p> <p>12.50 Desc. gentle W. slope.</p> <p>32.20 Wash, 5 lks. wide, 1 ft. deep, drains N.</p> <p>38.10 Small spur, slopes N.</p> <p>40.09 The ¼ sec. cor. of secs. 6 and 31 on the N. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1954 survey.</p>

BOOK 4764

Dependent Resurvey, Portion, N. Bdy., T. 39 N., R. 2 W.

2

2.

CHAINS	
	N. 89°58' W., beginning new measurement.
0.20	Head of draw, drains N.
0.96	Intersect a mound of stones with a hole in center of mound.
5.10	Spur, slopes NW.; desc. SW. slope.
10.50	Draw, drains NW.
25.30	Track road, bears S. 80° E. and N. 75° W.; desc. gentle W. slope.
37.64	The closing corner of secs. 6 and 31 on the N. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1954 survey.
	from which
	The cor. of secs. 1 and 36, Ts. 39 and 40 N., R. 3 W., bears North, 6.11 chs. dist., monumented with an iron post 3 ins. diam., set, mkd. and witnessed as described in the field notes of Township 40 North, Range 2 West, as executed by D. E. Harding in 1954.
	Land, rolling and broken. Soil, gravelly loam. Timber, none. Undergrowth, moderate sagebrush, scattered yellowbrush.
<hr/> Survey of the South Boundary Township 39 North, Range 2 West, G&SRM, Arizona <hr/>	
	Beginning at the corner of Ts. 38 and 39 N., Rs. 1 and 2 W., monumented by an iron post 3 inches diam., set, mkd. and witnessed as described in the official record of the 1916 survey.
	West, bet. secs. 1 and 36.
	Over rolling and broken land.
5.70	Small wash, drains SW.; asc. gentle SE. slope.
10.70	Begin gentle asc. along S. slope.
27.40	Track road, bears SE. and SW.
37.90	Same road, bears SE. and NW.
40.00	Point for the ¼ sec. cor. of secs. 1 and 36.
	Set the iron post 25 ins. in the ground and in a collar of stones, cap mkd.
	T39N R2W ¼ $\frac{S36}{S1}$ T38N 1965

BOOK 4764

South Boundary, T. 39 N., R. 2 W., Arizona

CHAINS	
	Build a mound with stones N. of the cor.
40.20	Spur, slopes S.; desc. SW. slope.
42.20	Begin desc. over rolling S. slope.
52.50	Begin asc. over SE. slope.
60.30	Low, ledgy rim, bears NE. and SW.
70.70	Same rim, bears S. 70° E. and W.
75.50	Begin desc. over steep SW. slope.
80.00	Point for the cor. of secs. 1, 2, 35 and 36.
	Set the iron post over an X chiseled on solid rock, mound with stones to top, cap mkd.
	T39N R2W S35 S36 S 2 S 1 T38N 1965
	Land, rolling and broken. Soil, rocky clay loam. Timber, moderate to scattered juniper and pinon. Undergrowth, moderate sagebrush, scattered buckbrush, brigham tea and cactus.
	West, bet. secs. 2 and 35.
	Over broken land, desc. SW. slope.
4.40	Small wash, drains N. from S. 60° E.; asc. steep E. slope.
10.90	Rocky spur, slopes N.; desc. W. slope.
16.60	Draw, drains N.; asc. NE. slope.
29.30	Ridge, bears N. and SE.; desc. broken W. slope.
38.60	Small draw, drains N. 80° W.
40.00	Point for the ¼ sec. cor. of secs. 2 and 35.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W S35 ¼ S 2 T38N 1965
44.70	Same draw, drains SW.; desc. along S. slope.
64.50	Begin desc. over steep SW. slope.
76.10	Wash, 20 lks. wide, 1 ft. deep, drains W. from S. 70° E.

BOOK 4764

South Boundary, T. 39 N., R. 2 W., Arizona

4

4.

CHAINS

77.30 Same wash, drains N. 60° W., curving to N.; asc. gentle E. slope.

80.00 Point for the cor. of secs. 2, 3, 34 and 35.
Set the iron post 22 ins. in the ground, cap mkd.

T39N R2W
S34 | S35
S 3 | S 2
T38N
1965

from which

A catch pond, 3.50 chs. diam., bears N.,
12.40 chs. dist.

A dike between two catch ponds, bears N. 17° 56'
E., 29.60 chs. dist.

Build a mound with stones W. of the cor.

Land, mountainous.
Soil, rocky clay loam.
Timber, scattered juniper and pinon.
Undergrowth, moderate sagebrush, scattered buckbrush,
brigham tea and cactus.

West, bet. secs. 3 and 34.

Over rolling and broken land; asc. E. slope.

1.60 Spur, slopes N.; desc. W. slope.

5.50 Small draw, drains N., also end of track road from
irregularly N.; asc. gentle E. slope.

10.00 Spur, slopes N.; desc. W. slope.

14.20 Draw, drains N. 10° W.; asc. E. slope.

20.70 Spur, slopes N. 15° W.; desc. broken SW. slope.

31.00 Track road, bears S. 10° E. and N. 10° W.

31.50 Small wash, drains S. 15° E.; asc. broken S. slope.

33.90 Fence, bears NE. and SW.

37.00 Spur, slopes S. 15° E.

40.00 Point for the ¼ sec. cor. of secs. 3 and 34.

Set the iron post 10 ins. in the ground, mound with
stones to top, cap mkd.

T39N R2W
¼ S34
S 3
T38N
1965

CHAINS	
49.60	N. Rim of canyon, bears SE. and SW.; asc. over rolling SE. slope.
61.50	Rim of mesa, bears NE. and SW.; thence over gently rolling mesa top through scattered timber.
73.20	Enter moderate timber.
80.00	Point for the cor. of secs. 3, 4, 33 and 34.
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T39N R2W $\frac{S33}{S4} \frac{S34}{S3}$ T38N 1965</p>
	<p>Land, rolling and broken. Soil, rocky clay loam. Timber, scattered to moderate juniper and pinon in W. 20 chs. Undergrowth, dense sagebrush, scattered buckbrush, brigham tea and cactus.</p>
	<hr/> <p>West, bet. secs. 4 and 33.</p>
	<p>Over rolling land, through moderate timber.</p>
20.00	Track road, bears N. 60° E. and S. 60° W., timber becomes scattered.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R2W $\frac{1}{4} \frac{S33}{S4}$ T38N 1965</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 72°40' E., 171 lks. dist., mkd. R2W $\frac{1}{4}$ S4 B T</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 81° W., 88 lks. dist., mkd. T38N $\frac{1}{4}$ S4 B T</p>
	<p>Build a mound with stones N. of the cor.</p>
60.10	Track road, bears SE. and NW.; enter moderate timber.
65.00	Small draw, drains SW.
75.90	Small draw, drains S.
78.80	Same track road, bears NE. and SW.
80.00	Point for the cor. of secs. 4, 5, 32 and 33.

BOOK 4764

South Boundary, T. 39 N., R. 2 W., Arizona

6

6.

CHAINS

Set the iron post 20 ins. in the ground, cap mkd.

T39N R2W
 $\frac{S32}{S5} | \frac{S33}{S4}$
 T38N
 1965

from which

A juniper, 10 ins. diam., bears S. 23°05' W.,
 96 lks. dist., mkd. T38N R2W S5 B T

A juniper, 10 ins. diam., bears N. 9°20' W.,
 108 lks. dist., mkd. T39N R2W S32 B T

A corral bears N. 51°54' W., 20.20 chs. dist.

Build a mound with stones W. of the cor.

Land, rolling.

Soil, rocky clay loam.

Timber, scattered to moderate juniper and pinon.

Undergrowth, dense sagebrush, scattered buckbrush,
 yellowbrush, brigham tea and cactus.

West, bet. secs. 5 and 32.

Over gently rolling land, through scattered timber.

8.70 Track road, bears S. 70° E. and N. 70° W.

31.40 Small draw, drains S.

39.70 Track road, bears NE. and SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32.

Set the iron post 6 ins. in the ground, mound with
 stones to top, cap mkd.

T39N R2W
 $\frac{1}{4} \frac{S32}{S5}$
 T38N
 1965

Continue over gently rolling land.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set the iron post 12 ins. in the ground, mound with
 stones to top, cap mkd.

T39N R2W
 $\frac{S31}{S6} | \frac{S32}{S5}$
 T38N
 1965

Land, gently rolling.

Soil, rocky clay loam.

Timber, scattered juniper and pinon.

Undergrowth, dense sagebrush, scattered buckbrush,
 yellowbrush, brigham tea and cactus.

CHAINS

West, bet. secs. 6 and 31.

Over gently rolling land, through scattered timber.

6.30 Small wash, drains NW.

40.00 Point for the 1/4 sec. cor. of secs. 6 and 31.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T39N R2W
 1/4 S31
 S 6
 T38N
 1965

48.70 Small draw, drains NW.

53.10 Low rocky rim, bears N. and S.

56.00 Draw, drains N., curving NW.

60.00 Low, rocky rim, bears SE. and NW.

63.80 Begin desc. over W. slope.

78.88 Intersect the E. bdy. of sec. 1, T. 38 N., R. 3 W.

Point for the closing corner of secs. 6 and 31, Ts. 38 and 39 N., R. 2 W.

Set the iron post 20 ins. in the ground, collar of stones to top, cap mkd.

T39N
 T38N R2W
 R3W S31 C
 S 1 S 6 C
 T38N
 1965

Build a mound with stones E. of the cor.

from which

The cor. of secs. 1, 6, 31 and 36, Ts. 38 and 39 N., Rs. 2 and 3 W., bears North, 6.17 chs. dist., monumented by an iron post 3 ins. diam., with brass cap mkd.

T39N
 R3W S36 S31 R2W
 S 1 S 6
 T38N
 1914

As this cor. now functions for secs. 1 and 36, Ts. 38 and 39 N., R. 3 W., only, I remark the brass cap to read

T39N
 R3W S36 S31 R2W
 S 1
 T38N
 1965
 1914

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

8

8.

CHAINS

Land, rolling.
Soil, rocky clay loam.
Timber, scattered juniper and pinon.
Undergrowth, moderate sagebrush, scattered buckbrush,
yellowbrush, brigham tea and cactus.

Subdivision, T. 39 N., R. 2 W., Arizona

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy.
of the township, previously described.

N. 0°01' W., bet. secs. 35 and 36.

Over rolling and broken land, asc. SW. slope.

1.30 Spur, slopes W.; thence over rolling W. slope.

7.40 Draw, drains W.; asc. SW. slope.

20.30 Top of mesa, desc. gentle N. slope.

20.80 Begin desc. over steep N. slope.

33.90 Draw, drains N. 60° W. from S. 20° E.; asc. steep
S. slope.

39.20 Rocky low rim of mesa, bears irregularly E. and W.;
asc. S. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set the iron post 5 ins. in the ground, mound with
stones to top, cap mkd.

T39N R2W

$\frac{1}{4}$
S35|S36
1965

from which

A pinon, 6 ins. diam., bears S. 66°40' E.,
7 lks. dist., mkd. $\frac{1}{4}$ S36 B T

A pinon, 12 ins. diam., bears S. 73°20' W.,
91 lks. dist., mkd. $\frac{1}{4}$ S35 B T

44.60 Top of gently rolling mesa; desc. gentle N. slope.

49.70 Wash, 6 lks. wide, 6 ins. deep, drains NW.

62.90 Begin desc. over steep NE. slope.

72.00 Wash, 10 lks. wide, with 3 ft. banks, drains N. 70° W.;
desc. over W. slope.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set the iron post 24 ins. in the ground, cap mkd.

T39N R2W

S26|S25
S35|S36
1965

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
	<p>Build a mound with stones W. of the cor.</p> <p>Land, broken and rolling. Soil, gravelly loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, brigham tea and cactus.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the township, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1916 survey.</p> <p>N. 89°57' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
6.80	Begin asc. over SE. slope.
14.50	Ridge, bears S. 15° W. and irregularly N.; desc. SW. slope.
24.80	Wash, 5 lks. wide, 1 ft. deep, drains N. 70° W.; asc. broken NE. slope.
24.90	Track road, bears S. 60° E. and N. 50° W.
39.97	Point for the ¼ sec. cor. of secs. 25 and 36.
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W ¼ $\frac{S25}{S36}$ 1965</p>
	Asc. NE. slope.
43.00	E. rim of ridge, rim bears S. 15° E. and N. 30° W.; thence over gently rolling ridge top.
50.50	W. rim of ridge, rim bears SE. and NW.; desc. steep SW. slope.
58.50	Draw, drains NW.; asc. steep NE. slope.
63.20	E. rim of ridge, rim bears SE. and NW.; desc. gentle SW. slope.
65.10	W. rim of ridge, rim bears irregularly N. and S.; desc. steep NW. slope.
79.94	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, broken and rolling. Soil, gravelly loam. Timber, scattered juniper and pinon. Undergrowth, dense sagebrush, scattered yellowbrush and cactus.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>

CHAINS	
12.70	Wash, 8 lks. wide, 6 ins. deep, drains irregularly W.
16.20	Begin desc. over gentle NW. slope.
24.80	Wash, 15 lks. wide, 1 ft. deep, drains irregularly SW. from N. 70° E.
25.40	Small wash, drains SW.
25.60	Track road, bears NE. and SW.
32.60	Wash in bottom of Pigeon Canyon, 10 lks. wide, 3 ft. deep, drains S. 20° W.; asc. SE. slope.
40.00	Point for the ¼ sec. cor. of secs. 25 and 26.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W ¼ S26 S25 1965
	Asc. S. slope.
45.90	Enter moderate timber, edge bears N. 75° E. and N. 65° W.
47.00	S. rim of ridge, bears E. and NW.
52.10	Crest of ridge, bears SE. and NW.; desc. gentle N. slope.
53.20	Track road, bears NE. and SW.; leave timbered area.
77.00	Track road, bears SE. and N. 60° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T29N R2W S23 S24 S26 S25 1965
	from which
	The center of a wire gate bears N. 81°41' W., 3.20 chs. dist.
	Land, rolling. Soil, gravelly loam. Timber, scattered juniper and pinon in the N. half mile. Undergrowth, moderate sagebrush, scattered yellowbrush and cactus.
	<hr/> From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1916 survey.

CHAINS		
	<p>N. 89°57' W., bet. secs. 24 and 25.</p>	
	<p>Over gently rolling land.</p>	
31.70	<p>Track road, bears S. 22° E. and N. 22° W.; asc. E. slope.</p>	
35.50	<p>Thence over nearly level land.</p>	
39.93	<p>Point for the ¼ sec. cor. of secs. 24 and 25.</p>	
	<p>Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p style="text-align: center;">T39N R2W ¼ $\frac{S24}{S25}$ 1965</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">The center of a corral bears S. 30°27' E., 20.70 chs. dist.</p>	
	<p style="padding-left: 40px;">The center of a metal water tank, 50 lks. diam., 2 ft. high, bears S. 28°25' E., 19.30 chs. dist.</p>	
62.60	<p>Desc. gentle SW. slope.</p>	
68.70	<p>Asc. gentle E. slope.</p>	
79.86	<p>The cor. of secs. 23, 24, 25 and 26.</p>	
	<p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush.</p>	
	<hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p>	
	<p>Over gently rolling land; desc. gentle N. slope.</p>	
0.50	<p>Track road, bears N. 20° E. and S. 15° W.</p>	
6.63	<p>Fence, bears N. 27°24' E. and S. 27°24' W.</p>	
17.50	<p>Wash, 5 lks. wide, 6 ins. deep, drains N. 80° W.; asc. SW. slope of Cedar Knoll through scattered timber.</p>	
25.50	<p>Track road, bears irregularly NE. and SW.; desc. gentle NW. slope.</p>	
37.30	<p>Head of draw, drains N. 50° W. for 3.50 chs., thence drains W.; asc. gentle SW. slope.</p>	
40.00	<p>Point for the ¼ sec. cor. of secs. 23 and 24.</p>	
	<p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p style="text-align: center;">T39N R2W ¼ $\frac{S23}{S24}$ 1965</p>	

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

12

12.

CHAINS		
42.60	Spur, slopes N. 60° W.; desc. N. slope through dense timber.	
46.10	Draw, drains NW. for 3.00 chs., thence drains W.	
48.30	Spur, slopes W.	
49.80	Draw, drains SW. for 3.00 chs., thence drains W.; asc. SE. slope.	
52.70	Spur, slopes W.; desc. N. slope.	
56.40	Draw, drains N. 20° W.; asc. S. slope.	
59.70	Spur, slopes W.; desc. NW. slope.	
63.20	Draw, drains W.; asc. SW. slope.	
65.80	Begin desc. along W. slope.	
69.50	Small draw, drains irregularly W.; asc. SW. slope.	
72.70	Low spur, slopes W.; desc. NW. slope.	
78.70	Small draw, drains irregularly W.; asc. gentle SW. slope.	
80.00	Point for the cor. of secs. 13, 14, 23 and 24.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	<p>T39N R2W <u>S14</u> <u>S13</u> <u>S23</u> <u>S24</u> 1965</p>	
	from which	
	<p>Triangulation station GRAVEL bears N. 71°22'37" E., 15.14 chs. dist.</p>	
	Build a mound with stones W. of the cor.	
	Land, gently rolling.	
	Soil, gravelly loam (with old washed gravel on slopes of Cedar Knoll).	
	Timber, none S. 20.00 chs., thence scattered to dense juniper and pinon.	
	Undergrowth, dense sagebrush in S. half mile, thence scattered sagebrush and cactus.	
	<hr/>	
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1916 survey.	
	N. 89°58' W., bet. secs. 13 and 24.	
	Over rolling land, asc. E. slope.	
23.50	E. rocky rim of draw, bears S. 10° E. and N. 10° W.	
24.80	Draw, drains N. 10° W.	
26.10	W. rocky rim of draw, bears S. 10° E. and N. 10° W.	

CHAINS	
30.50	Track road, bears SE. and NW.
39.87	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	Set the iron post 20 ins. in the ground, in a collar of stones to top, cap mkd.
	T39N R2W $\frac{1}{4}$ $\frac{S13}{S24}$ 1965
	Build a mound with stones N. of the cor.
	Asc. gentle E. slope.
41.60	Fence, bears N. 27°30' E. and S. 27°30' W.
54.30	Base of Cedar Knoll; asc. E. slope.
62.90	E. edge of Cedar Knoll, bears irregularly N. and S.; asc. gentle E. slope.
64.80	W. edge of Cedar Knoll, bears irregularly N. and S.; desc. W. slope.
67.10	Head of draw, drains N. 80° W.; desc. rolling and broken W. slope.
79.74	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling and hilly. Soil, gravelly loam, with washed gravel on slopes of Cedar Knoll. Timber, scattered on E. slopes, dense on W. slope. Undergrowth, moderate to scattered sagebrush.
	N. 0°01' W., bet. secs. 13 and 14.
	Over rolling land, through scattered timber.
8.00	Begin desc. over NE. slope.
11.70	Wash, 5 lks. wide, 6 ins. deep, drains N. 30° W.
30.40	Leave scattered timber; enter nearly level land through dense sagebrush.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	Set the iron post 20 ins. in the ground, cap mkd.
	T39N R2W $\frac{1}{4}$ $\frac{S14}{S13}$ 1965
	Build a mound of stones W. of the cor.
49.10	Wash, 10 lks. wide, 1 ft. deep, drains NW.
54.80	Enter widely scattered timber.
70.50	Small wash, drains NW.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

14.

14

CHAINS

77.30 Begin desc. over gentle N. slope.
 80.00 Point for the cor. of secs. 11, 12, 13 and 14.
 Set the iron post 20 ins. in the ground, cap mkd.

T39N R2W
 S11|S12
 S14|S13
 1965

Build a mound with stones W. of the cor.
 Land, gently rolling.
 Soil, gravelly loam.
 Timber, scattered juniper.
 Undergrowth, dense sagebrush, scattered yellowbrush
 and cactus.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy.
 of the township, monumented by an iron post 2 ins.
 diam., situated 2 lks. S. 27°28' W. of a cor. of fences
 bearing N. 40°23' E., S. 27°28' W. and N. 56°50' W.
 The cor. is marked as described in the official record
 of the 1916 survey.

N. 89°59' W., bet. secs. 12 and 13.

Over gently rolling land.

25.50 Begin desc. over gentle NW. slope.
 32.90 Draw, drains N. for 5.00 chs., thence drains NW.
 39.83 Point for the ¼ sec. cor. of secs. 12 and 13.

Set the iron post 5 ins. in the ground, mound with
 stones to top, cap mkd.

T39N R2W
 ¼ S12
 S13
 1965

50.30 Track road, bears S. 30° E. and NW.
 58.60 Enter scattered juniper; desc. gentle W. slope.
 74.60 Begin desc. over SW. slope.
 79.56 Small wash, drains NW.
 79.66 The cor. of secs. 11, 12, 13 and 14.

Land, gently rolling.
 Soil, gravelly loam.
 Timber, scattered juniper in west 20.00 chs.
 Undergrowth, dense sagebrush.

N. 0°01' W., bet. secs. 11 and 12.

Over rolling land, through dense sagebrush and
 scattered juniper.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
0.10	Small wash, drains NW.
10.70	Wash, 8 lks. wide, 6 ins. deep, drains S. 60° W.
25.60	Leave scattered juniper, continue through dense sagebrush.
33.40	Track road, bears N. 75° E. and SW.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W ¼ S11 S12 1965
42.85	Fence, bears S. 70° 15' E. for 10.00 chs., thence bears E., and bears N. 70° 15' W. for 0.90 chs., thence bears N. 23° W.
51.50	S. rim of draw, bears E. and irregularly W.
55.60	Wash, 10 lks. wide, 2 ft. deep, drains W. for 2.00 chs., thence drains N. 20° W.
61.50	N. rim of same draw, bears irregularly SE. and N. 80° W.
74.60	Small draw, drains NW. 6.00 chs. to main draw.
79.85	Wash, 8 lks. wide, 6 ins. deep, drains W.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W S 2 S 1 S11 S12 1965
	Land, gently rolling. Soil, rocky and sandy loam. Timber, scattered juniper. Undergrowth, dense sagebrush, scattered yellowbrush.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1916 survey.
	N. 89° 58' W., bet. secs. 1 and 12.
	Over rolling land.
1.70	E. rim of rocky draw, bears SE. and irregularly NW.
2.80	W. rim of same draw, bears irregularly E. and S. 70° W.
22.00	Low ridge, bears S. 70° E. and N. 80° W.; desc. gentle W. slope.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

16.

16

CHAINS	
38.90	E. rim of draw, bears irregularly N. and S.; desc. W. slope.
39.79	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12. Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
<p>T39N R2W $\frac{1}{4}$ $\frac{S 1}{S 12}$ 1965</p>	
41.60	Wash, 8 lks. wide, 2 ft. deep, drains N. 20° E. for 5.00 chs., thence drains NW.
44.60	W. rim of draw, bears same as draw.
56.00	Small draw, drains N. 40° E.
77.10	Small wash, 6 lks. wide, 6 ins. deep, drains S. 15° W.
79.58	The cor. of secs. 1, 2, 11 and 12. Land, broken and rolling. Soil, gravelly loam. Timber, scattered juniper. Undergrowth, dense sagebrush, scattered yellowbrush.
<hr/> <p>N. 0°19' W., bet. secs. 1 and 2.</p>	
<p>Over gently rolling land.</p>	
32.70	S. rim of draw, bears S. 20° E. and N. 30° W. for 1.00 chain, thence bears E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
<p>T39N R2W $\frac{1}{4}$ S 2 S 1 1965</p>	
<p>from which A catch pond, bears N. 79°48' W., 45.80 chs. dist.</p>	
45.50	Wash, 15 lks. wide, 2 ft. deep, drains NW. from S. 20° E.
46.70	N. rim of draw, bears irregularly SE. and NW.
48.00	Spur, slopes W.
49.40	Wash, 15 lks. wide, 1 ft. deep, drains W. from N. 80° E.
59.50	Track road, bears S. 60° E. and NW.
64.80	Begin desc. over gentle N. slope.

CHAINS	
77.80	Wash, 10 lks. wide, 2 ft. deep, drains W. for 3.00 chs., thence drains SW.
80.07	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the township, monumented by an iron post, $\frac{1}{2}$ ins. diam. and witnessed as described in the official record of the 1954 survey.</p> <p>Land, rolling. Soil, gravelly loam. Timber, widely scattered juniper. Undergrowth, dense sagebrush, scattered yellowbrush.</p>
<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the township, previously described.</p>	
<p>N. 0°01' W., bet. secs. 34 and 35.</p>	
<p>Over rolling land, desc. NE. slope through dense sagebrush.</p>	
2.30	Wash, 30 lks. wide, 1 ft. deep, drains irregularly NW. from SE.
8.53	S. bank of catch pond.
12.00	N. bank of same pond.
12.90	Fence, bears S. 80° E. and N. 80° W.
18.20	Spur, slopes SE.; asc. along E. slope.
29.30	Begin asc. over SE. slope.
36.50	Rim, bears NE. and SW.; thence over nearly level land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
<p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p>	
<p style="text-align: center;">T39N R2W $\frac{1}{4}$ S34 S35 1965</p>	
44.10	Track road, bears N. 60° E. and S. 60° W.
54.20	Enter moderate timber, edge bears E. and W.; asc. S. slope.
59.50	Low ridge, bears E. and W.
66.30	Desc. gentle NE. slope.
73.70	End of NE. slope; thence over nearly level land.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
<p>Set the iron post 22 ins. in the ground, cap mkd.</p>	
<p style="text-align: center;">T39N R2W S27 S26 S34 S35 1965</p>	

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

18

18.

CHAINS	
	Build a mound with stones W. of the cor.
	Land, S. half mile broken, N. half mile gently rolling. Soil, gravelly loam. Timber, scattered juniper and pinon. Undergrowth, dense sagebrush, scattered yellowbrush and cactus.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°58' W., bet. secs. 26 and 35, through scattered timber.
	Over rolling land, asc. gentle NE. slope.
2.20	Desc. gentle W. slope.
30.30	Wash, 5 lks. wide, 1 ft. deep, drains irregularly SW.; leave scattered timber.
30.90	Track road, bears NE. and SW.
39.96	Point for the ¼ sec. cor. of secs. 26 and 35.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W ¼ $\frac{S26}{S35}$ 1965
44.20	Wash, 5 lks. wide, 1 ft. deep, drains S. 20° E. from NW.
45.20	Fence, bears N. 27°24' E. and S. 27°24' W.; asc. steep E. slope.
49.10	Rim, bears irregularly N. and S.; asc. gentle E. slope.
53.80	Track road, bears N. 25° E. and S. 25° W.; enter moderate timber.
63.90	Begin desc. along gentle S. slope.
78.50	Track road, bears SE. and NW.; desc. gentle SW. slope.
79.92	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling and broken. Soil, gravelly loam. Timber, scattered to moderate. Undergrowth, dense sagebrush.
	N. 0°01' W., bet. secs. 26 and 27.
	Over nearly level land, through scattered timber.
1.70	Track road, bears SE. and NW.
8.00	Enter moderate timber.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
16.00	Timber thins to scattered.
30.10	Track road, bears NE. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W $\frac{1}{4}$ S27 S26 1965
51.30	Leave scattered timber.
71.90	Desc. gentle N. slope.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W S22 S23 S27 S26 1965
	Land, nearly level. Soil, gravelly loam. Timber, widely scattered juniper and pinon. Undergrowth, dense sagebrush, scattered cactus.
	From the cor. of secs. 23, 24, 25 and 26.
	N. $89^{\circ}57'$ W., bet. secs. 23 and 26.
3.40	Fence, bears N. $27^{\circ}24'$ E. and S. $27^{\circ}24'$ W. (A wire gate in fence line, bears N. $27^{\circ}24'$ E., 46 lks. dist.)
3.90	Track road, bears N. $27^{\circ}24'$ E. for 50 lks., curving to E. and S. $27^{\circ}24'$ W.
25.90	Begin desc. over gentle SW. slope.
29.90	Thence over nearly level land.
39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	Set the iron post 20 ins. in the ground, cap mkd.
	T39N R2W $\frac{1}{4}$ $\frac{S23}{S26}$ 1965
	Build a mound with stones N. of the cor.
53.90	Asc. gentle E. slope.
79.92	The cor. of secs. 22, 23, 26 and 27.
	Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered cactus.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

20

20.

CHAINS		
	N. 0°01' W., bet. secs. 22 and 23.	
	Over nearly level land.	
30.20	Track road, bears N. 80° E. and W.	
40.00	Point for the ¼ sec. cor. of secs. 22 and 23.	
	Set the iron post 18 ins. in the ground, cap mkd.	
	T39N R2W ¼ S22 S23 1965	
	Build a mound with stones W. of the cor.	
54.10	Enter scattered timber.	
57.70	Draw, drains N. 70° W. from irregularly SE.	
80.00	Point for the cor. of secs. 14, 15, 22 and 23.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T39N R2W S15 S14 S22 S23 1965	
	Build a mound with stones W. of the cor.	
	Land, nearly level.	
	Soil, gravelly loam.	
	Timber, widely scattered juniper in S. half mile.	
	Undergrowth, dense sagebrush.	

	From the cor. of secs. 13, 14, 23 and 24.	
	N. 89°57' W., bet. secs. 14 and 23.	
	Over gently rolling land, through dense patches of timber, by triangulation, topography as estimated.	
	Desc. SW. slope through dense timber.	
20.00	Wash, 10 lks. wide, 1 ft. deep, drains NW.; thence over gently rolling land.	
39.96	Point for the ¼ sec. cor. of secs. 14 and 23; end of triangulation.	
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.	
	T39N R2W ¼ <u>S14</u> S23 1965	
	from which	
	A juniper, 12 ins. diam., bears N. 31°15' W., 72 lks. dist., mkd. ¼ S14 B T	

CHAINS	
	<p>A juniper, 24 ins. diam., bears S. 35°15' E., 73 lks. dist., mkd. $\frac{1}{4}$ S23 B T</p> <p>Thence through scattered timber.</p>
52.80	Leave scattered timber; enter dense sagebrush.
56.40	Wash, 5 lks. wide, 6 ins. deep, drains irregularly NW.
64.10	Track road, bears S. 30° E. and NW.
79.92	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, rolling in E. half mile, nearly level W. half mile. Soil, gravelly loam. Timber, moderate in E. half mile, scattered in W. half mile. Undergrowth, moderate to dense sagebrush.</p>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p>
21.40	Draw, drains NW.
31.80	Track road, bears S. 40° E. and N. 40° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R2W $\frac{1}{4}$ S15 S14 1965</p>
	Build a mound with stones W. of the cor.
64.00	Draw, drains N. 50° W.
68.80	Wash, 8 lks. wide, 6 ins. deep, drains irregularly SW.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R2W S10 S11 S15 S14 1965</p>
	<p>Land, gently rolling. Soil, gravelly loam. Timber, widely scattered in N. 20.00 chains. Undergrowth, dense sagebrush.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°57' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through widely scattered timber.</p>

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

22

22.

CHAINS		
17.80	Leave scattered timber, enter dense sagebrush.	
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.	
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.	
	T39N R2W $\frac{1}{4}$ $\frac{S11}{S14}$ 1965	
52.00	Track road, bears SE. and NW.	
57.10	Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.	
61.00	Enter moderate timber, edge bears SE. and NW.	
73.60	Leave moderate timber, edge bears NE. and S. 80° W.	
79.96	The cor. of secs. 10, 11, 14 and 15.	
	Land, nearly level. Soil, gravelly loam. Timber, patches of juniper in E. and W. 20.00 chains. Undergrowth, dense sagebrush.	
	N. 0°01' W., bet. secs. 10 and 11.	
	Over gently rolling land.	
20.70	Track road, bears N. 40° E. and S. 50° W.	
24.00	Wash, 12 lks. wide, 1 ft. deep, drains N. 70° W.	
33.60	Draw, drains NW.	
39.30	Wash, 8 lks. wide, 1 ft. deep, drains N. 60° W. from SE.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T39N R2W $\frac{1}{4}$ S10 S11 1965	
	Build a mound with stones W. of the cor.	
50.40	Wash, 10 lks. wide, 2 ft. deep, drains irregularly W.	
59.20	Draw, drains irregularly W.	
70.00	Small wash, 6 lks. wide, 6 ins. deep, drains NW.	
74.10	Draw, drains W. for 4.00 chs., thence drains N. 20° W.	
80.00	Point for the cor. of secs. 2, 3, 10 and 11.	
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.	

CHAINS		
	<p style="text-align: center;">T39N R2W $\frac{S\ 3}{S10} \frac{S\ 2}{S11}$ 1965</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, widely scattered juniper. Undergrowth, dense sagebrush, scattered yellowbrush.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12. N. 89°58' W., bet. secs. 2 and 11. Over rolling land, desc. W. slope through scattered timber.</p>	
2.90	Wash, 10 lks. wide, 1 ft. deep, drains irregularly N.	
19.50	Track road, bears SE. and NW.	
19.65	Fence, bears same as road.	
25.80	Rim of draw, bears S. 60° E. and NW.; desc. SW. slope.	
27.40	Wash, 15 lks. wide, 6 ins. deep, drains N. 30° W. from S. 20° E.; asc. NE. slope.	
29.40	W. rim of same draw, bears S. 20° E. and N. 60° W.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.	
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.	
	<p>T39N R2W $\frac{1}{4} \frac{S\ 2}{S11}$ 1965</p>	
44.80	Wash, 10 lks. wide, 6 ins. deep, drains N. 10° E.	
52.10	Leave scattered timber.	
66.00	Track road, bears S. 30° E. and N. 30° W.	
67.10	Rocky outcrop, bears S. 60° W. and NW.; enter scattered timber.	
73.60	Wash, 5 lks. wide, 6 ins. deep, drains SW. from N.	
77.00	Asc. gentle E. slope.	
80.00	The cor. of secs. 2, 3, 10 and 11.	
	<p>Land, gently rolling. Soil, gravelly loam. Timber, scattered patches of juniper. Undergrowth, dense sagebrush.</p> <hr/> <p>N. 0°19' W., bet. secs. 2 and 3. Over gently rolling land.</p>	

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

24

24.

CHAINS	
23.70	Track road, bears S. 40° E. and NW.
36.93	Fence, bears N. 42°40' E. and S. 42°40' W.
40.00	Point for the ¼ sec. cor. of secs. 2 and 3.
	Set the iron post 20 ins. in the ground, cap mkd.
	T39N R2W ¼ S 3 S 2 1965
	Build a mound with stones W. of the cor.
44.10	Wash, 5 lks. wide, 1 ft. deep, drains N. 60° W. from irregularly SE.
53.70	Track road, bears S. 80° E. and N. 70° W.
80.07	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1954 survey.
	Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the township, previously described.
	N. 0°02' W., bet. secs. 33 and 34.
	Over gently rolling land, through moderate timber.
5.20	Track road, bears E. and irregularly W.; timber thins to widely scattered.
26.10	Desc. gentle N. slope.
38.70	Draw, drains N. 70° W.; asc. gentle SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 33 and 34.
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W ¼ S33 S34 1965
45.20	Desc. gentle N. slope.
51.90	Rim of small draw, bears SE. and SW.
52.20	Small draw, drains irregularly W.
53.20	Rocky ledge, bears SE. and N. 60° W.
61.00	Desc. gentle NW. slope.

CHAINS	
76.00	Asc. gentle S. slope.
79.60	S. edge of bedding ground for sheep, bears E. and W.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W $\frac{S28}{S33} \frac{S27}{S34}$ 1965
	Land, gently rolling. Soil, gravelly loam. Timber, widely scattered juniper. Undergrowth, dense sagebrush.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89°57' W., bet. secs. 27 and 34.
	Over nearly level land, desc. gentle SW. slope through widely scattered timber.
2.40	Wash, 8 lks. wide, 1 ft. deep, drains N. 70° W.
24.00	Leave widely scattered timber, enter dense sagebrush.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	Set the iron post 20 ins. in the ground, cap mkd.
	T39N R2W $\frac{1}{4} \frac{S27}{S34}$ 1965
	Build a mound with stones N. of the cor.
	Desc. gentle SW. slope.
65.70	Thence over nearly level land.
75.80	Asc. gentle NE. slope.
77.80	E. edge of bedding ground for sheep, bears SE. and N. 10° W.; thence over level land.
80.02	The cor. of secs. 27, 28, 33 and 34.
	Land, gently rolling. Soil, gravelly loam. Timber, widely scattered juniper. Undergrowth, dense sagebrush.
	N. 0°02' W., bet. secs. 27 and 28.
	Over nearly level land.
3.20	N. edge of bedding ground for sheep, bears E. and SW.; desc. gentle N. slope.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

26

26.

CHAINS		
9.90	Wash, 6 lks. wide, 1 ft. deep, drains NW.; asc. gentle S. slope.	
13.90	Track road, bears N. 80° W. and SE. for 1.50 chs., thence bears E.	
40.00	Point for the ¼ sec. cor. of secs. 27 and 28. Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.	
51.80	Track road, bears SE. and NW.	
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set the iron post 18 ins. in the ground, cap mkd. <div style="text-align: center;"> T39N R2W $\frac{1}{4}$ S28 S27 1965 </div>	
40.02	<div style="text-align: center;"> T39N R2W S21 S22 S28 S27 1965 </div> <p>Build a mound with stones W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, widely scattered juniper in south portion. Undergrowth, dense sagebrush, scattered cactus.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over nearly level land, through dense sagebrush.</p>	
40.02	Point for the ¼ sec. cor. of secs. 22 and 27. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd. <div style="text-align: center;"> T39N R2W $\frac{1}{4}$ $\frac{S22}{S27}$ 1965 </div>	
80.04	The cor. of secs. 21, 22, 27 and 28. Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered cactus.	
31.00	<p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land, through dense sagebrush.</p> <p>Track road, bears E. and W.</p>	

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ S21 S22 1965</p>
41.40	<p>Track road, bears NE. and SW.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W S16 S15 S21 S22 1965</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered cactus.</p>
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>West, bet. secs. 15 and 22.</p>
	<p>Over gently rolling land.</p>
28.40	<p>Small draw, drains N. 5° E. from S.</p>
40.05	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.</p> <p>Set the iron post over an X chiseled on solid rock, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ S15 S22 1965</p>
43.40	<p>Wash, 5 lks. wide, 1 ft. deep, drains N. for 60 lks., thence drains NW.</p>
78.70	<p>Track road, bears SE. and NW.</p>
80.10	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, widely scattered in E. half mile. Undergrowth, dense sagebrush, widely scattered cactus.</p>
	<hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p>
	<p>Over gently rolling land, through dense sagebrush.</p>
0.80	<p>Track road, bears SE. and NW.</p>

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

28

28.

CHAINS		
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.</p> <p>Set the iron post 18 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ S16 S15 1965</p> <p>Build a mound with stones W. of the cor.</p>	
50.20	<p>Wash, 13 lks. wide, 1 ft. deep, drains NW.</p>	
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W S 9 S10 S16 S15 1965</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered cactus.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. $89^{\circ}59'$ W., bet. secs. 10 and 15.</p> <p>Over gently rolling land.</p>	
19.70	<p>Track road, bears NE. and SW.</p>	
26.90	<p>Track road, bears SE. and N. 60° W.</p>	
35.00	<p>Desc. gentle SW. slope.</p>	
40.05	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Set the iron post 18 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ <u>S10</u> S15 1965</p> <p>from which</p> <p style="padding-left: 40px;">A catch pond bears N. 76° W., 21.00 chs. dist.</p> <p>Build a mound with stones N. of the cor.</p>	
51.00	<p>Wash, 7 lks. wide, 1 ft. deep, drains NW.</p>	
80.10	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, widely scattered juniper in E. half mile. Undergrowth, dense sagebrush, scattered cactus.</p> <hr/>	

CHAINS

N. $0^{\circ}02'$ W., bet. secs. 9 and 10.

Over gently rolling land.

15.60 Wash, 10 lks. wide, 1 ft. deep, drains irregularly SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T39N R2W

$\frac{1}{4}$
S 9 | S10
1965

Cor. is set in bottom of a small draw draining W.

49.00 Desc. gentle N. slope.

54.80 Draw, drains SW.

66.10 Track road, bears S. 80° E. and W. for 2.00 chs., thence SW.

69.10 Track road, bears NE. and SW.

73.00 Desc. gentle NW. slope.

76.30 Track road, bears N. 55° E. and S. 60° W.; desc. gentle N. slope.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set the iron post 20 ins. in the ground, cap mkd.

T39N R2W

S 4 | S 3
S 9 | S10
1965

Build a mound with stones W. of the cor.

Land, gently rolling.

Soil, gravelly loam.

Timber, widely scattered juniper.

Undergrowth, dense sagebrush, scattered cactus.

From the cor. of secs. 2, 3, 10 and 11.

N. $89^{\circ}58'$ W., bet. secs. 3 and 10.

Over rolling land, desc. gentle W. slope through widely scattered timber.

12.30 Wash, 7 lks. wide, 1 ft. deep, drains N. from S. 30° W.; asc. gentle E. slope.

21.30 Leave widely scattered timber; thence over gently rolling land.

33.82 Point on line, from which a cor. of fences bearing N. $43^{\circ}15'$ E. and W., bears N., 76 lks. dist.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
40.05	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ $\frac{S\ 3}{S10}$ 1965</p>
43.80	Wash, 10 lks. wide, 1 ft. deep, drains SW.
56.00	Wash area, drains NW.
70.50	Track road, bears N. 20° W. and S. 25° E. for 1.00 chain, thence S. 70° W.
80.10	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, widely scattered juniper. Undergrowth, dense sagebrush, scattered yellowbrush and cactus.</p>
N. 0°19' W., bet. secs. 3 and 4.	
Over gently rolling land.	
0.23	Fence, bears N. 89°30' E. and S. 89°50' W.
0.35	Track road, parallel to fence.
12.10	Track road, bears SE. and NW.
14.40	Wash, 6 lks. wide, with 3 ft. banks, drains N. 35° W. from SE.
32.50	Wash, 5 lks. wide, 1 ft. deep, drains NW.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ S 4 S 3 1965</p>
from which	
A catch pond bears N. 58° W., 26.90 chs. dist.	
64.10	S. rim of draw, bears SE. and NW.; desc. NE. slope.
69.40	Wash, 10 lks. wide, 1 ft. deep, drains NW.; asc. S. slope.
72.10	Slope changes to a W. slope.
78.50	Wash, 7 lks. wide, 6 ins. deep, drains S. 60° W.; asc. S. slope.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
80.08	<p>The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1954 survey.</p> <p>Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered yellowbrush and cactus.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the township, previously described.</p>
	<p>N. 0°03' W., bet. secs. 32 and 33.</p>
	<p>Over gently rolling land.</p>
10.30	<p>Track road, bears E. and W.</p>
32.00	<p>Desc. gentle N. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 32 and 33.</p>
	<p>Set the iron post 18 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R2W ½ S32 S33 1965</p>
	<p>Build a mound with stones W. of the cor.</p>
56.00	<p>Over gently rolling land.</p>
67.90	<p>Track road, bears N. 20° E. and S. 80° W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p>
	<p>Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T39N R2W S29 S28 S32 S33 1965</p>
	<p>Land, gently rolling. Soil, gravelly loam. Timber, widely scattered juniper in S. half mile. Undergrowth, dense sagebrush, widely scattered cactus.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>N. 89°57' W., bet. secs. 28 and 33.</p>
	<p>Over gently rolling land.</p>
2.50	<p>W. edge of bedding ground for sheep, bears N. and S.</p>
21.50	<p>Draw, drains N. 60° W.</p>
25.40	<p>Wash, 5 lks. wide, 6 ins. deep, drains NW. from N. 60° E.</p>

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS

- 39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.
 Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
 T39N R2W
 $\frac{1}{4}$ $\frac{S28}{S33}$
 1965
- 43.70 Track road, bears N. 65° E. and S. 65° W.
- 79.98 The cor. of secs. 28, 29, 32 and 33.
 Land, gently rolling.
 Soil, gravelly loam.
 Timber, widely scattered juniper in E. 20.00 chs.
 Undergrowth, dense sagebrush, widely scattered cactus.
-
- N. 0°03' W., bet. secs. 28 and 29.
 Over gently rolling land.
- 38.30 Wash, 15 lks. wide, 1 ft. deep, drains N. 85° W.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
 Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
 T39N R2W
 $\frac{1}{4}$
 S29 | S28
 1965
- Continue over nearly level land.
- 80.00 Point for the cor. of secs. 20, 21, 28 and 29.
 Set the iron post 20 ins. in the ground, cap mkd.
 T39N R2W
 S20 | S21
 S29 | S28
 1965
- Build a mound with stones W. of the cor.
 Land, gently rolling to nearly level.
 Soil, gravelly loam.
 Timber, none.
 Undergrowth, dense sagebrush, scattered cactus.
-
- From the cor. of secs. 21, 22, 27 and 28.
 N. 89°58' W., bet. secs. 21 and 28.
 Over nearly level land; desc. gentle W. slope.
- 39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.
 Set the iron post 18 ins. in the ground, cap mkd.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS

T39N R2W
 $\frac{1}{4}$ $\frac{S21}{S28}$
 1965

Build a mound with stones N. of the cor.

51.30 Track road, bears S. 60° E. and N. 60° W.

58.60 Track road, bears NE. and S. 30° W.

79.94 The cor. of secs. 20, 21, 28 and 29.

Land, nearly level.
 Soil, gravelly loam.
 Timber, none.
 Undergrowth, dense sagebrush, scattered cactus.

N. 0°03' W., bet. secs. 20 and 21.

Over gently rolling land.

6.80 Bladed right of way for future fence, bears N. and W.;
 thence along E. edge of bladed right of way.

14.20 Track road, bears S. 60° E. and N. 70° W.

21.30 Track road, bears N. 70° E. and S. 50° W.

28.40 Track road, bears S. 60° E. and N. 60° W.

33.60 Track road, bears N. 76° E. and S. 76° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.

Set the iron post 20 ins. in the ground, cap mkd.

T39N R2W
 $\frac{1}{4}$ $\frac{S20}{S21}$
 1965

from which

A catch pond bears S. 65°15' E., 8.10 chs. dist.

Build a mound with stones W. of the cor.

40.80 Draw, drains NW.

63.20 Desc. gentle N. slope.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set the iron post 18 ins. in the ground, cap mkd.

T39N R2W
 $\frac{S17}{S20}$ $\frac{S16}{S21}$
 1965

Build a mound with stones W. of the cor.

CHAINS	
	<p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p>
	<p>N. 89°58' W., bet. secs. 16 and 21.</p>
	<p>Over gently rolling land.</p>
39.96	<p>Point for the ¼ sec. cor. of secs. 16 and 21. Set the iron post 15 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R2W ¼ $\frac{S16}{S21}$ 1965</p>
	<p>Build a mound with stones N. of the cor.</p>
	<p>Continue over gently rolling land.</p>
79.92	<p>The cor. of secs. 16, 17, 20 and 21.</p>
	<p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered cactus.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p>
	<p>Over gently rolling land.</p>
28.00	<p>Track road, bears N. 29°30' E. and S. 28°30' W.; desc. gentle N. slope.</p>
36.00	<p>Draw, drains NW.; asc. gentle S. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 16 and 17. Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T39N R2W ¼ S17 S16 1965</p>
69.70	<p>Junction of track roads, bearing SE., SW. and NW.</p>
72.00	<p>Desc. gentle N. slope.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17. Set the iron post 5 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R2W S 8 S 9 S17 S16 1965</p>
	<p>Build a mound with stones W. of the cor.</p>

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
	<p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16. N. 89°59' W., bet. secs. 9 and 16. Over gently rolling land.</p>
23.20	Desc. gentle W. slope.
26.90	Draw, drains N. 30° W. from SE.; asc. broken E. slope.
28.70	W. rim of same draw, bears N. 30° W. and SE.; thence over gently rolling land.
39.97	Point for the ¼ sec. cor. of secs. 9 and 16. Set the iron post 18 ins. in the ground, cap mkd.
	<p>T39N R2W ¼ $\frac{S\ 9}{S16}$ 1965</p>
	Build a mound with stones N. of the cor.
49.60	Track road, bears N. and S.
70.60	E. rim of draw, bears SE. and N.
73.20	Draw, drains irregularly N. from SE.
75.90	W. rim of same draw, bears N. and S. for 5.50 chs., thence SE.
79.94	The cor. of secs. 8, 9, 16 and 17.
	<p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9. Over gently rolling land.</p>
4.90	Bladed right of way for future fence, bears N. 31°30' E. and S.
15.20	Desc. N. slope.
24.60	Wash, 6 lks. wide, 1 ft. deep, drains N. 80° W. for 4.00 chs. thence drains irregularly N.; asc. S. slope.
28.60	N. Rim of draw, bears irregularly E. and W.
36.80	Desc. NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 8 and 9.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

36

36.

CHAINS		
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{2}$ S 8 S 9 1965</p> <p>from which</p> <p style="padding-left: 40px;">A catch pond bears S. 65° W., 2.00 chs. dist.</p> <p>Build a mound with stones W. of the cor.</p>	
40.70	Draw, drains irregularly SW. into catch pond.	
73.30	Track road, bears S. 60° E. and NW.	
74.00	Track road, bears S. 60° E. and NW.	
79.90	Fence bears E. and W. for 21 lks., thence N. 70°30' W.	
80.00	Point for the cor. of secs. 4, 5, 8 and 9.	
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W S 5 S 4 S 8 S 9 1965</p> <p>Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered yellowbrush.</p>	
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p>	
30.30	Track road, bears E. and S. 29°30' W.	
31.00	Bladed right of way for future fence, bears S. 29°30' W.	
33.00	Fence, bears N. 89°36' E. and S. 89°36' W.	
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.	
	<p>Set the iron post 15 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ S 4 S 9 1965</p> <p>from which</p> <p style="padding-left: 40px;">An East-West fence bears S., 4 lks. dist.</p>	
54.60	Wash, 5 lks. wide, 6 ins. deep, drains NW.	

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
71.50	Small wash, drains NW.
73.80	Wash, 10 lks. wide, 1 ft. deep, drains N. 40° W.
79.94	The cor. of secs. 4, 5, 8 and 9.
	Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered yellowbrush and cactus.
	N. 0°18' W., bet. secs. 4 and 5.
	Over gently rolling land.
11.20	Wash, 5 lks. wide, 6 ins. deep, drains irregularly NW.
22.50	Small draw, drains NW.
28.30	Track road, bears N. 60° E. and SW.
36.00	Small draw, drains NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R2W $\frac{1}{4}$ S 5 S 4 1965</p>
	Build a mound with stones W. of the cor.
46.20	Wash, 10 lks. wide, 6 ins. deep, drains NW. from S. 60° E.
50.00	Draw, drains W.; asc. S. slope.
56.00	Desc. along gentle W. slope.
64.00	Desc. gentle N slope.
71.00	S. rim of draw, bears SE. and NW.; desc. N. slope.
72.00	Draw, drains NW.
73.50	N. rim of same draw, bears irregularly SE. and NW.; asc. gentle S. slope.
78.90	Desc. steep N. slope.
80.18	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the township, monumented by an iron post 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1954 survey.
	Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush.

CHAINS	
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the township, previously described.</p>
	<p>N. 0°03' W., bet. secs. 31 and 32.</p>
	<p>Over gently rolling land.</p>
23.00	<p>Track road, bears SE. and NW.</p>
28.30	<p>Asc. gentle S. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p>
	<p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T39N R2W $\frac{1}{4}$ S31 S32 1965</p>
	<p>Desc. gentle N. slope.</p>
53.90	<p>Track road, bears S. 60° E. and N. 60° W.</p>
55.50	<p>Wash, 5 lks. wide, 6 ins. deep, drains N. 85° W.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p>
	<p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T39N R2W S30 S29 S31 S32 1965</p>
	<p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered yellowbrush.</p>
	<hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p>
	<p>West, bet. secs. 29 and 32.</p>
	<p>Over gently rolling land.</p>
11.70	<p>Asc. gentle NE. slope.</p>
24.00	<p>Desc. gentle W. slope.</p>
39.99	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.</p>
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T39N R2W $\frac{1}{4}$ S29 S32 1965</p>
	<p>Build a mound with stones N. of the cor.</p>

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS

68.00 Small draw, drains N.

79.98 The cor. of secs. 29, 30, 31 and 32.

Land, gently rolling.
Soil, gravelly loam.
Timber, none.
Undergrowth, dense sagebrush.

West, bet. secs. 30 and 31.

Over gently rolling land.

14.40 Draw, drains N. 30° W., track road, bears N. 25° E. and S. 25° W.

36.80 Track road, bears SE. and NW.

40.00 Point for the 1/4 sec. cor. of secs. 30 and 31.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T39N R2W
1/4 S30
S31
1965

45.60 Track road, bears SE. and NW.

62.40 Small draw, drains NW.; asc. NE. slope.

64.60 Spur, slopes N.; desc. gentle NW. slope.

67.10 Wash, 7 lks. wide, 1 ft. deep, drains N. 10° E.; asc. E. slope.

77.40 Desc. gentle W. slope.

78.82 Intersect the W. bdy. of the township.

Point for the closing cor. of secs. 30 and 31.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T39N | T39N
S36 | S30 C
R3W | S31 C
R2W
1965

from which

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township, bears North, 6.23 chs. dist., monumented by an iron post 3 ins. diam. with brass cap mkd.

T39N
R3W | S25 | S30 | R2W
S36 | S31
1914

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

40

40.

CHAINS

As this cor. now functions for secs. 25 and 36 only, I remark the brass cap to read

T39N
 R3W $\frac{S25}{S36}$ | R2W
 1965
 1914

Land, gently rolling.
 Soil, gravelly loam.
 Timber, none.
 Undergrowth, dense sagebrush.

The point for the $\frac{1}{4}$ sec. cor. of sec. 31 is on the W. bdy. of the township at mid-point bet. the closing corners.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T39N
 $\frac{1}{4}$ S31
 R2W
 1965

from which

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36 on the W. bdy. of the township bears North, 6.20 chs. dist., monumented by an iron post 1 inch diam., with brass cap mkd.

$\frac{1}{4}$
 S36 | S31
 1914

As this cor. now functions for sec. 36 only, I remark the brass cap to read

$\frac{1}{4}$
 T39N |
 S36 |
 R3W |
 1965
 1914

From the cor. of secs. 29, 30, 31 and 32.

N. 0°03' W., bet. secs. 29 and 30.

Over gently rolling land.

27.50 Track road, bears N. 55° E. and S. 55° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Set the iron post 22 ins. in the ground, cap mkd.

T39N R2W
 $\frac{1}{4}$
 S30 | S29
 1965

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
	Build a mound with stones W. of the cor.
49.40	Track road, bears N. 80° E. and S. 75° W.
76.70	Desc. gentle N. slope.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T39N R2W $\frac{S19}{S30} \frac{S20}{S29}$ 1965</p>
	Land, gently rolling.
	Soil, gravelly loam.
	Timber, none.
	Undergrowth, dense sagebrush, scattered cactus.
	From the cor. of secs. 20, 21, 28 and 29.
	West, bet. secs. 20 and 29.
	Over gently rolling land.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.
	Set the iron post 18 ins. in the ground, cap mkd.
	<p style="text-align: center;">T39N R2W $\frac{1}{4} \frac{S20}{S29}$ 1965</p>
	Build a mound with stones N. of the cor.
53.40	Track road, bears N. 30° E. and S. 30° W.
71.70	Draw, drains NW.
79.90	The cor. of secs. 19, 20, 29 and 30.
	Land, gently rolling.
	Soil, gravelly loam.
	Timber, none.
	Undergrowth, dense sagebrush, scattered cactus.
	West, bet. secs. 19 and 30.
	Over gently rolling land.
35.20	Track road, bears N. 20° E. and S. 20° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T39N R2W $\frac{1}{4} \frac{S19}{S30}$ 1965</p>

CHAINS

- 40.30 Small draw, drains N. for 5.00 chs., thence drains NW.; asc. E. slope.
- 51.00 Top of low hill; desc. over rolling W. slope.
- 61.00 Desc. along S. slope.
- 66.10 Asc. SE. slope.
- 68.50 Spur, slopes N.; desc. over NW. slope.
- 78.68 Intersect the W. bdy. of the township.

Point for the closing corner of secs. 19 and 30.

Set the iron post 20 ins. in the ground, cap mkd.

$$\begin{array}{r} \text{T39N} \\ \text{T39N} \left| \begin{array}{l} \text{S19} \\ \text{S25} \end{array} \right. \text{C} \\ \text{R3W} \left| \begin{array}{l} \text{S30} \\ \text{R2W} \end{array} \right. \text{C} \\ 1965 \end{array}$$

from which

The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the township, bears North, 6.32 chs. dist., monumented by an iron post 3 ins. diam. with brass cap mkd.

$$\begin{array}{r} \text{T39N} \\ \text{R3W} \left| \begin{array}{l} \text{S24} \\ \text{S25} \end{array} \right. \left| \begin{array}{l} \text{S19} \\ \text{S30} \end{array} \right. \text{R2W} \\ 1914 \end{array}$$

As this cor. now functions for secs. 24 and 25 only, I remark the brass cap to read

$$\begin{array}{r} \text{T39N} \\ \text{R3W} \left| \begin{array}{l} \text{S24} \\ \text{S25} \end{array} \right. \text{R2W} \\ 1965 \\ 1914 \end{array}$$

Land, gently rolling
Soil, gravelly loam.
Timber, none.
Undergrowth, dense sagebrush.

The point for the 1/4 sec. cor. of sec. 30 is on the W. bdy. of the township at mid-point bet. the closing corners.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

$$\begin{array}{r} \text{T39N} \\ \left| \begin{array}{l} \frac{1}{4} \text{S30} \\ \text{R2W} \end{array} \right. \\ 1965 \end{array}$$

from which

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the W. bdy. of the township, bears North, 6.28 chs. dist., monumented by an iron post 1 inch diam., with brass cap mkd.

$\frac{1}{4}$
S25 | S30
1914

As this cor. now functions for sec. 25 only, I remark the brass cap to read

$\frac{1}{4}$
T39N |
S25 |
R3W |
1965
1914

From the cor. of secs. 19, 20, 29 and 30.

N. $0^{\circ}03'$ W., bet. secs. 19 and 20.

Over gently rolling land.

- 3.40 Wash, 5 lks. wide, 8 ins. deep, drains N. 60° W.
 - 6.70 Bladed right of way for future fence, bears E. and W. for 4.00 chs., thence N. 75° W.
 - 30.90 Track road, bears irregularly E. and W.; desc. gentle N. slope.
 - 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
- Set the iron post 20 ins. in the ground, cap mkd.

T39N R2W
 $\frac{1}{4}$
S19 | S20
1965

Build a mound with stones W. of the cor.

- 40.90 Draw, drains W.
 - 58.50 Track road, bears NE. and SW.
 - 76.10 Track road, bears SE. and N. 60° W.
 - 80.00 Point for the cor. of secs. 17, 18, 19 and 20.
- Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T39N R2W
S18 | S17
S19 | S20
1965

Land, gently rolling.
Soil, gravelly loam.
Timber, none.
Undergrowth, dense sagebrush, scattered cactus.

CHAINS	
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°58' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>
0.12	Center of bladed right of way for future fence line, bears N. and S.
14.40	Track road, bears N. 30° E. and S. 35° W.
39.96	Point for the ¼ sec. cor. of secs. 17 and 20.
	Set the iron post 18 ins. in the ground, cap mkd.
	<p>T39N R2W ¼ $\frac{S17}{S20}$ 1965</p>
	Build a mound with stones N. of the cor.
67.40	Draw, drains N. 30° W.
69.20	Track road, bears N. 20° E. and S. 20° W.
79.10	Track road, bears S. 85° E. and N. 15° W.
79.92	The cor. of secs. 17, 18, 19 and 20.
	<p>Land, gently rolling.</p> <p>Soil, gravelly loam.</p> <p>Timber, none.</p> <p>Undergrowth, dense sagebrush, scattered cactus.</p>
	<hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p>
8.20	Track road, bears SE. and NW. for 2.00 chs., thence N. 30° W.
19.00	Track road, bears S. 40° E. and NW.
24.00	E. rim of draw, bears irregularly N. and SW.
28.10	W. rim of draw, bears N. 70° E. and S. 70° W.
40.00	Point for the ¼ sec. cor. of secs. 18 and 19.
	Set the iron post 18 ins. in the ground, cap mkd.
	<p>T39N R2W ¼ $\frac{S18}{S19}$ 1965</p>
	Build a mound with stones N. of the cor.
63.20	Wash, 5 lks. wide, 1 ft. deep, drains NW.
63.24	W. rim of same draw, bears SE. and NW.
78.55	Intersect the W. bdy. of the township.

CHAINS

Point for the closing corner of secs. 18 and 19.
Set the iron post 18 ins. in the ground, cap mkd.

$$\begin{array}{r} \text{T39N} \\ \text{T39N} \left| \begin{array}{l} \text{S18} \\ \text{S24} \end{array} \right. \begin{array}{l} \text{C} \\ \text{C} \end{array} \\ \text{R3W} \left| \begin{array}{l} \text{S19} \\ \text{R2W} \end{array} \right. \\ 1965 \end{array}$$

from which

The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township bears North, 6.32 chs. dist., monumented by an iron post 3 ins. diam. with brass cap mkd.

$$\begin{array}{r} \text{T39N} \\ \text{R3W} \left| \begin{array}{l} \text{S13} \\ \text{S24} \end{array} \right. \begin{array}{l} \text{S18} \\ \text{S19} \end{array} \right. \text{R2W} \\ 1914 \end{array}$$

As this cor. now functions for secs. 13 and 24 only, I remark the brass cap to read

$$\begin{array}{r} \text{T39N} \\ \text{R3W} \left| \begin{array}{l} \text{S13} \\ \text{S24} \end{array} \right. \begin{array}{l} \\ \end{array} \right. \text{R2W} \\ 1965 \\ 1914 \end{array}$$

Land, gently rolling.
Soil, gravelly loam.
Timber, none.
Undergrowth, dense sagebrush.

The point for the ¼ sec. cor. of sec. 19 is on the W. bdy. of the township at mid-point bet. the closing corners.

Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.

$$\begin{array}{r} \text{T39N} \\ \left| \begin{array}{l} \frac{1}{4} \\ \text{S19} \\ \text{R2W} \end{array} \right. \\ 1965 \end{array}$$

from which

The ¼ sec. cor. of secs. 19 and 24, on the W. bdy. of the township, bears North, 6.32 chs. dist., monumented by an iron post 1 inch diam., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \text{S24} \left| \text{S19} \right. \\ 1914 \end{array}$$

As this cor. now functions for sec. 24 only, I remark the brass cap to read

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

46

46.

CHAINS	
	T39N $\frac{1}{2}$ S24 R3W 1965 1914
	<hr/> From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over gently rolling land.
0.30	Track road, bears S. 75° E. and N. 75° W.
14.00	Wash, 10 lks. wide, 1 ft. deep, drains W.
24.00	Desc. gentle N. slope.
36.00	Desc. along W. slope of a draw.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 17 and 18. Set the iron post 15 ins. in the ground, cap mkd.
	T39N R2W $\frac{1}{2}$ S18 S17 1965
	Build a mound with stones W. of the cor.
44.60	Wash, 5 lks. wide, 1 ft. deep, drains S. 80° W.; asc. S. slope.
50.80	Desc. gentle N. slope.
67.60	Small draw, drains N. 60° W. for 3.00 chs., thence N.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W S 7 S 8 S18 S17 1965
	Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered yellowbrush.
	<hr/> From the cor. of secs. 8, 9, 16 and 17. N. 89°59' W., bet. secs. 8 and 17. Over gently rolling land.
0.10	Old right of way for fence, bears N. and S.
11.50	Track road, bears irregularly SE. and NW.
28.40	Draw, drains N. for 3.00 chs., thence NW.

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
39.96	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p> <p>Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ $\frac{S\ 8}{S17}$ 1965</p>
60.80	<p>Track road, bears S. 30° E. and N. 30° W.</p>
79.92	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered cactus.</p>
<hr/>	
	<p>West, bet. secs. 7 and 18.</p>
	<p>Over gently rolling land.</p>
0.60	<p>Small wash, drains N. 20° W. from S. 20° W.</p>
10.40	<p>Small draw, drains NW.</p>
33.70	<p>Wash, 5 lks. wide, 8 ins. deep, drains N. 30° W. from SW.</p>
37.00	<p>Desc. gentle NW. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ $\frac{S\ 7}{S18}$ 1965</p>
50.50	<p>Draw, drains N. 35° W.</p>
52.20	<p>Spur, slopes N.</p>
53.80	<p>Draw, drains N.</p>
59.50	<p>Draw, drains N. from source 1.00 chain S.</p>
63.20	<p>Head of draw, drains N. 10° E.; asc. gentle E. slope.</p>
71.00	<p>Desc. gentle W. slope.</p>
78.43	<p>Intersect the W. bdy. of the township.</p> <p>Point for the closing corner of secs. 7 and 18.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N S13 $\frac{S\ 7}{S18}$ C R3W R2W 1965</p>

CHAINS

from which

The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the township, bears North, 6.34 chs. dist., monumented by an iron post 3 ins. diam. with brass cap mkd.

$$\begin{array}{ccc} & & \text{T39N} \\ & & \text{S12} \mid \text{S 7} \\ \text{R3W} & & \text{S13} \mid \text{S18} \\ & & \text{1914} \end{array} \quad \text{R2W}$$

As this cor. now functions for secs. 12 and 13 only, I remark the brass cap to read

$$\begin{array}{ccc} & & \text{T39N} \\ & & \text{S12} \mid \\ \text{R3W} & & \text{S13} \mid \\ & & \text{1965} \\ & & \text{1914} \end{array} \quad \text{R2W}$$

Land, gently rolling.
Soil, gravelly loam.
Timber, none.
Undergrowth, dense sagebrush, scattered yellowbrush and cactus.

The point for the $\frac{1}{4}$ sec. cor. of sec. 18 is on the W. bdy. of the township at mid-point bet. the closing corners.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

$$\begin{array}{c} \text{T39N} \\ \mid \\ \frac{1}{4} \\ \mid \\ \text{S18} \\ \mid \\ \text{R2W} \\ \text{1965} \end{array}$$

from which

The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the W. bdy. of the township, bears North, 6.33 chs., dist., monumented by an iron post 1 inch diam., with brass cap mkd.

$$\begin{array}{ccc} & & \frac{1}{4} \\ & & \text{S13} \mid \text{S18} \\ & & \text{1914} \end{array}$$

As this cor. now functions for sec. 13 only, I remark the brass cap to read

$$\begin{array}{ccc} & & \text{T39N} \\ & & \frac{1}{4} \mid \\ & & \text{S13} \mid \\ \text{R3W} & & \mid \\ & & \text{1965} \\ & & \text{1914} \end{array}$$

EOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

CHAINS	
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over gently rolling land.</p>
8.10	Wash, 10 lks. wide, 1 ft. deep, drains NW.
24.70	Track road, bears SE. and N. 55° W.
33.00	Wash, 8 lks. wide, with 3 ft. banks, drains W. for 1.00 chain, thence NW.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ S 7 S 8 1965</p>
56.80	Series of small washes draining NW. for 4.00 chs., thence W.
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W S 6 S 5 S 7 S 8 1965</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered yellowbrush.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°57' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p>
0.48	Fence, bears N. 65° W. and S. 65° E. to bend, thence E.
10.50	Track road, bears SE. and NW.
16.00	Desc. gentle W. slope.
29.30	E. rim of canyon, bears S. 30° E. and N. 70° W.; desc. SW. slope.
37.30	Desc. SW. slope of spur.
39.97	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.</p> <p>Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T39N R2W $\frac{1}{4}$ S 5 S 8 1965</p>

CHAINS	
	Build a mound with stones N. of the cor.
42.30	Wash, 6 lks. wide, 3 ft. deep, drains SW. for 8.00 chs., thence irregularly W.; asc. NE. slope.
45.10	Spur, slopes N.
47.50	Desc. W. slope.
49.40	Wash, 10 lks. wide, 1 ft. deep, drains N. for 4.50 chs., thence W.; asc. NE. slope.
58.80	Top of asc. thence over gently rolling land.
69.40	Rim of draw, bears S. and N. 30° W.
73.60	Wash, 10 lks. wide, 2 ft. deep, drains NW. from S.; asc. NE. slope.
78.50	Rim of same draw, bears SE. and NW.; thence over level land.
79.94	The cor. of secs. 5, 6, 7 and 8.
	Land, rolling and broken. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush, scattered yellowbrush and cactus.
	West, bet. secs. 6 and 7.
	Over gently rolling land.
5.50	Small draw, drains N.
12.00	Desc. broken SW. slope.
21.90	Wash, 13 lks. wide, 1 ft. deep, drains N. from SW.; asc. E. slope.
25.50	Spur, slopes N.
29.00	Draw, drains N. for 2.50 chs. into main draw, thence W.
34.80	Desc. gentle W. slope.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7.
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W ¼ $\frac{S\ 6}{S\ 7}$ 1965
41.30	Draw, drains N. 70° W.
43.40	Spur, slopes N.
45.90	Draw, drains S. 70° W.
47.70	Draw, drains NW.

CHAINS

- 57.00 Desc. gentle W. slope.
- 63.40 Draw, drains N. 30° E. from S. 30° E.; asc. E. slope.
- 75.20 Over nearly level land.
- 78.32 Intersect the W. bdy. of the township.

Point for the closing cor. of secs. 6 and 7.

Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.

	T39N	
S12	S 6	C
R3W	S 7	C
	R2W	
	1965	

from which

The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the township, bears North, 6.34 chs. dist., monumented by an iron post 3 ins. diam., with brass cap mkd.

	T39N	
R3W	R2W	
S 1	S 6	
S12	S 7	
	1914	

As this cor. now functions for secs. 1 and 12 only, I remark the brass cap to read

	T39N	
R3W	R2W	
S 1	S 1	
S12	S 1	
	1965	
	1914	

Land, rolling and broken.
 Soil, gravelly loam.
 Timber, none.
 Undergrowth, dense sagebrush, scattered yellowbrush and cactus.

The point for the ¼ sec. cor. of sec. 7 is on the W. bdy. of the township at mid-point bet. the closing corners.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

	T39N	
	¼ S 7	
	R2W	
	1965	

from which

BOOK 4764

Subdivision, T. 39 N., R. 2 W., Arizona

52

52.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 7 and 12 on the W. bdy. of the township bears North, 6.34 chs. dist., monumented by an iron post 1 inch diam. with brass cap mkd.

$\frac{1}{4}$
S12 | S 7
1914

As this cor. now functions for sec. 12 only, I remark the brass cap to read

T39N
 $\frac{1}{4}$ |
S12 |
R3W |
1965
1914

The point for the $\frac{1}{4}$ sec. cor. of sec. 6 is on the W. bdy. of the township at 40.00 chs. in northing from the closing corner of secs. 6 and 7.

Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.

T39N
| $\frac{1}{4}$ S 6
| R2W
1965

from which

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the W. bdy. of the township, bears North, 6.34 chs. dist., monumented by an iron post 1 inch diam., with brass cap mkd.

$\frac{1}{4}$
S 1 | S 6
1914

As this cor. now functions for sec. 1 only, I remark the brass cap to read

T39N
 $\frac{1}{4}$ |
S 1 |
R3W |
1965
1914

From the cor. of secs. 5, 6, 7 and 8.

N. $0^{\circ}21'$ W., bet. secs. 5 and 6.

Over rolling land, desc. gentle NE. slope.

2.10 S. rim of canyon, bears SE. and N. 25° W.; desc. NE. slope.

10.10 Wash, 8 lks. wide, 3 ft. deep, drains irregularly W. from S. 60° E.; asc. steep S. slope.

CHAINS	
15.00	N. rim of same canyon, bears E. and W.; thence over gently rolling land.
23.60	Track road, bears SE. and N. 60° W.
27.50	Fence, bears S. 71° E. and N. 71° W.
27.60	Track road, parallels fence.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	T39N R2W S 6 S 5 1965
50.50	Head of draw, drains N. for 2.00 chs., thence N. 30° E.
61.00	Spur, slopes N. 80° E.
73.80	Draw, drains irregularly NW.
76.60	Spur, slopes W.
78.90	Wash, 15 lks. wide, 4 ft. banks, drains irregularly NW.; asc. S. slope.
80.14	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township, monumented by an iron post 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the 1954 survey.
	Land, rolling and broken. Soil, gravelly loam. Timber, none. Undergrowth, dense sagebrush.
	<hr/> General Description <hr/>
	Township 39 North, Range 2 West, Gila and Salt River Meridian, Arizona, is in gently rolling country. There is some broken land in the extreme north and west portions. The elevation ranges from about 5,670 feet down to about 4,750 feet above sea level. The general drainage is from the southeast to the northwest.
	There is a moderate growth of juniper and pinon in the southeast portion of the township. A heavy growth of sagebrush dominates the entire township. Some grass was noticed in the bottom of the deeper draws.
	The township is laced with a network of track roads some of which were established by sheepmen.
	Stock grazing is the primary use of this township.
	No mining claims or dwellings were noted in the township.

54

Form 4-680
(June 1963)

BOOK 4764
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Lyman Polacca	Notes
Howard Thomas	Chainman
Jimmy Brown	Flagman
Charles J. Kriz	Cornerman

55

BOOK 4764

CERTIFICATE OF SURVEY

I, Boyd S. Owens, Paul G. Bauer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1964, I have dependently resurveyed a portion of the north boundary, and surveyed the south boundary and subdivisional lines of Township 39 North, Range 2 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 1, 1965 (Date)

Boyd S. Owens (Cadastral Surveyor)

December 1, 1965 (Date)

Paul G. Bauer (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date JAN 11 1966

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the north boundary and survey of the south boundary and subdivisional lines of Township 39 North, Range 2 West, of the Gila and Salt River Meridian in the State of Arizona,

executed by Boyd S. Owens and Paul G. Bauer, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

FEB 11 1966 (Date)

[Signature] (Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in [redacted], is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)