BOOK 4768

Form 4--679 (January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Walter desired and the second		
	SURVEY	
	of the	
	Subdivisional Lines	
	of	
	Township 37 North, Range 6 West	
w		
		
Of the	Gila and Salt River	Meridian
In the State of	Arizona	
	EXECUTED BY	
	Boyd S. Owens, Cadastral Surveyor	
	Paul G. Bauer, Cadastral Surveyor	
Under special instructions d	lated <u>March 2</u> , 19 <u>64</u> , which provid	led for the survey
included under Group Number.	406 W. 1 2 1064	or for the surveys
	dated, approved, 19, 19	
assignment instructions of	, 17	
Surve	ey commenced, 19 65	

May 25

Survey completed _

_, 19 65

INDEX DIAGRAM

To	ownsh	ip3	7 No	rth		, Range		6 West		······································
6	38	5	29	4	23	8	16	2	8	1
38		37		28		-22		15		8
7	36	8	28	9	22	10	15	11	7	12
36		·35		27		21		14		. 6
18	35	17	27	16	21	15	13	14	5	18
34		34		26		20		13		5
19	33	20	25	21	20	22	12	28	4	24
32		32		25		19		11		3
80	31	29	24	28	18	27	11	26	2	25
31	:	30		24		18		10		2
			•							
31	29	82	23	88	17	84	9	85	1	86

(1B

CHAINS

The south boundary, the Ninth Standard Parallel North, was surveyed in 1915 by T. B. Matthews. The north, east and west boundaries were surveyed in 1924 by Hiester and Hunter. A portion of the west boundary was dependently resurveyed in 1964 by B. S. Owens.

The following field notes are those of a survey of the subdivisional lines of Township 37 North, Range 6 West, of the Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 2, 1964.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of Township 37 North, Range 6 West, as computed from triangulation station TRENCH is: Latitude 36°33'23.4" North and Longitude 112°52'47.7 West.

The magnetic declination was found to be 16°45' East.

Survey of the Subdivisional Lines Township 37 North, Range 6 West

Beginning at the standard corner of sections 35 and 36 on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., set mkd. and witnessed as described in the official record of the 1915 survey.

N. $0^{\circ}01'$ W., bet. secs. 35 and 36.

Over rolling land through medium undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set the iron post 16 inches in the ground, mound with stones to top, cap mkd.

T37N R6W 之 S35 | S36 1965

The corner is located on a gentle NW. slope.

54.20 | Small spur, slopes W.

79.50 Four-strand barbed wire fence, bears N. 89°40' E. and S. 89°40' W.

80.00 | Point for the cor. of secs. 25. 26, 35 and 36.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd .

T37N R6W S26 S25 S35 S36 1965

2.

	
CHAINS	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, native grass and scattered greasewood.
	From the corner of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set mkd. and witnessed as described in the official record of the 1924 survey.
	N. 89°55' W., bet. secs. 25 and 36.
	Over nearly level land.
9.90	Unimproved road, bears N. 25° W. and SE. 1.00 chain, thence S. 80° E.
39. 98	Point for the ½ sec. cor. for secs. 25 and 36.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W
	<u>s25</u>
•	⁴ \$36 1965
	1903
	from which
	A four strand barbed wire fence bears South, 25 lks. dist.; fence bears N. 89°43' E. and S. 89°43' W.
	A dry pond bears N. 26°55' W., 18.90 chs. dist.
53.10	Dry wash, 25 1ks. wide, 2 ft. deep, drains N. 25° E.
79.96	The cor. of secs. 25, 26 35 and 36.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grass, scattered greasewood and cactus.
	N. 0°01' W., bet. secs. 25 and 26.
	Over gently rolling land through grama grass and scattered cactus.
1.30	Spur, slopes W.
6.00	Dry wash drains NE.
12.60	Spur, slopes E.
40.00	Point for the ½ sec. cor. of secs. 25 and 26.
	Set the iron post 22 ins. in the ground, in a collar of stones to top, cap mkd.
	T37N R6W
,	\$26 \$25 1965

CHAINS		
	Raise a mound of stone W. of the cor.	
	The corner falls on a gentle SW. slope.	
42.80	Small draw, drains E.	
53.00	Spur, slopes S. 15° E.	
72.00	Unimproved road, bears N. 30° W. and SE.	
80.00	Point for the corner of secs. 23, 24, 25 and 26.	
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
	T37N R6W <u>S23 S24</u> S26 S25 1965	
	Raise a mound of stone W. of the cor.	
:	The cor. is located on a grassy S. slope.	
	Land, rolling. Soil, sandy loam and rocky. No timber; undergrowth, medium grass, scattered greasewood and cactus.	
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.	
-	from which	
	Triangulation Station TRENCH bears N. 79°58' E., 30.87 chs. dist., monumented by a standard disk set 6 ins. below the surface of the ground.	
	N. 89°54' W., bet. secs. 24 and 25.	
	Over gently rolling land.	
19.50	Low ridge, bears N. and S.	
3 2.90	Draw, drains N.	
40.00	Point for the 4 sec. cor. of secs. 24 and 25.	
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.	
	T37N R6W 2 S24 S25 1965	
	The corner is located on a small spur sloping SE.	
41.50	Low ridge, bears N. and S.	
50.20	Low ridge, bears N. and S.	
64.80	Draw, drains N.	

·	4.
CHAINS	
71.00	Small spur projects N.
71.80	Dry wash, 20 1ks. wide, 2 ft. deep, drains N. 70° E.
80.00	The corner of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, rocky, sandy loam. Timber, scattered cedars. Undergrowth, grama grass, scattered greasewood and cactus.
	N. 0°01' W., bet. secs. 23 and 24.
	Over rolling grass land through scattered timber.
6.00	Spur, slopes SW.
15.70	Dry wash, drains N. 40° E.
37.70	Top of rocky ridge, bears S. 80° W. and N. 80° E.
	Desc. N. slope.
40.00	Point for the ½ sec. cor. of secs. 23 and 24.
	Set the iron post 10 ins. in the ground, mound with stones to top cap mkd.
	T37N R6W ₹ S23 S24 1965
46.20	Draw, drains W.
49.00	Spur, slopes NW.
63.00	Spur, slopes E.
64.90	Draw, drains SE.
72.90	Low spur slopes E.
79.90	Four strand barbed wire fence, bears E. and W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set the iron post 21 ins. in the ground, in a collar of stones, cap mkd.
	T37N R6W S14 S13 S23 S24 1965
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky and sandy loam. Timber, scattered cedar. Undergrowth, grama grass, scattered greasewood and cactus.

CHAINS	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey. The cor. is located in the cor. of a fence; fences bear South, and N. 89°57' W. N. 89°53' W., bet. secs. 13 and 24.
	Over rolling land through medium timber.
2.00	Rocky spur, slopes N.
11.40	Dry wash, 20 1ks. wide, 2 ft. deep, drains N. 10° W.
18.20	Spur, slopes S.
21.10	Draw, drains S.
34.10	Spur, slopes SE.
3 7.75	Draw, drains S.
40.03	Point for the ½ sec. cor. of secs. 13 and 24.
	Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W ¹ / ₄ S13 S24 1965
	Corner falls on SE. slope of rocky spur.
40.30	Spur, projects S. 15° E.
44.80	Dry wash, drains SE.
80.06	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling and broken. Soil, rocky and sandy loam. Timber, medium cedar. Undergrowth, grama grass and scattered greasewood and cactus.
	N. 0°01' W., bet. secs. 13 and 14.
	Over rolling land through medium timber and undergrowth.
3.00	Spur, slopes W.
11.80	Draw, drains N. 40° E.
16.20	Small spur, slopes W. 1.00 chain to saddle.
29.40	Draw, drains NE.
33.50	Spur, slopes E.
35.30	Draw, drains SE.
39.80	Spur, slopes W.
40.00	Point for the % sec. cor. of secs. 13 and 14.

CHAINS	
	Set the iron post 9 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W
	S14 S13 1965
	from which
	Heaton Reservoir, bears S. 87°47' W., 34.50 chs. dist.
43.00	Spur, slopes NW.
47.30	Draw, drains NW.
50.50	Spur, slopes W.
63.60	Wash, 20 1ks. wide, 5 ft. deep, drains N. 80° E.
67.70	N. rim of canyon, bears N. 65° E. and S. 65° W.
69.30	Draw, drains NE.
74.30	Draw, drains NE.
76.70	Spur, slopes E.
79 .3 0	Draw, drains SE.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set the iron post 20 ins. in the ground, in a collar of stones, cap mkd.
	T37N R6W <u>S11 S12</u> <u>S14 S13</u> 1965
	Raise a mound of stone W. of the cor. Land, rolling and broken. Soil, rocky limestone. Timber, medium cedar.
	Undergrowth, grama grass and scattered cactus and greasewood.
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.
	N. 89°52' W., bet. secs. 12 and 13.
	Over rolling and broken land, through scattered timber and medium undergrowth.
1 3. 90	Wash, 10 1ks. wide, 2 ft. deep, drains NW.
20.50	Wide draw, drains N. 10° W.

	CHAINS	
	36.90	Draw, drains N.
	38.20	Low ridge, bears N. and S.
	40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.
		Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	·	T37N R6W
		1 S12 S13
		1965
	,	Cor. falls on a W. slope.
	46.50	Wide draw, drains NE.
	55.40	Low ridge, bears N. and S.
	63.90	Wash, 20 1ks. wide, $4\frac{1}{2}$ ft. deep, drains N. 15° E.
	80.16	The cor. of secs. 11, 12, 13 and 14.
		Land, rolling and broken. Soil, rocky and sandy loam. Timber, medium cedar.
		Undergrowth, grama grass, scattered greasewood and cactus.
	-	N. 0°01' W. bet. secs. 11 and 12.
		Over rolling land through scattered timber and medium undergrowth.
	4.80	Low ridge, bears NE. and SW.
	5.30	Desc. over N. slope.
	21.30	Enter open, flat land bearing E. and W.
	40.00	Point for the ½ sec. cor. of secs. 11 and 12.
		Set the iron post 22 ins. in the ground, cap mkd.
		T37N R6W
		\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
		Raise a mound of stone W. of the cor.
	49.65	Center of unimproved road bearing E. and W.
	50.00	Wash, 15 1ks. wide, 1 ft. deep, drains E.
	66.00	Small ridge, bears NW. and SE.
	77.40	Spur, slopes SE.
ļ	80.00	Point for the cor. of secs. 1, 2, 11 and 12.
		Set the iron post 22 ins. in the ground, in a collar of stones, cap mkd.

\mathcal{O}
7
v

	Subdivision, T. 37 N., R. 6 W., Arizona 8.
CHAINS	
	T37N R6W
	<u>S 2 S 1</u> S11 S12
	1965
	Raise a mound of stone W. of the cor.
	Land, gently rolling.
	Soil, sandy loam.
	Timber, medium to scattered cedar. Undergrowth, grama grass and scattered cactus and
	greasewood.
	To the F him of
	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.
	N. 89°51' W., bet. secs. 1 and 12.
	Over rolling land covered with grass.
1.30	Draw, near head, drains S.
40.10	Point for the $\frac{1}{2}$ sec. cor. of secs. 1 and 12.
	Set the iron post 23 ins. in the ground, cap mkd.
	T37N R6W
	½ S 1 S12
	1965
	Raise a mound of stone N. of the cor.
62.40	Low ridge bears N. and S.
80.20	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling.
	Soil, sandy loam. No timber; undergrowth, grama grass and scattered
	greasewood.
	N. 0°11' E., bet. secs. 1 and 2.
	Over gently rolling land through medium undergrowth.
14.00	Spur, slopes W.
24.70	Wash, 10 1ks. wide, 1 ft. deep, drains S. 70° E.
28.50	Low spur, slopes W.
40.00	Point for the ½ sec. cor. of secs. 1 and 2.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W
	S 2 S 1 1965
	1905

_					
	CHAINS 79.81	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.			
		The cor. is located 2 lks. south of a fence cor.; fences bear S. 89°55' E., S. 89°50' W., and N.			
		Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass and scattered greasewood.			
		From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1915 survey.			
		N. 0°01' W., bet. secs. 34 and 35.			
		Over rolling land, through medium timber and undergrowth.			
	5.60	Spur, slopes E.			
	10.60	Wash, 10 1ks. wide, 1 ft. deep, drains SE.			
	16.60	Small ridge, bears N. 10° E. and S. 10° W.			
	24.30	Small draw, drains N. 75° W.			
	28.00	Spur, slopes W.			
	32.10	Draw, drains NW.			
	36.00	Spur, slopes W.			
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.			
		Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.			
		T37N R6W			
		834 S35 1965			
		Cor. falls on N. slope.			
	44.70	Wash, 30 1ks. wide, 1 ft. deep, drains NE.			
	47.90	Wash, 10 1ks. wide, 1 ft. deep, drains NE.			
	50.00	Spur, slopes E.			
	55.80	Wash, 30 1ks. wide, 1 ft. deep, drains NW.			
	61.00	Spur, slopes W.			
	64.20	Wash, 20 1ks. wide, 5 ft. deep, drains N. 80° E.			
	70.70	Wash, 20 1ks. wide, 5 ft. deep, drains N. 10° W.			
	78.85	Four strand barbed wire fence, bears S. 89°30' W. and N. 89°30' E.			
	,				

•	
	,,
	1/

CHAINS	
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post over an "X" chiseled in solid rock, mound with stones to top, cap mkd.
	T37N R6W
	<u>S27 S26</u> S34 S35
	1965
	Cor. falls on a N. slope.
	Land, rolling. Soil, rocky cinder stone first ½ mile, sandy loam on remainder.
	Timber, medium cedars. Undergrowth, grama grass, scattered greasewood and cactus.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°55' W., bet. secs. 26 and 35.
	Over rolling land through scattered timber and grease-wood.
1.20	Wash, 5 1ks. wide, 1 ft. deep, drains N.
16.10	Spur, slopes S.
29.50	Wash, 10 1ks. wide, 1 ft. deep, drains N. 60° W.
39.00	Draw, drains N.
39.94	Point for the ½ sec. cor. of secs. 26 and 35.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W
	½ <u>S26</u> S35
	1965
	Cor. falls on an E. slope.
41.00	Spur, slopes NW.
45.60	Small draw, drains NW.
51.50	Spur, slopes N.
56.30	Spur, slopes NW.
60.90	Draw, drains NW.
79.88	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling. Soil, sandy loam. Timber, medium and scattered cedar. Undergrowth, grass, greasewood and cactus.

		11.	
CI	HAINS		
		N. 0°01' W., bet. secs. 26 and 27.	
		Over rolling land through medium timber.	
12	2.70	Wash, 20 1ks. wide, 5 ft. deep, drains S. 80° E.	
17	7.80	Spur, slopes S. 60° E.	
27	7.10	Draw, drains N. 70° E.	
39	9.30	Spur, slopes SW.; leave timber, desc. over rolling N. slope.	
40	0.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.	
		Set the iron post 16 ins. in the ground, in a collar of stones, cap mkd.	
		T37N R6W	
		\$27 S26 1965	
		Raise a mound of stone W. of the cor.	
48	3.00	Low ridge, bears NE. and SW.	
55	5.80	Enter nearly level land.	
80	0.00	Point for the cor. of secs. 22, 23, 26 and 27.	
		Set the iron post 19 ins. in the ground, in a collar of stones, cap mkd.	
		T37N R6W <u>S22 S23</u> <u>S27 S26</u> 1965	
		Raise a mound of stones W. of the cor.	
		Land, rolling first ½ mile and nearly level second ½ mile. Soil, rocky and sandy loam. Timber, medium cedar first ½ mile. Undergrowth, grama grass and scattered greasewood and cactus.	
		From the cor. of secs. 23, 24, 25 and 26.	
		N. 89°56' W., bet. secs. 23 and 26.	
		Over rolling land through medium undergrowth.	
		Asc. gentle E. slope.	
	3.20	Unimproved road, bears N. 10° W. and S. 30° E.	
24	4.40	Small spur, slopes N.; enter moderate timber.	
39	9.94	Point for the ½ sec. cor. of secs. 23 and 26.	
		Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.	
		T37N R6W 1/4 S23	

12

CHAINS	Cor. falls on a NE. slope.
43.90	Spur, projects N.; desc. over W. slope.
45.90	Wash, 10 1ks. wide, 1 ft. deep, drains S. 30° W.
48.40	Wash, 10 1ks. wide, 1 ft. deep, drains NW.
51.30	Wash, 10 1ks. wide, 1 ft. deep, drains S. 40° W.
53.00	Spur, slopes SW.
55.00	Wash, 10 lks. wide, 1 ft. deep, drains NW.; enter open flat and leave timber.
72.30	Drainage ditch, man made, drains N. 10° W.
79.88	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling on E. 60° chs., nearly level on remainder. Soil, rocky and sandy loam. Timber, medium juniper east ½ mile. Undergrowth, grama grass, yellow brush, cactus and greasewood.
	N. 0°01' W., bet. secs. 22 and 23.
	Over nearly level land covered with grass and scattered sagebrush and greasewood.
18.20	Wash, 10 1ks. wide, 1 ft. deep, drains N. 35° E.
20.90	Wash, 30 1ks. wide, 1 ft. deep, drains N. 40° E.
26.20	Unimproved road, bears NE. and SW.
37.30	Unimproved road, bears E. and W.
40.00	Point for the ½ sec. cor. of secs. 22 and 23.
	Set the iron post 19 ins. in the ground, in a collar of stones, cap mkd.
	T37N R6W
	S22 S23 1965
	from which
	The SW. corner of a cabin 12 ft. wide and 16 ft. long, bears S. 73°15' E., 5.62 chs. dist. Cabin is set with 12-ft. sides facing N. and S.
	The center of a dike 4 chs. long, bet. the two ponds of Earl Reservoir, bears S. 47°45' E., 10.00 chs. dist.
	Cor. falls on a SE. slope.
	Raise a mound of stone W. of the cor.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W <u>S15 S14</u> S22 S23 1965

~

			13.
	CHAINS	from which	
		A fence cor. bears S. 86° E., 1.34 chs. dist.; fences bear E. and NW.	
		Cor. falls on a gentle NW. slope.	
		Land, nearly level. Soil, sandy loam. No timber; undergrowth, grass, scattered greasewood and sagebrush.	
		From the cor. of secs. 13, 14, 23 and 24.	
		N. 89°58' W., bet. secs. 14 and 23.	
		Over gently rolling land through scattered juniper.	
	27.50	Leave scattered juniper.	
	31.40	Fence, bears N., and S. 10 1ks. dist. to fence bearing E. and W.	
	39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.	
		Set the iron post 22 ins. in the ground, cap mkd.	
		T37N R6W	
		$\frac{1}{4} \frac{\text{S14}}{\text{S23}}$	
		1965	
		The cor. is located 8 lks. north of a fence bearing E. and W.	
	60.20	Unimproved road, bears N. and S.	
	78.70	Fence, bears NW., and SE. 10 1ks., thence E.	
	79.86	The cor. of secs. 14, 15, 22 and 23.	
		Land, rolling. Soil, gravelly clay loam. Timber, scrub juniper on E. 20 chs. Undergrowth, greasewood, yellow brush, cactus and grass.	
		N. 0°01' W., bet. secs. 14 and 15.	
		Over nearly level land covered with grass and scattered greasewood and sagebrush.	
	1.25	Four strand barbed wire fence, bears NW. and SE.	
	11.60	Spur, slopes N. 20° E.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.	
		Set the iron post 18 ins. in the ground, in a collar of stones, cap mkd.	
		T37N R6W	
		\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
		1965	
- 1	ı		

	Subdivision, T. 3/ N., R. 6 W., Arizona
CHAINS	
	Raise a mound of stone W. of the cor.
52.00	Unimproved road, bears S. 75° E. and N. 60° W.
60.90	Wash, 10 1ks. wide, 2 ft. deep, drains E.
78.00	Unimproved road, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set the iron post 19 ins. in the ground, in a collar of stones, cap mkd.
	T37N R6W S10 S11 S15 S14 1965
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, scattered greasewood and sagebrush.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°59' W., bet. secs. 11 and 14.
	Over rolling land through scattered juniper.
	Asc. along SE. slope.
4.00	Low ridge, bears NE. and SW.
22.60	Small draw, drains N.
31.00	Small draw, 2.00 chs. from head, drains N. 40° E.
39.93	Point for the ½ sec. cor. of secs. 11 and 14.
	Set the iron post 4 ins. in the ground to bedrock, mound with stones to top, cap mkd.
	T37N R6W 2 S11 514 1965
51.90	Graded road, bears N., and S. for 1.00 chain, thence curves W.
58.20	Fence, bears N. 10° W. and S. 10° E.
65.90	Track road, bears N. and S.
76.00	Track road, bears NE. and SW.
79.86	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling. Soil, gravelly clay loam. Timber, scattered juniper on E. 1/2 mile. Undergrowth, grass and scattered greasewood.

	15.	
CHAINS		
	N. 0°01' W., bet. secs. 10 and 11.	
	Over nearly level land covered with grass and scattered greasewood.	
29.10	Unimproved road, bears S. 30° E. and N. 40° W.	
40.00	Point for the ½ sec. cor. of secs. 10 and 11.	
	Set the iron post 19 ins. in the ground, in a collar of stones, cap mkd.	
	T37N R6W	
	\$10 \$11 1965	
	from which	
	A fence cor. bears N. 9°11' E., 8.74 chs. dist.; fences bear N. 1°20' W. and S. 22°50' E.	
	Raise a mound of stone W. of the cor.	
48.70	Enter rolling land and scattered timber.	
59.70	Spur, slopes N. 35° W.	
67.70	Draw, drains S. 80° W.	
80.00	Point for the cor. of secs. 2, 3, 10 and 11.	
	Set the iron post 16 ins. in the ground, in a collar of stones, cap mkd.	
	T37N R6W S 3 S 2 S10 S11 1965	
	from which	
	A four strand barbed wire fence bears E. 1.00 chain dist.; fence bears N. and S.	
	Land, S. 1/2 mile level, N. 1/2 mile rolling.	
	Soil, sandy loam and rocky. Timber, S. 1/2 mile none, N. 1/2 mile scattered juniper. Undergrowth, grama grass and scattered greasewood, cactus and sagebrush.	
	From the cor. of secs. 1, 2, 11 and 12.	
	S. 89°59' W., bet. secs. 2 and 11.	
	Over rolling land through scattered timber.	
3.50	Low rise, bears N. 20° W. and S. 40° W.	
7.90	Draw, drains N.	
11.50	Small spur, slopes S.	
21.00	Spur, slopes S.	

16		56561V151511, 1. 57 N., R. 6 W., Al 12616	16.
*	CHAINS		
	39.92	Point for the ½ sec. cor. of secs. 2 and 11.	
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
		T37N_R6W	
		$\begin{array}{c} \frac{1}{4} \frac{\text{S 2}}{\text{S11}} \\ 1965 \end{array}$	
	43.00	Spur, slopes N.	
	49.30	Draw, drains NE.	
	78.84	Four strand barbed wire fence, bears N. 0°30' W. and S. 0°30' E.	
	79.84	The cor. of secs. 2, 3, 10 and 11.	
		Land, rolling. Soil, sandy clay loam. Timber, scattered juniper. Undergrowth, grama grass, yellowbrush and scattered greasewood.	
		N. 0°05' E., bet. secs. 2 and 3.	
		Over rolling land through scattered timber, mostly dead, and medium undergrowth.	
	18.90	Spur, slopes SE.	
	35.60	Spur, slopes NW.	
	39.50	Shallow draw, drains NW.	
	40.00	Point for the 1/2 sec. cor. of secs. 2 and 3.	
		Set the iron post 18 ins. in the ground, in a collar of stones, cap mkd.	
		T37N R6W	
		s 3 s 2 1965	
	į	from which	
		The NE. cor. of a square corral bears S. 71°30' W., 28.30 chs. dist.	
		Raise a mound of stone W. of the cor.	
	42.80	Spur, slopes NW.	
	50.50	Spur, slopes W.	
	68.80	Wash, 10 1ks. wide, 2 ft. deep, drains N. 20° W.	
	72.70	Fence cor. bears East 6 lks. dist.; fences bear N. 0°30' W., S. 0°30' E. and W.	
	77.00	Wash, 5 1ks. wide, 2 ft. deep, drains N. 20° E.	

_		
	CHAINS 79.93	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey. The cor. is located at the cor. of a fence; fences bear E. and S. 0°30' E. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass and scattered greasewood.
		From the standard corner of the secs. 33 and 34 on the S. bdy. of the Tp., monumented by an iron post 3 ins. in diam., set, mkd. and witnessed as described in the official record of the 1915 survey.
		N. 0°02' W., bet. secs. 33 and 34.
		Over rolling land through scattered timber.
		Asc. along W. side of Heaton Knolls.
	8.00	Spur, slopes W.
	14.90	Draw, drains S. 75° W.
	15.70	Spur, slopes N. 80° W.
	19.30	Draw, drains S. 80° W.
	22.00	Spur, slopes W.
	25.30	Draw, drains NW.
	28.70	Spur, slopes NW.; leave timber, desc. over NW. slope.
	40.00	Point for the ½ sec. cor. of secs. 33 and 34.
		Set the iron post 20 ins. in the ground, cap mkd.
		T37N R6W \$33 S34 1965
		Raise a mound of stone W. of the cor.
		Continue over gently rolling land.
	77.50	Four strand barbed wire fence, bears N. 88°40' E. and S. 88°40' W.
	80.00	Point for the cor. of secs. 27, 28, 33 and 34.
		Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
		T37N R6W <u>S28 S27</u> S33 S34 1965
		The cor. is located on a gentle NE. slope.
		Į.

CHAINS	Land, rolling. Soil, rocky cinder stone. Timber, scattered juniper on S. ½ mile. Undergrowth, grama grass, scattered Brigham tea and greasewood.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89°53' W., bet. secs. 27 and 34.
	Over rolling land through medium timber.
1.30	Wash, 20 1ks. wide, 5 ft. deep, drains N. 10° W.
8.80	Draw, drains N.
26.60	Spur, slopes SE.
30.60	Spur, slopes N. 25° E.
36.00	Small draw, drains irregularly N.
38,40	Small draw, drains N.; asc. over E. slope.
40.02	Point for the 1/2 sec. cor. of secs. 27 and 34.
	Set an iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W 2 S27 S34 1965
	The cor. is located on a spur sloping N.
46.50	Spur, slopes N.
61.30	Spur, slopes S.
79.20	Wash, 10 1ks. wide, 1 ft. deep, drains N.
80.04	The cor. of secs. 27, 28, 33 and 34.
	Land, rolling. Soil, sandy loam and rocky. Timber, medium to scattered juniper. Undergrowth, grama grass, scattered sage, greasewood and cactus.
,	N. 0°02' W. bet. secs. 27 and 28.
	Over nearly level land covered with grass, sage and greasewood.
2.40	Draw, drains NW.
4.10	Draw, drains NW.
5.90	Wash, 20 lks. wide, 1 ft. deep, drains N. 40° E.; track road bears irregularly NE. and SW.
	Clack load bears lilegularly Ma. and bu.

1	0
	9

		19.
CHAINS		
21.50	Same wash, drains N. 70° E.	
40.00	Point for the 1/2 sec. cor. of secs. 27 and 28.	
	Set the iron post 21 ins. in the ground, cap mkd.	
	T37N R6W	
	\$28 \$27 1965	
	The cor. is located on a S. slope.	
	Raise a mound of stone W. of the cor.	
73.80	Unimproved road, bears N. 80° E. and S. 80° W.	
80.00	Point for the cor. of secs. 21, 22, 27 and 28.	
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.	
	T37N R6W	
	<u>\$21</u> <u>\$22</u> <u>\$28</u> <u>\$27</u>	
	1965	
	The cor. is located on a gentle SE. slope.	
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sagebrush,	
	greasewood and yellowbush.	_
	From the cor. of secs. 22, 23, 26 and 27.	
	N. 89°53' W., bet. secs. 22 and 27.	
	Over nearly level land covered with grass, sage, and cactus.	
17.10	Wash, 15 1ks. wide, 5 ft. deep, drains N. 15° E.	
23.00	Unimproved road, bears N. 10° E. and S. 10° W.	
40.01	Point for the 1/4 sec. cor. of secs. 22 and 27.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T37N R6W	
	½ <u>\$22</u> \$27	
	1965	
	Raise a mound of stone N. of the cor.	
65.40	Unimproved road, bears NE. and SW.	
80.02	The cor. of secs. 21, 22, 27 and 28.	
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, greasewood and cactus.	
		-

Subdivision, T. 37 N., R. 6 W., Arizona

N. 0°02' W., bet. secs. 21 and 22. Over nearly level land, covered with sage, greasewood and cactus. 40.00 Point for the k sec. cor. of secs. 21 and 22. Set the iron post 7 ins. in the ground, mound with stones to top, cap mkd. T37N R6W \$21[\$22 1965 The cor. is located on a NE. slope. Wide draw, drains NE. Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W \$16[\$15 \$15 \$21 \$22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. 40.03 Point for the k sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W \$\frac{1}{852}\$\frac{552}{852}\$\frac{1965}{852}\$ Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere greasewood.		
Over nearly level land, covered with sage, greasewood and cactus. 40.00 Point for the \$\frac{1}{2}\$ sec. cor. of secs. 21 and 22. Set the iron post 7 ins. in the ground, mound with stones to top, cap mkd. T37N R6W \$21[\$22\$ \$1965 The cor. is located on a NE. slope. Wide draw, drains NE. Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. \$16[\$15\$ \$21[\$22\$ \$2965 Raise a mound of stone W. of the cor. Land, nearly level. \$30i1, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. 40.03 Point for the \$\frac{1}{2}\$ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. \$315\$ \$822\$ \$1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling, S011, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattered.	CHAINS	N 08021 II hat are 21 and 22
and cactus. Point for the k sec. cor. of secs. 21 and 22. Set the iron post 7 ins. in the ground, mound with stones to top, cap mkd. T37N R6W S21[S22 1965 The cor. is located on a NE. slope. Wide draw, drains NE. Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W S16[S15 S21]S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. 40.03 Point for the k sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W k S15 S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
Set the iron post 7 ins. in the ground, mound with stones to top, cap mkd. T37N R6N \$21 \$22 \$1965 The cor. is located on a NE. slope. Wide draw, drains NE. 80.00 Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W \$16 \$15 \$221 \$1922 \$1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. 40.03 Point for the \$\frac{1}{2}\$ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W \$\frac{1}{3}\$ \frac{15}{322}\$ \frac{1965}{1965} Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling, Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
stones to top, cap mkd. T37N R6W \$21 \$22 \ 1965 The cor. is located on a NE. slope. Wide draw, drains NE. Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W \$16 \$15 \ \$21 \$322 \ 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ \$15 \ 522 \ 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere	40.00	Point for the ½ sec. cor. of secs. 21 and 22.
S21 S22 1965 The cor. is located on a NE. slope. Wide draw, drains NE. 80.00 Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W S16 S15 S21 S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15 S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
The cor. is located on a NE. slope. 56.00 Wide draw, drains NE. 80.00 Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W S16 S15 S21 S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. Point for the & sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W & \$115 / S22 / 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		T37N R6W
The cor. is located on a NE. slope. Wide draw, drains NE. Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W S16 S15 S21 S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15 S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		•
Wide draw, drains NE. Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W S16 S15 S21 S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
80.00 Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W S16 S15 S21 S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
Set the iron post 22 ins. in the ground, cap mkd. T37N R6W S16 S15 S21 S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15 S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere	56.00	Wide draw, drains NE.
T37N R6W S16 S15 S21 S22 1965 Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere	80.00	Point for the cor. of secs. 15, 16, 21 and 22.
Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Set the iron post 22 ins. in the ground, cap mkd.
Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		· •
Raise a mound of stone W. of the cor. Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. 20.70 Track road, bears N. and S. Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		S21 S22
Land, nearly level. Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush, scattered greasewood and cactus. From the cor. of secs. 14, 15, 22 and 23. N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ \$\frac{\$\frac{515}{\$\frac{522}{\$\frac{1965}{\$\frac{5}{\$\frac{10}{\$\frac{5}{\$\frac{10}{\$\frac{5}{\$\frac{10}{\$\frac{5}{		
N. 89°53' W., bet. secs. 15 and 22. Over gently rolling land. Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Soil, sandy loam. No timber; undergrowth, grama grass, sage, yellowbrush,
Over gently rolling land. 20.70 Track road, bears N. and S. 40.03 Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15 ½ S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		From the cor. of secs. 14, 15, 22 and 23.
Track road, bears N. and S. Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		N. 89°53' W., bet. secs. 15 and 22.
Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15 322 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Over gently rolling land.
Set the iron post 22 ins. in the ground, cap mkd. T37N R6W 1/4 S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
T37N R6W 1 S15 2 S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. 80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere	20.70	Track road, bears N. and S.
Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		
Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Point for the ½ sec. cor. of secs. 15 and 22.
Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Point for the 2 sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd.
Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W
80.06 The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. $\frac{\text{T37N R6W}}{\frac{1}{4}} = \frac{\text{S15}}{\text{S22}}$
Land, rolling. Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd.
Soil, rocky clay loam. No timber; undergrowth, grass, yellowbrush and scattere		Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd.
No timber; undergrowth, grass, yellowbrush and scattere	40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd.
	40.03	Point for the ½ sec. cor. of secs. 15 and 22. Set the iron post 22 ins. in the ground, cap mkd. T37N R6W ½ S15/S22 1965 Raise a mound of stone N. of the cor. Continue over rolling land. The cor. of secs. 15, 16, 21 and 22. Land, rolling.

 CHAINS	N. 0°02' W., bet. secs. 15 and 16.
	Over nearly level land, covered with grass, sage, yellowbrush, scattered greasewood and cactus.
40.00	Point for the ½ sec. cor. of secs. 15 and 16.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W
	S16 S15 1965
56.40	Unimproved road, bears N. 80° E. and S. 80° W.
66.80	Unimproved road, bears N. 80° E. and S. 80° W.
79.75	Four strand barbed wire fence, bears E. and W.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W
	<u>S 9 S10</u> S16 S15
	1965
	from which
	The cor. of a four strand barbed wire fence bears S. 76°32' E., 1.46 chs. dist.; fences bear W. and SE.
	Raise a mound of stone W. of the cor.
	Land, level. Soil, sandy loam.
	No timber; undergrowth, grama grass, sage, yellowbrush and scattered greasewood and cactus.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89°54' W., bet. secs. 10 and 15.
	Over gently rolling land.
40.05	Point for the $\frac{1}{2}$ sec. cor. of secs. 10 and 15.
	Set the iron post 20 ins. in the ground, cap mkd.
	T37N R6W
	½ <u>S10</u> S15
	1965
	Raise a mound of stone N. of the cor.
	Thence over nearly level land.
80.10	The cor. of secs. 9, 10, 15 and 16.

22	Subdivision, T. 3/ N., R. 6 W., Arizona 22
CHAINS	Land, nearly level. Soil, clay and rocky. No timber; undergrowth, grass, yellowbrush, cactus and sagebrush.
	N. 0°02' W., bet. secs. 9 and 10.
	Over nearly level land covered with grass, yellowbrush and scattered greasewood.
40.00	Point for the ½ sec. cor. of secs. 9 and 10.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W
	s 9 s10 1965
55.00	Low ridge, bears E. and W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 22 ins. in the ground cap mkd.
	T37N R6W <u>S 4 S 3</u> S 9 S10 1965
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, sandy and clay loam. No timber; undergrowth, grama grass, yellowbrush and greasewood.
	From the cor. of secs. 2, 3 10 and 11.
	N. 89°51' W., bet. secs. 3 and 10.
	Over gently rolling land covered with grass yellowbrush and scattered greasewood.
5.60	Spur, slopes S. 25° E.
12.20	Unimproved road, bears N. and S.
27.75	Wash, 5 1ks. wide, 1 ft. deep, drains N.
32.50	Unimproved road, bears N. and S. 10° E.
32.90	Unimproved road, bears N. 30° W. and S. 40° E.
40.05	Point for the 2 sec. cor. of secs. 3 and 10.
	Set the iron post 18 ins. in the ground, cap mkd.
	T37N R6W \[\frac{S}{4} \frac{S}{S10} \\ 1965

CHAINS		
	Raise a mound of stone N. of the cor.	
71.60	Unimproved road, bears NW. and SE.	
80.10	The cor. of secs. 3, 4, 9 and 10.	
	Land, nearly level. Soil sandy clay loam. No timber; undergrowth, grama grass yellowbrush sage and greasewood.	
	N. 0°10' E., bet. secs. 3 and 4.	
	Over level land covered with grass yellowbrush and scattered greasewood.	
4.30	Wash, 5 lks. wide 1 ft. deep drains E.	
36.00	Draw, drains E.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.	
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
:	T37N_R6W	
	S 4 S 3 1965	
52.10	Four strand barbed wire fence, bears S. 89°05' W., and N. 89°05' E. 5 lks. to fence bearing N. 0°04' E. and S. 0°04' W.	
72.54	Fence cor. bears E. 1 link dist., fences bear N. 0°04' E., S. 0°04' W., and E.	
79.78	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., monumented by an iron post 2 ins. in diam. set, mkd. and witnessed as described in the official record of the 1924 survey.	
	The cor. is located in a fence line bearing N. 0°04' E. and S. 0°04' W.	
	Land, level. Soil, sandy clay loam. Timber, scattered dead juniper. Undergrowth, grama grass yellowbrush and scattered greasewood.	
	From the standard cor. of secs. 32 and 33 on the S. bdy. of the Tp., monumented by an iron post 3 ins. in diam., set, mkd. and witnessed as described in the official record of the 1915 survey.	
	N. 0°03' W., bet. secs. 32 and 33.	
	Over nearly level land, through scattered timber and medium undergrowth.	
0.85	Unimproved road, bears NE. and SW.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.	

24		24.
	CHAINS	Set the iron post 13 ins. in the ground, mound with stones to top, cap mkd.
		T37N_R6W
		\$32 \$33 1965
	79.95	Four strand barbed wire fence, bears N. 89°10' W. and S. 89°10' E.
	80.00	Point for the cor. of secs. 28, 29 32 and 33.
		Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
		T37N R6W <u>S29 S28</u> S32 S33 1965
		Land, nearly level. Soil, sandy clay loam. Timber, scattered juniper on S. ½ mile. Undergrowth, grama grass, yellowbrush and scattered greasewood.
		From the cor. of secs. 27, 28, 33 and 34.
		N. 89°57' W., bet. secs. 28 and 33.
		Over nearly level land covered with grass yellowbrush and scattered greasewood.
	10.70	Unimproved road, bears N. 60° E. and SW.
	12.80	Wash, 30 1ks. wide 1 ft. deep, drains N. 60° E.
	16.90	Spur slopes SW.
	3 9.98	Point for the ½ sec. cor. of secs. 28 and 33.
		Set the iron post 20 ins. in the ground, cap mkd.
		T37N R6W
		Raise a mound of stone N. of the cor.
		The cor. is located on level land 70 lks. N. of an E-W fence line.
	79.96	The cor. of secs. 28, 29, 32 and 33.
·		Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass yellowbrush and scattered greasewood.
		N. 0°03' W., bet. secs. 28 and 29.
		Over nearly level land covered with grass, yellowbrush and scattered greasewood.

		23.	
	CHAINS		
	32.00	Low ridge, bears E. and W.	
	40.00	Point for the 4 sec. cor. of secs. 28 and 29.	
		Set the iron post 7 ins. in the ground, mound with stones to top, cap mkd.	
		T37N R6W	
		S29 S28	
		1965	
	52.00	Unimproved road, bears NE. and S. 70° W.	
	76.80	Spur, slopes NE.	
	80.00	Point for the cor. of secs. 20, 21 28 and 29.	
		Set the iron post 23 ins. in the ground cap mkd.	
		T37N R6W	
		S20 S21 S29 S28	
		1965	
		Raise a mound of stone W. of the cor.	
		Land, nearly level.	
		Soil, sandy clay loam.	
		No timber; undergrowth, grama grass, yellowbrush and scattered greasewood.	
		From the cor. of secs. 21, 22, 27 and 28.	
		N. 89°56' W., bet. secs. 21 and 28.	
		Asc. over gentle E. slope.	
	28.00	Low ridge, bears N. and S.; desc. over gentle W. slope.	
	39.99	Point for the ½ sec. cor. of secs. 21 and 28.	
		Set the iron post 20 ins. in the ground, cap mkd.	
l		T37N R6W	
		$\frac{1}{4} \frac{S21}{S28}$	
		1965	
		Raise a mound of stone N. of the cor.	
		Continue over nearly level land.	
	79.98	The cor. of secs. 20, 21, 28 and 29.	
		Land, gently rolling.	
		Soil, fine gravel and clay. No timber; undergrowth, grama grass greasewood,	
		yellowbrush and cactus.	
		N. 0°03' W., bet. secs. 20 and 21.	
		Over nearly level land covered with grass yellowbrush	
		and scattered greasewood.	

~	/
	1_
	w

26.50	Low ridge, bears E. and W.
40.00	Point for the ½ sec. cor. of secs. 20 and 21.
-10100	Set the iron post 19 ins. in the ground, cap mkd.
	T37N R6W
	\$20 \$21
	1965
	Raise a mound of stone W. of the cor.
	The cor. is located on the W. side of a draw draining N. 10° E.
52.00	Spur, slopes N. 60° E.
58.80	Wide draw, drains E.
63.80	Low ridge, bears N. 80° E. and W.
80.00	Point for the cor. of secs. 16, 17 20 and 21.
	Set the iron post 18 ins. in the ground in a collar of stones, cap mkd.
	T37N R6W <u>S17 S16</u> S20 S21 1965
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass yellowbrush and scattered greasewood.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89°57' W., bet. secs. 16 and 21.
	Over gently rolling land.
40.00	Point for the な sec. cor. of secs. 16 and 21.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T37N R6W 1 S16
	½ S16 S21 1965
54.90	Wash, 5 lks. wide, 1 ft. deep, drains N.
80.00	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling.
	Soil, rocky clay loam. No timber; undergrowth, grass, greasewood and

\sim	-	
/	/	

	27	•
CHAINS	N. 0°03' W., bet. secs. 16 and 17.	
	Over nearly level land covered with grass, yellowbrush and scattered greasewood.	
4.30	Spur, slopes NW.	
40.00	Point for the ½ sec. cor. of secs. 16 and 17.	
	Set the iron post 16 ins. in the ground, in a collar of stones, cap mkd.	
	T37N R6W	
	\$17 \$16 1965	
	Raise a mound of stone W. of the cor.	
41.40	Unimproved road, bears N. 60° E. and SW.	
79.70	Four strand barbed wire fence, bears E. and W.	
80.00	Point for the cor. of secs. 8, 9, 16 and 17.	
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.	
	T37N R6W <u>S 8 S 9</u> S17 S16 1965	
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass, yellowbrush and scattered greasewood.	
	From the cor. of secs. 9, 10, 15 and 16.	
	N. 89°57' W., bet. secs. 9 and 16.	
	Over nearly level land.	
37.00	Desc. over rocky SW. slope.	
40.00	Point for the 1/2 sec. cor. of secs. 9 and 16.	
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.	
	T37N R6W 2 S 9 S16 1965	
56.00	Continue over nearly level land.	
80.00	The cor. of secs. 8, 9, 16 and 17.	
	Land, gently rolling. Soil, clay loam and rocky. No timber; undergrowth, yellowbrush, cactus, sagebrush and grass.	

		28
CHAINS	N. 0°03' W., bet. secs. 8 and 9.	
	Over nearly level land through medium undergrowth.	
0.40	Wash, 5 lks. wide, 1 ft. deep, drains NW.	Ì
18.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 70° W.	
21.20	Unimproved road, bears S. 60° E. and N. 60° W.	
40.00	Point for the ½ sec. cor. of secs. 8 and 9.	
	Set the iron post 21 ins. in the ground, cap mkd.	
	T37N R6W	
	s 8 s 9 1965	
	Raise a mound of stone W. of the cor.	
70.20	Draw, drains S. 30° W.; asc. over rolling SW. slope.	
74.00	Spur, slopes SW.	
75.20	Draw, drains SW.	
78.80	Rocky S. rim of Little Hurricane Ridge, bears NW. and SE.; asc. SW. slope.	
80.00	Point for the cor. of secs. 4, 5, 8 and 9.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T37N R6W S 5 S 4 S 8 S 9	
	Raise a mound of stone W. of the cor.	
	Land, mostly level. Soil, sandy clay loam and rocky. No timber; undergrowth, grama grass, yellowbrush and scattered greasewood.	
	From the cor. of secs. 3, 4, 9 and 10.	
	N. 89°56' W., bet. secs. 4 and 9.	
	Over nearly level land through medium undergrowth.	
40.00	Point for the ½ sec. cor. of secs. 4 and 9.	
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.	
	T37N R6W 1/4 S 9 1965	
	The cor. is located on an E. slope.	
78.70	Rocky rim of Little Hurricane Ridge, bears NW. and SE.; desc. SW. slope.	
		-

	CHAINS 80.00	The cor. of secs. 4, 5, 8 and 9.
		Land, nearly level. Soil, sandy clay loam. No timber, undergrowth, grama grass, yellowbrush, sage and scattered greasewood.
		N. 0°10' E., bet. secs. 4 and 5.
		Over rolling land through medium undergrowth.
		Asc. over SW. slope of Little Hurricane Ridge.
	5.30	High point on Little Hurricane Ridge, bears NW. and SE.; desc. over gentle N. slope.
	40.00	Point for the ½ sec. cor. of secs. 4 and 5.
		Set the iron post 3 ins. in the ground, mound with stones to top, cap mkd.
	,	T37N R6W
		s 5 s 4 1965
	42.30	Small draw, drains N. 80° E.
	50.80	Fence cor. bears E. 6 1ks. dist.; fence bears N. 0°03' E. and N. 89°05' E.
	79.82	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the 1924 survey.
	•	The cor. is located at the cor. of a fence; fences bear N. 0°03' E.; S. 0°03' W., and SW.
		Land, nearly level. Soil, sandy clay loam and rocky. No timber; undergrowth, grama grass, yellowbrush and scattered greasewood.
		From the standard cor. of secs. 31 and 32 on the S. bdy. of the Tp., monumented by an iron post 3 ins. in diam., set, mkd. and witnessed as described in the official record of the 1915 survey.
		N. 0°03' W., bet. secs. 31 and 32.
		Over nearly level land through medium undergrowth.
	10.60	Wash, 5 lks. wide, 1 ft. deep, drains N. 30° E.
	40.00	Point for the ½ sec. cor. of secs. 31 and 32.
	į	Set the iron post 21 ins. in the ground, cap mkd.
		T37N R6W
		S31 S32 1965
- 1		· ·

4		
	CHAINS	from which
		A cor. of a four strand barbed wire fence bears N. 68°47' W., 1.01 chs. dist.; fences bear S. 89°55' W. and N. 0°17' W.
		Raise a mound of stone W. of the cor.
	74.70	Spur, slopes W.
	80.00	Point for the cor. of secs. 29, 30, 31 and 32.
		Set the iron post 22 ins. in the ground, cap mkd.
		T37N R6W <u>S30 S29</u> S31 S32 1965
	:	from which
		Fence cor., bears N. 64°52' W., 1.22 chs. dist.; fences bear S. 89°40' E., N. 89°40' W., S. 0°17' E. and N. 0°23' W.
		Raise a mound of stone W. of the cor.
		Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass, yellowbrush and scattered greasewood.
		From the cor. of secs. 28, 29, 32 and 33.
		N. 89°56' W., bet. secs. 29 and 32.
		Over nearly level land through medium undergrowth.
	6.40	Four strand barbed wire fence, bears N. 89°10' W. and S. 89°10' E.
	39.70	Small draw, drains N. 15° W.
	39.98	Point for the ½ sec. cor. of secs. 29 and 32.
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
		T37N R6W 2 S29 S32 1965
		from which
		A four strand barbed wire fence bears N., 40 lks. dist.; fence bears S. 89°40' E. and N. 89°40' W.
	43.30	Small spur, slopes N.
	51.30	Small spur, slopes NW.
	78.90	Spur, slopes N.
	79.96	The cor. of secs. 29, 30, 31 and 32.

CHAINS	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass, yellowbrush and scattered greasewood.
	N. 89°57' W., bet. secs. 30 and 31.
	Over rolling land through medium undergrowth.
1.10	Fence, bears S. 0°17' E. and N. 0°17' W.
6.50	Wash, 10 1ks. wide, 2 ft. deep, drains N.
29.70	Wide draw, drains N. 20° W.
40.00	Point for the ½ sec. cor. of secs. 30 and 31.
	Set the iron post 20 ins. in the ground, cap mkd.
	T37N R6W ¹ / ₂ <u>S30</u> S31 1965
	Raise a mound of stone N. of the cor.
	The cor. is located on a gentle W. slope.
44.40	Wash, 10 1ks. wide, 1 ft. deep, drains N.
62.10	Ridge, bears N. and S.
79.85	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.
	Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, grama grass, yellowbrush, and scattered greasewood.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over nearly level land through medium undergrowth.
0.50	Four strand barbed wire fence, bears N. 89°40' W. and S. 89°40' E.
40.00	Point for the ½ sec. cor. of secs. 29 and 30.
	Set the iron post 19 ins. in the ground, cap mkd.
	T37N R6W
,	S30 S29 1965
	from which
	A four strand barbed wire fence bears W., 1.33 chs. dist.; fence bears N. 0°27' W. and S. 0°23' E.
]	

32			32.
	CHAINS		
		Raise a mound of stone W. of the cor.	}
	50.00	Wash, 5 1ks. wide, 1 ft. deep, drains N. 30° W.	
	72.00	Small spur, slopes W.	
	80.00	Point for the cor. of secs. 19, 20, 29 and 30.	
		Set the iron post 23 ins. in the ground, cap mkd.	
		T37N R6W S19 S20 S30 S29	
		1965	
		from which	
		A corner of fence bears S. 79°31' W., 1.64 chs. dist.; fences bear N. 44°33' E. and S. 0°27' E.	
		Raise a mound of stone W. of the cor.	
		Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass, yellowbrush, scattered brigham tea and greasewood.	
		From the cor. of secs. 20, 21, 28 and 29.	
		N. 89°54' W., bet. secs. 20 and 29.	
		Over rolling land.	
	39.97	Point for the ½ sec. cor. of secs. 20 and 29.	
		Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.	
		T37N R6W 1/4 S20 S29 1965	
		Cor. falls on E. side of small draw draining NW.	
	66.90	Track road, bears NE. and SW.	
	79.94	The cor. of secs. 19, 20, 29 and 30.	
	,	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grass, yellowbrush and scattered greasewood.	
	,	N. 89°59' W., bet. secs. 19 and 30.	
		Over nearly level land.	
	1.30	Barbed wire fence, bears N. 44°33' E. and S. 44°33' W.	
	20.10	Track road, bears N. 80° E. and S. 80° W.	
	28.60	Wash, 10 1ks. wide, 1 ft. deep, drains NW.	
	20.00	nabi, to the wide, i it. deep, diatie in.	

38.60	Wash, 20 1ks. wide, 2 ft. deep, drains N.	
40.00	Point for the ½ sec. cor. of secs. 19 and 30.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T37N R6W	
	½ <u>S19</u> S30	
	1965	
	Raise a mound of stone N. of the cor.	
68.00	N. side of small knoll.	
79.71	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.	
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grass, yellowbrush and scattered greasewood.	
	From the cor. of secs. 19, 20, 29 and 30.	
*	N. 0°03' W., bet. secs. 19 and 20.	
	Over nearly level land covered with grass, yellowbrush and scattered greasewood.	
1.34	Four strand barbed wire fence, bears N. 44°33' E., and S. 44°33' W. 2.30 chs. dist. to fence cor.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.	
	Set the iron post 16 ins. in the ground, in a collar of stones, cap mkd.	
	T37N R6W	
, , , , , , , , , , , , , , , , , , ,	S19 S20 1965	
,	from which	
	Center of a pond bears S. 88°30' W., 70.55 chs. dist.	
	Raise a mound of stone W. of the cor.	
80.00	Point for the cor. of secs. 17, 18, 19 and 20.	
	Set the iron post 19 ins. in the ground, cap mkd.	
	T37N R6W S18 S17 S19 S20 1965	
	from which	
	Loading chute at NW. cor. of a corral, bears N. 18°20' E., 23.75 chs. dist.	

•		
	CHAINS	Raise a mound of stone W. of the cor.
		Land, nearly level. Soil, sandy clay loam.
	,	No timber; undergrowth, grama grass, yellowbrush, sage and greasewood.
		From the cor. of secs. 16, 17, 20 and 21.
	'	N. 89°53' W., bet. secs. 17 and 20.
		Over rolling land.
İ	39.96	Point for the ½ sec. cor. of secs. 17 and 20.
		Set the iron post 20 ins. in the ground, cap mkd.
		T37N R6W
		½ <u>\$17</u> \$20
		1965
		Raise a mound of stone W. of the cor.
		The cor. is located on a gentle SE. slope.
	59.80	Barbed wire fence, bears N. 25°15' W. and S. 25°15' E.
	79.92	The cor. of secs. 17, 18, 19 and 20.
		Land, nearly level. Soil, fine gravel and clay. No timber; undergrowth, sagebrush, greasewood and cactus.
		West, bet. secs. 18 and 19.
		Over rolling land.
	0.70	Track road bears N. and S.
	19.90	Barbed wire fence, bears N. 55°15' E. and S. 55°15' W.
	40.00	Point for the ½ sec. cor. of secs. 18 and 19.
		Set the iron post 22 ins. in the ground, cap mkd.
		T37N R6W 2 S18 S19
		1965
		Raise a mound of stone N. of the cor.
	79.56	True point for cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., from which its witness corner bears S. 50 1ks. dist., monumented by an iron post 2½ ins. in diam., set, mkd. and witnessed as described in the official record of the 1964 resurvey.
		Land, nearly level. Soil, fine gravel and clay. No timber; undergrowth, sagebrush, greasewood and cactus.

 1	33	•
CHAINS	From the cor. of secs. 17, 18, 19 and 20.	
	N. 0°03' W., bet. secs. 17 and 18.	
	Over nearly level land through medium undergrowth.	
5.70	Unimproved road, bears N. 10° E. and S. 10° W.	
16.40	Four strand barbed wire fence bears N. 50°40' E. and S. 50°40' W.	
22.60	Unimproved road, bears E. and S. 85° W.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.	
	Set the iron post 17 ins. in the ground, cap mkd.	
	T37N R6W	
	\$18 \$17 1965	
	from which	
	A fence cor. bears S. 70° E., 1.40 chs. dist.; fences bear S. 25°15' E. and N.	
	Center of a pond bears N. 55°15' E., 20.80 chs. dist.	
	Raise a mound of stone W. of the cor.	
63.80	Unimproved road, bears N. 10° W. and S. 30 E.	
68.50	Same road, bears N. 20° E. and S. 20° W.	•
76.30	Same road, bears N. 40° W. and S. 40° E.	
79.00	Same road, bears SE., and N. 15° W. for 50 1ks., then N. 30° E.	
79.50	Fence, bears E., and W. 1.36 chs. dist. to a N-S fence.	
80.00	Point for the cor. of secs. 7, 8, 17 and 18.	
	Set the iron post 18 ins. in the ground, cap mkd.	
	T37N R6W <u>S 7 S 8</u> S18 S17 1965	
	Raise a mound of stone W. of the cor.	
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass, yellowbrush, sage and scattered greasewood.	
	From the cor. of secs. 8, 9, 16 and 17.	
	N. 89°55' W., bet. secs. 8 and 17.	
	Over nearly level land.	
39.96	Point for the ½ sec. cor. of secs. 8 and 17.	

36			36.
	CHAINS	Set the iron post 20 ins. in the ground, cap mkd.	
		T37N R6W	
		½ <u>S 8</u> S17	
		1965	
		Raise a mound of stone N. of the cor.	
	53.40	Barbed wire fence bears N. 0°50' W., and S. 0°50' E. 50 lks. dist. to fence bearing E. and W.	
	78.60	Barbed wire fence bears N., and S. 50 lks. dist. to cor. of fences bearing N., S., and E.	
	79.50	Draw, 20 1ks. wide, 1 ft. deep, drains NW.	
	79.92	The cor. of secs. 7, 8, 17 and 18.	
		Land, gently rolling. Soil, clay and rocky. No timber; undergrowth, grass, yellowbrush, cactus and sagebrush.	
		S. 89°57' W., bet. secs. 7 and 18.	
		Over nearly level land.	
	2.40	Track road, bears NW. and SE.	
	40.00	Point for the ½ sec. cor. of secs. 7 and 18.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T37N R6W 2 S 7 3 S 18	
		4 S18 1965	
		Raise a mound of stone N. of the cor.	
	51.90	Track road, bears S. 40° W. and N. 40° E.	
	79.00	Ditch, 10 1ks. wide, 2 ft. deep, drains NW.	
	79.47	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post 2 ins. in diam., set, mkd. and witnessed as described in the official record of the 1924 survey.	
		Land, nearly level. Soil, light clay. No timber; undergrowth, grass, yellowbrush, cactus and scattered greasewood.	
		From the cor. of secs. 7, 8, 17 and 18.	
		N. 0°03' W., bet. secs. 7 and 8.	
		Over nearly level land through medium undergrowth.	
	0.80	Wash, 10 1ks. wide, 2 ft. deep, drains NW.	
	17.90	Unimproved road, bears N. 40° E. and S. 40° W.	
	17.50	on improved road, bears N. 40 E. and S. 40 W.	

2	7	
٦.	•	

		37.
	CHAINS	Detail Control
	40.00	Point for the ½ sec. cor. of secs. 7 and 8.
		Set the iron post 24 ins. in the ground, cap mkd.
		T37N R6W 社
		S 7 S 8 1965
		Raise a mound of stone W. of the cor.
	76.30	Dim unimproved road, bears NE. and SW.
	80.00	Point for the cor. of secs. 5, 6, 7 and 8.
		Set the iron post 17 ins. in the ground, cap mkd.
		T37N R6W S 6 S 5 S 7 S 8 1965
		from which
		A fence cor. bears S. 81°10' E., 1.45 chs. dist.; fences bear N. 44°32' E. and S.
		Raise a mound of stone W. of the cor.
		Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass, yellowbrush and scattered greasewood.
		From the cor. of secs. 4, 5, 8 and 9.
		N. 89°53' W., bet. secs. 5 and 8.
		Desc. over SW. slope.
	1.10	Rocky rim, bears NW. and SE.; desc. over general W. slope of Little Hurricane Ridge.
	8.90	Enter nearly level land.
	24.40	Unimproved road, bears N. and S.
	39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
		Set the iron post 19 ins. in the ground, cap mkd.
		T37N_R6W
		$\frac{1}{4} \frac{S}{S} \frac{5}{8}$ 1965
		Raise a mound of stone N. of the cor.
	41.50	Wash, 10 1ks. wide, 1 ft. deep, drains N. 15° W.
	52.45	Four strand barbed wire fence, bears N. and S.
	60.90	Unimproved road, bears N. 10° E. and S. 20° W.
I	l	

38		30.
	CHAINS	
	78.28	Four strand barbed wire fence, bears N. 44°32' E. and S. 44°32' W.
	79.90	The cor. of secs. 5, 6, 7 and 8.
		Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grama grass, scattered grease- wood and yellowbrush.
		S. 89°55' W., bet. secs. 6 and 7.
		Over nearly level land through medium undergrowth.
	0.80	Unimproved road, bears N. 10° E. and S. 10° W.
	3.60	Unimproved road, bears NE. and SW.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
		Set the iron post 20 ins. in the ground, cap mkd.
	,	T37N R6W 1/4 S 6 S 7 1965
		Raise a mound of stone N. of the cor.
	79.34	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam. set, mkd. and witnessed as described in the official record of the 1924 survey.
		from which
		An earthen dike bears N., 16.15 chs. dist.; dike bears N. 51°15' E. and S.
	-	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grass and scattered greasewood and sagebrush.
		From the cor. of secs. 5, 6, 7 and 8.
		N. 0°06' E., bet. secs. 5 and 6.
		Over nearly level land through medium undergrowth.
	9.50	Unimproved road, bears NE. and S. 30° W.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
		Set the iron post 18 ins. in the ground, cap mkd.
		T37N R6W
	,	S 6 S 5 1965
		Raise a mound of stone W. of the cor.

	Subdivision, T. 37 N., R. 6 W., Arizona 39.
 CHAINS	
73.80	Wash, 20 1ks. wide, 2 ft. deep, drains N. 60° W.
79.74	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.
	from which
	Center of a cabin bears N. 82°42' E., 20.31 chs. dist.
	Center of a pond bears N. 57°35' E., 3 chs. dist.
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, grass, yellowbrush and scattered greasewood.
	General Description
	Very little change in land and soil is found in the township. The elevation ranges from about 5,100 feet to 5,400 feet above sea level, with the top of Heaton Knolls, in the southwest corner of Section 34, about 450 feet higher. The soil is sandy clay loam with some rocky areas at higher elevations. The timber, primarily cedars, is found scattered through the eastern part of the township.
	The only water source noted in the township is runoff caught in ponds or reservoirs scattered throughout the township. Heaton Reservoir, in Section 14, Earl Reser-

voir in Section 23, and another reservoir in Section 6appear to contain water the year around.

The main use of the land, which is covered throughout with a good stand of native grass is grazing. There are numerous fences in the township, many of which run along or close to section lines. There are corrals and loading chutes scattered throughout the township. One cabin used for temporary quarters was noted in Section 23. Bladed roads run throughout the township, with track roads in the more remote portions.

BOOK4708

Form 4-680 (June 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Gary T. Oviatt	Notekeeper and Chainman
Lyman W. Polacca	Chainman
Howard H. Thomas	Cornerman
Jimmy B. Brown	Flagman
Wallace R. Ott	Notekeeper and Chainman
Daniel R. Bauer	Transitman
Willie D. Bettis	Chainman
Martin W. Fuller	Flagman
John F. Shaughnessy	Cornerman

(n)

BOOK 4768

CERTIFICATE OF SURVEY

We, ★x	Boyd S. Ower Paul G. Bau		, HEREBY CERTIFY	ipon honor that,
in pursu	ance of special instr	octions bearing date of the 2nd	day of March	, 19 64 ,
We ≵ have	surveyed the s	ıbdivisional lines of T	ownship 37 North,	, Range 6 West
	Gila and Salt R		11.6	, which our
are represented in the foregoing field notes as having been executed by me and under my direction;				
		n made in strict conformity wit		
of Inst	ructions for the Surv	ey of the Public Lands of the	· United States, and in	specific manner
describ	oed in the foregoing fi	eld notes.		
Ma	rch 10, 1966 (Date)		(Cadastral Surveyor	vers
Ma	nrch 10, 1966 (Date)		(Cadastral Surveyor	, Q, j^
CERTIFICATE OF APPROVAL				
	MITTED FOR APPR MAY 1 1 19	OVAL 66	BUREAU OF LAND Washington, D. C.	MANAGEMENT,
The f	foregoing field notes	of the survey of the su	ıbdivisional lines	s of Township
37 North, Range 6 West of the Gila and Salt River Meridian in the				
S	tate of Arizona			
		wens and Paul G. Bauer	_	yors,
havir	ng been critically exam	nined and found correct, are he	reby approved.	
	UN 2 4 1966 (Date)		Chief, Division of Eng	intering) NES
CERTIFICATE OF TRANSCRIPT				
I CERTIFY That the foregoing transcript of the field notes of the above described surveys in				
		,	is a true copy of the c	DURIUM HELD HOIES.

(Date)

(Chief, Division of Engineering)