

BOOK 4772

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of a

Portion of the East Boundary

and

SURVEY

of the

Subdivisional Lines

and

METES AND BOUNDS SURVEYS

of

Tracts in the Southeast One-Quarter

of

Section 19

Township 8 South, Range 26 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer, Cadastral Surveyor

Under special instructions dated October 15, 19 65, which provided for the surveys included under Group Number 436, approved October 15, 1965, and assignment instructions dated December 7, 19 65.

Survey commenced December 13, 19 65

Survey completed December 17, 19 65

1A

BOOK 4772
INDEX DIAGRAM

Township 8 South, Range 26 East

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
3 4	20	21	22	23	24	
19						8 6 10 5 7 4
2						
30	29	28	27	26	25	
31	32	33	34	35	36	

BOOK4772

Surveys in Section 19,
Township 8 South, Range 26 East, G&SRM, Arizona

1. B

CHAINS		
	<p>The west boundary of section 19 was resurveyed in 1957 by D. E. Harding. The south, east and north boundaries were resurveyed in 1961 by Dell Cazier.</p> <p>The following field notes are those of a dependent resurvey of a portion of the east boundary of section 19, a survey of the subdivisional lines, and a metes and bounds survey of tracts in the southeast $\frac{1}{4}$ of section 19.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated October 15, 1965.</p> <p>Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, $2\frac{1}{2}$ inches in diameter, flanged at the base, and with a brass cap riveted to the top. Bathey markers herein described are 1 inch "T" iron stakes, 24 inches long, with aluminum caps.</p> <p>The geographic position of the southeast corner of section 19 is: Latitude $32^{\circ}42'55''$ North, and Longitude $109^{\circ}42'49''$ West, as determined from a tie to triangulation station "SWIFT" in section 17, Tp. 8 S., R. 26 E.</p> <p>The mean magnetic declination was found to be 13° East.</p> <hr/> <p>Dependent Resurvey of a Portion of the East Boundary, Section 19, Township 8 South, Range 26 East, Arizona</p> <hr/> <p>Beginning at the cor. of secs. 19, 20, 29 and 30, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1961 resurvey.</p> <p>from which</p> <p style="padding-left: 40px;">A concrete pillar built by United States Federal Prison personnel, standing 7 ft. high, tapering from 2 ft. square at the base to 6 ins. square at the top, bears SW., 5 lks. dist. A sign on the pillar reads: U. S. Property No Trespassing.</p> <p>N. $0^{\circ}13'$ W., over gently rolling land.</p>	
19.34	Fence, bears irregularly E. and W.	
19.92	Point for the S. $\frac{1}{16}$ cor. of secs. 19 and 20.	
	Set the iron post 18 ins. in the ground, collar of stones to top, brass cap mkd.	
	<p>T8S R26E S $\frac{1}{16}$ S19 S20 1965</p>	
21.80	Track road, bears irregularly E. and W.	

CHAINS

- 23.00 Wash, 15 lks. wide, 2 ft. deep, drains E.
- 30.60 Wash, 10 lks. wide, 1 ft. deep, drains E.
- 39.85 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1961 resurvey.

Subdivision, Sec. 19, T. 8 S., R. 26 E., Arizona

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1961 resurvey.

N. $0^{\circ}14'$ W., on the N. and S. center line of sec. 19.

Over nearly level land.

- 8.77 The SW. and long side of U. S. Federal Prison Dorm No. 6, bearing S. $25^{\circ}59'$ E. and N. $25^{\circ}59'$ W. The building is 34 ft. wide and 84 ft. long.
- 12.70 The center of the NW. end of Dorm No. 5, bearing N. $64^{\circ}01'$ E. and S. $64^{\circ}01'$ W., with same dimensions as Dorm No. 6.
- 13.65 Fence, inside of prison yard, bears N. 64° E. and S. 64° W.
- 14.20 Road, in prison yard, bears same as fence.
- 19.96 Point for the CS $1/16$ cor. of sec. 19 falls in the prison yard and is not monumented.
- 21.00 Masonry wall, 18 ins. wide, 3 ft. high, bears N. $40^{\circ}19'$ E. and S. $40^{\circ}19'$ W.
- 21.07 Telephone line, parallels masonry wall.
- 21.80 Center of Arizona Hwy. No. 366, (Swift Trail Road), bears N. $40^{\circ}19'$ E. and S. $40^{\circ}19'$ W.
- 22.70 Power line, parallels Hwy. 366.
- 27.40 Wash, 30 lks. wide, 2 ft. deep, drains N. 30° E.
- 30.00 Major power line, bears S. 26° E. and N. 26° W.
- 30.40 Bladed road, parallels power line.
- 33.20 Wash, 10 lks. wide, 2 ft. deep, drains NE.
- 39.91 Point for the C $\frac{1}{4}$ cor. of sec. 19.

Set the iron post 18 ins. in the ground, collar of stones to top, brass cap mkd.

T8S R26E
C $\frac{1}{4}$ +S19
1965

Build a mound with stones W. of the iron post.

BOOK4772

Subdivision, Sec. 19, T. 8 S., R. 26 E., Arizona

CHAINS	
44.60	Wash, 5 lks. wide, 6 ins. deep, drains E.
55.30	Fence, bears NE. and SW.
56.30	Wash, 10 lks. wide, 6 ins. deep, drains E.
69.50	Track road, bears E. and SW.
71.50	Wash, 10 lks. wide, 6 ins. deep, drains N. 70° E.
74.30	Wash, 10 lks. wide, 6 ins. deep, drains N. 80° E.; asc. S. slope.
75.40	S. rim of a low mesa, bears N. 80° E. and S. 80° W.; thence over nearly level land.
79.96	The ¼ sec. cor. of secs. 18 and 19, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1961 resurvey.
	<p>Land, nearly level to gently rolling. Soil, gravelly loam. Timber, scattered small mesquite. Undergrowth, moderate greasewood, scattered catclaw.</p>
	<p>From the ¼ sec. cor. of secs. 19 and 20.</p>
	<p>S. 89°59' W., on the E. and W. center line of sec. 19.</p>
	<p>Over nearly level land.</p>
4.85	Surfaced street, bears N. into private subdivision and S. 50 lks. to an E-W surfaced road.
9.25	Power line pole on S. end of access line bearing N.
13.15	Surfaced street, bears N. into private subdivision and S. 50 lks. to an E-W surfaced road.
19.50	Surfaced road, bears N. 3° W. and S. 3° E., curving to E.
19.78	Point for the CE 1/16 cor. of sec. 19.
	<p>Set the iron post 20 ins. in the ground, collar of stones to top, brass cap mkd.</p>
	<p style="text-align: center;">T8S R26E E $\frac{1}{16}$ C ————— C S19 1965</p>
	<p>from which</p>
	<p style="text-align: center;">A concrete pillar built by United States Federal Prison personnel, standing 7 ft. high, tapering from 2 ft. square at the base to 6 ins. square at the top, bears SW. 5 lks. dist. A sign on the pillar reads: U. S. Property No Trespassing.</p>
19.90	Fence, bears S. 10°15' W. and irregularly N.
23.60	Telephone line, bears N. 40°19' E. and S. 40°19' W.
24.20	Center of Arizona Hwy. No. 366 (Swift Trail Road), bears N. 40°19' E. and S. 40°19' W.

BOOK 4772

Subdivision, Sec. 19, T. 8 S., R. 26 E., Arizona

4

4.

CHAINS

- 25.00 Power line, parallels Hwy. 366.
- 27.80 Wash, 25 lks. wide, 2 ft. deep, drains NE.
- 39.56 The C $\frac{1}{4}$ cor. of sec. 19.
- 44.00 Bladed road, bears S. 26° E. and N. 26° W.
- 44.30 Major power line, parallels road.
- 47.30 Wash, 8 lks. wide, 6 ins. deep, drains NE.
- 52.60 Wash, 20 lks. wide, 1 ft. deep, drains NE.
- 59.28 Point for the CW 1/16 cor. of sec. 19. This point also functions as the NW. cor. of P L O 1767.

Set the iron post 24 ins. in the ground, collar of stones to top, brass cap mkd.

T8S R26E
W $\frac{1}{16}$
C ————— C
S19
1965
- 63.80 Fence, bears N. 57°30' E. and S. 57°30' W.
- 73.30 Wash, 20 lks. wide, 1 ft. deep, drains NE.
- 77.97 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1957 resurvey.

Land, gently rolling.
Soil, gravelly loam.
Timber, scattered small mesquite.
Undergrowth, moderate greasewood.

- From the E. 1/16 cor. of secs. 19 and 30, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1961 resurvey.

N. 0°14' W., on the N. and S. center line of the SE. $\frac{1}{4}$ of sec. 19.

Over nearly level land.
- 0.20 Bladed road, bears irregularly SE. and W.
- 0.40 Fence, parallels road.
- 5.10 Bladed road, bears SE. and NW.
- 7.00 Wash, 20 lks. wide, 2 ft. deep, drains NE.
- 8.40 Bladed road, bears NE. and SW.
- 10.00 Bladed road, bears SE. and NW.
- 13.30 Bladed road on dike bet. two small ponds, bears N. 70° E. and S. 70° W.
- 15.30 Fence, bears S. 70° E. and N. 70° W.
- 19.00 Bladed road, bears irregularly E. and W.

BOOK4772

Subdivision, Sec. 19, T. 8 S., R. 26 E., Arizona

CHAINS

- 19.50 Fence, bears irreg. E. and W.
- 19.941 Point for the SE 1/16 cor. of sec. 19.

Set the iron post 20 ins. in the ground, collar of stones to top, brass cap mkd.

T8S R26E
SE $\frac{1}{16}$ +S19
1965

from which

A concrete pillar built by United States Federal Prison personnel, standing 7 ft. high, tapering from 2 ft. square at the base to 6 ins. square at the top, bears S. 20° W., 4 lks. dist. A sign on the pillar reads: U. S. Property No Trespassing.
- 23.30 Bladed road, bears E. and W.
- 24.02 Cor. 2 of Tract G, monumented by a $\frac{3}{4}$ in. iron rod set by a local surveyor.

At the cor. point, set the iron post 20 ins. in the ground, collar of stones to top, brass cap mkd.

T8S R26E
S19 |
COR 2 |
TR G |
PLO
1767
1965

Bury the iron rod alongside the iron post.
- 25.536 Cor. 1 of Tract G, common to Cor. 2 of Tract F, monumented by a $\frac{3}{4}$ in. iron rod set in an E-W fence line by a local surveyor.

At the cor. point, set a Bathey marker 20 ins. in the ground, collar of stones to top, aluminum cap mkd.

COR 2 |
TR F |
TR G |
COR 1 |

Bury the iron rod alongside the iron post.
- 27.052 Cor. 1 of Tract F, common to Cor. 2 of Tract E, monumented by a $\frac{3}{4}$ in. iron rod set in an E-W fence line by a local surveyor.

At the cor. point, set a Bathey marker 20 ins. in the ground, collar of stones to top, aluminum cap mkd.

COR 2 |
TR E |
TR F |
COR 1 |

Bury the iron rod alongside the iron post.

BOOK 4772

Subdivision, Sec. 19, T. 8 S., R. 26 E., Arizona

6.

6

CHAINS									
28.568	<p>Cor. 1 of Tract E, common to Cor. 2 of Tract D, monumented by a $\frac{3}{4}$ in. iron rod set by a local surveyor.</p> <p>At the cor. point, set a Bathey marker 20 ins. in the ground, collar of stones to top, aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>COR 2</td><td> </td></tr> <tr><td>TR D</td><td> </td></tr> <tr><td>TR E</td><td> </td></tr> <tr><td>COR 1</td><td> </td></tr> </table> </div> <p>Bury the iron rod alongside the iron post.</p>	COR 2		TR D		TR E		COR 1	
COR 2									
TR D									
TR E									
COR 1									
29.470	<p>Private lane, 15 ft. wide, bears E. and W.</p>								
30.084	<p>Cor. 1 of Tract D, common to Cor. 2 of Tract C, monumented by a wooden stake set in an E-W fence line by a local surveyor.</p> <p>At the cor. point, set a Bathey marker 20 ins. in the ground, collar of stones to top, aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>COR 2</td><td> </td></tr> <tr><td>TR C</td><td> </td></tr> <tr><td>TR D</td><td> </td></tr> <tr><td>COR 1</td><td> </td></tr> </table> </div> <p>Bury the wooden stake alongside the iron post.</p>	COR 2		TR C		TR D		COR 1	
COR 2									
TR C									
TR D									
COR 1									
30.935	<p>S. side of a dwelling, bears S. $81^{\circ}49'$ E. for 11.5 ft. and N. $81^{\circ}49'$ W. for 28.5 ft. The house dimensions are 24.5 ft. N. and S. by 40 ft. E. and W. There is an 11 ft. wide carport attached to the N. side of the house.</p>								
33.103	<p>Cor. 1 of Tract C, common to Cor. 2 of Tract B, monumented by a $\frac{3}{4}$ in. iron rod set in an E-W fence line by a local surveyor.</p> <p>At the cor. point, set a Bathey marker 20 ins. in the ground, collar of stones to top, aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>COR 2</td><td> </td></tr> <tr><td>TR B</td><td> </td></tr> <tr><td>TR C</td><td> </td></tr> <tr><td>COR 1</td><td> </td></tr> </table> </div> <p>Bury the iron rod alongside the iron post.</p>	COR 2		TR B		TR C		COR 1	
COR 2									
TR B									
TR C									
COR 1									
34.278	<p>Cor. 1 of Tract B, common to Cor. 2 of Tract A, monumented by a small wooden stake set by a local surveyor.</p> <p>At the cor. point, set a Bathey marker 20 ins. in the ground, collar of stones to top, aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>COR 2</td><td> </td></tr> <tr><td>TR A</td><td> </td></tr> <tr><td>TR B</td><td> </td></tr> <tr><td>COR 1</td><td> </td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An iron rod $\frac{3}{4}$ in. diam., bears N. $89^{\circ}38'$ E., 0.611 chs. dist.</p> <p style="padding-left: 40px;">An iron rod $\frac{3}{4}$ in. diam., bears S. $89^{\circ}38'$ W., 0.313 chs. dist.</p> <p>Bury the small wooden stake alongside the iron post.</p>	COR 2		TR A		TR B		COR 1	
COR 2									
TR A									
TR B									
COR 1									

BOOK4772


Subdivision, Sec. 19, T. 8 S., R. 26 E., Arizona

CHAINS

35.966 Point for Cor. 1 of Tract A at intersection with the W. bdy. of the tracts.

After diligent search, find no evidence of a local survey marker.

At the cor. point, set the iron post 20 ins. in the ground, collar of stones to top, brass cap mkd.



36.100 Fence, bears N. 10° E. and S. 10° W.

36.200 Power line, bears same as fence.

37.540 Bladed road, bears same as fence.

39.882 The CE 1/16 cor. of sec. 19.

From the S 1/16 cor. of secs. 19 and 20.

S. 89°56'30" W., on the E. and W. center line of the SE ¼ of sec. 19.

Over nearly level land.

9.50 Bladed road, bears irreg. N. and S.

11.40 Wash, 20 lks. wide, 2 ft. deep, drains NE.

19.78 The SE 1/16 cor. of sec. 19.

23.18 Fence, bears N. and S. 40 lks. to cor. of fences bearing N. and E.

23.30 Bladed road, bears N. and S.

23.49 Cor. of fences bearing S. and W.

26.00 Wash, 15 lks. wide, 1 ft. deep, drains NE.

34.70 Major power line, bears S. 26° E. and N. 26° W.

35.10 Masonry wall, 18 ins. wide, 3 ft. high, parallels power line.

39.56 The CS 1/16 cor. of sec. 19, not monumented.

BOOK 4772

Metes and Bounds Survey of the West and South Boundaries
of Parcels of Land in the Southeast ¼ of Section 19,
T. 8 S., R. 26 E., Arizona

8

8.

CHAINS

From Cor. 1 of Tract A.

S. 10°14'30" W., along the W. bdy. of the tracts
and along the E. side of a bladed road.

0.130 Fence, bears N. 10° E. and S. 10°05' W.; thence along
the W. side of the same fence.

1.717 Cor. 3 of Tract A, common to Cor. 4 of Tract B,
monumented by a ¾ in. iron rod set by a local surveyor.

At the cor. point, set the iron post 21 ins. in the
ground, collar of stones to top, brass cap mkd.

T8S R26E
S19 / COR 3
PLO / TR A
1767 / TR B
COR 4
1965

from which

Cor. 2 of Tract A, common to Cor. 1 of Tract B,
bears N. 89°38' E., 0.313 chs. dist.

Bury the iron rod alongside the iron post.

2.916 Cor. 3 of Tract B, common to Cor. 4 of Tract C,
monumented by a wooden survey stake set by a local
surveyor.

At the cor. point, set the iron post 15 ins. in the
ground, mound with stones to top, brass cap mkd.

T8S R26E
S19 / COR 3
PLO / TR B
1767 / TR C
COR 4
1965

from which

Cor. 2 of Tract B, common to Cor. 1 of Tract C,
bears N. 89°15' E., 0.531 chs. dist.

A cor. of fences bearing N. 9°30' E., N. 89°36' E.
and S. 10°07' W., bears NE., 0.05 chs. dist.

Bury the wooden survey stake alongside the iron post.

4.48 Private lane, 12 ft. wide, bears S. 82° E., 0.53 chs.
to a carport on the N. side of a house, and N. 82° W.,
0.27 chs. to the center of a bladed access road.

5.989 Cor. 3 of Tract C, common to Cor. 4 of Tract D,
monumented by a wooden survey stake set by a local
surveyor.

At the cor. point, set the iron post 24 ins. in the
ground, collar of stones to top, brass cap mkd.

T8S R26E
S19 / COR 3
PLO / TR C
1767 / TR D
COR 4
1965

BOOK4772

Metes and Bounds Survey of the West and South Boundaries
of Parcels of Land in the Southeast $\frac{1}{4}$ of Section 19,
T. 8 S., R. 26 E., Arizona

9.

CHAINS

from which

Cor. 2 of Tract C, common to Cor. 1 of Tract D,
bears N. 89°22' E., 1.090 chs. dist.

A cor. of fences bearing N. 10°07' E., N. 89°52' E.,
and S. 10°24' W., bears NE., 0.07 chs. dist.

Bury the wooden survey stake alongside the iron post.

6.582 Private lane, bears E. to subdivision and W. 0.30 chs.
to the center of a bladed access road.

7.532 Cor. 3 of Tract D, common to Cor. 4 of Tract E,
monumented by a wooden survey stake set by a local
surveyor.

At the cor. point, set the iron post 24 ins. in the
ground, collar of stones to top, brass cap mkd.

T8S R26E
S19/ COR 3
PLO / TR D
1767 / TR E
COR 4
1965

from which

Cor. 2 of Tract D, common to Cor. 1 of Tract E,
bears N. 89°25' E., 1.370 chs. dist.

Bury the wooden survey stake alongside the iron post.

9.075 Cor. 3 of Tract E, common to Cor. 4 of Tract F,
monumented by a wooden survey stake set by a local
surveyor.

At the cor. point, set the iron post 23 ins. in the
ground, collar of stones to top, brass cap mkd.

T8S R26E
S19/ COR 3
PLO / TR E
1767 / TR F
COR 4
1965

from which

Cor. 2 of Tract E, common to Cor. 1 of Tract F,
bears N. 89°27' E., 1.651 chs. dist.

A cor. of fences bearing N. 10°14' E., N. 89°52' E.,
and S. 10°15' W., bears NE., 0.04 chs. dist.

Bury the wooden survey stake alongside the iron post.

10.618 Cor. 3 of Tract F, common to Cor. 4 of Tract G,
monumented by a wooden survey stake set by a local
surveyor.

At the cor. point, set the iron post 25 ins. in the
ground, collar of stones to top, brass cap mkd.

BOOK 4772

Metes and Bounds Survey of the West and South Boundaries
of Parcels of Land in the Southeast $\frac{1}{4}$ of Section 19,
T. 8 S., R. 26 E., Arizona

10.

10

CHAINS

T8S R26E
S19/COR 3
PLO/TR F
1767/TR G
COR 4
1965

from which

Cor. 2 of Tract F, common to Cor. 1 of Tract G,
bears N. 89°28' E., 1.932 chs. dist.

A cor. of fences bearing N. 10°14' E. and
N. 89°52' E., bears NE., 0.04 chs. dist.

Bury the wooden survey stake alongside the iron post.

12.161

Cor. 3 of Tract G, monumented by an iron rod $\frac{3}{4}$ in. diam.,
set by a local surveyor.

At the cor. point, set the iron post 25 ins. in the
ground, collar of stones to top, brass cap mkd.

T8S R26E
S19/COR 3
PLO/TR G
1767
1965

from which

Cor. 2 of Tract G, bears N. 89°29' E., 2.213 chs.
dist.

Bury the iron rod alongside the iron post.

General Description

The land in section 19, Township 8 South, Range 26 East,
ranges from nearly level to gently rolling. The soil is
a gravelly loam. Numerous small washes drain to the
northeast. The section has a moderate growth of grease-
wood and scattered small mesquite trees and cacti.

The northeast $\frac{1}{4}$ of the southeast $\frac{1}{4}$ of section 19 is a
subdivision with new homes under construction.

Arizona Highway No. 366, known as "Swift Trail Road",
bears northeasterly and southwesterly through the
section.

A United States Federal Prison is located in the south $\frac{1}{2}$
of the section.

The mean elevation is 3,100 feet above sea level.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Frank W. Rogers	Transitman
Robert F. Johnson	Front Chainman
Howard H. Thomas	Note Keeper
Dennis R. Hiekes	Cornerman
Gus M. Menninger	Flagman

BOOK4772

CERTIFICATE OF SURVEY

I, Paul G. Bauer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15 day of October, 19 65, I have dependently resurveyed a portion of the east boundary and surveyed the subdivision of Section 19, and by metes and bounds surveyed parcels of land in the southeast 1/4 of Section 19, Township 8 South, Range 26 East of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 12, 1966
(Date)

Paul G. Bauer
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date OCT 26 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the east boundary and survey of the subdivision of Section 19, and the metes and bounds surveys of parcels of land in the southeast 1/4 of Section 19, Township 8 South, Range 26 East, of the Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

NOV 17 1966
(Date)

E. J. Remington
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)