

BOOK 4775

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

RETRACEMENT

of the

East Boundary

of

Township 38 North, Range 11 West

for

Alignment Only

and

SURVEY

of the

Subdivisional Lines

of

Township 38 North, Range 11 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Wallace R. Ott, Cadastral Surveyor

Under special instructions dated July 1, 19 65, which provided for the surveys
included under Group Number 427, approved July 1, 1965,
and assignment instructions dated July 1, 19 65.

Survey commenced July 7, 19 65

Survey completed August 6, 19 65

1A

BOOK 4775 INDEX DIAGRAM

Township 38 North, Range 11 West,

6 45 44	5 32 44	4 24 32	3 17 23	2 10 16	1 3 9
7 42 42	8 31 41	9 23 30	10 16 22	11 8 15	12 2 8
18 40 39	17 29 39	16 21 29	15 14 21	14 7 13	13 2 6
19 38 37	20 28 36	21 20 27	22 13 19	23 6 12	24 2 5
30 35 35	29 27 34	28 18 26	27 12 18	26 4 11	25 2 4
31 33	32 25	33 17	34 10	35 3	36 1

BOOK4775

Township 38 North, Range 11 West, G&SRM, Arizona

1. B

CHAINS

The south boundary was surveyed in 1924 by W. E. Heister and C. E. Hunter, and is shown on the plat of T. 37 N., R. 11 W., accepted June 17, 1926. The east boundary was surveyed in 1934 by Warboys, Proctor and Hester and is shown on the plat of T. 38 N., R. 10 W., accepted April 29, 1935. The west boundary was surveyed in 1915 by T. B. Mathews and independently resurveyed in 1934 by Warboys and Proctor and is shown on the plat of T. 38 N., R. 12 W., accepted April 29, 1935. The north boundary was surveyed in 1939 by Muscott, Warner and Motch and is shown on the plat of T. 39 N., R. 11 W., accepted February 10, 1944. (Note: The distance between the township corner of T. 39 N., Rs. 11 and 12 W., and the township corner of T. 38 N., Rs. 11 and 12 W., is 1.06 chs. This is shown erroneously as 1.66 chs. on the plat of T. 39 N., R. 11 W., accepted February 10, 1944.)

The following field notes are those of a retracement of the east boundary for alignment only, and of the survey of the subdivisional lines of Township 38 North, Range 11 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 1, 1965.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 36°38'40.6" North, and Longitude 113°25'07.3" West as determined from ties to U.S.C.&G.S. triangulation station PASS in Section 23, Township 38 N., Range 11 West, Gila and Salt River Meridian, Arizona.

The magnetic declination was found to be 16°15' East.

Retracement of the East Boundary
Township 38 North, Range 11 West, Arizona
for alignment only

The following retracement of the east boundary for alignment only was performed to establish a mean course for the east boundary in order that the meridional section lines could be run parallel to the governing east boundary. The topography was found to be essentially the same as reported in the 1934 survey.

Beginning at the corner of Ts. 37 and 38 N., Rs. 10 and 11 W., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.

N. 0°05' E., bet. secs. 31 and 36.

40.00

Record dist. for the ¼ sec. cor. of secs. 31 and 36, monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record of the 1934 survey.

BOOK4775

Retracement, E. Bdy., T. 38 N., R. 11 W., Arizona

2

2.

CHAINS		
80.00	Record dist. for the cor. of secs. 25, 30, 31 and 36, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/> N. 0°05' E., bet. secs. 25 and 30.	
40.00	Record dist. for the ¼ sec. cor. of secs. 25 and 30, monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
80.00	Record dist. for the cor. of secs. 19, 24, 25 and 30, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/> N. 0°05' E., bet. secs. 19 and 24.	
40.00	Record dist. for the ¼ sec. cor. of secs. 19 and 24; monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/> Thence, N. 0°02' E.	
40.00	Record dist. for the cor. of secs. 13, 18, 19 and 24, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/> N. 0°01' E., bet. secs. 13 and 18.	
40.00	Record dist. for the ¼ sec. cor. of secs. 13 and 18, monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/> Thence, N. 0°03' E.	
40.00	Record dist. for the cor. of secs. 7, 12, 13 and 18, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/> N. 0°03' E., bet. secs. 7 and 12.	
40.00	Record dist. for the ¼ sec. cor. of secs. 7 and 12, monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/> Thence, N. 0°04' E.	
40.10	Record dist. for the witness cor. of secs. 1, 6, 7 and 12, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 survey.	
	<hr/>	

CHAINS	
	From the true point for the cor. of secs. 1, 6, 7 and 12 N. 0°02' E., bet. secs. 1 and 6.
40.00	Record dist. for the ¼ sec. cor. of secs. 1 and 6, monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record of the 1934 survey.
80.00	Record dist. for the township cor. of Ts. 38 and 39 N., Rs. 10 and 11 W., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 survey.
Subdivision, Township 38 North, Range 11 West, Arizona	
The meridional lines, as surveyed in the subdivision of T. 38 N., R. 11 W., are parallel to the mean course of the E. bdy. of the Tp., which was found to be N. 0°04' E.	
From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey. This cor. is located at a fence cor.; fences bear S. and W.	
N. 0°03' E., bet. secs. 35 and 36.	
Over gently rolling land in Main Street Valley.	
.20	Track road, bears S. and W.
1.00	Track road, bears E. and W.
16.90	Bladed road from St. George, Utah to Mt. Trumble, Arizona, bears S. 20° E. and N. 20° W.
40.00	Point for the ¼ sec. cor. of secs. 35 and 36. Set the iron post 20 ins. in the ground, cap mkd.
T38N R11W ¼ S35 S36 1965	
Build a mound of stones W. of the cor.	
41.00	Small draw, drains W.; continue over rolling land on E. side of valley.
80.00	Point for the cor. of secs. 25, 26, 35 and 36. Set the iron post 4 ins. in the ground, mound with stones to the top, cap mkd.
T38N R11W S26 S25 S35 S36 1965	

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

4

4.

CHAINS	
	<p>Land, gently rolling. Soil, clay loam and gravel. No timber; undergrowth, sage brush, yellow brush and grass.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp. S. 89°59' W., bet. secs. 25 and 36. Over rolling land through widely scattered timber.</p>
4.50	Low ridge, bears N. and S.
8.50	Bladed road, bears N. 30° E. and S. 30° W.
40.11	<p>Point for the ¼ sec. cor. of secs. 25 and 36. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W ¼ $\frac{S25}{S36}$ 1965</p>
	The cor. is located on a NW. slope.
42.80	Small draw, drains NE.
43.80	Same draw, drains SE. curving to NE.; asc. over E. slope.
61.70	Limestone rim, bears NW. and S.; desc. over steep W. slope.
70.00	Base of steep descent; continue over gently rolling land draining W. into Mainstreet Valley.
80.22	<p>The cor. of secs. 25, 26, 35 and 36. Land, rolling. Soil, rocky clay loam. Timber, widely scattered junipers. Undergrowth, moderate sage, yellow brush, cacti and grass.</p> <hr/> <p>N. 0°03' E., bet. secs. 25 and 26. Over rolling land through moderate undergrowth.</p>
17.00	Asc. over SW. slope.
36.90	Limestone rim, bears SE. and N. 20° W.; thence over rolling mesa top.
40.00	<p>Point for the ¼ sec. cor. of secs. 25 and 26. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W ¼ $\frac{S26}{S25}$ 1965</p>

CHAINS	
66.00	Small draw, drains E. about 2.00 chs. to rim.
70.00	Rim, bears irregularly E. and W. curving to NW.
74.40	Head of deep draw draining NE.
79.10	High narrow spur, projects N. 60° E.; desc. over steep NW. slope.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	<p>T38N R11W $\frac{S23}{S26}$ $\frac{S24}{S25}$ 1965</p>
	<p>Land, rolling and broken. Soil, rocky clay loam. No timber; undergrowth, sage, yellow brush, cactus and grass.</p>
	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp.</p>
	<p>N. 89°58' W., bet. secs. 24 and 25.</p>
	<p>Over rolling land.</p>
14.70	Canyon, about 3.00 chs. wide, drains NE.
25.90	Draw, drains NE.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p>T38N R11W $\frac{1}{4} \frac{S24}{S25}$ 1965</p>
	<p>The cor. is located on a steep E. slope.</p>
	<p>Raise a mound of stone N. of the cor.</p>
43.90	Desc. over W. slope.
51.70	Deep draw, drains N.
65.80	Wash, 50 lks. wide, 15-ft. banks, drains NE.
79.70	High narrow spur, projects N. 60° E.
80.24	The cor. of secs. 23, 24, 25 and 26.
	<p>Land, rolling and broken. Soil, clay loam and rocky. No timber; undergrowth, sage, black brush, yellow brush and cactus.</p>

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

6

6.

CHAINS		
	<p>N. 0°03' E., bet. secs. 23 and 24.</p> <p>Desc. over steep NW. slope.</p>	
10.60	Gully, 15 lks. wide, 6 ft. deep, drains NE.; continue over rolling land.	
29.90	Rim, bears N. 60° E. and SW.	
40.00	<p>Point for the ¼ sec. cor. of secs. 23 and 24.</p> <p>Set the iron post 4 ins. in the ground, mound with stones to the top, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ S23 S24 1965</p>	
44.50	Small spur, near end, slopes NE.	
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W S14 S13 S23 S24 1965</p> <p>The cor. is located on a gentle NE. slope.</p> <p>Land, rolling. Soil, clay loam and rocky. Timber, widely scattered juniper. Undergrowth, sage, blackbrush, yellow brush and cactus.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 89°59' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>	
9.70	Navajo trail (bladed dirt road), bears E. and NW. 2.00 chs. curving W.	
16.40	Small draw, drains N.	
35.80	Small draw, drains N. 30° E.	
40.11	<p>Point for the ¼ sec. cor. of secs. 13 and 24.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ $\frac{S13}{S24}$ 1965</p> <p>from which</p> <p>A metal water tank bears N. 40°39' W., 15.30 chs. dist.</p>	

CHAINS	
52.90	Draw, drains N.
72.30	Wash, 20 lks. wide, 2 ft. deep, drains NE.
78.70	Same wash, drains SE. curving to NE.; asc. over gentle NE. slope.
80.22	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling. Soil, rocky clay loam. Timber, widely scattered juniper. Undergrowth, blackbrush, sage, yellow brush and cactus.
	N. 0°03' E., bet. secs. 13 and 14.
	Desc. over gentle NE. slope.
3.00	Wash, 20 lks. wide, 1 ft. deep, drains S. 20° E.; asc. over S. slope.
8.00	Navajo trail, bears irregularly E. and W.
24.20	Top of ascent, bears E. and W.; desc. over N. slope.
33.20	Wash, 10 lks. wide, 3 ft. deep, drains E.; asc. over S. slope.
38.00	Low spur, slopes E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	Set the iron post 20 ins. in the ground, cap mkd.
	T38N R11W
	$\frac{1}{4}$ S14 S13 1965
	Raise a mound of stone W. of the cor.
42.10	Wash, 30 lks. wide, 3 ft. deep, drains SE.; asc. over S. slope.
50.70	High narrow spur, projects SE. about 2.00 chs. to end.
54.00	Wash in bottom of draw, 15 lks. wide, 2 ft. deep, drains S. 60° E.
59.90	Fence, barbed wire, bears E. and W.
72.50	Wash in bottom of draw, 20 lks. wide, 2 ft. deep, drains E.; thence over nearly level mesa through heavy sage brush.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set the iron post 20 ins. in the ground, cap mkd.
	T38N R11W
	$\frac{1}{4}$ S11 S12 S14 S13 1965

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

8

8.

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling to nearly level. Soil, clay loam and rocky. No timber; undergrowth, heavy sage, scattered yellow brush and cactus.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.</p> <p>S. 89°55' W., bet. secs. 12 and 13.</p> <p>Asc. over NE. slope.</p>
9.70	Narrow spur, projects S. 75° E.
15.80	East rim of mesa, bears E. and S. 60° W.; thence over gently rolling mesa top.
22.80	Fence, barbed wire, bears N. 55° E. and S. 55° W.
40.10	Point for the ¼ sec. cor. of secs. 12 and 13.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p>T38N R11W</p> <p>¼ $\frac{S12}{S13}$</p> <p>1965</p>
	<p>Raise a mound of stone N. of the cor.</p>
53.70	East rim of canyon, bears N. and S.; desc. over steep W. slope.
60.00	Wash in canyon bottom, 20 lks. wide, 3 ft. deep, drains N. 15° W.
67.60	West rim of canyon, bears S. 15° E. and N.; continue over point projecting N.
72.80	Head of draw, steep drainage to NE.; thence, over nearly level mesa.
80.20	The cor. of secs. 11, 12, 13 and 14.
	<p>Land, rolling and broken. Soil, clay loam and rocky. No timber; undergrowth, moderate black brush and sage, scattered cactus.</p> <hr/> <p>N. 0°03' E., bet. secs. 11 and 12.</p> <p>Over nearly level mesa top.</p>
2.00	Rim of mesa, bears E. and W.; desc. over steep N. slope.
13.90	Enter low rolling land, N. 15° E. drainage.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12.
	Set the iron post 20 ins. in the ground, cap mkd.

CHAINS	
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ S11 S12 1965</p> <p>Raise a mound of stone W. of the cor.</p>
42.70	Old trail road, bears N. 15° E. and S. 15° W.
50.00	Wash, 50 lks. wide, 2 ft. deep, drains NE.
62.80	Rocky spur, projects NE.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	<p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W S 2 S 1 S11 S12 1965</p> <p>Land, rolling. Soil, clay loam and limestone. Timber, scattered junipers. Undergrowth, sage, yellow brush, cactus and brigham tea.</p> <hr/> <p>From the true point for the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp.</p> <p>S. 89°52' W., bet. secs. 1 and 12.</p> <p>Over broken land, putting N.</p>
8.30	Wash, 40 lks. wide, steep ledgesides, drains N.; asc. over steep E. slope.
23.30	High ridge, bears N. and S.
29.30	Rocky draw, drains N. from SE.
39.90	Wash in bottom of draw, 10 lks. wide, 1 ft. deep, drains N. 70° W. curving to N.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
	<p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ $\frac{S 1}{S12}$ 1965</p> <p>Continue along rolling N. slope.</p>
44.90	Wash, 20 lks. wide, 2 ft. deep, drains NE.
53.60	Ridge, bears N. and S. curving to SE.; desc. over W. slope.
67.70	Wash, with trail road in the bottom, 30 lks. wide, 2 ft. deep, drains N. 20° E.
77.00	Small draw, drains N.

BOOK4775

Subdivision, T. 38 N., R. 11 W., Arizona

10

10.

CHAINS		
79.40	Top of rocky spur, slopes N.; desc. over rocky NW. slope.	
80.08	The cor. of secs. 1, 2, 11 and 12.	
	Land, rolling and broken. Soil, rocky and clay loam. Timber, scattered junipers. Undergrowth, black brush, sage, yellow brush, brigham tea and cactus.	
	N. 0°09' E., bet. secs. 1 and 2.	
	Desc. over NW. slope.	
6.70	Wash, 20 lks. wide, 1 ft. deep, drains NE.; asc. over SE. slope.	
18.20	S. rim of ridge, bears NE. and SW.	
23.30	Desc. along rolling W. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.	
	Set the iron post 4 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	T38N R11W $\frac{1}{4}$ S 2 S 1 1965	
	The cor. is located at the head of a small rocky draw draining W.	
40.60	Small finger spur, slopes W.	
59.70	Wash, 15 lks. wide, 1 ft. deep, drains NE. curving to E.	
74.00	Spur, slopes NE.	
80.34	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.	
	Land, rolling and broken. Soil, clay loam and rocky. Timber, scattered junipers. Undergrowth, sage, black brush, brigham tea and cactus.	
	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.	
	N. 0°03' E., bet. secs. 34 and 35.	
	Over gently rolling land.	
2.50	Fence, barbed wire, bears irregularly E. and W.	
4.50	Wash, 10 lks. wide, 2 ft. deep, drains S. 75° E.	

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

CHAINS	
4.80	Track road, bears irregularly E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Set the iron post 22 ins. in the ground, cap mkd.
	T38N R11W $\frac{1}{4}$ S34 S35 1965
	Raise a mound of stone W. of the cor.
58.00	Small draw, drains S. 70° E.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 20 ins. in the ground, cap mkd.
	T38N R11W S27 S26 S34 S35 1965
	Raise a mound of stone W. of the cor.
	Land, gently rolling. Soil, rocky clay loam. No timber; undergrowth, sage, black brush, yellow brush and cactus.
	<hr/> From the cor. of secs. 25, 26, 35 and 36.
	West, bet. secs. 26 and 35.
	Over gently rolling land.
21.50	Main road from St. George, Utah, to Mt. Trumble, Arizona, bears N. 25° W. and S. 25° E.; thence over bottom of Mainstreet Valley.
31.50	Man-made ditch, 10 lks. wide, 1 ft. deep, drains N. 25° W.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
	Set the iron post 20 ins. in the ground, cap mkd.
	T38N R11W $\frac{1}{4}$ $\frac{S26}{S35}$ 1965
	Raise a mound of stone N. of the cor.
79.98	The cor. of secs. 26, 27, 34 and 35.
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, sage and yellow brush.

BOOK4775

Subdivision, T. 38 N., R. 11 W., Arizona

12

12.

CHAINS		
	<p>N. 0°03' E., bet. secs. 26 and 27.</p> <p>Over gently rolling range land in Mainstreet Valley.</p>	
40.00	<p>Point for the ¼ sec. cor. of secs. 26 and 27.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ S27 S26 1965</p>	
63.20	<p>Raise a mound of stone W. of the cor.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains N. 80° E.</p>	
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R11W S22 S23 S27 S26 1965</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, blackbrush, sage and cactus.</p>	
	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°59' W., bet. secs. 23 and 26.</p> <p>Desc. over NW. slope.</p>	
7.40	<p>Gully, 20 lks. wide, 3 ft. deep, drains N. 70° E.</p>	
17.90	<p>Low ridge, bears N. and S.; desc. over W. slope.</p>	
39.97	<p>Point for the ¼ sec. cor. of secs. 23 and 26.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ $\frac{S23}{S26}$ 1965</p>	
	<p>Raise a mound of stone N. of the cor.</p>	
55.80	<p>Main road from St. George, Utah, to Mt. Trumble, Arizona, bears S. 24° E. and N. 24° W.</p>	
56.44	<p>Point for the witness point bet. secs. 23 and 26.</p> <p>Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W W P S23 S26 1965</p>	

CHAINS	
	Continue over nearly level land in Mainstreet Valley.
69.10	Wash, 30 lks. wide, 1 ft. deep, drains N. 20° W.
79.94	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling on E 1/2 mile, nearly level on remainder.
	Soil, clay loam and rocky.
	No timber; undergrowth, sage, black brush and yellow brush.
	N. 0°03' E., bet. secs. 22 and 23.
	Over nearly level range land.
32.90	Track road, bears E. and W. 8.60 chs. to Dutchman Tank.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ S22 S23 1965</p>
	from which
	<p style="text-align: center;">The center of dike, and track road, on the N. side of Dutchman Tank, bears S. 47°30' W., 11.67 chs. dist.</p>
	Raise a mound of stone W. of the cor.
49.00	Main road, from St. George, Utah, to Mt. Trumble, Arizona, bears S. 34° E. and N. 34° W.
51.40	Wash, 20 lks. wide, 2 ft. deep, drains S. 80° W. 1.20 chs. dist. to road.
70.10	Wash, 15 lks. wide, 3 ft. deep, drains W.; enter low rolling hills.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T38N R11W S15 S14 S22 S23 1965</p>
	Land, level to gently rolling.
	Soil, clay loam.
	No timber; undergrowth, black brush, sage, yellow brush, cactus and brigham tea.
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89°59' W., bet. secs. 14 and 23.
	Over rolling mountainous land.

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

14

14.

CHAINS		
13.30	Wash, 15 lks. wide, 2 ft. deep, drains N. about 2.00 chs. thence E.	
36.10	Small wash, drains S. circling to E.; asc. over SE. slope.	
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23. Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.	
	<p>T38N R11W $\frac{1}{4}$ $\frac{S14}{S23}$ 1965</p>	
	<p>from which</p> <p style="text-align: center;">U.S.C. & G.S. triangulation station PASS bears S. $13^{\circ}15'$ W., 21.44 chs. dist., monumented with a standard disk in a drill hole, stamped PASS 1953.</p>	
45.90	Top of hills, bears NE. and SW.; desc. over NW. slope.	
79.86	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, scattered junipers. Undergrowth, black brush, sage, cactus and grass.</p>	
	<hr/> <p>N. $0^{\circ}03'$ E., bet. secs. 14 and 15.</p>	
	<p>Over mountainous land; desc. over general N. slope.</p>	
2.90	Wash, 30 lks. wide, 2 ft. deep, drains N. 80° W. from N. 70° E.	
12.90	Bladed road, (Navajo trail) bears E. and W.	
14.50	Wash, 30 lks. wide, 1 ft. deep, drains W.	
20.00	Low ridge, bears E. and W.	
27.70	Wash; 10 lks. wide, 2 ft. deep, drains W.; asc. over S. slope.	
35.90	Top of ascent, bears E. and W.; desc. along NE. slope.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ S15 S14 1965</p>	
	<p>Raise a mound of stone W. of the cor.</p> <p>Continue over rolling land.</p>	
60.00	Barbed wire fence, bears E. and W.	

CHAINS	
66.60	Wash, 10 lks. wide, 2 ft. deep, drains W. Trail road in bottom of wash; asc. over rolling W. slope.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.
	T38N R11W $\begin{array}{c c} \hline S10 & S11 \\ \hline S15 & S14 \\ \hline \end{array}$ 1965
	Land, mountainous. Soil, rocky clay loam. Timber, scattered juniper. Undergrowth, sage, blackbrush, cactus and grass.
	<hr/> From the cor. of secs. 11, 12, 13 and 14 N. 89°58' W., bet. secs. 11 and 14. Asc. over gently rolling E. slope of mesa.
18.90	Small draw, drains N. 75° E.
25.00	Same draw, drains S. 70° E. curving to N. 75° E.
30.30	W. rim of mesa, bears S. and NE.; desc. over steep W. slope.
36.00	Desc. over gentle W. slope.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Set the iron post 20 ins. in the ground, cap mkd.
	T38N R11W $\frac{1}{4} \frac{S11}{S14}$ 1965
	Raise a mound of stone N. of the cor.
40.00	Old Navajo trail (track road), bears NE. and SW.
43.40	Dim track road, bears NW. and SE.
54.90	Small draw, drains S.
62.70	Wash in bottom of small draw, 20 lks. wide, 1 ft. deep, drains S. circling W.
69.50	Same draw, near head, drains N. 70° E.
73.80	Spur, slopes S.; desc. over W. slope.
79.90	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling and broken. Soil, clay loam and exposed limestone. Timber, scattered juniper. Undergrowth, blackbrush, sage, cacti and grass.

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

16

16.

CHAINS	
	<p>N. 0°03' E., bet. secs. 10 and 11.</p> <p>Asc. over low rolling hills.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>Set the iron post over an "X" cut in solid limestone, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ S10 S11 1965</p> <p>The cor. is located on a W. slope.</p>
64.00	<p>Track road, bears SE. and irregularly N.; continue over gently rolling E. slope.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W S 3 S 2 S10 S11 1965</p> <p>Land, rolling. Soil, clay loam and rocky. Timber, scattered juniper. Undergrowth, black brush, sage, cactus and grass.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°54' W., bet. secs. 2 and 11.</p> <p>Desc. over NW. slope.</p>
6.00	<p>Wash, 30 lks. wide, 1 ft. deep, drains irregularly NE.; asc. along draw draining from W.</p>
14.30	<p>Leave draw near head; asc. steep E. slope.</p>
27.30	<p>NE. end of high rocky hill, thence over N. end.</p>
36.90	<p>Leave hill, bears SW. and E.; desc. over NW. slope.</p>
39.94	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.</p> <p>Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ $\frac{S 2}{S11}$ 1965</p> <p>Desc. over W. slope.</p>
49.40	<p>Wash, 10 lks. wide, 1 ft. deep, drains N.; asc. over E. slope.</p>

CHAINS	
79.88	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, mountainous on E$\frac{1}{2}$, rolling on remainder. Soil, rocky and clay loam. Timber, scattered junipers. Undergrowth, black brush, sage, cactus and grass.</p>
	<p>N. 0°05' E., bet. secs. 2 and 3.</p> <p>Over gently rolling land.</p>
15.20	Spur, slopes E.
30.00	Low ridge, bears NE. and SW.
36.70	Small rocky spur, slopes NW.; desc. over N. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.</p> <p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ S 3 S 2 1965</p>
53.50	Head of ledged wash, 20 lks. wide, 3 ft. deep, drains N. 60° E.
62.50	Wash, 10 lks. wide, steep ledged sides, drains E.; thence over gently rolling land.
80.27	<p>The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p> <p>Land, rolling. Soil, clay loam and rocky. Timber, scattered juniper and pinon. Undergrowth, black brush, sage, cactus and grass.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey. The cor. is located 3 lks. N. of fence bearing irregularly E. and W.</p>
	N. 0°02' E., bet. secs. 33 and 34.
	Over rolling, slightly broken land; desc. over N. slope.
4.50	Wash, 10 lks. wide, 2 ft. deep, drains E. from SW.
11.80	Draw, drains S. 60° E.
30.30	Track road, bears NW. and SE.
31.40	Barbed wire fence, bears N. 47° W. and S. 47° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

CHAINS

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T38N R11W
 $\frac{1}{4}$
 S33|S34
 1965

Continue over gently rolling land through moderate undergrowth.

80.00

Point for the cor. of secs. 27, 28, 33 and 34.

Set the iron post 20 ins. in the ground, cap mkd.

T38N R11W
S28|S27
S33|S34
 1965

The cor. is located in a small draw draining NW.

Raise a mound of stone W. of the cor.

Land, rolling.

Soil, clay loam.

No timber; undergrowth, black brush, yellow brush, sage and grass.

From the cor. of secs. 26, 27, 34 and 35.

N. 89°58' W., bet. secs. 27 and 34.

Asc. over gentle E. slope of Mainstreet Valley.

4.20

Leave valley; continue over gently rolling land.

37.40

Desc. over NW. slope.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.

Set the iron post 20 ins. in the ground, cap mkd.

T38N R11W
 $\frac{1}{4}$ S27
 S34
 1965

Raise a mound of stone N. of the cor.

Continue over rolling land.

80.00

The cor. of secs. 27, 28, 33 and 34.

Land, gently rolling.

Soil, clay loam and rocky.

No timber; undergrowth, black brush, sage, yellow brush, cactus and grass.

N. 0°02' E., bet. secs. 27 and 28.

Over rolling land through moderate black brush.

CHAINS	
8.10	Shallow draw, drains irregularly NE.
28.30	Small draw, drains N. 70° E.
30.60	Low spur, slopes E. about 3.00 chs. to end.
34.40	Shallow wash, 200 lks. wide, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T38N R11W $\frac{1}{4}$ S28 S27 1965
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T38N R11W <u>S21 S22</u> <u>S28 S27</u> 1965
	Land, rolling. Soil, clay loam and rocky. No timber; undergrowth, black brush, sage, cactus and grass.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°58' W., bet. secs. 22 and 27.
	Over nearly level land in Mainstreet Valley.
21.00	Leave valley; enter gently rolling land.
36.10	Draw, drains NE.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T38N R11W $\frac{1}{4}$ <u>S22</u> <u>S27</u> 1965
43.30	Low spur, slopes NE.
58.90	Canyon rim, bears N. and S.; desc. over W. slope.
63.80	Small wash, drains N. 15° E.
66.50	Track road, bears N. and S.
70.00	Asc. over E. slope.

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

CHAINS		
78.70	Desc. over W. slope.	
80.08	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, nearly level to rolling. Soil, clay loam and rocky. No timber; undergrowth, black brush, sage, cactus and grass.</p>	
	<p>N. 0°02' E., bet. secs. 21 and 22.</p>	
	<p>Over rolling land through moderate undergrowth.</p>	
17.20	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.</p>	
22.50	<p>Track road, bears E. and W.</p>	
35.60	<p>Low ridge, bears E. and W.; desc. over N. slope.</p>	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ S21 S22 1965</p>	
	<p>Raise a mound of stone W. of the cor.</p>	
	<p>Continue over gently rolling land.</p>	
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set the iron post 8 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T38N R11W S16 S15 S21 S22 1965</p>	
	<p>Land, rolling. Soil, clay loam and rocky. No timber; undergrowth, black brush, sage, cactus and grass.</p>	
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>	
	<p>N. 89°59' W., bet. secs. 15 and 22.</p>	
	<p>Over rolling land.</p>	
6.60	<p>Wash, 10 lks. wide, 3 ft. deep, drains SW.</p>	
11.70	<p>Main road from St. George, Utah, to Mt. Trumble, Arizona, bears S. 20° E. and N. 20° W.</p>	
12.10	<p>Point for the witness point bet. secs. 15 and 22.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p>	

CHAINS	
	<p style="text-align: center;">T38N R11W W P <u>S15</u> S22 1965</p> <p>Thence, over nearly level bottom of Main Street Valley.</p>
23.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 20° W.
40.04	Point for the ¼ sec. cor. of secs. 15 and 22.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T38N R11W <u>¼ S15</u> S22 1965</p> <p>Raise a mound of stone N. of the cor.</p> <p>Leave valley; enter gently rolling land.</p>
47.40	Wash in bottom of small draw, 10 lks. wide, 1 ft. deep, drains N. 20° E.
56.80	Low ridge, bears NE. and S. 70° W.
68.40	Shallow, grassy draw, drains N. 60° E.
75.50	Low ridge, bears NE. and S. 60° W.
80.08	The cor. of secs. 15, 16, 21 and 22.
	<p>Land, nearly level to rolling. Soil, clay loam. No timber; undergrowth, black brush, sage, cactus and grass.</p> <hr/> <p>N. 0°02' E., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
4.30	Shallow draw, drains NE.
15.00	Low spur, slopes E.
18.10	Head of small rocky draw draining E.
40.00	Point for the ¼ sec. cor. of secs. 15 and 16.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T38N R11W <u>¼ S16</u> S15 1965</p> <p>The cor. is located in the bottom of wide draw draining NE.</p> <p>Raise a mound of stone W. of the cor.</p>

BOOK4775

Subdivision, T. 38 N., R. 11 W., Arizona

22

22.

CHAINS		
60.00	Barbed wire fence, bears E. and W.	
75.00	Desc. along E. slope.	
80.00	Point for the cor. of secs. 9, 10, 15 and 16.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T38N R11W $\begin{array}{c c} \text{S } 9 & \text{S10} \\ \hline \text{S16} & \text{S15} \end{array}$ 1965	
	Raise a mound of stone W. of the cor.	
	Land, rolling. Soil, clay loam and rocky. No timber; undergrowth, black brush, sage, cactus and grass.	
	From the cor. of secs. 10, 11, 14 and 15.	
	N. 89°56' W.; bet. secs. 10 and 15.	
	Over rolling mountainous land; desc. over W. slope.	
7.20	Wash, 10 lks. wide, 2 ft. deep, drains S.; asc. over E. slope.	
11.20	Low ridge, bears N. 20° E. and S.; desc. over W. slope.	
17.50	Shallow wash, 30 lks. wide, drains S.	
25.60	Ridge, bears N. 15° E. and S.; desc. over steep W. slope.	
32.10	Enter gently rolling land in Main Street Valley.	
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T38N R11W $\frac{1}{4} \frac{\text{S10}}{\text{S15}}$ 1965	
	Raise a mound of stone N. of the cor.	
54.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 30° E.	
63.80	Main road from St. George, Utah, to Mt. Trumble, Arizona, bears S. 38° E. and N. 38° W.	
68.00	Track road, bears N. and S.; leave valley.	
80.14	The cor. of secs. 9, 10, 15 and 16.	
	Land, mountainous on E. 30 chs., gently rolling on remainder. Soil, clay loam and rocky. Timber, widely scattered juniper on E. 32 chs. Undergrowth, black brush, sage, snake weed, cactus and grass.	

CHAINS	
	N. 0°02' E., bet. secs. 9 and 10.
	Over rolling land.
9.80	Main road from St. George, Utah, to Mt. Trumble, Arizona, bears E. and W.; thence over rolling land, NE. drainage.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set the iron post 20 ins. in the ground, cap mkd.
	<div style="text-align: center;">T38N R11W</div>
	<div style="text-align: center;">$\frac{1}{4}$</div>
	<div style="text-align: center;">S 9 S10</div>
	<div style="text-align: center;">1965</div>
	The cor. is located in a shallow draw draining NE.
	Raise a mound of stone W. of the cor.
53.80	Wash, 20 lks. wide, 4 ft. deep, drains E.
78.50	Shallow draw, drains NE.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 20 ins. in the ground, cap mkd.
	<div style="text-align: center;">T38N R11W</div>
	<div style="text-align: center;">S 4 S 3</div>
	<div style="text-align: center;">S 9 S10</div>
	<div style="text-align: center;">1965</div>
	Raise a mound of stone W. of the cor.
	Land, gently rolling.
	Soil, fine gravel and clay.
	Timber, widely scattered juniper.
	Undergrowth, heavy sage and black brush, scattered
	snakeweed, cactus and grass.
	<hr/>
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89°57' W., bet. secs. 3 and 10.
	Asc. over gentle E. slope.
2.60	Track road on top of ridge, bears irregularly N. and S.; desc. over broken W. slope through scattered juniper.
24.20	Leave timber, enter gently rolling land in Main Street Valley.
38.60	Man-made ditch, 15 lks. wide, 2 ft. deep, drains N. from S. 30° E.
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	Set the iron post 22 ins. in the ground, cap mkd.
	<div style="text-align: center;">T38N R11W</div>
	<div style="text-align: center;">$\frac{1}{4}$ S 3</div>
	<div style="text-align: center;">S10</div>
	<div style="text-align: center;">1965</div>

CHAINS		
	<p>from which</p> <p>The center of fenced pond (Larson Blake Tank) bears N. $13\frac{1}{4}^{\circ}$ W., 8.40 chs. dist.</p> <p>The center of fenced pond (Larson Blake Tank) bears N. $12\frac{1}{2}^{\circ}$ W., 11.90 chs. dist.</p> <p>Raise a mound of stone N. of the cor.</p>	
40.40	Track road, bears NE. and SW.	
41.60	Track road, bears N. and S.	
42.10	Track road, bears S. 20° E. and N.	
53.60	Leave valley; asc. over E. slope.	
70.60	Low spur, slopes N.; enter scattered juniper.	
77.90	Shallow draw, drains NE.	
80.14	The cor. of secs. 3, 4, 9 and 10.	
	<p>Land, mountainous on E. 25 chs., gently rolling on remainder.</p> <p>Soil, clay loam and rocky.</p> <p>Timber, scattered juniper on each end.</p> <p>Undergrowth, black brush, sage, cactus, snakeweed and grass.</p>	
	<p>N. $0^{\circ}13'$ E., bet. secs. 3 and 4.</p> <p>Asc. along gentle SE. slope.</p>	
6.50	Low spur, slopes NE.; desc. over N. slope.	
15.70	Wash, 10 lks. wide, 1 ft. deep, drains S. 75° E.; thence over rolling land.	
21.30	Spur, slopes S. 30° E.	
28.70	Draw, drains E.	
33.90	Small draw, drains S. 75° E.	
38.70	Small draw, drains E.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	<p style="text-align: center;">T38N R11W</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 4 S 3</p> <p style="text-align: center;">1965</p>	
	Raise a mound of stone W. of the cor.	
41.70	Wash, 10 lks. wide, 3 ft. deep, drains N. 70° E.	
49.60	Shallow draw, drains NE.	

CHAINS	
51.80	Small spur, slopes E.
80.30	<p>The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p> <p>Land, gently rolling. Soil, clay loam. Timber, widely scattered juniper. Undergrowth, black brush, sage, cactus and grass.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey. The cor. is located in a fence bearing E. and W.</p>
	<p>N. 0°01' E., bet. secs. 32 and 33.</p>
	<p>Over rolling land through moderate undergrowth.</p>
7.20	Draw, drains N. 65° E.
17.60	Draw, drains NE.
29.30	Shallow draw, 1.00 chain wide, drains S. 75° E.
32.50	Low spur, slopes S. 75° E.
37.70	Shallow draw, drains S. 70° E.; asc. over gentle S. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p>T38N R11W $\frac{1}{4}$ S32 S33 1965</p>
47.80	Low spur, slopes NE.
56.80	Draw, drains N. 30° E.
62.40	Top of low rocky spur sloping N. 30° E.
71.80	Rocky spur, projects N. 60° E.
79.00	Draw, drains E.
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p>T38N R11W S29 S28 S32 S33 1965</p>
	<p>Raise a mound of stone W. of the cor.</p>

CHAINS	
	<p>Land, gently rolling. Soil, clay loam and rocky. No timber; undergrowth, black brush, sage, cactus and grass.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34. N. 89°58' W., bet. secs. 28 and 33. Over low rolling hills through heavy sage.</p>
3.80	Draw, drains N. 30° E.
9.70	Low ridge, bears N. 15° E. and S. 15° W.
13.50	Fence, bears N. and S.
13.70	Track road, bears N. and S.
14.10	Draw, drains N.
17.70	Low spur, slopes N.
23.70	Draw, drains N. 20° W.
25.90	Small spur, slopes N.
31.50	Small spur, slopes N.
35.50	Draw, drains NE.; asc. over E. slope.
40.00	<p>Point for the ¼ sec. cor. of secs. 28 and 33. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W ¼ $\frac{S28}{S33}$ 1965</p> <p>from which</p> <p style="text-align: center;">A stock pond (Hard Pan), bears N. 52°45' E., 16.60 chs. dist.</p>
45.00	Spur, slopes NE.
59.00	Draw, drains N. 60° E. from irregularly W.
64.40	Small finger spur, slopes S. 1.00 chain to end.
68.20	Enter bottom of same draw, drains from W.
80.00	<p>The cor. of secs. 28, 29, 32 and 33. Land, low rolling hills. Soil, clay loam and rocky. No timber; undergrowth, heavy sage brush, scattered thimbleberry, buck brush and cactus.</p> <hr/>

CHAINS	
	N. 0°01' E., bet. secs. 28 and 29. Over rolling land through heavy undergrowth.
12.60	Small draw, drains E.
38.40	Rocky draw, drains NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29. Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd. T38N R11W $\frac{1}{4}$ S29 S28 1965
51.90	Wash, 10 lks. wide, 1 ft. deep, drains NE.
52.50	Track road, bears NE. and SW.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 20 ins. in the ground, cap mkd. T38N R11W S20 S21 S29 S28 1965 Raise a mound of stone W. of the cor. Land, rolling. Soil, clay loam and rocky. Timber, widely scattered juniper. Undergrowth, heavy sage brush, scattered buck brush, cactus, yellow brush and grass.
	From the cor. of secs. 21, 22, 27 and 28. N. 89°58' W., bet. secs. 21 and 28. Over rolling land.
4.00	Shallow draw, drains N.
8.00	Fence, bears N. and S.
29.00	Track road, bears NE. and SW.
29.30	Small wash, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28. Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd. T38N R11W $\frac{1}{4}$ $\frac{S21}{S28}$ 1965 from which

BOOK4775

Subdivision, T. 38 N., R. 11 W., Arizona

28

28.

CHAINS	
	<p>A stock pond (West Dutchman), bears N. 10°36' E., 19.65 chs. dist.</p> <p>A corral bears N. 32°50' W., 26.30 chs. dist.</p> <p>Raise a mound of stone N. of the cor.</p>
41.50	Top of knoll.
52.50	Wash, 10 lks. wide, 1 ft. deep, drains NE.
59.60	Track road, bears NE. and SW.; asc. over E. slope.
74.10	Low rocky ridge, bears N. and S.
80.00	The cor. of secs. 20, 21, 28 and 29.
	<p>Land, rolling. Soil, clay loam and rocky. No timber; undergrowth, sagebrush, black brush, cactus, buck brush and grass.</p>
	<p>N. 0°01' E., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p>
10.00	Low spur, slopes W. 1.00 chain to end.
14.20	Small wash, drains N. 50° E.; thence over bottom of valley bearing E. and W.
23.60	Small wash, drains S. 80° E.
28.00	Track road, bears S. 70° E. and N. 70° W.
28.90	Small wash, drains S. 70° E.; leave valley, asc. over gentle S. slope.
38.60	Asc. along gentle W. slope.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T38N R11W 1/4 S20 S21 1965</p>
	<p>Raise a mound of stone W. of the cor.</p> <p>Asc. over SW. slope.</p>
44.60	Spur, slopes N. 60° W.
52.90	Small draw, drains W.
71.20	Draw, drains NE.
73.90	Small spur, slopes E.
77.10	Draw, drains E.; asc. over gentle S. slope.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.

CHAINS

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T38N R11W
 S17 | S16
 S20 | S21
 1965

Land, gently rolling.
 Soil, rocky clay loam.
 No timber; undergrowth, heavy sage, scattered buck brush and cactus.

From the cor. of secs. 15, 16, 21 and 22.

N. 89°59' W., bet. secs. 16 and 21.

Over gently rolling land.

3.20 Wash, 10 lks. wide, 1 ft. deep, drains N.

6.10 Spur, slopes N.

11.80 Fence, bears S. and N. 2.20 chs., thence NW.

29.40 Draw, drains N.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set the iron post 18 ins. in the ground, cap mkd.

T38N R11W
 $\frac{1}{4}$ $\frac{S16}{S21}$
 1965

Raise a mound of stone N. of the cor.

43.90 Desc. over W. slope.

49.60 Wash, 10 lks. wide, 1 ft. deep, drains N.

73.60 Wash, 10 lks. wide, 1 ft. deep, drains NE.

79.96 The cor. of secs. 16, 17, 20 and 21.

Land, gently rolling.
 Soil, clay loam and rocky.
 No timber; undergrowth, sagebrush, buck brush, cactus and grass.

N. 0°01' E., bet. secs. 16 and 17.

Asc. over gentle S. slope through heavy undergrowth.

9.00 Ridge, bears N. 60° E. and S. 80° W.; desc. over rolling N. slope.

20.20 Draw, drains E. curving NE.

27.00 Small spur, slopes E.

29.20 Small draw, drains E. about 3.00 chs., thence SE.

CHAINS	
35.00	Spur, slopes E.
37.70	Small draw, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T38N R11W $\frac{1}{4}$ S17 S16 1965
40.50	Spur, slopes S. 80° E.
47.60	Draw, drains S. 80° E.
51.30	Spur, slopes S. 70° E.
53.20	Draw, drains S. 70° E. curving to SE.
58.00	Ridge, bears E. and W.
60.00	Fence, bears E. and W.; desc. N. slope.
62.60	Enter nearly level land.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set the iron post 20 ins. in the ground, cap mkd. T38N R11W S 8 S 9 S17 S16 1965 Raise a mound of stone W. of the cor. Land, gently rolling. Soil, rocky clay loam. Timber, widely scattered juniper. Undergrowth, sage brush, buck brush and cactus.
<hr/>	
	From the cor. of secs. 9, 10, 15 and 16. N. 89°59' W., bet. secs. 9 and 16. Asc. over E. slope.
4.60	Spur, slopes N.; desc. over W. slope.
8.00	Enter small valley bearing N. 70° E. and W.
20.00	Wash, 10 lks. wide, 1 ft. deep, drains NE.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set the iron post 20 ins. in the ground, cap mkd. T38N R11W $\frac{1}{4}$ S 9 S16 1965

CHAINS	
	<p>Raise a mound of stone N. of the cor.</p> <p>Asc. over gentle E. slope.</p>
58.50	Leave valley, continue over gently rolling land.
79.94	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling to nearly level. Soil, clay loam and rocky. Timber, widely scattered juniper. Undergrowth, sage brush and grass.</p>
	<p>N. 0°01' E., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p>
3.70	Shallow draw, drains NE.
10.00	Low spur, slopes NE.
28.10	Small wash, drains N. 70° E.
30.00	Main road from St. George, Utah, to Mt. Trumble, Arizona, bears S. 43° E. and N. 60° W.; asc. over gentle S. slope.
34.00	Enter scattered junipers.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ S 8 S 9 1965</p>
	<p>from which</p> <p style="padding-left: 40px;">A stock pond bears S. 41°39' E., 14.83 chs. dist.</p>
41.10	Track road, bears N. 20° E. and S. 20° W.
49.60	Spur, slopes E.; leave timber.
52.80	Draw, drains irregularly SE.
57.70	Spur, slopes SE.
63.60	Draw, near head, drains E. 4.00 chs., thence SE.
71.00	Ridge, bears E. and W.
74.40	Desc. over N. slope.
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T38N R11W S 5 S 4 S 8 S 9 1965</p>

BOOK4775

Subdivision, T. 38 N., R. 11 W., Arizona

CHAINS		
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam and rocky. Timber, small clumps of scattered juniper. Undergrowth, medium to dense sage, scattered buck brush.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land.</p>	
11.70	Ridge, bears SE. and NW.	
19.50	Spur, slopes NE.	
23.30	Wash, 10 lks. wide, 1 ft. deep, drains NE.	
25.80	Spur, slopes N.	
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	<p>T38N R11W</p> <p>$\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$</p> <p>1965</p>	
	Raise a mound of stone N. of the cor.	
44.80	Small wash in bottom of draw, drains NE.; asc. over steep E. slope.	
52.30	Ridge, bears SE. and NW.	
58.30	Draw, drains N.	
67.10	Spur, slopes N.	
70.90	Wash, 10 lks. wide, 1 ft. deep, drains N.	
75.10	Spur, slopes NW.	
79.96	The cor. of secs. 4, 5, 8 and 9.	
	<p>Land, rolling hills. Soil, rocky clay loam. No timber; undergrowth, medium sage, scattered buck brush and grass.</p> <hr/> <p>N. 0°12' E., bet. secs. 4 and 5.</p> <p>Over gently rolling land through moderate undergrowth.</p>	
1.20	Bottom of draw, drains NE. from W.	
7.90	Spur, slopes NE.	
13.20	Draw, drains N. 60° E.	
26.70	Draw, drains E.	

CHAINS	
30.10	Spur, slopes E.
37.50	Draw, drains E.; asc. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set the iron post 18 ins. in the ground and in a collar of stone, cap mkd.
	T38N R11W $\frac{1}{4}$ S 5 S 4 1965
	Raise a mound of stone W. of the cor.
42.40	Ledgy rim, 6 ft. high, bears E. and W.; thence over rolling land draining E.
44.90	Point, projects E. about 2.00 chs. dist.
51.20	Spur, slopes E.
55.30	Draw, drains E.
58.90	Spur, slopes E.
63.80	Bottom of large draw, drains S. 60° E.
69.90	Rocky spur, slopes W.
73.90	Draw, drains S. 15° W., curving to SW.
77.90	Same draw, drains S. 15° E. from NW.
80.30	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.
	Land, rolling. Soil, clay loam and rocky. Timber, widely scattered juniper. Undergrowth, sage brush and cactus.
	<hr/> From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey. This cor. is located in a fence bearing E. and irregularly W.
	N. 0°01' E., bet. secs. 31 and 32.
	Over nearly level land through moderate undergrowth and scattered timber.
18.70	Shallow draw, drains NE.
26.90	Spur, slopes N. 30° E.; finger spur slopes N.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

34

34.

CHAINS		
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ S31 S32 1965</p>	
	<p>Continue desc. over N. slope.</p>	
45.40	<p>Bottom of large draw, drains NE.</p>	
54.90	<p>Spur, slopes E.</p>	
61.20	<p>Small draw, drains E.</p>	
77.50	<p>Small draw, drains E.</p>	
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p>	
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p style="text-align: center;">T38N R11W <u>S30 S29</u> <u>S31 S32</u> 1965</p>	
	<p>Land, low rolling hills. Soil, rocky clay loam. Timber, scattered to widely scattered junipers. Undergrowth, dense sage, scattered buck brush, thimble-berry and cactus.</p>	
	<hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p>	
	<p>S. 89°59' W., bet. secs. 29 and 32.</p>	
	<p>Over rolling land through moderate undergrowth.</p>	
	<p>Asc. along the bottom of draw draining from the west.</p>	
7.00	<p>Leave draw, main one drains from SW., small draw drains from NW.; asc. along rolling SE. slope.</p>	
16.10	<p>Slope changes to rolling E.; ascend.</p>	
39.99	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.</p>	
	<p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ $\frac{S29}{S32}$ 1965</p>	
44.00	<p>Ridge, bears N. 15° E. and S. 15° W.</p>	
58.20	<p>Draw, drains irregularly NE. from S. 70° W.; thence over rolling S. slope.</p>	
73.70	<p>Draw, drains SE.</p>	
76.40	<p>Small spur, slopes SE.; asc. along general S. slope.</p>	
79.98	<p>The cor. of secs. 29, 30, 31 and 32.</p>	

CHAINS	
	<p>Land, low rolling hills. Soil, clay loam and rocky. Timber, widely scattered juniper. Undergrowth, dense sage, scattered buck brush, thimbleberry and cactus.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling land through moderate undergrowth.</p> <p>Asc. over rolling S. slope.</p> <p>7.90 Desc. gentle SW. slope.</p> <p>13.70 Draw, drains SE. curving to E.; asc. over E. slope.</p> <p>22.50 Ridge, bears N. and S.; desc. over steep, rocky W. slope.</p> <p>37.50 East edge of wide valley bearing N. and S.; thence, over gently rolling land.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ $\frac{S30}{S31}$ 1965</p> <p>Raise a mound of stone N. of the cor.</p> <p>77.80 Small wash, drains N. 20° W.</p> <p>78.00 Track road, bears N. and S.</p> <p>78.28 The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the 1934 resurvey. This cor. is located in a fence bearing N. and S. at the NE. cor. of a fenced stock pond.</p> <p>Land, mountainous on E 1/2 mile, nearly level on remainder. Soil, clay loam and rocky. No timber; undergrowth, moderate sage, scattered buck brush and cactus.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°01' E., bet. secs. 29 and 30.</p> <p>Asc. over S. slope through moderate undergrowth.</p> <p>.70 Spur, slopes E.; desc. over NE. slope.</p> <p>6.00 Draw, drains S. 70° E.; asc. over S. slope.</p> <p>10.40 Rocky rim, bears N. 70° W. and S. 70° E.; thence over rolling land.</p>

BOOK4775

Subdivision, T. 38 N., R. 11 W., Arizona

36

36.

CHAINS		
16.00	Spur, slopes NE.	
21.50	Draw, drains N. 30° E.	
26.10	Spur, slopes E.	
34.00	Draw, drains S. 70° E. curving to SE.	
40.00	Point for the ¼ sec. cor. of secs. 29 and 30.	
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.	
	T38N R11W ¼ S30 S29 1965	
40.50	Narrow divide, bears E. and W.; desc. along small draw draining N.	
45.30	Draw, curves to N. 15° E.	
53.10	Draw, drains N. 80° E. curving to NE.	
60.00	Spur, slopes E.	
64.00	Draw, drains E.	
67.20	Spur, slopes E.	
69.70	Draw, drains E.	
73.20	Spur, slopes E.	
79.00	Shallow draw, near head, drains N. 80° E. curving to NE.	
80.00	Point for the cor. of secs. 19, 20, 29 and 30.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T38N R11W S19 S20 S30 S29 1965	
	Raise a mound of stone W. of the cor.	
	Land, low rolling hills. Soil, clay loam and rocky. No timber; undergrowth, dense sage, scattered buck brush, thimbleberry and cactus.	
	<hr/> From the cor. of secs. 20, 21, 28 and 29. S. 89°58' W., bet. secs. 20 and 29. Over rolling land through dense undergrowth.	
.80	Small wash, drains N.	
7.70	Draw, drains N. 30° E.	
12.70	Spur, slopes NE.	

CHAINS	
17.00	Draw, drains NE.
32.00	Spur, slopes NE.
37.70	Head of draw draining N. 30° E.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.
	Set the iron post 20 ins. in the ground, cap mkd.
	T38N R11W $\frac{1}{4}$ $\frac{S20}{S29}$ 1965
	Raise a mound of stone N. of the cor.
54.20	Spur, slopes N. from SW.
58.60	Draw, drains N.
61.20	Finger spur, slopes N.
69.00	Low flat spur, slopes NE.
77.20	Shallow draw, drains NE.
79.98	The cor. of secs. 19, 20, 29 and 30.
	Land, low rolling hills. Soil, clay loam and rocky. Timber, widely scattered juniper. Undergrowth, dense sage brush, scattered buck brush, thimbleberry, snakeweed and cactus.
	West, bet. secs. 19 and 30.
	Over rolling land through dense undergrowth.
2.20	Spur, slopes N. 60° E.
5.50	Draw, drains N. 30° E.; asc. over E. slope.
15.10	Spur, slopes N.; desc. along rolling N. slope.
23.00	Spur, slopes NW.; desc. over W. slope.
37.00	East edge of wide valley, bears N. and S.; thence over gently rolling land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.
	Set the iron post 20 ins. in the ground, cap mkd.
	T38N R11W $\frac{1}{4}$ $\frac{S19}{S30}$ 1965
	Raise a mound of stone N. of the cor.
46.70	Track road, bears N. 48° E. and S. 42° W.
78.26	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 resurvey. This cor. is located alongside a fence bearing N. and S.

CHAINS	
	<p>Land, low rolling hills on E 1/2 mile, nearly level on remainder. Soil, clay loam and rocky. No timber; undergrowth, dense sage, moderate snakeweed, scattered buck brush and cactus.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30. N. 0°01' E., bet. secs. 19 and 20. Asc. over gentle SE. slope.</p>
1.00	Spur, slopes N. 60° E.; desc. over gentle N. slope.
15.70	Small wash, drains N. 80° E.
16.70	Track road, bears N. 80° E. and S. 80° W.; thence over gently rolling land facing S.
29.10	Wash, 10 lks. wide, 1 ft. deep, drains E.
36.70	Spur, slopes S. 70° E.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20. Set the iron post 20 ins. in the ground, cap mkd.
	<p>T38N R11W 1/4 S19 S20 1965</p>
	The cor. is located in a draw draining S. 60° E.
44.00	Spur, slopes S. 60° E.
51.60	Draw, drains E.
54.80	Rocky spur, slopes S. 70° E.
58.30	Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E.
66.20	Large spur, slopes E.; desc. along the W. side of spur sloping N.
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	<p>T38 N R11W S18 S17 S19 S20 1965</p>
	<p>Land, rolling hills. Soil, clay loam and rocky. Timber, scattered junipers. Undergrowth, dense sage brush, scattered buck brush, thimbleberry and cactus.</p> <hr/>

CHAINS		
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°55' W., bet. secs. 17 and 20.</p> <p>Over rolling land through heavy undergrowth.</p>	
6.20	Small draw, drains SE.	
10.40	Top of small knoll; thence over gently rolling land.	
29.80	Track road, bears SE. and NW.	
40.00	Point for the ¼ sec. cor. of secs. 17 and 20.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	<p>T38N R11W</p> <p>¼ $\frac{S17}{S20}$</p> <p>1965</p>	
	Raise a mound of stone N. of the cor.	
61.10	Spur, slopes NE.	
63.90	Small wash, drains NE.	
70.80	Spur, slopes N.	
74.50	Draw, drains N.	
78.80	Spur, slopes N.	
80.00	The cor. of secs. 17, 18, 19 and 20.	
	<p>Land, rolling.</p> <p>Soil, rocky clay loam.</p> <p>Timber, widely scattered junipers.</p> <p>Undergrowth, dense sagebrush, scattered buck brush, thimbleberry and cactus.</p>	
	<hr/>	
	N. 89°56' W., bet. secs. 18 and 19.	
	Desc. over W. slope.	
7.00	Wash, in bottom of draw, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope.	
12.70	Spur, slopes N. 30° E.; continue over rolling land.	
17.60	Spur, slopes NE.	
20.30	Wash, 10 lks. wide, 1 ft. deep, drains NE.	
27.60	Spur, slopes NE.	
33.50	Ridge, bears N. and S.; desc. over W. slope.	
37.20	Draw, drains N. 15° W.; asc. over E. slope.	
40.00	Point for the ¼ sec. cor. of secs. 18 and 19.	
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

40

40.

CHAINS		
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ $\frac{S18}{S19}$ 1965</p>	
	<p>The cor. is located on a spur sloping N. 15° W.</p>	
	<p>Desc. over steep W. slope.</p>	
48.50	<p>East edge of valley bearing N. and S.; continue over gently rolling land.</p>	
61.10	<p>Wash, 20 lks. wide, 1 ft. deep, drains S. 60° W.</p>	
78.27	<p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 resurvey.</p>	
	<p>Land, rolling hills on 48.00 chs., nearly level on remainder. Soil, clay loam and rocky. Timber, scattered junipers. Undergrowth, dense sage brush, scattered buck brush, cactus and snakeweed.</p>	
	<p>From the cor. of secs. 17, 18, 19 and 20.</p>	
	<p>N. 0°01' E., bet. secs. 17 and 18.</p>	
	<p>Desc. over N. slope through scattered junipers.</p>	
13.80	<p>Wash, in bottom of draw, 20 lks. wide, 1 ft. deep, drains irregularly E. from SW.; thence over the end of spur sloping from NW.</p>	
20.80	<p>Wash, 5 lks. wide, 1 ft. deep, drains S. 15° E.; asc. over rocky S. slope.</p>	
28.60	<p>Ridge, bears E. and W.</p>	
34.90	<p>Small wash, drains NW.</p>	
37.80	<p>Small spur, slopes NW.</p>	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18. Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p style="text-align: center;">T38N R11W $\frac{1}{4}$ S18 S17 1965</p>	
47.20	<p>Bottom of rocky draw, drains E.</p>	
51.20	<p>Rocky spur, slopes N. 60° E.</p>	
52.30	<p>Desc. over ledge, 10 ft. high, facing N.; thence over gently rolling land.</p>	
55.90	<p>Small wash, drains E.</p>	

CHAINS	
60.17	Fence, bears E. and W.
65.90	Wash, 10 lks. wide, 2 ft. deep, drains NE.
70.10	Wash, 10 lks. wide, 1 ft. deep, drains E.
71.60	Wash, 10 lks. wide, 1 ft. deep, drains E.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T38N R11W $\frac{S\ 7}{S18} \frac{S\ 8}{S17}$ 1965</p>
	<p>Land, rolling. Soil, rocky clay loam. Timber, scattered junipers. Undergrowth, dense sagebrush, scattered buck brush, thimbleberry and cactus.</p>
	<hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p>
	S. 89°55' W., bet. secs. 8 and 17.
	Over rolling land through moderate undergrowth.
5.00	Shallow draw, drains NE.
25.30	Low ridge, bears NE. and SW.
32.20	Fence, bears S. 37° E. and N. 37° W.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T38N R11W $\frac{1}{4} \frac{S\ 8}{S17}$ 1965</p>
46.10	Wash, 15 lks. wide, 1 ft. deep, drains NE.
59.50	Small flat-topped knoll.
65.60	Wash, 10 lks. wide, 1 ft. deep, drains N.
68.40	Track road, bears N. 30° W. and S. 30° E.; asc. over E. slope.
79.96	The cor. of secs. 7, 8, 17 and 18.
	<p>Land, gently rolling. Soil, clay loam and rocky. Timber, scattered junipers. Undergrowth, dense sage brush, scattered buck brush and cactus.</p>

CHAINS	
	N. 89°55' W., bet. secs. 7 and 18. Over rolling land; asc. over E. slope.
6.20	Ridge, bears N. and S.
11.90	Small wash, drains N.
19.40	Spur, slopes NE.
26.60	Wash, 10 lks. wide, 1 ft. deep, drains N.
35.20	Wash, 10 lks. wide, 2 ft. deep, drains NE.
35.30	Trail road, bears N. 50° E. and S. 50° W.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18. Set the iron post 22 ins. in the ground, cap mkd.
	T38N R11W ¼ $\frac{S\ 7}{S18}$ 1965
	Raise a mound of stone N. of the cor.
41.80	Small wash, drains SE.
51.33	Ridge, bears N. 30° W. and S. 30° E.; desc. along N. side of spur sloping W.
66.80	E. side of valley bearing irregularly N. and S.; continue over gently rolling land.
73.30	Fence, on E. side of experimental plot, about 5.00 chs. square, bears N. and S.; thence through the center of plot.
78.31	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 resurvey. This cor. is located on the W. side of experimental plot, in a fence bearing N. and S. Land, rolling to nearly level. Soil, clay loam and rocky. Timber, scattered junipers. Undergrowth, dense sage brush, scattered buck brush and cactus.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°01' E., bet. secs. 7 and 8. Over gently rolling E. slope through scattered timber.
10.60	Small spur, slopes E.
16.90	Track road, bears SE. and NW.
26.60	Wash, 10 lks. wide, 1 ft. deep, drains NE.
37.70	Top of small hill.

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W $\frac{1}{4}$ S 7 S 8 1965</p> <p>from which</p> <p style="padding-left: 40px;">A stock pond bears N. 70° E., 12.00 chs. dist.</p>
42.60	Wash, 10 lks. wide, 3 ft. deep, drains E.
43.60	Small wash, drains E.
44.90	<p>Point for the witness point bet. secs. 7 and 8.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T28N R11W W P S 7 S 8 1965</p> <p>Raise a mound of stone W. of the cor.</p>
45.30	Main road from St. George, Utah, to Mt. Trumble, Arizona, bears E. and W.
49.20	Spur, slopes E.
51.70	Wash, 10 lks. wide, 2 ft. deep, drains SE.
57.10	Spur, slopes SE.
60.20	Small wash, drains E.
62.10	Spur, slopes E.
63.60	Draw, drains SE.
68.30	Fence, bears S. 35° E. and N. 35° W.
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T38N R11W S 6 S 5 S 7 S 8 1965</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling to nearly level. Soil, clay loam and rocky. Timber, scattered juniper. Undergrowth, dense sage brush, scattered buck brush and cactus.</p>

BOOK 4775

Subdivision, T. 38 N., R. 11 W., Arizona

44

44.

CHAINS	
	From the cor. of secs. 4, 5, 8 and 9.
	S. 89°56' W., bet. secs. 5 and 8.
	Along side of large draw draining from the W.
9.80	Small spur, slopes S.
15.80	Bottom of same draw, drains irregularly E. from SW.
20.30	Asc. over SE. slope.
30.50	Ridge, bears N. 30° E. and S. 30° W.
39.97	Point for the ¼ sec. cor. of secs. 5 and 8.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T38N R11W $\frac{1}{4} \frac{S \ 5}{S \ 8}$ 1965</p>
54.70	Draw, drains NE.
55.80	Spur, slopes N.
56.40	Enter gently rolling land.
79.94	The cor. of secs. 5, 6, 7 and 8.
	Land, rolling to gently rolling.
	Soil, clay loam and rocky.
	Timber, scattered junipers.
	Undergrowth, dense sage, scattered buck brush and cactus.
	N. 89°52' W., bet. secs. 6 and 7.
	Over gently rolling land through scattered junipers.
8.70	Fence, bears S. 40° E. and N. 40° W.; asc. along S. side of spur sloping from irregularly W.
23.30	Small draw, drains SE.
28.80	Top of spur, slopes irregularly E.; thence over mesa top.
37.10	Desc. over W. slope.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T38N R11W $\frac{1}{4} \frac{S \ 6}{S \ 7}$ 1965</p>
	from which

CHAINS	
	<p>U.S.C. & G.S. triangulation station WHITE bears S. 14°17' W., 14.16 chs. dist., monumented by a standard disk set in a drill hole, flush with the surface, mkd. WHITE 1953.</p> <p>The cor. is located in a small draw draining NE.</p>
52.40	East edge of valley bearing irregularly N. and S.; continue over gently rolling land.
56.50	Wash, 10 lks. wide, 2 ft. deep, drains NW.
60.30	Wash, 10 lks. wide, 2 ft. deep, drains NW.
67.70	Wash, 10 lks. wide, 2 ft. deep, drains NW.
78.10	Wash, 10 lks. wide, 6-ft. banks, drains irregularly S. 80° W.
78.26	<p>The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1934 resurvey.</p> <p>Land, rolling on E. 50 chs., gentle W. slope on remainder. Soil, clay loam and rocky. Timber, scattered juniper. Undergrowth, dense sage brush, scattered buck brush and cactus.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°12' E., bet. secs. 5 and 6.</p> <p>Over gently rolling land through scattered junipers.</p>
11.90	Draw, drains NE.
19.20	Wash, 20 lks. wide, 2 ft. deep, drains SE. from W.
26.50	Spur, slopes SE.
34.00	S. rim of small canyon about 40 ft. deep draining E.
36.10	N. rim, bears E. and W.
40.00	<p>Point for the ¼ sec. cor. of secs. 5 and 6.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T38N R11W ½ S 6 S 5 1965</p>
	Raise a mound of stone W. of the cor.
58.40	Draw, drains E.
70.90	Draw, drains NE.
74.20	Spur, slopes NE.

46

CHAINS	80.30 Track road, bears E. and W.
80.48	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.
	Land, low rolling hills. Soil, clay loam and rocky. Timber, scattered junipers. Undergrowth, sage brush, buck brush and cactus.
	General Description
	Township 38 North, Range 11 West, located on the Arizona Strip, varies about 800 feet in elevation, the average being approximately 5300 feet. The higher area, in the northeast, is broken hills and flat-topped mesas; the remainder, with the exception of the nearly level land along the extreme west side and Main Street Valley, is low rolling hills cut by numerous small washes and draws. Most of the drainage is toward Main Street Valley, which runs northerly through Section 35 on the south boundary, leaving through Section 3 on the north boundary.
	Scattered junipers, buck brush, black brush and cactus are found at the higher elevations, with sage brush the dominant vegetation throughout the township. A fair growth of native grass over most of the area, together with well located reservoirs, affords graze and water for livestock, which at present is the predominating interest.
	A good bladed road from St. George, Utah, to Mt. Trumble, Arizona, enters the township in Section 7, traversing easterly and leaving the township through Main Street Valley in Section 36. Numerous track roads and stock trails give access to most of the township.
	No minerals or mineral activity within the township were noted during the survey.

BOOK 4775

CERTIFICATE OF SURVEY

We Boyd S. Owens
Wallace R. Ott, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 1st day of July, 19 65,
we have retraced the east boundary and surveyed the subdivisional lines of
Township 38 North, Range 11 West

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by ~~me~~ ^{us} and under ~~my~~ ^{our} direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

January 26, 1966
(Date)

Boyd S. Owens
(Cadastral Surveyor)

January 26, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date AUG 11 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the retracement of the east boundary and survey of
the subdivisional lines of Township 38 North, Range 11 West of the
Gila and Salt River Meridian in the State of Arizona,

executed by Boyd S. Owens and Wallace R. Ott, Cadastral Surveyors,
having been critically examined and found correct, are hereby approved.

SEP 6 1966
(Date)

Clark J. Gumm
Acting (Chief, Division of Engineering) *AKS*

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~_____~~, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)