

BOOK 4788

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 14 North, Range 10 East

[Lined area for field notes]

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 25, 19 66, which provided for the surveys included under Group Number 445, approved March 25, 1966, and assignment instructions dated May 17, 19 66.

Survey commenced May 25, 19 66

Survey completed June 30, 19 66

1A

INDEX DIAGRAM

Township 14 North, Range 10 East
2 2 1

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 14 North, Range 10 East
Gila and Salt River Meridian, Arizona

1B

CHAINS

The boundaries and subdivisional lines were surveyed in 1881 by T. F. White. The south and west boundaries were resurveyed in 1934 by C. W. Devendorf and B. J. Molette.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 25, 1966, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541 dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Remonumentation, T. 14 N., R. 10 E., Arizona

The point for the cor. of secs. 1, 2, 35 and 36, Ts. 14 and 15 N., R. 10 E., is monumented by a mound of stone, from which the remains of the original bearing trees

A pine stump bears N. 46° E., 82 lks. dist.

A pine snag, 38 ins. diam., bears S. 19° E., 1.26 chs. dist., mkd. TXIVRXE 1

A fallen pine, 40 ins. diam., bears S. 24° W., 75 lks. dist., mkd. TXIVRXE S2 BT

A pine stump bears N. 46½° W., 1.48 chs. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR10E	
S35	S36
S 2	S 1
T14N	
1966	

from which

A pine, 6 ins. diam., bears N. 62° E., 73 lks. dist., mkd. T15NR10ES36BT

A pine, 9 ins. diam., bears S. 36° E., 31 lks. dist., mkd. T14NR10ES1BT

A pine, 12 ins. diam., bears S. 28° W., 57 lks. dist., mkd. T14NR10ES2BT

A pine, 10 ins. diam., bears N. 51½° W., 86 lks. dist., mkd. T15NR10ES35BT

Build a mound with stones W. of the iron post.

Cor. is on a N. slope in heavy timber, approx. 4.00 chs. S. of gravel road (F.S. Road No. 211), and 30 lks. E. of a N. and S. fence.

CHAINS

The point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, Ts. 14 and 15 N., R. 10 E., is determined by using record bearing and distance from the remains of the original bearing trees and falls in the center of a scattered mound of stone

A pine stump bears S. $26\frac{1}{2}^\circ$ E., 1.68 chs. dist., mkd. $\frac{1}{4}$ S BT

A pine stump bears N. 55° W., 1.40 chs. dist., no visible markings

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15NR10E

$\frac{1}{4}$ $\frac{S35}{S 2}$

T14N
1966

from which

A pine, 12 ins. diam., bears N. 58° E., 15 lks. dist., mkd. T15NR10E $\frac{1}{4}$ S35BT

A pine, 9 ins. diam., bears S. 12° E., 39 lks. dist., mkd. T14NR10E $\frac{1}{4}$ S2BT

Cor. is on a S. slope in moderate timber, about 2.00 chs. S. of Forest Service Road No. 211, which bears E. and W.

The cor. of secs. 2, 3, 34 and 35, Ts. 14 and 15 N., R. 10 E., monumented by a rotted wooden post set in the ground under a mound of stones, from which the original bearing trees

A pine, 40 ins. diam., bears N. 8° E., 1.24 chs. dist., mkd. TXVNRXESXXXVBT

A pine, 28 ins. diam., bears S. $47\frac{3}{4}^\circ$ E., 61 lks. dist., mkd. TXIVRXES11BT

A pine, 24 ins. diam., bears S. 18° W., 71 lks. dist., mkd. with an overgrown blaze

A stump hole bears N. 64° W., 72 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15NR10E

$\frac{S34}{S 3}$ $\frac{S35}{S 2}$

T14N
1966

from which

A pine, 6 ins. diam., bears N. $34\frac{1}{2}^\circ$ W., 52 lks. dist., mkd. S34BT

Cor. is on a S. slope in heavy timber, 6 lks. W. of a N. and S. fence.

CHAINS

The point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3 is determined by using record course and distance from the original bearing trees

A pine, 16 ins. diam., bears S. 21° E., 112 lks. dist., mkd. with an overgrown blaze

A pine, 26 ins. diam., bears S. 10° W., 128 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR10E
 $\frac{1}{4}$
 S 3 | S 2
 1966

from which

A pine, 7 ins. diam., bears S. 46° E., 18 lks. dist., mkd. $\frac{1}{4}$ S2BT

A pine, 7 ins. diam., bears N. 38° W., 47 lks. dist., mkd. $\frac{1}{4}$ S3BT

Cor. is on the E. side of a draw draining NW. and 40 lks. W. of a North and South fence.

The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented by a rotted wooden post set under a mound of stone, from which the original bearing trees.

A dead pine, 26 ins. diam., bears N. 49° E., 78 lks. dist., mkd. $\frac{1}{4}$ SBT

A pine, 26 ins. diam., bears N. 55° W., 57 lks. dist., parts of scribe mks. visible

At the cor point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR10E
 $\frac{1}{4}$
 S21 | S22
 1966

from which

A pine, 20 ins. diam., bears S. $38\frac{1}{2}^\circ$ E., 59 lks. dist., mkd. T14NR10E $\frac{1}{4}$ S22BT

Cor. is on nearly level land in heavy timber and undergrowth about 12.00 chs. N. of a track road bearing SE. and NW.

The cor. of secs. 15, 16, 21 and 22, mounmented by an old mound of stone, from which the original bearing trees

A pine, 24 ins. diam., bears N. $77\frac{1}{2}^\circ$ E., 45 lks. dist., mkd. TXIVNRXESXVBT

A pine stump bears S. $50\frac{1}{2}^\circ$ E., 74 lks. dist., mkd. with an overgrown blaze

CHAINS

A pine stump bears S. 53° W., 109 lks. dist.

A pine, 26 ins. diam., bears N. 40° W., 118 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR10E

S16 | S15

S21 | S22

1966

from which

A pine, 20 ins. diam., bears S. 33° E., 65 lks. dist., mkd. T14NR10ES22BT

A pine, 16 ins. diam., bears S. 83° W., 68 lks. dist., mkd. T14NR10ES21BT

Cor. is on gently rolling land in moderate timber 51 lks. E. of a North and South fence.

The ¼ sec. cor. of secs. 21 and 28, monumented by an old mound of stone, from which the original bearing trees

A pine, 24 ins. diam., bears N. 60° E., 82 lks. dist., mkd. ¼ SBT

A pine, 26 ins. diam., bears S. 58° W., 52 lks. dist., mkd. with an overgrown blaze. I remark this tree ¼S28BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR10E

¼ S21

S28

1966

Cor. is on a gentle S. slope in heavy timber.

4

BOOK 4788

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of March, 19 66, I have remonumented cadastral survey corners in Township 14 North, Range 10 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 18, 1966 (Date)

Wallace R. Ott (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date FEB 15 1967

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 14 North, Range 10 East, of the Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician having been critically examined and found correct, are hereby approved.

MAY 18 1967 (Date)

E. Livingston (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)