

Form 4-679  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

\_\_\_\_\_

\_\_\_\_\_

REMONUMENTATION

\_\_\_\_\_

in

\_\_\_\_\_

Township 15 North, Range 11 East

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Of the \_\_\_\_\_ Gila and Salt River \_\_\_\_\_ Meridian,

In the State of \_\_\_\_\_ Arizona \_\_\_\_\_

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

\_\_\_\_\_

\_\_\_\_\_

Under special instructions dated \_\_\_\_\_ March 25 \_\_\_\_\_, 19 66 \_\_\_\_\_, which provided for the surveys  
included under Group Number \_\_\_\_\_ 445 \_\_\_\_\_, approved \_\_\_\_\_ March 25, 1966 \_\_\_\_\_,  
and assignment instructions dated \_\_\_\_\_ May 17 \_\_\_\_\_, 19 66 \_\_\_\_\_.

Survey commenced \_\_\_\_\_ May 25 \_\_\_\_\_, 19 66 \_\_\_\_\_

Survey completed \_\_\_\_\_ June 30 \_\_\_\_\_, 19 66 \_\_\_\_\_

# INDEX DIAGRAM

Township 15 North, Range 11 East,

	1	1			
6	15 5	4	8	2	1
14	13 14	10	8 9		
7	8	9	8 10	5 11	12
			7 7		
18	17	16	15	5 14	13
			6 7	4	
19	20	21	22	23	24
13	12				
30	12 29	28	27	26	25
11	11	9 10	6	3 4	2
31	32	9 33	5 34	3 35	2 36

Township 15 North, Range 11 East  
Gila and Salt River Meridian, Arizona

18

## CHAINS

The boundaries and subdivisional lines were surveyed in 1881 by T. F. White. The north boundary was retraced in 1883 by O. D. Wheeler.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 25, 1966, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

The point for the cor. of secs. 4, 5, 32 and 33, Ts. 15 and 16 N., R. 11 E., is determined by using record bearing and distance from the original bearing trees

A pine, 14 ins. diam., bears N. 41° E., 38 lks. dist., mkd. with an overgrown blaze; I remark this tree T16N R11E S33 BT.

A pine, 10 ins. diam., bears S. 49¾° E., 34 lks. dist., mkd. with an overgrown blaze; I remark this tree T15N R11E S4 BT.

A pine, 12 ins. diam., bears S. 61½° W., 8 lks. dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears N. 57½° W., 39 lks. dist., mkd. TXVIN RXIE XXXII.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T16N R11E
<u>S32</u>   <u>S33</u>
S 5   S 4
T15N
1966

Cor. is on a SW. slope, at the E. edge of a clearing.

The cor. of secs. 5, 6, 31 and 32, Ts. 15 and 16 N., R. 11 E., is monumented by the remains of a rotted wooden stake in a mound of stone, from which the remains of the original bearing trees

A fallen pine, bears N. 10¾° E., 130 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears S. 40½° E., 16 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears N. 36° W., 200 lks. dist., mkd. TXVIN RXIE XXXI.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T16N R11E  
 S31|S32  
 S 6|S 5  
 T15N  
 1966

Cor. is in an E. and W. fence, on a SW. slope in moderate timber.

The ¼ sec. cor. of secs. 35 and 36, is monumented by an unmarked stone in the center of a mound of stone, from which the remains of the original bearing trees

A pine stump, 34 ins. diam., bears S. 52° E., 66 lks. dist., mkd. ¼ S BT.

A stump hole, bears S. 65° W., 26 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E  
 ¼  
 S35|S36  
 1966

from which

An oak, 9 ins. diam., bears S. 78° E., 42 lks. dist., mkd. T15N R11E ¼ S36 BT.

An oak, 6 ins. diam., bears N. 71° W., 48 lks. dist., mkd. ¼ S35 BT.

Fence cor. bears S. 12° E., 75 lks. dist.; fences bear S. and W.

Cor. is on a W. slope, among thick timber and undergrowth.

The cor. of secs. 25, 26, 35 and 36, is monumented by the remains of an old wood stake, partially buried under the ground, from which the remains of the original bearing trees

A pine, 26 ins. diam., bears N. 34° E., 158 lks. dist., mkd. TXVN RXIE SXXV BT.

A pine stump, 34 ins. diam., bears S. 67° E., 45 lks. dist., mkd. TXVN RXIE SXXXVI BT.

A fallen pine, bears S. 21° W., 94 lks. dist., part of scribe marks visible.

A pine, 26 ins. diam., bears N. 47½° W., 118 lks. dist., mkd. with an overgrown blaze.

At the cor. point

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E  
 S26|S25  
 S35|S36  
 1966

Raise a mound of stone W. of the iron post.

Cor. is on an E. slope in moderate timber, with a large draw about 8.00 chs. NE.; draw drains irregularly N.

The ¼ sec. cor. of secs. 34 and 35, is marked with a rebar in a small mound of stone, from which the original bearing trees

A pine, 42 ins. diam., bears S. 67° E., 50 lks. dist., mkd. with an overgrown blaze.

A dead pine, 40 ins. diam., bears N. 7° W., 33 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E  
 ¼  
 S34|S35  
 1966

Raise a mound of stone W. of the iron post.

Cor. is on an E. slope in moderate timber, from which a small frame house bears E., 80 lks. dist.

The cor. of secs. 26, 27, 34 and 35, is marked by the remains of an old rotted wood stake set in the ground, and in a mound of stone, from which the remains of the original bearing trees

A pine, 30 ins. diam., bears S. 58½° E., 82 lks. dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears S. 80° W., 70 lks. dist., mkd. with an overgrown blaze.

A pine, 26 ins. diam., bears N. 16° W., 125 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E  
 S27|S26  
 S34|S35  
 1966

Cor. is on a N. slope in moderate timber, with a draw 125 lks. N., draining NW.

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, is monumented by a squared wooden post in a mound of stone, from which the remains of the original bearing trees

A dead pine, bears N.  $6^{\circ}$  E., 200 lks. dist., mkd.  $\frac{1}{4}$  S BT.

A pine stump, bears S.  $47\frac{1}{2}^{\circ}$  E., 54 lks. dist.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E

$\frac{1}{4}$   $\frac{S26}{S35}$

1966

from which

A pine, 18 ins. diam., bears North, 60 lks. dist., mkd. T15N R11E  $\frac{1}{4}$  S26 BT.

An oak, 9 ins. diam., bears S.  $19\frac{3}{4}^{\circ}$  E., 50 lks. dist., mkd. T15N R11E  $\frac{1}{4}$  S35 BT.

Reset the squared wooden post, inverted and alongside the iron post.

Cor. is on a gentle NW. slope in thick timber, with a track road about 12.00 chs. E., bearing N. and S.

The cor. of secs. 14, 15, 22 and 23, is monumented by a mound of stone, the center of which is accepted as the cor. point, from which the original bearing trees

A pine, 20 ins. diam., bears N.  $34^{\circ}$  E., 187 lks. dist., mkd. with an overgrown blaze.

A fallen pine, bears S.  $48^{\circ}$  E., 166 lks. dist., mkd. TXVN RXIE XXIII BT.

A fallen pine, bears S.  $36^{\circ}$  W., 48 lks. dist.

A pine, 32 ins. diam., bears N.  $26^{\circ}$  W., 122 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E

$\frac{S15}{S22}$   $\frac{S14}{S23}$

1966

Raise a mound of stone W. of the iron post.

Cor. is on a SE. slope in moderate timber, with a ravine about 6.00 chs. S., draining E.

Remonumentation, T. 15 N., R. 11 E., Arizona

5.

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, is monumented by a lava rock, 8x12x14 ins., firmly set,  $\frac{1}{4}$  dimly mkd. on the W., with a mound of stone to the N., from which the original bearing trees

A pine, 18 ins. diam., bears N. 51° E., 166 lks. dist., mkd. with an overgrown blaze.

A pine, 30 ins. diam., bears S. 59° W., 138 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long., 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E

$\frac{1}{4}$   
S15 | S14  
1966

Bury the original corner stone alongside the iron post.

Cor. is in nearly level grassy area, with scattered to moderate timber.

The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, is monumented by the remains of a wooden stake set in the ground, from which the original bearing trees

A pine, 36 ins. diam., bears N. 20° E., 8 lks. dist., mkd. with an overgrown blaze.

A pine, 16 ins. diam., bears N. 80° E., 43 lks. dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E

$\frac{1}{4}$   
S10 | S11  
1966

Raise a mound of stone W. of the iron post.

Cor. is on a SW. slope in moderate timber.

The  $\frac{1}{4}$  sec. cor. of secs. 33 and 34, is monumented by the remains of a wooden stake set in a mound of stone, from which the remains of the original bearing trees

A fallen pine, bears N. 60° E., 38 lks. dist., mkd.  $\frac{1}{4}$  S BT.

A fallen pine, bears S. 14 $\frac{1}{2}$ ° W., 82 lks. dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

6

CHAINS

T15N R11E

$\frac{1}{2}$   
S33|S34  
1966

from which

A pine, 28 ins. diam., bears N. 78° E., 222 lks. dist., mkd. T15N R11E  $\frac{1}{2}$  S34 BT.

A pine, 18 ins. diam., bears S. 25° E., 124 lks. dist., mkd. T15N R11E  $\frac{1}{2}$  S34 BT.

Cor. is on a NW. slope in scattered timber.

The cor. of secs. 27, 28, 33 and 34, is marked by a 1 inch iron pipe, set in a mound of stone, from which the remains of the original bearing trees

A pine stump, bears N. 56½° E., 133 lks. dist., no mks. visible.

A pine, 18 ins. diam., bears S. 63° E., 43 lks. dist., mkd. TXVN RXIE SXXXIV BT.

A pine stump, bears S. 82° W., 177 lks. dist., no mks. visible.

A pine, 30 ins. diam., bears N. 55° W., 19 lks. dist., mkd. TXVN RXIE SXXVIII BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E  
S28|S27  
S33|S34  
1966

Raise a mound of stone W. of the iron post.

Cor. is on a NW. slope in moderate timber, with a bladed road 1.00 chn. W., bears NE. and SW.

The cor. of secs. 15, 16, 21 and 22, is monumented by the remains of a wooden stake in a mound of stone, from which the remains of the original bearing trees

A pine snag, 18 ins. diam., bears N. 7½° E., 137 lks. dist., part of scribe mks. visible.

A pine snag, 40 ins. diam., bears S. 12° E., 27 lks. dist., part of scribe mks. visible.

A pine, 24 ins. diam., bears S. 46½° W., 220 lks. dist., mkd. with an overgrown blaze.

A fallen pine, bears N. 61° W., 194 lks. dist., mkd. TXVN RXIE SXVI BT.

At the cor. point



Remonumentation, T. 15 N., R. 11 E., Arizona

7.

## CHAINS

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., over an X cut in solid rock, mound of stone to top, brass cap mkd.

T15N R11E  
 $\frac{S16}{S21} | \frac{S15}{S22}$   
 1966

Cor. is on a gentle S. slope, among scattered timber.

The  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, is monumented by parts of a wooden stake in a mound of stone, from which the remains of the original bearing trees

A fallen pine, bears N.  $85^\circ$  E., 141 lks. dist., mkd. with an overgrown blaze.

A stump hole, bears N.  $67^\circ$  E., 206 lks. dist.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E  
 $\frac{1}{4} \frac{S15}{S22}$   
 1966

Cor. is on a grassy S. slope, among widely scattered timber.

The cor. of secs. 9, 10, 15 and 16, is monumented by parts of a wooden stake in a mound of stone, from which the remains of the original bearing trees

A pine, 24 ins. diam., bears N.  $37^\circ$  E., 113 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears S.  $67^\circ$  W., 139 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears N.  $34\frac{1}{2}^\circ$  W., 124 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E  
 $\frac{S9}{S16} | \frac{S10}{S15}$   
 1966

Raise a mound of stone W. of the iron post.

Cor. is on rolling land in moderate timber.

The  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, is monumented by a mound of stone, the center of which is accepted as the cor. point, from which the original bearing trees

## CHAINS

A fallen pine, bears N. 42° E., 160 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears S. 70° W., 63 lks. dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E

$\frac{1}{4}$  S10  
S15

1966

Cor. is on a gentle grassy W. slope, in lightly scattered timber.

The  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, is monumented by the remains of a wooden stake in a mound of stone, from which the original bearing trees

A pine, 20 ins. diam., bears S. 26° E., 42 lks. dist., mkd. with an overgrown blaze.

A pine, 34 ins. diam., bears N. 60° W., 179 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E

$\frac{1}{4}$   
S 9 | S10

1966

Raise a mound of stone W. of the iron post.

Cor. is on gently rolling land, in moderate timber, with a dirt road, No. 294A, about 180 lks. W.; road bears N. and S.

The cor. of secs. 3, 4, 9 and 10, is monumented by a mound of stone, the center of which is accepted as the cor. point, from which the original bearing trees

A pine, 24 ins. diam., bears N. 47½° E., 157 lks. dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears S. 57½° E., 88 lks. dist., mkd. with an overgrown blaze.

A pine, 34 ins. diam., bears S. 78° W., 127 lks. dist., mkd. with an overgrown blaze.

A pine, 28 ins. diam., bears N. 45° W., 95 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

CHAINS

T15N R11E

 $\frac{S}{S} \frac{4}{9} | \frac{S}{S} \frac{3}{10}$ 

1966

Cor. is on a W. slope, and about 2.00 chs. E. of a shallow draw, 50 lks. wide, drains NE.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, is monumented by the remains of a wooden stake in a mound of stone, from which the original bearing trees

A pine, 30 ins. diam., bears N.  $72^\circ$  E., 19 lks. dist., mkd. with an overgrown blaze.

A fallen pine, bears S.  $26^\circ$  W., 52 lks. dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E

 $\frac{1}{4} \frac{S}{S} \frac{3}{10}$ 

1966

Cor. is on a rocky W. slope in moderate timber.

The  $\frac{1}{4}$  sec. cor. of secs. 32 and 33, is monumented by the remains of a rotted wooden stake in a mound of stone, from which the original bearing trees

A pine, 18 ins. diam., bears N.  $67\frac{1}{2}^\circ$  E., 47 lks. dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears S.  $11\frac{1}{2}^\circ$  W., 30 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E

 $\frac{1}{4} \frac{S}{S} \frac{32}{33}$ 

1966

Cor. is on a W. slope in moderate timber, and about 100 lks. E. of a narrow wash, draining N.

The cor. of secs. 28, 29, 32 and 33, is monumented by a wooden stake, 4 ft. long, 4 ins. sq., mkd. with faint scribe mks., set in a mound of stone, from which the original bearing trees

A pine, 34 ins. diam., bears N.  $39^\circ$  E., 69 lks. dist., mkd. with an overgrown blaze.

A pine, 32 ins. diam., bears S.  $38^\circ$  E., 133 lks. dist., mkd. with an overgrown blaze.

CHAINS

A pinon, 16 ins. diam., bears S. 76° W., 165 lks. dist., mkd. TXVN RXIE SXXIX BT.

A pine, 32 ins. diam., bears N. 11° W., 48 lks. dist., mkd. TXVN RXIE SXXVIII BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E  
S29 | S28  
S32 | S33  
 1966

Raise a mound of stone W. of the iron post.

Reset the wooden stake, inverted and alongside the iron post.

Cor. is on an E. slope, and 50 lks. W. of East Clear Creek rim, bearing NE. and SW.

The ¼ sec. cor. of secs. 28 and 33, is monumented by the remains of a wooden stake in a mound of stone, from which the remains of the original bearing trees

A pine stump, bears N. 85° E., 87 lks. dist.

A pine stump, bears S. 1½° E., 71 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E  
 ¼ S28  
S33  
 1966

from which

A double pine, 42 ins. diam., bears S. 45° E., 125 lks. dist., mkd. T15N R11E ¼ S33 BT.

A pine, 12 ins. diam., bears N. 88° W., 18 lks. dist., mkd. T15N R11E ¼ S28 BT.

Cor. is on a gentle W. slope, in moderate timber and undergrowth.

The point for the cor. of secs. 4, 5, 8 and 9 is determined by using record bearing and distance from the remains of the original bearing trees

A pine, 24 ins. diam., bears N. 66° E., 250 lks. dist., mkd. with an overgrown blaze.

A pine stump, 34 ins. diam., bears S. 79° E., 336 lks. dist., mkd. with an overgrown blaze.

CHAINS

A pine, 26 ins. diam., bears S. 67° W., 212 lks. dist., mkd. TXVN RXIE VIII BT.

Stump hole, bears N. 82° W., 212 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E  

S 5	S 4
S 8	S 9

 1966

Raise a mound of stone W. of the iron post.

Cor. is on gently rolling land in moderate timber.

The cor. of secs. 29, 30, 31 and 32, is monumented by a lava rock, 6x10x16 ins., firmly set, mkd. with 5 notches on the E. and 1 on the S., with a mound of stone to the N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E  

S30	S29
S31	S32

 1966

from which

A pine, 8 ins. diam., bears S. 72¾° W., 223 lks. dist., mkd. S31 BT.

A pine, 10 ins. diam., bears N. 65½° W., 385 lks. dist., mkd. T15N R11E S30 BT.

Cor. of barbed wire fence, bears W. about 5.00 chs. dist.; fence bears N. and W.

Bury the original corner stone and deposit glass alongside the iron post.

Cor. is in an open area on gently rolling land.

The ¼ sec. cor. of secs. 30 and 31, is monumented by the remains of a rotted wooden stake in a mound of stone, from which the original bearing trees

A pine, 26 ins. diam., bears S. 34½° W., 93 lks. dist., mkd. with a blaze partly grown over and parts of scribe marks visible.

A pine, 26 ins. diam., bears N. 81½° W., 86 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, mound of stone to top, brass cap mkd.

## CHAINS

T15N R11E

 $\frac{1}{4}$   $\frac{S30}{S31}$ 

1966

from which

A pine, 7 ins. diam., bears N. 53° E., 25 lks.  
dist., mkd. T15N R11E  $\frac{1}{4}$  S30 BT.

A pine, 6 ins. diam., bears S. 6° W., 78 lks.  
dist., mkd.  $\frac{1}{4}$  S31 BT.

Cor. is on a S. slope among scattered to moderate timber,  
with a canyon about 15.00 chs. S., draining E.

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, is monumented by a  
lava rock, 8x12x18 ins., set in a mound of stone, mkd.  
 $\frac{1}{4}$  on the W., from which the remains of the original  
bearing trees

A stump hole, bears North, 84 lks. dist.

A pine, 22 ins. diam., bears N. 84° E., 186 lks.  
dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in  
the ground, mound of stone to top, brass cap mkd.

T15N R11E

 $\frac{1}{4}$  S30|S29

1966

from which

A fence cor. bears S. 60° E., about 6.50 chs.  
dist.; fences bear E., W. and S.

Bury the original corner stone and deposit glass  
alongside the iron post.

Cor. is on gently rolling land in scattered timber.

The cor. of secs. 19, 20, 29 and 30, is monumented by the  
remains of a wooden stake in a mound of stone, from  
which the remains of the original bearing trees

A pine, 30 ins. diam., bears N. 6 $\frac{1}{2}$ ° E., 189 lks.  
dist., mkd. with an overgrown blaze.

A pine stump hole, bears S. 31° E., 264 lks.  
dist.; tree has fallen, parts of scribe mks. are  
visible.

A pine, 18 ins. diam., bears N. 71° W., 44 lks.  
dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in  
the ground, mound of stone to top, brass cap mkd.

Remonumentation, T. 15 N., R. 11 E., Arizona

13.

## CHAINS

T15N R11E

 $\frac{S19}{S30} | \frac{S20}{S29}$ 

1966

from which

A pine, 10 ins. diam., bears N.  $72^\circ$  E., 84 lks. dist., mkd. T15N R11E S20 BT.

A juniper, 4 ins. diam., bears S.  $58\frac{1}{2}^\circ$  E., 56 lks. dist., mkd. X BT.

Fence cor. bears W. 22 lks. dist.; fences bear N. and SW.

Cor. is on gently rolling land.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, is monumented by the remains of a wooden stake in the center of a mound of stone, from which the remains of the original bearing trees

A stump hole, bears N.  $25\frac{1}{2}^\circ$  E., 57 lks. dist. (Record)

A pine stump, 8 ft. high, 30 ins. diam., bears S.  $24\frac{1}{2}^\circ$  W., 104 lks. dist., mkd.  $\frac{1}{4}$  S visible.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, mound of stone to top, brass cap mkd.

T15N R11E

 $\frac{1}{4} \frac{S19}{S30}$ 

1966

from which

A pine, 12 ins. diam., bears N.  $20\frac{1}{2}^\circ$  E., 45 lks. dist., mkd. T15N R11E  $\frac{1}{4}$  S19 BT.

A pine, 9 ins. diam., bears S.  $46\frac{3}{4}^\circ$  E., 29 lks. dist., mkd. T15N R11E  $\frac{1}{4}$  S30 BT.

Cor. is on gently rolling land, about 2.00 chs. W. of bladed road, bearing N. and S.

The cor. of secs. 5, 6, 7 and 8, is monumented by the remains of a rotted wooden stake in a mound of stone, from which the original bearing trees

A dead pine, 22 ins. diam., bears N.  $57^\circ$  E., 71 lks. dist., mkd. TXVN RXIE VIII BT.

A pine, 22 ins. diam., bears S.  $73^\circ$  E., 129 lks. dist., blaze partly grown over with parts of scribe marks visible.

A pine, 24 ins. diam., bears S.  $32\frac{1}{2}^\circ$  W., 103 lks. dist., mkd. with an overgrown blaze.

14  
CHAINS

A pine, 28 ins. diam., bears N. 54° W., 155 lks. dist., blaze partly grown over with parts of scribe marks visible.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, mound of stone to top, brass cap mkd.

T15N R11E  
 $\frac{S}{S} \frac{6}{7} | \frac{S}{S} \frac{5}{8}$   
 1966

Cor. is on a gentle rolling NW. slope in moderate timber, with a N. and S. barbed wire fence 5 lks. to the W.

The ¼ sec. cor. of secs. 5 and 8, is monumented by the remains of a rotted wooden stake in a mound of stone, from which the original bearing trees

A pine, 18 ins. diam., bears S. 5° E., 45 lks. dist., mkd. with an overgrown blaze.

A dead pine, 16 ins. diam., bears N. 1½° W., 79 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R11E  
 $\frac{1}{4} \frac{S}{S} \frac{5}{8}$   
 1966

from which

A pine, 16 ins. diam., bears N. 12½° E., 96 lks. dist., mkd. T15N R11E ¼ S5 BT.

Raise a mound of stone N. of the iron post.

Cor. is on a gentle E. slope among moderate timber.

The ¼ sec. cor. of secs. 6 and 7, is monumented by a mound of stone, the center of which is accepted as the point for the cor., from which the original bearing trees

A pine, 36 ins. diam., bears N. 5° E., 48 lks. dist., mkd. ¼ S BT.

A pine, 42 ins. diam., bears S. 52½° E., 55 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.



Township 15 North, Range 11 East  
Gila and Salt River Meridian, Arizona

15.

CHAINS

T15N R11E

$$\frac{1}{4} \begin{array}{l} S 6 \\ S 7 \end{array}$$

1966

Raise a mound of stone N. of the iron post.

Cor. is on an E. slope in moderate timber.

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, is monumented by the remains of a rotted wooden stake in a mound of stone, from which the original bearing trees

A dead pine, 22 ins. diam., bears N. 75° E.,  
12 lks. dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears S. 81½° W., 31 lks.  
dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins.  
in the ground, mound of stone to top, brass cap mkd.

T15N R11E

$$\frac{1}{4} \begin{array}{l} S 6 \\ S 5 \end{array}$$

1966

from which

A pine, 22 ins. diam., bears N. 40° W., 115 lks.  
dist., mkd. T15N R11E  $\frac{1}{4}$  S6 BT.

Cor. is on a gentle E. slope in moderate timber.

Form 4-680  
(June 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
U. S. Forest Service personnel:	
Gordon H. Long	Cadastral Surveyor
John Higgins	Engineering Assistant
Jim Muth	Engineering Assistant

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25 day of March, 1966, I have remonumented cadastral survey corners in Township 15 North, Range 11 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 16, 1966 (Date)

Wallace R. Ott (Cadastral Surveyor) (Supervisory Surveying Technician)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date FEB 15 1967

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the remonumentation of cadastral survey corners in Township 15 North, Range 11 East, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician, having been critically examined and found correct, are hereby approved.

MAY 18 1967 (Date)

E. L. Lemington (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)