



FIELD NOTES

REMONUMENTATION

in

Township 15 North, Range 12 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 25, 19 66, which provided for the surveys included under Group Number 445, approved March 25, 1966, and assignment instructions dated May 17, 19 66.

Survey commenced May 25, 19 66

Survey completed June 30, 19 66

INDEX DIAGRAM

Township 15 North, Range 12 East,

		7	6 6	5	5
6	5	4	3	2	1
		18	14	11	8
7	8	18 9	10	11	12
	21 22	17	13	10 11	4
18	20 17	17 16	15	14	8 13 4
	20	16	13	10	7 3
19	20	21	22	23	24
	19	15	12	9	3
30	29	28	27	26	25 2
	19	14 15	12	9	2
31	32	33	11 34	35	36 1

Township 15 North, Range 12 East
Gila and Salt River Meridian, Arizona

1β

CHAINS

The west boundary was surveyed in 1881 by T. F. White. The east boundary was surveyed in 1883 by J. B. McLaughlin. The east boundary was resurveyed, and the north and south boundaries and subdivisional lines were surveyed in 1893 by D. Drummond. The north boundary of section 4 was retraced by E. R. Sievers, U. S. Forest Service, in 1941.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b), dated October 16, 1958.

The approval of the Special Instructions on March 25, 1966, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open site compass was used to obtain the bearings, and a standard steel tape was used to measure the distances to corner accessories.

Remonumentation, T. 15 N., R. 12 E., Arizona

The 1/4 sec. cor. of secs. 31 and 36, T. 15 N., Rs. 12 and 13 E., is monumented by a sandstone, 10x18x20 ins., loosely set, mkd. 1/4, from which the original bearing trees

A pinon, 13 ins. diam., bears N. 48° E., 192 lks. dist., mkd. 1/4 S BT.

A pinon, 10 ins. diam., bears N. 13 1/2° W., 210 lks. dist., blaze rotted with parts of scribe mks. visible.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N
R12E R13E
1/4
S36|S31
1966

from which

A pinon, 6 ins. diam., bears S. 30 1/2° W., 46 lks. dist., mkd. T15N R12E 1/4 S36 BT.

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land, in moderate to thick timber.

CHAINS

The cor. of secs. 25, 30, 31 and 36, T. 15 N., Rs. 12 and 13 E., is monumented by a sandstone 8x10x18 ins., firmly set, mkd. with 5 notches on N. and 1 notch on the S., from which the original bearing trees

A juniper, 30 ins. diam., bears N. 29° E., 80 lks. dist., mkd. with an overgrown blaze.

A pine, 36 ins. diam., bears S. 34° E., 124 lks. dist., mkd. T15N R13E S31 BT.

A dead pine, 32 ins. diam., bears S. 50° W., 120 lks. dist., mkd. with an overgrown blaze.

A pinon, 16 ins. diam., bears N. 66½° W., 175 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N
R12E R13E
S25 | S30
S36 | S31
1966

from which

A pine, 8 ins. diam., bears N. 11° E., 113 lks. dist., mkd. T15N R13E S30 BT.

A double pinon, 7 ins. diam., bears S. 43½° W., 18 lks. dist., mkd. T15N R12E S36 BT.

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is 50 lks. S. of a track road, bearing NE. and SW., and 80 lks. W. of a shallow draw draining N.

The ¼ sec. cor. of secs. 25 and 30, T. 15 N., Rs. 12 and 13 E., is monumented by a sandstone 6x10x16 ins., firmly set, mkd. ¼ on the W., from which the original bearing trees

A pine, 18 ins. diam., bears S. 89° E., 113 lks. dist., mkd. with an overgrown blaze; I remark this tree T15N R13E ¼ S30 BT.

A pine 24 ins. diam., bears N. 44½° W., 70 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N
R12E R13E
¼
S25 | S30
1966

Bury the original corner stone alongside the iron post.

CHAINS

Cor. is on a S. slope, about 5.00 chs. N. of a draw draining SE.

The cor. of secs. 19, 24, 25 and 30, T. 15 N., Rs. 12 and 13 E., is monumented by a sandstone, 5x12x18 ins., firmly set, mkd. with 4 notches on N. and 2 notches on the S., from which the original bearing trees

A pinon, 14 ins. diam., bears S. 7° E., 96 lks. dist., mkd. with an overgrown blaze

A pinon, 12 ins. diam., bears S. 15½° W., 71 lks. dist., mkd. T15N R12E S25 BT

A pinon, 9 ins. diam., bears N. 21° W., 87 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N
R12E R13E .
S24 | S19
S25 | S30
1966

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land, in thick timber, and is 30 lks. E. of a track road bearing irregularly N. and S.

The cor. of secs. 13, 18, 19 and 24, T. 15 N., Rs. 12 and 13 E., is monumented by a sandstone, 9x12x22 ins., set 8 ins. in the ground, mkd. with 3 notches on the S. and dimly mkd. on the N., from which the original bearing trees

A pinon, 12 ins. diam., bears N. 8½° E., 49 lks. dist., mkd. T15N R13E S18 BT

A juniper, 12 ins. diam., bears S. 37½° E., 253 lks. dist., mkd. T15N R13E S19 BT

A juniper, 16 ins. diam., bears S. 5° W., 249 lks. dist., mkd. T15N R12E S24 BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T15N
R12E R13E
S13 | S18
S24 | S19
1966

Bury the original corner stone alongside the iron post.

Cor. is 50 lks. E. of a track road bearing N. and S., and a fence cor. bears N. 11° W., 28 lks. dist.; fences bear N. and E.

CHAINS

The point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, T. 15 N., Rs. 12 and 13 E., is determined by using record bearing and distance from the remains of the original bearing tree

Stump hole of fallen pine, bears N. $41\frac{1}{2}^{\circ}$ E.,
29 lks. dist., pine mkd. $\frac{1}{4}$ S BT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone to the top, with brass cap mkd.

T15N
R12E R13E
 $\frac{1}{4}$
S13|S18
1966

from which

A juniper, 4 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., 35 lks. dist., mkd. X BT

Cor. is 34 lks. NE. of fence cor.; fences bear N., S., and E.

The point for the cor. of secs. 7, 12, 13 and 18, T. 15 N., Rs. 12 and 13 E., is determined by using record bearing and distance from the remains of the original bearing trees

A fallen pine, 14 ins. diam., bears S. 35° E.,
168 lks. dist., mkd. T15N R13E S18 BT

A fallen pine, 10 ins. diam., bears N. $74\frac{1}{2}^{\circ}$ W.,
155 lks. dist., mkd. T15N R12E S12 BT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N
R12E R13E
S12|S 7
S13|S18
1966

from which

A juniper, 5 ins. diam., bears S. 74° W., 94 lks. dist., mkd. T15N R12E S13 BT

A juniper, 10 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W., 137 lks. dist., mkd. S12 BT

Cor. is on nearly level land, at edge of a railed area and 5 lks. SW. of fence cor., from which fences bear S. and E.

CHAINS

The cor. of secs. 1, 2, 35 and 36, Ts. 15 and 16 N., R. 12 E., is monumented by a malpais stone 5x12x20 ins., set in a mound of stone, mkd. with 5 notches on the W. and 1 notch on the E., from which the original bearing trees

A pinon, 9 ins. diam., bears S. 34½° E., 45 lks. dist., mkd. T15N R12E S1 BT.

A dead pinon, 7 ins. diam., bears S. 26° W., 52 lks. dist., mkd. T15N R12E S2 BT.

A dead pinon, 16 ins. diam., bears N. 86° W., 108 lks. dist., mkd. T16N R12E S35 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T16N	R12E
S35	S36
S 2	S 1
T15N	
1966	

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is at the E. edge of a railed area bearing N. and S., and 250 lks. W. of wash draining N.

The cor. of secs. 2, 3, 34 and 35, Ts. 15 and 16 N., R. 12 E., is monumented by a malpais stone 5x12x20 ins., firmly set in the ground and in a small mound of stone, dimly mkd. with 4 notches on the W. and 2 notches on the E., from which the original bearing trees

A juniper, 16 ins. diam., bears N. 40° E., 64 lks. dist., mkd. T16N R12E S35 BT.

A juniper, 14 ins. diam., bears S. 70° E., 87 lks. dist., mkd. T15N R12E S2 BT.

A pinon, 12 ins. diam., bears S. 22½° W., 150 lks. dist., mkd. T15N R12E S3 BT.

A pinon, 8 ins. diam., bears N. 58° W., 168 lks. dist., mkd. T16N R12E S34 BT. Tree is dead and has fallen.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T16N	R12E
S34	S35
S 3	S 2
T15N	
1966	

from which

CHAINS

A double pinon, 8 ins. diam., bears N. 57° W., 59 lks. dist., mkd. T16N R12E S34 BT.

Bury the original corner stone alongside the iron post.

Cor. is on gently rolling land, and at the W. edge of a railed area.

The ¼ sec. cor. of secs. 3 and 34, Ts. 15 and 16 N., R. 12 E., is monumented by a malpais stone 6x14x16 ins., firmly set in the ground and in a mound of stone, mkd. ¼ on the N., from which the original bearing trees

A pinon, 10 ins. diam., bears S. 48° W., 17 lks. dist., mkd. ¼ S BT.

A pinon, 7 ins. diam., bears N. 35° W., 7 lks. dist., mkd. with an overgrown blaze; I remark this tree ¼ S34 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T16N R12E

¼ S34
S 3

T15N

1966

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on rolling land in thick timber, and is 6 lks. S. of an old E. and W. fence.

The cor. of secs. 3, 4, 33 and 34, Ts. 15 and 16 N., R. 12 E., is monumented by a sandstone, 8x12x27 ins., firmly set in the ground and in a mound of stone, mkd. with 3 notches on the E., and 3 notches on the W., with a cross on top, from which the remains of the original bearing trees

A pinon, 15 ins. diam., bears S. 70° E., 16 lks. dist., mkd. T15N R12E S3 BT.

Stump hole of fallen pinon, 10 ins. diam., bears S. 83° W., 40 lks. dist., mkd. T15N R12E S4 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T16N R12E

S33 | S34
S 4 | S 3

T15N

1966

from which

A juniper, 18 ins. diam., bears N. 9° E., 45 lks. dist., mkd. S34 BT.

CHAINS

Bury the original corner stone alongside the iron post.

Cor. is on a S. slope, about 2.00 chs. N. of a dirt road bearing E. and W.

The cor. of secs. 4, 5, 32 and 33, Ts. 15 and 16 N., R. 12 E., is monumented by a malpais stone, 6x11x17 ins., set 5 ins. in the ground and in a mound of stone, mkd. with 4 notches on the E. and 2 notches on the W., from which the original bearing trees

A pinon, 14 ins. diam., bears N. 74½° E., 95 lks. dist., mkd. T16N R12E S33 BT.

A pinon, 8 ins. diam., bears S. 26½° E., 53 lks. dist., mkd. T15N R12E S4 BT.

A pinon, 8 ins. diam., bears S. 70° W., 33 lks. dist., mkd. T15N R12E S5 BT; tree is dead and has fallen.

A pinon, 8 ins. diam., bears N. 53° W., 26 lks. dist., mkd. T16N R12E S32 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T16N R12E	
S32	S33
S 5	S 4
T15N	
1966	

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is in moderate timber, on the E. slope of a ridge bearing N. and S.

The cor. of secs. 13, 14, 23 and 24, is monumented by a malpais stone, 5x15x18 ins., set in a mound of stone, mkd. with 3 notches on the S. and 1 notch on the E., from which the remains of the original bearing trees

A stump hole, bears N. 61° E., 198 lks. dist.

A pinon, 7 ins. diam., bears S. 27° E., 58 lks. dist., mkd. T15N R12E S24 BT.

A pinon, 12 ins. diam., bears S. 3° W., 34 lks. dist., mkd. T15N R12E S23 BT; tree is dead and has fallen.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E	
S14	S13
S23	S24
1966	

CHAINS

from which

A juniper, 4 ins. diam., bears N. $38\frac{3}{4}^{\circ}$ W., 6 lks. dist., mkd. X BT.

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on rolling land, at the SW. edge of a railed area.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, is monumented by a malpais stone, 6x10x18 ins., set in a mound of stone, with $\frac{1}{4}$ dimly mkd. on the W., from which the remains of the original bearing trees

A juniper, 14 ins. diam., bears S. 40° E., 8 lks. dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in solid rock, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

$\frac{1}{4}$
S14 | S13
1966

from which

A pinon, 14 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 22 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on rolling land at the W. edge of a railed area, and 1.00 ch. south of a wash, 1.00 ch. wide draining N. 75° E.

The cor. of secs. 1, 2, 11 and 12, is monumented by a malpais stone, 5x15x20 ins., set in a mound of stone, mkd. with 5 notches on the S. and 1 notch on the E., from which the remains of the original bearing trees

A pinon, 14 ins. diam., bears N. 77° E., 47 lks. dist.; tree is dead and has fallen, mkd.
T15N R12E S2 BT.

A pinon, 11 ins. diam., bears N. 84° W., 44 lks. dist.; tree is dead and has fallen, mkd.
T15N R12E S2 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

S 2 | S 1
S11 | S12
1966

CHAINS

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on nearly level land, in a railed area.

The cor. of secs. 26, 27, 34 and 35, is monumented by a sandstone 6x16x20 ins., loosely set in a small mound of stone, mkd. with 1 notch on the S., and 2 notches on the E., from which the remains of the original bearing trees

A juniper, 18 ins. diam., bears S. 55° E., 14 lks. dist., mkd. T15N R12E S35 BT.

A dead pinon, 9 ins. diam., bears S. 7° W., 9 lks. dist., mkd. T15N R12E S34 BT.

A juniper, 10 ins. diam., bears N. 77° W., 64 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N R12E	
S27	S26
S34	S35
1966	

from which

A pinon, 5 ins. diam., bears S. 37° W., 24 lks. dist., mkd. T15N R12E S34 BT.

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a NE. slope in thick timber and undergrowth.

The cor. of secs. 22, 23, 26 and 27, is monumented by a sandstone, 6x12x18 ins., firmly set in the ground and in a mound of stone, mkd. with 2 notches on the S. and E. edges, from which the original bearing trees

A pine, 12 ins. diam., bears N. 43° E., 159 lks. dist., mkd. with an overgrown blaze.

A pinon, 8 ins. diam., bears S. 56° E., 162 lks. dist., mkd. with a partly overgrown blaze.

A pine, 12 ins. diam., bears S. 44° W., 73 lks. dist., mkd. with a partly overgrown blaze.

A pine, 26 ins. diam., bears N. 45½° W., 34 lks. dist., mkd. T15N R12E S22 BT.

At the cor point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

CHAINS

T15N R12E
S22 | S23
S27 | S26
 1966

Bury the original corner stone alongside the iron post.

Cor. is on a N. slope, in thick timber and undergrowth and 25 lks. S. of a draw draining E.

The point for the cor. of secs. 14, 15, 22 and 23 is determined by using record bearing and distance from the remains of the original bearing trees

A pinon, 10 ins. diam., bears N. 71° E., 43 lks. dist., mkd. T15N R12E S14 BT.

Stump hole of fallen pinon, 14 ins. diam., bears S. 34° E., 40 lks. dist., mkd. T15N R12E S23 BT.

Stump hole of fallen pinon, 8 ins. diam., bears S. 52° W., 38 lks. dist., mkd. T15N R12E S22 BT.

Stump hole of fallen pinon, 7 ins. diam., bears N. 25° W., 9 lks. dist., mkd. T15N R12E S15 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E
S15 | S14
S22 | S23
 1966

from which

A juniper, 6 ins. diam., bears N. 20¾° W., 60 lks. dist., mkd. S15 BT.

Cor. is on a W. slope, in thick timber.

The point for the cor. of secs. 10, 11, 14 and 15 is determined by using record bearing and distance from the remains of the original bearing trees

A pinon, 14 ins. diam., bears S. 70½° E., 337 lks. dist., mkd. T15N R12E S14 BT.

A juniper, 18 ins. diam., bears S. 10° W., 224 lks. dist., mkd. T15N R12E S15 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T15N R12E
S10 | S11
S15 | S14
 1966

Cor. is on nearly level land at the cor. of fences bearing S. and E. and 35 lks. south of track road bearing E. and W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, is monumented by a malpais stone, 8x12x18 ins., set in a small mound of stone, mkd. $\frac{1}{4}$ on the N., from which the original bearing trees

A pinon, 12 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ E., 187 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pinon, 16 ins. diam., bears N. 85° W., 127 lks. dist., mkd. $\frac{1}{4}$ S BT; tree is dead and has fallen.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

$\frac{1}{4}$ S11
S14

1966

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on gently rolling land, and at the S. edge of a railed area.

The cor. of secs. 2, 3, 10 and 11, is monumented by a limestone, 8x12x16 ins., set in a mound of stone, mkd. with 5 notches on the S. and 2 notches on the E., from which the original bearing trees

A dead pinon, 14 ins. diam., bears S. $25\frac{1}{2}^{\circ}$ E., 176 lks. dist., mkd. T15N R12E S11 BT.

A pinon, 10 ins. diam., bears S. 7° W., 261 lks. dist., mkd. T15N R12E S10 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in solid rock, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

S 3 | S 2
S10 | S11

1966

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is near the top of a rim facing W.; rim bears N. and S.

The $\frac{1}{4}$ sec. cor. of secs. 33 and 34 is monumented by a sandstone, 6x11x20 ins., firmly set, mkd. $\frac{1}{4}$ on the W., from which the remains of the original bearing trees

An oak stump, bears S. 5° E., 19 lks. dist.

A pine, 20 ins. diam., bears N. 64° W., 33 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N R12E

$\frac{1}{4}$ S33 | S34

1966

12

CHAINS

from which

A pine, 22 ins. diam., bears N. $14\frac{3}{4}^{\circ}$ W., 29 lks. dist., mkd. T15N R12E S33 BT.

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is about 200 lks. W. of a ridge top bearing N. and S.

The cor. of secs. 27, 28, 33 and 34, is monumented by a sandstone, 4x12x22 ins., firmly set, mkd. with 3 notches on the E. and 1 notch on the S., from which the remains of the original bearing trees

A pine, 20 ins. diam., bears N. 14° E., 22 lks. dist., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears S. 48° W., 87 lks. dist., mkd. with an overgrown blaze.

A juniper, 16 ins. diam., bears N. 40° W., 25 lks. dist., mkd. with an overgrown blaze; I remark this tree T15N R12E S28 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E	
S28	S27
S33	S34
1966	

from which

An oak, 7 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ E., 73 lks. dist., mkd. T15N R12E S34 BT.

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land, in thick timber.

The cor. of secs. 21, 22, 27 and 28, is monumented by a large sandstone in place, 1x4x5 ft. above ground, mkd. by an X, with 3 notches on the E. and 2 notches on the S., from which the original bearing trees

A pine, 20 ins. diam., bears N. 42° E., 56 lks. dist., mkd. with an overgrown blaze.

A pine, 32 ins. diam., bears S. 39° E., 118 lks. dist., mkd. with an overgrown blaze.

A pine, 14 ins. diam., bears S. 58° W., 69 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears N. $26\frac{1}{2}^{\circ}$ W., 144 lks. dist., mkd. T15N R12E S21 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in sandstone in place, and in a mound of stone to the top, with brass cap mkd.

T15N R12E	
S21	S22
S28	S27
1966	

from which

CHAINS

A pine, 22 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ E., 65 lks. dist., mkd. T15N R12E S22 BT.

A pine, 10 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W., 46 lks. dist., mkd. T15N R12E S28 BT.

Cor. is among thick timber and undergrowth, on a W. slope and 20 lks. E. of a wash, 15 lks. wide, 2 ft. deep, drains NE.

The cor. of secs. 15, 16, 21 and 22, is monumented by a sandstone, 6x10x20 ins., lying loose on the ground, mkd. with 3 notches on one side, from which the remains of the original bearing trees

A pine, 15 ins. diam., bears N. $22\frac{1}{2}^{\circ}$ E., 162 lks. dist., mkd. with an overgrown blaze.

A fallen pine, bears S. 86° E., 152 lks. dist., mkd. T15N R12E S22 BT.

A stump hole, bears S. 28° W., 36 lks. dist.

A dead pine, 22 ins. diam., bears N. 41° W., 104 lks. dist., mkd. T15N R12E S16 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E
S16 | S15
S21 | S22
 1966

from which

A pine, 8 ins. diam., bears S. 65° E., 142 lks. dist., mkd. S22 BT.

A pine, 12 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ W., 57 lks. dist., mkd. T15N R12E S16 BT.

Bury the original corner stone alongside the iron post.

Cor. is on an E. slope 80 lks. W. of track road bearing SE. and NW., and 120 lks. W. of a wash, 20 lks. wide, 1 ft. deep, drains NW.

The cor. of secs. 9, 10, 15 and 16, is monumented by a malpais stone, 8x12x18 ins., set in a mound of stone, mkd. with 4 notches on the S. and 3 notches on the E., from which the remains of the original bearing trees

A pinon, 8 ins. diam., bears N. 12° E., 53 lks. dist., mkd. T15N R12E S10 BT.

A fallen pinon, 14 ins. diam., bears S. 43° E., 20 lks. dist., mkd. T15N R12E S15 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E
S 9 | S10
S16 | S15
 1966

Bury the original corner stone alongside the iron post.

CHAINS

Cor. is on top of a low spur sloping N., and is 27 lks. N. of an E. and W. fence.

The cor. of secs. 3, 4, 9 and 10, is monumented by a malpais stone, 5x12x18 ins., set in a mound of stone, mkd. with 4 notches on the E. and 5 notches on the S., from which the original bearing trees

A fallen pinon, 9 ins. diam., bears N. 38° E., 31 lks. dist., mkd. T15N R12E S3 BT.

A fallen pinon, 11 ins. diam., bears S. 36° E., 44 lks. dist., mkd. T15N R12E S10 BT.

A pinon, 8 ins. diam., bears S. 27° W., 23 lks. dist., mkd. T15N R12E S9 BT.

A fallen pinon, 10 ins. diam., bears N. 2° W., 43 lks. dist., mkd. T15N R12E S4 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

S 4	S 3
S 9	S 10

 1966

from which

A pinon, 5 ins. diam., bears S. 63½° E., 24 lks. dist., mkd. S10 BT.

A pinon, 6 ins. diam., bears N. 32½° W., 24 lks. dist., mkd. T15N R12E S4 BT.

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on nearly level land in thick timber 24 lks. E. of a fence cor., from which fences bear N. and W.

The cor. of secs. 28, 29, 32 and 33, is monumented by a sandstone, 8x11x18 ins., set loosely in a small mound of stone, mkd. with 4 notches on the E. and 1 notch on the S., from which the remains of the original bearing trees

A pine stump, 16 ins. diam., bears N. 7½° E., 48 lks. dist.

A pine stump, 16 ins. diam., bears S. 43° E., 6 lks. dist.

A pine stump, 30 ins. diam., bears S. 70° W., 101 lks. dist., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears N. 78° W., 72 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

CHAINS

T15N R12E
 $\frac{S29}{S32}$ | $\frac{S28}{S33}$
 1966

from which

A juniper, 4 ins. diam., bears N. $6\frac{1}{2}^{\circ}$ E., $8\frac{1}{2}$ lks. dist., mkd. X BT.

Bury the original corner stone alongside the iron post.

Cor. is on a SE. slope, about 3.00 chs. E. of a large draw draining N.; a fence cor. bears North 1.00 ch. dist., fences bear N. and SW.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, is monumented by a sandstone $6 \times 11 \times 17$ ins., firmly set, mkd. with $\frac{1}{4}$ on the N., from which the original bearing trees

An oak, 6 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ E., 66 lks. dist., mkd. with an overgrown blaze.

A pine, 26 ins. diam., bears N. 22° W., 68 lks. dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E
 $\frac{1}{4}$ $\frac{S28}{S33}$
 1966

from which

An oak, 5 ins. diam., bears N. 61° W., 42 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on gently rolling land among moderate timber and undergrowth.

The cor. of secs. 20, 21, 28 and 29, is monumented by a sandstone, $4 \times 11 \times 20$ ins., firmly set, mkd. with 2 notches on the S. and 4 notches on the E., from which the remains of the original bearing trees

A pine, 16 ins. diam., bears S. 2° E., 35 lks. dist., mkd. with an overgrown blaze.

A juniper, 12 ins. diam., bears S. 78° W., 139 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears N. $47\frac{1}{2}^{\circ}$ W., 84 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

16

CHAINS

T15N R12E
S20 | S21
S29 | S28
 1966

from which

An oak, 9 ins. diam., bears S. 29° E., 83 lks. dist., mkd. T15N R12E S28 BT.

An oak, 5 ins. diam., bears N. 27° W., 55 lks. dist., mkd. S20 BT.

Bury the original corner stone alongside the iron post.

Cor. is among thick timber and undergrowth 50 lks. W. of a shallow draw, draining N.

The cor. of secs. 16, 17, 20 and 21, is monumented by a sandstone, 5x12x14 ins., lying loose on the ground, mkd. with 3 notches on the S. and 4 notches on the E., from which the original bearing trees

A pine, 15 ins. diam., bears N. 69½° E., 104 lks. dist., mkd. T15N R12E S16 BT.

A pine, 22 ins. diam., bears S. 4° E., 109 lks. dist., mkd. with an overgrown blaze.

A pine, 21 ins. diam., bears S. 63° W., 149 lks. dist., mkd. with an overgrown blaze.

A pine, 26 ins. diam., bears N. 71° W., 212 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N R12E
S17 | S16
S20 | S21
 1966

from which

A pine, 7 ins. diam., bears N. 32° E., 159 lks. dist., mkd. S16 BT.

A pine, 30 ins. diam., bears S. 71¾° W., 150 lks. dist., mkd. T15N R12E S20 BT.

Raise a mound of stone W. of the iron post.

Deposit the original corner stone in the mound of stone W. of the iron post.

Cor. is in moderate timber in the bottom of a wide draw draining N. 10° W., and 40 lks. W. of a track road bearing S. 10° E. and N. 10° W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, is monumented by a sandstone, 8x12x22 ins., lying loose on the ground, mkd. $\frac{1}{4}$, from which the remains of the original bearing trees

A juniper stump, 9 ins. diam., bears N. 37° E., 36 lks. dist.

A pinon, 14 ins. diam., bears N. 66° W., 44 lks. dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N R12E

$\frac{1}{4}$
S17 | S16
1966

from which

A juniper, 24 ins. diam., bears N. 44° E., 35 lks. dist., mkd. T15N R12E $\frac{1}{4}$ S16 BT.

A juniper, 5 ins. diam., bears S. 25° E., 48 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

Raise a mound of stone W. of the iron post.

Deposit the original corner stone in the mound of stone W. of the iron post.

Cor. is on a gentle S. slope among moderate timber and undergrowth.

The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, is monumented by a malpais stone, 6x7x12 ins., lying loose on the ground, mkd. $\frac{1}{4}$, from which the original bearing trees

A fallen pinon, 13 ins. diam., bears N. 54° E., 16 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pinon, 11 ins. diam., bears S. 15° W., 11 lks. dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N R12E

$\frac{1}{4}$ $\frac{S 9}{S16}$

1966

from which

A pinon, 15 ins. diam., bears S. 76 $\frac{3}{4}$ ° E., 18 lks. dist., mkd. T15N R12E $\frac{1}{4}$ S16 BT.

Bury the original corner stone and a sandstone 6x4x4 ins. mkd. X, alongside the iron post.

Cor. is in nearly level area among thick timber.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, is monumented by a sandstone, 4x13x20 ins., loosely set, mkd. $\frac{1}{4}$ on the W., from which the remains of the original bearing trees

A pine, 14 ins. diam., bears N. $9\frac{1}{2}^\circ$ E., 170 lks. dist., mkd. with an overgrown blaze.

A pine stump, 34 ins. diam., bears N. $19\frac{1}{2}^\circ$ W., 87 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

$\frac{1}{4}$
S 8 | S 9
1966

from which

A pine, 40 ins. diam., bears N. $52\frac{3}{4}^\circ$ W., 193 lks. dist., mkd. T15N R12E $\frac{1}{4}$ S8 BT.

Bury the original corner stone alongside the iron post.

Cor. is at the W. edge of clearing and 100 lks. W. of a track road bearing N. and S.

The point for the cor. of secs. 4, 5, 8 and 9, is determined by using record bearing and distance from the remaining original bearing trees

A pine, 32 ins. diam., bears N. 61° E., 176 lks. dist., mkd. T15N R12E S4 BT.

A pine, 20 ins. diam., bears S. 19° E., 236 lks. dist., mkd. with an overgrown blaze.

A juniper, 10 ins. diam., bears S. $52\frac{1}{2}^\circ$ W., 374 lks. dist., mkd. T15N R12E S8 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15N R12E

S 5 | S 4
S 8 | S 9
1966

from which

The center of a metal water tank, 60 ft. diam., bears SE. 100 lks. dist.

Raise a mound of stone W. of the iron post.

Cor. is in the bottom of a wide draw draining NE. and 100 lks. S. of an E. and W. fence.

Remonumentation, T. 15 N., R. 12 E., Arizona

19.

CHAINS

The cor. of secs. 29, 30, 31 and 32, is monumented by a sandstone, 8x11x16 ins., set 6 ins. in the ground and in a mound of stone, mkd. with 1 notch on the S. and 5 notches on the E., from which the original bearing trees

A juniper, 18 ins. diam., bears N. 19° E., 55 lks. dist., mkd. with an overgrown blaze; I remark this tree T15N R12E S29 BT.

A pine, 24 ins. diam., bears S. 57° E., 66 lks. dist., mkd. with an overgrown blaze.

A pine, 28 ins. diam., bears S. 53° W., 32 lks. dist., mkd. with an overgrown blaze.

A juniper, 24 ins. diam., bears N. 82° W., 42 lks. dist., mkd. T15N R12E S30 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N	R12E
S30	S29
S31	S32
1966	

from which

A juniper, 6 ins. diam., bears N. 78° W., 53 lks. dist., mkd. T15N R12E S30 BT.

Bury the original corner stone alongside the iron post.

Cor. is on gently rolling land, about 8.00 chs. E. of State Highway #65.

The cor. of secs. 19, 20, 29 and 30, is monumented by a sandstone, 6x12x18 ins., firmly set in the ground, and in a mound of stone, mkd. with 2 notches on the S. and 5 notches on the E., from which the original bearing trees

A pine, 26 ins. diam., bears N. 38½° E., 31 lks. dist., mkd. with an overgrown blaze; I remark this tree T15N R12E S20 BT.

A pine, 30 ins. diam., bears S. 36° E., 160 lks. dist., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears S. 51° W., 64 lks. dist., mkd. with an overgrown blaze; I remark this tree S30 BT.

A pine, 26 ins. diam., bears N. 7° W., 29 lks. dist., mkd. with an overgrown blaze; I remark this tree T15N R12E S19 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

CHAINS

T15N R12E

S19|S20

S30|S29

1966

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on rolling land among moderate timber and about 1.50 chs. E. of State Highway #65.

The cor. of secs. 17, 18, 19 and 20, is monumented by a limestone, 10x12x18 ins., set 5 ins. in the ground, and in a small mound of stone, mkd. with 3 notches on the S. and 5 notches on the E., from which the remains of the original bearing trees

A pine stump, 24 ins. diam., bears N. 79° E., 123 lks. dist.

A pinon, 10 ins. diam., bears S. 30° E., 223 lks. dist.; blaze is partly grown over, E S20 BT still visible.

A fallen oak, 6 ins. diam., bears S. 71° W., 108 lks. dist.

A stump hole bears N. 31½° W., 113 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

S18|S17

S19|S20

1966

from which

A pine, 5 ins. diam., bears S. 55° E., 34 lks. dist., mkd. X BT.

A pinon, 8 ins. diam., bears N. 47½° W., 28 lks. dist., mkd. T15N R12E S18 BT.

Bury the original corner stone alongside the iron post.

Cor. is on rolling land among moderate timber.

The ¼ sec. cor. of secs. 17 and 18, is monumented by a malpais stone, 10x14x20 ins., set 6 ins. in the ground, mkd. ¼ on the W., from which the remains of the original bearing trees

A pine, 18 ins. diam., bears N. 64° E., 89 lks. dist., mkd. with an overgrown blaze.

A pine stump, 30 ins. diam., bears S. 84° W., 100 lks. dist., mkd. with an overgrown blaze.

At the cor. point

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

$\frac{3}{4}$
S18|S17
1966

from which

A pine, 5 ins. diam., bears S. $84\frac{1}{2}^\circ$ W., 16 lks. dist., mkd. X BT.

Bury the original corner stone alongside the iron post.

Cor. is in moderate timber, 100 lks. E. of a small draw, draining NE.

The cor. of secs. 7, 8, 17 and 18, is monumented by a malpais stone, 6x12x18 ins., set 8 ins. in the ground, and in a mound of stone, mkd. with 4 notches on the S. and 5 notches on the E., from which the original bearing trees

A pine, 16 ins. diam., bears N. 73° E., 162 lks. dist., mkd. with an overgrown blaze.

A pinon, 12 ins. diam., bears S. 73° E., 142 lks. dist., mkd. with an overgrown blaze.

A pinon, 16 ins. diam., bears S. 40° W., 40 lks. dist., mkd. T15N R12E S18 BT.

A pinon, 13 ins. diam., bears N. 63° W., 91 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

S 7|S 8
S18|S17
1966

from which

A pinon, 12 ins. diam., bears S. 11° W., 20 lks. dist., mkd. T15N R12E S18 BT.

A pinon, 7 ins. diam., bears N. 30° W., 18 lks. dist., mkd. S7 BT.

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on level land in moderate timber, and about 5.00 chs. W. of State Highway #65.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, is monumented by a malpais stone, 7x14x30 ins., lying loose on the ground, mkd. $\frac{1}{4}$ on the N., from which the original bearing trees

A pine stump, 6 ft. high, 30 ins. diam., bears S. $8\frac{1}{2}^{\circ}$ W., 93 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pine, 20 ins. diam., bears N. 21° W., 73 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to the top, with brass cap mkd.

T15N R12E

$\frac{1}{4}$ $\frac{S\ 8}{S17}$

1966

from which

A pinon, 6 ins. diam., bears N. 42° E., 54 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A pine, 5 ins. diam., bears N. $74\frac{1}{2}^{\circ}$ W., 68 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on an E. slope, about 3.00 chs. W. of a road in the bottom of a wide draw, draining NW.

Form 4-680
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
U. S. Forest Service personnel:	
Gordon H. Long	Cadastral Surveyor
John Higgins	Engineering Assistant
Jim Muth	Engineering Assistant

24

BOOK4792

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25 day of March, 19 66, I have remonumented cadastral survey corners in Township 15 North, Range 12 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 16, 1966 (Date)

Wallace R. Ott (Cadastral Surveyor) (Supervisory Surveying Technician)

(Date)

(Cadastral Surveyor)

SUBMITTED FOR APPROVAL Date FEB 15 1967

CERTIFICATE OF APPROVAL Bureau of Land Management

The foregoing field notes of the remonumentation of cadastral survey corners in Township 15 North, Range 12 East, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician, having been critically examined and found correct, are hereby approved. Washington, D.C.

MAY 18 1967 (Date)

E. S. ... (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)