

BOOK 4799

Form 4-679  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

SURVEY

of the

EAST BOUNDARY

and a

COMPLETION SURVEY

of the

SUBDIVISIONAL LINES

of

Township 4 North, Range 7 East

Of the Gila and Salt River Meridian,

In the State of Arizona

## EXECUTED BY

Paul G. Bauer, Cadastral Surveyor

Under special instructions dated September 15, 19 65, which provided for the surveys included under Group Number 435, approved September 17, 1965, and assignment instructions dated March 4 and 18, 19 66.

Survey commenced March 25, 19 66

Survey completed May 4, 19 66

119

# BOOK 4799 INDEX DIAGRAM

Township 4 North, Range 7 East

6	5	4 27	8 26	2 13	1 5
			26	25	13
7	8	9	10 24	11 12	12 4
			24	23	11
18	17	16	15 22	14 10	13 4
			22	21	9
19	20	21	22 20	23 9	24 3
			19	19	8
30	29	28	27 17	26 8	25 2
			16	16	7
31	32	33	34 15	35 6	36 2

BOOK 4799

Township 4 North, Range 7 East  
Gila and Salt River Meridian, Arizona

10

CHAINS

The north boundary, the First Standard Parallel North, was surveyed in 1867 by W. H. Pierce. The east 2½ miles was resurveyed in 1878 by W. A. Hancock.

The west boundary, a portion of the south boundary, and the boundaries of the Fort McDowell Indian Reservation were surveyed in 1900 by H. Santee.

The area within the Fort McDowell Indian Reservation was subdivided and the meander lines of the Verde River were surveyed in 1902 by P. Contzen.

In 1911, R. A. Farmer resurveyed the boundaries of the Fort McDowell Indian Reservation and the subdivisional lines and meander lines of the Verde River within the reservation.

S. E. Blout resurveyed the north 1 mile of the west boundary in 1919.

Homestead Entry Survey No. 413 was surveyed in 1915 by Walter G. Turley.

The west 2 miles of the north boundary, the First Standard Parallel North, was independently resurveyed, and secs. 5, 6, 7 and 8 and the meanders of the Verde River lying outside Fort McDowell Indian Reservation were surveyed in 1963 by Leonard W. Murphy.

The east 4 miles of the north boundary, the First Standard Parallel North, was concurrently resurveyed by Paul G. Bauer under this same group and is described in the field notes of Township 5 North, Range 7 East.

The east portion of the south boundary was concurrently surveyed by Wallace R. Ott under Group 434, and described in the field notes of Township 3 North, Range 7 East.

The following field notes are those of a survey of the east boundary and a portion of the subdivisional lines of Township 4 North, Range 7 East, of the Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated September 15, 1965.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of Township 4 North, Range 7 East, is: Latitude 33°38'25.3" North, and Longitude 111°34'47.8" West, as determined by a traverse from Coast & Geodetic Survey Triangulation Station, "Texas" (Adams).

The mean magnetic declination was found to be 14° East.

BOOK 4799

2

Survey, E., Bdy., T. 4 N., R. 7 E., Arizona

2.

CHAINS

Survey of the East Boundary  
Township 4 North, Range 7 East, Arizona

From the Tp. cor. of Tps. 3 and 4 N., Rs. 7 and 8 E.,  
monumented by an iron post, 2½ ins. diam., as described  
in the field notes of the concurrent survey of  
T. 3 N., R. 7 E., Group 434.

North, bet. secs. 31 and 36.

Over rolling land, through moderate palo verde.

15.20 Large wash, 90 lks. wide, ½ ft. deep, drains N. 35° W.

37.00 Spur, slopes N. 50° W.

40.00 Point for the ¼ sec. cor. of secs. 31 and 36.

Set the iron post 14 ins. in the ground, in a collar  
of stone, brass cap mkd.

T4N  
R7E R8E  
¼  
S36|S31

1966

45.70 Wash, 20 lks. wide, ½ ft. deep, drains N. 40° W.

64.60 Spur, slopes N. 60° W.

78.70 Wash, 15 lks. wide, ½ ft. deep, drains N. 60° W.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set the iron post 22 ins. in the ground, brass cap  
mkd.

T4N  
R7E R8E  
S25|S30  
S36|S31

1966

Build a mound of stone W. of the iron post.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

North, bet. secs. 25 and 30.

Over rolling land, through moderate palo verde.

13.20 Spur, slopes W.

19.50 Wash, 30 lks. wide, 1 ft. deep, drains N. 40° W.

37.80 Wash, 20 lks. wide, ½ ft. deep, drains N. 80° W.

40.00 Point for the ¼ sec. cor. of secs. 25 and 30.

BOOK 4799

E. Bdy., T. 4 N., R. 7 E., Arizona

3.

CHAINS		
	<p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E R8E <math>\frac{1}{4}</math> S25 S30 1966</p>	
50.80	<p>Sycamore Creek, 325 lks. wide, 2 ft. deep, drains N. 80° W., no flowing water.</p>	
71.17	<p>U. S. Forest Service road, No. 403, bears NE. and S. 84° W.</p>	
80.00	<p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R7E R8E S24 S19 S25 S30 1966</p> <p>Build a mound with stone W. of the iron post.</p> <p>Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.</p>	
	<p>North, bet. secs. 19 and 24.</p>	
	<p>Over rolling land, through moderate palo verde.</p>	
25.70	<p>Draw, drains SW.</p>	
35.70	<p>Draw, drains SW.</p>	
39.50	<p>Spur, slopes SW.</p>	
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24.</p> <p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E R8E <math>\frac{1}{4}</math> S24 S19 1966</p>	
58.50	<p>Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.</p>	
70.50	<p>Spur, slopes S. 80° W.</p>	
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E R8E S13 S18 S24 S19 1966</p>	

BOOK 4799

E. Bdy., T. 4 N., R. 7 E., Arizona

4.

4

CHAINS

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

North, bet. secs. 13 and 18.

Over rolling land, through moderate palo verde.

14.40

Draw, drains SE.

26.60

Low saddle of ridge, bears N. 51° E. and S. 51° W.

38.60

Wash, 30 lks. wide, ½ ft. deep, drains S. 80° W.

40.00

Point for the ¼ sec. cor. of secs. 13 and 18.

Set the iron post 20 ins. in the ground, brass cap mkd.

T4N  
R7E R8E  
½  
S13|S18

1966

Build a mound with stone W. of the iron post.

47.00

Draw, drains SW.

68.80

High spur, slopes SW.

80.00

Point for the cor. of secs. 7, 12, 13 and 18.

Set the iron post 9 ins. in the ground, mound with stone to top, brass cap mkd.

T4N  
R7E R8E  
S12|S 7  
S13|S18

1966

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

North, bet. secs. 7 and 12.

Over rolling land, through moderate palo verde.

.40

Enter wash bottom (Ironwood Wash), drains NW.

2.00

Track road, bears S. 25° W. and N. 25° E.

5.40

Leave wash bottom.

17.50

Wash, 10 lks. wide, 1 ft. deep, drains S. 25° W.

25.70

Same wash, drains S. 40° E.

40.00

Point for the ¼ sec. cor. of secs. 7 and 12.

CHAINS	
	<p>Set the iron post 9 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E R8E <math>\frac{1}{2}</math> S12   S 7 1966</p>
55.90	Spur, slopes S. 30° W.
61.40	Draw, drains W. from NE., asc. SE. slope.
67.90	4-strand barbed wire fence, bears N. 80° E. and S. 80° W. for 2.05 chs., thence bears SW.
79.30	Enter wash bottom.
79.45	Track road, bears E. and W.
80.00	Point for the cor. of secs. 1, 6, 7 and 12.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R7E R8E <u>S 1   S 6</u> S12   S 7 1966</p> <p>Build a mound with stone W. of the iron post.</p> <p>Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.</p>
	North, bet. secs. 1 and 6.
	Over rolling land, through moderate palo verde.
.50	Wash, 30 lks. wide, 1 ft. deep, drains W.
1.10	Leave wash bottom; asc. over steep S. slope of Black Mesa.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 1 and 6.
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
	<p style="text-align: center;">T4N R7E R8E <math>\frac{1}{2}</math> S 1   S 6 1966</p>
45.50	Top of ridge, bears NE. and W., desc. over N. slope.
65.60	Wash, 20 lks. wide, 1 ft. deep, drains SW., asc. SE. slope.
73.90	Base of rocky ledge, 40 ft. high, bears N. 10° E. and S. 10° W.
74.50	Top of same ledge, continue asc.
78.50	Intersect the First Standard Parallel North.
	Point for the closing cor. of T. 4 N., Rs. 7 and 8 E.

6

CHAINS

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

S36  
S 1 | S 6  
R7E | R8E

T4N

CC

1966

From point of intersection, the Standard Tp. cor. of T. 5 N., Rs. 7 and 8 E., bears East, 9.41 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the concurrent survey of T. 5 N., R. 7 E.

Land, heavy rolling.  
Soil, gravelly loam and rocky.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

Completion Survey of the Subdivisional Lines,  
Township 4 North, Range 7 East, Arizona

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., as described in the field notes of the concurrent survey of T. 3 N., R. 7 E., Group 434.

from which

Triangulation Station "Texas," bears N.  
50°02'09" E., 33.57 chs. dist.

N. 0°01' W., bet. secs. 35 and 36.

Over rolling land, through moderate palo verde.

- 1.80 Draw, drains NW.
- 3.00 Draw, drains S. 30° W., asc. SE. slope.
- 16.40 Spur, slopes SW., desc. NW. slope.
- 30.70 Draw, drains S. 30° W., asc. SE. slope.
- 38.40 Saddle on ridge, bears N. 70° E. and S. 70° W., desc. NW. slope.
- 40.00 Point for the ¼ sec. cor. of secs. 35 and 36.

Set the iron post 4 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E

½  
S35 | S36

1966

- 65.90 Draw, drains NW.
- 67.70 Same draw, drains NE.
- 79.20 Draw, near head, drains N. 10° E.
- 80.00 Point for the cor. of secs. 25, 26, 35 and 36.



CHAINS

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

T4N	R7E
S26	S25
S35	S36

1966

Build a mound with stone W. of the iron post.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

N. 89°55' E., bet. secs. 25 and 36.

Over rolling land, through moderate palo verde.

- 0.10 Small draw, drains N. 10° E., asc. W. slope.
- 3.10 Spur, slopes N. 20° E., desc. E. slope.
- 6.60 Wash, 15 lks. wide, 1½ ft. deep, drains NE.
- 13.70 Wash, 20 lks. wide, 1½ ft. deep, drains N. 30° W.
- 17.80 Spur, slopes N. 30° W.
- 33.10 Wash, 10 lks. wide, 1½ ft. deep, drains N.
- 37.30 Spur, slopes N.
- 39.00 Enter wash bottom area with drainage to N.
- 40.00 Point for the ¼ sec. cor. of secs. 25 and 36.

Set the iron post 22 ins. in the ground, brass cap mkd.

T4N	R7E
¼ S25	
S36	

1966

Build a mound with stone N. of the iron post.

- 43.00 Leave wash bottom area, asc. W. slope.
- 48.00 Spur, slopes N., desc. E. slope.
- 58.60 Wash, 30 lks. wide, ½ ft. deep, drains NW.
- 64.80 Spur, slopes N. 30° E., desc. NE. slope.
- 67.50 Enter wash bottom area with drainage to NW.
- 74.58 The cor. of secs. 25, 30, 31 and 36 on the E. Bdy. of the Tp.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti, creosote and scattered cat claw.

BOOK 4799

Subdivision, T. 4 N., R. 7 E., Arizona

8

8.

CHAINS

From the cor. of secs. 25, 26, 35 and 36.

N. 0°01' W., bet. secs. 25 and 26.

Over rolling land, through moderate palo verde.

2.30 Spur, slopes N. 10° E.

6.60 Enter wash bottom with drainage to NW.

13.00 Wash, 20 lks. wide, 1 ft. deep, drains NW.

15.20 Leave wash bottom, asc. SW. slope.

19.50 Spur, slopes N. 80° W., desc. N. slope.

25.70 Enter Sycamore Creek bottom land, bears S. 70° E. and N. 70° W.

40.00 Point for the ¼ sec. cor. of secs. 25 and 26.

Set the iron post 22 ins. in the ground, brass cap mkd.

T4N R7E

½  
S26 | S25

1966

Build a mound with stone W. of the iron post.

50.50 Main channel in Sycamore Creek (dry), 310 lks. wide, ½ ft. deep, drains W.

58.35 Bladed road, bears N. 70° E. and S. 62° W.

59.90 Leave bottom land of Sycamore Creek.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E

S23 | S24  
S26 | S25

1966

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

N. 89°55' E., bet. secs. 24 and 25.

Over rolling land, through moderate palo verde.

15.80 Ironwood Wash, 30 lks. wide, 1 ft. deep, drains S.

40.00 Point for the ¼ sec. cor. of secs. 24 and 25.

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

T4N R7E

¼  
S24  
S25

1966

BOOK 4799

Subdivision, T. 4 N., R. 7 E., Arizona

9.

CHAINS		
	Raise a mound of stone N. of the cor.	
42.80	Track road, bears N. and S.	
68.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.	
74.56	The cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp.	
	Land, rolling. Soil, gravelly loam. Timber, moderate palo verde and scattered ironwood. Undergrowth, moderate cacti and scattered cat claw and scrub mesquite.	
	From the cor. of secs. 23, 24, 25 and 26.	
	N. 0°01' W., bet. secs. 23 and 24.	
	Over rolling land, through moderate palo verde.	
25.50	Enter wash area, with drainage to SE.	
34.50	Wash, 20 lks. wide, 1 ft. deep, drains SE.	
38.70	Leave wash area.	
40.00	Point for the ¼ sec. cor. of secs. 23 and 24.	
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.	
	T4N R7E ¼ S23   S24  1966	
63.60	Enter wash area, drainage SW.	
66.40	Leave wash area, asc. S. slope.	
80.00	Point for the cor. of secs. 13, 14, 23 and 24.	
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.	
	T4N R7E S14   S13 S23   S24  1966	
	Build a mound with stone W. of the iron post.	
	Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.	
	N. 89°53' E., bet. secs. 13 and 24.	
	Over rolling land, through moderate palo verde, desc. E. slope.	
3.60	Enter wash area, drains S.	
7.10	Leave wash area, asc. W. slope.	

## CHAINS

- 11.60 Spur, slopes S., desc. E. slope.
- 26.20 Enter Ironwood Wash area, drains S.
- 26.70 Track road, in bottom of Ironwood Wash, bears S. 26° E. and N. 20° W.
- 36.60 Leave Ironwood Wash area, asc. W. slope.
- 38.30 Spur, slopes SW., desc. SE. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 24.
- Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E

$$\frac{\frac{1}{4}}{S13}$$

$$S24$$

1966

Thence over gently rolling land.

- 42.20 Wash, 20 lks. wide,  $\frac{1}{2}$  ft. deep, drains SW.
- 47.05 Wash, 30 lks. wide, 1 ft. deep, drains S. 60° W. from NE.
- 68.20 Wash, 30 lks. wide, 1 ft. deep, drains S.
- 71.60 Spur, slopes S. 30° W., desc. E. slope.
- 74.40 Low spur, slopes SE. for 2.50 chs.
- 74.65 The cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

From the cor. of secs. 13, 14, 23 and 24.

N. 0°01' W., bet. secs. 13 and 14.

Over rolling land, through moderate palo verde, asc. SE. slope.

- 6.90 Spur, slopes S. 10° W., asc. over W. slope.
- 30.00 Spur, slopes W.
- 33.80 Enter wash area, drains W.
- 37.00 Leave wash area, asc. S. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 14.
- Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E

$$\frac{\frac{1}{4}}{S14} | S13$$

1966

BOOK 4799

Subdivision, T. 4 N., R. 7 E., Arizona

11.

CHAINS	
41.80	Build a mound with stone W. of the iron post. Low spur, slopes SW., desc. NW. slope.
45.80	Draw, drains SW.
61.23	Fence, 4-strand barbed wire, bears N. 56° E. and S. 56° W.
61.30	Spur, slopes S. 56° W., desc. NW. slope.
76.90	Wash, 15 lks. wide, 1 ft. deep, drains SW., asc. SE. slope.
80.00	Point for the cor. of secs. 11, 12, 13, and 14. Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R7E <u>S11</u>   <u>S12</u> <u>S14</u>   <u>S13</u> 1966
	Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.
	N. 89°57' E., bet. secs. 12 and 13.
	Over rolling land, through moderate palo verde.
1.00	Wash, 10 lks. wide, ½ ft. deep, drains S., asc. steep NW. slope.
12.90	Ridge, bears N. 20° E. and S. 20° W.
13.20	Fence, 4-strand barbed wire, bears N. 21°30' E. and S. 21°30' W., desc. E. slope.
22.90	Draw, drains SE.
24.70	Enter wash area, bears N. and S.
32.20	Leave wash area, bears NE. and SW., drainage to the SW., asc. W. slope.
40.00	Point for the ¼ sec. cor. of secs. 12 and 13. Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R7E ¼ <u>S12</u> <u>S13</u> 1966
40.50	Bladed road on ridge, bears N. 25° E. and S. 25° W., desc. E. slope.
50.20	Enter Ironwood Wash area, drains S.
52.60	Jeep road, bears N. 20° E. and S., in main channel of Ironwood Wash.

BOOK 4799

12

Subdivision, T 4 N., R. 7 E., Arizona

12.

CHAINS	
59.10	Leave wash area, asc. SW. slope.
70.40	Spur, slopes NW., desc. over N. slope.
74.64	<p>The cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14. N. 0°01' W., bet. secs. 11 and 12.</p>
	Over rolling land, through moderate palo verde.
13.40	Ridge, bears E. and W., desc. N. slope.
22.60	Wash, 20 lks. wide, 1 ft. deep, drains W., asc. steep S. slope.
29.10	Ridge, bears E. and W., desc. steep N. slope.
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12.</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T4N R7E <math>\frac{1}{4}</math> S11   S12 1966</p>
	from which
	<p style="text-align: center;">Indian writing (petroglyph site), on numerous black lava rocks, bears S. 58°35' E., 29.07 chs. dist.</p>
43.75	Track road on ridge, bears E. and W., desc. steep N. slope.
55.80	Wash, 85 lks. wide, 1½ ft. deep, drains W., asc. S. slope.
64.80	Spur, slopes SW., thence over rolling W. slope.
71.60	Draw, drains S. 35° W. from NE., asc. SE. slope.
78.10	Ridge, bears E. and W., desc. steep N. slope.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T4N R7E S 2   S 1 S11   S12 1966</p>
	<p>Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.</p>

BOOK 4799

Subdivision, T. 4 N., R. 7 E., Arizona

13.

CHAINS		
	<p>N. 89°58' E., bet. secs. 1 and 12.</p> <p>Over rolling land, through moderate palo verde, asc. over N. slope.</p>	
8.60	Low spur, slopes N., desc. E. slope.	
10.80	Wash, 20 lks. wide, 1 ft. deep, drains N., asc. W. slope.	
31.10	Spur, slopes S., desc. E. slope.	
35.40	Draw, drains S., asc. W. slope.	
40.00	<p>Point for the ¼ sec. cor. of secs. 1 and 12.</p> <p>Set the iron post on bed rock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E ¼ <math>\frac{S 1}{S 12}</math> 1966</p> <p>from which</p> <p style="text-align: center;">Dyke between twin stock tanks, known as Black Mesa tanks, bears S. 50°40' E., 21.81 chs. dist.</p>	
41.00	Spur, projects 50 lks. S., desc. E. slope.	
49.00	Draw, drains S.	
54.60	Spur, slopes S.	
59.60	Draw, drains S.	
63.30	Spur, slopes S.	
73.50	Wash, 30 lks. wide, 1 ft. deep, drains SW.	
74.63	<p>The cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp.</p> <p>Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.</p>	
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Desc. over W. slope of Black Mesa.</p>	
4.80	Draw, drains W., head of draw, bears E. 6.00 chs. dist.	
8.00	Spur, projects W. for 2 chs., desc. N. slope.	
11.00	Wash, 25 lks. wide, 1½ ft. deep, drains W., asc. SW. slope.	
22.70	Draw, drains W.	

14

CHAINS		
36.50	Draw, drains W.	
39.90	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 1 and 2.	
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.	
	T4N R7E $\frac{1}{4}$ S 2   S 1 W C 1966	
40.00	True point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, falls on a steep W. face of a lava rock, impracticable to perpetuate.	
	Continue asc. over west slope of Black Mesa.	
74.30	Draw, drains W.	
78.58	Intersect the First Standard Parallel North.	
	Point for the closing cor. of secs. 1 and 2.	
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.	
	T5N R7E S 35 S 2   S 1 T4N   R7E C C 1966	
	From point of intersection, the standard cor. of secs. 35 and 36, bears East 3.98 chs. dist., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., as described in the field notes of the concurrent survey of T. 5 N., R. 7 E.	
	Land, rolling and mountainous. Soil, rocky and gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.	
	The point for the $\frac{1}{4}$ sec. cor. of sec. 1 is on the N. bdy. at 40 chs. in easting from the closing cor. of secs. 1 and 2.	
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.	
	$\frac{1}{4}$ S 1 T4N R7E 1966	
	From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 36, bears East, 3.98 chs. dist., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., as described in the field notes of the concurrent survey of T. 5 N., R. 7 E.	



CHAINS

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., monumented by an iron post as described in the field notes of the concurrent survey of T. 3 N., R. 7 E., Group 434.

N. 0°01' W., bet. secs. 34 and 35.

Over rolling land, through moderate palo verde.

1.30 Wash, 130 lks. wide, 1 ft. deep, drains W., asc. S. slope.

4.50 Spur, slopes W., desc. N. slope.

9.80 Draw, drains S. 20° W., from S. 30° E., asc. S. slope.

12.30 Spur, slopes W., desc. N. slope.

37.80 Wash, 10 lks. wide, ½ ft. deep, drains W.

40.00 Point for the ¼ sec. cor. of secs. 34 and 35.

Set the iron post 7 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E

¼  
S34|S35

1966

51.40 White quartz outcrop, bears E. and W.

72.30 Jeep road, bears E. and W.

72.90 Wash, 10 lks. wide, ½ ft. deep, drains W., asc. S. slope.

75.00 Spur, slopes N. 70° W.

77.30 Draw, drains NW., asc. S. slope.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set the iron post 20 ins. in the ground, brass cap mkd.

T4N R7E

S27|S26  
S34|S35

1966

from which

A windmill, bears N. 15°50' E., 40.14 chs. dist.

Build a mound with stone W. of the iron post.

Land, rolling.

Soil, gravelly loam.

Timber, moderate palo verde.

Undergrowth, moderate cacti.

16

CHAINS

From the cor. of secs. 25, 26, 35 and 36.  
 S. 89°56' W., bet. secs. 26 and 35.  
 Over rolling land, through moderate palo verde.  
 0.80 Spur, slopes N., desc. W. slope.  
 2.00 Draw, drains N.  
 13.10 Wash, 20 lks. wide, ½ ft. deep, drains N.  
 25.90 Wash, 20 lks. wide, ½ ft. deep, drains NW. from S.  
 33.40 Enter flooded area, drainage N.  
 38.40 Leave flooded area.  
 39.30 Spur, slopes N., desc. W. slope.  
 40.01 Point for the ¼ sec. cor. of secs. 26 and 35.  
 Set the iron post 20 ins. in the ground, brass cap mkd.

T4N R7E  
 ¼ S 26  
 S 35  
 1966

Build a mound with stone N. of the iron post.  
 40.30 Wash, 5 lks. wide, ½ ft. deep, drains N.  
 42.80 Wash, 30 lks. wide, ½ ft. deep, drains N.  
 61.40 Wash, 15 lks. wide, 1 ft. deep, drains N.  
 74.50 Wash, 10 lks. wide, ½ ft. deep, drains NW., asc. NE. slope.  
 80.02 The cor. of secs. 26, 27, 34 and 35.

Land, rolling.  
 Soil, gravelly loam.  
 Timber, moderate palo verde.  
 Undergrowth, moderate cacti.

S. 89°55' W., bet. secs. 27 and 34.  
 Over rolling land, through moderate palo verde.

6.00 Wash, 20 lks. wide, ½ ft. deep, drains NW.  
 6.90 Jeep road, bears S. 25° E. and N. 25° W.  
 22.00 Spur, slopes SW.  
 40.00 Point for the ¼ sec. cor. of secs. 27 and 34.  
 Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E  
 ¼ S 27  
 S 34  
 1966

BOOK 4799

Subdivision, T. 4 N., R. 7 E., Arizona

17.

CHAINS												
52.00	Enter Sycamore Creek bottom.											
62.20	Track road, bears N. and S.											
62.70	Sycamore Creek, 50 lks. wide, 1 ft. deep, drains SW.											
66.63	Intersect the E. bdy. of Fort McDowell Indian Reservation.											
	Point for the closing cor. of secs. 27 and 34 falls in wash area and was not monumented.											
	<u>Note:</u> This corner was not monumented during earlier surveys.											
	From point of intersection, the cor. of secs. 27, 28, 33 and 34, bears West, 13.28 chs. dist., monumented by an iron post, 1 in. diam., set, mkd., and witnessed as described in the official record of the 1911 survey.											
	From point of intersection, the WC 8½ MP, bears N. 6°43' E., 11.39 chs. dist., monumented by an iron post, 1 in. diam., set, mkd., and witnessed as described in the official record of the 1911 survey.											
	Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.											
	From the cor. of secs. 26, 27, 34 and 35.											
	N. 0°01' W., bet. secs. 26 and 27.											
	Over rolling land, through moderate palo verde.											
4.40	Wash, 5 lks. wide, 6 ins. deep, drains NW.											
12.60	Spur, slopes NW., desc. N. slope.											
15.30	Enter Sycamore Creek bottom land.											
18.40	Sycamore Creek, 1 ch. wide, 2 ft. deep, with some running water, drains S. 85° W.											
22.90	Leave wash area in Sycamore Creek.											
24.20	4-strand barbed wire fence, bears E. and W.											
25.91	Intersect line bet. cors. 6 and 7 of HES 413.											
	Point for the closing cor. of secs. 26 and 27.											
	Set the iron post 22 ins. in the ground, brass cap mkd.											
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">HES 413</td></tr> <tr><td style="text-align: center;">S27</td><td style="text-align: center;">S26</td></tr> <tr><td style="text-align: center;">T4N</td><td style="text-align: center;">R7E</td></tr> <tr><td style="text-align: center;">C</td><td style="text-align: center;">C</td></tr> <tr><td colspan="2" style="text-align: center;">1966</td></tr> </table>	HES 413		S27	S26	T4N	R7E	C	C	1966		
HES 413												
S27	S26											
T4N	R7E											
C	C											
1966												
	from which											
	Cor. No. 6 of HES 413 bears N. 78°23' E., 13.09 chs. dist., monumented by a quartzite stone, 24x10x8 mkd. "x" on top and 6 HES 413 on NW. face.											

CHAINS

Cor. No. 7 of HES 413, bears S. 78°23' W., 11.79 chs. dist., monumented by a basalt stone, 25x9x8 ins., mkd. "x" on top and 7 HES 413 on the N. face.

Build a mound of stone S. of the iron post.

40.00 Point for the 1/2 sec. cor. of secs. 26 and 27, falls within HES 413 and is not monumented.

41.50 Track road, bears N. 85° E. and S. 85° W.

42.33 4-strand barbed wire fence, bears N. 80° E. and S. 80° W.

42.35 Intersect line bet. cors. 4 and 5 of HES 413.

Point for the closing cor. of secs. 26 and 27.

Set the iron post 22 ins. in the ground, brass cap mkd.



1966

from which

Cor. No. 5 of HES 413, bears N. 80°10' E., 12.84 chs. dist., monumented by a quartzite stone, 25x12x6 ins., mkd. "x" on top and 5 HES 413 on the SW. face.

Cor. No. 4 of HES 413, bears S. 80°10' W., 45.38 chs. dist., monumented by a porphyry stone, 26x14x7 ins., mkd. "x" on top and 4 HES 413 on the S. face.

Build a mound with stones N. of the iron post.

43.60 Leave Sycamore Creek bottom land, asc. S. slope.


66.00 Spur, slopes SE.

69.00 Wash, 10 lks. wide, 6 ins. deep, drains SW.

72.90 Same wash, 5 lks. wide, 6 ins. deep, drains S. 20° W. from N. 70° E.

80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.



1966

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

CHAINS		
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°56' W., bet. secs. 23 and 26.</p> <p>Over rolling land, through moderate palo verde.</p>	
9.30	Wash, 5 lks. wide, 1 ft. deep, drains SW., asc. E. slope.	
14.30	Spur, slopes S., desc. W. slope.	
16.60	Enter wash area with drainage to S.	
22.00	Leave wash area, asc. E. slope.	
28.70	Spur, slopes S.	
32.90	Wash, 10 lks. wide, ½ ft. deep, drains S., asc. E. slope.	
37.30	Low spur, slopes S., desc. W. slope.	
38.80	Enter wash area with drainage to S.	
40.01	Point for the ¼ sec. cor. of secs. 23 and 26.	
	<p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E  <math>\frac{1}{4}</math> S 23  <math>\frac{1}{4}</math> S 26                      1966</p>	
40.40	Leave wash area, asc. E. slope.	
41.70	Spur, slopes S., desc. W. slope.	
45.50	Enter nearly level wash area.	
51.70	Leave wash area.	
53.50	Low spur, slopes S.	
66.80	Low spur, slopes S., desc. W. slope.	
76.30	Wash, 20 lks. wide, ½ ft. deep, drains S.	
78.50	Spur, slopes S., desc. W. slope.	
80.02	The cor. of secs. 22, 23, 26 and 27.	
	<p>Land, rolling.                      Soil, gravelly loam.                      Timber, moderate palo verde.                      Undergrowth, moderate cacti.</p>	
	<p>S. 89°55' W., bet. secs. 22 and 27.</p> <p>Over dry wash area, drains S.</p>	
2.40	Leave dry wash area, asc. E. slope.	
8.80	Spur, slopes SW. from N., thence over rolling land.	
20.20	Wash, 10 lks. wide, 1 ft. deep, drains S.	

CHAINS									
39.80	Wash, 10 lks. wide, 1 ft. deep, drains S.								
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.								
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.								
	<p style="text-align: center;">T4N R7E  <math>\frac{1}{4}</math> S 22  <math>\frac{1}{4}</math> S 27  1966</p>								
	Build a mound with stones N. of the iron post.								
	Asc. E. slope.								
41.60	Spur, slopes S., desc. W. slope.								
43.40	Wash, 10 lks. wide, 1/2 ft. deep, drains S.								
52.55	Jeep trail, bears NE. and SW.								
52.70	Spur, slopes SW., desc. NW. slope.								
55.30	Draw, drains SW., asc. SE. slope.								
57.21	4-strand barbed wire fence, bears N. 7° E. and S. 7° W.								
57.23	The closing cor. of secs. 22 and 27, on the E. bdy. of Fort McDowell Indian Reservation, monumented by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1911 survey. I re-mark the brass cap to read:								
	<p style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-left: 5px;">22</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R7E</td> <td style="padding-left: 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">T4N</td> <td style="padding-left: 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-left: 5px;">27</td> </tr> </table> <p style="text-align: center;">1966 1911</p> </p>	S	22	R7E		T4N		S	27
S	22								
R7E									
T4N									
S	27								
	Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.								
	From the cor. of secs. 22, 23, 26 and 27.								
	N. 0°01' W., bet. secs. 22 and 23.								
	Over rolling land, through moderate palo verde.								
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.								
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.								
	<p style="text-align: center;">T4N R7E  <math>\frac{1}{4}</math> S22   S23  1966</p>								
45.30	Draw, drains SE., asc. S. slope.								

CHAINS								
51.35	4-strand barbed wire fence, bears N. 67°50' E. and S. 67°50' W.							
52.00	Spur, slopes S. 67° W., thence asc. rolling SW. slope.							
72.20	Wash, 20 lks. wide, ½ ft. deep, drains S. 60° W.							
78.10	Spur, slopes SW., desc. NW. slope.							
79.10	Draw, drains SW., asc. SE. slope.							
80.00	Point for the cor. of secs. 14, 15, 22 and 23.  Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.							
	<table border="0"> <tr><td>T4N</td><td>R7E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td>S22</td><td>S23</td></tr> </table>	T4N	R7E	S15	S14	S22	S23	
T4N	R7E							
S15	S14							
S22	S23							
	1966							
	Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.							
	From the cor. of secs. 13, 14, 23 and 24.							
	S. 89°57' W., bet. secs. 14 and 23.							
	Over rolling land, through moderate palo verde.							
2.60	Spur, slopes S., desc. W. slope.							
7.10	Wash, 20 lks. wide, 1 ft. deep, drains S.; thence over gently rolling land.							
17.70	Wash area, 300 lks. wide, drains S.							
40.04	Point for the ¼ sec. cor. of secs. 14 and 23.  Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.							
	<table border="0"> <tr><td>T4N</td><td>R7E</td></tr> <tr><td>¼ S</td><td>14</td></tr> <tr><td>      </td><td>S 23</td></tr> </table>	T4N	R7E	¼ S	14		S 23	
T4N	R7E							
¼ S	14							
	S 23							
	1966							
49.70	Wash area, 350 lks. wide, drains S., asc. E. slope.							
54.20	High spur, slopes S. 24° E., also a 4-strand barbed wire fence on top of spur which bears S. 24°15'E. and N. 24°15' W., desc. W. slope.							
78.00	Draw, drains SW., asc. SE. slope.							
80.08	The cor. of secs. 14, 15, 22 and 23.  Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.							

CHAINS

S. 89°51' W., bet. secs. 15 and 22.

Over rolling land, through moderate palo verde.

39.20 Draw, drains S. 70° W. from NE.

40.00 Point for the 1/4 sec. cor. of secs. 15 and 22.

Set the iron post 18 ins. in the ground, brass cap mkd.


T4N R7E

1/4 S 15  
S 22

1966

Build a mound with stone N. of the iron post.

47.85 The closing cor. of secs. 15 and 22 on the E. bdy. of the Fort McDowell Indian Reservation, monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1911 survey. I re-mark the brass cap to read:



Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

From the cor. of secs. 14, 15, 22 and 23.

N. 0°01' W., bet. secs. 14 and 15.

Over rolling land, through moderate palo verde.

0.80 Low spur, slopes SW.

22.00 Wash, 20 lks. wide, 1 ft. deep, drains W. from NE.

35.80 Wash, 30 lks. wide, 1 ft. deep, drains W.

38.00 Wash, 20 lks. wide, 1 ft. deep, drains SW., asc. S. slope.

40.00 Point for the 1/4 sec. cor. of secs. 14 and 15.

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T4N R7E

1/4 S15 | S14

1966

Build a mound with stones W. of the cor.

73.00 Wash, 15 lks. wide, 1 ft. deep, drains SW., asc. SE. slope.



CHAINS	
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E  <u>S10   S11</u>            S15   S14</p> <p style="text-align: center;">1966</p> <p>Land, rolling.            Soil, gravelly loam.            Timber, moderate palo verde.            Undergrowth, moderate cacti.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°57' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through moderate palo verde, asc. SE. slope.</p>
6.50	Ridge, bears S. 30° W. and N. 30° E., desc. NW. slope.
14.90	Wash, 10 lks. wide, ½ ft. deep, drains S., asc. SE. slope.
17.50	Spur, slopes S., desc. W. slope.
20.50	Draw, drains S.
24.90	Low spur, slopes S., asc. E. slope.
34.30	Spur, slopes S., desc. W. slope.
39.98	<p>Point for the ¼ sec. cor. of secs. 11 and 14.</p> <p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T4N R7E            ¼ <u>S 11</u>            S 14</p> <p style="text-align: center;">1966</p>
48.00	Along the top of a ridge which bears E. and W.
54.00	Descend NW. slope of the ridge.
71.10	Enter wash area, drains S. 30° W.
74.80	Leave wash area, asc. SE. slope.
79.96	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling.            Soil, gravelly loam.            Timber, moderate palo verde.            Undergrowth, moderate cacti.</p>

24

CHAINS	
	<p>West, bet. secs. 10 and 15.</p> <p>Over rolling land, through moderate palo verde.</p> <p>.90 Spur, slopes SW.</p> <p>12.90 Wash, 40 lks. wide, 1 ft. deep, drains SW.</p> <p>38.42 Intersect the E. bdy. of Fort McDowell Indian Reservation.</p> <p>Point for the closing cor. of secs. 10 and 15.</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p><i>FMCDIR</i> / T4N R7E              S 10              S 15 CC              1966</p> </div> <p>from which</p> <p>The R. A. Farmer closing cor. of secs. 10 and 15, bears S. 6°40' W., 37 lks. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1911 survey.</p> <p>The 5½ MP, bears S. 6°40' W., 3.61 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1911 survey.</p> <p>Land, rolling.              Soil, gravelly loam.              Timber, moderate palo verde.              Undergrowth, moderate cacti.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land, through moderate palo verde.</p> <p>0.70 Spur, slopes SW., desc. NW. slope.</p> <p>6.80 Wash, 90 lks. wide, 1 ft. deep, drains SW., asc. SE. slope.</p> <p>18.15 Spur, slopes SW., desc. NW. slope.</p> <p>26.35 Wash, 20 lks. wide, 1 ft. deep, drains SW., asc. SE. slope.</p> <p>36.20 Spur, sloping SW.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 10 and 11.</p> <p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R7E              ¼              S10   S11              1966</p> </div>

CHAINS

49.70 Wash, 40 lks. wide, 1 ft. deep, drains W., asc. S. slope.

56.80 Spur, slopes W., desc. N. slope.

59.20 Track road, bears SE. and NW.

69.70 Small canyon, drains W., asc. S. slope.

73.00 Spur, slopes W.; desc. N. slope.

76.60 Malpais Canyon, drains S. 60° W., asc. N. slope.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E  
S 3 | S 2  
S10 | S11

1966

from which

A concrete watering trough, fed from adjacent Aqua Chiquita Spring, bears S. 37°13' W., 9.38 chs. dist.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

From the cor. of secs. 1, 2, 11 and 12.

S. 89°56' W., bet. secs. 2 and 11.

Over rolling land, through moderate palo verde, asc. NE. slope.

10.00 Spur, slopes S., thence over rolling W. slope.

37.40 Draw, drains N., asc. E. slope.

40.00 Point for the ¼ sec. cor. of secs. 2 and 11.

Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R7E  
¼ S 2  
S 11

1966

Desc. over rolling land on N. slope.

70.00 Malpais Canyon, drains S.

80.00 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

CHAINS																				
	<p>S. 89°40' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through moderate palo verde.</p>																			
10.80	<p>Spur, slopes S. 60° W.; desc. NW. slope.</p>																			
13.65	<p>Jeep road, bears NE. and SW.</p>																			
27.58	<p>The closing cor. of secs. 3 and 10, on the E. bdy. of the Fort McDowell Indian Reservation, monumented by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1911 survey. I re-mark the brass cap to read:</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>S</td> <td>3</td> </tr> <tr> <td>C</td> <td>T4N</td> <td></td> </tr> <tr> <td>C</td> <td>R7E</td> <td></td> </tr> <tr> <td>FMCDIR</td> <td>S</td> <td>10</td> </tr> <tr> <td></td> <td>1966</td> <td></td> </tr> <tr> <td></td> <td>1911</td> <td></td> </tr> </table> </div> <p>Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.</p>		S	3	C	T4N		C	R7E		FMCDIR	S	10		1966			1911		
	S	3																		
C	T4N																			
C	R7E																			
FMCDIR	S	10																		
	1966																			
	1911																			
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land, through moderate palo verde.</p> <p>Asc. S. slope.</p>																			
3.00	<p>Spur, slopes SW., thence over rolling SW. slope.</p>																			
34.30	<p>Wash, 30 lks. wide, 1 ft. deep, drains W.</p>																			
37.50	<p>Low spur, slopes S. 70° W.</p>																			
38.90	<p>Draw, drains SW., asc. SE. slope.</p>																			
40.00	<p>Point for the ¼ sec. cor. of secs. 2 and 3.</p> <p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T4N</td> <td>R7E</td> </tr> <tr> <td colspan="2" style="text-align: center;">¼</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">1966</td> </tr> </table> </div>	T4N	R7E	¼		S 3	S 2	1966												
T4N	R7E																			
¼																				
S 3	S 2																			
1966																				
70.00	<p>Wash, 15 lks. wide, 1½ ft. deep, drains W.</p>																			
78.67	<p>Intersect the First Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2" style="text-align: center;">S 34</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td>T4N</td> <td>R7E</td> </tr> <tr> <td colspan="2" style="text-align: center;">C C</td> </tr> <tr> <td colspan="2" style="text-align: center;">1966</td> </tr> </table> </div>	S 34		S 3	S 2	T4N	R7E	C C		1966										
S 34																				
S 3	S 2																			
T4N	R7E																			
C C																				
1966																				

CHAINS

From point of intersection, the standard cor. of secs. 34 and 35, bears East, 4.05 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the concurrent survey of T. 5 N., R. 7 E.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

The point for the ¼ sec. cor. of sec. 2 is on the N. bdy. at mid-point bet. the closing cors.

Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.

¼ S 2  
T4N R7E

1966

From this cor., the standard ¼ sec. cor. of sec. 35 bears East, 4.02 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the concurrent survey of T. 5 N., R. 7 E.

From the closing cor. of secs. 3 and 4, on the N. bdy. of Fort McDowell Indian Reservation, monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1911 survey. I re-mark the brass cap to read:

T4N R7E  
S 4 | S 3  
FMCDIR  
CC  
1966  
1911

N. 0°02' W., bet. secs. 3 and 4.

Over rolling land, through moderate palo verde.

.13 Fence, 4-strand barbed wire, bears N. 80°30' E. and S. 80°30' W., desc. N. slope.

7.30 Wash, 10 lks. wide, 1 ft. deep, drains W., asc. S. slope.

14.30 Spur, slopes W., desc. N. slope.

18.15 Point for the ¼ sec. cor. of secs. 3 and 4.

Set the iron post over an "x" chiseled on solid rock, mound with stone to top, brass cap mkd.

T4N R7E  
¼  
S 4 | S 3

1966

23.40 Canyon, drains W.

CHAINS

26.60

Bottom of canyon, drains W.

53.90

Draw, drains SW.

57.16

Intersect the First Standard Parallel North.

Point for the closing cor. of secs. 3 and 4.

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

S 33  
 $\frac{S\ 4}{T4N\ R7E}$   
 C C

1966

From point of intersection, the standard cor. of secs. 33 and 34, bears East, 3.32 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the concurrent survey of T. 5 N., R. 7 E.

Land, rolling.  
 Soil, gravelly loam.  
 Timber, moderate palo verde.  
 Undergrowth, moderate cacti.

The point for the ¼ sec. cor. of secs. 3 is on the N. bdy. at 40.00 chs. in westing from the closing cor. of secs. 2 and 3.

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

$\frac{1}{4}$  S 3  
 T4N R7E

1966

From this corner, the standard ¼ sec. cor. of sec. 34, bears East, 4.05 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the concurrent survey of T. 5 N., R. 7 E.

The point for the ¼ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

$\frac{1}{4}$  S 4  
 T4N R7E

1966

From this corner, the standard ¼ sec. cor. of sec. 33, bears East 3.30 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the concurrent survey of T. 5 N., R. 7 E.

CHAINS

## General Description

The elevation of that portion of Township 4 North, Range 7 East, adjacent to Fort McDowell Indian Reservation, ranges from about 3,000 ft. in sec. 1 to about 1,500 ft. in the northwest corner of sec. 34. The land is rolling to mountainous, with the drainage generally to the southwest.

The Forest Service road in the southern portion is good but the roads in the northern portion are rough. The area is used primarily for grazing. Aqua Chiquita Springs in sec. 10, sporadic water along Sycamore Creek, and a windmill and large water tank near the east boundary of HES 413 are the main sources of water for cattle and wild life.

Palo verde trees, assorted cacti, creosote brush, cat claw and scattered grass are found throughout the area. Mesquite trees and considerable grass are found along the Sycamore Creek bottom land.

No mining activity or dwellings were noted.

CHAINS		



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

31

FIELD ASSISTANTS

NAMES	CAPACITY
Howard H. Thomas	Supervisory Surveying Technician
Ray E. Thiessen	Surveying Aid
Martin W. Fuller	Surveying Aid
Loyal E. Steele	Surveying Aid
George P. Oviatt	Surveying Aid

32

CERTIFICATE OF SURVEY

I, Paul G. Bauer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of September, 1965, I have made a survey of the east boundary and a completion survey of the subdivisional lines of Township 4 North, Range 7 East.

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

7/25/67  
\_\_\_\_\_  
(Date)

Paul G. Bauer  
\_\_\_\_\_  
(Cadastral Surveyor)

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date JUL 26 1967

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the survey of the east boundary and a completion survey of the subdivisional lines of Township 4 North, Range 7 East, Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 21 1967  
\_\_\_\_\_  
(Date)

Acting *R. E. Brown*  
\_\_\_\_\_  
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief, Division of Engineering)