F_{orm} 4-679 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY	•
of the	
East Boundary	
and a	
Portion of the Subdivisional Line	es .
of	
Township 4 North, Range 8 East	
·	
Of theGila and Salt River	W:J:
A!	Meridian,
In the State ofArizona	•
EXECUTED BY	
Paul G. Bauer, Cadastral Surveyor	
Gary T. Oviatt, Surveying Technician	
Gary 1. Ovract, Surveying Technician	
Under special instructions dated September 15 , 19 65	, which provided for the surveys
included under Group Number 435, approved September	per 17, 1965
and assignment instructions dated <u>March 4 and 18</u> , 19 <u>66</u> .	
, 17	
Survey commenced March 29	1966
Survey completedMay 10,	

BOOK 4800 INDEX DIAGRAM

Т	ownsh	ip 4 No	rth			, Range8	B East	······································	ı
6	24	8	15	4	9	8	2	1	5
24		23		14					
7	23	8	14	9	8	10	11	12	4
22		. 22		13					
18	21	17	13	16	7	15	14	13	3
21		20		12					
19	20	20	11	21	7	22	28	24	3
19		18		11					
30	18	29	11	28	6	27	26	25	2
17		17		10					
31	16	32	9	88	5	84	35	36	1

Township 4 North, Range 8 East Gila and Salt River Meridian, Arizona

CHAINS

The north boundary, the First Standard Parallel North, was surveyed concurrently under group 435 by Bauer and Oviatt. The record thereof is included in the field notes of Township 5 North, Range 8 East.

The west boundary was surveyed concurrently under this same group by Bauer and Oviatt. The record thereof is included in the field notes of Township 4 North, Range 7 East.

The south boundary of this township was surveyed concurrently under group 434 by Ott and Oviatt. The record thereof is included in the field notes of Township 3 North, Range 8 East.

These notes are those of a survey of the east boundary and a portion of the subdivisional lines of Township 4 North, Range 8 East.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches in diameter, flanged at the base, and with a brass cap riveted to the top.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated September 15, 1965.

The geographic position of the southeast corner of the township is: Latitude 33°38'25.3" North, and Longitude 111°28'34" West, as determined by computations from Coast and Geodetic Survey Triangulation Station "Rolls," which is located in sec. 25 of the township.

The mean magnetic declination was found to be 14° East.

Survey of the East Boundary Township 4 North, Range 8 East

Beginning at the Tp. cor. of Ts. 3 and 4 N., Rs. 8 and 9 E., monumented by an iron post as described in the concurrent survey of group 434, T. 3 N., R. 8 E.

North, bet. secs. 31 and 36 on the E. bdy. of the Tp. Over rolling land, through moderate palo verde.

Wash, 10 lks. wide, $1\frac{1}{2}$ ft. deep, drains S. 30° E.

Wash, 10 1ks. wide, 1 ft. deep, drains SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.

Set the iron post 22 ins. in the ground, brass cap mkd.

T4N R8E, R9E \$36 | S31

1966

Raise a mound of stone W. of the cor.

11.50

16.00

	Survey of E. Buy., 1. 4 N., R. 8 E., Arizona
chains 46.00	Wash, 10 1ks. wide, 1 ft. deep, drains S. 80° W.
60.32	Fence, bears N. 19°25' E. and S. 19°25' W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36.
	Set the iron post 24 ins. in the ground, brass cap
	T4N
	R8E R9E S25 S30
	S36 S31
	1966
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, gravelly loam.
	Timber, moderate palo verde.
	Undergrowth, moderate cacti, creosote and brush.
	North, bet. secs. 25 and 30, on the E. bdy. of the Tp.
	Over rolling land, through moderate palo verde.
.97	Fence, bears E. and W.
22.90	Trail road, bears N. 18°15' E. and S. 18°15' W.
37.30	Fence, bears S. 80° E. and N. 80° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.
	Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
	T4N R8E R9E
	1/4
	S25 S30 1966
40.45	Trail road, bears S. 65° E. and N. 65° W.
40.95	Fence, bears S. 63'40' E. and N. 61°15' W.
64.60	Bladed road, bears E. and W.
80.00	·
80.00	Point for the cor. of secs. 19, 24, 25 and 30.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T4N
	R8E R9E S24 S19
	S25 S30
	from which
	"Rolls" Triangulation Station, bears S. 8°28' W.,
	15.62 chs. dist., monumented with a brass tablet, 3 ins. diam., set in cement.
	Raise a mound of stone W. of the cor.

CHAINS	Land, rolling. Soil, rocky and shallow gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
· •	North, bet. secs. 19 and 24 on E. bdy. of the Tp. Over heavy rolling land, through moderate palo verde.
20.00	Wash, 20 1ks. wide, 1 ft. deep, drains W.
40.00	Point for the ½ sec. cor. of secs. 19 and 24.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E R9E
	S24 S19
	1966
49.90	High ridge, bears E. and W.
71.90	Wash, 20 lks. wide, 1 ft. deep, drains W.
80.00	Point for the cor. of secs. 13, 18, 19 and 24.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T4N R8E R9E <u>S13 S18</u> S24 S19
	1966
	from which
	A spring, bears S. 7°02' E., 8.16 chs. dist.; the spring drains W., has very little seepage.
	Raise a mound of stone W. of the cor.
, .	Land, heavy rolling. Soil, rocky and shallow gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
	North, bet. secs. 13 and 18 on the E. bdy. of the Tp.
	Over heavy rolling land, through moderate palo verde.
13.00	High ridge, bears S. 75° E. and N. 75° W.
34.90	Old Beeline Highway (bladed road), bears S. 35° E. and N. 35° W.
36.50	Wash, 20 1ks. wide, 2 ft. deep, drains NW.
40.00	Point for the ½ sec. cor. of secs. 13 and 18.
	Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.

Survey	of.	Ε.	Bdv.	Т.	4 N	R.	Q	F	Ari zon o
241 409	OΈ.		Duy.g.	τ.	4- I/	Λ.	0	L.	Arizona

-		Darvoy of D. Buy. 1. 4 N., R. o E., Arizona
	CHAINS	
		T4N R8E R9E
		S13 S18 ,
+	the street, it is not deposite.	- 1966-
	72.80	Wash, 20 1ks. wide, 1 ft. deep, drains S. 75° W., water 1 ft. wide, 2 ft. deep, course S. 75° W.
	80.00	Point for the cor. of secs. 7, 12, 13 and 18.
		Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd. T4N R8E R9E S12 S 7 S13 S18
l		1966
		Land, rolling. Soil, rocky and gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
		North, bet. secs. 7 and 12 on the E. bdy. of the Tp.
,	5	Over heavy rolling land, through moderate palo verde.
	23.70	Wash, 20 1ks. wide, 2 ft. deep, drains W.
	40.00	Point for the ½ sec. cor. of secs. 7 and 12.
		Set the iron post 13 ins. in the ground, mound with stone to top, brass cap mkd.
	- ,	T4N R8E R9E
		S12 S 7
		1966
	52•40	Wash, 10 1ks. wide, 1 ft. deep, drains S. 75° W., water 1 ft. wide, 2 ft. deep, course S. 75° W.
	80 . 00	Point for the cor. of secs. 1, 6, 7 and 12.
		Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
	•	T4N R8E R9E S 1 S 6 S12 S 7
	. ^	from which
		. A prominent peak, bears N. 80° W., 9.00 chs. dist.
	·	Land, heavy rolling. Soil, rocky and shallow gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.

	, , , , , , , , , , , , , , , , , , , ,
CHAINS	North, bet. secs. 1 and 6 on the E. bdy. of the Tp.
	Over heavy rolling land, through moderate palo verde.
5.00	Spur, slopes E.
34.70	Wash, 20 1ks. wide, 2 ft. deep, water 2 ft. wide, 2 ft. deep, course S.80° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E R9E
	s 1 s 6
	1966
57.20	Ridge, bears E. and W.
78.56	Intersect the First Standard Parallel North.
	Point for the closing Tp. cor. of T. 4 N., Rs. 8 and 9 E.
	Set the iron post 18 ins. in the ground, mound with stone to top, brass cap mkd.
	S36
	S 1 S 6 R8E R9E
	C C
	T4N
	1966
	from which
	The standard Tp. cor. of T. 5 N., Rs. 8 and 9 E., bears East, 10.66 chs. dist., monumented with a $2\frac{1}{2}$ ins. iron post, set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 5 N., R. 8 E.
	Land, heavy rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
	Survey of a Portion of the Subdivisional Lines T. 4 N., R. 8 E., Arizona
	From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., monumented with a $2\frac{1}{2}$ ins. iron post, set,

of the Tp., monumented with a $2\frac{1}{2}$ ins. iron post, set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 3 N., R. 8 E.

N. 0°02' W., bet. secs. 33 and 34.

Over rolling land, through moderate palo verde.

T4N R8E S21 S22 S28 S27 1966

CHAINS	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
	N. 0°02' W., bet. secs. 21 and 22.
	Over rolling land, through moderate palo verde.
11.80	Wash, 10 1ks. wide, 1 ft. deep, drains NW.
40.00	Point for the ½ sec. cor. of secs. 21 and 22.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E
	S21 S22
	1966
47.70	Top of ridge, bears N. 50° E. and S. 65° W.
75.70	Bladed road, bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set the iron post over an "x" chiseled on solid rock, mound with stone to top, brass cap mkd.
	T4N R8E S16 S15 S21 S22
	1966
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
	N. 0°02' W., bet. secs. 15 and 16.
	Over rolling land, through moderate palo verde.
	Begin triangulation. (Topography as taken from ADAMS MESA QUAD.)
12.00	Begin asc. SW. slope of Sugarloaf Mountain.
35.45	Spur, sloping W., end of triangulation.
40.00	Point for the ½ sec. cor. of secs. 15 and 16.
	Set the iron post 18 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E
	S16 S15
	1966
45.40	Deep draw, drains S. 60° W.
66.50	High spur, slopes E., desc. NE. slope of Sugarloaf Mountain.

	Subdivision, 1. 4 N., N. O L., Alizona
CHAINS	
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E S 9 S10
	S16 S15
	1966
	from which
	The top of Sugarloaf Mountain bears S. 54° W., 12.00 chs. dist., elevation of Sugarloaf Mountain is 2,884.
	Land, rolling and mountainous. Soil, rocky (lava) and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
	N. 0°02' W., bet. secs. 9 and 10.
	By triangulation. (Topography as taken from U.S.G.S. topographic sheet, ADAMS MESA, ARIZ.)
20.00	Large draw at the base of Sugarloaf Mountain, drains N. 60° W., thence over rolling land.
32.90	Low ridge, bears E. and W. End of triangulation.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set the iron post over an "x" chiseled on solid rock, mound with stone to top, brass cap mkd.
	T4N R8E
	s 9 s10
	1966
45.40	Rocky ridge, bears E. and W.
54.80	Left bank of Sycamore Creek, bears SE. and NW.
56.00	Right bank of Sycamore Creek, bears S. 60° E. and N. 60° W.
65.30	Top of rocky spur, slopes S. 30° E.
70.00	Right bank of Sycamore Creek, bears S. 10° E. and N. 10° W.
79.00	Left bank of Sycamore Creek, bears S. 10° E. and N. 10° W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E
	<u>S 4 S 3</u> S 9 S10
	1966

Ī	CHAINS	
l	·	Land, rolling and broken.
١		Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde and sycamore trees on
l		the banks of the creek.
		Undergrowth, moderate cacti, cat claw and brush.
		N. 0°02' W., bet. secs. 3 and 4.
		By triangulation. (Topography as taken from U.S.G.S. topographic sheet, ADAMS MESA, ARIZ.)
-		Along the left bank of Sycamore Creek.
	28.50	Leave left bank, thence across Sycamore Creek bottom.
		Course S. 75° W., curving to the S.
	30.00	Right bank of Sycamore Creek, bears N. 75° E. and S. 75° W., curves to the S., thence asc. S. slope of mountain.
	36.20	Spur, slopes S. 25° W., end of triangulation.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T4N R8E
		s 4 s 3
		1966
		Raise a mound of stone W. of the cor.
	62.20	High ridge, bears E. and W., desc. NE. slope over a series of small spurs and draws.
	78.41	Intersect the First Standard Parallel North.
		Point for the closing cor. of secs. 3 and 4.
		Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	٠	s33
		S 4 S 3
		clc
		T4N R8E
		1966
		from which
		The standard cor. of secs. 33 and 34, bears East, 10.72 chs. dist., monumented by a $2\frac{1}{2}$ ins. iron post, set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 5 N., R. 8 E.
		Land, broken. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde and sycamore trees on the banks of the creek. Undergrowth, moderate cacti, cat claw and brush.
		1

-	Subdivision, T. 4 N., R. 8 E., Arizona
CHAINS	From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., monumented by a $2\frac{1}{2}$ ins. iron post, set, mkd. and witnessed as described in the concurrent survey of Group 434, T. 3 N., R. 8 E.
	N. 0°02' W., bet. secs. 32 and 33.
	Over rolling land, through moderate palo verde.
4.90	Bladed road, bears E. and N. 81° W.
19.50	Wash, 20 lks. wide, 1 ft. deep, drains S. 80° W.
24.90	Wash, 20 lks. wide, 1 ft. deep, drains S. 65° W.
40.00	Point for the ½ sec. cor. of secs. 32 and 33.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	T4N R8E
	S32 S33
	1966
67.20	Ridge, bears N. 80° E. and S. 80° W.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T4N R8E <u>\$29</u> \$28 \$32 \$33
	1966
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
	From the cor. of secs. 27, 28, 33 and 34.
	West, bet. secs. 28 and 33.
	Over rolling land, through moderate palo verde.
12.60	Wash, 20 lks. wide, 1 ft. deep, drains S. 15° W.
40.01	Point for the ½ sec. cor. of secs. 28 and 33.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E 1 S28
	1966
80.02	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
1	1

CHAINS	N. 0°02 W., bet. secs. 28 and 29.
	Over rolling land, through moderate palo verde.
40.00	Point for the ½ sec. cor. of secs. 28 and 29.
	Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
	T4N R8E 表
	S29 S28
	1966
65.20	Wash, 20 1ks. wide, 1 ft. deep, drains N. 60° W.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
ŕ	Set the iron post 18 ins. in the ground, brass cap mkd.
	T4N R8E S20 S21 S29 S28
	1966
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, brush and scattered cat claw.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°59' W., bet. secs. 21 and 28.
٠.	Over rolling land, through moderate palo verde.
39.97	Point for the k sec. cor. of secs. 21 and 28.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E 1 S21
	\$\frac{7}{528}
	1966
70.00	Wash, 10 lks. wide, 1 ft. deep, drains NW.
79.94	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate cacti. Undergrowth, moderate cacti, cat claw and brush.
	N. 0°02' W., bet. secs. 20 and 21. Over rolling land, through moderate palo verde.
4.20	Trail road, bears N. 65° E. and S. 65° W.
4.40	Trail load, board in a land land land

12.

. Subdivision,	\mathbf{T}_{ullet}	4	N.,	R_{\bullet}^{\prime}	8	Ε.,	Arizona
----------------	----------------------	---	-----	------------------------	---	-----	---------

CHAINS	
25.00	Wash, 10 lks. wide, 2 ft. deep, drains S. 75° W.
34.80	Trail road, bears E. and W.
40.00	Point for the ½ sec. cor. of secs. 20 and 21.
(Set the iron post 18 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E
	\$20\\$21
	1966
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	T4N R8E S17 S16 S20 S21
	1966
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89°59' W., bet. secs. 16 and 21.
	Over rolling land, through moderate palo verde.
17.35	Bladed road, bears N. and S
36.40 ·	Trail road, bears N. and S., wash, 50 lks. wide, 1 ft. deep, drains N.
40.02	Point for the ½ sec. cor. of secs. 16 and 21.
	Set the iron post 18 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E 2 S16 S21
	1966
44.60	Spur, slopes N.
56.70	Top of ridge, bears N. and S.
80.04	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling and broken. Soil, rocky and shallow, gravelly loam. Timber, moderate pale verde Undergrowth, moderate cacti, creosote, cat claw and brush.

CHAINS	16 1.17
	N. 0°02' W., bet. secs. 16 and 17.
	Over rolling and broken land, through moderate palo verde.
31.90	Top of high ridge, bears E. and S. 70° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.
	Set the iron post over an "x" chiseled on solid rock, mound with stone to top, brass cap mkd.
·	T4N R8E
	S17 S16
	1966
53.00	Sycamore Creek, 70 lks. wide, 2 ft. deep, course S. 80° W.
64.50	Low ridge, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T4N R8E
	<u>S 8 S 9</u> S17 S16
·	1966
	from which
	A windmill at Sheep Camp, bears S. 53°40' E., 38.37 chs. dist.
	A gaging station at Sheep Camp, bears S. 47°38' E., 30.54 chs. dist.
	Land, rolling and broken. Soil, rocky and shallow, gravelly loam.
	Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and brush.
	ondergrowth, moderate cater, the train and brosh
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°58' W., bet. secs. 9 and 16.
·	Over N. slope of Sugarloaf Mountain.
22.40	Long spur, slopes N., desc. SW. slope.
40.02	Point for the $\frac{1}{2}$ sec. cor. of secs. 9 and 16.
	Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E
	¹ / ₄ S 9/ ₅₁₆
	1966
41.90	Base of Sugarloaf Mountain, bears S. 20° E. and N. 20° W.

Subdivision, T. 4 N., R. 8 E., A	Arizona
----------------------------------	---------

14.

_		Dasarvision, 1. 4 N., N. O B., Milsona
	CHAINS	Left bank of Sycamore Creek, 3 ft. high, bears S. 20° E. and N. 20° W.
	42.40	Center of Sycamore Creek, course S. 20° E.
	45.10	Right bank of Sycamore Creek, bears N. and S., thence over rolling land, through moderate palo verde.
	80.04	The cor. of secs. 8, 9, 16 and 17.
		Land, broken and rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
		N. 0°02' W., bet. secs. 8 and 9.
		Over rolling land, through moderate palo verde.
	39.20	Wash, 20 lks. wide, 1 ft. deep, drains SE.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
		Set the iron post 24 ins. in the ground, in a collar of stone, brass cap mkd.
		T4N ₁ R8E
		s 8 (s 9
		1966
	62.50	Spur, slopes E.
	78.20	Long spur, slopes E.
	80.00	Point for the cor. of secs. 4, 5, 8 and 9.
ļ		Set the iron post 20 ins. in the ground, brass cap mkd.
		T4N R8E S 5 S 4 S 8 S 9
		1966
		Raise a mound of stone W. of the cor.
		Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
		From the cor. of secs. 3, 4, 9 and 10.
		West, bet. secs. 4 and 9.
		Over broken land, through moderate palo verde.
	. 50	Center of Sycamore Creek, course S.
	3.70	Top of rocky ledge, bears N. and S.
	5.70	Top of Tooky Teage, bears N. and b.

	Subdivision, T. 4 N., R. 8 E., Arizona
CHAINS	
28.10	Top of ridge, bears S. 20° E. and N. 20° W.
39.97	Point for the ½ sec. cor. of secs. 4 and 9.
	Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E
	$\frac{1}{4} \frac{S}{S} \frac{4}{9}$
	1966
47.00	Wash, 150 lks. wide, 1 ft. deep, drains S. 30° E.
56.00	Spur, sloping N. 10° E.
79.94	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling and broken. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw
	and brush.
	N. 0°02' W., bet. secs. 4 and 5.
	Over rolling land, through moderate palo verde.
13.20	Wash, 20 1ks. wide, 1 ft. deep, drains N. 80° E.
28.50	Wash, 70 1ks. wide, ½ ft. deep, drains S. 80° E.
36.80	Wash, 100 lks. wide, ½ ft. deep, drains S. 40° E.
40.00	Point for the ½ sec. cor. of secs. 4 and 5.
	Set the iron post over an "x" chiseled on solid rock, mound with stone to top, brass cap mkd.
	T4N R8E
	s 5 s 4
	1966
78.36	Intersect the First Standard Parallel North.
	Point for the closing cor. of secs. 4 and 5.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	S32 S 5 S 4
	S 5 S 4
	T4N R8E
	1966
	from which
	The standard cor. of secs. 32 and 33 bears East, 10.70 chs. dist., monumented by an
	iron post, 2½ ins. diam., set, mkd., and
	witnessed as described in the field notes of the concurrent survey of T. 5 N., R. 8 E.

of the concurrent survey of T. 5 N., R. 8 E.

CH	Ą	п	18

Land, rolling.
Soil, rocky and shallow, gravelly loam.
Timber, moderate palo verde.
Undergrowth, moderate cacti, creosote, cat claw and brush.

The point for the $\frac{1}{4}$ sec. cor. of sec. 4 is on the N. bdy. at mid-point between the closing cors.

Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd .

½ S 4 T4N R8E 1966

from which

The standard $\frac{1}{4}$ sec. cor. of sec. 33 bears East, 10.71 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 5 N., R. 8 E.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. in diam., set, mkd. and witnessed as described in the concurrent survey of Group 434, T. 3 N., R. 8 E.

N. 0°03' W., bet. secs. 31 and 32.

Over rolling land, through moderate palo verde.

6.80 | Wash, 10 1ks. wide, 1 ft. deep, drains N. 25° W.

18.50 Top of ridge, bears S. 20° E. and N. 15° W.

27.40 Wash, 20 lks. wide, $1\frac{1}{2}$ ft. deep, drains NE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set the iron post 24 ins. in the ground, brass cap mkd.

T4N R8E

Raise a mound of stone W. of the cor.

48.70 Top of low ridge, bears SE, and NW.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set the iron post 24 ins. in the ground, brass cap mkd.

T4N R8E S30 S29 S31 S32

1966

Raise a mound of stone W. of the cor.

CHAINS	
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
	From the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 29 and 32.
	Over rolling land, through moderate palo verde.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T4N R8E
	$\frac{1}{4} \frac{S29}{S32}$
	$\frac{4}{532}$
	1966
	Raise a mound of stone N. of the cor.
64.00	Bladed road, bears N. 10° E. and S. 10° W.
67.00	Wash, 30 1ks. wide, 1 ft. deep, drains N.
80.12	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling. Soil, rocky and gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, brush and scattered cat claw.
	N. 89°59' W., bet. secs. 30 and 31.
	Over rolling land, through moderate palo verde.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T4N R8E
	$\frac{1}{4} \frac{S30}{-24}$
	\$31
	1966
	Raise a mound of stone N. of the cor.
52.00	Wash, 10 1ks. wide, ½ ft. deep, drains N. 30° W.
78.75	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 4 N., R. 7 E.
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, brush and scattered cat claw.

	CHAINS	From the cor. of secs. 29, 30, 31 and 32.
		N. 0°03' W., bet. secs. 29 and 30.
		Over rolling land, through moderate palo verde.
	2.80	Wash, 10 1ks. wide, 1 ft. deep, drains NW.
	22.30	Wash, 10 1ks, wide, 1½ ft. deep, drains irreg. N.
	40.00	Point for the ½ sec. cor. of secs. 29 and 30.
		Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
		T4N R8E
		S30 S29
		1966
	48.40	Wash, 30 1ks. wide, 1 ft. deep, drains NW.
	51.60	Bladed road, bears S. 33°15' E. and N. 27°30' W.
	58.10	Bladed road, bears N. 10° E. and S. 10° W.
	63.90	Left bank of Sycamore Creek (dry), drains S. 80° W., thence over flooded area.
	65.40	Road in Sycamore Creek, bears S. 15° E. and N. 15° W.
	80.00	True point for the cor. of secs. 19, 20, 29 and 30 falls in flooded area of Sycamore Creek, in unsafe position. Land, rolling.
		Soil, rocky and sandy and gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
		From the cor. of secs. 20, 21, 28 and 29.
		N. 89°59' W., bet. secs. 20 and 29.
		Over rolling land, through moderate palo verde.
	4.40	Trail road, bears N. 70° E. and S. 80° W.
	7.00	Trail road, bears S. 50° E. and N. 50° W.
	12.90	Trail road, bears N. 80° E. and S. 80° W.
	40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T4N R8E ¹ / ₂ S20 S29
		1966
		Raise a mound of stone N. of the cor.
- 1		l l

CHAINS	
55.20	Left bank of Sycamore Creek, bears N. 20° E. and S. 20° W., thence across flooded area of Sycamore Creek, drainage S. 20° W.
80.06	The true point for cor. of secs. 19, 20, 29 and 30, the witness cor., bears N. 0°03' W., 3.00 chs. dist.
	Land, rolling and nearly level. Soil, rocky and sandy, and gravelly loam. Timber, moderate palo verde. Undergrowth, moderate creosote and cat claw.
	From the true point for cor. of secs. 19, 20, 29 and 30.
	N. 89°59' W., bet. secs. 19 and 30.
	Over nearly level land, through moderate palo verde and mesquite.
4.80	Fence, bears N. 60° E. and S. 60° W.
9.40	Right bank of Sycamore Creek, bears N. 55° E. and S. 55° W.
33.10	Wash, 20 1ks. wide, 1 ft. deep, drains SW.
38.40	Fence, bears N. and S.
40.00	Point for the ½ sec. cor. of secs. 19 and 30.
-	Set the iron post 24 ins. in the ground, brass cap mkd.
	T4N R8E
	$\frac{1}{4} \frac{\text{S19}}{\text{S30}}$
	1966
	Raise a mound of stone N. of the cor.
78.68	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 4 N., R. 7 E.
	Land, nearly level. Soil, sandy, clay loam, and rocky. Timber, moderate palo verde and mesquite. Undergrowth, moderate cacti, cat claw and brush.
	From the true point for the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over rolling and broken land, through moderate palo verde.
2.90	Right bank of Sycamore Creek, bears E. and W.

	Subdivision, T. 4 N., R. 8 E., Arizona
CHAINS	
3.00	Point selected for the witness cor. of secs. 19, 20, 29 and 30.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	w c
	T4N R8E S19 S20
	S30 S29
	1966
	from which
	A windmill, bears S. 77°28' W., 9.66 chs. dist.
	The SE. cor. of loading corral, bears N. 31°18' W., 1.46 chs. dist.
	Raise a mound of stone W. of the cor.
38.40	Rocky ridge, bears S. 30° E. and N. 30° W.
40.00	Point for the ½ sec. cor. of secs. 19 and 20.
	Set the iron post over an "x" chiseled on solid rock, mound with stone to top, brass cap mkd.
	T4N R8E
	」 S19 S20
	1966
61.10	Top of ridge, bears S. 60° E. and N. 60° W.
74.10	Wash, 10 1ks. wide, 1 ft. deep, drains E.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E
	S18 S17
	S19 S20
	1966
	Land, rolling and broken.
	Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde.
•	Undergrowth, moderate cacti, creosote, cat claw
	and brush.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89°58' W., bet. secs. 17 and 20.
	Over broken land, through moderate palo verde.
22.30	Top of rocky ridge, bears N. 30° E. and S. 20° W.
32.90	Left bank of Sycamore Creek, bears NE. and SW.
35.40	Center of Sycamore Creek, course SW.

CHAINS	
38.00	Right bank of Sycamore Creek, bears NE. and SW.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.
	Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.
	T4N R8E 1/4 S17 S20
	1966
73.00	Wash, 30 1ks. wide, 1 ft. deep, drains S.
80.16	The cor. of secs. 17, 18, 19 and 20.
	Land, broken. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.
	N. 89°59' W., bet. secs. 18 and 19.
	Over rolling land, through moderate palo verde.
28.40	Wash, 20 1ks. wide, 1 ft. deep, drains SE.
40.00	Point for the ½ sec. cor. of secs. 18 and 19.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T4N R8E ½ S 18 S 19
	1966
55.90	Wash, 30 1ks. wide, 1 ft. deep, drains S. 20° E.
78.66	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 4 N., R. 7 E.
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over rolling land, through moderate palo verde.
3.70	Wash, 15 lks. wide, 1 ft. deep, drains E.
10.20	Wash, 20 lks. wide, $1\frac{1}{2}$ ft. deep, drains S. 35° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

	T					
	CHAINS	Set the iron post 18 ins. in the ground, mound with stone to top, brass cap mkd.				
		T4N R8E				
		S18 S17				
		1966				
	55.40	Ridge, bears E. and W.				
	63.10	Wash, 10 lks. wide, 1 ft. deep, drains E.				
	67.70	Wash, 10 lks. wide, 1½ ft. deep, drains E.				
	77.40	Wash, 20 lks. wide, 1 ft. deep, drains S. 60° E.				
	80.00	Point for the cor. of secs. 7, 8, 17 and 18.				
		Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.				
		T4N R8E <u>S 7 S 8</u> S18 S17				
		1966				
		Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.				
		From the cor. of secs. 8, 9, 16 and 17.				
		N. 89°59' W., bet. secs. 8 and 17.				
		Over rolling land, through moderate palo verde.				
	22.20	Top of ridge, bears NE. and S.				
	40.11	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.				
		Set the iron post 5 ins. in the ground, mound with stone to top, brass cap mkd.				
		T4N R8E 14 S 8 517				
		1966				
	41.80	Wash, 40 lks. wide, 1 ft. deep, drains S.				
	48.90	Wash, 80 lks. wide, 1 ft. deep, drains S. 10° E.				
	80.22	The cor. of secs. 7, 8, 17 and 18.				
		Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.				
1						

CHAINS	West, bet. secs. 7 and 18.				
	Over rolling land, through moderate palo verde.				
10.00	Point for the 4 sec. cor. of secs. 7 and 18.				
40.00					
	Set the iron post 18 ins. in the ground, mound with stone to top, brass cap mkd.				
	T4N R8E				
	$\frac{1}{4} \frac{S}{S18}$				
	1966				
40.20	Top of ridge, bears N. 30° E. and SE.				
78.63	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 4 N., R. 7 E.				
	Land, rolling. Soil, rocky and shallow, gravelly loam.				
	Timber, moderate palo verde. Undergrowth, moderate cacti, creosote,				
	cat claw and brush.				
	From the cor. of secs. 7, 8, 17 and 18.				
	N. 0°03' W., bet. secs. 7 and 8.				
	Over rolling land, through moderate palo verde.				
2.20	Spur, slopes E.				
21.30	Wash, 20 1ks. wide,1 ft. deep, drains S. 55° E.				
24.70	Old mining road leads to rose quartz deposit, bears N. 10° E. and S. 10° W.				
31.20	Wash, 20 lks. wide, 1 ft. deep, drains SE.				
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.				
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.				
	T4N R8E				
	s 7 s 8				
	1966				
	from which				
	A rose quartz deposit, bears South, 14.70 chs. dist.; deposit is approximately 150 lks. long, 100 lks. wide. Had been mined years ago.				
64.10	Wash, 20 1ks. wide, 1 ft. deep, drains S. 75° E.				
80.00	Point for the cor. of secs. 5, 6, 7 and 8.				

		Subdivision, I. 4 N., R. 8 E., Arizona	24
	CHAINS	Set the iron post 6 ins. in the ground, mound with	
		stone to top, brass cap mkd.	
		T4N R8E S 6 S 5 S 7 S 8	
		1966	
		Land, rolling. Soil, rocky and gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.	
		From the cor. of secs. 4, 5, 8 and 9.	
		S. 89°58' W., bet. secs. 5 and 8.	
		Over rolling land, through moderate palo verde.	
	31.30	Spur, slopes N.	
	40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.	
		Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.	
		T4N R8E 1 S 5 4 S 8 1966	
	53.60	Spur, slopes SW.	
	74.50	Wash, 25 1ks. wide, 1 ft. deep, drains S. 20° E.	
	80.18	The cor. of secs. 5, 6, 7 and 8.	
		Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered cat claw.	
		West, bet. secs. 6 and 7.	
		Over rolling land, through moderate palo verde.	
	33.70	Black spur, slopes S. 10° E.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.	
1		Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.	
		T4N R8E 2 S 6 S 7 1966	
	48.40	East rim of Black Mountain, bears N. and S.	
	49.85	Fence, bears NE. and SW.	

	Subdivision, T. 4 N., R. 8 E., Arizona			
CHAINS				
51.80	Track road, top of mountain, bears N. and S.			
58.40	West rim of mountain, bears N. 15° E. and S. 15° W.			
78.53	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 4 N., R. 7 E.			
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered cat claw.			
	From the cor. of secs. 5, 6, 7 and 8.			
	N. 0°03' W., bet. secs. 5 and 6.			
	Over rolling land, through moderate palo verde.			
2.60	Wash, 10 1ks. wide, 2 ft. deep, drains S. 80° E.			
29.10	Top of ridge, bears E. and W.			
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.			
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.			
	T4N R8E			
	s 6 s 5			
	1966			
67.70	Top of low ridge, bears N. 75° E. and S. 75° W.			
78.39	Intersect the First Standard Parallel North.			
	Point for the closing cor. of secs. 5 and 6.			
	Set the iron post 24 ins. in the ground, brass cap mkd.			
	S31 S 6 S 5 C C T4N R8E			
	1966			
	from which			
	The standard corner of secs. 31 and 32, bears East, 10.88 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 5 N., R. 8 E.			
	Raise a small mound of stone S. of the cor.			
	Land, rolling. Soil, rocky and shallow, gravelly loam. Timber, moderate palo verde.			
	Undergrowth, moderate cacti, brush and scattered cat claw.			

CHAINS

The point for the $\frac{1}{4}$ sec. cor. of sec. 5 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 20 ins. in the ground, brass cap mkd.

½ S 5 T4N R8E

1966

Raise a mound of stone S. of the cor.

from which

The standard $\frac{1}{4}$ sec. cor. of sec. 32, bears East, 10.79 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 5 N., R. 8 E.

The point for the $\frac{1}{4}$ sec. cor. of sec. 6 is on the N. bdy. at 40.00 chs. West from the closing cor. of secs. 5 and 6.

Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.

²4 S 6 T4N R8E

1966

from which

The standard $\frac{1}{2}$ cor. of sec. 31, bears East, 10.88 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 5 N., R. 8 E.

General Description

The land in the township changes from rolling to mountainous throughout the township. The elevation ranges from about 1,630 ft. along Sycamore Creek where it leaves sec. 30 to 3,132 ft. above sea level in sec. 6, with Sheep Mesa being the highest point. The soil is rocky and gravelly loam with the exceptions of sandy loam along Sycamore Creek. The timber is moderate palo verde, with small patches of mesquite around washed areas.

Sycamore Creek runs through the township, starting in sec. 3 and goes through sec. 30; course of the creek is generally SW. A good steady stream flows the year round down to the south half of sec. 20; from there the creek is dry.

CHAINS

The main use of the land is primarily for grazing. There is one rose quartz deposit just south of the ½ sec. cor. of secs. 7 and 8, which hasn't been mined for some time. Sheep Camp gaging station is located in sec. 16. There are two water wells or windmills. They are located in sec. 16 and in the SE. cor. of sec. 19. There are a few bladed and trail roads throughout the township, and the Beeline Highway goes through the SE. portion of sec. 33.

No other known improvements have been made and there are no settlers in the township.

	CHAINS						
ļ							
			1	•	Section 1		1
				. 1			
				•			
					•		
						•	
							ر
	:						
				·			
		 					· .

BOOK 4800

Form 4-680 (June 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ira M. Thiessen	Surveying Aid
James E. Muth	Surveying Aid
Eugene V. Templeton	Surveying Aid
Ned E. Carnahan	Surveying Aid
60 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	

NTERIOR--PORTLAND, OREGON

BOOK 4800			
CERTIFICATE OF SURV	'EY		
We, 1, Paul G. Bauer and Gary T. Oviatt	, HEREBY CERTIFY upon honor that,		
in pursuance of special instructions bearing date of the 15	thday of September , 19 65,		
we I have made a survey of the east boundary and lines of Township 4 North, Range 8 East.	d a portion of the subdivisional		
	•		
of the Gila and Salt River Meridian, in the St	ate of Arizona , which		
are represented in the foregoing field notes as having been	us our executed by me and under my direction;		
and that said survey has been made in strict conformity w			
of Instructions for the Survey of the Public Lands of th	e United States, and in specific manner		
described in the foregoing field notes.			
June 26, 1967 (Date)	(Cadastral Surveyor)		
(Date)	(62.22.22.22.23.23)		
	J. Avratt		
(Date)	(Cadastral Surveyor)		
CERTIFICATE OF APPROVAL			
SUBMITTED FOR APPROVAL Date	BUREAU OF LAND MANAGEMENT, Washington, D. C.		
The foregoing field notes of the survey of the east	boundary and a portion of the		
subdivisional lines of Township 4 North, F			
Salt River Meridian in the State of Arizor	18.		

executed by Paul G. Bauer and Gary T. Oviatt, Cadastral Surveyor and Surveying Technician having been critically examined and found correct, are hereby approved.

DEC 2 1 1967	Kaskour
(Date)	Acting (Chief, Division of Engineering)
CERTI	FICATE OF TRANSCRIPT
I CERTIFY That the foregoing transcri	ipt of the field notes of the above-described surveys in
	, is a true copy of the original field notes.

(Datė)

(Chief, Division of Engineering)