

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY  
of the  
EAST and NORTH BOUNDARIES  
and the  
SUBDIVISIONAL LINES  
Between  
Sections 35-36 and 25-36  
Township 2 North, Range 8 East

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Wallace R. Ott, Cadastral Surveyor

Gary T. Oviatt, Surveying Technician

Under special instructions dated September 10, 19 65, which provided for the surveys  
supplemental special instructions dated April 20, 1966,  
included under Group Number 434, approved September 13, 1965,  
supplemental special instructions approved April 20, 1966,  
and assignment instructions dated December 16, 19 65.

Survey commenced January 6, 19 66

Survey completed November 9, 19 66

1A

BOOK 4803

INDEX DIAGRAM

Township 2 North, Range 8 East

11	10	9	8	8	7
6	5	4	3	2	1 6
7	8	9	10	11	12 5
18	17	16	15	14	13 4
19	20	21	22	23	24 4
30	29	28	27	26	25 3 13
31	32	33	34	35 12	36 1

**BOOK 4803**

Township 2 North, Range 8 East  
Gila and Salt River Meridian, Arizona

1. B

CHAINS

D. Averill and

The south boundary was surveyed in 1924 by/R. Wilson.  
The west boundary was surveyed in 1930 by T. Vander Meer.

The following field notes are those of a survey of the east and north boundaries and the subdivisional lines between secs. 35 and 36 and 25 and 36 of Township 2 North, Range 8 East, of the Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated September 10, 1965, and the Supplemental Special Instructions dated April 20, 1966.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of Township 2 North, Range 8 East, as computed from the Triangulation Station STEWART DAM is: Latitude, 33°27'56.98" North, and Longitude, 111°28'34.04" West.

The mean magnetic declination was found to be 14° E.

Survey of the East Boundary  
Township 2 North, Range 8 East

Beginning at the Tp. cor. of Tps. 1 and 2 N., Rs. 8 and 9 E., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey. The cor. is in a fence cor. from which fences bear N. 50° E., S. and W.

North, bet. secs. 31 and 36.

Over rolling land, through moderate timber.

- 0.40 Bladed road, bears S. 30° E. and NW.
- 1.10 Dirt road, curves in a half circle to intersect above road at two points, road functioning as a turnout.
- 4.20 Wash, 30 lks. wide, 1 ft. deep, drains NW.
- 4.50 Barbed wire fence, bears S. 75° E. and N. 75° W.
- 5.30 Bladed road, bears S. 60° E. and NW.
- 8.90 Barbed wire fence, bears S. 75° E. and N. 75° W., for 95 lks., thence SW.
- 9.09 A 4"x4' wooden post, bears West, 2½ lks. dist., mkd. "Emerald SW."
- 9.90 Bladed road, bears irreg. E. and W.
- 10.80 Bladed road, bears N. 30° E. and SW.
- 16.90 Wash, 45 lks. wide, 1 ft. deep, drains S. 80° W.
- 18.17 A 4"x4' wooden post, bears West 4 lks. dist., mkd. "Ruby Dawn 5 SW."

CHAINS	
23.10	Dirt road, bears E. and W.
26.20	Wash, 20 lks. wide, 1 ft. deep, drains irreg. W.
30.20	Wash, 40 lks. wide, 1 ft. deep, drains S. 50° W.
32.50	Arizona State Highway No. 88, bears N. 39°40' E. and S. 38° W.
33.40	Power line, bears N. 39°40' E. and S. 38° W.
34.40	Bladed road, bears N. 40° E. and S. 40° W.
36.50	Wash, 10 lks. wide, 1 ft. deep, drains S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36. Set the iron post 22 ins. in the ground, brass cap mkd.
	T2N R8E R9E $\frac{1}{4}$ S36   S31 1966
	from which Cor. No. 1, Mineral Survey No. 4507, Treasure Chest No. 1 Lode, bears S. 82°02' W., 12.35 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the mineral survey notes.
43.70	Bladed road, bears S. 25° E. and N. 25° W.
46.30	Power lines, bears NE. and SW.
46.50	Dirt road, bears NE. and SW.
49.32	Intersect the line bet. cors. 1 and 4 of Treasure Chest No. 1. from which Cor. No. 4, Mineral Survey No. 4507, Treasure Chest No. 1 Lode, bears N. 47°57' E., 6.26 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the mineral survey notes.
50.20	Bladed road, bears N. 70° E. and W.
51.90	Power lines, bears N. 40° E. and S. 40° W.
53.00	Power line, bears E. and W.
61.57	Intersect the line bet. cors. 2 and 3 of the Treasure Chest No. 1. from which Cor. No. 3, Mineral Survey No. 4507, Treasure Chest No. 1 Lode, bears N. 47°57' E., 9.70 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the mineral survey notes.
64.60	Wash, 10 lks. wide, 2 ft. deep, drains S. 50° E.
73.80	Spur, slopes E.

BOOK 4803

East Boundary of T. 2 N., R. 8 E., Arizona

3.

CHAINS																													
77.60	Draw, drains SE.																												
80.00	<p>Point for the cor. of secs. 25, 30, 31 and 36.</p> <p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T2N R8E R9E S25 S30 S36 S31</p> <p style="text-align: center;">1966</p> <p>Land, rolling. Soil, sandy loam. Timber, medium palo verde. Undergrowth, cat claw, saguaro and cacti.</p>																												
	<p>North, bet. secs. 25 and 30.</p> <p>Over rolling land, through medium timber.</p> <tr> <td data-bbox="289 1112 435 1147">2.40</td> <td data-bbox="435 1112 1372 1147">Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E.</td> </tr> <tr> <td data-bbox="289 1180 435 1214">6.50</td> <td data-bbox="435 1180 1372 1214">Bladed road, bears S. 35° E. and N. 35° W.</td> </tr> <tr> <td data-bbox="289 1247 435 1282">32.10</td> <td data-bbox="435 1247 1372 1282">Spur, slopes SW.</td> </tr> <tr> <td data-bbox="289 1314 435 1349">34.20</td> <td data-bbox="435 1314 1372 1349">Draw, drains S. 80° W.</td> </tr> <tr> <td data-bbox="289 1381 435 1416">37.70</td> <td data-bbox="435 1381 1372 1416">Spur, slopes S. 80° W.</td> </tr> <tr> <td data-bbox="289 1448 435 1483">39.30</td> <td data-bbox="435 1448 1372 1483">Draw, drains S. 80° W.</td> </tr> <tr> <td data-bbox="289 1516 435 1550">40.00</td> <td data-bbox="435 1516 1372 2601"> <p>Point for the ¼ sec. cor. of secs. 25 and 30.</p> <p>Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T2N R8E R9E ¼ S25 S30</p> <p style="text-align: center;">1966</p> <p>Raise a mound of stone W. of the cor.; cor. falls on a SW. slope.</p> <tr> <td data-bbox="289 1991 435 2026">42.60</td> <td data-bbox="435 1991 1372 2026">High spur, slopes W.</td> </tr> <tr> <td data-bbox="289 2059 435 2093">53.60</td> <td data-bbox="435 2059 1372 2093">High round knoll.</td> </tr> <tr> <td data-bbox="289 2126 435 2161">66.00</td> <td data-bbox="435 2126 1372 2161">Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.</td> </tr> <tr> <td data-bbox="289 2193 435 2228">68.30</td> <td data-bbox="435 2193 1372 2228">Small spur, slopes W.</td> </tr> <tr> <td data-bbox="289 2260 435 2295">75.20</td> <td data-bbox="435 2260 1372 2295">Spur, slopes S. 80° W.</td> </tr> <tr> <td data-bbox="289 2327 435 2362">78.70</td> <td data-bbox="435 2327 1372 2362">Draw, drains irreg. W.</td> </tr> <tr> <td data-bbox="289 2395 435 2429">80.00</td> <td data-bbox="435 2395 1372 2429">Point for the cor. of secs. 19, 24, 25 and 30.</td> </tr> </td></tr>	2.40	Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E.	6.50	Bladed road, bears S. 35° E. and N. 35° W.	32.10	Spur, slopes SW.	34.20	Draw, drains S. 80° W.	37.70	Spur, slopes S. 80° W.	39.30	Draw, drains S. 80° W.	40.00	<p>Point for the ¼ sec. cor. of secs. 25 and 30.</p> <p>Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T2N R8E R9E ¼ S25 S30</p> <p style="text-align: center;">1966</p> <p>Raise a mound of stone W. of the cor.; cor. falls on a SW. slope.</p> <tr> <td data-bbox="289 1991 435 2026">42.60</td> <td data-bbox="435 1991 1372 2026">High spur, slopes W.</td> </tr> <tr> <td data-bbox="289 2059 435 2093">53.60</td> <td data-bbox="435 2059 1372 2093">High round knoll.</td> </tr> <tr> <td data-bbox="289 2126 435 2161">66.00</td> <td data-bbox="435 2126 1372 2161">Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.</td> </tr> <tr> <td data-bbox="289 2193 435 2228">68.30</td> <td data-bbox="435 2193 1372 2228">Small spur, slopes W.</td> </tr> <tr> <td data-bbox="289 2260 435 2295">75.20</td> <td data-bbox="435 2260 1372 2295">Spur, slopes S. 80° W.</td> </tr> <tr> <td data-bbox="289 2327 435 2362">78.70</td> <td data-bbox="435 2327 1372 2362">Draw, drains irreg. W.</td> </tr> <tr> <td data-bbox="289 2395 435 2429">80.00</td> <td data-bbox="435 2395 1372 2429">Point for the cor. of secs. 19, 24, 25 and 30.</td> </tr>	42.60	High spur, slopes W.	53.60	High round knoll.	66.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.	68.30	Small spur, slopes W.	75.20	Spur, slopes S. 80° W.	78.70	Draw, drains irreg. W.	80.00	Point for the cor. of secs. 19, 24, 25 and 30.
2.40	Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E.																												
6.50	Bladed road, bears S. 35° E. and N. 35° W.																												
32.10	Spur, slopes SW.																												
34.20	Draw, drains S. 80° W.																												
37.70	Spur, slopes S. 80° W.																												
39.30	Draw, drains S. 80° W.																												
40.00	<p>Point for the ¼ sec. cor. of secs. 25 and 30.</p> <p>Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T2N R8E R9E ¼ S25 S30</p> <p style="text-align: center;">1966</p> <p>Raise a mound of stone W. of the cor.; cor. falls on a SW. slope.</p> <tr> <td data-bbox="289 1991 435 2026">42.60</td> <td data-bbox="435 1991 1372 2026">High spur, slopes W.</td> </tr> <tr> <td data-bbox="289 2059 435 2093">53.60</td> <td data-bbox="435 2059 1372 2093">High round knoll.</td> </tr> <tr> <td data-bbox="289 2126 435 2161">66.00</td> <td data-bbox="435 2126 1372 2161">Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.</td> </tr> <tr> <td data-bbox="289 2193 435 2228">68.30</td> <td data-bbox="435 2193 1372 2228">Small spur, slopes W.</td> </tr> <tr> <td data-bbox="289 2260 435 2295">75.20</td> <td data-bbox="435 2260 1372 2295">Spur, slopes S. 80° W.</td> </tr> <tr> <td data-bbox="289 2327 435 2362">78.70</td> <td data-bbox="435 2327 1372 2362">Draw, drains irreg. W.</td> </tr> <tr> <td data-bbox="289 2395 435 2429">80.00</td> <td data-bbox="435 2395 1372 2429">Point for the cor. of secs. 19, 24, 25 and 30.</td> </tr>	42.60	High spur, slopes W.	53.60	High round knoll.	66.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.	68.30	Small spur, slopes W.	75.20	Spur, slopes S. 80° W.	78.70	Draw, drains irreg. W.	80.00	Point for the cor. of secs. 19, 24, 25 and 30.														
42.60	High spur, slopes W.																												
53.60	High round knoll.																												
66.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.																												
68.30	Small spur, slopes W.																												
75.20	Spur, slopes S. 80° W.																												
78.70	Draw, drains irreg. W.																												
80.00	Point for the cor. of secs. 19, 24, 25 and 30.																												

CHAINS

Set the iron post 20 ins. in the ground, brass cap mkd.

T2N  
R8E R9E  
S24 | S19  
S25 | S30

1966

Raise a mound of stone W. of the cor.

Land, rolling.

Soil, rocky and sandy loam.

Timber, palo verde.

Undergrowth, moderate cacti, cat claw and bunch grass.

North, bet. secs. 19 and 24.

Over rolling mountains, through moderate timber.

7.00 High rocky spur, slopes S. 75° E.

38.60 Wash, 10 lks. wide, 1 ft. deep, drains N. 75° W.

40.00 Point for the 1/4 sec. cor. of secs. 19 and 24.

Set the iron post 18 ins. in the ground, in a collar of stone to top, brass cap mkd.

T2N  
R8E R9E  
1/4  
S24 | S19

1966

53.10 Spur, slopes W.

67.60 High rocky ridge, bears E. and W.

68.00 Spur, slopes E.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set the iron post 6 ins. in the ground, mound with stones to top, brass cap mkd.

T2N  
R8E R9E  
S13 | S18  
S24 | S19

1966

Land, rolling and broken.

Soil, rocky limestone and sandy loam.

Timber, moderate palo verde.

Undergrowth, cat claw, grass and cacti.

North, bet. secs. 13 and 18.

Over rolling land, through moderate timber and undergrowth.

0.80 Ledgy yellow spur, slopes S. 80° E.

19.80 Track road in wash, 35 lks. wide, 2 ft. deep, drains W.

BOOK 4803

East Boundary of T. 2 N., R. 8 E., Arizona

5.

CHAINS

- 26.70 Small ridge, bears E. and N. 70° W.
- 31.10 Large draw, drains S. 80° W.
- 40.00 Point for the ¼ sec. cor. of secs. 13 and 18.  
Set the iron post 12 ins. in the ground, mound with stones to top, brass cap mkd.
- T2N  
R8E R9E  
¼  
S13|S18  
1966
- 42.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.
- 56.70 Draw, drains S. 25° W.
- 61.10 Spur, slopes W.
- 65.90 Draw, drains S. 70° W.
- 80.00 Point for the cor. of secs. 7, 12, 13 and 18.  
Set the iron post 18 ins. in the ground, in a collar of stones, brass cap mkd.
- T2N  
R8E R9E  
S12|S 7  
S13|S18  
1966
- Cor. falls on a SW. slope.
- Land, rolling.  
Soil, rocky limestone and sandy loam.  
Timber, moderate palo verde.  
Undergrowth, cat claw, creosote and cacti.
- 
- North, bet. secs. 7 and 12.  
Over rolling land, through scattered timber.
- 6.70 High spur, slopes W.
- 25.10 Wash, 30 lks. wide, 1 ft. deep, drains W.
- 40.00 Point for the ¼ sec. cor. of secs. 7 and 12.  
Set the iron post 8 ins. in the ground, mound with stones to top, brass cap mkd.
- T2N  
R8E R9E  
¼  
S12|S 7  
1966
- 50.00 Wash, 10 lks. wide, 2 ft. deep, drains W., for 50 lks., thence S.
- 71.20 High spur, slopes N. 80° W.

6

CHAINS	
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set the iron post 3 ins. in the ground, mound with stones to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T2N R8E R9E S 1   S 6 S 12   S 7</p> <p>1966</p> </div> <p>Land, rolling. Soil, rocky limestone and sandy loam. Timber, palo verde. Undergrowth, scattered creosote and cacti.</p>
	<p>North, bet. secs. 1 and 6.</p>
	<p>Over rolling land, though scattered timber.</p>
8.80	<p>Wash, 10 lks. wide, 2 ft. deep, drains W.</p>
36.30	<p>Spur, slopes S. 50° W.</p>
39.70	<p>Small draw, drains NW.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 1 and 6.</p>
	<p>Set the iron post 16 ins. in the ground, with mound of stones to top, brass cap mkd.</p>
	<div style="text-align: center;"> <p>T2N R8E R9E S 1   S 6</p> </div>
	<div style="text-align: center;"> <p>¼ S 1   S 6</p> </div>
	<p>1966</p>
	<p>Cor. falls on SW. slope.</p>
48.60	<p>High ridge, bears W. and N. 50° W.</p>
57.80	<p>Draw, drains N. 60° E.</p>
61.70	<p>Draw, drains N. 5° W.</p>
65.90	<p>Draw, drains E.</p>
67.20	<p>Spur, slopes S. 70° E.</p>
76.60	<p>Draw, drains E.</p>
81.90	<p>Top of sheer round ledge.</p>
82.41	<p>True point for Tp. cor. of Tps. 2 and 3 N., Rs. 8 and 9 E., falls on sheer ledge; it is impractical to set cor. at this point.</p>
	<p>from which</p>
	<p>Point selected for the witness corner of Ts. 2 and 3 N., Rs. 8 and 9 E., bears North, 50 lks. dist.</p>



BOOK 4803

North Boundary of T. 2 N., R. 8 E., Arizona

7.

CHAINS		
	<p>Set the iron post over an "x" chiseled on solid rock, mound with stones to top, brass cap mkd.</p> <p style="text-align: center;">                     T3N                      R8E R9E  <u>S36</u>   <u>S31</u>                      S 1 ↓ S 6                      W C                      T2N                        1966                 </p> <p>Land, broken and rolling.                      Soil, rocky limestone and sandy loam.                      Timber, scattered palo verde.                      Undergrowth, medium cat claw and cacti, scattered creosote.</p>	
	<p>Survey of the North Boundary                      Township 2 North, Range 8 East</p>	
	<p>From the true point for the cor. of Tps. 2 and 3 N., Rs. 8 and 9 E.</p>	
	<p>West, over rolling and broken land, through scattered timber.</p>	
4.30	<p>Spur, slopes N. 20° W.</p>	
11.00	<p>Draw, drains N. 5° E.</p>	
20.90	<p>Spur, slopes SE.</p>	
30.70	<p>Ridge, bears N. and S.</p>	
37.90	<p>Draw, drains N.</p>	
40.00	<p>Point for the ¼ sec. cor. of secs. 1 and 36.</p>	
	<p>Set the iron post over an "x" chiseled on solid rock, mound with stone to top, brass cap mkd.</p>	
	<p>                     T3N R8E                      ¼ S 36                      S 1                      T2N                      1966                 </p>	
50.60	<p>Ridge, bears N. and S.</p>	
79.00	<p>Point selected for the witness corner of secs. 1, 2, 35 and 36.</p>	
	<p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p>	
	<p>                     T3N R8E  <u>S 35</u>   <u>S 36</u> W                      S 2   S 1 C                      T2N                      1966                 </p>	
	<p>Witness corner falls on S. side of high cliff.</p>	
80.00	<p>True point falls on side of cliff facing S.</p>	

8

CHAINS	
	<p>Land, broken last half mile, rolling first half. Soil, rocky limestone. Timber, scattered palo verde. Undergrowth, medium cacti and bunch grass, scattered cat claw.</p>
	<p>West, bet. secs. 2 and 35.</p> <p>Over steep, mountainous land, through scattered timber.</p>
13.70	Black spur, slopes SE.
20.00	Spur, slopes S.
36.50	Wash, 60 lks. wide, 3 ft. deep, drains N. 10° W., 1.50 chs., into Saguaro Lake.
40.00	Point for the ¼ sec. cor. of secs. 2 and 35.
	<p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T3N R8E ¼ S 35 S 2 T2N 1966</p>
59.00	Rocky spur, slopes NW.
68.50	Willow Spring Canyon, which is a bay of Saguaro Lake, bears N. and S.
80.00	Point for the cor. of secs. 2, 3, 34 and 35.
	<p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T3N R8E S34   S35 S 3   S 2 T2N 1966</p> <p>Cor. falls on a steep E. slope.</p> <p>Land, broken and ledgy. Soil, rocky limestone. Timber, scattered palo verde, Undergrowth, grass, cat claw and cacti.</p>
	<p>West, bet. secs. 3 and 34.</p> <p>Over broken land, through scattered timber.</p>
16.20	Rocky spur, slopes N. 15° W.
39.00	Rocky spur, slopes N.
40.00	Point for the ¼ sec. cor. of secs. 3 and 34.

BOOK 4803

North Boundary of T. 2 N., R. 8 E., Arizona

9.

CHAINS

Set the iron post over an "x" chiseled on solid rock, mound with stones to top, brass cap mkd.

T3N R8E

$\frac{1}{4}$   $\frac{S\ 34}{S\ 3}$

T2N

1966

48.60 Spur, slopes SE.

57.40 Wash, in bottom of canyon, drains N. 15° E.

65.60 Spur, slopes N.

78.80 Draw, drains NE.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set the iron post over an "x" chiseled in solid rock, mound with stones to top, brass cap mkd.

T3N R8E

$\frac{S33}{S\ 4}$  |  $\frac{S34}{S\ 3}$

T2N

1966

Land, broken.

Soil, rocky and sandy.

Timber, scattered palo verde.

Undergrowth, cat claw, grass and cacti.

West, bet. secs. 4 and 33.

Over broken land.

10.20 Long yellow spur, slopes N. 20° E.

20.70 High ridge, bears N. 15° W. and S. 15° E.

31.30 Large draw, drains N. 25° W.

34.00 Base of ledge outcropping, bears S.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 33.

Set the iron post 10 ins. in the ground, mound with stones to top, brass cap mkd.

T3N R8E

$\frac{1}{4}$   $\frac{S\ 33}{S\ 4}$

T2N

1966

51.00 Enter gentle rolling land.

51.80 Old left bank of Salt River, bears N. 40° E. and SW.

68.20 Left bank of Salt River, bears N. 50° E. and S. 40° W.

72.00 Center of Salt River, course SW.

BOOK 4803

North Boundary of T. 2 N., R. 8 E., Arizona

10.

10

CHAINS

75.90 Right bank of Salt River, bears N. 62° E. and S. 60° W.

80.00 Point for the cor. of secs. 4, 5, 32 and 33.

Set the iron post 22 ins. in the ground, in a collar of stones, brass cap mkd.

T3N R8E  
S32 | S33  
 S 5 | S 4  
 T2N

1966

Raise a mound of stone W. of the cor.

Land, broken, first half, rolling, last half.

Soil, rocky and sandy.

Timber, scattered palo verde.

Undergrowth, cat claw and cacti, willow along both banks of Salt River.

West, bet. secs. 5 and 32.

Over gentle rolling land, through moderate palo verde, through flooded area.

12.50 Leave flooded area.

13.70 Old right bank of Salt River, bears N. 64° E. and S. 55° W.

19.70 Center of bladed road (old Bush Highway), bears N. 70° E. and S. 72° W.

40.00 Point for the ¼ sec. cor. of secs. 5 and 32.

Set the iron post 22 ins. in the ground, brass cap mkd.

T3N R8E  
¼ S 32  
 S 5

1966

Raise a mound of stone N. of the cor.

49.10 Spur, slopes S. 20° W.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set the iron post 22 ins. in the ground, brass cap mkd.

T3N R8E  
S31 | S32  
 S 6 | S 5  
 T2N

1966

No accessories available.

Land, rolling.

Soil, rocky and sandy.

Timber, moderate palo verde.

Undergrowth, moderate cat claw, mesquite, brush, grass and scattered cacti.

CHAINS

West, bet. secs. 6 and 31.

Over gentle, rolling land, through moderate timber.

10.60 Power line, bears N. 77°45' E. and S. 77°45' W.

13.10 Bladed road (old Bush Highway), bears S. 70° E. and N. 72° W.

24.60 Junction of bladed roads bearing S. 65° E., S. 5° E. and N. 5° W.; enter dense thicket of mesquite.

31.80 Thicket changes from dense to moderate mesquite.

40.00 Point for the ¼ sec. cor. of secs. 6 and 31.

Set the iron post 22 ins. in the ground on a deposit of broken glass, brass cap mkd.

T3N R8E

¼  $\frac{S\ 31}{S\ 6}$

T2N

1966

45.90 Bladed road, bears S. 30° E. and N. 30° W.

47.30 Leave mesquite thicket; enter flooded area.

56.90 Left bank of Salt River, bears N. 5° E. and S. 5° W.

61.80 High right bank of Salt River, bears N. and S.

62.90 Telephone line, bears N. 60° E. and S. 60° W.

64.10 Bladed road, bears N. 15° E. and S. 15° W.

65.00 Dirt road, bears N. 10° E. and S. 10° W.

72.50 Bladed road (old Bush Highway), bears N. 46° E. and S. 44°20' W.

79.39 The Tp. cor. of Tps. 2 and 3 N., Rs. 7 and 8 E., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1930 survey.

Land, rolling.

Soil, sandy.

Timber, moderate palo verde.

Undergrowth, cat claw, brush, grass, cacti, and dense mesquite.

BOOK 4803

Subdivisional Lines Bet. Secs. 35-36 and 25-36,  
T. 2 N., R. 8 E., Arizona

12.

12

CHAINS	Survey of the Subdivisional Lines Between Secs. 35-36 and 25-36 Township 2 North, Range 8 East
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1924 survey.</p> <p>from which</p> <p>The W.C. to cor. No. 4, Mineral Survey No. 3886, Indian No. 1 lode, identical with cor. No. 2, Indian No. 4 lode, and cor. No. 3, Indian No. 2 lode, bears N. 55°04' E., 5.57 chs. dist., monumented by a pine post, 4 ins. sq., set, mkd. and witnessed as described in the mineral survey notes.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land, through moderate timber.</p>
0.80	Draw, drains S. 30° W.
3.72	Intersect line bet. cors. 3 and 4 of the Indian No. 1 lode.
	<p>from which</p> <p>The W.C. to cor. No. 4, Mineral Survey No. 3886, Indian No. 1 lode, identical with cor. No. 2, Indian No. 4 lode, and cor. No. 3, Indian No. 2 lode, bears S. 83°20' E., 4.59 chs. dist.</p>
34.60	Spur, slopes SW.
39.40	Draw, drains E.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, brass cap mkd.</p> <p style="text-align: center;">T2N R8E 1/4 S35 S36 1966</p>
	<p>from which</p> <p>Cor. No. 3, Mineral Survey No. 3886, Indian No. 4 lode, bears S. 26°28' E., 15.77 chs. dist., monumented by a limestone rock, set, mkd. and witnessed as described in mineral survey notes.</p>
73.90	Spur, slopes SE.
78.30	Draw, drains NW.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
	<p>Set the iron post 5 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T2N R8E S26 S25 S35 S36 1966</p>
	<p>Land, rolling. Soil, gravelly loam. Timber, moderate palo verde. Undergrowth, moderate cacti.</p>

CHAINS

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.

S. 89°54' W., bet. secs. 25 and 36.

Over rolling land, through moderate palo verde.

5.60 Draw, drains S. 60° W.

32.50 Wash, 15 lks. wide, 1 ft. deep, drains S.

37.40 Draw, drains SE.

40.02 Point for the 1/4 sec. cor. of secs. 25 and 36.

Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.

T2N R8E

1/4 S 25  
S 36

1966

from which

Cor. No. 4, Mineral Survey No. 1568, Black Hawk Lode, bears S. 38°24' E., 7.40 chs. dist., monumented by a granite stone, set, mkd. and witnessed as described in the mineral survey notes.

63.10 Ridge, bears S. 30° E. and N. 30° W.

71.20 Draw, drains SW.

80.04 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.  
Soil, gravelly loam.  
Timber, moderate palo verde.  
Undergrowth, moderate cacti.

Mineral Surveys

Survey No. 1568, May Day Lode; cor. No. 1 is a porphyry stone, firmly set and properly marked; cor. No. 2 could not be found; cor. No. 3 is a granite stone, firmly set in a mound of stone and properly marked; cor. No. 4 is a porphyry stone, firmly set and properly marked. Line 3-4 was found to be approximately correct as approved; line 4-1 was found to be S. 10°35' E., 1500 ft., instead of S. 11°49' E. as approved. Lines 1-2 and 2-3 are shown parallel to their respective and side lines.

General Description

The area covered by this survey, located in the Goldfield Mountains on the Tonto National Forest, lies northwest of the Superstition Mountains, north of the town of Goldfield and south of the Salt River and Saguaro Lake.

14

CHAINS

The land is rolling and mountainous, with cacti, palo verde and creosote bush the predominant vegetation. (The soil is rocky and sandy loam.)

There is one major highway, known as Apache Trail, which runs through the southeast corner of sec. 36. There are also numerous bladed roads throughout the area.

Many improvements have been made and there are a few settlers throughout the township. There are numerous mineral claims in sec. 36.

The land is being mined and used for grazing.





BOOK 4803

CERTIFICATE OF SURVEY

I, We, Wallace R. Ott and Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 10th day of September, 1965, and Supplemental Special Instructions bearing date of the 20th day of April, 1966, we have made a survey of the east and north boundaries and a portion of the subdivisional lines of Township 2 North, Range 8 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~ us and ~~my~~ our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 11, 1966  
(Date)

Wallace R. Ott  
(Cadastral Surveyor)

November 11, 1966  
(Date)

Gary T. Oviatt  
(Cadastral Surveyor)  
(Surveying Technician)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date OCT 13 1967

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the survey of the east and north boundaries, and a portion of the subdivisional lines of Township 2 North, Range 8 East, Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott and Gary T. Oviatt, having been critically examined and found correct, are hereby approved.

DEC 21 1967  
(Date)

R. E. Brown  
Acting (Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief, Division of Engineering)~~