

BOOK 4807

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 15 North, Range 10 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 28, 19 66, which provided for the surveys included under Group Number 446, approved March 29, 1966, and assignment instructions dated June 28, 19 66.

Survey commenced July 6, 19 66

Survey completed October 25, 19 66

1A

BOOK 4807
INDEX DIAGRAM

Township 15 North, Range 10 East,

6	5	4	3	2	1	3
7	8	9	10	11	12	3
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	2
31	32	33	34	35	36	1
						1

BOOK 4807

Township 15 North, Range 10 East
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The boundaries and subdivisional lines were surveyed in 1881 by T. F. White.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Remonumentation, T. 15 N., R. 10 E., Arizona

The point for the cor. of secs. 25, 30, 31 and 36, T. 15 N., Rs. 10 and 11 E., is determined by using record bearing and distance from the remains of the original bearing trees

A pine, 36 ins. diam., bears S. 45½° E., 141 lks. dist., mkd. with an overgrown blaze

A pine, 40 ins. diam., bears S. 16° W., 207 lks. dist., mkd. TXVNRXESXXXVIBT

A pine, 34 ins. diam., bears N. 28° W., 172 lks. dist., mkd. TXVNRXESXXVBT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15N
R10E R11E
S25|S30
S36|S31
1966

from which

A pine, 6 ins. diam., bears N. 56° E., 19 lks. dist., mkd. T15NR11ES30BT

A pine, 6 ins. diam., bears S. 84° E., 18 lks. dist., mkd. T15NR11ES31BT

Cor. is on a grassy SE. slope in moderate timber about 150 lks. N. of a draw draining E.

The ¼ sec. cor. of secs. 25 and 30, T. 15 N., Rs. 10 and 11 E., monumented by the remains of a rotted wooden stake in a mound of stone, from which the original bearing trees

A pine, 28 ins. diam., bears N. 9° E., 64 lks. dist., part of scribe mks. visible

BOOK 4807

Remonumentation, T. 15 N., R. 10 E., Arizona

2.

2

CHAINS

A pine, 28 ins. diam., bears West, 75 lks. dist.,
mkd. with an overgrown blaze; I remark
T15NR10E½S25BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins.
in the ground, mound of stone to top, brass cap mkd.

T15N
R10E R11E
½
S25|S30
1966

from which

A pine, 16 ins. diam., bears N. 57¾° E., 29 lks.
dist., mkd. T15NR11E½S30BT

Cor. is on a gentle NE. slope in scattered timber.

The cor. of secs. 19, 24, 25 and 30, T 15 N., Rs. 10
and 11 E., monumented by the remains of a rotted
wooden stake in a large mound of stone, from which the
original bearing trees

A pine, 36 ins. diam., bears N. 34½° E., 341 lks.
dist., mkd. with an overgrown blaze

A pine, 38 ins. diam., bears S. 30° E., 206 lks.
dist., mkd. TXVNRXIESXXXBT

A fallen pine, 40 ins. diam., bears S. 52° W.,
394 lks. dist., no mks. visible

A pine, 34 ins. diam., bears N. 7½° W., 360 lks.
dist., mkd. with faint scribe mks.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins.
in the ground, mound of stone to top, brass cap mkd.

T15N
R10E R11E
S24|S19
S25|S30
1966

from which

A pine, 7 ins. diam., bears S. 45° E., 57 lks.
dist., mkd. T15NR11ES30BT

A pine, 10 ins. diam., bears S. 43° W., 108 lks.
dist., mkd. T15NR10ES25BT

The center of Butler's Tank, bears N. 25° W.,
about 15.00 chs. dist.

Cor. is on gently rolling land in scattered timber.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, T. 15 N., Rs. 10 and 11 E., is monumented by a wooden stake with faint scribe mks. lying loose on the ground alongside a mound of stone, from which the remains of the original bearing trees

A juniper, 40 ins. diam., bears S. 18° W., 274 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15N
R10E R11E
 $\frac{1}{4}$
S 1 | S 6
1966

from which

A juniper, 4 ins. diam., bears S. 9° E., 100 lks. dist., mkd. XBT.

Cor. is on a gentle SE. slope in scattered timber, and 6 lks. E. of a N. and S. fence.

The Tp. cor. of Ts. 15 and 16 N., Rs. 10 and 11 E., monumented by an old post lying alongside a mound of stone, the center of which is accepted as the cor. point, from which the original bearing trees

A juniper, 24 ins. diam., bears S. 37° E., 488 lks. dist., mkd. TXVNRXIEVI

A juniper, 17 ins. diam., bears S. $7\frac{1}{4}^\circ$ W., 519 lks. dist., mkd. TXVNRXE1

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T16N
R10E R11E
S36 | S31
S 1 | S 6
T15N
1966

from which

A juniper limb, 12 ins. diam., bears N. $28\frac{3}{4}^\circ$ E., 288 lks. dist., mkd. T16NR11ES31BT.

A juniper, 5 ins. diam., bears N. $79\frac{1}{2}^\circ$ W., 96 lks. dist., mkd. S36BT.

A fence cor., bears N. 41° W., 39 lks. dist.; fences bear E., W. and S.

Cor. is on a gentle N. slope at the S. edge of a grassy area.

BOOK 4807

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
James E. Muth	Engineering Aid
John H. Higgins	Engineering Aid
All U. S. Forest	Service personnel

BOOK 4807
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 28 day of March, 19 66,
I have remonumented cadastral survey corners in Township 15 North, Range
10 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

November 18, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)
(Supervisory Surveying Technician)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in
Township 15 North, Range 10 East, Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician,
having been critically examined and found correct, are hereby approved.

FEB 27 1968
(Date)

R. E. Brown
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)