



1A

# BOOK 4808 INDEX DIAGRAM

Township 9 North, Range 24 East,  
3

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1

BOOK 4808

Township 9 North, Range 24 East  
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The boundaries and subdivisional lines were surveyed in 1882 by A. P. Johnson. The south and east boundaries were partially resurveyed and the subdivisional lines were partially retraced in 1915 by S. E. Blout.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

---

Re monumentation, T. 9 N., R. 24 E., Arizona

---

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, T. 9 N., Rs. 24 and 25 E., monumented by a basalt stone, 10 x 12 x 22 ins., firmly set in ground, mkd.  $\frac{1}{4}$ , from which the original bearing trees

A pine, 22 ins. diam., bears S. 61° E., 77 lks. dist., mkd.  $\frac{1}{4}$  S BT; I remark  $\frac{1}{4}$  S19 BT

A pine, 48 ins. diam., bears N. 20° W., 23 lks. dist., mkd. BT; I remark  $\frac{1}{4}$  S24 BT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, mound of stone to top, brass cap mkd.

T9N  
R24E R25E  
 $\frac{1}{4}$   
S24|S19  
1966

Bury the original corner stone alongside the iron post.

Cor. is in a N. and S. fence.

---

The  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, monumented by a basalt stone, 8 x 14 x 20 ins., firmly set in a small mound of stone, mkd. dimly, from which an original bearing tree

A pine, 27 ins. diam., bears S. 61° E., 23 lks. dist., mkd.  $\frac{1}{4}$  S BT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R24E  
 $\frac{1}{4}$  S15  
S22  
1966

2

CHAINS

from which

A pine, 22 ins. diam., bears N.  $54\frac{1}{2}^\circ$  W., 102 lks. dist., mkd.  $\frac{1}{2}$  S15 BT

Bury the original corner stone alongside the iron post.

The cor. of secs. 16, 17, 20 and 21, monumented by a basalt stone, 10 x 10 x 14 ins., firmly set in a mound of stone, mkd. dimly., from which the original bearing trees

A pine, 14 ins. diam., bears N.  $40^\circ$  E., 23 lks. dist., mkd. with an overgrown blaze

A pine, 28 ins. diam., bears S.  $60^\circ$  E., 91 lks. dist., mkd. with parts of scribe marks visible

A dead pine, 26 ins. diam., bears S.  $39^\circ$  W., 128 lks, dist., no mks. found

A pine, 17 ins. diam., bears N.  $62^\circ$  W., 71 lks. dist., mkd. T9NR24E S17 BT

At the cor. point

Set an iron post, 30 ing. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T9N R24E  
 $\frac{1}{2}$  S17 | S16  
 $\frac{1}{2}$  S20 | S21  
 1966

from which

A pine, 6 ins. diam., bears S.  $15\frac{1}{2}^\circ$  W., 61 lks. dist., mkd. T9NR24E S20 BT

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 9 and 16, monumented by a basalt stone, 10 x 12 x 12 ins., firmly set in a collar of stone, mkd.  $\frac{1}{4}$  on N. face, from which the original bearing trees

A pine, 24 ins. diam., bears S.  $34\frac{1}{2}^\circ$  E., 37 lks. dist., mkd. with an overgrown blaze

A pine, 22 ins. diam., bears N.  $8\frac{1}{2}^\circ$  W., 11 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T9N R24E  
 $\frac{1}{4}$  S9  
 $\frac{1}{4}$  S16  
 1966

Bury the original corner stone alongside the iron post.

BOOK 4808

Remonumentation, T. 9 N., R. 24 E., Arizona

3.

CHAINS

The cor. of secs. 4, 5, 8 and 9, monumented by a broken basalt stone, 8 x 8 x 10 ins., firmly set in a mound of stone, mkd. with 5 notches on S. face and 4 notches on E. face, from which the original bearing trees

A fallen pine, 30 ins. diam., bears N. 28° E., 107 lks. dist., mks. obliterated

A pine, 22 ins. diam., bears S. 21° E., 26 lks. dist., mkd. T9NR24E S9 BT

A pine, 20 ins. diam., bears S. 19° W., 73 lks. dist., mks. partially obliterated

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R24E  
 $\frac{S5}{S8} | \frac{S4}{S9}$   
 1966

from which

A pine, 22 ins. diam., bears N. 35° E., 72 lks. dist., mkd. T9NR24E S4 BT

A pine, 7 ins. diam., bears N. 56° W., 84 lks. dist., mkd. T9NR24E S5 BT

Bury the original corner stone alongside the iron post.

The ¼ sec. cor. of secs. 5 and 32, Ts. 9 and 10 N., R. 24 E., monumented by a basalt stone, 10 x 14 x 18 ins., firmly set in a large collar of stone, mkd. ¼ on side, from which an original bearing tree

A pine, 30 ins. diam., bears N. 35° E., 50 lks. dist., mkd. ¼ S

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R24E  
 $\frac{1}{4} \frac{S32}{S5}$   
 T9N  
 1966

from which

A pine, 12 ins. diam., bears S. 55½° E., 27 lks. dist., mkd. ¼ S5 BT

A pine, 18 ins. diam., bears N. 86½° W., 101 lks. dist., mkd. ¼ S32 BT

Bury the original corner stone alongside the iron post.



BOOK 4808  
CERTIFICATE OF SURVEY

I, Robert F. Johnson, HEREBY CERTIFY upon honor that,  
in pursuance of special instructions bearing date of the 28th day of March, 1966,  
I have remonumented cadastral survey corners in Township 9 North, Range  
24 East,

of the Gila and Salt River Meridian, in the State of Arizona, which  
are represented in the foregoing field notes as having been executed by me and under my direction;  
and that said survey has been made in strict conformity with said special instructions, the Manual  
of Instructions for the Survey of the Public Lands of the United States, and in specific manner  
described in the foregoing field notes.

November 18, 1966  
(Date)

*Robert F. Johnson*  
(Cadastral Surveyor)  
(Supervisory Surveying Technician)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the remonumentation of cadastral survey corners in  
Township 9 North, Range 24 East, Gila and Salt River Meridian, Arizona,

executed by Robert F. Johnson, Supervisory Surveying Technician,  
having been critically examined and found correct, are hereby approved.

FEB 27 1968  
(Date)

*R. E. Brown*  
(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Engineering)~~