

BOOK 4810

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 20 North, Range 7 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 28, 19 66, which provided for the surveys included under Group Number 446, approved March 29, 1966, and assignment instructions dated June 28, 19 66.

Survey commenced July 6, 19 66

Survey completed October 25, 19 66

BOOK 4810 INDEX DIAGRAM

Township 20 North, Range 7 East,

	6	5	4	3	2	1	5
		21		16	13	10 10	4
	7	8	9	10	11	9 12	4
7	20					8 9	3
7	18	17	16	15	14	13	3
6		20			13		2
	19	20	17 21	15 22	12 23	24	2
		19 19	17 17	15	11 12	8	1
5	30	18 29	28	14 27	11 26	25	1
5		18	16	13 14		7	
	31	32	33	34	10 35	36	

BOOK 4810

Township 20 North, Range 7 East
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The boundaries and subdivisional lines were surveyed in 1878 by J. L. Harris. The north 2 miles of the east boundary were resurveyed in 1902 by Caudle & Caudle.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Remonumentation, T. 20 N., R. 7 E., Arizona

The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, T. 20 N., Rs. 7 and 8 E., monumented by an old wooden post, set in a mound of stones, mkd. with faint scribe mks., from which the original bearing tree

A pine, 34 ins. diam., bears S. 18° W., 27 lks. dist., mkd. $\frac{1}{2}$ S

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T20N
R7E R8E
 $\frac{1}{4}$
S25|S30
1966

from which

A pine, 15 ins. diam., bears N. 78° W., 38 lks. dist., mkd. T20NR7E $\frac{1}{4}$ S25BT

Cor. is on a NE. slope in moderate timber, about 6.00 chs. W. of a gravel road bearing SE. and NW.

The cor. of secs. 19, 24, 25 and 30, T. 20 N., Rs. 7 and 8 E., monumented by a limestone, 6 x 12 x 20 ins., (record calls for a post), set in a mound of stones, mkd. with 4 notches on the N. and 2 notches on the S., from which the remains of the original bearing tree

A pine stump, 38 ins. diam., bears S. 13° W., 36 lks. dist., mkd. with part of the scribe mks. visible

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

CHAINS

T20N
R7E R8E
S24|S19
S25|S30
1966

from which

A pine, 30 ins. diam., bears N. 59° E., 137 lks. dist., mkd. T20NR8ES19BT

Raise a mound of stones W. of the iron post.

Cor. is on an E. slope, about 2.00 chs. W. of a track road in the bottom of a draw draining N.

The ¼ sec. cor. of secs. 19 and 24, T. 20 N., Rs. 7 and 8 E., monumented by a limestone, 8 x 14 x 20 ins., (record calls for a post), set in a mound of stones, mkd. with ¼ on W. face, from which the remains of the original bearing trees

A stump hole of a fallen pine, bears S. 52° E., 18 lks. dist.

A pine, 34 ins. diam., bears S. 9° W., 34 lks. dist., mkd. ½S

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, mound of stone to top, brass cap mkd.

T20N
R7E R8E
½
S24|S19
1966

from which

A pine, 8 ins. diam., bears N. 70° E., 39 lks. dist., mkd. ¼T20NR8ES19BT

Cor. is on a gentle N. slope in moderate timber about 5.00 chs. S. of a track road bearing NE. and SW.

The cor. of secs. 13, 18, 19 and 24, T. 20 N., Rs. 7 and 8 E., monumented by an old wooden post, 2½ ft. long, lying alongside a mound of stones, mkd. with part of the scribe mks. visible, from which the remains of the original bearing trees

A pine stump, bears N. 89° E., 5 lks. dist.

A pine stump, bears S. 55° W., 21 lks. dist.

A stump hole of a fallen pine, bears N. 34° W., 31 lks. dist., pine mkd. TXXNRVIIEX111

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

3.

CHAINS

T20N
R7E R8E
S13|S18
S24|S19
1966

from which

A pine, 6 ins. diam., bears S. 46° W., 2 lks.
dist., mkd. T20NR7ES24BT

A pine, 7 ins. diam., bears N. 82½° W., 37 lks.
dist., mkd. T20NR7ES13BT

Raise a mound of stones W. of the iron post.

Bury the original cor. post alongside the iron post.

Cor. is on top of a small rocky spur sloping SE.,
about 5.00 chs. W. of a bladed road bearing N. and S.

The ¼ sec. cor. of secs. 13 and 18, T. 20 N., Rs. 7 and
8 E., monumented by an old wooden post, 3 ft. long, set
10 ins. in the ground, with a mound of stones around
the post, from which the remains of the original bearing
trees

A pine, 28 ins. diam., bears S. 15° E., 47 lks.
dist., mkd. ¼S

A pine stump, bears N. 12° W., 78 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, brass cap mkd.

T20N
R7E R8E
¼
S13|S18
1966

from which

A pine, 20 ins. diam., bears S. 54° W., 88 lks.
dist., mkd. ¼S13BT

Raise a mound of stones W. of the iron post.

Bury the original cor. post alongside the iron post.

Cor. is on a gentle N. slope, and Lake Mary Well #2
bears N. 40° E., about 8.00 chs. dist.

The cor. of secs. 7, 12, 13 and 18, T. 20 N. Rs. 7 and
8 E., monumented by an old mound of stones and verified
by record course and distance from the remains of the
original bearing trees

A pine stump, bears N. 32° E., 30 lks. dist.

A pine stump, bears S. 55° E., 133 lks. dist.

A pine, 36 ins. diam., bears S. 12° W., 113 lks.
dist., mkd. TXXNRVIIEX111

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

4.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N
R7E R8E
S12 | S 7
S13 | S18
1966

Raise a mound of stones W. of the iron post.

Cor. is on nearly level land in moderate timber.

The ¼ sec. cor. of secs. 7 and 12, T. 20 N., Rs. 7 and 8 E., monumented by a charred stake set in the ground under a mound of stones, from which the original bearing tree

A pine, 40 ins. diam., bears N. 29° W., 63 lks. dist., mkd. with a burned out blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N
R7E R8E
¼
S12 | S 7
1966

from which

A pine, 5 ins. diam., bears N. 42° E., 32 lks. dist., mkd. X BT

A pine, 38 ins. diam., bears S. 49° W., 31 lks. dist., mkd. T20NR7E¼S12BT

Raise a mound of stones W. of the iron post.

Cor. is on a N. slope in moderate timber.

The point for the cor. of secs. 1, 6, 7 and 12, T. 20 N., Rs. 7 and 8 E., is determined by using record course and distance from the original bearing trees

A pine stump, bears S. 47° E., 59 lks. dist.

A pine, 36 ins. diam., bears S. 45° W., 111 lks. dist., mkd. TXXNRVIIEX11

A pine, 34 ins. diam., bears N. 85° W., 93 lks. dist., mkd. TXXNRVIIEL

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T20N
R7E R8E
S 1 | S 6
S12 | S 7
1966

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

5.

CHAINS

Cor. is on a steep W. slope about 4.00 chs. E. of Walnut Creek, draining N., and about 8.00 chs. E. of a bladed road, bearing N. and S.

The point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, T. 20 N., Rs. 7 and 8 E., is determined by using record course and distance from the original bearing trees

A pine snag, bears N. 55° E., 108 lks. dist., mkd. with an overgrown blaze

A pine, 28 ins. diam., bears S. 20° W., 11 lks. dist., mkd. $\frac{1}{2}$ SBT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T20N
R7E R8E
 $\frac{1}{4}$
S1|S6
1966

Cor. is on a steep NW. slope 20 lks. S. of a small draw, draining W., and 6.00 chs. E. of a bladed road bearing N. and S.

The cor. of secs. 25, 30, 31 and 36, T. 20 N., Rs. 6 and 7 E., monumented by a mound of stones, from which the remains of the original bearing tree

A pine stump, bears N. 35° W., 56 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T20N
R6E R7E
S25|S30
S36|S31
1966

from which

A pine, 15 ins. diam., bears S. 80° E., 13 lks. dist., mkd. T20NR7ES31BT

A pine, 10 ins. diam., bears N. 7° W., 20 lks. dist., mkd. T20NR6ES25BT

Cor. is on a SE. slope 30 lks. W. of a small draw, draining S., and 1.00 chs. E. of a bladed road bearing NE. and SW.

The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, T. 20 N., Rs. 6 and 7 E., monumented by a rotted post set in the ground under a mound of stones, from which the remains of the original bearing trees

A pine stump, bears N. 79° E., 30 lks. dist.

A pine stump, bears N. $69\frac{1}{2}^\circ$ W., 32 lks. dist.

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

6.

6

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone to top, brass cap mkd.

T20N
R6E R7E
½
S25|S30
1966

from which

A pine, 16 ins. diam., bears S. 59½° E., 42 lks. dist., mkd. T20NR7E½S30BT

A pine, 14 ins. diam., bears S. 12½° W., 30 lks. dist., mkd. T20NR6E½S25BT

Cor. is on a rocky E. slope 20 lks. W. of a fence cor. from which fences bear E. and N.

The cor. of secs. 13, 18, 19 and 24, T. 20 N., Rs. 6 and 7 E., monumented by a surveyor stake set in a mound of stones, from which the original bearing trees

A pine stump, bears N. 27° E., 36 lks. dist., mkd. with part of the scribe mks. visible

A pine stump, bears S. 8° E., 41 lks. dist., mkd. TXXNRVIIEXIX

A pine, 32 ins. diam., bears S. 64° W., 76 lks. dist., mkd. TXXNRVIEXXIV

A pine, 38 ins. diam., bears N. 83½° W., 98 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone to top, brass cap mkd.

T20N
R6E R7E
S13|S18
S24|S19
1966

Cor. is on gently rolling land in heavy timber 20 lks. N. of a track road bearing NE. and W., and 10 lks. E. of a fence corner, from which fences bear N., S. and W.

The ¼ sec. cor. of secs. 13 and 18, monumented by a rotted post set in a mound of stones, from which the remains of the original bearing tree

A stump hole, bears N. 62° W., 37 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

CHAINS

T20N
R6E R7E
 $\frac{1}{4}$
S13|S18
1966

from which

A pine, 18 ins. diam., bears S. 21° W., 33 lks. dist., mkd. T20NR6E $\frac{1}{4}$ S13BT

A pine, 7 ins. diam., bears N. 24 $\frac{3}{4}$ ° W., 55 lks. dist., mkd. XBT

Raise a mound of stones W. of the iron post.

Cor. is on gently rolling land in heavy timber 5 lks. W. of a fence bearing N. and S.

The cor. of secs. 7, 12, 13 and 18, T. 20 N., Rs. 6 and 7 E., monumented by a newly mkd. stone (record calls for a post), from which the original bearing trees

A pine, 32 ins. diam., bears N. 38° E., 94 lks. dist., mkd. TXXNRVIEVII

A pine stump, bears S. 9° E., 75 lks. dist.

A pine, 36 ins. diam., bears S. 19° W., 51 lks. dist., mkd. with an overgrown blaze

A pine stump, bears N. 20 $\frac{1}{2}$ ° W., 57 lks. dist., mkd. TXXNRVIE XII

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N
R6E R7E
S12|S 7
S13|S18
1966

Raise a mound of stones W. of the iron post.

Cor. is 20 lks. E. of a N. and S. fence and about 6.00 chs. N. of alternate U. S. Hwy. 89.

The cor. of secs. 25, 26, 35 and 36, monumented by a charred stake set in the ground under a mound of stones, from which the original bearing trees

A pine snag, bears N. 20° E., 20 lks. dist., part of scribe marks visible

A pine stump, bears S. 88° W., 97 lks. dist.

A pine stump, bears N. 46° W., 54 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

BOOK 4810

8

Remonumentation, T. 20 N., R. 7 E., Arizona

8.

CHAINS

T20N R7E
S26 | S25
S35 | S36
 1966

Raise a mound of stones W. of the iron post.

Cor. is at the base of a N. slope at the N. edge of timber and 70 lks. S. of a wash draining irregularly E.

The cor. of secs. 23, 24, 25 and 26, monumented by a limestone, firmly set in a collar of stones, mkd. with one notch on the E. and 2 notches on the S., with the remains of a charred stake set in ground alongside, from which the remains of the original bearing trees

A pine stump, bears S. 10½° E., 32 lks. dist.

A pine stump, bears S. 41° W., 72 lks. dist.

A pine stump, bears N. 58½° W., 92 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
S23 | S24
S26 | S25
 1966

from which

A pine, 6 ins. diam., bears S. 32½° W., 77 lks. dist., mkd. S26BT

A pine, 7 ins. diam., bears N. 70° W., 73 lks. dist., mkd. S23BT

Raise a mound of stones W. of the iron post.

Bury the original cor. stone alongside the iron post.

Cor. is on rolling land in scattered timber 80 lks. S. of a fence which bears NW. and SE.

The cor. of secs. 11, 12, 13 and 14, monumented by an old mound of stones (no evidence of original cor. post), from which the remains of the original bearing trees

A fallen pine, bears N. 20° E., 65 lks. dist.

A fallen pine, bears S. 72° W., 19 lks. dist., mkd. TXXNRVIIEXIV

A pine stump, bears N. 63° W., 22 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
S11 | S12
S14 | S13
 1966

from which

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

9.

CHAINS

An oak, 12 ins. diam., bears N. 63° E., 24 lks. dist., mkd. T2ONR7ES12BT

A pine, 16 ins. diam., bears N. 65° W., 48 lks. dist., mkd. T2ONR7ES11BT

Raise a mound of stones W. of the iron post.

Cor. is on a steep E. slope in moderate timber.

The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented by a stone set in a mound of stones, mkd. $\frac{1}{4}$ on N. face, (record calls for a post), from which the remains of the original bearing trees

A pine stump, bears S. 58° E., 102 lks. dist.

A pine stump, bears N. 28° W., 95 lks. dist.

A pine, 26 ins. diam., bears N. 9° W., 30 lks. dist., mkd. $\frac{1}{4}$ SBT, (not called for in record)

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground, mound of stone to top, brass cap mkd.

T2ON R7E

$\frac{1}{4}$ $\frac{S12}{S13}$
1966

Deposit mkd. rock cor. in mound of stones alongside the iron post.

Cor. is on a S. slope of small ridge bearing E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by an old mound of stones, (no evidence of orig. cor. post), from which the original bearing trees

A pine, 26 ins. diam., bears S. 55° E., 16 lks. dist., mkd. $\frac{1}{4}$ S

A pine stump, bears N. 65° W., 78 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T2ON R7E

$\frac{1}{4}$
S11|S12
1966

from which

A double pine, 12 ins. diam., bears S. 72 $\frac{1}{2}$ ° W., 76 lks. dist., mkd. T2ONR7E $\frac{1}{4}$ S11BT

Raise a mound of stones W. of the iron post.

Cor. is on a N. slope in moderate to thick timber about 4.00 chs. S. of a power line, which bears E. and W.

10

CHAINS

The cor. of secs. 1, 2, 11 and 12, monumented by a sandstone, 18 x 12 x 5 ins., firmly set, mkd. with 5 notches on the S. and 5 notches on the W., from which the remains of the original bearing trees

A pine stump, bears N. 66° E., 94 lks. dist.

A pine, 32 ins. diam., bears N. 11° W., 128 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 $\frac{S}{S11} \frac{2}{S12}$
 1966

Bury the original cor. stone and glass alongside the iron post.

Cor. is in a clearing on nearly level ground 8 lks. NE. of a fence cor. from which fences bear S. and E.

The ¼ sec. cor. of secs. 1 and 12, monumented by a limestone, 16 x 10 x 8 ins., firmly set in a mound of stones, mkd. ¼ on N., from which the remains of the original bearing trees

A pine stump, bears N. 79° E., 38 lks. dist.

A pine, 24 ins. diam., bears S. 13° E., 38 lks. dist., mkd. ½S

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 $\frac{1}{4} \frac{S}{S12}$
 1966

from which

A pine, 16 ins. diam., bears N. 21° E., 42 lks. dist., mkd. T20NR7E½S1BT

Raise a mound of stones N. of the iron post.

Bury the original cor. stone alongside the iron post.

Cor. is on an E. slope in thick timber 38 lks. N. of a fence which bears E. and W., and 60 lks. W. of a small draw, draining NE.

The ¼ sec. cor. of secs. 34 and 35, monumented by an old wooden post, firmly set 3 ft. above ground, from which the remains of the original bearing trees

A pine stump, bears N. 19½° E., 114 lks. dist.

A pine stump, bears S. 56° E., 26 lks. dist.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E

$\frac{1}{2}$
S34|S35
1966

from which

A pine, 28 ins. diam., bears N. 22° W., 17 lks. dist., mkd. $\frac{1}{2}$ S34BT

Raise a mound of stones W. of the iron post.

Bury the old original cor. alongside the iron post.

Cor. is in an open area on a S. slope.

The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented by a mound of stones (no evidence of the original cor. post), from which the remains of the original bearing trees

A pine stump, bears N. 25° E., 136 lks. dist.

A pine stump, bears S. 9° E., 69 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R7E

$\frac{1}{2}$
S27|S26
1966

from which

A pine, 8 ins. diam., bears S. 29° E., 91 lks. dist., mkd. $\frac{1}{2}$ S26BT

A pine, 9 ins. diam., bears S. 85° W., 31 lks. dist., mkd. $\frac{1}{2}$ S27BT

Cor. is on a rocky W. slope in moderate timber 8 lks. NE. of a fence cor., from which fences bear N., S. and E.

The cor. of secs. 22, 23, 26 and 27, monumented by remains of an old post set in the ground, and in a mound of stones, from which the remains of the original bearing trees

A pine stump, bears N. 32° E., 145 lks. dist.

A stump hole, bears S. 46° E., 33 lks. dist.

A pine stump, bears S. 75° W., 102 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

12.

12

CHAINS

T20N R7E
 $\frac{1}{2}$ S22 | S23
 $\frac{1}{4}$ S27 | S26
 1966

Raise a mound of stones W. of the iron post.

Cor. is 20 lks. W. of a fence cor., from which fences bear N., S. and E.

The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented by part of a charred stake set in the ground under a mound of stones, from which the remains of the original bearing trees

A pine stump, bears S. 6° E., 32 lks. dist.

A pine stump, bears N. 39° E., 48 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R7E
 $\frac{1}{2}$ S23
 $\frac{1}{4}$ S26
 1966

from which

A pine, 6 ins. diam., bears S. 76° W., 100 lks. dist., mkd. $\frac{1}{2}$ S26BT

A pine, 8 ins. diam., bears N. 10° W., 114 lks. dist., mkd. $\frac{1}{2}$ S23BT

Cor. is 35 lks. E. of a small draw, drains S.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented by part of a charred stake set in the ground, from which the remains of the original bearing trees

A pine, 22 ins. diam., bears N. 75° E., 52 lks. dist., mkd. with an overgrown blaze

A pine stump, bears S. 80° W., 102 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 $\frac{1}{4}$
 $\frac{1}{2}$ S22 | S23
 1966

Raise a mound of stones W. of the iron post.

Cor. is on nearly level land 30 lks. W. of a N. and S. fence, and about 6.00 chs. S. of a pond.

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

13.

CHAINS

The cor. of secs. 14, 15, 22 and 23, monumented by the original cor. post, firmly set in a mound of stones, mkd. 3 notches on the S.; 2 notches on the E., XXII on the SW., and XXIII on the SE., from which the remains of the original bearing trees

A pine stump, bears S. 55° E., 92 lks. dist.

A stump hole, bears S. 1° W., 53 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R7E
 S15|S14
 S22|S23
 1966

from which

A pine, 7 ins. diam., bears S. 26° W., 10 lks. dist., mkd. S22BT

A pine, 11 ins. diam., bears N. 80° W., 30 lks. dist., mkd. T20NR7ES15BT

Invert the original cor. and set alongside the iron post.

Cor. is in thick timber on a narrow rocky spur sloping S. 55° E.

The cor. of secs. 2, 3, 10 and 11, monumented by a limestone, 24 x 10 x 6 ins., firmly set in the ground in a mound of stones, mkd. 5 notches on the S. and 2 notches on the E., from which the remains of the original bearing trees

A pine, 28 ins. diam., bears S. 63° E., 67 lks. dist., mkd. ~~TX~~NRVIIEXI

A pine stump, bears S. 27° W., 29 lks. dist.

A pine stump, bears N. 8° W., 162 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 S 3|S 2
 S10|S11
 1966

Raise a mound of stones W. of the iron post.

Bury the original cor. stone alongside the iron post.

Cor. is on an E. slope in moderate timber.

The cor. of secs. 27, 28, 33 and 34, monumented by a limestone, 12 x 6 x 4 ins., firmly set, mkd. with one notch on the S. and 3 notches on the E., from which the remains of the original bearing trees

14

CHAINS

A pine stump, bears N. 50° E., 50 lks. dist.

A pine, 24 ins. diam., bears S. 19° E., 125 lks. dist., mkd, NRVIEX

A pine stump, bears S. 80° W., 100 lks. dist.

A pine stump, bears N. 28° W., 101 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
S28 | S27
S33 | S34
 1966

Bury the original cor. stone alongside the iron post.

Cor. is at a fence cor., from which fences bear N., S. and W., and 15 lks. N. of a track road bearing NE. and SW.

The ¼ sec. cor. of secs. 27 and 34, monumented by a charred stake and a limestone, 22 x 12 x 10 ins., firmly set, mkd. with a ¼ on the N. side, from which the remains of the original bearing trees

A pine stump, bears S. 38° E., 85 lks. dist.

A pine stump, bears N. 50° W., 42 lks. dist., mkd. with an old blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 ¼ S27
 ¼ S34
 1966

from which

A pine, 12 ins. diam., bears N. 46° E., 124 lks. dist., mkd. ¼S27BT

A pine, 12 ins. diam., bears S. 55½° W., 73 lks. dist., mkd. ¼S34BT

Bury the original cor. stone alongside the iron post.

Cor. is in a E. and W. fence line on nearly level land.

The ¼ sec. cor. of secs. 27 and 28, monumented by a charred stake set in the ground alongside a ½ in. iron pipe, from which the remains of the original bearing trees

A pine stump, bears N. 1° E., 111 lks. dist.

At the cor. point

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

15.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E

½
S28|S27
1966

from which

A pine, 24 ins. diam., bears S. 41½° E., 40 lks. dist., mkd. T20NR7E½S27BT

A pine, 26 ins. diam., bears N. 2¾° W., 123 lks. dist., mkd. ½S28BT

Deposit glass, the old charred stake and ½ in. pipe alongside the iron post.

Cor. is 15 lks. S. of a dirt road which bears E. and W., and in a fence cor. from which fences bear S. and W.

The ¼ sec. cor. of secs. 22 and 27, monumented by the remains of a old rotted wooden post set in the ground under a mound of stones, from which the remains of the original bearing trees

A pine stump, bears N. 23° E., 42 lks. dist.

A pine stump, bears S. 22½° E., 15 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R7E

½
S22
S27
1966

from which

A pine, 12 ins. diam., bears N. 20° E., 39 lks. dist., mkd. ½S22BT

A pine, 14 ins. diam., bears S. 9½° E., 30 lks. dist., mkd. T20NR7E½S27BT

Cor. is in moderate timber on a low ridge which bears E. and W.

The ¼ sec. cor. of secs. 21 and 22, monumented by the remains of the original cor. post set in the ground under a mound of stones, from which the remains of the original bearing trees

A pine stump, bears N. 23° E., 28 lks. dist.

A pine, 22 ins. diam., bears S. 60° W., 20 lks. dist., mkd. ½S

At the cor. point

16

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R7E

½
S21 | S22
1966

from which

A pine, 10 ins. diam., bears N. 66° E., 17 lks. dist., mkd. T20NR7E½S22 BT

Cor. is on a SW. slope in moderate timber about 8 chs. N. of a dirt road which bears E. and W.

The point for the cor. of secs. 3, 4, 9 and 10 is determined by using record course and distance from the remains of the original bearing trees

A pine stump, bears N. 28° E., 76 lks. dist.

A pine stump, bears S. 70° E., 95 lks. dist.

A pine stump, bears S. 51° W., 51 lks. dist.

A pine, 26 ins. diam., bears N. 25° W., 123 lks. dist., mkd. TXXNRVIIIEIV

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
S 4 | S 3
S 9 | S10
1966

Raise a mound of stones W. of the iron post.

Cor. is on a N. slope in a small draw which drains N.

The point for the cor. of secs. 28, 29, 32 and 33 is determined by using record course and distance from the remains of the original bearing trees

A fallen pine, bears N. 60° E., 225 lks. dist., mkd. with part of scribe mks. visible

A pine stump, bears S. 59° E., 416 lks. dist.

A pine stump, bears S. 85° W., 418 lks. dist.

A pine stump, bears N. 50° W., 112 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
S29 | S28
S32 | S33
1966

from which

BOOK 4810

Remonumentation, T. 20 N., R. 7 E., Arizona

17.

CHAINS

A pine, 14 ins. diam., bears N. 50° W., 13 lks. dist., mkd. S29BT

Raise a mound of stones W. of the iron post.

Cor. is on the SW. edge of a clearing about 5 chs. SE. of a railroad track, which bears NE. and SW.

The cor. of secs. 20, 21, 28 and 29, monumented by a re-bar firmly set, from which the remains of the original bearing trees

A pine, 22 ins. diam., bears N. 60° E., 107 lks. dist., mkd. TXXNRVIIEXXI

A pine stump, bears S. 66° E., 16 lks. dist.

A pine stump, bears S. 85° W., 122 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E	
S20	S21
S29	S28
1966	

from which

A fence cor., bears N. 67° W., 23 lks. dist.; fences bear E. and S.

The NW. cor. of a fireplace, bears S. 50° E., 71 lks. dist.

The ¼ sec. cor. of secs. 21 and 28, monumented by an old mound of stones, from which an original bearing tree

A pine, 36 ins. diam., bears S. 45½° E., 25 lks. dist., mkd. ½S

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E	
¼	S21
	S28
1966	

from which

A pine, 5 ins. diam., bears N. 56° W., 36 lks. dist., mkd. XBT

Cor. is on a NW. slope in moderate timber.

The ¼ sec. cor. of secs. 20 and 21, monumented by a limestone, 5 x 12 x 17 ins., firmly set in a mound of stone, mkd. ¼ on the W., from which the remains of the original bearing tree

CHAINS

A stump hole, bears S. 46° E., 20 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
¼
S20|S21
1966

from which

A pine, 24 ins. diam., bears S. 88° E., 64 lks. dist., mkd. T20NR7E¼S21BT

A pine, 14 ins. diam., bears S. 52½° W., 35 lks. dist., mkd. ¼S20BT

Raise a mound of stones W. of the iron post.

Bury the original cor. stone alongside the iron post.

Cor. is at a fence cor. from which fences bear W. and N., and is 35 lks. W. of a small draw draining SW.

The ¼ sec. cor. of secs. 29 and 32, monumented by the remains of an old wooden post under a mound of stone, from which the original bearing trees

A pine, 18 ins. diam., bears S. 25° W., 24 lks. dist., mkd. ¼SBT

A pine, 20 ins. diam., bears N. 77° W., 54 lks. dist., mkd. ¼SBT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
¼
S29
S32
1966

Raise a mound of stones N. of the iron post.

Cor. is on gently rolling land in moderate timber about 5 chs. N. of a fence which bears E. and W. and about 6 chs. E. of a bladed road.

The ¼ sec. cor. of secs. 29 and 30, monumented by an old mound of stone, from which the remains of the original bearing trees

A pine stump, bears N. 24° E., 90 lks. dist.

A pine stump, bears N. 85° W., 60 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground, mound of stone to top, brass cap mkd.

CHAINS

T20N R7E

$\frac{1}{4}$
S30|S29
1966

from which

A pine, 20 ins. diam., bears S. $36\frac{1}{2}^{\circ}$ E., 34 lks. dist., mkd. T20NR7E $\frac{1}{4}$ S29BT

A pine, 24 ins. diam., bears S. 25° W., 81 lks. dist., mkd. $\frac{1}{4}$ S30BT

Cor. is in a E. and W. fence line and 60 lks. W. of a power line bearing N. and S.

The point for the cor. of secs. 19, 20, 29 and 30 is determined by using record course and distance from the remains of the original bearing trees

A pine stump, bears N. 77° E., 50 lks. dist., scribe mks. visible

A pine stump, bears S. 55° W., 143 lks. dist.

A pine stump, bears N. $43\frac{3}{4}^{\circ}$ W., 141 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, brass cap mkd.

T20N R7E
S19|S20
S30|S29
1966

Deposit glass in the hole alongside the iron post.

Cor. is in a track road bearing N. and E. and about 6 chs. W. of the Black Canyon Hwy. which bears N. and S.

The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented by a limestone, 8 x 12 x 25 ins., firmly set and in a mound of stone, mkd. $\frac{1}{4}$ on N., from which the remains of the original bearing tree

A stump hole, bears N. 21° E., 35 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 $\frac{1}{4}$ S20
S29
1966

from which

A pine, 12 ins. diam., bears N. 35° E., 105 lks. dist., mkd. T20NR7E $\frac{1}{4}$ S20BT

A pine, 12 ins. diam., bears S. 27° E., 96 lks. dist., mkd. $\frac{1}{4}$ S29BT

CHAINS

Raise a mound of stones N. of the iron post.

Deposit the original cor. stone in the mound N. of the cor.

Cor. is 35 lks. NE. of a power line which bears SE. and NW.

The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented by an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set and in a mound of stones, from which the remains of the original bearing trees

A pine, 20 ins. diam., bears S. 65° E., 22 lks. dist., mkd. $\frac{1}{4}$ S

A pine stump, bears N. $74\frac{1}{2}^\circ$ W., 50 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 $\frac{1}{4}$ $\frac{S17}{S20}$
 1966

from which

A pine, 7 ins. diam., bears N. 27° E., 39 lks. dist., mkd. $\frac{1}{4}$ S17BT

Raise a mound of stones N. of the iron post.

Cor. is on a steep W. slope about 3.50 chs. E. of a power line and about 6 chs. E. of a bladed road, both bearing N. and S.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented by a malpais stone, 6 x 14 x 20 ins., firmly set, mkd. with $\frac{1}{4}$ on N., (record calls for a post), from which the remains of the original bearing trees

A stump hole, bears N. 33° W., 83 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E
 $\frac{1}{4}$ $\frac{S7}{S18}$
 1966

from which

A pine, 14 ins. diam., bears N. $20\frac{1}{2}^\circ$ E., 30 lks. dist., mkd. T20NR7E $\frac{1}{4}$ S7BT

A pine, 8 ins. diam., bears N. 54° W., 51 lks. dist., mkd. XBT

Raise a mound of stones N. of the iron post.

Bury the original cor. stone alongside the iron post.

CHAINS

Cor. is located 20 lks. S. of a fence which bears E. and W.

The cor. of secs. 5, 6, 7 and 8, monumented by a 1 in. iron pipe, firmly set, from which the remains of the original bearing trees

A pine stump, bears N. 40° E., 60 lks. dist.

A pine stump, bears S. 50° E., 70 lks. dist.

A pine snag, bears N. 7½° W., 57 lks. dist., mkd. TXXNRVIEVI

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T20N R7E

S6 | S5

S7 | S8

1966

from which

A pine, 9 ins. diam., bears S. 71° W., 9 lks. dist., mkd. T20NR7ES7BT

Raise a mound of stones W. of the iron post.

Cor. is located at the cor. of a pole fence from which fences bear N. and W. The cor. is about 3 chs. W. of the road to Sedona and about 6 chs. W. of U. S. Hwy. 89, both bearing N. and S.

BOOK 4810
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 28th day of March, 1966,
I have remonumented cadastral survey corners in Township 20 North,
Range 7 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

November 18, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)
Supervisory Surveying Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in
Township 20 North, Range 7 East, of the Gila and Salt River Meridian,
Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician,
having been critically examined and found correct, are hereby approved.

FEB 27 1968
(Date)

R. E. Brown
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)