

BOOK 4811

Form 4-679  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of

REMONUMENTATION

in

Township 9 North, Range 23 East

Of the Gila and Salt River Meridian,

In the State of Arizona

## EXECUTED BY

Robert F. Johnson, Supervisory Surveying Technician

Under special instructions dated March 28, 19 66, which provided for the surveys  
included under Group Number 446, approved March 29, 1966,  
and assignment instructions dated October 25, 19 66.

Survey commenced October 26, 19 66

Survey completed November 16, 19 66

1A

# BOOK 4811 INDEX DIAGRAM

Township 9 North, Range 23 East

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

3

2

1

1

BOOK 4811

Township 9 North, Range 23 East  
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The south boundary, the Second Standard Parallel North, and the east, west and north boundaries and the subdivisional lines were surveyed in 1883 by O. D. Wheeler. The south boundary, the Second Standard Parallel North, was resurveyed in 1908 by J. B. Wright.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Re monumentation, T. 9 N., R. 23 E., Arizona

The SC  $\frac{1}{2}$  sec. cor. of sec. 34, T. 9 N., R. 23 E., monumented by a malpais stone, 8 x 14 x 22 ins., firmly set in mound of stone, mkd. SC  $\frac{1}{2}$

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, mound of stone to top, brass cap mkd.

SC  
T9N R23E  
 $\frac{1}{2}$  S34  
1966

from which

A pine, 6 ins. diam., bears N.  $45\frac{1}{2}^\circ$  W., 22 lks. dist., mkd.  $\frac{1}{2}$  S34 BT

A pine, 6 ins. diam., bears N.  $13^\circ$  W., 52 lks. dist., mkd.  $\frac{1}{2}$  S34 BT

Bury the original corner stone alongside the iron post.

The SC of secs. 33 and 34, T. 9 N., R. 23 E., was established by record dist. from the original bearing trees

A pine, 20 ins. diam., bears N.  $24\frac{1}{2}^\circ$  E., 80 lks. dist., mkd. SC T9NR23E S34 BT

A pine, 14 ins. diam., bears S.  $1^\circ$  W., 64 lks. dist., mkd. T8N R23E S3 BT

A pine, 24 ins. diam., bears N.  $47\frac{1}{2}^\circ$  W., 54 lks. dist., mkd. SC T9NR23E S33 BT

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, mound of stone to top, brass cap mkd.

BOOK 4811

Remonumentation, T. 9 N., R. 23 E., Arizona

2.

2

CHAINS

SC  
T9N R23E  
S33|S34  
1966

The SC  $\frac{1}{4}$  sec. cor. of sec. 33, T. 9 N., R. 23 E., was established by record dist. from the original bearing trees

A pine, 20 ins. diam., bears N. 8° E., 65 lks. dist., mkd.  $\frac{1}{4}$  S BT

A pine stump, 18 ins. diam., bears S. 32° E., 49 lks. dist., mkd.  $\frac{1}{4}$  S

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., on bed-rock, mound of stone to top, brass cap mkd.

SC  
T9N R23E  
 $\frac{1}{4}$  S33  
1966

from which

A pine, 12 ins. diam., bears N. 64° E., 109 lks. dist., mkd. SC  $\frac{1}{4}$  S33 BT

The cor. of secs. 1, 2, 11 and 12, monumented by a basalt stone, 6 x 8 x 14 ins. firmly set in a mound of stone, mkd. with 5 notches on S. face and 1 notch on E. face, from which the original bearing trees

A pine, 26 ins. diam., bears N. 71° E., 70 lks. dist., mkd. T9N R23E 1 BT

A pine, 28 ins. diam., bears S. 72° E., 105 lks. dist., mks. partially visible

A pine, 24 ins. diam., bears S. 22° W., 68 lks. dist., mks. obliterated; I remark T9N R23E S11 BT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 14 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E  
S 2 | S 1  
S11 | S12  
1966

from which

A pine, 8 ins. diam., bears N. 4° E., 7 lks. dist., mkd. T9N R23E S1 BT

Bury the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, monumented by a shattered basalt stone, set in a mound of stone, mkd. dimly, from which the original bearing trees

BOOK 4811

Remonumentation, T. 9 N., R. 23 E., Arizona

3.

CHAINS

A pine, 12 ins. diam., bears N. 47° E., 68 lks. dist., mkd.  $\frac{1}{4}$  S BT

A dead pine, 24 ins. diam., bears S. 46° E., 61 lks. dist., mkd.  $\frac{1}{4}$  S BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T9N R23E

$\frac{1}{4}$  S14  
S23

1966

from which

A pine, 10 ins. diam., bears N. 64½° E., 113 lks. dist., mkd.  $\frac{1}{4}$  S14 BT

A pine, 10 ins. diam., bears S. 77° W., 34 lks. dist., mkd.  $\frac{1}{4}$  S23 BT

Bury the original corner stone alongside the iron post.

The cor. of secs. 2, 3, 10 and 11 was established by record dist. from the original bearing trees

A pine stump, 24 ins. diam., bears N 30½° E., 118 lks. dist., mks. obliterated

A pine stump, 36 ins. diam., bears S. 34° E., 102 lks. dist., mks. obliterated

A dead pine, 24 ins. diam., bears S. 55° W., 51 lks. dist., mkd. dimly R23E BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E

S 3 | S 2  
S10 | S11

1966

from which

A pine, 8 ins. diam., bears S. 26° E., 120 lks. dist., mkd. T9N R23E S11 BT

A pine, 10 ins. diam., bears S. 46½° W., 84 lks. dist., mkd. T9N R23E S10 BT

Cor. is at a fence cor. from which fences bear E., W. and N.

The standard tp. cor. of T. 9 N., Rs. 22 and 23 E., monumented by a basalt stone, 12 x 16 x 26 ins., mkd. with 6 notches on the N., E. and W. faces, from which the remains of an original bearing tree

A pine stump, 22 ins. diam., bears N. 76° E., 44 lks. dist., mkd. BT on W. face

BOOK 4811

4

Remonumentation, T. 9 N., R. 23 E., Arizona

4.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

SC	
T9N	
R22E	R23E
S36	S31
1966	

from which

A pine, 8 ins. diam., bears N. 41½° E., 73 lks. dist., mkd. SC T9N R23E S31 BT

A pine, 8 ins. diam., bears N. 81½° W., 29 lks. dist., mkd. SC T9N R22E S36 BT

Bury the original corner stone alongside the iron post.



6

BOOK 4811  
CERTIFICATE OF SURVEY

I, Robert F. Johnson, HEREBY CERTIFY upon honor that,  
in pursuance of special instructions bearing date of the 28th day of March, 19 66,  
I have remonumented a portion of the cadastral survey corners in  
Township 9 North, Range 23 East,

of the Gila and Salt River Meridian, in the State of Arizona, which  
are represented in the foregoing field notes as having been executed by me and under my direction;  
and that said survey has been made in strict conformity with said special instructions, the Manual  
of Instructions for the Survey of the Public Lands of the United States, and in specific manner  
described in the foregoing field notes.

November 18, 1966  
\_\_\_\_\_  
(Date)

*Robert F. Johnson*  
\_\_\_\_\_  
(Cadastral Surveyor)  
(Supervisory Surveying Technician)

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the remonumentation of a portion of the cadastral  
survey corners in Township 9 North, Range 23 East, Gila and Salt River  
Meridian, Arizona,

executed by Robert F. Johnson, Supervisory Surveying Technician,  
having been critically examined and found correct, are hereby approved.

FEB 27 1968  
\_\_\_\_\_  
(Date)

*RE Braun*  
\_\_\_\_\_  
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
, is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief, Division of Engineering)