

BOOK 4812

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 16 North, Range 9 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 28, 19 66, which provided for the surveys
included under Group Number 446, approved March 29, 1966,
and assignment instructions dated June 28, 19 66.

Survey commenced July 6, 19 66

Survey completed October 25, 19 66

1A

BOOK 4812
INDEX DIAGRAM

Township 16 North, Range 9 East,

6	5	4	3	2	1
	5				
7	5 8	9	1 10	11	12
	4			1	
18	17	16	15	14	13
	3	3			
19	20	21	22	23	24
	3	2			
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4812

Township 16 North, Range 9 East
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The north boundary was surveyed in 1879 by J. L. Harris and retraced in 1883 by J. B. McLaughlin. The south, east and west boundaries and subdivisional lines were surveyed by T. F. White in 1881.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541 dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The cor. of secs. 10, 11, 14 and 15, monumented by an oak post, 3½ ft. long, mkd. with most of the scribe mks. visible, and set in a large mound of stone, from which the original bearing trees

A pine snag, bears S. 55° E., 70 lks. dist., mkd. with an overgrown blaze.

A pine, 34 ins. diam., bears S. 45° W., 68 lks. dist., mkd. with an overgrown blaze.

A fallen pine, bears N. 19° W., 1.09 chs. dist.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone to top, brass cap mkd.

T16N R9E	
S10	S11
S15	S14
1966	

from which

A pine, 18 ins. diam., bears N. 39° E., 34 lks. dist., mkd. T16NR9ES11BT.

A pine, 16 ins. diam., bears N. 21½° W., 40 lks. dist., mkd. T16NR9ES10BT.

Cor. is on a S. slope of a low ridge in heavy timber about 8.00 chs. S. of a bladed dirt road bearing E. and W.

The ½ sec. cor. of secs. 9 and 10, monumented by an oak post, firmly set in the ground with a mound of stone around the base, mkd. with part of the scribe mks. visible, from which the original bearing trees

BOOK 4812

Remonumentation, T. 16 N., R. 9 E., Arizona

2.

2

CHAINS

A pine, 38 ins. diam., bears S. 33° E., 18 lks. dist., mkd. with an overgrown blaze.

A pine stump, bears N. 75° W., 78 lks. dist., mkd. $\frac{1}{2}$ S.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone to top, brass cap mkd.

T16N R9E
 $\frac{1}{2}$
 S 9 | S10
 1966

from which

An oak, 11 ins. diam., bears N. 56½° W., 18 lks. dist., mkd. T16NR9E½S9BT.

Invert the original cor. and set alongside the iron post.

Cor. is on a S. slope in moderate timber, about 5.00 chs. N. of a bladed dirt road, bearing NE. and SW.

The cor. of secs. 20, 21, 28 and 29, monumented by an oak post, 3½ ft. long, firmly set in the ground with a mound of stone around the base, mkd. with most of the scribe mks. visible, from which the remains of the original bearing trees

A pine stump, bears N. 68° E., 60 lks. dist., mkd. TXVINRIXEXX1.

A pine stump, bears S. 50½° E., 1.39 chs. dist., mkd. with an overgrown blaze.

A pine stump, bears S. 13° W., 76 lks. dist., mkd. with an overgrown blaze.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone to top, brass cap mkd.

T16N R9E
S20 | S21
S29 | S28
 1966

from which

A pine, 13 ins. diam., bears S. 43½° W., 26 lks. dist., mkd. T16NR9ES29BT.

A pine, 8 ins. diam., bears N. 17° W., 20 lks. dist., mkd. T16NR9ES20BT.

Cor. is on a steep NE. slope in heavy timber.

BOOK 4812

Remonumentation, T. 16 N., R. 9 E., Arizona

3.

CHAINS

The cor. of secs. 16, 17, 20 and 21, monumented by the remains of an old rotted post in a scattered mound of stone, from which the original bearing trees

A pine, 26 ins. diam., bears N. 42° E., 22 lks. dist., mkd. with part of the scribe mks. visible.

A pine, 26 ins. diam., bears N. 55° W., 37 lks. dist., mkd. with an overgrown blaze.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T16N R9E
S17|S16
S20|S21
 1966

from which

A pine, 7 ins. diam., bears S. 16° W., 35 lks. dist., mkd. S20BT.

Cor. is about 5.00 chs. S. of a track road, bearing E. and W.

The cor. of secs. 19, 20, 29 and 30, monumented by an oak post, 4 ins. square, 4 ft. long, plainly mkd., and set firmly in a mound of stone, from which the original bearing trees

A pine snag, bears N. 48° E., 75 lks. dist., mkd. TXVINRIXEXX.

An oak, 14 ins. diam., bears S. 79° E., 32 lks. dist., mkd. with an overgrown blaze.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, collar of stone to top, brass cap mkd.

T16N R9E
S19|S20
S30|S29
 1966

from which

A pine, 10 ins. diam., bears N. 61¾° E., 32 lks. dist., mkd. T16NR9ES20BT.

A pine, 12 ins. diam., bears N. 55° W., 28 lks. dist., mkd. T16NR9ES19BT.

Cor. is on a SW. slope in heavy timber.

The cor. of secs. 17, 18, 19 and 20, monumented by a small mound of stone, from which the remains of the original bearing trees

BOOK 4812

Remonumentation, T. 16 N., R. 9 E., Arizona

4.

4

CHAINS

A pine stump, bears N. 56° E., 1.64 chs. dist., mkd. with an overgrown blaze.

A pine stump, bears S. 61° E., 1.34 chs. dist., mkd. with an overgrown blaze.

A pine stump, bears S. 23° W., 1.09 chs. dist., mkd. with part of the scribe mks. visible.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone to top, brass cap mkd.

T16N R9E
 S18|S17
 S19|S20
 1966

from which

A pine, 14 ins. diam., bears S. 50° E., 22 lks. dist., mkd. T16NR9ES20BT.

A pine, 12 ins. diam., bears S. 21° W., 21 lks. dist., mkd. T16NR9ES19BT.

Cor. is on a NW. slope in moderate timber.

The cor. of secs. 7, 8, 17 and 18, monumented by part of an old post set in a mound of stone, from which the remains of the original bearing trees

A pine, 22 ins. diam., bears N. 66° E., 40 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears S. 31° E., 8 lks. dist., mkd. with an overgrown blaze.

A pine stump, bears S. 80¾° W., 88 lks. dist., mkd. TXVINRIXESXVIIIBT.

A pine stump, bears N. 27° W., 69 lks. dist.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T16N R9E
 S 7|S 8
 S18|S17
 1966

from which

A pine, 12 ins. diam., bears S. 46° W., 61 lks. dist., mkd. T16NR9ES18BT.

An oak, 14 ins. diam., bears N. 46° W., 50 lks. dist., mkd. T16NR9ES7BT.

Cor. is on a rocky W. slope in moderate timber.

BOOK 4812

Remonumentation, T. 16 N., R. 9 E., Arizona

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented by an old rotted post set in the ground under a mound of stone, from which the original bearing trees

A pine, 22 ins. diam., bears N. $29\frac{1}{2}^{\circ}$ E., 19 lks. dist., mkd. $\frac{1}{4}$ S.

A pine, 20 ins. diam., bears N. $66\frac{3}{4}^{\circ}$ W., 15 lks. dist., mkd. with an overgrown blaze.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T16N R9E

$\frac{1}{4}$
S7|S8
1966

Cor. is on rocky ground in moderate timber.

The cor. of secs. 5, 6, 7 and 8, monumented by parts of a rotted post under a mound of stone, from which the remains of the original bearing trees

A pine stump, bears N. 87° E., 113 lks. dist., mkd. T16NR9ESV.

A pine, 18 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ E., 101 lks. dist., mkd. with an overgrown blaze.

A pine, 40 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ W., 86 lks. dist., mkd. with an overgrown blaze.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, mound of stone to top, brass cap mkd.

T16N R9E

S 6|S 5
S 7|S 8
1966

from which

A pine, 8 ins. diam., bears N. $52\frac{1}{4}^{\circ}$ E., 51 lks. dist., mkd. T16NR9ES5BT.

Cor. is on a SW. slope in heavy timber 1.20 chs. N. of a track road, bearing SE. and NW.

Form 4-680
(June 1963)

BOOK 4812
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
James E. Muth	Engineering Assistant
John L. Higgins	Engineering Assistant
(All U. S. Forest Service Personnel)	

7
BOOK 4812
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 28 day of March, 19 66,
I have remonumented cadastral survey corners in Township 16 North, Range
9 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

November 18, 1966

(Date)

Wallace R. Ott

(Cadastral Surveyor)
(Supervisory Surveying Technician)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in
Township 16 North, Range 9 East, Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician,
having been critically examined and found correct, are hereby approved.

FEB 27 1968

(Date)

R. E. Brown

(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
Township 16 North, Range 9 East, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Engineering)~~