

BOOK 4815

Form 4-679  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 19 North, Range 8 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 28, 19 66, which provided for the surveys  
included under Group Number 446, approved March 29, 1966,  
and assignment instructions dated June 28, 19 66.

Survey commenced July 6, 19 66

Survey completed October 25, 19 66

1A

# BOOK 4815 INDEX DIAGRAM

Township 19 North, Range 8 East,  
2 2 1

<b>6</b>	<b>10 5</b>	<b>4</b>	<b>8 3</b>	<b>2</b>	<b>1</b>
	<b>9</b>	<b>9</b>	<b>7 7</b>	<b>5 5</b>	
<b>7</b>	<b>8</b>	<b>8 9</b>	<b>10</b>	<b>11</b>	<b>3 12</b>
			<b>6 6</b>	<b>4 4</b>	<b>3</b>
<b>18</b>	<b>17</b>	<b>16</b>	<b>15</b>	<b>14</b>	<b>13</b>
<b>19</b>	<b>20</b>	<b>21</b>	<b>22</b>	<b>23</b>	<b>24</b>
<b>30</b>	<b>29</b>	<b>28</b>	<b>27</b>	<b>26</b>	<b>25</b>
<b>31</b>	<b>32</b>	<b>33</b>	<b>34</b>	<b>35</b>	<b>36</b>

CHAINS

The boundaries and subdivisional lines were surveyed in 1879 by J. L. Harris.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

---

Remonumentation, T. 19 N., R. 8 E., Arizona

---

The cor. of secs. 3, 4, 33 and 34, Ts. 19 and 20 N., R. 8 E., monumented by a 1 in. iron pipe and a mound of stone, and verified by record bearing and dist. to the remains of the original bearing trees

A pine stump, bears N. 42° E., 153 lks. dist.

A pine stump, bears S. 18° E., 184 lks. dist.

A pine stump, bears S. 50° W., 103 lks. dist.,  
mkd. T19N R8E S4 BT

A fallen pine, bears N. 78° W., 94 lks. dist.,  
mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone to top, brass cap mkd.

T20N R8E	
S33	S34
S 4	S 3
T19N	
1966	

from which

A pine, 13 ins. diam., bears N. 84° E., 114 lks. dist., mkd. T20N R8E S34 BT

A pine, 12 ins. diam., bears S. 42° E., 110 lks. dist., mkd. T19N R8E S3 BT

Cor. is on a gentle N. slope in moderate timber, 5 lks. E. of a fence bearing N. and S.

---

2

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, Ts. 19 and 20 N., R. 8 E., monumented by a rock mkd. with an X, set in a mound of stone, and verified by record bearing and dist. to the original bearing trees

A pine stump, bears S.  $67^{\circ}$  W., 67 lks. dist.

A pine stump, bears N.  $45^{\circ}$  W., 19 lks. dist., mkd.  $\frac{1}{4}$ S

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R8E  
 $\frac{1}{4}$  S33  
 S 4  
 T19N  
 1966

from which

A pine, 21 ins. diam., bears S.  $47\frac{1}{2}^{\circ}$  W., 120 lks. dist., mkd. T19N R8E  $\frac{1}{4}$  S4 BT

A pine, 8 ins. diam., bears N.  $48\frac{1}{2}^{\circ}$  W., 7 lks. dist., mkd. T20N R8E  $\frac{1}{4}$  S33 BT

Cor. is on a S. slope about 3.50 chs. NW. of a dirt road, bearing NE. and SW.

The cor. of secs. 5, 6, 31 and 32, Ts. 19 and 20 N., R. 8 E., monumented by an oak post,  $3\frac{1}{2}$  ft. long, firmly set in a large mound of stone, mkd. with 5 notches on E., 1 notch on W., XXXI on NW., and TXXNRVIIIIE XXXII on NE., from which the remains of the original bearing trees

A pine stump, bears N.  $25^{\circ}$  E., 52 lks. dist.

A fallen pine, bears S.  $20^{\circ}$  E., 59 lks. dist.

A pine stump, bears N.  $5^{\circ}$  W., 35 lks. dist.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., over an X chiseled on solid rock, mound of stone to top, brass cap mkd.

T20N R8E  
S31 | S32  
 S 6 | S 5  
 T19N  
 1966

from which

A pine, 14 ins. diam., bears N.  $46^{\circ}$  E., 22 lks. dist., mkd. T20N R8E S32 BT

A pine, 10 ins. diam., bears N.  $57^{\circ}$  W., 27 lks. dist., mkd. S31 BT

Cor. is on a steep NW. slope in heavy timber.

BOOK 4815

Remonumentation, T. 19 N., R. 8 E., Arizona

3.

CHAINS

The cor. of secs. 11, 12, 13 and 14, monumented by a malpais stone, 8 x 12 x 18 ins., firmly set in a mound of stone, mkd. with 4 notches on S. and 1 notch on E., from which the original bearing trees

A pine, 24 ins. diam., bears N. 71° E., 124 lks. dist., mkd. with an overgrown blaze.

A pine stump, bears S. 60° E., 532 lks. dist.

A pine stump, bears S. 21° W., 124 lks. dist.

A pine, 30 ins. diam., bears N. 15° W., 104 lks. dist., mkd. TXIXNRVIIIEXI

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T19N R8E  
 $\frac{S11}{S14} | \frac{S12}{S13}$   
 1966

from which

A pine, 18 ins. diam., bears S. 61¾° E., 208 lks. dist., mkd. T19NR8ES13BT

A pine, 16 ins. diam., bears N. 75° W., 125 lks. dist., mkd. T19NR8ES11BT

Deposit the original corner stone in the mound of stones alongside the iron post.

Cor. is on nearly level land in heavy timber.

The ¼ sec. cor. of secs. 11 and 12, monumented by a malpais stone, 8 x 14 x 24 ins., firmly set in the ground, mkd. with ¼ on W., from which the original bearing trees

A pine stump, bears N. 6° E., 100 lks. dist.

A pine snag, 42 ins. diam., bears S. 32° W., 241 lks. dist., mkd. ¼S

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T19N R8E  
 $\frac{1}{4}$   
 $S11 | S12$   
 1966

from which

A pine, 6 ins. diam., bears N. 85° E., 62 lks. dist., mkd. ¼ S12 BT

A pine, 6 ins. diam., bears S. 47° W., 30 lks. dist., mkd. ¼ S11 BT

Raise a mound of stones W. of the iron post.

4

CHAINS

Deposit the original corner stone in the mound of stones.  
Cor. is on a gentle S. slope, about 3.00 chs. N. of Newman Canyon.

The cor. of secs. 10, 11, 14 and 15, monumented by a malpais stone, 10 x 16 x 30 ins., firmly set in a mound of stones, mkd. with 4 notches on S., and 2 notches on E., from which the original bearing trees

A pine, 32 ins. diam., bears S 0°30' E., 274 lks. dist., mkd. TXIXNRVIIIIE XIV

A pine stump, bears S 75° W., 181 lks. dist., mkd. TXIXNRVIIIIE XV

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T19N R8E  
S10|S11  
S15|S14  
1966

Deposit the original corner stone in the mound of stones alongside the iron post.

Cor. is in a nearly level clearing, about 4.00 chs. N. of a fence bearing E. and W.

The ¼ sec. cor. of secs. 11 and 14, monumented by a malpais stone, 8 x 12 x 20 ins., firmly set in a mound of stones, mkd. with ¼ on N., from which the original bearing tree

A pine snag, bears South, 82 lks. dist., mkd. ¼S

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone to top, brass cap mkd.

T19N R8E  
¼ S11  
S14  
1966

from which

A pine, 12 ins. diam., bears N. 6° W., 27 lks. dist., mkd. T19NR8E ¼ S11 BT

Deposit the original corner stone in the mound of stones alongside the iron post.

Cor. is on a NW. slope in heavy timber, 1.00 chs. N. of a fence bearing E. and W.

CHAINS

The cor. of secs. 2, 3, 10 and 11, monumented by a malpais stone, 6 x 10 x 22 ins., firmly set in the ground and in a mound of stones, mkd. with 5 notches on the S. and 2 notches on the E., from which the original bearing trees

A pine stump, bears N. 17° E., 40 lks. dist., mkd. with most of the scribe mks. visible

A pine, 36 ins. diam., bears S. 51½° E., 106 lks. dist., mkd. with an overgrown blaze

A pine, bears S. 66½° E., 101 lks. dist., mkd. with an overgrown blaze

A pine stump, bears N. 42½° W., 191 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T19N R8E  
 $\frac{S}{S10} \frac{S}{S11} \frac{2}{2}$   
 1966

Raise a mound of stones W. of the iron post.

Deposit the original corner stone in the mound of stones.

Cor. is on a gently rolling NE. slope, 1.20 chs. N. of a logging road bearing SE. and NW.

The ¼ sec. cor. of secs. 2 and 11, monumented by a malpais stone, 8 x 10 x 18 ins., firmly set in a mound of stones, mkd. with ¼ on the N., from which the original bearing trees

A pine, 17 ins. diam., bears N. 65° E., 67 lks. dist., mkd. with an overgrown blaze; I remark this tree, T19N R8E ¼ S2 BT

A pine, 22 ins. diam., bears S. 30° W., 68 lks. dist., mkd. ¼S

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, collar of stone to top, brass cap mkd.

T19N R8E  
 $\frac{1}{4} \frac{S}{S11} \frac{2}{2}$   
 1966

Raise a mound of stones N. of the iron post.

Deposit the original corner in the mound of stones.

Cor. is on gently rolling land in moderate timber.

6

CHAINS

The cor. of secs. 9, 10, 15 and 16, monumented by an old mound of stones, and verified by record bearing and dist. to the remains of the original bearing trees

A pine stump, bears N.  $61\frac{1}{2}^\circ$  E., 81 lks. dist.

A stump hole, left by a fallen pine, bears S.  $43^\circ$  W., 73 lks. dist., tree mkd. with part of scribe mks. visible

A pine stump, bears N.  $36^\circ$  W., 53 lks. dist.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, collar of stone to top, brass cap mkd.

T19N R8E  
 $\frac{S\ 9}{S16} | \frac{S10}{S15}$   
 1966

from which

A pine, 8 ins. diam., bears S.  $16^\circ$  W., 15 lks. dist., mkd. S16 BT

A pine, 12 ins. diam., bears N.  $1\frac{1}{2}^\circ$  W., 46 lks. dist., mkd. T19N R8E S9 BT

Cor. is on a S. slope in heavy timber, 2.50 chs. N. of a logging road bearing E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, monumented by a malpais stone, 14 x 16 x 20 ins., mkd. with  $\frac{1}{4}$  on N. and X on S., with a large mound of stones N., from which the original bearing trees

A pine stump, bears S.  $25^\circ$  E., 235 lks. dist., mkd.  $\frac{1}{4}$ S

A pine, 37 ins. diam., bears N.  $27\frac{1}{2}^\circ$  W., 194 lks. dist., mkd.  $\frac{1}{4}$ S

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T19N R8E  
 $\frac{1}{4} \frac{S10}{S15}$   
 1966

from which

A pine, 28 ins. diam., bears S.  $49\frac{3}{4}^\circ$  E., 84 lks. dist., mkd. T19N R8E  $\frac{1}{4}$  S15 BT

Deposit the original corner stone in the mound of stones alongside the iron post.

Cor. is on a W. slope in heavy timber.



CHAINS

The cor. of secs. 3, 4, 9 and 10 is established by record bearing and dist. from the original bearing trees

A pine, 30 ins. diam., bears N. 38° E., 255 lks. dist., mkd. TXIXNRVIIIIE III

A double pine, 54 ins. diam., bears S. 80° E., 131 lks. dist., mkd. with an overgrown blaze

A pine stump, bears S. 54½° W., 46 lks. dist.

A pine, 36 ins. diam., bears N. 79½° W., 72 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T19N R8E  
 $\frac{S}{S} \frac{4}{9} | \frac{S}{S10} \frac{3}{10}$   
 1966

from which

A pine, 13 ins. diam., bears N. 21½° E., 82 lks. dist., mkd. T19N R8E S10 BT

A pine, 16 ins. diam., bears S. 7½° E., 83 lks. dist., mkd. T19N R8E S10 BT

Cor. is in the bottom of a shallow grassy draw, draining irregularly E.

The ¼ sec. cor. of secs. 3 and 10, monumented by a malpais stone, 5 x 10 x 22 ins., firmly set in the ground and in a mound of stone, mkd. ¼ on the N., from which the original bearing trees

A pine, 22 ins. diam., bears S. 3° E., 132 lks. dist., mkd. ¼S

A pine, 24 ins. diam., bears N. 41½° W., 93 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T19N R8E  
 $\frac{1}{4} \frac{S}{S10} \frac{3}{10}$   
 1966

Raise a mound of stones N. of the iron post.

Deposit the original corner stone in the mound of stones.

Cor. is on a gentle NE. slope in moderate timber.

BOOK 4815

8

Remonumentation, T. 19 N., R. 8 E., Arizona

8.

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, monumented by a rotted wooden post in a mound of stones, from which the remains of the original bearing tree

A pine stump, bears West, 14 lks. dist.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T19N R8E

$\frac{1}{4}$   
S4|S3  
1966

from which

A pine, 12 ins. diam., bears N.  $81\frac{1}{2}^{\circ}$  E., 19 lks. dist., mkd. T19N R8E  $\frac{1}{4}$  S3 BT

An oak, 8 ins. diam., bears S.  $47^{\circ}$  W., 36 lks. dist., mkd. T19N R8E  $\frac{1}{4}$  S4 BT

Raise a mound of stones W. of the iron post.

Cor. is on a rocky N. slope in heavy timber 80 lks. E. of a fence bearing N. and S.

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, monumented by a mound of stones, and verified by record bearing and dist. from the original bearing trees

A pine stump, bears S.  $7^{\circ}$  E., 101 lks. dist.

A pine, 22 ins. diam., bears N.  $10^{\circ}$  W., 22 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, mound of stone to top, brass cap mkd.

T19N R8E

$\frac{1}{4}$   
S8|S9  
1966

from which

A pine, 5 ins. diam., bears N.  $57^{\circ}$  E., 29 lks. dist., mkd.  $\frac{1}{4}$  S9 BT

A pine, 32 ins. diam., bears N.  $33^{\circ}$  W., 36 lks. dist., mkd. T19N R8E  $\frac{1}{4}$  S8 BT

## CHAINS

The cor. of secs. 4, 5, 8 and 9 is in the center of a scattered mound of stones, verified by record course and dist., from the remains of the original bearing trees

A pine stump, bears N. 78° E., 64 lks. dist.

A pine stump, bears S. 44° E., 71 lks. dist.

A pine stump, bears S. 89° W., 122 lks. dist.

A pine stump, bears N. 45° W., 208 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T19N R8E	
S 5	S 4
S 8	S 9
1966	

from which

A pine, 8 ins. diam., bears S. 57° E., 23 lks. dist., mkd. S9 BT

A pine, 15 ins. diam., bears N. 4° W., 13 lks. dist., mkd. T19N R8E S5 BT

Cor. is on a W. slope in heavy timber about 5.00 chs. W. of a wash draining N. 30° W.

The cor. of secs. 5, 6, 7 and 8, monumented by an old mound of stones, verified by record bearing and dist. from the original bearing trees

A pine snag, bears S. 54° W., 103 lks. dist., mkd. TXIXNRVIIIIE VII

A pine, 22 ins. diam., bears N. 28° W., 68 lks. dist., mkd. TXIXNRVIIIIE VI

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T19N R8E	
S 6	S 5
S 7	S 8
1966	

from which

A pine, 10 ins. diam., bears N. 34° E., 45 lks. dist., mkd. T19N R8E S5 BT

A pine, 11 ins. diam., bears S. 16½° E., 32 lks. dist., mkd. T19N R8E S8 BT

Raise a mound of stones W. of the iron post.

Cor. is on a NW. slope in heavy timber in a fence bearing N. and S., and about 2.50 chs. E. of a wash draining N.

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, monumented by an old wooden post, firmly set in a mound of stones, mkd.  $\frac{1}{4}$ S, from which the original bearing trees

A pine, 26 ins. diam., bears N.  $53^{\circ}$  E., 100 lks. dist., mkd. with an overgrown blaze

A pine, 26 ins. diam., bears S.  $38^{\circ}$  W., 80 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., over an X chiseled in solid rock, mound of stone to top, brass cap mkd.

T19N R8E

$\frac{1}{4}$   
S6 | S5  
1966

from which

A pine, 16 ins. diam., bears N.  $67\frac{1}{2}^{\circ}$  E., 40 lks. dist., mkd.  $\frac{1}{4}$  S5 BT

A pine, 13 ins. diam., bears N.  $86^{\circ}$  W., 21 lks. dist., mkd. T19N R8E  $\frac{1}{4}$  S6 BT

Cor. is on a rocky SE. slope in thick timber.



BOOK 4815  
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,  
in pursuance of special instructions bearing date of the 28th day of March, 19 66,  
I have remonumented cadastral survey corners in Township 19 North, Range  
8 East,

of the Gila and Salt River Meridian, in the State of Arizona, which  
are represented in the foregoing field notes as having been executed by me and under my direction;  
and that said survey has been made in strict conformity with said special instructions, the Manual  
of Instructions for the Survey of the Public Lands of the United States, and in specific manner  
described in the foregoing field notes.

November 18, 1966  
(Date)

*Wallace R. Ott*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the remonumentation of cadastral survey corners in  
Township 19 North, Range 8 East, of the Gila and Salt River Meridian,  
Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician,  
having been critically examined and found correct, are hereby approved.

FEB 27 1968  
(Date)

*R. E. Brown*  
(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Engineering)~~