

BOOK 4823

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

RETRACEMENT and DEPENDENT RESURVEY

of a

Portion of the Boundaries and Subdivision

and

SURVEY

of a

Portion of the Subdivision

of

Section 26

Township 10 North, Range 6 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Paul G. Bauer, Cadastral Surveyor

Under special instructions dated November 4, 19 64, which provided for the surveys
included under Group Number 420, approved November 4, 1964,
and assignment instructions dated November 5, 19 64, and July 5, 19 67.

Survey commenced November 9, 19 64

Survey completed July 7, 19 67

BOOK 4823

INDEX DIAGRAM

Township 10 North, Range 6 West,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

<u>Section 26:</u>	<u>Page</u>
Retracement & Resurvey - N $\frac{1}{2}$ W. Bdy. -----	1
Retracement - W $\frac{1}{2}$ N. Bdy. -----	2
Retracement - N-S Center Line -----	3
Resurvey portion of E-W Center Line -----	3
Subdivision - NW $\frac{1}{4}$ -----	4

Township 10 North, Range 6 West,
Gila and Salt River Meridian, Arizona

CHAINS

Section 26 was surveyed in 1904 by J. F. Hesse and re-surveyed and partially subdivided in 1952 by Ty White.

The following notes are those of a retracement and dependent resurvey of a portion of the boundaries and subdivision and the survey of a portion of the subdivision of Section 26, Township 10 North, Range 6 West, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated November 4, 1964, and Instructions in memorandum from Chief, Division of Engineering, dated January 4, 1966.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes.

The geographic position of the southeast corner of Section 26 is: Latitude 34°10'33" North, and Longitude 112°49'50" West, as shown on the plat accepted January 23, 1953.

The mean magnetic declination was found to be 14°30' East.

Retracement and Dependent Resurvey of a Portion
of the Boundaries and Subdivision of Section 26,
T. 10 N., R. 6 W., Arizona

Reestablishment of the Survey
Executed by Ty White in 1952

From the ¼ sec. cor. of secs. 26 and 27, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1952 resurvey.

N. 0°01' W., bet. secs. 26 and 27.


Desc. over NE. slope.

7.35 Graded road, bears SE. to Congress Junction and NW., curving to N. to Congress Mine.

7.79 Intersect line 3-4, Mineral Survey No. 3156, Gold Dollar No. 3 lode.

Point for the closing cor. of secs. 26 and 27.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.



from which

Cor. No. 4, M.S. 3156, Gold Dollar No. 3 lode, bears S. 47°02' E., 9.20 chs. dist., monumented by a granite stone, 10 x 10 x 8 ins., firmly set, mkd. 4G D 3 3156, with + on top.

Cor. No. 3, M.S. 3156, Gold Dollar No. 3 lode, bears N. 47°02' W., 13.467 chs. dist., monumented by a granite stone, 10 x 8 x 6 ins., above ground, firmly set, plainly mkd. 3 on SE. face.

GD3
3156

BOOK 4823

Retracement of the West Half of the North Boundary
Section 26, T. 10 N., R. 6 W., Arizona

CHAINS	
	Raise a mound of stone N. of the closing cor.
10.35	Small wash, drains SE.
13.09	Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.
20.045	Point for the N 1/16 sec. cor. of secs. 26 and 27. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	T10N R6W N 1/16 S27 S26 1964
	Raise a mound of stone West of the iron post.
24.10	Shallow wash and barrow pit; drains S. 20° W.
26.90	Same graded road, bears S. 20° W. and N. 20° E.
30.40	Shallow wash and barrow pit; drains S. 20° W.
40.09	The cor. of secs. 22, 23, 26 and 27, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1952 resurvey.
Retracement of the West Half of the North Boundary Section 26, T. 10 N., R. 6 W., Arizona	
	From the ¼ sec. cor. of secs. 23 and 26, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1952 resurvey.
	S. 89°55' W., bet. secs. 23 and 26.
	Over gently rolling land.
2.60	Wash, 10 lks. wide, 2 ft. deep, drains S. 15° W.
9.30	Wash, 30 lks. wide, 1 ft. deep, drains S. 10° E.
12.30	Track road, bears N. 15° W. and S. 20° E.
18.00	Wash, 40 lks. wide, 1 ft. deep, drains S. 30° W.
19.97	Point for the W 1/16 sec. cor. of secs. 23 and 26, at proportionate dist.
	This cor. was not monumented.
20.45	Track road, bears S. and N. 15° W.
22.30	Small wash, drains S.
30.80	Wash, 50 lks. wide, 1 ft. deep, drains S. 30° W.
31.80	Wash, 10 lks. wide, 1 ft. deep, drains S.
38.10	Graded road, bears N. 15° E. and S. 15° W.
39.60	Small wash, drains S. 15° W.
39.94	The cor. of secs. 22, 23, 26 and 27.

Retracement of the N-S Center Line
Section 26, T. 10 N., R. 6 W., Arizona

CHAINS	
Retracement of the N-S Center Line Section 26, T. 10 N., R. 6 W., Arizona	
	From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1952 resurvey.
	N. $0^{\circ}06'$ W., on the N-S center line of sec. 26.
	Over rolling land; asc. SW. slope.
1.60	Spur, slopes S. 15° E.
6.00	Small draw, drains S. 30° E.
9.50	Track road, bears S. 15° E. and N. 15° W.
17.60	Small draw, near head, drains E. about 50 lks., thence NE.
18.60	Desc. over NE. slope.
20.056	The C-S $1/16$ sec. cor. of sec. 26, monumented by a $2\frac{1}{2}$ in. iron post, set, mkd. and witnessed as described in the official record of the 1952 survey.
25.90	Wash, 30 lks. wide, 2 ft. deep, drains SE.
40.112	The center $\frac{1}{4}$ sec. cor. of sec. 26, monumented by a 2 in. iron post, set, mkd. and witnessed as described in the official record of the 1952 survey.
57.00	Wash, 20 lks. wide, 1 ft. deep, drains S. 20° E., from N. 20° E.
60.132.	Point for the C-N $1/16$ sec. cor. of sec. 26. This cor. was not monumented.
63.80	Same wash, drains SE. on curve to SW.
80.152	The $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
Resurvey of a portion of the E-W Center Line Section 26, T. 10 N., R. 6 W., Arizona	
	From the C-W $1/16$ sec. cor. of sec. 26, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1952 survey.
	S. $89^{\circ}51'$ W., on E-W center line.
	Over rolling land.
3.20	Desc. over SW. slope.
4.60	Small wash, drains S.; thence, over bottom of draw.
6.80	Wash, 10 lks. wide, 1 ft. deep, drains S. about 2.00 chs. to junction with wash draining from N. 70° W.
10.002	The C-W-W $1/64$ sec. cor. of sec. 26, monumented by a 2 x 2 in. wooden post, firmly set, 12 ins. above ground, mkd. $1/64$.

Resurvey of a portion of the E-W Center Line
Section 26, T. 10 N., R. 6 W., Arizona

CHAINS	
11.80	Wash, 60 lks. wide, 3 ft. deep, drains S. 70° E.; asc. over NE. slope.
14.10	Top of ascent; thence over rolling land.
14.574	The closing cor., at point of intersection with line 1-4, M.S. 3156, Gold Dollar No. 3 lode, monumented by a 2 x 2 in. wooden post, firmly set, 12 ins. above ground.
	Nail a Bathey aluminum cap to top of post, mkd.
	from which
	Cor. No. 1, M.S. 3156, Gold Dollar No. 3 lode, bears S. 40°47' W., 7.11 chs. dist., monumented by a granite stone, 6 x 3 x 1 ft., above ground, mkd. 1G-D 3-3156 on NE., with a + on top.
	Cor. No. 4, M.S. 3156, Gold Dollar No. 3 lode, bears N. 40°47' E., 1.978 chs. dist., previously described.
15.60	Bladed road, bears N. 29° W. and S. 29° E.
16.20	Graded road, bears N. 29° W. to Congress Mine and S. 29° E. to Congress Junction; asc. over NE. slope.
17.40	Old railroad bed, bears N. 29° W. and S. 29° E.
20.004	The ½ sec. cor. of secs. 26 and 27.
<hr/> Subdivision of the NW¼, Sec. 26, T. 10 N., R. 6 W., Arizona <hr/>	
	From the C-W 1/16 sec. cor. of sec. 26.
	N. 0°03'30" W., on the N-S center line of the NW¼ of sec. 26.
	Over nearly level land.
12.70	Track road, bears irregularly N. and S. 10° W.
20.028	Point for the NW 1/16 sec. cor. of sec. 26 at intersection with E-W center line of the NW¼.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	Raise a mound of stone west of the iron post.
23.40	Small wash, drains S. 15° E.
27.50	Same track road, bears N. 15° W. and S. 15° E.
40.062	The point for the W 1/16 sec. cor. of secs. 23 and 26.

Subdivision of the NW $\frac{1}{4}$, Section 26,
T. 10 N., R. 6 W., Arizona

CHAINS	
	<p>From the point for the C-N 1/16 sec. cor. of sec. 26.</p> <p>S. 89°53' W., on the E-W center line of the NW$\frac{1}{4}$ of sec. 26.</p> <p>Over gently rolling land.</p>
2.90	Small wash, drains S.
5.50	Track road, bears N. and S.
7.00	Small draw, near head, drains S. 30° W.
9.70	Draw, drains S. 15° E.
14.30	Small wash in bottom of draw, drains S. 15° E. about 2.00 chs.; thence East.
19.984	The NW 1/16 sec. cor. of sec. 26.
24.30	Wash, 10 lks. wide, 1 ft. deep, drains S.
30.40	Wash, 10 lks. wide, 1 ft. deep, drains S.
31.80	Wash, 20 lks. wide, 1 ft. deep, drains SE.
39.969	The N 1/16 sec. cor. of secs. 26 and 27.
<p>GENERAL DESCRIPTION</p> <p>The land in section 26, T. 10 N., R. 6 W., Arizona, varies from nearly level in the SW$\frac{1}{4}$SW$\frac{1}{4}$ to rolling on the remainder. The primary undergrowth is creosote brush, catclaw, cacti and palo verde, with sparse grass along the draws and washes.</p> <p>The City of Congress extends into the SW$\frac{1}{4}$ of the section, with streets, homes, utilities and other improvements in. An oiled road enters section 26 near the W 1/16 sec. cor. of sections 26 and 35, extending northwesterly, with the oil ending near M.S. 3156; a graded road continues northerly to the old Congress Mine.</p>	

BOOK 4828

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert F. Johnson	Surveying Technician
Daniel R. Bauer	Surveying Aid
Louis D. Gilbert	Surveying Aid
Lyman W. Polacca	Surveying Aid
David L. Sakiestewa	Surveying Aid

BOOK 4823

CERTIFICATE OF SURVEY

We,
 /s/ Boyd S. Owens and Paul G. Bauer, HEREBY CERTIFY upon honor that,
 in pursuance of special instructions bearing date of the 4th day of November, 1964, and
 we instructions bearing date of the 4th day of January, 1966,
 /s/ have retraced and dependently resurveyed a portion of the boundaries and
 subdivision and surveyed a portion of the subdivision of Section 26, Town-
 ship 10 North, Range 6 West,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by ~~me~~ ^{us} and under ~~my~~ ^{our} direction;
 and that said survey has been made in strict conformity with said special instructions, the Manual
 of Instructions for the Survey of the Public Lands of the United States, and in specific manner
 described in the foregoing field notes.

April 12, 1968
 (Date)

Boyd S. Owens
 (Cadastral Surveyor)

April 12, 1968
 (Date)

Paul G. Bauer
 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAY 17 1968

BUREAU OF LAND MANAGEMENT,
 Washington, D. C.

The foregoing field notes of the retracement and resurvey of a portion of the
 boundaries and subdivision, and survey of a portion of the subdivision,
 of Section 26, Township 10 North, Range 6 West, of the Gila and Salt
 River Meridian in the State of Arizona,

executed by Boyd S. Owens and Paul G. Bauer, Cadastral Surveyors,
 having been critically examined and found correct, are hereby approved.

SEP 27 1968
 (Date)

R.E. Brown
 (Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.~~

~~_____
 (Date)~~

~~_____
 (Chief, Division of Engineering)~~