

BOOK 4824

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of a

Portion of the

SOUTH BOUNDARY

Township 12½ North, Range 2 West

SURVEY

of the

NORTH BOUNDARY

and

SUBDIVISIONAL LINES

of

Township 12 North, Range 2 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Leonard W. Murphy, Cadastral Surveyor

Under special instructions dated November 18, 19 58, which provided for the surveys included under Group Number 331, approved November 26, 1958, and assignment instructions dated July 5, 19 62.

Survey commenced July 18, 19 62

Survey completed November 27, 19 62

BOOK 4824

INDEX DIAGRAM

Township 12 North, Range 2 West
 1 2 4 5 6 8

6 60 60	5 48 59	4 39 47	3 29 38	2 20 28	1 19
7 58 58	8 47 57	9 37 46	10 27 37	11 17 26	12 16
18 56 55	17 45 54	16 36 44	15 25 35	14 15 25	13 14
19 53 53	20 43 52	21 34 43	22 24 34	23 13 23	24 12
30 51 51	29 42 50	28 33 41	27 23 32	26 11 22	25 11
31 49	32 40	33 31	34 21	35 10	36

CHAINS

The west boundary, and a portion of the south boundary of Township 12½ North, Range 2 West, was surveyed by J. P. Davis in 1919. The south boundary was surveyed by N. E. Shearer in 1938. The east boundary was surveyed concurrently under this same Group and is contained in the field notes of the survey of Township 12 North, Range 1 West.

The following field notes are those of the dependent resurvey of a portion of the south boundary, Township 12½ North, Range 2 West, and a survey of the north boundary and subdivisional lines of Township 12 North, Range 2 West, Gila and Salt River Meridian, Arizona.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated November 18, 1958.

The geographic position of the southeast corner of the township is: Latitude 34°19'54" North and Longitude 112°24'55" West, as determined by computation from U.S.G.S. triangulation station MT. UNION.

The mean magnetic declination was found to be 15° East.

Dependent Resurvey, Portion of S. Bdy.,
T. 12½ N., R. 2 W., Arizona

Beginning at the standard cor. of T. 12½ N., Rs. 2 and 3 W., monumented by a rock, 16x12x10 ins., loosely set, properly mkd., and witnessed by a mound of stone N. of the corner.

At the corner point

Set the iron post 24 ins. in the ground, cap mkd.

SC
T12½ N
R3W | R2W
S36 | S31
S 1
T12N
1962

Raise a mound of stone, 4 ft. base, 3 ft. high, N. of the cor.

Set the orig. cor. stone alongside the iron post.

East, bet. secs. 1 and 31.

Over rolling land, through dense undergrowth and sparse timber.

Asc. rocky NW. slope.

4.26

The closing cor. of T. 12 N., Rs. 2 and 3 W., which is an "X" chiseled in a large granite ledge, 6 ft. high, properly mkd. and witnessed by a mound of stone S. of the cor. There are no bearing trees.

At the corner point

BOOK 4824

2

N. Bdy., T. 12 N., R. 2 W., Arizona

2.

CHAINS

Set a brass tablet, $3\frac{1}{2}$ ins. diam., $3\frac{1}{2}$ ins. stem, in a drilled hole, surrounded by concrete, with top mkd.

T12 $\frac{1}{2}$ N
 S 31
 C C
 S 1 S 6
 R3W R2W
 T12N
 1962

Survey, N. Bdy., T. 12 N., R. 2 W., Arizona

From the remonumented closing cor. of T. 12 N., Rs. 2 and 3 W.

East, bet. secs. 6 and 31.

Over mountainous land, through dense undergrowth.

3.10 Wash, 15 lks. wide, 2 ft. deep, drains W.

6.00 Wash, 10 lks. wide, 2 ft. deep, drains SW. for 2 chains, thence W.

20.27 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.

Set the iron post 24 ins. in the ground, cap mkd.

T12 $\frac{1}{2}$ N R2W
 $\frac{1}{4}$ S 31
 S 6
 T12N
 1962

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

29.00 Low ridge, bears SE. and NW.

38.70 Small draw, course NW.; begin asc. steep W. slope of ridge.

45.40 Ridge, bears N. and S.; desc. E. slope.

60.27 Point for the cor. of secs. 5, 6, 31 and 32.

Set the iron post 24 ins. in the ground, cap mkd.

T12 $\frac{1}{2}$ N R2W
 S31 S32
 S 6 S 5
 T12N
 1962

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

Cor. falls on N. slope.

Land, rolling.

Soil, rocky.

Timber, scattered pinon pine.

Undergrowth, oak brush, laurel, manzanita and mahogany.

East, bet. secs. 5 and 32.

Over rolling and mountainous land, through dense undergrowth.

BOOK 4824

N. Bdy., T. 12 N., R. 2 W., Arizona

3.

CHAINS	
4.05	Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. W. slope of hill.
7.20	Spur, projects N.; desc. E. slope.
12.60	Ravine, course N.; asc. W. slope.
19.00	Spur, slopes N.; continue asc. along N. slope.
27.70	Spur, slopes N.; desc. along N. slope.
29.32	Intersect Line 2-3 Rail Road lode M.S. 1646 at a point from which Cor. No. 3 bears N. 74°45' E., 1.52 chs. dist.
30.88	Intersect line 3-4 Rail Road lode M.S. 1646 at a point from which Cor. No. 3 bears N. 14°28' W., 0.41 chs. distant.
37.00	Small ravine, course NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32. Set the iron post 24 ins. in the ground, cap mkd.
	$T12\frac{1}{2}N R2W$ $\frac{1}{4} \frac{S32}{S 5}$ $T12N$ 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.
40.30	Ravine, 15 lks. wide, course NW.; asc. steep W. slope.
47.10	Point selected for witness point on the line bet. secs. 5 and 32. Set the iron post 24 ins. in the ground, cap mkd.
	$T12\frac{1}{2}N R2W$ $WP \frac{S32}{S 5}$ $T12N$ 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the iron post.
47.25	Road, bladed, leads to Big Chief and Jersey Lily mines, bears generally N. and S.; cont. asc. W. slope.
53.35	Spur, slopes NW.; begin gentle desc. along N. slope.
69.50	Road, bladed, leads to Buzzard Mine, bears NNW. and SE.; asc. steep W. slope.
80.00	Point for the cor. of secs. 4, 5, 32 and 33. Set the iron post 24 ins. in the ground, with cap mkd.
	$T12\frac{1}{2}N R2W$ $\frac{S32 S33}{S 5 S 4}$ $T12N$ 1962

BOOK 4824

N. Bdy., T. 12 N., R. 2 W., Arizona

4

4.

CHAINS	
	<p>from which</p> <p>A fir, 14 ins. diam., bears S. 18°45' E., 104 lks. dist., mkd. T12N R2W S4 B T</p> <p>A fir, 10 ins. diam., bears N. 63° W., 64 lks. dist., mkd. T12½N R2W S32 B T</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.</p> <p>Land, mountainous. Soil, rocky. Timber, patches of fir and pine in E. 1/2 mile. Undergrowth, manzanita, oakbrush, catclaw.</p>
	<p>East, bet. secs. 4 and 33.</p> <p>Over mountainous land, through scattered timber and dense undergrowth.</p>
.80	Spur, slopes N.; cont. asc. W. slope.
11.52	Intersect Line 3-4 Nugget lode M.S. 2942 at a point from which Cor. No. 3 bears S. 78°45' W., 6.78 chs. dist.
13.93	Intersect Line 4-1 Nugget lode M.S. 2942 at a point from which Cor. No. 4 bears N. 18°02' W., 0.47 chs. dist.
21.10	Ridge, bears N. and S.; begin desc. E. slope.
23.30	Road, bladed, leads to Mt. Tritle, bears irregularly N. and S.
30.10	Wash, 15 lks. wide, 2 ft. deep, drains SE.; desc.
40.00	Point for the ¼ sec. cor. of secs. 4 and 33.
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T12½N R2W ¼ $\frac{S33}{S4}$ T12N 1962</p>
	<p>from which</p> <p>Cor. No. 1 Dosoris lode M.S. 300 bears S. 82°42' E., 19.58 chs. dist.</p> <p>U.S.M.M. No. 2, Hassayampa Mining District, bears S. 19°34' E., 26.70 chs. dist., monumented by a slate boulder, mkd. U.S.M.M. H D No. 2</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor.</p> <p>Cor. falls on SE. slope.</p>
47.50	Ravine, course S.; begin asc. steep W. slope.
80.00	Point for the cor. of secs. 3, 4, 33 and 34.

CHAINS	
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} T12\frac{1}{2}N R2W \\ \hline S33 S34 \\ S 4 S 3 \\ \hline T12N \\ 1962 \end{array}$ </p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.</p> <p>Cor. located on NW. slope; no bearing trees available.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered pine and fir. Undergrowth, oakbrush, manzanita and buckbrush.</p> <hr/> <p>East, bet. secs. 3 and 34.</p> <p>Over mountainous land, through dense undergrowth, sparse timber.</p> <p>Continue asc. steep NW. slope.</p> <p>7.90 Ridge, bears NE. and SW.; desc. along S. slope.</p> <p>19.00 Spur, projects S.; continue desc. SE. slope.</p> <p>30.00 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. SW. slope.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 3 and 34.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} T12\frac{1}{2}N R2W \\ \frac{1}{4} \frac{S34}{S3} \\ \hline T12N \\ 1962 \end{array}$ </p> <p>from which</p> <p style="padding-left: 40px;">Cor. No. 4 Don Pedro lode M.S. 4205 bears N. 34°37' E., 5.17 chs. dist.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. falls on crest of spur, slopes SSW.</p> <p>Asc. SW. slope.</p> <p>45.17 Intersect Line 3-4 Don Pedro lode M.S. 4205 at a point from which Cor. No. 3 bears S. 27°40'30" E., 4.29 chs. distant.</p> <p>48.00 SW. slope changes to WSW. slope.</p> <p>51.00 Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. WSW. slope.</p> <p>52.87 Intersect Line 2-3 Don Pedro lode M.S. 4205 at a point from which Cor. No. 3 bears S. 56°22'30" W., 6.86 chs. distant.</p> <p>58.00 Crest of spur, slopes SW.; desc. SE. slope.</p>

BOOK 4824

6

N. Bdy., T. 12 N., R. 2 W., Arizona

6.

CHAINS		
61.00	Wash, 15 lks. wide, 3 ft. deep, drains SE.; asc. SW. slope.	
65.00	Crest of spur, slopes SE.; desc. SE. slope.	
77.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. W. slope.	
80.00	Point for the cor. of secs. 2, 3, 34 and 35.	
	Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	<p style="text-align: center;">T12½N R2W <u>S34 S35</u> S 3 S 2 T12N 1962</p>	
	from which	
	A pine, 8 ins. diam., bears N. 22° E., 60 lks. dist., mkd. T12½N R2W S 35 BT	
	A pine, 10 ins. diam., bears S. 37½° E., 30 lks. dist., mkd. T12N R2W S 2 BT	
	Cor. No. 2 Little Betty lode M.S. 2420, bears S. 68°21'30" E., 11.15 chs. dist.	
	Cor. No. 4 Davis Number 3 North lode M.S. 1690, identical with Cor. No. 4 New Era No. 2 lode M.S. 1691, bears S. 46°12' W., 5.05 chs. dist.	
	Cor. falls on W. slope.	
	Land, mountainous. Soil, rocky. Timber, patches of pine and fir. Undergrowth, oakbrush, manzanita, laurel.	
	East, bet. secs. 2 and 35.	
	Over mountainous land, through dense timber and undergrowth.	
	Asc. steep W. slope.	
0.70	Intersect Line 3-4 Davis Number 3 North lode M.S. 1690 at a point from which Cor. No. 3 bears N. 51°12' E., 17.17 chs. dist.	
2.50	Road, bladed, leads to Mt. Tritle, bears irregularly NW. and SE.	
2.60	Point selected for the witness point on the line bet. secs. 2 and 35.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	<p style="text-align: center;">T12½N R2W WP <u>S 35</u> S 2 T12N 1962</p>	

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the iron post.
15.20	Intersect Line 1-2 Davis Number 3 North lode M.S. 1690 at a point from which Cor. No. 1 bears S. 51°12' W., 16.80 chs. dist.
15.70	Ridge top, bears irregularly E. and W.; thence along N. slope.
16.65	Fence, barbed wire, bears S. 45° E. and N. 45° W.
17.51	Intersect Line 2-3 Little Betty lode M.S. 2420 at a point from which Cor. No. 2 bears S. 60°09' W., 8.26 chs. dist.
18.00	Desc. N. slope.
32.00	Crest of spur, projects NE.; desc. E. slope.
33.02	Intersect Line 3-4 Kentucky Judge lode M.S. 2420 at a point from which Cor. No. 4 bears S. 22°20' E., 7.13 chs. dist.
34.50	E. slope changes to NE. slope.
40.00	Point for the ¼ sec. cor. of secs. 2 and 35. Set the iron post 24 ins. in the ground, cap mkd. <div style="text-align: center;"> $T12\frac{1}{2}N R2W$ $\frac{1}{4} \frac{S35}{S 2}$ $T12N$ 1962 </div> from which A ponderosa pine 11 ins. diam. bears N. 7°15' E., 33 lks. dist., mkd. ¼ S35 B T A ponderosa pine 8 ins. diam. bears S. 13°30' W., 18 lks. dist., mkd. ¼ S2 B T Cor. located on NE. slope.
45.50	Intersect Line 3-4 Skylight lode M.S. 1289 at a point from which Cor. No. 3 bears S. 45° W., 2.03 chs. dist.
50.00	Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. N. slope.
55.00	Crest of small spur, slopes NE.; desc. ENE. slope.
59.00	Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. S. slope.
62.00	Spur, slopes NE.; desc. SE. slope.
70.00	Senator Highway, graded, bears approximately NE. and SW.; desc. SE. slope.
80.00	Point for the cor. of secs. 1, 2, 35 and 36. Set the iron post 24 ins. in the ground, cap mkd.

BOOK 4824

N. Bdy., T. 12 N., R. 2 W., Arizona

8

8.

CHAINS		
	<p style="text-align: center;">T12½N R2W S35 S36 S 2 S 1 T12N 1962</p> <p>from which</p> <p>A spruce, 9 ins. diam., bears S. 59°30' W., 28 lks. dist., mkd. T12N R2W S 2 BT.</p> <p>A silver spruce, 12 ins. diam., bears S. 12°30' W., 42 lks. dist., mkd. S 2 B T.</p> <p>Cor. No. 3 Snoozer lode M.S. 964 bears N. 2°47' W., 8.15 chs. dist.</p> <p>Cor. No. 4 Cashier lode M.S. 1459 bears N. 73°57' E., 9.01 chs. dist.</p> <p>Cor. falls on NW. slope.</p> <p>Land, mountainous. Soil, rocky. Timber, spruce, cedar and fir. Undergrowth, oakbrush.</p> <hr/> <p>East, bet. secs. 1 and 36.</p> <p>Over mountainous land, through dense timber, sparse undergrowth.</p> <p>Asc. NW. slope.</p>	
3.27	Intersect Line 5-6 Snoozer lode M.S. 964 at a point from which Cor. No. 5 bears N. 51°40' E., 4.93 chs. dist.	
6.15	Intersect Line 4-1 Cashier lode M.S. 1459 at a point from which Cor. No. 4 bears N. 45°16' E., 3.53 chs. dist.	
6.40	Begin desc. N. slope.	
7.30	Wash, 15 lks. wide, 3 ft. deep, drains NW.; asc. NW. slope.	
15.00	Small spur, slopes NE.; desc. along N. slope.	
22.66	Intersect Line 3-4 Cash lode M.S. 410 at a point from which Cor. No. 4 bears S. 60°20' W., 10.96 chs. dist.	
23.00	Slope changes from N. to E.	
29.87	Intersect Line 4-1 Forlorn Hope lode M.S. 4298 at a point from which Cor. No. 1 bears N. 51°56' E., 1.52 chs. dist.	
30.00	Wash, 10 lks. wide, 1 ft. deep, drains NE.; asc. SE. slope.	
35.00	SE. slope changes to SW. slope.	
38.00	Road, bladed, bears N. 15° W. and S. 15° E.	
40.00	Point for the ¼ sec. cor. of secs. 1 and 36.	

CHAINS

Set the iron post 24 ins. in the ground, cap mkd.

T12½N R2W

¼ $\frac{S36}{S1}$

T12N

1962

from which

A pine 10 ins. diam. bears S. 62°30' E., 57 lks. dist., mkd. T12N R2W ¼ S1 B T

A pine 16 ins. diam. bears N. 64°45' W., 22 lks. dist., mkd. T12½N R2W ¼ S36 B T

Cor. No. 2 Forlorn Hope lode M.S. 4298 bears S. 6°56' W., 3.36 chs. dist., monumented by a stone 7x9x15 ins., mkd. FH2 4298

Cor. No. 3 Dakota lode M.S. 1955 bears N. 89°45' W., 7.22 chs. dist., monumented by a stone 6x8x12 ins., mkd. C2 D3 1955 This area being subdivided under the title of " Mt. Pine Acres."

41.40

Road, graded, bears S. 20° E. and N. 20° W.; asc. NW. slope.

49.20

Spur, slopes N. 10° W., desc. NE. slope.

62.40

Wash, 10 lks. wide, 2 ft. deep, drains NW.; asc. NW. slope.

63.00

Road, unimproved, bears irregularly NE. and SW.

66.80

Ridge, bears N. and S.; desc. E. slope.

70.26

Intersect Line 1-2 Trapezoid lode M.S. 2110 at a point from which Cor. No. 1 bears N. 49°28' W., 3.25 chs. dist.

72.28

Intersect Line 4-1 Porto Rico lode M.S. 2349 at a point from which Cor. No. 1 bears N. 21°21' E., 6.55 chs. distant.

80.00

Intersect the E. bdy. of T. 12 N., R. 1 W.

Point for the closing cor. of Ts. 12 and 12½ N., R. 2 W.

Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T12½N
R2W | R1W
S36 C | S6
S 1 C |
T12N
1962

from which

A silver spruce 6 ins. diam. bears S. 14° W., 43 lks. dist., mkd. S 1 B T

A silver spruce 6 ins. diam. bears N. 67°15' W., 56 lks. dist., mkd. S36 B T

BOOK 4824

Subdivision of T. 12 N., R. 2 W., Arizona

10

10.

CHAINS

The cor. of Ts. 12 and 12½ N., R. 1 W., bears North, 6.23 chs. dist., monumented by an iron post as described in the current survey of T. 12 N., R. 1 W., under this group number.

Cor. No. 4 Porto Rico lode M.S. 2349 bears S. 47°32' W., 16.30 chs. dist.

Cor. No. 2 Trapezoid lode M.S. 2110 bears S. 54°23' W., 6.52 chs. dist.

Cor. falls on E. slope.

Land, mountainous.

Soil, rocky.

Timber, silver spruce, pine, cedar and fir.

Undergrowth, oakbrush.

Subdivision of T. 12 N., R. 2 W., Arizona

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township, monumented by an iron post as described in the official record.

N. 0°01' W., bet. secs. 35 and 36.

Over mountainous and rolling land, through dense undergrowth.

Asc. SW. slope.

1.85 Spur, projects W.; thence desc. to draw.

6.20 Draw, course W.; asc. very steep rocky slope.

40.00 Point for the ¼ sec. cor. of secs. 35 and 36.

Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T12N R2W
¼
S35|S36
1962

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.

Cor. falls on steep S. slope.

60.00 Ridge top, bears NW. and SE.; desc. along N. slope.

67.00 Road, bladed, bears NE. and SW.

71.20 End desc.; thence along W. slope.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set the iron post 5 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T12N R2W
S26|S25
S35|S36
1962

CHAINS	
	<p>No bearing trees available.</p> <p>Cor. falls on SW. slope.</p> <p>Land, rolling and mountainous. Soil, gravelly and rocky. Timber, none. Undergrowth, oakbrush, manzanita and laurel.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township.</p> <p>N. 89°56' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through dense undergrowth, sparse timber.</p>
15.70	Road, unimproved, bears irregularly N. and S.
16.10	Crooks Canyon Creek, 25 lks. wide, course SW.; asc. E. slope.
34.25	Intersect Line 3-4 "1900" lode M.S. 1804 at a point from which Cor. No. 4 bears N. 33°11' W., 7.77 chs. distant.
39.94	<p>Point for the ¼ sec. cor. of secs. 25 and 36.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T12N R2W</p> <p>¼ $\frac{S25}{S36}$</p> <p>1962</p> </div> <p>from which</p> <p style="padding-left: 40px;">Cor. No. 4 "1900" lode M.S. 1804 bears N. 12°29' E., 6.66 chs. dist.</p> <p style="padding-left: 40px;">Cor. No. 1 "1900" lode M.S. 1804 bears N. 69°40' W., 7.11 chs. dist.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor.</p>
40.25	Ravine, 15 lks. wide, course S.; asc. E. slope.
45.00	Intersect Line 1-2 "1900" lode M.S. 1804 at a point from which Cor. No. 1 bears N. 33°11' W., 2.95 chs. distant.
74.40	Crest of ridge, bears NE. and SW.; desc. steep SW. slope.
79.88	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling. Soil, rocky. Timber, pinon pine E 1/2 mile. Undergrowth, oakbrush and tamarack.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land, through dense undergrowth.</p>

BOOK 4824

Subdivision of T. 12 N., R. 2 W., Arizona

12

12.

CHAINS

- 12.10 Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. gentle SW. slope.
- 21.30 Spur, slopes W.; desc. along gentle SW. slope.
- 28.90 Wash, 10 lks. wide, 1 ft. deep, drains SW.; asc. gentle S. slope.
- 37.90 Wash, 10 lks. wide, 2 ft. deep, drains W. for 4 chs. thence SW.; asc. S. slope.
- 39.70 Road, unimproved, circles from NE. to NW.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
Set the iron post 24 ins. in the ground, cap mkd.

T12N R2W
 $\frac{1}{4}$
S26 | S25
1962

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

No bearing trees available.
- 49.65 Road, unimproved, bears NW. and SE.
- 77.70 Spur, slopes SW.; desc. along gentle W. slope of ridge.
- 80.00 Point for the cor. of secs. 23, 24, 25 and 26.
Set the iron post 24 ins. in the ground, cap mkd.

T12N R2W
S23 | S24
S26 | S25
1962

Land, rolling and mountainous.
Soil, rocky.
Timber, scattered juniper.
Undergrowth, manzanita, laurel and buck brush.

From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township.

N. $89^{\circ}57'$ W., bet. secs. 24 and 25.

Over mountainous land, through timber and dense undergrowth.

Asc. E. slope.
- 16.90 Crest of spur, projects SE.; desc. NW. slope.
- 39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, falls in wash area where the cor. cannot be perpetuated.
- 39.95 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.; asc. NE. slope.

CHAINS	
40.28	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 24 and 25.</p>
	<p>Set the iron post 12 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ $\frac{S24}{S25}$ \rightarrow W C 1962</p>
45.30	<p>Crest of spur, projects SE.; desc. NW. slope.</p>
49.70	<p>Crest of spur, slopes irregularly S.; asc. along NE. slope.</p>
76.00	<p>Ridge, slopes to SW.; desc. W. slope to cor.</p>
79.88	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered pine and cedar. Undergrowth, oak brush, laurel and manzanita.</p>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p>
	<p>Over mountainous land, through dense undergrowth, 6 to 10 ft. high.</p>
	<p>Asc. NW. slope.</p>
13.40	<p>Crest of spur, slopes SW.; desc. NW. slope.</p>
18.70	<p>Ravine, course S. 70° W.; asc. SW. slope.</p>
28.90	<p>Crest of spur, slopes WSW.; desc. steep NW. slope.</p>
30.00	<p>Enter timber.</p>
35.20	<p>Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.; asc. SW. slope.</p>
38.60	<p>Spur, projects N. 40° W.; desc. N. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p>
	<p>Set the iron post 6 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ S23 S24 1962</p>
	<p>from which</p>
	<p>An oak, 8 ins. diam., bears S. 82°30' E., 18 lks. dist., mkd. $\frac{1}{4}$ S24 B T</p>
	<p>A pine, 6 ins. diam., bears N. 85°45' W., 19 lks. dist., mkd. $\frac{1}{4}$ S23 B T</p>
	<p>Cor. falls on steep N. slope.</p>

CHAINS

- 65.60 Ridge, bears NE. and SW.; desc. NW. slope.
- 74.00 Wash, 15 lks. wide, 3 ft. deep, drains N. 40° W.; asc. SW. slope.
- 75.60 Crest of small spur, projects N. 40° W.; desc. W. slope.
- 79.80 Crest of small spur, slopes NW.; desc. NW. slope.
- 80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set the iron post 15 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T12N R2W
 $\frac{S14}{S23} | \frac{S13}{S24}$
 1962

from which

A pine 8 ins. diam. bears N. 8°15' E., 10 lks. dist., mkd. S13 B T

A pine 8 ins. diam. bears S. 50°15' W., 31 lks. dist., mkd. S23 B T

A pine 8 ins. diam. bears N. 84°30' W., 13½ lks. dist., mkd. S14 B T

Cor. falls on NW slope.

Land, mountainous.

Soil, rocky.

Timber, oak, pine, and cedar.

Undergrowth, oakbrush and manzanita

From the true point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the township, 40 lks. N. of the witness cor.

N. 89°52' W., bet. secs. 13 and 24.

Over mountainous land, through thick timber.

Asc. NE. slope.

- .20 Wash, 10 lks. wide, 1 ft. deep, drains E.
- 29.00 Crest of spur, bears irregularly NE. and SW.; desc. NW. slope.
- 31.60 Wash, 1 ft. deep, drains N. 10° E.; asc. E. slope.
- 39.93 Point for the ¼ sec. cor. of secs. 13 and 24.

Set the iron post 26 ins. in the ground, cap mkd.

T12N R2W
 $\frac{1}{4} \frac{S13}{S24}$
 1962

from which

CHAINS	
	<p>A pine 10 ins. diam. bears S. 5°30' W., 29 lks. dist., mkd. ¼ S24 B T</p> <p>A pine 8 ins. diam. bears N. 34°45' W., 44 lks. dist., mkd. ¼ S13 B T</p> <p>U S.L.M. No. 1181, Hassayampa Mining District, bears N. 61°04' W., 15.06 chs. dist., monumented by a wood post 6 ins. square, set in a mound of stone, mkd. U.S.L.M. 1181</p> <p>Cor. falls on SE. slope.</p>
41.40	Spur, slopes SE.; asc. gentle S. slope.
52.00	Ridge, bears SE. and NW.; desc. SW. slope.
53.39	Intersect Line 4-1 Nellie lode M.S. 1181 at a point from which Cor. No. 4 bears N. 14°19' W., 15.26 chs. distant.
62.78	Intersect Line 2-3 Nellie lode M.S. 1181 at a point from which Cor. No. 3 bears N. 14°19' W., 14.03 chs. distant.
75.80	Ravine, course NW.; desc. steep SW. slope.
79.86	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, mountainous. Soil, rocky. Timber, pine cedar and oak. Undergrowth, oakbrush and manzanita.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over mountainous land, through timber.</p>
2.00	Wash, 2 ft. deep, drains NW.; asc. SW. slope.
26.70	Spur, projects WSW.; desc. NW. slope.
29.50	Ravine, course W.; asc. SW. slope.
34.30	Crest of spur, slopes WSW.; desc. SW. slope.
39.80	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 13 and 14.
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T12N R2W ¼ S14 S13 1962</p> <p>from which</p> <p>A pine 6 ins. diam. bears N. 45°15' E., 28½ lks. dist., mkd. ¼ S13 B T</p> <p>A pine 16 ins. diam. bears N. 59°45' W., 31 lks. dist., mkd. ¼ S14 B T</p>

16

CHAINS									
	Cor. falls on SW. slope.								
42.60	Crest of spur, slopes SW.; desc. NW. slope.								
44.60	Wash, 10 lks. wide, 1 ft. deep, drains SW.; asc. SW. slope.								
46.80	Spur, projects SW.; desc. steep NW. slope.								
55.00	Ravine, course SW.								
73.10	Ravine, course SW.; asc. over small spur.								
75.90	Spur, slopes SW.; desc. steep NW. slope.								
77.80	Wash, 10 lks. wide, 1 ft. deep, drains SW.; desc. steep NW. slope.								
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set the iron post 24 ins. in the ground, cap mkd <div style="text-align: center;"> <table border="0"> <tr><td>T12N</td><td>R2W</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td>S14</td><td>S13</td></tr> <tr><td colspan="2">1962</td></tr> </table> </div> from which A pine 18 ins. diam. bears N. 5° E., 59 lks. dist., mkd. S12 B T A pine 10 ins. diam. bears N. 32°30' W., 80 lks. dist., mkd. S11 B T Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner. Cor. falls on steep NW. slope. Land, mountainous. Soil, rocky. Timber, pine and cedar. Undergrowth, oak brush and manzanita.	T12N	R2W	S11	S12	S14	S13	1962	
T12N	R2W								
S11	S12								
S14	S13								
1962									
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township. N. 89°47' W., bet. secs. 12 and 13. Over mountainous land, through dense timber and undergrowth. Desc. steep NW. slope.								
10.40	Wash, 30 lks. wide, 3 ft. deep, drains irregularly SE.								
13.00	Senator Highway, bears NW. and SE.; asc. NE. slope.								
16.00	Spur, bears NW. and SE.; desc. SE. slope.								
17.57	Intersect Line 4-1 Joe B III lode M.S. 4459 at a point from which Cor. No. 1 bears N. 11°26' W., 2.81 chs. distant.								
19.50	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. NE. slope.								

CHAINS	
21.50	Crest of spur, projects SE.; asc. SE. slope.
29.07	Intersect Line 3-4 B. Frank lode M.S. 4459 at a point from which Cor. No. 4 bears S. 76°03' W., 1.77 chs. distant.
30.82	Intersect Line 4-1 B. Frank lode M.S. 4459 at a point from which Cor. No. 4 bears S. 5°16' E., 0.43 chs. dist.
38.40	Wash, 15 lks. wide, 1 ft. deep, drains ESE.; asc. steep E. slope.
39.94	Point for the ¼ sec. cor. of secs. 12 and 13. Set the iron post 20 ins. in the ground, cap mkd.
	<p style="text-align: center;">T12N R2W ¼ $\frac{S12}{S13}$ 1962</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine 8 ins. diam. bears N. 21°30' W., 45 lks. dist., mkd. ¼ S12 B T</p> <p style="padding-left: 40px;">No other bearing trees available.</p> <p style="padding-left: 40px;">U.S.L M. No. 1 4459 bears N. 15°43' E., 19.47 chs. dist.</p> <p style="padding-left: 40px;">Cor. No. 3 Easy To Get lode M S. 4372 bears N. 7°41' W., 12.79 chs. dist.</p> <p>Cor. falls on steep E. slope.</p>
60.00	Crest of spur, slopes SSW.; desc. NW. slope.
63.20	Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. steep SE. slope.
65.70	Crest of ridge, bears irregularly SE. and NW.
66.20	Road, unimproved, bears irregularly NNW. and S.; desc. W. slope.
75.30	Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.; desc. NW. slope.
79.88	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, mountainous. Soil, rocky. Timber, oak, pine and cedar. Undergrowth, oak brush and manzanita.</p>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over mountainous land.</p>
.30	Wash, 10 lks. wide, 2 ft. deep, drains WSW.; asc. S. slope.
3.00	Crest of spur, slopes SW.; desc. NW. slope.

BOOK 4824

Subdivision of T. 12 N., R. 2 W., Arizona

18

18.

CHAINS	
5.00	Wash, 10 lks. wide, 1 ft. deep, drains WSW.; asc. SW. slope.
8.00	Crest of spur, projects WSW.; desc. NW. slope.
11.90	Wash, 15 lks. wide, 2 ft. deep, drains WSW.; asc. steep SW. slope.
32.10	Road, unimproved, bears irregularly NW. and SE.; thence along ridge top.
37.60	Desc. steep NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T12N R2W $\frac{1}{4}$ S11 S12 1962</p>
	from which
	<p>A pine 6 ins. diam. bears S. 66°15' E., 62 lks. dist., mkd. $\frac{1}{4}$ S12 B T</p>
	<p>A pine 10 ins. diam. bears S. 73°45' W., 50 lks. dist., mkd. $\frac{1}{4}$ S11 B T</p>
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Cor. falls on steep NNE. slope.
45.00	Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. along E. slope.
48.00	Low spur, slopes E.; desc. NE. slope.
53.20	Wash, 10 lks. wide, 1 ft. deep, drains ENE.; asc. SE. slope.
57.00	Crest of spur, projects E.; desc. NE. slope.
59.10	Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. steep SE. slope.
69.60	Spur, slopes ESE.; desc. NE. slope.
76.20	Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. S. slope.
76.85	Cross old mine shaft.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	<p>T12N R2W <u>S 2 S 1</u> S11 S12 1962</p>
	from which
	<p>A pine 10 ins. diam. bears S. 80°45' E., 40 lks. dist., mkd. S12 B T</p>

CHAINS	
	<p>A pine 8 ins. diam. bears S. 71°45' W., 33 lks. dist., mkd. S11 B T</p> <p>A pine 6 ins. diam. bears N. 35° W., 31 lks. dist., mkd. S2 B T</p> <p>Land, mountainous. Soil, rocky. Timber, oak, spruce and pine. Undergrowth, oakbrush.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township.</p> <p>N. 89°48' W., bet. secs. 1 and 12.</p> <p>Over mountainous land, through thick timber.</p> <p>Asc. steep ENE. slope.</p>
4.90	Spur, slopes S.; thence along S. slope.
14.80	Spur, slopes SSE.; desc. steep W. slope.
16.75	Intersect Line 1-2 Mountain View lode M.S. 2588 at a point from which Cor. No. 1 bears N. 18°33' E., 10.55 chs. dist.
21.76	Intersect Line 2-3 Aligaitor lode M.S. 1588 at a point from which Cor. No. 3 bears S. 2°47' W., 9.22 chs. dist.
30.86	Intersect Line 4-1 Aligaitor lode M.S. 1588 at a point from which Cor. No. 1 bears N. 2°47' E., 9.53 chs. dist.
31.00	Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. E. slope.
35.40	Crest of spur, slopes S.; thence along S. slope.
39.93	Point for the ¼ sec. cor. of secs. 1 and 12.
	<p>Set the iron post 15 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T12N R2W ¼ $\frac{S 1}{S12}$ 1962</p> <p>from which</p> <p>Cor. No. 3 Mexia lode M.S. 1588 bears N. 33°04' W., 2.19 chs. dist.</p> <p>A pine 10 ins. diam. bears N. 89°45' W., 28 lks. dist., mkd. ¼ S1 B T</p> <p>No other bearing trees available.</p>
45.80	Spur, slopes S.; desc. along W. slope.
61.00	Ravine, 20 lks. wide, 2 ft. deep, course SE.; asc. E. slope.
65.20	Senator Highway, bears NW. and SE.
79.86	The cor. of secs. 1, 2, 11 and 12.

CHAINS		
	<p>Land, mountainous. Soil, rocky. Timber, spruce, pine and cedar. Undergrowth, manzanita and oak brush.</p> <hr/> <p>N. 0°07' W., bet. secs. 1 and 2.</p> <p>Over mountainous land, through dense timber.</p>	
1.00	Low spur, slopes ENE.; desc. N. slope.	
5.00	Senator Highway, bears irregularly NW. and SE	
6.50	Wash, 30 lks. wide, 2 ft. deep, drains SE.; asc. SSW. slope.	
22.50	Slope changes from SSW. to steep W. slope.	
30.00	Wash, 10 lks. wide, 1 ft. deep, drains SW.; asc. over small spur.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	<p>T12N R2W $\frac{1}{4}$ S 2 S 1 1962</p>	
	from which	
	<p>A pine 16 ins. diam. bears S. 36° E., 38 lks. dist., mkd. $\frac{1}{4}$ S1 B T</p> <p>A pine 12 ins. diam. bears N. 8° W., 2 lks. dist., mkd. $\frac{1}{4}$ S2 B T</p> <p>Cor. No. 4 Forest lode M.S. 4298 bears N. 24°45' W., 4.32 chs. dist.</p>	
	Cor. falls on W. slope.	
43.03	Intersect Line 3-4 Forest lode M.S. 4298 at a point from which Cor. No. 4 bears N. 63°46' W., 2.02 chs. dist.	
43.20	Road, bladed, bears irregularly NW. and SE.	
45.89	Intersect Line 4-1 Forest lode M.S. 4298 at a point from which Cor. No. 4 bears S. 42°19' W., 2.66 chs. dist.	
47.40	Road, bladed, leads to Mr. Union Ranger Station.	
47.80	Point selected for witness point on the line bet. secs. 1 and 2.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	<p>T12N R2W W P S 2 S 1 1962</p>	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.	

CHAINS	
50.00	Desc. over N. slope.
55.11	Intersect Line 1-2 Cashier lode M.S. 1459 at a point from which Cor. No. 2 bears S. 45°16' W., 2.25 chs. distant.
55.40	Wash, 10 lks. wide, 1 ft. deep, drains irregularly N.; continue descent.
60.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 50° W.; desc. along W. slope.
67.43	Intersect Line 3-4 Cashier lode M.S. 1459 at a point from which Cor. No. 3 bears S. 45°16' W., 8.52 chs. distant.
68.50	Slope changes to NW.
70.93	Intersect Line 5-6 Snoozer lode M.S. 964 at a point from which Cor. No. 6 bears S. 51°40' W., 13.64 chs. distant.
73.51	The cor. of secs. 1, 2, 35 and 36.
	Land, rolling and mountainous. Soil, rocky. Timber, spruce, fir and oak. Undergrowth, oak brush.
	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post as described in the official record.
	N. 0°01' W., bet. secs. 34 and 35.
	Over rolling land, through dense undergrowth; asc. S. slope.
12.80	Ridge, bears NE. and SW.; desc. N. slope.
30.40	Wash, 10 lks. wide, 1 ft. deep, drains W.
40.00	Point for the ¼ sec. cor. of secs. 34 and 35.
	Set the iron post 6 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T12N R2W ¼ S34 S35 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
	Cor. falls on SW. slope.
49.10	Crest of spur, slopes W.; desc. NW. slope.
53.50	Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. SE. slope.
66.60	Ridge, slopes SW.; asc. SW. slope.

BOOK 4824

Subdivision of T. 12 N., R. 2 W., Arizona

22

22.

CHAINS	
78.50	Spur, slopes WNW.; desc. NE. slope.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 20 ins. in the ground, cap mkd.
	T12N R2W S27 S26 S34 S35 1962
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of corner.
	Cor. falls on NE. slope.
	Land, rolling.
	Soil, gravelly and rocky.
	Timber, none.
	Undergrowth, oak brush, laurel, manzanita and buckbrush.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°49' W., bet. secs. 26 and 35.
	Over rolling land, no timber.
20.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. small spur.
25.20	Wash, 15 lks. wide, 2 ft. deep, drains SE.; asc. NE. slope.
33.30	Crest of ridge, bears irregularly N. and S.; desc. SSW. slope.
36.70	Slope changes to NW.
40.04	Point for the ¼ sec. cor. of secs. 26 and 35.
	Set the iron post 12 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T12N R2W ¼ — S26 S35 1962
	Cor. falls on steep rocky NW. slope.
42.20	Ravine, course S. 10° W.; asc. SE. slope.
50.30	Spur, slopes SW.; desc. W. slope.
60.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.
68.00	Crest of spur, desc. gentle SW. slope.
78.00	Crest of spur, slopes W.; desc. NW. slope.
80.08	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling.
	Soil, gravelly and rocky.
	Timber, none.
	Undergrowth, manzanita, laurel and oakbrush.

CHAINS	
	N. 0°01' W., bet. secs. 26 and 27.
	Over rolling land, through dense undergrowth.
	Desc. ENE. slope.
7.00	Wash, 10 lks. wide, 3 ft. deep, drains SW.; asc. SE. slope.
40.00	Point for the ¼ sec. cor. of secs. 26 and 27.
	Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ S27 S26 1962</p>
	Cor. falls on S. slope.
42.00	Spur, bears NE. and SW.; desc. N. slope.
61.50	Ash Creek, course SW.; asc. S. slope.
79.50	Road, unimproved, bears W. and NE.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 6 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	<p style="text-align: center;">T12N R2W S22 S23 S27 S26 1962</p>
	Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, oakbrush, laurel and manzanita.
	<hr/> From the cor. of secs. 23, 24, 25 and 26.
	N. 89°49' W., bet. secs. 23 and 26.
	Over rolling land, through dense undergrowth, no timber.
	Desc. W. slope.
6.50	Ravine, course S.; asc. E. slope.
16.00	Spur, bears NE. and SW.
21.15	Desc. steep W. slope.
35.00	Jeep trail, bears NW. and SE.; end steep desc.
40.06	Point for the ¼ sec. cor. of secs. 23 and 26.
	Set the iron post 15 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ $\frac{S23}{S26}$ 1962</p>

BOOK 4824

Subdivision of T. 12 N., R. 2 W., Arizona

24

24.

CHAINS									
52.70	Begin desc. W. slope.								
63.00	Ash Creek, 20 lks. wide, 3 ft. deep, course SW.								
63.20	Asc. E. slope.								
78.50	Road, unimproved, bears W. and NE.								
80.12	Cor. of secs. 22, 23, 26 and 27.								
	Land, mountainous. Soil, rocky, gravelly. Timber, none. Undergrowth, laurel and oakbrush.								
	N. 0°01' W., bet. secs. 22 and 23.								
	Over mountainous land, through dense undergrowth, sparse timber.								
	Asc. S. slope of ridge.								
23.80	Draw, course SE.								
35.65	Crest of spur, bears NE. and SW.; desc. along NE. slope.								
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.								
	Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T12N R2W</td> </tr> <tr> <td style="text-align: center;">$\frac{1}{4}$</td> <td></td> </tr> <tr> <td style="text-align: center;">S22</td> <td style="text-align: center;">S23</td> </tr> <tr> <td colspan="2" style="text-align: center;">1962</td> </tr> </table>	T12N R2W		$\frac{1}{4}$		S22	S23	1962	
T12N R2W									
$\frac{1}{4}$									
S22	S23								
1962									
	Cor. falls on NNE. slope.								
46.20	Draw, course SE.; asc. SE. slope.								
60.00	Crest of ridge, bears NE. and SW.; asc. along SW. ridge.								
80.00	Point for the cor. of secs. 14, 15, 22 and 23.								
	Set the iron post 15 ins. in the ground to bedrock, mound with stone to top, cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T12N R2W</td> </tr> <tr> <td style="text-align: center;">S15</td> <td style="text-align: center;">S14</td> </tr> <tr> <td style="text-align: center;">S22</td> <td style="text-align: center;">S23</td> </tr> <tr> <td colspan="2" style="text-align: center;">1962</td> </tr> </table>	T12N R2W		S15	S14	S22	S23	1962	
T12N R2W									
S15	S14								
S22	S23								
1962									
	from which								
	E Cross L Spring bears S. 65°59' E., 23.87 chs. dist.								
	Raise a mound of stone, 4 ft. base, 2 ft. high, W. of corner.								
	Cor. falls on SW. slope.								

CHAINS	
	<p>Land, mountainous. Soil, rocky. Timber, none. Undergrowth, manzanita, laurel and oakbrush.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24. N. 89°49' W., bet. secs. 14 and 23. Over mountainous land, through dense timber and undergrowth. Desc. steep W. slope.</p>
8.30	Trail, bears NE. and SW.; asc. SE. slope.
20.80	Crest of ridge, bears NE. and SW.; desc. steep SW. slope.
39.60	Low ridge, slopes S.; desc. gentle W. slope.
40.06	Point for the ¼ sec. cor. of secs. 14 and 23. Set the iron post 24 ins. in the ground, cap mkd.
	<p>T12N R2W ¼ $\frac{S14}{S23}$ 1962</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine 5 ins. diam. bears N. 41°30' E., 6 lks. dist., mkd. ¼ S14 B T</p> <p style="padding-left: 40px;">A pine 6 ins. diam. bears S. 76°15' E., 13 lks. dist., mkd. ¼ S23 B T</p> <p style="padding-left: 40px;">Cor. No. 5 of Homestead Entry No. 80 bears S. 78°36' W., 7.97 chs. dist.</p>
	<p>Raise a mound of stone, 4 ft. base, 2 ft. high, N. of corner.</p>
45.50	Ash Creek, 20 lks. wide, 2 ft. deep, course S.; asc. W. slope (road in creek bed).
76.00	Trail, bears irregularly SSW. and NNE. along ridge top.
76.20	Crest of ridge, bears NNE. and SSW.; desc. steep W. slope.
80.12	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, mountainous. Soil, rocky. Timber, pine and oak E 1/2 mile. Undergrowth, manzanita, oakbrush and laurel.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15. Over mountainous land, through dense undergrowth. Asc. SW. slope.</p>

CHAINS		
8.00	Crest of ridge, bears irregularly N. and S.; desc. along E. slope.	
13.00	Draw, course W.; asc. SE. slope.	
29.40	Crest of ridge, bears irregularly N. and S.; asc. along E. slope.	
29.60	Trail, bears irregularly NNW. and SSE. along the ridge top; thence along E. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15. Set the iron post 20 ins. in the ground, mound with stone to top, cap mkd.	
	T12N R2W $\frac{1}{4}$ S15 S14 1962	
	Cor. falls on E. slope. No bearing trees available.	
70.85	Spur, bears NE. and SW.; asc. along E. slope of spur.	
71.50	Enter into dense timber, sparse undergrowth.	
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set the iron post 16 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	T12N R2W S10 S11 S15 S14 1962	
	Land, mountainous. Soil, rocky. Timber, pine, oak and cedar N 1/2 mile. Undergrowth, oakbrush and manzanita.	
	From the cor. of secs. 11, 12, 13 and 14.	
	N. 89°47' W., bet. secs. 11 and 14.	
	Desc. W. slope through dense undergrowth.	
9.70	Ravine, course S.; asc. E. slope.	
17.00	Ridge, bears N. and S.; desc. W. slope.	
26.20	Ravine, course SW.; asc. SE. slope.	
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	T12N R2W $\frac{1}{4}$ $\frac{S11}{S14}$ 1962	
	Cor. falls on SE. slope.	

CHAINS	
40.40	Trail, bears irregularly SW. and NE., in wash, drains S.
42.10	Spur, projects SSE.; desc. W. slope.
43.80	Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. E. slope.
51.60	Spur, slopes SE.; desc. SW. slope.
63.00	Ravine, course SE.; asc. SE. slope.
80.10	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, mountainous. Soil, rocky. Timber, patches of fir, spruce and pine. Undergrowth, oakbrush and laurel.</p>
	<hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p>
	Over mountainous land, through dense timber.
	Desc. NE. slope.
9.30	Ravine, course SE.; asc. S. slope.
23.60	Point selected as witness point on the line bet. secs. 10 and 11.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T12N R2W W P S10 S11 1962</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.
23.80	Road, bladed, bears NE. and SW.; leads to Golden Eagle Mine.
35.77	Intersect Line 3-4 Last Chance lode M.S. 3347 at a point from which Cor. No. 3 bears S. 43°30' W., 5.87 chs. dist.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ S10 S11 1962</p>
	from which
	A pine, 4 ins. diam., bears S. 12°30' E., 20 lks. dist., mkd. B T
	A pine, 10 ins. diam., bears N. 68°30' W., 23 lks. dist., mkd. $\frac{1}{4}$ S10 B T

CHAINS	
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.
43.20	Desc. along NW. slope.
45.80	Fence, bears NE. and SW.
49.90	Ravine, course irregularly W.; asc. SW. slope.
58.10	Spur, slopes W.; desc. NW. slope.
69.00	Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. SE. slope.
76.00	Spur, projects irregularly W.; desc. N. slope.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T12N R2W S 3 S 2 S10 S11 1962
	from which
	Cor. No. 3 Clay Bank lode M.S. 3347 bears S. 11°43' E., 5.96 chs. dist.
	Cor. No. 2 Arctic lode M.S. 3347 bears S. 50°22' W., 9.42 chs. dist.
	Cor. No. 3 Little Ross lode M.S. 3865 bears N. 77°40' W., 12.37 chs. dist.
	Cor. falls on steep N. slope.
	Land, high rolling and mountainous. Soil, rocky. Timber, cedar and pine. Undergrowth, oakbrush and manzanita.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°56' W., bet. secs. 2 and 11.
	Over rolling mountainous land, through dense timber.
	Asc. steep E. slope.
8.90	Ridge, bears NW. and S.; thence along SE. slope.
28.00	Spur, slopes NE.; asc. NE. slope.
32.40	Intersect Line 1-2 M.S. 2913 High Line No. 1 lode at a point from which Cor. No. 1 bears N. 63°28' W., 5.17 chs. dist.
33.00	Ridge top, bears NW. and SE.
33.70	Road, unimproved, follows ridge top, bears NW. and SE.; desc. NW. slope.
35.60	Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. SE. slope.

CHAINS	
38.19	Intersect Line 4-1 High Line No. 1 lode M.S. 2913 at a point from which Cor. No. 1 bears N. 26°32' E., 2.62 chs. dist.
38.55	Road, bladed, bears NE. and SW. to Golden Eagle Mine.
38.78	Intersect Line 2-3 High Line No. 3 lode M.S. 2913 at a point from which Cor. No. 2 bears N. 36°54' E., 2.93 chs. dist.
40.06	<p>Point for the ¼ sec. cor. of secs. 2 and 11.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T12N R2W $\frac{1}{4} \frac{S 2}{S11}$ 1962</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine 12 ins. diam. bears S. 64°15' E., 24 lks. dist., mkd. T12N R2W ¼ S11 B T</p> <p style="padding-left: 40px;">A ponderosa pine 14 ins. diam. bears N. 46°30' W., 15 lks. dist., mkd. T12N R2W ¼ S2 B T</p> <p style="padding-left: 40px;">Cor. No. 3 High Line No. 1 lode M.S. 2913 bears S. 11°06'30" E., 17.50 chs. dist.</p> <p style="padding-left: 40px;">Cor. No. 3 High Line No. 3 lode M.S. 2913 bears S. 33°36' W., 18.50 chs. dist.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.</p> <p>Cor. falls on ENE. slope.</p>
49.97	Intersect Line 4-1 High Line No. 3 lode M.S. 2913 at a point from which Cor. No. 1 bears N. 36°54' E., 8.03 chs. dist.
52.80	Ridge top, bears irregularly N. and S.
58.60	Fence, bears N. and S.; begin desc. NW. slope.
59.96	Intersect Line 4-1 Hollywood lode M.S. 3347 at a point from which Cor. No. 1 bears N. 7° E., 5.10 chs. dist.
72.00	Wash, 15 lks. wide, 3 ft. deep, drains MNW.; desc. NE. slope.
77.00	Slope changes from NE. to N.; asc. to cor.
80.12	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, mountainous. Soil, rocky. Timber, spruce, pine and fir. Undergrowth, oakbrush.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over mountainous land, through dense timber and undergrowth.</p>

CHAINS	
	Desc. over very steep N. slope.
18.00	Wash, 20 lks. wide, 2 ft. deep, drains W.; asc. steep SW. slope.
21.74	Intersect Line 1-2 Little Ross lode M.S. 3865 at a point from which Cor. No. 2 bears S. 54°46' E., 4.35 chs. dist.
30.00	Road, bladed, bears generally E. and W. to mining claims.
33.00	Spur, bears E. and W.; desc. steep N. slope.
37.20	Road, unimproved, same road given above, bears SW. and NE.
38.82	Intersect Line 1-2 Jay Hawker lode M.S. 2348 at a point from which Cor. No. 1 bears S. 79°15' W., 2.14 chs. dist.
40.00	Point for the ¼ sec. cor. of secs. 2 and 3.
	Set the iron post 14 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	<p style="text-align: center;">T12N R2W ¼ S 3 S 2 1962</p>
	from which
	<p style="text-align: center;">U.S.L.M. No. 1691, Hassayampa Mining District, bears S. 40°55' W., 9.46 chs. dist., monumented by a cross chiseled in rock in place and chiseled marks U.S.L.M. No. 1691</p>
	<p style="text-align: center;">Cor. No. 1 Jay Hawker lode M.S. 2348 bears S. 53°06' W., 2.63 chs. dist., monumented by a stone, 8x10x24 ins., mkd. W 1-1 JH-1-2348</p>
	Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of cor.
	Cor. falls on NW. slope.
43.00	Wash, 10 lks. wide, 1 ft. deep, drains WSW.; asc. SW. slope.
46.93	Intersect Line 3-4 Jay Hawker lode M.S. 2348 at a point from which Cor. No. 4 bears S. 77°33' W., 7.23 chs. dist.
48.64	Intersect Line 4-1 Dunkirk lode M.S. 2420 at a point from which Cor. No. 1 bears S. 67°40' W., 5.41 chs. dist.
58.47	Intersect Line 2-3 Dunkirk lode M.S. 2420 at a point from which Cor. No. 3 bears N. 67°40' E., 13.59 chs. distant.
60.80	Intersect Line 1-2 New Era No. 2 lode M.S. 1691 at a point from which Cor. No. 1 bears N. 49°35' E., 2.77 chs. dist.
63.00	SW. Slope changes to WSW. slope.
72.57	Intersect Line 3-4 Davis Number 3 North lode M.S. 1690 at a point from which Cor. No. 4 bears S. 51°12' W., 4.67 chs. dist.

CHAINS	
73.13	<p>The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the township.</p> <p>Land, mountainous. Soil, rocky. Timber, fir, spruce, oak and pine. Undergrowth, oakbrush and manzanita.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land, through scattered timber and sparse undergrowth.</p> <p>Asc. SE. slope.</p>
6.90	Ridge top, bears SSW. and NE.; desc. along W. slope.
18.30	Ravine, course SW.; asc. rocky SE. slope.
26.30	Ravine, course SW.; asc. SE. slope.
37.30	Wash, drains SW.; asc. SE. slope.
38.00	Small spur, slopes SW.; thence along W. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.
	<p>Set the iron post 15 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ S33 S34 1962</p>
	<p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
	Cor. falls on rocky W. slope.
42.60	Wash, drains S. 10° W.; asc. SE. slope.
47.30	Desc. along W. slope.
49.90	Ravine, course SW.; asc. SE. slope.
58.40	Road, bladed, bears SW. and NE.
59.80	Spur, bears E. and W.; desc. N. slope.
62.60	Wash, drains W.; asc. over W. slope.
72.00	Desc. gentle NW. slope.
77.80	Wash, drains SW.; asc. over small spur.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>

CHAINS	
	T12N R2W $\frac{S28}{S33} \frac{S27}{S34}$ 1962
	from which A juniper 10 ins. diam. bears N. $71\frac{3}{4}^{\circ}$ W., 95 lks. dist., mkd. T12N R2W S28 B T No other bearing tree available. Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of corner. Cor. falls on WNW. slope. Land, rolling. Soil, rocky. Timber, scattered juniper. Undergrowth, laurel, catclaw, oakbrush and mahogany.
	From the cor. of secs. 26, 27, 34 and 35. N. $89^{\circ}54'$ W., bet. secs. 27 and 34. Over rolling land, through dense undergrowth. Asc. NE. slope.
3.60	Crest of spur, bears NE. and SW.; desc. W. slope.
10.00	Ash Creek, course irregularly S.; asc. E. slope.
33.80	Ridge, bears N. and S.; desc. SW. slope.
39.86	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34. Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T12N R2W $\frac{1}{4} \frac{S27}{S34}$ 1962
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, N. of corner. Cor. falls on SW. slope. Desc. SW. slope.
40.70	Wash, drains SW.; desc. along S. slope.
55.00	Spur, slopes S.; desc. gentle SSW. slope.
68.00	Road, bladed, bears irregularly SW. and NE.; asc. NE. slope.
72.70	Low ridge, bears N. and S.; desc. W. slope.
79.72	The cor. of secs. 27, 28, 33 and 34.

CHAINS	
	<p>Land, rolling. Soil, rocky. Timber, scattered juniper. Undergrowth, oakbrush, laurel and catclaw.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land, through dense undergrowth 3 to 10 ft. high.</p> <p>Asc. over small spur, slopes SW.</p> <p>2.30 Desc. NW. slope.</p> <p>5.80 Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. SE. slope.</p> <p>17.30 Desc. abrupt N. rim.</p> <p>34.00 Rocky wash, 15 lks. wide, 3 ft. deep, drains W.; asc. rocky steep S. slope.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.</p> <p>Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T12N R2W $\frac{1}{4}$ S28 S27 1962</p> <p style="text-align: center;">No bearing trees available.</p> <p>49.20 Crest of spur, slopes S.; desc. along NW. slope.</p> <p>52.00 Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. S. slope.</p> <p>57.70 Ridge top, bears irregularly E. and W.; asc. gradually along W. slope.</p> <p>80.00 Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T12N R2W S21 S22 S28 S27 1962</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.</p> <p>Cor. falls on W. slope.</p> <p>Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, scrub oak, cactus and manzanita.</p> <hr/>

CHAINS	
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°57' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through dense undergrowth.</p> <p>Along S. slope of ridge.</p>
3.00	Crest of ridge, slopes S.; desc. SW. slope.
30.20	Road, bladed, bears irregularly NE. and SW.; thence over Johnson Flat.
39.85	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.</p> <p>Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T12N R2W $\frac{1}{4}$ $\frac{S22}{S27}$ 1962</p> <p>Cor. falls on gentle ESE. slope.</p>
60.00	Leave Johnson Flat; asc. E. slope of ridge.
77.70	Ridge, bears N. and S.; desc. W. slope to cor.
79.70	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, rocky. Timber, none. Undergrowth, sage brush, cactus and laurel.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land, through dense undergrowth, no timber.</p> <p>Asc. W. slope.</p>
2.30	Spur, slopes NW.; desc. rocky NW. slope.
3.30	Fence, barbed wire, bears NW. and SE.
14.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° W.; thence over moderately rolling land of Johnson Flat.
39.20	Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. gentle SW. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Set the iron post 21 ins. in the ground, collar of stone to top, cap mkd.</p> <p style="text-align: center;">T12N R2W $\frac{1}{4}$ $\frac{S21}{S22}$ 1962</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p>

CHAINS	
	Cor. falls on SW. slope.
44.80	Wash, 15 lks. wide, 3 ft. deep, drains irregularly W.; asc. SE. slope; leave Johnson Flat.
51.70	Spur, slopes SE.; desc. NE. slope.
57.50	Wash, 20 lks. wide, 3 ft. deep, drains SE.; asc. rocky SW. slope.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 24 ins. in the ground, cap mkd.
	T12N R2W S16 S15 S21 S22 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
	Cor. falls on SW slope.
	Land, rolling. Soil, rocky. Timber, none. Undergrowth, cactus, manzanita and laurel.
	From the cor. of secs. 14, 15, 22 and 23. N. 89°58' W., bet. secs. 15 and 22. Over rolling land, through dense undergrowth, sparse timber. Desc. SW. slope.
10.00	Spur, slopes S.; desc. over SW. slope.
30.00	Wash, 25 lks. wide, 3 ft. deep, drains SW.; asc. SE slope.
36.00	Ridge, bears NW. and SE.; desc. SW. slope.
39.84	Point for the ¼ sec. cor. of secs. 15 and 22. Set the iron post 15 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T12N R2W ¼ S15 S22 1962
	Cor. falls on SW. slope.
50.60	Fence, barbed wire, bears N. 30° E., S. 30° W.
55.30	Wash, 10 lks. wide, 2 ft. deep, drains S.; asc. ESE. slope.
60.10	Spur, slopes NE.; asc. NE. slope.
76.20	Slope changes to S.; desc. over SW. slope to cor.

CHAINS	
79.68	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, rocky. Timber, scattered juniper. Undergrowth, laurel and manzanita.</p>
	<hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p>
	<p>Over rolling land, through dense undergrowth.</p>
	<p>Asc. SW. slope.</p>
13.10	<p>Desc. steep N. slope.</p>
22.00	<p>Wash, 15 lks. wide, 3 ft. deep, drains SW.; asc. rocky SE. slope.</p>
32.90	<p>Crest of spur, projects SW.; thence along SW. slope.</p>
37.90	<p>Desc. steep NW. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.</p>
	<p>Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ S16 S15 1962</p>
	<p>Cor. falls on steep NW. slope.</p>
	<p>Desc. steep NW. slope.</p>
45.00	<p>Wash, in Box Canyon, 35 lks. wide, 3 ft. deep, course SW.; asc. steep SE. slope.</p>
66.00	<p>Spur, slopes SE.; desc. along NE. slope.</p>
70.00	<p>Wash, 10 lks. wide, 1 ft. deep, drains SSE.; asc. S. slope.</p>
75.95	<p>Spur, slopes ESE.; desc. along NW. slope.</p>
79.85	<p>Small ravine, course SE.; asc. to cor.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p>
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T12N R2W S 9 S10 S16 S15 1962</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.</p>
	<p>Cor. falls on SE. slope.</p>
	<p>Land, rolling and mountainous. Soil, rocky. Timber, scattered juniper, pine and oak. Undergrowth, manzanita and oakbrush.</p>

CHAINS	
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89°58' W., bet. secs. 10 and 15.
	Over rolling and mountainous land, through dense timber.
2.00	Ridge, bears N. and S.; desc. W. slope.
5.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.; desc. N. slope.
9.30	Wash, 10 lks. wide, 2 ft. deep, drains WSW.; thence along S. slope.
16.60	Small spur, slopes WSW.; desc. W. slope.
25.00	Wash, 10 lks. wide, 3 ft. deep, drains SW.; asc. SE. slope.
31.80	Crest of ridge, slopes irregularly S.
32.20	Road, unimproved, bears N. and S.; leave dense timber and enter into dense undergrowth.
33.50	Desc. W. slope.
39.81	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	Set the iron post 6 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ $\frac{S10}{S15}$ 1962.</p>
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.
	Cor. falls on steep SW. slope.
44.60	Wash, 10 lks. wide, 2 ft. deep, drains SSW.; asc. SE. slope.
58.00	Crest of spur, slopes SW.; desc. steep NW. slope.
68.00	Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. SE. slope to cor.
79.62	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling.
	Soil, rocky.
	Timber, fir, pine and oak E 1/2 mile.
	Undergrowth, oakbrush, manzanita and laurel.
	<hr/> N. 0°02' W., bet. secs. 9 and 10.
	Over rolling and mountainous land, through dense undergrowth.
	Asc. SE. slope.
8.00	Wash, 10 lks. wide, 2 ft. deep, drains SSE.; asc. steep S. slope.

38

CHAINS	
15.60	Ridge top, bears irregularly E. and W.; desc. WNW. slope.
16.50	Enter heavy timber.
25.10	Ravine, course W.; asc. SW. slope.
28.90	Spur, slopes NW.; desc. N. slope.
32.00	Road, bladed, bears irregularly W., leading to Golden Eagle Mine; desc. over very steep N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T12N R2W $\frac{1}{4}$ S 9 S10 1962</p>
	from which
	<p style="text-align: center;">A Douglas fir 24 ins. diam. bears N. 5° E., 37 lks. dist., mkd. T12N R2W $\frac{1}{4}$ S10 B T</p>
	<p style="text-align: center;">A Douglas fir 14 ins. diam. bears S. 31°30' W., 76 lks. dist., mkd. T12N R2W $\frac{1}{4}$ S9 B T</p>
	Cor. falls on very steep N. slope.
43.20	Ravine, 15 lks. wide, course W.; leave timber, enter dense undergrowth; asc. S. slope.
52.00	Spur, slopes SW.
65.20	Leave dense undergrowth, enter timber.
66.50	Desc. N. slope.
74.10	Ravine, 25 lks. wide, course SW.; asc. S. slope.
78.80	Spur, slopes W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T12N R2W S 4 S 3 S 9 S10 1962</p>
	<p>Land, rolling and mountainous. Soil, rocky. Timber, fir and oak. Undergrowth, manzanita, laurel and oakbrush.</p>
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89°59' W., bet. secs. 3 and 10.
	Over mountainous land, through dense timber.
	Along steep N. slope.

CHAINS	
8.60	Crest of spur, slopes NW.; desc. steep WSW. slope.
12.70	Ravine, course WNW.; desc. NW. slope.
14.47	Intersect Line 3-4 Katherine lode M.S. 3865 at a point from which Cor. No. 4 bears N 13°54' E., 0.49 chs. dist.
21.60	Ravine, course SW.; asc. SE. slope.
25.60	Crest of spur, bears irregularly E. and W.; desc. NW. slope.
39.82	Point for the ¼ sec. cor. of secs. 3 and 10. Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd. T12N R2W ¼ $\frac{S 3}{S10}$ 1962 Cor. falls on steep N. slope.
43.10	Spur, slopes irregularly W.; desc. WSW. slope.
59.60	Ravine, course NW.; thence along S. slope.
72.40	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. SE. slope.
78.00	Spur, slopes irregularly SW.
79.64	The cor. of secs. 3, 4, 9 and 10. Land, mountainous. Soil, rocky. Timber, fir, spruce, oak and pine. Undergrowth, manzanita and scrub oak.
<hr/>	
	N. 0°16' W., bet. secs. 3 and 4. Over mountainous land, through medium dense undergrowth.
3.00	Spur, slopes W.; desc. N. slope.
9.00	Ravine, course NW.; asc. SW. slope.
12.30	Crest of spur; desc. NW. slope.
19.00	Slate creek, 10 lks. wide, 1 ft. deep, excellent running water, flows irregularly SW.; asc. S. slope.
30.30	Spur, slopes SW.
40.00	Point for the ¼ sec. cor. of secs. 3 and 4. Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd. T12N R2W ¼ $\frac{S 4}{S 3}$ 1962 No bearing trees available.

CHAINS		
61.70	Spur, projects SW.; thence along SW. slope.	
67.30	Draw, course SW.; asc. SW. slope.	
71.30	Spur, slopes SW.; desc. along NW. slope.	
72.93	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the township.	
	Land, mountainous. Soil, rocky. Timber, fir and oak S 1/2 mile; none in N 1/2 mile. Undergrowth, oakbrush and manzanita.	
	From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, monumented by an iron post as described in the official record.	
	N. 0°02' W., bet. secs. 32 and 33.	
	Over moderately rolling land, through medium dense undergrowth.	
.50	Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. SW. slope.	
4.50	Small spur; desc. NW. slope.	
10.00	Desc. steep NW. slope.	
13.20	Wash, drains SSW.; asc. steep SE. slope.	
23.30	Crest of spur, bears irregularly NE. and SW.; desc. NW. slope.	
30.50	Ravine, course SW.; asc. S. slope.	
35.50	Crest of spur, slopes W.; desc. steep NNW. slope.	
40.00	Point for the ¼ sec. cor. of secs. 32 and 33.	
	Set the iron post 12 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	<p style="text-align: center;">T12N R2W ¼ S32 S33 1962</p>	
	from which	
	<p style="text-align: center;">A juniper, 6 ins. diam., bears N. 35° E., 41 lks. dist., mkd. ¼ S33 B T</p>	
	<p style="text-align: center;">A pinon pine, 8 ins. diam., bears S. 81° E., 15 lks. dist., mkd. T12N R2W ¼ S33 B T</p>	
40.40	Wash, drains W.; asc. SSW. slope.	
45.80	Along W. slope.	
48.10	Desc. NNE. slope.	
58.00	Ravine, course W.; asc. SW. slope.	

CHAINS	
60.00	Spur, slopes NW.; desc. NE. slope.
64.00	Box Canyon Wash, drains irregularly SSW.; asc. SE. slope.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T12N R2W <u>S29</u> <u>S28</u> <u>S32</u> <u>S33</u> 1962</p>
	Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
	<p>Land, moderately rolling. Soil, gravelly, rocky. Timber, scattered pinon pine and juniper. Undergrowth, catclaw, yucca, Spanish sword.</p>
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89°50' W., bet. secs. 28 and 33.
	Over moderately rolling land, through medium dense undergrowth.
4.40	Wash, 20 lks. wide, 2 ft. deep, drains S
6.40	Wash, 15 lks. wide, 2 ft. deep, drains SW.
24.90	Low spur, slopes SW.; desc. SW. slope.
37.70	Wash, 10 lks. wide, 1 ft. deep, drains NW.; asc. along NE. slope.
40.04	Point for the ¼ sec. cor. of secs. 28 and 33.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T12N R2W ¼ <u>S28</u> <u>S33</u> 1962</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
49.40	Ravine, course N.; asc. N. slope.
54.00	Saddle of spur, bears E. and W.
67.20	Desc. W. slope.
78.90	Box Canyon Wash, 60 lks. wide, course S.; asc. E. slope.
80.08	The cor. of secs. 28, 29, 32 and 33.
	<p>Land, rolling and mountainous. Soil, rocky. Timber, scattered pinon pine and juniper. Undergrowth, oak brush, cactus and laurel.</p>

42

CHAINS	
	N. 0°02' W., bet. secs. 28 and 29.
	Over rolling and mountainous land, through dense undergrowth.
4.00	Small spur, slopes E ; desc. NW. slope.
8.20	Ravine, course E.; asc. SSE. slope.
20.00	Spur, slopes SE.; desc. NW. slope.
24.30	Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. S. slope.
34.50	Crest of spur, slopes ESE.; desc. steep ENE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
	Set the iron post 24 ins. in the ground with brass cap mkd.
	T12N R2W $\frac{1}{4}$ S29 S28 1962
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
	Cor. falls on ENE. slope.
41.50	Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. SE. slope.
47.60	Desc. NE. slope.
55.00	Box Canyon Wash, 50 lks. wide, 2 ft. deep, course irregularly E.; asc. SW. slope.
73.80	Desc. NW. slope.
78.20	Wash, 30 lks. wide, 2 ft. deep, drains W.; asc. gentle slope to cor.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T12N R2W <u>S20 S21</u> S29 S28 1962
	from which
	A pinon pine 10 ins. diam. bears N. 21° E., 109 lks. dist., mkd. S21 B T
	A pinon pine 10 ins. diam. bears S. 67° E., 76 lks. dist., mkd. T12N R2W S28 B T
	Land, rolling and mountainous.
	Soil, rocky.
	Timber, scattered pinon pine.
	Undergrowth, oak brush and manzanita.

CHAINS	
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°44' W., bet. secs. 21 and 28.
	Over rolling and broken land, through dense undergrowth.
2.05	Fence, barbed wire, bears approximately N. and S.; desc. W. slope.
25.00	Ravine, course SW.; asc. SE. slope.
31.50	Thence along S. slope.
39.00	Spur, slopes S.; desc. steep W. slope.
40.01	Point for the ¼ sec. cor. of secs. 21 and 28.
	Set the iron post 6 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T12N R2W ¼ $\frac{S21}{S28}$ 1962
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor.
	Cor. falls on S. slope.
40.15	Wash, 10 lks. wide, 1 ft. deep, drains SW.; desc. along S. slope.
45.20	Ravine, course SSW.; asc. E. slope.
56.60	Spur, slopes SE.; desc. SW. slope.
70.30	Desc. steep SW. slope to cor.
80.02	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling and broken. Soil, very rocky. Timber, scattered pinon pine and juniper. Undergrowth, oak brush and cactus.
	N. 0°02' W., bet. secs. 20 and 21.
	Over rocky mountainous land, through dense undergrowth.
	Asc. SE. slope.
5.00	Crest of spur, slopes W.; desc. NW. slope.
9.30	Box Canyon Wash, 50 lks. wide, 2 ft. deep, course irregularly S.; asc. rocky SW. slope.
17.10	Ravine, course SE.; asc. SW. slope.
19.40	Spur, slopes SE.; desc. NE. slope.
27.00	Ravine, course E.; asc. SE. slope.
34.30	Spur, slopes SE.; thence along E. slope.

BOOK 4824

Subdivision of T. 12 N., R. 2 W., Arizona

44

44.

CHAINS		
39.00	Wash, drains ESE.; asc. SW. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T12N R2W $\frac{1}{4}$ S20 S21 1962	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
	Cor. falls on SW. slope.	
78.60	Ridge top, bears irregularly N. and S.; thence along W. slope.	
80.00	Point for the cor. of secs. 16, 17, 20 and 21.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T12N R2W S17 S16 S20 S21 1962	
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.	
	Cor. falls on W. slope.	
	Land, mountainous. Soil, rocky. Timber, scattered pinon pine. Undergrowth, oak brush, laurel and cactus.	
	From the cor. of secs. 15, 16, 21 and 22.	
	N. $89^{\circ}49'$ W., bet. secs. 16 and 21.	
	Over mountainous land, through dense undergrowth.	
	Desc. SW. slope.	
22.00	Box Canyon Wash, drains SW.; asc. along SE. slope.	
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T12N R2W $\frac{1}{4}$ $\frac{S16}{S21}$ 1962	
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.	
	Cor. falls on gentle S. slope.	
42.70	Rocky spur, projects SW.; begin desc. steep rocky NW. slope.	

CHAINS	
55.00	Wash, 40 lks. wide, 2 ft. deep, drains SW.; asc. E. slope.
70.00	Spur, slopes SE.; asc. SE. slope.
79.00	Crest of ridge, bears N. and S.; desc. W. slope to cor.
80.04	The cor. of secs. 16, 17, 20 and 21.
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, oak brush, manzanita and laurel.
	N. 0°02' W., bet. secs. 16 and 17.
	Over mountainous land, through dense undergrowth, no timber.
	Desc. along W. slope.
15.00	Ravine, course SW.; asc. W. slope.
23.10	Saddle of spur, slopes W.; desc. NE. slope.
35.00	Wash, 15 lks. wide, drains NW.; asc. SW. slope of spur.
39.70	Spur, slopes W for about 5 chains to end; desc. N. slope to cor.
40.00	Point for the ¼ sec. cor. of secs. 16 and 17.
	Set the iron post 24 ins. in the ground, cap mkd.
	T12N R2W ¼ S17 S16 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Cor. falls on N. slope of spur.
	Cont. desc. N. slope.
41.20	Wash, 30 lks. wide, drains W.; asc. S. slope.
49.80	Spur, slopes SW.; thence along W. slope.
55.00	Desc. steep NW. slope.
63.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. steep SE. slope.
71.20	Crest of spur; desc. gradually over NW. slope.
74.80	Wash, drains SW.; asc. small knoll.
77.30	Top of knoll; desc. N. slope to cor.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set the iron post 24 ins. in the ground, cap mkd.

CHAINS	
	<p style="text-align: center;">T12N R2W $\frac{S\ 8}{S17} \frac{S\ 9}{S16}$ 1962</p> <p>Raise a small mound of stone W. of cor.</p> <p>No bearing trees available. Cor. falls on N. slope.</p> <p>Land, mountainous. Soil, rocky. Timber, none. Undergrowth, oak brush.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°49' W., bet. secs. 9 and 16.</p> <p>Over mountainous land, through patches of timber.</p> <p>Asc. SE. slope.</p> <p>13.75 Ridge, bears NE. and SW.; thence along ridge top through dense manzanita 6 to 10 feet high.</p> <p>17.40 Leave dense undergrowth; desc. W. slope through timber.</p> <p>35.00 Leave timber, re-enter dense undergrowth of oakbrush and manzanita.</p> <p>39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T12N R2W $\frac{1}{4} \frac{S\ 9}{S16}$ 1962</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. falls on steep W. slope.</p> <p>49.00 Draw, course SW.; asc. gentle E. slope.</p> <p>53.00 Ridge, bears NE. and SW.; desc. gentle W. slope.</p> <p>74.20 Road, unimproved, leads to Golden Eagle Mine, bears NE. and SW.</p> <p>76.00 Desc. steep SW. slope.</p> <p>77.50 Small wash, drains NW.; asc. along N. slope to cor.</p> <p>79.94 The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, mountainous. Soil, rocky. Timber, fir, pinon pine and oak. Undergrowth, manzanita, scrub oak brush and laurel.</p> <hr/>

CHAINS	
	<p>N. 0°02' W., bet. secs. 8 and 9.</p>
	<p>Over broken mountainous land, through dense undergrowth.</p>
	<p>Desc. N. slope.</p>
10.80	<p>Slate Creek, 50 lks. wide, drains SW.; asc. steep S. slope.</p>
36.00	<p>Asc. gentle S. slope; enter dense manzanita.</p>
38.45	<p>Road, unimproved, bears NE. and SW.; desc. gentle N. slope.</p>
40.00	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 8 and 9.</p>
	<p>Set the iron post 16 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T12N R2W</p>
	<p style="text-align: center;">S 8^{$\frac{1}{2}$} S 9</p>
	<p style="text-align: center;">1962</p>
	<p>Raise a small mound of stone W. of cor.</p>
	<p>Cor. falls on gentle N. slope.</p>
40.65	<p>Wash, 15 lks. wide, drains SW.; asc. SW. slope.</p>
45.10	<p>Spur, slopes W.; desc. NW. slope.</p>
50.00	<p>Ravine, course W.; asc. steep SW. slope.</p>
62.00	<p>Spur, slopes SW.; desc. steep NW. slope.</p>
75.20	<p>Ravine, course SW.; asc. steep S. slope.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p>
	<p>Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T12N R2W</p>
	<p style="text-align: center;">S 5 S 4</p>
	<p style="text-align: center;">S 8 S 9</p>
	<p style="text-align: center;">1962</p>
	<p>Cor. falls on S. slope.</p>
	<p>Land, mountainous.</p>
	<p>Soil, rocky.</p>
	<p>Timber, scattered juniper.</p>
	<p>Undergrowth, manzanita, oak brush and laurel.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p>
	<p>N. 89°51' W., bet. secs. 4 and 9.</p>
	<p>Over rolling land, through dense undergrowth.</p>
	<p>Desc. W. slope.</p>
1.50	<p>Small wash, drains SW.</p>
14.00	<p>Wash, 10 lks. wide, 2 ft. deep, drains NW.; desc. along N. slope.</p>

BOOK 4824

48

Subdivision of T. 12 N., R. 2 W., Arizona

48.

CHAINS		
27.70	Slate Creek, 50 lks. wide, drains SW.; asc. SE. slope.	
39.20	Crest of spur, slopes S.; desc. SW. slope.	
39.98	Point for the ¼ sec. cor. of secs. 4 and 9.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T12N R2W $\frac{1}{4} \frac{S}{S} \frac{4}{9}$ 1962	
	Cor. No. 4 Blue Dick lode M.S. 2943, bears N. 21°15' W., 46.09 chs. dist.	
	Cor. falls on SW. slope.	
41.20	Ravine, course S.; desc. SW. slope.	
48.75	Intersect Line 2-3 Raven lode M.S. 302 at a point from which Cor. No. 3 bears S. 66° W., 1.22 chs. dist.	
50.00	Wash, 20 lks. wide, drains SE.; asc. E. slope.	
50.09	Intersect Line 3-4 Raven lode M.S. 302 at a point from which Cor. No. 3 bears S. 24° E., 0.55 chs. dist.	
60.00	Road, unimproved, bears N. and S.	
60.40	Desc. steep W. slope.	
67.00	Ravine, course S.; desc. small spur sloping S.	
74.80	Ravine, course S.; asc. along S. slope to cor.	
79.96	The cor. of secs. 4, 5, 8 and 9.	
	Land, rolling. Soil, rocky. Timber, none. Undergrowth, oak brush, manzanita and laurel.	
	N. 0°04' W., bet. secs. 4 and 5.	
	Over mountainous land, through dense undergrowth.	
	Asc. steep S. slope.	
5.00	Small spur, slopes SW.; continue asc. SW. slope.	
8.20	Small wash, drains SW.; asc. S. slope.	
29.00	Buzzard Roost Wash, drains SW.; asc. SE. slope.	
40.00	Point for the ¼ sec. cor. of secs. 4 and 5.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T12N R2W $\frac{1}{4} S 5 S 4$ 1962	

CHAINS		
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. falls on SE. slope; no bearing trees available.</p>	
60.50	Road, bladed, leads to Buzzard Mine, bears generally E. and W.	
63.70	Ridge, slopes W.; desc. gentle N. slope.	
72.70	<p>The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the township.</p> <p>Land, mountainous. Soil, rocky. Timber, juniper and fir N 1/2 mile. Undergrowth, manzanita, oak brush and laurel.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over nearly level to rolling land on mesa.</p>	
4.90	Leave mesa, desc. N. slope.	
19.00	Crest of spur, slopes E.; drift fence meanders along crest.	
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set the iron post 12 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T12N R2W 1/4 S31 S32 1962</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. falls on SE. slope.</p> <p>Asc. SE. slope.</p>	
41.00	Crest of spur, slopes E.; desc. NE. slope.	
48.00	Over nearly level land.	
66.50	Road, follows wash bottom, bears NW. and SE.	
74.00	Wash, 150 lks. wide, drains SE.	
75.30	Fence, barbed wire, bears S. 75° E. and N. 75° W.	
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T12N R2W S30 S29 S31 S32 1962</p>	

CHAINS

from which

A juniper, 10 ins. diam., bears S. 49°30' E.,
8 lks. dist., mkd. T12N R2W S32 B T

A juniper, 8 ins. diam., bears S. 28° W., 31
lks. dist., mkd. T12N R2W S31 B T

A juniper, 6 ins. diam., bears N. 10°30' W.,
30 lks. dist., mkd. T12N R2W S30 B T

Raise a mound of stone, 3 ft. base, 2 ft. high, W.
of cor.

Land, level N 1/2 mile, rolling S 1/2 mile.

Soil, sandy, gravelly.

Timber, juniper, oak, pinon pine in N 1/2 mile.

Undergrowth, laurel and oak brush in S 1/2 mile.

From the cor. of secs. 28, 29, 32 and 33.

N. 89°50' W., bet. secs. 29 and 32.

Over rolling land, through scattered timber and under-
growth.

Asc. SE. slope.

18.10 Ridge, bears N. and S.; desc. W. slope.

30.00 Small wash, drains SW.; asc. small spur.

39.50 Slate Creek Wash, 30 lks. wide, 2 ft. deep, drains S.

39.98 Point for the 1/4 sec. cor. of secs. 29 and 32.

Set the iron post 20 ins. in the ground, rock collar
to top, cap mkd.

T12N R2W

1/4 $\frac{S29}{S32}$

1962

from which

A black oak 10 ins. diam. bears S 64°30' E.,
31 lks. dist., mkd. 1/4 S32 B T

A black oak 10 ins. diam. bears S. 9° E., 39
lks. dist., mkd. T12N R2W 1/4 S32 B T

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of
cor. Cor. falls 40 lks. W. of Slate Creek.

Over a series of small spurs and washes.

71.90 Desc. SW. slope of low spur.

73.00 Enter nearly level land.

79.96 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.

Soil, sandy.

Timber, pinon pine, juniper and oak.

Undergrowth, oak brush and cactus.

CHAINS	
	N. 89°50' W., bet. secs. 30 and 31.
	Over nearly level land, through dense timber.
8.00	Pole Camp Canyon Wash, 30 lks. wide, drains SE., jeep road in wash.
18.00	Asc. Knoll.
38.00	Wash, 2 ft. deep, 15 lks. wide, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
	Set the iron post 24 ins. in the ground, cap mkd.
	$\begin{array}{r} T12N R2W \\ \frac{1}{4} \frac{S30}{S31} \\ 1962 \end{array}$
	from which
	A pinon pine 14 ins. diam. bears S. 31°15' E., 50 lks. dist., mkd. T12N R2W $\frac{1}{4}$ S31 B T
	A pinon pine 10 ins. diam. bears N. 53°30' W., 53 lks. dist., mkd. T12N R2W $\frac{1}{4}$ S30 B T
	Raise a mound of stone, 4 ft. base, 3 ft. high, N. of corner.
	Cor. falls 30 lks. E. of wash.
40.30	Wash, 2 ft. deep, 10 lks. wide, drains E.
43.50	Asc. broken E. slope.
51.00	Top of rim, bears NE. and SW.
60.71	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the township, monumented by an iron post as described in the official record.
	Land, level and broken. Soil, clay. Timber, pinon pine, juniper. Undergrowth, oak brush and cactus.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over rolling land, through scattered timber.
22.30	Leave nearly level land; asc. SW. slope.
34.30	Spur, slopes SSE.; thence along E. slope.
38.70	Small wash, drains NW.; asc. gentle SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.
	Set the iron post 24 ins. in the ground, cap mkd.

52

CHAINS

T12N R2W

$\frac{1}{4}$
S30 | S29
1962

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of corner. Cor. falls on gentle S. slope.

48.00 Asc. W. slope of ridge bearing irregularly S.; thence over series of low spurs and ravines with general W. drainage.

79.85 Wash, 10 lks. wide, 2 ft. deep, drains SW.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set the iron post 24 ins. in the ground, brass cap mkd.

T12N R2W
S19 | S20
S30 | S29
1962

from which

A juniper 15 ins. diam. bears S. 46°45' E.,
49 lks. dist., mkd. T12N R2W S29 B T

A juniper 10 ins. diam. bears N. 76° W., 44
lks. dist., mkd. S19 B T

Land, rolling.

Soil, light clay and rocky.

Timber, juniper and pinon pine.

Undergrowth, laurel, manzanita and oak brush.

From the cor. of secs. 20, 21, 28 and 29.

N. 89°57' W., bet. secs. 20 and 29.

Over mountainous land, through scattered timber and undergrowth.

Over level, rocky land.

3.80 Desc. W. slope.

5.00 Box Canyon Wash, 50 lks. wide, drains S.; asc. NE. slope.

16.60 Ridge, bears N. and SE.; desc. along gentle S. slope.

31.00 Slope changes to NW.

39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.

Set the iron post 24 ins. in the ground, cap mkd.

T12N R2W
 $\frac{1}{4}$ S20
S29
1962

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

CHAINS	
	Cor. falls on NW. slope.
46.50	Slate Creek Wash, 90 lks. wide, drains S.; asc. steep E. slope.
74.10	Ridge, bears N. and S.; desc. W slope.
79.90	Wash, 10 lks. wide, 2 ft. deep, drains SW.
79.98	The cor. of secs. 19, 20, 29 and 30.
	Land, mountainous. Soil, rocky. Timber, scattered pinon pine and juniper. Undergrowth, laurel and oak brush.
<hr/>	
	N. 89°45' W., bet. secs. 19 and 30.
	Over mountainous terrain by triangulation, topography scaled from U.S.G.S. quadrangle sheet.
	Asc. S. slope.
5.00	Spur, slopes S.; desc. W. slope.
13.00	Ravine, course SW.; asc. SE. slope.
20.00	Spur, slopes SW.; desc. W. slope.
30.00	Wash, drains S.; asc. over series of clayish knolls.
40.00	Point for the ¼ sec. cor. of secs. 19 and 30.
	Set the iron post 24 ins. in the ground, cap mkd.
	T12N R2W ¼ $\frac{S19}{S30}$ 1962
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.
	Cor. falls on E. slope.
	Asc. gentle E. slope.
49.90	Ridge, bears N. and S.; desc. W. slope.
51.90	Road, bladed, bears N. and S.
53.00	Pole Camp Canyon Wash, 20 lks. wide, 3 ft. deep, drains South.
60.68	The cor. of secs. 19, 24, 25 and 30, monumented by an iron post as described in the official record.
	Land, broken, mountainous. Soil, rocky. Timber, scattered pinon pine and juniper. Undergrowth, manzanita, oak brush and laurel.
<hr/>	
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.

54

CHAINS

Asc. SE. slope through dense timber.

10.70 Ridge, bears NE. and SW.; desc. steep NE. slope.

19.00 Ravine, course E.; asc. SE. slope.

25.00 Spur, slopes E.; desc. NE. slope.

28.20 Ravine, course E.; asc. S. slope.

32.20 Spur, slopes SE.; desc. N. slope.

36.60 Ravine, course NE.; asc. steep S. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

Set the iron post 24 ins. in the ground, cap mkd.

T12N R2W
 $\frac{1}{4}$
S19 | S20
1962

from which

A pinon pine 6 ins. diam. bears S. 78° E., 64
lks. dist., mkd. $\frac{1}{4}$ S20 B T

A pinon pine 6 ins. diam. bears N. 37° W., 7
lks. dist., mkd. $\frac{1}{4}$ S19 B T

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W.
of cor.

Cor. falls on S. slope.

44.00 Spur, slopes E.; over series of small spurs.

63.00 Wash, drains E.; asc. SW. slope.

77.80 Crest of spur, slopes SE.; desc. steep NE. slope to cor.

80.00 Point for the cor. of secs. 17, 18, 19 and 20.

Set the iron post 10 ins. in the ground to bedrock,
mound with stone to top, cap mkd.

T12N R2W
S18 | S17
S19 | S20
1962

Raise a mound of stone, 3 ft. base, 2½ ft. high, W.
of cor.

Cor. falls on NE. slope.

Land, rolling and mountainous.
Soil, rocky.
Timber, patches of pinon pine and juniper.
Undergrowth, manzanita, laurel and oak brush.

From the cor. of secs. 16, 17, 20 and 21.

N. 89°55' W., bet. secs. 17 and 20.

CHAINS	
	Over mountainous land, through dense undergrowth. Desc. W. slope.
17.50	Ravine, course SW.; asc. W. slope.
36.80	Ridge, bears N. and S.; over nearly level ridge top.
39.99	Point for the ¼ sec. cor. of secs. 17 and 20. Set the iron post 18 ins. in the ground to bedrock, collar of stone to top, cap mkd. T12N R2W ¼ $\frac{S17}{S20}$ 1962 Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor. No bearing trees available.
42.30	Desc. SW. slope.
61.20	Slate Creek Wash, 35 lks. wide, drains S.; asc. steep NE. slope.
76.40	Slope changes to N.
79.98	The cor. of secs. 17, 18, 19 and 20. Land, mountainous. Soil, rocky. Timber, scattered pinon pine and juniper. Undergrowth, oak brush and laurel 5 to 10 ft. high.
	N 89°46' W., bet. secs. 18 and 19. Over mountainous land, through scattered timber and undergrowth. Asc. gentle E. slope.
7.90	Point selected for witness point on the line bet. secs. 18 and 19. Set the iron post 22 ins. in the ground, cap mkd. T12N R2W WP $\frac{S18}{S19}$ 1962 Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the iron post.
8.15	Road, unimproved, bears NE. and SW.; desc. gentle W. slope.
10.80	Wash, 15 lks. wide, 1 ft. deep, drains irregularly S.; asc. E. slope.
25.80	Low ridge, slopes to SW.; desc. W. slope.
37.50	Wash, 20 lks. wide, 2 ft. deep, drains SW.; asc. gentle E. slope.

56

CHAINS

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
 Set the iron post 24 ins. in the ground, cap mkd.
- T12N R2W
 $\frac{1}{4}$ $\frac{S18}{S19}$
 1962
- from which
- A pinon pine 12 ins. diam. bears N. $24^{\circ}30'$ E.,
 46 lks. dist., mkd. T12N R2W $\frac{1}{4}$ S18 B T
- A pinon pine 8 ins. diam. bears S. $41^{\circ}30'$ E.,
 89 lks. dist., mkd. T12N R2W $\frac{1}{4}$ S19 B T
- Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, N.
 of cor.
- Cor. falls on NE. slope.
- 49.50 Ridge, bears NE. and SW.; desc. W. slope.
- 60.62 The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of
 the township, monumented by an iron post as described
 in the official record.
- Land, mountainous.
 Soil, rocky, gravelly.
 Timber, pinon pine, juniper.
 Undergrowth, oak brush and laurel.
-
- From the cor. of secs. 17, 18, 19 and 20.
 N. $0^{\circ}03'$ W., bet. secs. 17 and 18.
- Over mountainous land, through scattered timber and
 undergrowth.
- Asc. along NE. slope.
- 24.30 Road, unimproved, bears NE. and SW.
- 35.40 Fence, barbed wire, bears N. 15° W. and S. 15° E.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.
 Set the iron post 24 ins. in the ground, with brass
 cap mkd.
- T12N R2W
 $\frac{1}{4}$
 S18 | S17
 1962
- Raise a mound of stone, 3 ft. base, 2 ft. high, W.
 of cor.
- Cor. falls on E. slope between road and barbed wire
 fence.
- 42.80 Desc. abrupt N. slope; rim bears NE. and W.
- 51.00 Draw, course W.; asc. over series of spurs sloping W.

CHAINS	
69.90	Ridge, slopes W.; desc. along W. slope.
79.60	Wash, 15 lks. wide, drains NW.; asc. SW. slope to cor.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set the iron post 24 ins. in the ground, cap mkd.
	T12N R2W $\frac{S\ 7}{S18} \frac{S\ 8}{S17}$ 1962
	Land, mountainous. Soil, rocky. Timber, pinon pine and juniper. Undergrowth, oak brush and manzanita.
	From the cor. of secs. 8, 9, 16 and 17.
	N. 89°56' W., bet. secs. 8 and 17.
	Over mountainous land, distance by triangulation; topography scaled from U.S G.S. quadrangle sheet.
4.50	Desc. NW. slope.
7.00	Slope changes to W.
21.00	Slate Creek, 80 lks. wide, 2 ft. deep, drains irregularly SW.; asc. SE. slope.
32.15	Long spur, slopes SW.; bladed road follows crest of spur.
35.10	Desc. gradually along N. slope.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
	Set the iron post 24 ins. in the ground, cap mkd.
	T12N R2W $\frac{1}{4} \frac{S\ 8}{S17}$ 1962
	Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of cor.
	Cor. falls on N. slope 150 lks. N. of small bare knoll.
41.00	Desc. NW. slope.
57.00	Ravine, course NW.; asc. over small spur sloping NW.
65.00	Wash, drains NW.; asc. NE. slope.
73.80	Spur, slopes N.; desc. steep NW. slope.
78.60	Wash, drains SW.; asc. over small spur, slopes SW.
79.98	The cor. of secs. 7, 8, 17 and 18.
	Land, mountainous and rolling. Soil, rocky. Timber, scattered pinon pine and juniper. Undergrowth, manzanita, laurel, oak brush and cactus.

58

CHAINS

N. 89°45' W., bet. secs. 7 and 18.

Over mountainous land, through dense timber.

Desc. along W slope.

4.30 Wash, 15 lks. wide, drains NW.; over series of small spurs sloping to NW.

31.10 Ravine, course NW.; asc. steep NE. slope.

33.30 Spur, bears SE. and W.; desc. W. slope.

40.00 Point for the ¼ sec. cor. of secs. 7 and 18.

Set the iron post 24 ins. in the ground, cap mkd.

T12N R2W

¼ $\frac{S 7}{S 18}$

1962

from which

A pinon pine 6 ins. diam. bears S. 32° W ,
34 lks. dist., mkd. ¼ S18 B T

A pinon pine 6 ins. diam. bears N. 43°15' W.,
16 lks. dist., mkd. ¼ S7 B T

Cor. falls on W. slope of spur.

44.70 Wash, 30 lks. wide, 2 ft. deep, drains NW.; asc. E. slope.

51.90 Ridge, bears NW. and SE.

52.60 Desc. W. slope to cor.

60.47 The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township, monumented by an iron post as described in the official record.

Land, rolling.

Soil, rocky.

Timber, scattered pinon pine.

Undergrowth, oak brush and manzanita.

From the cor. of secs. 7, 8, 17 and 18.

N. 0°03' W., bet. secs. 7 and 8.

Asc. steep SW. slope.

4.00 Crest of spur, slopes W.; desc. NW. slope.

8.90 Spur, projects NW.; desc. N. slope.

12.00 Wash, 30 lks. wide, drains NW.; asc. SW. slope.

21.20 Crest of spur, slopes NW.; desc. NW. slope.

30.00 Ravine, course SW.; asc. steep SE. slope.

35.50 Spur, projects SW.; desc. steep NW. slope to cor.

40.00 Point for the ¼ sec. cor. of secs. 7 and 8.

CHAINS

Set the iron post 24 ins. in the ground, cap mkd.

T12N R2W

$\frac{1}{4}$
S 7 | S 8
1962

Cor. falls on steep NW. slope.

45.00 Buzzard Roost Wash, drains SW.; asc. steep SE. slope.

70.20 Crest of spur, slopes SW.; asc. SW. slope to cor.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set the iron post 22 ins. in the ground, cap mkd.

T12N R2W

S 6 | S 5
S 7 | S 8
1962

No bearing trees available.

Land, rolling and mountainous.

Soil, rocky.

Timber, scattered pinon pine and juniper.

Undergrowth, oak brush and manzanita.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°56' W., bet. secs. 5 and 8.

Over mountainous land by triangulation, topography scaled from U.S.G.S. quadrangle sheet.

3.50 Crest of spur, slopes SW.; desc. NW. slope.

10.00 Buzzard Roost Wash, drains irregularly SW.; asc. steep SW. slope.

17.00 Ravine, course SE.; asc. E. slope.

19.00 Crest of spur, slopes SE.; desc. over series of small spurs and washes.

37.00 Wash, drains S.; asc. E. slope to cor.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

Set the iron post 24 ins. in the ground, cap mkd.

T12N R2W

$\frac{1}{4}$ S 5
S 8
1962

from which

Cor. No. 4 Jersey Lilly lode M.S. 1169 bears
N. 43°31' W., 20.59 chs. dist.

45.00 Road, graded, bears irregularly NW. and SE. along crest of spur.

60

CHAINS	
48.00	Desc. NW. slope.
51.00	Over series of spurs and washes with general drainage S.
78.10	Crest of spur, slopes SW.; desc. SW. slope to cor.
80.04	The cor. of secs. 5, 6, 7 and 8.
	Land, mountainous. Soil, rocky. Timber, scattered pinon pine and juniper. Undergrowth, dense manzanita, oak brush, laurel and cactus.
	N. 89°59' W., bet. secs. 6 and 7.
	Over mountainous land, through dense undergrowth.
	Desc. SW. slope.
2.00	Small ravine, course S.; asc. E. slope.
22.10	Main wash, 40 lks. wide, 3 ft. deep, drains SW.; asc. SE. slope.
35.90	Crest of spur, slopes SW.; asc. W. slope.
39.00	Ravine, course S.; asc. SE. slope.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7.
	Set the iron post 22 ins. in the ground, cap mkd.
	T12N R2W $\frac{1}{4} \frac{S 6}{S 7}$ 1962
	Cor. falls on SE. slope.
45.00	Ravine, course S.; asc. SE. slope.
52.00	Crest of spur, slopes SW.; over nearly level land.
57.00	Small ravine, course S.; asc. steep E. slope.
60.30	Crest of spur, slopes S.
60.34	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township, monumented by an iron post as described in the official record.
	Land, rolling and mountainous. Soil, rocky. Timber, scattered juniper and pinon pine. Undergrowth, oak brush, manzanita and cactus.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°08' W., bet. secs. 5 and 6.
	Over rolling land, through dense undergrowth.
	Asc. SW. slope.

CHAINS	
1.70	Spur, projects W.; desc. NW. slope.
25.00	Wash, 20 lks. wide, 2 ft. deep, drains W.; asc. S. slope.
30.20	Crest of spur, bears E. and W.; desc. NW. slope.
35.00	Ravine, course SW.; asc. SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	Set the iron post 18 ins. in the ground to bedrock, collar of stone to top, cap mkd.
	T12N R2W $\frac{1}{4}$ S 6 S 5 1962
	Cor. falls on SW. slope.
63.20	Crest of ridge, bears E. and W.; trail follows ridge top; thence over nearly flat ridge top.
71.50	Begin desc. N. slope.
72.58	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township.
	Land, rolling and mountainous. Soil, rocky. Timber, sparse juniper. Undergrowth, oak brush and manzanita 5 to 10 ft. high.
	<hr/> General Description <hr/>
	The area included in this survey lies entirely within the Prescott National Forest. The west boundary of the township constitutes a portion of the west boundary of the National Forest.
	The area covered by this survey is generally mountainous, and slopes southward. Elevations vary from 7500 feet above sea level at Mt. Tritle, which is on the north boundary, to 4100 feet above sea level in section 32.
	The northern portion of the township and the area west of Slate Creek Wash is forested with patches of commercial trees such as fir, cedar, spruce and pine. The southern portion is forested with scattered non-commercial trees such as mesquite, juniper and pinon pine. Undergrowth generally consists of oak brush, mountain laurel, manzanita and some desert plants.
	There are no settlers living within the area. The improvements mainly consist of timber access roads and roads leading to early day mining ventures. Some small tract subdivision surveys within patented mining claims have been completed in the north portion of section 1. The present name of the subdivision is "Mountain Pine Acres." Most of the springs as shown on the U.S. Geological Survey Mt. Union Quadrangle no longer carry any surface water. The township has been extensively mined for gold prior to 1900. There is no evidence of active mining now.

BOOK 4824

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel R. Bauer	Front Chainman
Gordon H. Black	Axeman
Jack R. Bowker	Instrumentman
Gary P. Bowler	Flagman
Henry A. Guerrero	Axeman
Michael J. Lissy	Cornerman
Wallace R. Ott	Instrumentman
Gary W. Rutledge	Notekeeper
Tom D. Carter	Flagman

63

BOOK 4824

CERTIFICATE OF SURVEY

I, Leonard W. Murphy, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of November, 1958, I have dependently resurveyed a portion of the south boundary of Township 12 1/2 North, Range 2 West, and surveyed the north boundary and subdivisions of Township 12 North, Range 2 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 18, 1963
(Date)

Leonard W. Murphy
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date OCT 19 1965
SEP 6 1968

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 12 1/2 North, Range 2 West, and the survey of the north boundary and subdivisions of Township 12 North, Range 2 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Leonard W. Murphy, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 27 1968
(Date)

R. E. Brown
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)