

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

BOUNDARIES

and

SUBDIVISIONAL LINES

of

Township 11 North, Range 27 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer, Cadastral Surveyor

Robert F. Johnson, Surveying Technician

Under special instructions dated April 21, 19 64, which provided for the survey

included under Group Number 413, approved April 21, 1964

and assignment instructions dated June 23, 19 66.

Survey commenced July 14, 19 66

Survey completed August 5, 19 66

11A

# BOOK 4831 INDEX DIAGRAM

Township 11 North, Range 27 East

21 16 6 58	20 5 48	19 4 41	18 3 35	18 2 28	17 1 11
57 15 7 56	57 8 47	48 9 40	41 10 34	34 11 27	28 12 10
55 14 18 54	55 17 46	46 16 39	40 15 32	33 14 26	26 13 9
54 14 19 52	53 20 44	45 21 38	39 22 31	32 23 24	25 24 8
52 13 30 51	51 29 43	44 28 36	37 27 30	31 26 23	24 25 7
50 12 31 49	50 32 42	43 33 35	36 34 29	29 35 21	22 36 7
5 5	5 5	4 4	3 3	2 2	1 1

18

Township 11 North, Range 27 East  
Gila and Salt River Meridian, Arizona

CHAINS

The boundaries were surveyed in 1875 by C. B. Foster. The boundaries were resurveyed and the subdivisional lines surveyed in 1882 by A. P. Johnson.

The following notes are those of a dependent resurvey of the boundaries and subdivisional lines of Township 11 North, Range 27 East, Gila and Salt River Meridian, Arizona, designed to restore the corners in their true original location according to the best available evidence.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated April 21, 1964.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of Township 11 North, Range 27 East, is: Latitude, 34°17'56" North, and Longitude, 109°24'45" West, as scaled from U.S.G.S. control diagram, "Saint Johns," Arizona; New Mexico.

The magnetic declination was found to be 14° East.

Dependent Resurvey, South Boundary,  
Township 11 North, Range 27 East

Reestablishment of the Survey  
Executed by A. P. Johnson in 1882

The cor. of Tps. 10 and 11 N., Rs. 27 and 28 E., monumented by a lava stone, 14 x 8 x 8 ins., mkd. with 6 notches on each side, firmly set with a mound of stone North.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T11N	
R27E	R28E
S 36	S 31
S 1	S 6
T10N	

1966

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

The cor. is located 01 lk. West of old N-S. fence line.

Topography as adjusted from random lines.

N. 89°53' W., bet. secs. 1 and 36.

Over gently rolling land.

BOOK 4831

2.

Dep. Resurvey, South Bdy., T. 11 N., R. 27 E., Arizona

CHAINS		
37.80	Track road, bears N. 25° E. and S. 25° W.	
40.16	<p>The ¼ sec. cor. of secs. 1 and 36, monumented by a lava stone, 12 x 10 x 10 ins., firmly set and plainly mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 36}{S\ 1}</math>                      T10N                      1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°15' W., beginning new measurement.</p> <p>Over gently rolling land.</p>	
13.70	Draw, drains NE.	
40.31	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 4 ins. in the ground, over an "X" chiseled in solid bedrock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{S\ 35}{S\ 2}</math>   <math>\frac{S\ 36}{S\ 1}</math>                      T10N                      1966</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p> <hr/> <p>N. 89°15' W., bet. secs. 2 and 35.</p> <p>Over gently rolling land.</p>	
1.00	Barbed wire fence, bears N. and S.	
40.31	<p>The ¼ sec. cor. of secs. 2 and 35, monumented by a lava stone, 12 x 10 x 9 ins., firmly set, dimly mkd.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 35}{S\ 2}</math>                      T10N                      1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p>	

CHAINS							
<p>24.40</p> <p>40.33</p>	<p>N. 89°48' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>Track road, bears SE. and NW.</p> <p>The cor. of secs. 2, 3, 34 and 35, monumented by a lava stone, 18 x 10 x 8 ins., firmly set, mkd. with 2 notches on E. face and 4 notches on W. face, with a mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T11N</td> <td>R27E</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> </table> <p>T10N</p> <p>1966</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	T11N	R27E	S 34	S 35	S 3	S 2
T11N	R27E						
S 34	S 35						
S 3	S 2						
<p>8.80</p> <p>40.35</p>	<p>N. 89°02' W., bet. secs. 3 and 34.</p> <p>Over gently rolling land.</p> <p>Small draw, drains N. 70° E.</p> <p>The ¼ sec. cor. of secs. 3 and 34, monumented by a lava stone, 6 x 5 x 4 ins., firmly set, mkd. ¼ on W. face</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T11N</td> <td>R27E</td> </tr> <tr> <td>¼ S 34</td> <td></td> </tr> <tr> <td>S 3</td> <td></td> </tr> </table> <p>T10N</p> <p>1966</p> <p>from which</p> <p style="padding-left: 40px;">A windmill bears N. 0°14' W., 18.90 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>	T11N	R27E	¼ S 34		S 3	
T11N	R27E						
¼ S 34							
S 3							
<p>40.04</p>	<p>S. 89°39' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>The cor. of secs. 3, 4, 33 and 34, monumented by a lava stone, 18 x 8 x 8 ins., firmly set, mkd. with 3 notches on E. face and 3 notches on the W. face, with mound of stone W.</p>						

BOOK 4831

4.

Dep. Resurvey, S. Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
11.80 40.24  67.00 79.50 80.49	<p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">                     T11N R27E  <u>S 33   S 34</u>                      S 4   S 3                      T10N                      1966                 </p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p> <hr/> <p>N. 89°42' W., bet. secs. 4 and 33.</p> <p>Over gently rolling land.</p> <p>Track road, bears NE. and SW.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 33, at proportionate dist.; unable to find any remaining evidence of orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">                     T11N R27E  <math>\frac{1}{4}</math> <u>S 33</u>                      S 4                      T10N                      1966                 </p> <p>Raise a mound of stone N. of the cor.</p> <p>Asc. over rolling land.</p> <p>Small wash, drains N. 10° E.</p> <p>The cor. of secs. 4, 5, 32 and 33, monumented by a lava stone, 14 x 12 x 8 ins., firmly set, mkd. with 4 notches on E. face and 2 notches on W. face.</p> <p>At the cor. point,</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">                     T11N R27E  <u>S 32   S 33</u>                      S 5   S 4                      T10N                      1966                 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>

Dep. Resurvey, S. Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
<p>15.10 25.60 32.60 40.74</p>	<p>N. 89°57' W., bet. secs. 5 and 32.</p> <p>Asc. along N. slope.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains N.</p> <p>Spur, slopes N.</p> <p>Spur, slopes N. 20° W.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 32, monumented by a lava stone, 18 x 12 x 6 ins., firmly set in a small mound of stone, mkd. <math>\frac{1}{4}</math> on W. face.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> <math>\frac{S\ 32}{S\ 5}</math> T10N 1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p>
<p>1.20 9.10 15.90 39.65 40.44</p>	<p>N. 89°56' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>Draw, drains N.</p> <p>Spur, slopes S., desc. over W. slope.</p> <p>Track road, bears N. and S.</p> <p>Barbed wire fence, bears N. and S.</p> <p>The cor. of secs. 5, 6, 31 and 32, monumented by a lava stone, 12 x 8 x 8 ins., firmly set in mound of stone, mkd. with 1 notch on E. face and 5 notches on W. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{S\ 31\   S\ 32}{S\ 6\   S\ 5}</math> T10N 1966</p> <p>Land, rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
<p>34.30</p>	<p>N. 89°26' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land.</p> <p>Track road, bears N. and S.</p>

BOOK 4831

6.

Dep. Resurvey, S. Bdy., T. 11 N., R. 27 E., Arizona

CHAINS  
40.16

The  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, monumented by a lava stone, 12 x 6 x 6 ins., firmly set, mkd.  $\frac{1}{4}$  on W. face, with mound of stone N.

At the corner point

Set the iron post 18 ins. in the ground, brass cap mkd.

T11N R27E

$\frac{1}{4}$   $\frac{S\ 31}{S\ 6}$

T10N

1966

from which

A windmill, bears N. 20°49' E., 30.24 chs. dist.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone N. of the cor.

---

N. 85°56' W., beginning new measurement.

Over gently rolling land.

9.30 Track road, bears N. 10° E. and S. 10° W.

41.00 Track road, bears N. 70° E. and S. 70° W.

44.22 The cor. of Tps. 10 and 11 N., Rs. 26 and 27 E., monumented by a lava stone, 14 x 10 x 10 ins., firmly set, mkd. with 6 notches on each side with a scattered mound of stone around the cor.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T11N  
R26E | R27E  
 $\frac{S\ 36}{S\ 1}$  |  $\frac{S\ 31}{S\ 6}$

T10N

1966

Deposit the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

Land, gently rolling.

Soil, sandy loam.

No timber; undergrowth, grama and bunch grass.



CHAINS	Dependent Resurvey, East Boundary, Township 11 North, Range 27 East
	<p>Reestablishment of the Survey Executed by A. P. Johnson in 1882</p>
	<p>From the Tp. cor. of Tps. 10 and 11 N., Rs. 27 and 28 E.</p>
	<p>N. 0°04' E., bet. secs. 31 and 36.</p>
	<p>Over gently rolling land.</p>
24.10	<p>Track road, bears SE. and NW.</p>
40.61	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>
	<p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T11N R27E   R28E       ¼ S 36   S 31</p>
	<p style="text-align: center;">1966</p>
60.80	<p>Barbed wire fence, bears E. and W.</p>
81.22	<p>The cor. of secs. 25, 30, 31 and 36, monumented by a lava stone, 12 x 10 x 5 ins., firmly set, mkd. with 5 notches on the N. face and 1 notch on the S. face.</p>
	<p>At the corner point</p>
	<p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T11N R27E   R28E S 25   S 30 S 36   S 31</p>
	<p style="text-align: center;">1966</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
	<p>N. 0°10' W., bet. secs. 25 and 30.</p>
	<p>Over gently rolling land.</p>
4.90	<p>Track road, bears N. 50° W. and S. 50° E.</p>
12.00	<p>Low ridge, bears E. and W.</p>
18.50	<p>Track road, bears E. and W.</p>
40.74	<p>The ¼ sec. cor. of secs. 25 and 30, monumented by a lava stone, 12 x 8 x 5 ins., firmly set in a mound of stone, mkd. ¼ on W. face.</p>

BOOK 4831

8.

Dep. Resurvey, East Bdy., T. 11 N., R. 27 E., Arizona

CHAINS		
40.64	<p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E <math>\frac{1}{2}</math> S 25 S 30 1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°23' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>The cor. of secs. 19, 24, 25 and 30, monumented by a lava stone, 24 x 14 x 18 ins., firmly set, mkd. with 2 notches on S. face and 4 notches on N. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E S 24 S 19 S 25 S 30 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Deposit the orig. cor. stone in the mound West.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	
21.50 35.30 40.62	<p>N. 0°38' E., bet. secs. 19 and 24.</p> <p>Over gently rolling land.</p> <p>Ridge, bears E. and W.</p> <p>Track road, bears NE. and SW.</p> <p>Point for the <math>\frac{1}{2}</math> sec. cor. of secs. 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E <math>\frac{1}{2}</math> S 24 S 19 1966</p> <p>Raise a mound of stone W. of the cor.</p>	

Dep. Resurvey, E. Bdy., T. 11 N., R. 27 E., Arizona

CHAINS																			
52.00	Track road, bears E. and W.																		
80.00	Track road, bears E. and W.																		
81.24	<p>The cor. of secs. 13, 18, 19 and 24, monumented by a lava stone, 14 x 12 x 6 ins., firmly set in a mound of stone, mkd. with 3 notches on S. face and 3 notches on N. face.</p> <p>At the corner point Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E S 13 S 18 S 24 S 19 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, native grass.</p>																		
	<p>N. 0°34' E., bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p> <tr> <td data-bbox="267 1370 422 1405">8.90</td> <td data-bbox="422 1370 1356 1405">Track road, bears S. 60° E. and N. 60° W.</td> <td data-bbox="1356 1370 1502 1405"></td> </tr> <tr> <td data-bbox="267 1432 422 1467">28.70</td> <td data-bbox="422 1432 1356 1467">Rocky rim, bears N. 50° E. and S. 50° W., desc. over rolling land, through widely scattered timber.</td> <td data-bbox="1356 1432 1502 1467"></td> </tr> <tr> <td data-bbox="267 1494 422 1529">29.70</td> <td data-bbox="422 1494 1356 1529">Track road, bears E. and W.</td> <td data-bbox="1356 1494 1502 1529"></td> </tr> <tr> <td data-bbox="267 1556 422 1591">38.60</td> <td data-bbox="422 1556 1356 1591">Small draw, drains N. 30° E.</td> <td data-bbox="1356 1556 1502 1591"></td> </tr> <tr> <td data-bbox="267 1618 422 1653">40.61</td> <td data-bbox="422 1618 1356 2612"> <p>The ¼ sec. cor. of secs. 13 and 18, monumented by a lava stone, 12 x 6 x 5 ins., firmly set, mkd. ¼ on W. face.</p> <p>At the corner point Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E ¼ S 13 S 18 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°36' E., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered cedar.</p> </td> <td data-bbox="1356 1618 1502 2612"></td> </tr> <tr> <td data-bbox="267 2486 422 2521">18.70</td> <td data-bbox="422 2486 1356 2521">Desc. steep NW. slope.</td> <td data-bbox="1356 2486 1502 2521"></td> </tr>	8.90	Track road, bears S. 60° E. and N. 60° W.		28.70	Rocky rim, bears N. 50° E. and S. 50° W., desc. over rolling land, through widely scattered timber.		29.70	Track road, bears E. and W.		38.60	Small draw, drains N. 30° E.		40.61	<p>The ¼ sec. cor. of secs. 13 and 18, monumented by a lava stone, 12 x 6 x 5 ins., firmly set, mkd. ¼ on W. face.</p> <p>At the corner point Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E ¼ S 13 S 18 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°36' E., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered cedar.</p>		18.70	Desc. steep NW. slope.	
8.90	Track road, bears S. 60° E. and N. 60° W.																		
28.70	Rocky rim, bears N. 50° E. and S. 50° W., desc. over rolling land, through widely scattered timber.																		
29.70	Track road, bears E. and W.																		
38.60	Small draw, drains N. 30° E.																		
40.61	<p>The ¼ sec. cor. of secs. 13 and 18, monumented by a lava stone, 12 x 6 x 5 ins., firmly set, mkd. ¼ on W. face.</p> <p>At the corner point Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E ¼ S 13 S 18 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°36' E., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered cedar.</p>																		
18.70	Desc. steep NW. slope.																		

BOOK 4831

10.

Dep. Resurvey, East Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
24.70	Wash, 15 lks. wide, 2 ft. deep, drains N. 20° E., thence asc. SE. slope.
32.50	Spur, slopes N. 30° E., desc. N. slope.
40.40	<p>The cor. of secs. 7, 12, 13 and 18, monumented by a lava stone, 12 x 11 x 5 ins., firmly set, mkd. with 4 notches on S. face and 2 notches on N. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R27E R28E <u>S 12   S 7</u> <u>S 13   S 18</u></p> <p>1966</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, widely scattered cedars. Undergrowth, native grass.</p>
	<p>N. 0°25' W., bet. secs. 7 and 12.</p> <p>Over rolling land and through widely scattered timber.</p> <p>2.50 Wash, 15 lks. wide, 1 ft. deep, drains N. 80° E.</p> <p>2.90 Barbed wire fence, bears S. 70° E. and N. 70° W.</p> <p>5.60 Low spur, slopes W., desc. N. slope.</p> <p>7.90 Wash, 10 lks. wide, 1 ft. deep, drains W., asc. over rolling land.</p> <p>23.20 Wash, 15 lks. wide, 2 ft. deep, drains SE.</p> <p>31.60 Top of ascent, thence over gently rolling land which has been railed over.</p> <p>40.22 The ¼ sec. cor. of secs. 7 and 12, monumented by an old post, 3 ft. long, 3 ins. diam., firmly set in a mound of stone; no marks legible.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R27E R28E <u>S 12   S 7</u> <u>¼</u></p> <p>1966</p> </div> <p>Set the orig. cor. post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dep. Resurvey, East Bdy., T. 11 N., R. 27 E., Arizona

CHAINS		
	<p>N. 2°12' E., beginning new measurement.</p> <p>Over gently rolling land, through railed area.</p> <p>1.30 Track road, bears NE. and SW.</p> <p>18.80 Rim, bears NE. and SW., desc. steep NW. slope; leave railed area.</p> <p>37.90 Wash, 40 lks. wide, 1 ft. deep, drains N. 60° E.</p> <p>40.56 The cor. of secs. 1, 6, 7 and 12, monumented by a boulder stone, 12 x 12 x 10 ins., firmly set in a mound of stone, mkd. with 5 notches on S. face, and 1 notch on N. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E S 1   S 6 S 12   S 7 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, grama and bunch grass.</p>	
	<p>N. 0°23' E., bet. secs. 1 and 6.</p> <p>Over rolling land, through widely scattered timber.</p> <p>6.80 Wash, 20 lks. wide and 2 ft. deep, drains S. 80° E.</p> <p>41.46 The 1/4 sec. cor. of secs. 1 and 6, monumented by an old post, 3 ft. long, 3 ins. diam., firmly set in a mound of stone. I accept this as the best evidence of the orig. cor. position. (Record called for a mkd. sandstone 16 x 9 x 4 ins.)</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E R28E 1/4 S 1   S 6 1966</p> <p>Set the old cor. alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>	

BOOK 4831

12.

Dep. Resurvey, West Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
	<p>N. 4°05' E., beginning new measurement.</p> <p>Over rolling land, through widely scattered timber.</p> <p>15.90 Wash, 15 lks. wide, 4 ft. deep, drains E.</p> <p>31.30 Wash, 20 lks. wide, 3 ft. deep, drains E.</p> <p>39.70 The cor. of Tps. 11 and 12 N., Rs. 27 and 28 E., monumented by a lava stone, 15 x 12 x 10 ins., firmly set, mkd. with 6 notches on each face, with old mound of earth and stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R27E R28E S 36   S 31 S 1   S 6 T11N</p> <p>1966</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone S. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, grama and bunch grass.</p>
	<p>Dependent Resurvey, West Boundary, Township 11 North, Range 27 East</p>
	<div style="text-align: center;"> <p>Reestablishment of the Survey Executed in 1882 by A. P. Johnson</p> <hr/> </div> <p>From the Tp. cor. of Tps. 10 and 11 N., Rs. 26 and 27 E.</p> <p>N. 0°51' E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p> <p>19.40 Track road, bears N. 85° E. and S. 85° W.</p> <p>21.20 Asc. over rolling land.</p> <p>40.22 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R26E R27E S 36   S 31 1/4</p> <p>1966</p> </div>

Dep. Resurvey, West Bdy., T. 11 N., R. 27 E., Arizona

CHAINS									
80.20	Barbed wire fence, bears N. 88°23' E. and S. 88°23' W.								
80.45	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.								
	Set the iron post 18 ins. in the ground, with collar of stone to top, brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11N</td></tr> <tr><td>R26N</td><td>R27E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table>	T11N		R26N	R27E	S 25	S 30	S 36	S 31
T11N									
R26N	R27E								
S 25	S 30								
S 36	S 31								
	1966								
	Land, rolling. Soil, sandy loam. No timber; undergrowth, native grass.								
	N. 0°51' E., bet. secs. 25 and 30.								
	Over rolling land.								
5.70	Ridge, bears E. and W.								
30.30	Low ridge, bears E. and W., desc. N. slope.								
40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.								
	Set the iron post 18 ins. in the ground, brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td colspan="2"><math>\frac{1}{4}</math></td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T11N		R26E	R27E	$\frac{1}{4}$		S 25	S 30
T11N									
R26E	R27E								
$\frac{1}{4}$									
S 25	S 30								
	1966								
	Raise a mound of stone W. of the cor.								
41.50	Track road, bears NE. and SW.								
48.80	Track road, bears SE. and NW.								
80.45	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.								
	Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T11N		R26E	R27E	S 24	S 19	S 25	S 30
T11N									
R26E	R27E								
S 24	S 19								
S 25	S 30								
	1966								
	Land, rolling. Soil, sandy loam. No timber; undergrowth, native grass.								

Dep. Resurvey, West Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
	N. 0°51' E., bet. secs. 19 and 24.
	Over rolling land.
	Desc. over N. slope.
12.90	Rocky rim, bears E. and W.; continue descent.
40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T11N R26E R27E <math>\frac{1}{4}</math> S 24 S 19 1966</p>
	Raise a mound of stone W. of the cor.
69.10	Enter valley.
80.45	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T11N R26E R27E S 13 S 18 S 24 S 19 1966</p>
	Raise a mound of stone W. of the cor.
	Land, rolling.
	Soil, sandy loam.
	No timber; undergrowth, native grass.
	N. 0°51' E., bet. secs. 13 and 18.
	Over rolling land.
18.30	Track road, bears SE. and NW.
20.50	Leave valley, asc. over S. slope.
40.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
	<p style="text-align: center;">T11N R26E R27E <math>\frac{1}{4}</math> S 13 S 18 1966</p>



Dep. Resurvey, West Bdy., T. 11 N., R. 27 E., Arizona

<p>CHAINS 80.46</p>	<p>The cor. of secs. 7, 12, 13 and 18, monumented by a lava stone, 16 x 12 x 8 ins., set in mound of stone, mkd. with 4 notches on S. face and 2 notches on N. face.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R26E R27E <u>S 12   S 7</u> S 13   S 18</p> <p style="text-align: center;">1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 50 lks. East of a fence bearing N. and S.</p> <p>Land, rolling. Soil, sandy loam. No timber; undergrowth, native grass.</p>
<p>2.80</p>	<p>N. 7°08' W., bet. secs. 7 and 12.</p> <p>Asc. over rolling land.</p> <p>Ridge, bears E. and W. Desc. over rolling land.</p>
<p>40.45</p>	<p>The ¼ sec. cor. of secs. 7 and 12, monumented by a lava stone, 12 x 8 x 7 ins., firmly set in scattered mound, mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N' R26E R27E <u>S 12   S 7</u> 1/4</p> <p style="text-align: center;">1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p>
<p>17.60</p>	<p>N. 5°18' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>Sag, drains NW.</p>
<p>25.50</p>	<p>Barbed wire fence, bears S. 2°10' E. and N. 2°10' W.</p>
<p>40.30</p>	<p>Fence, barbed wire, bears E. and W.</p>
<p>40.99</p>	<p>The cor. of secs. 1, 6, 7 and 12, monumented by a mound of stone accepted as the best remaining evidence of the position of the orig. cor.</p> <p>At the corner point</p>

BOOK 4831

16.

Dep. Resurvey, West Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
	<p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R26E R27E <u>S 1   S 6</u> <u>S 12   S 7</u></p> <p style="text-align: center;">1966</p> <p>from which</p> <p style="padding-left: 40px;">An old bearing tree, a cedar, 16 ins. diam., bears S. 72°38' W., 206 lks. dist., mkd. T. 11 N., R. XXVI E., S 1 BT. (Not recorded in the official record of the 1882 resurvey.) This tree serves as a four-way fence cor.; fences bear N-S., E. and W.</p> <p>Land, rolling Soil, sandy loam. No timber; undergrowth, native grass.</p> <hr/> <p>N. 2°17' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>2.60 Wash, 5 lks. wide, 1 ft. deep, drains N. 80° W.</p> <p>8.80 Track road, bears E. and W.</p> <p>27.10 Ridge, bears E. and W.</p> <p>37.04 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R26E R27E ¼ <u>S 1   S 6</u></p> <p style="text-align: center;">1966</p> <p>74.53 The cor. of Tps. 11 and 12 N., Rs. 26 and 27 E., monumented by a lava stone, 13 x 10 x 10 ins., firmly set, mkd. with 6 notches on each face, with old mound of earth and stone S.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R26E R27E <u>S 36   S 31</u> <u>S 1   S 6</u> T11N</p> <p style="text-align: center;">1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p>

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, grama and bunch grass.</p>
	<p>Dependent Resurvey, North Boundary Township 11 North, Range 27 East</p>
	<p>Reestablishment of the Survey Executed by A. P. Johnson in 1882</p>
	<p>From the Tp. cor. of Tps. 11 and 12 N., Rs. 27 and 28. E.</p> <p>S. 89°29' W., bet. secs. 1 and 36.</p> <p>Over rolling land, through widely scattered timber.</p> <p>Asc. over SE. slope.</p>
28.20	Top of rim, bears N. 80° E. and S. 85° W.; leave timber.
37.70	Track road, bears NE. and SW.
40.54	Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 36}{S\ 1}</math>                      T11N                      1966</p>
	<p>Raise a mound of stone N. of the cor.</p>
58.50	Track road, bears SE. and NW.
61.80	Track road, bears NE. and SW.
81.47	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R27E  <math>\frac{S\ 35}{S\ 2}</math>   <math>\frac{S\ 36}{S\ 1}</math>                      T11N                      1966</p>
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, widely scattered cedar East 28 chs., none on remainder. Undergrowth, grama and bunch grass.</p>

Dep. Resurvey, North Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
	S. 89°29' W., bet. secs. 2 and 35.
	Over gently rolling land.
9.60	Track road, bears N. 20° E. and S. 20° W.
40.53	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T12N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 35}{S\ 2}</math>                      T11N                      1966</p>
	Raise a mound of stone N. of the cor.
44.20	Track road, bears S. 30° E. and N. 30° W.
50.50	Barbed wire fence, bears S. 0°15' E. and N. 0°15' W.
54.20	Track road, bears N. 30° E. and S. 30° W.
81.07	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T12N R27E  <math>\frac{S\ 34}{S\ 3}   \frac{S\ 35}{S\ 2}</math>                      T11N                      1966</p>
	Raise a mound of stone W. of the cor.
	Land, gently rolling.
	Soil, sandy loam.
	No timber; undergrowth, grama and bunch grass.
40.53	S. 89°29' W., bet. secs. 3 and 34.
	Over gently rolling land.
40.53	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T12N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 34}{S\ 3}</math>                      T11N                      1966</p>
	Raise a mound of stone N. of the cor.
62.90	Barbed wire fence, bears N. 62°30' E. and S. 62°30' W.
81.07	The cor. of secs. 3, 4, 33 and 34, monumented by a lava stone, 12 x 12 x 12 ins., firmly set, mkd. with 3 notches on E. face and 3 notches on W. face.

Dep. Resurvey, North Bdy., T. 11 N., R. 27 E., Arizona

CHAINS							
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T12N</td> <td>R27E</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> </table> <p style="text-align: center;">T11N</p> <p style="text-align: center;">1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	T12N	R27E	S 33	S 34	S 4	S 3
T12N	R27E						
S 33	S 34						
S 4	S 3						
	<p>N. 89°59' W., bet. secs. 4 and 33.</p> <p>Over gently rolling land.</p>						
33.90	Rocky rim, bears S. 30° E. and N. 30° W.; desc. over SW. slope, through widely scattered timber.						
40.57	The ¼ sec. cor. of secs. 4 and 33, monumented by a basalt stone, 12 x 10 x 8 ins., firmly set, mkd. ¼ on N. face.						
	<p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T12N</td> <td>R27E</td> </tr> <tr> <td>¼ S 33</td> <td></td> </tr> <tr> <td>S 4</td> <td></td> </tr> </table> <p style="text-align: center;">T11N</p> <p style="text-align: center;">1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>	T12N	R27E	¼ S 33		S 4	
T12N	R27E						
¼ S 33							
S 4							
	<p style="text-align: center;">—————</p> <p>N. 89°51' W., beginning new measurement.</p> <p>Over rolling land, through widely scattered timber.</p>						
6.70	Wash, 20 lks. wide, 1 ft. deep, drains N.						
16.70	Spur, slopes N.						
24.90	Wash, 5 lks. wide, 2 ft. deep, drains N. 70° W.						
29.60	Wash, 25 lks. wide, 1 ft. deep, drains N.						
39.00	Barbed wire fence, bears N. and S.						
40.31	The cor. of secs. 4, 5, 32 and 33, monumented by a lava stone, 20 x 12 x 6 ins., loosely set, mkd. with 4 notches on E. face and 2 notches on W. face.						

Dep. Resurvey, North Bdy., T. 11 N., R. 27 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">                     T12N R27E  <u>S 32   S 33</u>                      S 5   S 4                      T11N                      1966                 </p> <p>Raise a mound of stone W. of the cor.</p> <p>Deposit the orig. cor. stone in the mound of stone.</p> <p>Land, rolling.                      Soil, sandy loam.                      Timber, widely scattered cedar.                      Undergrowth, grama and bunch grass.</p>
	<p>N. 89°59' W., bet. secs. 5 and 32.</p> <p>Over rolling land, through widely scattered timber.</p> <p>Asc. E. slope.</p>
4.90	Top of rocky rim, bears N. and SW.; leave timber.
12.50	Barbed wire fence, bears West. Continue along fence line.
40.39	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 32, monumented by a lava stone, 12 x 10 x 5 ins., firmly set, mkd. <math>\frac{1}{4}</math> on the W. face, with old mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">                     T12N R27E  <math>\frac{1}{4}</math> <u>S 32</u>                      S 5                      T11N                      1966                 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>
	<p style="text-align: center;">_____</p> <p>S. 88°34' W., beginning new measurement.</p> <p>Over rolling land.</p>
16.10	Barbed wire fence, bears N. and S.
18.90	Track road, bears SE. and NW.
29.00	Track road, bears S. 30° W. and N. 30° E.
40.70	The cor. of secs. 5, 6, 31 and 32, monumented by a lava stone, 12 x 6 x 6 ins., firmly set, mkd. with 5 notches on E. face and 1 notch on W. face, with mound of stone W.

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R27E  <math>\frac{S}{S} \frac{31}{6}   \frac{S}{S} \frac{32}{5}</math>                      T11N                      1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling.                      Soil, sandy loam.                      Timber, widely scattered cedar E. 5.00 chs., none on remainder.                      Undergrowth, grama and bunch grass.</p>
<p>40.76</p> <p>79.90</p> <p>81.53</p>	<p>S. 89°24' W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 31, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R27E  <math>\frac{1}{4} \frac{S}{S} \frac{31}{6}</math>                      T11N                      1966</p> <p>Barbed wire fence, bears N. and S.</p> <p>The Tp. cor. of Tps. 11 and 12 N., Rs. 26 and 27 E.</p> <p>Land, rolling.                      Soil, sandy loam.                      No timber; undergrowth, native grass.</p>
<p>36.00</p> <p>41.50</p>	<p style="text-align: center;">Dependent Resurvey, Subdivisional Lines                      Township 11 North, Range 27 East</p> <p style="text-align: center;">Reestablishment of the Survey Executed                      by A. P. Johnson in 1882</p> <hr style="width: 20%; margin: auto;"/> <p>From the sec. cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 1°04' E., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p> <p>Rocky rim, bears NE. and SW., desc. over NW. slope.</p> <p>Draw, drains NE., asc. over SE. slope.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS		
41.98	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, monumented by a lava stone, 12 x 8 x 4 ins., firmly set, mkd. <math>\frac{1}{4}</math> on W. face, old mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>  S 35   S 36  1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°54' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>1.90 Rocky rim, bears NE. and SW.</p> <p>7.80 Fence, bears N. 1° E. and S. 1° W.</p> <p>20.70 Track road, bears E. and W.</p> <p>40.73 The cor. of secs. 25, 26, 35 and 36, monumented by a basalt stone, 14 x 14 x 14 ins., loosely set, mkd. with 1 notch on S. face and 1 notch on E. face.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  S 26   S 25  S 35   S 36  1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears North 01 lk. dist.; fences bear S. 89° E., S. 1° W. and N. 89° W.</p> <p style="padding-left: 40px;">A corral, bears N. 40°02' E., 29.60 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling.  Soil, sandy loam.  No timber; undergrowth, grama and bunch grass.</p>	
5.90	<p>From the sec. cor. of secs. 25, 30, 31 and 36 on the East bdy. of the Tp.</p> <p>N. 88°34' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p> <p>Barbed wire fence, bears S. 60° E. and N. 30° W. for 4 chs., thence W.</p>	



BOOK 4831

23.

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
25.70	Fence cor.; fences bear N. and irreg. N.88°34' W.
39.59	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, collar with stone, brass cap mkd.
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> S 25  <math>\frac{1}{4}</math> S 36                      1966</p>
	Continue along fence line given at 25.70.
68.40	Low rocky rim, slopes E.
79.17	The cor. of secs. 25, 26, 35 and 36.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.
	N. 1°11' E., bet. secs. 25 and 26.
	Over gently rolling land.
37.50	Track road, bears SE. and NW.
39.50	Track road, bears S. 20° E. and N. 20° W.
40.82	The ¼ sec. cor. of secs. 25 and 26, monumented by a lava stone, 14 x 11 x 7 ins., firmly set, mkd. ¼ on W. face, old mound of stone W.
	At the corner point
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>                      S 26   S 25                      1966</p>
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	N. 1°31' E., beginning new measurement.
	Over gently rolling land.
27.60	Sag, bears NE. and SW.
40.82	The cor. of secs. 23, 24, 25 and 26, monumented by a lava stone, 22 x 15 x 9 ins., firmly set in mound of stone, dimly mkd.
	At the corner point

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
	<p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{S}{S} \frac{23}{26}   \frac{S}{S} \frac{24}{25}</math>                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A wind mill, bears N. 89°47' W., 10.20 chs. dist.</p> <p style="padding-left: 40px;">A fence cor., bears W. 01 lk. dist., from which fences bear N. and S. 23° E.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>
<p>37.80</p> <p>38.66</p>	<p>From the sec. cor. of secs. 19, 24, 25 and 30, on the East bdy. of the Tp.</p> <p>N. 88°22' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p> <p>Track road, bears NE. and SW.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 24 and 25, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4} \frac{S}{S} \frac{24}{25}</math>                      1966</p> <p>Raise a mound of stone N. of the cor.</p>
<p>70.10</p> <p>77.33</p>	<p>Track road, bears SE. and NW.</p> <p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>
	<p>N. 0°50' E., bet. secs. 23 and 24.</p> <p>Over gently rolling land.</p> <p>10.50 Track road, bears NE. and SW.</p> <p>12.90 Fence cor.; fences bear N. 1° E. and N. 89° W.</p> <p>40.88 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>

CHAINS	
81.75	<p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>            S 23   S 24            1966</p> <p>The cor. of secs. 13, 14, 23 and 24, monumented by a basalt stone, 16 x 10 x 8 ins., firmly set, mkd. with 3 notches on S. face and 1 notch on E. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E            S 14   S 13            S 23   S 24            1966</p> <p>from which</p> <p style="padding-left: 40px;">A windmill, bears S. 1°32' E., 9.05 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling.            Soil, sandy loam.            No timber; undergrowth, grama and bunch grass.</p>
38.48	<p>From the cor. of secs. 13, 18, 19 and 24 on the East bdy. of the Tp.</p> <p>N. 87°57' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> S 13            S 24            1966</p> <p>Raise a mound of stone N. of the cor.</p>
75.70	<p>Track road, bears N. and S.</p>
76.90	<p>Barbed wire fence, bears N. and S.</p>
76.97	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, gently rolling.            Soil, sandy loam.            No timber; undergrowth, grama and bunch grass.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS		
	<p>N. 0°34' E., bet. secs. 13 and 14.</p> <p>Over gently rolling land.</p>	
19.70	<p>Track road, bears N. 65° E. and S. 65° W.</p>	
40.75	<p>Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>  S 14   S 13  1966</p>	
	<p>from which</p> <p style="padding-left: 40px;">Fence cor., bears S. 23° E., 8 lks. dist.; fences bear E., W. and S.</p>	
72.90	<p>Track road, bears N. 30° W. and S. 30° E.</p>	
81.50	<p>The cor. of secs. 11, 12, 13 and 14, monumented by a lava stone, 18 x 16 x 12 ins., firmly set, and mkd. with 4 notches on S. face and 1 notch on E. face.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <u>S 11   S 12</u>  S 14   S 13  1966</p> <p>from which</p> <p style="padding-left: 40px;">An East-West fence, bears South, 2 lks. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Deposit the orig. cor. stone in the mound W.</p> <p>Land, gently rolling.  Soil, sandy loam.  No timber; undergrowth, grama and bunch grass.</p>	
	<p>From the sec. cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 87°35' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>	
13.70	<p>Fence, barbed wire, bears NE. and SW.</p>	
38.48	<p>Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>	

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{12}{13}</math>                      1966</p> <p>from which</p> <p style="padding-left: 40px;">An E.-W. fence, bears North, 50 lks. dist.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Continue along S. side of fence bearing irregularly E. and W.</p>
76.20	<p>Cross to N. side of E.-W. fence.</p>
76.97	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling to gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>
	<p>N. 1°18' E., bet. secs. 11 and 12.</p> <p>Over gently rolling land.</p>
8.70	<p>Track road, bears N. 20° E. and S. 20° W.</p>
39.55	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>                      S 11   S 12                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A wind mill, bears N. 87°35' E., 9.34 chs. dist.</p>
54.20	<p>Track road, bears SE. and NW.</p>
79.11	<p>Point for the sec. cor. of secs. 1, 2, 11 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{S}{S}</math> <math>\frac{2}{11}</math>   <math>\frac{S}{S}</math> <math>\frac{1}{12}</math>                      1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS		
35.13	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 84°34' W., bet. secs. 1 and 12.</p> <p>Over rolling land, through widely scattered timber.</p> <p>The ¼ sec. cor. of secs. 1 and 12, monumented by a broken sandstone, 8 x 6 x 3 ins., set in a mound of stone, dimly mkd.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, collar with stone, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ <math>\frac{S}{S}</math> <math>\frac{1}{12}</math> 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>S. 87°39' W., beginning new measurement.</p> <p>Over rolling land.</p>	
41.41	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling to gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, grama and bunch grass.</p> <hr/> <p>N. 1°28' W., bet. secs. 1 and 2.</p> <p>Over gently rolling land.</p> <p>25.40 Track road, bears N. 80° E. and S. 80° W.</p> <p>33.30 Wash, 30 lks. wide, 2 ft. deep, drains E. from SW.</p> <p>39.59 Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ <math>\frac{S}{S}</math> <math>\frac{1}{1}</math> 1966</p> <p>67.20 Track road, bears NE. and SW.</p> <p>78.78 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, grama and bunch grass.</p>	

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS	
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.</p>
	<p>N. 0°40' E., bet. secs. 34 and 35.</p>
	<p>Over gently rolling land.</p>
8.30	<p>Track road, bears SE. and NW.</p>
8.80	<p>Track road, bears E. and W.</p>
41.22	<p>Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>  S 34   S 35  1966</p>
	<p>Raise a mound of stone W. of the cor.</p>
71.80	<p>Track road, bears SE. and NW.</p>
82.44	<p>The cor. of secs. 26, 27, 34 and 35, monumented by a lava stone, 14 x 6 x 6 ins., firmly set in a mound of stone, mkd. with 1 notch on S. face and 2 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  S 27   S 26  S 34   S 35  1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor. bears West 5 lks. dist.; fences bear S. 89°30' W. and NE.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p>
	<p>N. 89°44' W., bet. secs. 26 and 35.</p>
8.00	<p>Fence, barbed wire, bears S. 89° E. and N. 89° W.</p>
36.60	<p>Track road, bears N. and S.</p>
40.52	<p>Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS		
81.06	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 26}{S\ 35}</math>                      1966</p> <p>Raise a mound of stone N. of the cor.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>	
40.00	<p>N. 1°42' E., bet. secs. 26 and 27.</p> <p>Over gently rolling land.</p> <p>Track road, bears NE. and SW.</p>	
41.37	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 27, monumented by a lava stone, 14 x 7 x 4 ins., firmly set, mkd. <math>\frac{1}{4}</math> on W. face.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 27}{S\ 26}</math>                      1966</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°46' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>Track road, bears N. 20° E. and S. 20° W.</p> <p>The cor. of secs. 22, 23, 26 and 27, monumented by a lava stone, 10 x 6 x 5 ins., firmly set, mkd. with 2 notches on S. face and 2 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{S\ 22}{S\ 27}</math>   <math>\frac{S\ 23}{S\ 26}</math>                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A wind mill, bears S. 60° E., 41.22 chs. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>	



Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS		
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°59' W., bet. secs. 23 and 26.</p> <p>Over gently rolling land.</p> <p>23.00 Barbed wire fence, bears irregularly NE. and SW.</p> <p>23.10 Track road, bears NE. and SW.</p> <p>40.63 Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ <math>\frac{S}{S}</math> <math>\frac{23}{26}</math> 1966</p> <p>Raise a mound of stone N. of the cor.</p> <p>66.30 Track road, bears S. 70° E. and N. 70° W.</p> <p>81.26 The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	
	<p>N. 0°02' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land.</p> <p>8.30 Track road, bears S. 60° E. and N. 60° W.</p> <p>40.59 The ¼ sec. cor. of secs. 22 and 23, monumented by a lava stone, 14 x 8 x 4 ins., firmly set, mkd. with ¼ on W. face, old mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ <math>\frac{S}{S}</math> <math>\frac{22}{23}</math> 1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°30' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>40.71 The cor. of secs. 14, 15, 22 and 23, monumented by a lava stone, 14 x 8 x 8 ins., firmly set, mkd. with 3 notches on S. face and 2 notches on E. face, old mound of stone W.</p>	

BOOK 4831

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{S}{S} \frac{15}{22}   \frac{S}{S} \frac{14}{23}</math></p> <p style="text-align: center;">1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling.            Soil, sandy loam.            No timber; undergrowth, grama and bunch grass.</p>
<p>7.20</p> <p>20.40</p> <p>33.80</p> <p>41.78</p>	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°16' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land.</p> <p>Track road, bears N. and S.</p> <p>Track road, bears NE. and SW.</p> <p>Track road, bears N. and S.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 23, monumented by a lava stone, 8 x 6 x 6 ins., firmly set, mkd. <math>\frac{1}{4}</math> on N. face, old mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4} \frac{S}{S} \frac{14}{23}</math></p> <p style="text-align: center;">1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
<p>40.42</p> <p>40.76</p>	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, gently rolling.            Soil, sandy loam.            No timber; undergrowth, grama and bunch grass.</p> <hr/> <p>N. 0°41' E., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 15, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>  S 15   S 14  1966</p>
	<p>Raise a mound of stone W. of the cor.</p>
44.20	<p>Barbed wire fence, bears E. and W.</p>
49.40	<p>Draw, drains NE.</p>
75.80	<p>Same draw, drains N. 25° W.</p>
81.53	<p>The cor. of secs. 10, 11, 14 and 15, monumented by a basalt stone, 14 x 10 x 8 ins., firmly set, mkd. with 4 notches on S. face and 2 notches on E. face, old mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 5 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <u>S 10   S 11</u>  S 15   S 14  1966</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling.  Soil, sandy loam.  No timber; undergrowth, grama and bunch grass.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°40' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land.</p>
3.00	<p>Track road, bears N. 10° E. and S.</p>
40.98	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <u>S 11</u>  S 14  1966</p>
	<p>Raise a mound of stone N. of the cor.</p>
48.90	<p>Fence cor., bears North 80 lks. dist.; fences bear N., S., E. and W.</p>
81.97	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, gently rolling.  Soil, sandy loam.  No timber; undergrowth, grama and bunch grass.</p>

BOOK 4831

34.

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS		
	<p>N. 0°42' E., bet. secs. 10 and 11.</p>	
	<p>Over gently rolling land.</p>	
1.30	<p>Barbed wire fence, bears E. and W.</p>	
40.78	<p>Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T11N R27E ¼ S 10 S 11</p>	
	<p style="text-align: center;">1966</p>	
	<p>Raise a mound of stone W. of the cor.</p>	
81.57	<p>The cor. of secs. 2, 3, 10 and 11, monumented by a lava stone, 8 x 6 x 4 ins., firmly set, mkd. with 5 notches on S. face and 2 notches on E. face, old mound of stone W.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 13 ins. in the ground, mound with stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">T11N R27E S 3 S 2 S10 S11</p>	
	<p style="text-align: center;">1966</p>	
	<p>Deposit the orig. cor. stone alongside the iron post.</p>	
	<p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	
	<p>From the cor. of secs. 1, 2, 11 and 12.</p>	
	<p>N. 88°37' W., bet. secs. 2 and 11.</p>	
	<p>Over gently rolling land.</p>	
7.30	<p>Track road, bears NE. and SW.</p>	
14.20	<p>Track road, bears S. 25° E. and N. 25° W.</p>	
41.39	<p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>	
	<p>Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">T11N R27E ¼ S 2 S 11</p>	
	<p style="text-align: center;">1966</p>	
51.80	<p>Barbed wire fence, bears N. and S.</p>	

## Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
82.79	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
5.20	<p>N. 0°14' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land.</p> <p>Track road, bears N. 60° E. and S. 60° W.</p>
21.10	<p>Track road, bears NE. and SW.</p>
38.07	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 3, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p>
75.98	<p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> S 3   S 2 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none; undergrowth, grama and bunch grass.</p>
7.80	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°47' E., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p> <p>Track road, bears NE. and S. 60° W.</p>
17.70	<p>Track road, bears E. and W.</p>
40.93	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 33 and 34, monumented by a basalt stone, 8 x 8 x 6 ins., firmly set, mkd. with <math>\frac{1}{2}</math> on W. face.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> S 33   S 34 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS						
40.24	<p>N. 1°49' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>The sec. cor. of secs. 27, 28, 33 and 34, monumented by a lava stone, 14 x 8 x 3 ins., firmly set, mkd. with 1 notch on S. face and 3 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, collar with stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R27E</p> <table border="1" style="margin: auto;"> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> <p>1966</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears North 3 lks. dist.; fences bear N., E. and W.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	S 28	S 27	S 33	S 34	
S 28	S 27					
S 33	S 34					
.05 39.75	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°23' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land.</p> <p>Fence cor.; fences bearing NE. and S. 89°30' W.</p> <p>Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R27E</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 27</td> <td></td> </tr> <tr> <td>S 34</td> <td></td> </tr> </table> <p>1966</p> </div> <p>Raise a mound of stone N. of the cor.</p>	¼ S 27		S 34		
¼ S 27						
S 34						
79.50 40.91	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p> <hr/> <p>N. 0°26' W., bet. secs. 27 and 28.</p> <p>Over gently rolling land.</p> <p>The ¼ sec. cor. of secs. 27 and 28, monumented by a lava stone, 10 x 6 x 4 ins., firmly set, mkd. with ¼ on W. face.</p> <p>At the corner point</p>					

CHAINS	
	<p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{2}</math>            S 28   S 27            1966</p> <p>from which</p> <p style="padding-left: 40px;">A N-S. fence, bears East, 23 lks. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°35' E., beginning new measurement.</p> <p>Over gently rolling land.</p>
10.90	<p>Fence, barbed wire, bears irregularly N. and S.</p>
40.86	<p>Point for the sec. cor. of secs. 21, 22, 27 and 28, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E            S 21   S 22            S 28   S 27            1966</p> <p>from which</p> <p style="padding-left: 40px;">A gate in N-S. fence, bears West, 6.5 lks. dist.</p> <p style="padding-left: 40px;">A dam on catch pond, bears N. 89°56' W., 3.60 chs. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling.            Soil, sandy loam.            No timber; undergrowth, grama and bunch grass.</p>
40.73	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°54' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27, monumented by a basalt stone, 15 x 8 x 8 ins., firmly set, mkd. with <math>\frac{1}{4}</math> on N. face</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> S 22            S 27            1966</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
40.40	<p>Deposit the orig. cor. stone alongside the iron post.</p> <hr/> <p>S. 89°36' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
0.10 30.00 40.87	<p>N. 0°17' E., bet. secs. 21 and 22.</p> <p>Over gently rolling land.</p> <p>Track road, bears NE. and NW.</p> <p>Fence, barbed wire, bears N. 1° E. and S. 1° W.</p> <p>The ¼ sec. cor. of secs. 21 and 22, monumented by a lava stone, 18 x 12 x 9 ins., firmly set, mkd. with ¼ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ S 21   S 22 1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence, bears East, 48 lks. dist.; fence bears irregularly N. and S.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
33.20 40.37	<hr/> <p>N. 0°24' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>Fence cor., bears West, 50 lks. dist.; fences bear N., S. and E.</p> <p>The cor. of secs. 15, 16, 21 and 22, monumented by the remains of a rotted post set in a mound of stone.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 16   S 15 S 21   S 22 1966</p> <p>Raise a mound of stone W. of the cor.</p>



Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
40.48	<p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23. S. 89°45' W., bet. secs. 15 and 22. Over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ S 15           S 22 1966</p> <p>Raise a mound of stone N. of the cor.</p>
58.80	Track road, bears SE. and NW.
80.96	The cor. of secs. 15, 16, 21 and 22.
39.91	<p>Land, gently rolling. Soil, sandy loam. To timber; undergrowth, grama and bunch grass.</p> <hr/> <p>N. 0°13' E., bet. secs. 15 and 16. Over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ S 16   S 15 1966</p> <p>from which     A dam, bears S. 63°54' W., 15.90 chs. dist.</p>
42.00	Barbed wire fence, bears E. and W.
79.82	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 9   S 10 S16   S 15 1966</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS		
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	
<p>40.81</p>	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 88°34' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E     S 10    ¼ S 15  1966</p> <p>Raise a mound of stone N. of the cor.</p>	
<p>81.62</p>	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p> <hr/> <p>N. 0°28' E., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p> <p>4.20 Barbed wire fence, bears E. and W.</p> <p>4.30 Fence, barbed wire, bears N. 6° E. and S. 6° W.</p> <p>17.60 Track road, bears N. 70° E. and S. 70° W.</p> <p>25.40 Dike, bears N. 41° E. for approx. 12 chs. and S. 41°45' W. for approx. 8 chs.</p> <p>39.91 Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E     ¼    S 9   S 10  1966</p> <p>from which</p> <p style="padding-left: 40px;">A metal cabin, 10 ft. square, bears S. 29°18' W., 11.75 chs. dist.</p> <p style="padding-left: 40px;">A tank, spring fed, bears S. 80°13' W., 6.57 chs. dist.</p> <p style="padding-left: 40px;">A tank, spring fed, bears N. 77°26' W., 8.65 chs. dist.</p>	

BOOK 4831

41.

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p>
41.50	<p>Fence, barbed wire, bears E. and W.</p>
42.20	<p>Track road, bears S. 70° E. and N. 70° W.</p>
47.70	<p>Draw, drains S. 60° W., asc. steep S. slope.</p>
59.00	<p>Rocky rim, bears N. 60° E. and S. 50° W.; continue over gently rolling land.</p>
79.82	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>
	<p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T11N R27E  <math display="block">\begin{array}{c c} S 4 &amp; S 3 \\ \hline S 9 &amp; S 10 \end{array}</math>                     1966</p>
	<p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p>
	<p>S. 87°23' W., bet. secs. 3 and 10.</p>
	<p>Over gently rolling land.</p>
14.90	<p>Track road, bears N. 25° E. and S. 25° W.</p>
40.99	<p>Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>
	<p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T11N R27E  <math display="block">\begin{array}{c c} \frac{1}{4} S 3 \\ \hline S 10 \end{array}</math>                     1966</p>
81.99	<p>The cor. of secs. 3, 4, 9 and 10.</p>
	<p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>
	<p>N. 0°24' E., bet. secs. 3 and 4.</p>
	<p>Over gently rolling land.</p>
39.91	<p>Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>

BOOK 4831

42.

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS	
70.20	<p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 4<sup>1</sup>/<sub>4</sub> S 3 1966</p>
79.02	<p>Barbed wire fence, bears N. 62°30' E. and S. 62°30' W.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
28.10	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0°50' E., bet. secs. 32 and 33.</p> <p>Over gently rolling land.</p> <p>Track road, bears E. and W.</p>
40.73	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 32 and 33, monumented by a basalt stone, 12 x 8 x 6 ins., firmly set, mkd. with <sup>1</sup>/<sub>4</sub> on W. face.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 32<sup>1</sup>/<sub>4</sub> S 33 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
40.70	<p>Small wash, drains irregularly E.</p>
40.79	<p>The cor. of secs. 28, 29, 32 and 33, monumented by a basalt stone, 12 x 9 x 4 ins., firmly set, mkd. with 1 notch on S. face and 4 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 29   S 28 S 32   S 33 1966</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS		
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	
<p>40.93</p>	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°27' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 33, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> <math>\frac{S 28}{S 33}</math> 1966</p> <p>Raise a mound of stone N. of the cor.</p>	
<p>81.86</p>	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>	
<p>10.20</p> <p>40.69</p>	<p>N. 0°54' E., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p> <p>Barbed wire fence, bears E. and W.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 29, monumented by a basalt stone, 8 x 6 x 5 ins., firmly set in a mound of stone, mkd. with <math>\frac{1}{4}</math> on W. face.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> <math>S 29   S 28</math> 1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p>	
<p>14.60</p> <p>40.54</p>	<p>N. 0°24' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>Draw, drains S. 80° E.</p> <p>The cor. of secs. 20, 21, 28 and 29, monumented by a lava stone, 12 x 10 x 8 ins., firmly set, mkd. with 2 notches on S. face and 4 notches on E. face, old mound of stone W.</p>	

CHAINS	
	<p>At the corner point, Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 20   S 21 S 29   S 28</p> <p style="text-align: center;">1966</p> <p>Bury the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
40.36	<p>From the cor. of secs. 21, 22, 27 and 28. N. 89°56' W., bet. secs. 21 and 28. Over gently rolling land.</p> <p>The ¼ sec. cor. of secs. 21 and 28, monumented by a lava stone, 12 x 8 x 5 ins., firmly set in mound of stone, mkd. with ¼ on the N. face.</p> <p>At the corner point Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E ¼ S 21 ¼ S 28</p> <p style="text-align: center;">1966</p> <p>Bury the orig. cor. stone alongside the iron post. Raise a mound of stone N. of the cor.</p>
41.26	<p>N. 89°47' W., beginning new measurement. Over gently rolling land.</p> <p>The cor. of secs. 20, 21, 28 and 29. Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
27.80	<p>N. 0°27' E., bet. secs. 20 and 21. Over gently rolling land.</p> <p>Track road, bears S. 50° E. and N. 50° W.</p>
40.71	<p>The ¼ sec. cor. of secs. 20 and 21, monumented by a basalt stone, 24 x 18 x 12 ins., firmly set, mkd. with ¼ on W. face, old mound of stone W.</p> <p>At the corner point</p>

CHAINS		
	<p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>                      S 20   S 21                      1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°17' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>40.66 The cor. of secs. 16, 17, 20 and 21, monumented by a lava stone, 15 x 12 x 6 ins., firmly set, mkd. with 3 notches on S. face and 4 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E                      S 17   S 16                      S 20   S 21                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A wind mill, bears N. 37°27' W., 12.54 chs. dist.</p> <p>Raise a mound of stone W. of the cor. Deposit the orig. cor. stone in mound W.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>	
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°43' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p> <p>.62 Barbed wire fence, bears N. and S.</p> <p>40.95 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 16 and 21, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> S 16                      S 21                      1966</p> <p>Raise a mound of stone N. of the cor.</p> <p>81.89 The cor. of secs. 16, 17, 20 and 21.</p>	

Dep. Resurvey, Subdivisional Lines, T.10 N., R. 27 E., Arizona

CHAINS	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.
N. 0°28' E., bet. secs. 16 and 17.	Over gently rolling land.
1.30	Barbed wire fence, bears S. 83°30' E. and N. 83°30' W.
4.90	Track road, bears E. and W.
36.60	Track road, bears NE. and SW.
40.56	The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented by a lava stone, 12 x 10 x 8 ins., firmly set in a mound of stone, mkd. with $\frac{1}{4}$ on W. face.
	At the corner point
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T11N R27E
	S 17 $\frac{1}{4}$  S 16
	1966
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	N. 0°43' E., beginning new measurement.
	Over gently rolling land.
36.50	Draw, drains NE. from S. 20° W.
40.55	The cor. of secs. 8, 9, 16 and 17, monumented by a lava stone, 16 x 12 x 8 ins., loosely set, mkd. with 4 notches on S. side and 4 notches on E. side.
	At the corner point
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T11N R27E
	S 8 S 9 S17 S16
	1966
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 88°50' W., bet. secs. 9 and 16.
	Over gently rolling land.



Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
5.20	Barbed wire fence, bears N. and S.
24.60	Track road, bears NE. and SW.
40.65	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 9}{S\ 16}</math>                      1966</p>
	Raise a mound of stone N. of the cor.
78.00	Draw, drains N. 60° E.
81.31	The cor. of secs. 8, 9, 16 and 17.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.
	N. 0°43' W., bet. secs. 8 and 9.
	Over gently rolling land.
32.70	Draw, drains E. from SW.
37.60	Barbed wire fence, bears E. and W.
40.40	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented by a lava stone, 12 x 10 x 4 ins., firmly set, mkd. with $\frac{1}{4}$ on W. face, old mound of stone W.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>                      S 8   S 9                      1966</p>
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	N. 0°25' E., beginning new measurement.
	Over rolling land.
11.10	Draw, drains NE.
13.60	Draw, drains E.
27.90	Draw, drains NE. from head, 4.50 chs. SW.
40.45	The cor. of secs. 4, 5, 8 and 9, monumented by a lava stone, 8 x 6 x 6 ins., firmly set in mound of stone, mkd. with 5 notches on S. face and 4 notches on E. face.

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{S}{S} \frac{5}{8}   \frac{S}{S} \frac{4}{9}</math>                      1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. falls on steep W. slope.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, widely scattered cedar.                      Undergrowth, grama and bunch grass.</p>
<p>41.07</p> <p>56.60</p> <p>63.50</p> <p>64.30</p> <p>80.60</p> <p>82.15</p>	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 88°08' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 9, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 7 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4} \frac{S}{S} \frac{4}{9}</math>                      1966</p> <p>Rocky rim, bears N. and S.; enter widely scattered cedar.</p> <p>Wash, 40 lks. wide, 4 ft. deep, drains N.</p> <p>Track road, bears N. and S., asc. E. slope.</p> <p>Spur, slopes N. 5° E.; desc. W. slope.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling to rolling.                      Soil, sandy loam.                      Timber, widely scattered cedar.                      Undergrowth, grama and bunch grass.</p>
<p>15.40</p> <p>20.80</p> <p>38.30</p> <p>38.73</p>	<p>N. 1°15' E., bet. secs. 4 and 5.</p> <p>Over rolling land, through widely scattered cedar.</p> <p>Wash, 30 lks. wide, 6 ft. deep, drains N. 30° E.</p> <p>Draw, drains W.</p> <p>Wash, 50 lks. wide, 6 ft. deep, drains NE.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>

BOOK 4831

49.

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
<p>42.20 43.40 72.20 76.42</p>	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{2}</math> S 5   S 4</p> <p style="text-align: center;">1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Wash, 20 lks. wide, 4 ft. deep, drains E.</p> <p>Barbed wire fence, bears S. 70° E. and N. 70° W.</p> <p>Deep draw, drains N. 60° E.; asc. over S. slope.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.</p> <p>Land, rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, grama and bunch grass.</p>
<p>21.90 40.79 42.50 59.20 81.58</p>	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 1°04' E., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p> <p>Barbed wire fence, bears NW. and SE. for approx. 80 lks. to a cor. of fences bearing S., NW. and N. 1°19' E.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> S 31   S 32</p> <p style="text-align: center;">1966</p> <p>Small draw, drains NE.</p> <p>Draw, drains W.</p> <p>The cor. of secs. 29, 30, 31 and 32, monumented by a basalt stone, 12 x 10 x 5 ins., loosely set, with top broken, mkd. with part of marks visible.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 30   S 29 S 31   S 32</p> <p style="text-align: center;">1966</p> <p>Cor. falls 2 lks. S. of a barbed wire fence which bears N. 88°04' W. and S. 88°04' E.</p> <p>Raise a mound of stone W. of the cor.</p>

BOOK 4831

50.

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS	
	<p>Deposit the orig. cor. stone in mound W.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
<p>17.80</p> <p>40.06</p>	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°56' W., bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p> <p>Small draw, drains S. 75° E.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> <math>\frac{S\ 29}{S\ 32}</math> 1966</p>
<p>78.00</p> <p>80.12</p>	<p>Fence cor.; fences bear N. 74°04' E., S. 1°19' W. and N. 88°04' W.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
<p>15.80</p> <p>44.31</p>	<p>N. 87°26' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p> <p>Track road, bears N. and S.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 30 and 31, monumented by a basalt stone, 24 x 12 x 8 ins., firmly set, mkd. with <math>\frac{1}{4}</math> on N. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> <math>\frac{S\ 30}{S\ 31}</math> 1966</p> <p>Cor. is located 33 lks. N. of E.-W. fence.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Deposit the orig. cor. stone in mound N.</p> <hr style="width: 20%; margin: 20px auto;"/>

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
<p>28.80</p> <p>40.42</p>	<p>N. 89°26' W., beginning new measurement.</p> <p>Over rolling land, asc. SE. slope.</p> <p>Barbed wire fence, bears N. and S.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.</p> <p>Land, rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
<p>40.51</p> <p>80.40</p>	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 1°59' W., bet. secs. 29 and 30.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> S 30   S 29 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Small draw, drains N. 25° E.</p>
<p>81.03</p> <p>35.70</p>	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a lava stone, 14 x 10 x 4 ins., firmly set, mkd. with 2 notches on S. face and 5 notches on E. face, old mound W.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 19   S 20 S 30   S 29 1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
<p>35.70</p>	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°44' W., bet. secs. 20 and 29.</p> <p>Over gently rolling land.</p> <p>Small draw, drains NE.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

CHAINS	
39.88	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 29, monumented by a basalt stone, 12 x 8 x 6 ins., firmly set in a mound of stone, dimly mkd.</p>
	<p>At the corner point</p>
	<p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 20}{S\ 29}</math>                      1966</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 89°59' W., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
40.40	<p>Small draw, drains NW.</p>
43.38	<p>The cor. of secs. 19, 20, 29 and 30.</p>
	<p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>
	<p>N. 88°42' W., bet. secs. 19 and 30.</p>
	<p>Over gently rolling land.</p>
17.90	<p>Track road, bears NE. and SW.</p>
40.31	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>
	<p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S\ 19}{S\ 30}</math>                      1966</p>
73.80	<p>Barbed wire fence, bears N. and S.</p>
80.75	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.</p>
	<p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p>
	<p>N. 2°04' E., bet. secs. 19 and 20.</p>
	<p>Over gently rolling land.</p>

CHAINS	
40.23	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>            S 19   S 20            1966</p>
61.30	<p>Track road, bears S. 50° E. and N. 50° W.</p>
80.47	<p>The cor. of secs. 17, 18, 19 and 20, monumented by a basalt stone, 12 x 8 x 5 ins., firmly set in mound of stone, mkd. with 3 notches on S. face and 5 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E            S 18   S 17            S 19   S 20            1966</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling.            Soil, sandy loam.            No timber; undergrowth, grama and bunch grass.</p>
40.25	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°12' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec cor. of secs. 17 and 20, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> S 17  <math>\frac{1}{4}</math> S 20            1966</p>
80.51	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling.            Soil, sandy loam.            No timber; undergrowth, grama and bunch grass.</p>

BOOK 4831

54.

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS		
	<p>N. 88°42' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p> <p>20.20 Track road, bears N. and S.</p> <p>36.90 Track road, bears S. 60° E. and N. 60° W.</p> <p>41.09 Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{18}{19}</math>                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A catch pond, bears S. 27°49' W., 3.23 chs. dist.</p> <p>Raise a mound of stone N. of the cor.</p> <p>80.20 Barbed wire fence, bears N. and S.</p> <p>82.39 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      No timber; undergrowth, grama and bunch grass.</p>	
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°38' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p> <p>11.90 Barbed wire fence, bears E. and W.</p> <p>35.50 Track road, bears E. and W.</p> <p>41.22 Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E  <math>\frac{1}{4}</math>                      S 18   S 17                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A catch pond, bears N. 27°04' W., 23.39 chs. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>60.00 Track road, bears E. and W.</p> <p>82.44 The cor. of secs. 7, 8, 17 and 18, monumented by a lava stone, 12 x 10 x 6 ins., firmly set, mkd. with 4 notches on S. face and 5 notches on E. face.</p>	



CHAINS

At the corner point

Set the iron post 18 ins. in the ground, brass cap mkd.

T11N R27E

S 7	S 8
S18	S17

1966

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

Land, gently rolling.

Soil, sandy loam.

No timber; undergrowth, grama and bunch grass.

41.14

From the cor. of secs. 8, 9, 16 and 17.

N. 89°54' W., bet. secs. 8 and 17.

Over gently rolling land.

Point for the  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post 22 ins. in the ground, brass cap mkd.

T11N R27E

$\frac{1}{4}$ S 8
S 17

1966

Raise a mound of stone N. of the cor.

82.29

The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling.

Soil, sandy loam.

No timber; undergrowth, grama and bunch grass.

18.00

S. 89°56' W., bet. secs. 7 and 18.

Over gently rolling land.

Track road, bears NE. and S.

40.05

Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post 18 ins. in the ground, brass cap mkd.

T11N R27E

$\frac{1}{4}$ S 7
S 18

1966

Raise a mound of stone N. of the cor.

BOOK 4831

56.

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

<p>CHAINS 80.37</p>	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. No timber, undergrowth, grama and bunch grass.</p>
<p>40.51</p>	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°37' E., bet. secs. 7 and 8.</p> <p>Over gently rolling land.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8, monumented by a basalt stone, 7 x 6 x 5 ins., firmly set in a mound of stone, mkd. with <math>\frac{1}{4}</math> on W. face.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> S 7   S 8 1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears NE., 2 lks. dist.; fences bear N. 1° E. and East.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°49' E., beginning new measurement.</p> <p>Over gently rolling land.</p>
<p>36.60</p>	<p>Fence cor., bears West, about 70 lks. dist.; fences bear N. 1°15' E., S. 1° W., East and West.</p>
<p>40.74</p>	<p>The cor. of secs. 5, 6, 7 and 8, monumented by a lava stone, 15 x 12 x 12 ins., firmly set, dimly mkd.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R27E S 6   S 5 S 7   S 8 1966</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>

Dep. Resurvey, Subdivisional Lines, T.11 N., R. 27 E., Arizona

CHAINS	
	From the cor. of secs. 4, 5, 8 and 9.
	N. 89°34' W., bet. secs. 5 and 8.
	Over rolling land and through widely scattered cedar.
3.40	Wash, 40 lks. wide, 4 ft. deep, drains N. 10° E.
39.83	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4} \frac{S \ 5}{S \ 8}</math>                      1966</p>
57.70	Barbed wire fence, bears N. and S.
79.67	The cor. of secs. 5, 6, 7 and 8.
	Land, rolling.
	Soil, sandy loam.
	Timber, widely scattered cedar.
	Undergrowth, grama and bunch grass.
	N. 89°59' W., bet. secs. 6 and 7.
	Over rolling land.
0.50	Barbed wire fence, bears N. and S.
17.40	Track road, bears SE. and NW.
41.82	The ¼ sec. cor. of secs. 6 and 7, monumented by a basalt stone, 6 x 4 ft. above ground, firmly set, mkd. ¼ X.
41.85	Point selected for the witness ¼ sec. cor. of secs. 6 and 7.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	<p style="text-align: center;">T11N R27E  <math>\frac{1}{4} \frac{S \ 6}{S \ 7} \rightarrow WC</math>                      1966</p>
	S. 89°26' W., beginning new measurement from the true point.
	Over rolling land.
35.30	Track road, bears NE. and SW.
42.25	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	Land, rolling.
	Soil, sandy loam.
	No timber; undergrowth, grama and bunch grass.

BOOK 4831

58.

Dep. Resurvey, Subdivisional Lines, T.11 N., R.27 E., Arizona

<p>CHAINS</p> <p>37.12</p> <p>70.00</p> <p>74.87</p>	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°19' E., bet. secs. 5 and 6.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R27E <math>\frac{1}{4}</math> S 6   S 5 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Track road, bears NE. and SW.</p> <p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, grama and bunch grass.</p>
<p>General Description</p> <p>The land in Township 11 North, Range 27 East, varies from gently rolling over most of the area to rolling in the NE. portion. The soil is sandy loam.</p> <p>Grass is found throughout the township, with widely scattered cedars in the NE. cor. Reservoirs, catch ponds, and springs in Sec. 9 afford water for the grazing of livestock, which is, at present, the predominant interest.</p> <p>Drainage is mostly to the north and east.</p> <p>Track roads afford access to most of the township.</p> <p>The average elevation is about 6,400 feet above sea level.</p>	



CERTIFICATE OF SURVEY

We, Paul G. Bauer and Robert F. Johnson, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of April, 1964, we have dependently resurveyed the boundaries and subdivisional lines of Township 11 North, Range 27 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 15, 1966  
(Date)

Paul G. Bauer  
(Cadastral Surveyor)

November 15, 1966  
(Date)

Robert F. Johnson  
Surveying (Cadastral Surveyor) Technician

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date JUN 19 1968

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the dependent resurvey of the boundaries and subdivisional lines of Township 11 North, Range 27 East, of the Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer and Robert F. Johnson, having been critically examined and found correct, are hereby approved.

JAN 13 1969  
(Date)

\_\_\_\_\_  
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief, Division of Engineering)