

BOOK 4832

Form 4-679  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

DEPENDENT RESURVEY

of the

SOUTH BOUNDARY

and a

Portion of the

EAST BOUNDARY

and

SURVEY

of a

Portion of the

SUBDIVISIONAL LINES

and

TRACT 37

in Section 34,

Township 11 North, Range 10 East

Of the Gila and Salt River Meridian,

In the State of Arizona

## EXECUTED BY

Kenneth D. Herman, Cadastral Surveyor

Jerrold E. Knight, Cadastral Surveyor

Under special instructions dated June 29, 19 67, which provided for the surveys included under Group Number 456, approved June 29, 1967, and Amended Supplemental Special Instructions, dated and approved April 30, 1968, and assignment instructions dated June 29, 19 67, and April 30, 1968.

Survey commenced July 10, 19 67

Survey completed May 8, 19 68

1A

# BOOK 4832 INDEX DIAGRAM

Township 11 North, Range 10 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
42 $\frac{1}{2}$ 30 41	42 28 35	36 28 30	32 27 25	26 26 21	22 25 17
39 $\frac{1}{2}$ 31 37	38 32 33	34 33 27	29 34 23	24 35 19	20 36 15
$\frac{1}{4}$	$\frac{1}{4}$	$\frac{1}{4}$	$\frac{1}{4}$	$\frac{1}{4}$	$\frac{1}{4}$
13	10	8	5	3	2

Survey of Tract 37 in Section 34, page 44.

Township 11 North, Range 10 East  
Gila and Salt River Meridian, Arizona

## CHAINS

The south boundary was surveyed in 1904 by Campbell and Oakes. The east boundary was surveyed in 1904 by C. L. Campbell. The west boundary was surveyed in 1919 by S. E. Blout. Exchange Survey No. 680 in sections 33 and 34 was surveyed in 1956 by Charles C. Doak, U. S. Forest Service, and was cancelled by memorandum from the Director, dated June 15, 1967. The north boundary of section 3, Township 10 North, Range 10 East, was concurrently resurveyed under Group 480 and again resurveyed under this group when a double set of corners were necessary. The field notes thereof are included under Township 11 North, Range 10 East.

The following notes are those of a dependent resurvey of the south boundary and a portion of the east boundary, designed to restore the corners in their true original location according to the best available evidence, and the survey of a portion of the subdivisional lines, and survey of Tract 37, section 34, Township 11 North, Range 10 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated June 29, 1967, and the Amended Supplemental Special Instructions dated April 30, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches diameter, flanged at the base, and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude, 34°14'46.76" North, and Longitude, 111°16'21.9" West, as determined by calculation from U.S.C.&G.S. triangulation station "Huston" located in section 23 of the township.

The mean magnetic declination was found to be 13½° East.

Dependent Resurvey of the South Boundary,  
Township 11 North, Range 10 East

Reestablishment of the Survey Executed  
by Campbell and Oakes in 1904

The Tp. cor. of Tps. 10 and 11 N., Rs. 10 and 11 E., monumented by a granite stone, 6 x 4 x 8 ins., firmly set and plainly mkd. with 6 notches on S. face and other faces very faintly notched, from which the original bearing trees

A juniper, 14 ins. diam., bears N. 45° E.,  
197½ lks. dist., mkd. T11N R11E S 31 BT.

A pine, 24 ins. diam., bears S. 48¼° E., 107½  
lks. dist., with sealed blaze (cut into blaze  
to confirm it as a BT).

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>A pine, 19 ins. diam., bears S. 75½° W., 104 lks. dist., with a partially sealed blaze, scribe marks visible but illegible.</p> <p>A cedar, 15 ins. diam., bears N. 17° W., 144 lks. dist., illegibly scribed.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">           T11N            R10E R11E  <u>S 36   S 31</u>            S 1   S 6            T10N            1967         </p> <p>from which</p> <p>A pine, 16 ins. diam., bears S. 66° E., 116 lks. dist., mkd. T10N R11E S 6 BT.</p> <p>A pine, 10 ins. diam., bears N. 71° W., 69½ lks. dist., mkd. T11N R10E S 36 BT.</p> <p>Bury the orig. cor. stone alongside the iron post. N. 89°38' W., bet. secs. 1 and 36.</p> <p>Over rolling land, through medium timber and undergrowth.</p> <p>4.10 Ridge, bears SE. and NW.</p> <p>14.80 Large granite boulder, bears South, 150 lks. dist.</p> <p>25.00 Rocky spur, slopes South.</p> <p>30.00 Draw, drains S. 30° E.</p> <p>39.00 Spur, slopes N.</p> <p>39.92 The ¼ sec. cor. of secs. 1 and 36, monumented by a granite stone, 6x4x10 ins., firmly set and plainly mkd. ¼ on N. face, from which an original bearing tree</p> <p style="text-align: center;">           A juniper, 20½ ins. diam., bears S. 69° W., 108½ lks. dist., mkd. ¼ S 1 BT.         </p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">           T11N R10E  <u>¼ S 36</u>            S 1            T10N            1967         </p> <p>from which</p> <p>A pine, 9 ins. diam., bears S. 50¾° E., 36½ lks. dist., mkd. T10N R10E ¼ S 1 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°50' W., beginning new measurement.</p>

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS											
7.40	Ravine, drains irregularly W.										
20.00	Ravine, drains N.										
32.60	Ravine, drains N. 20° W.; track road follows along the ravine.										
34.80	Ravine, drains N. 20° E.										
39.90	<p>The cor. of secs. 1, 2, 35 and 36, monumented by a granite stone, 6x4x12 ins., firmly set and plainly mkd. with 1 notch on E. and 5 notches on W. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 17½ ins. diam., bears S. 30¼° E., 154½ lks. dist., mkd. T10N R10E S 1 BT.</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears N. 20½° W., 104½ lks. dist., mkd. S 35 BT.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T11N</td> <td style="padding: 0 5px;">R10E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 35</td> <td style="padding: 0 5px; border-right: 1px solid black;">S 36</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 2</td> <td style="padding: 0 5px; border-right: 1px solid black;">S 1</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T10N</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1967</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 21½° E., 79 lks. dist., mkd. T11N R10E S36 BT.</p> <p style="padding-left: 40px;">A pine, 17½ ins. diam., bears N. 80¾° W., 53 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 13¼° W., 124½ lks. dist., mkd. T11N R10E S 35 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, gravelly loam. Timber, medium pine and juniper, with some oak. Undergrowth, dense manzanita, cat claw and cacti.</p> <hr/> <p>The remainder of the south boundary was found defective in measurement. Original corners have been altered to function for T. 10 N., R. 10 E. only, and new corners established for T. 11 N., R. 10 E., at 40.00 ch. intervals.</p> <p>N. 89°34' W., along the N. bdy. of sec. 2, T. 10 N., R. 10 E.</p> <p>Over rolling land, through medium timber and undergrowth.</p>	T11N	R10E	S 35	S 36	S 2	S 1	T10N		1967	
T11N	R10E										
S 35	S 36										
S 2	S 1										
T10N											
1967											
5.20	Power line, bears N. 71½° E. and S. 71½° W.										
14.10	Fence, bears N. 60° E. and S. 60° W.										
17.60	State Highway, No. 160, bears N. 62° E. and S. 62° W.										

BOOK 4832

4.

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS		
21.50	Bladed road (old highway), bears N. 20° E. and S. 20° W.	
28.80	<p>Spur, slopes South; highway marker bears North, 65 lks. dist., brass cap mkd.</p> <p style="text-align: center;">Arizona Highway Dept. P &amp; M 349-2 1966</p>	
31.70	Ravine, drains S.	
38.95	<p>The <math>\frac{1}{4}</math> sec. cor. originally set for secs. 2 and 35, monumented by a granite stone, 4x6x12 ins., firmly set and plainly mkd. <math>\frac{1}{4}</math> on N. face, from which an original bearing tree</p> <p style="text-align: center;">A pine, 22<math>\frac{1}{2}</math> ins. diam., bears S. 14<math>\frac{1}{2}</math>° W., 125 lks. dist., with sealed blaze.</p> <p>This cor. now functions as the <math>\frac{1}{4}</math> sec. cor. of sec. 2, T. 10 N., R. 10 E. only.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N <hr style="width: 50px; margin: auto;"/><math>\frac{1}{4}</math> S 2 T10N R10E 1967</p> <p>from which</p> <p style="text-align: center;">A pine, 6<math>\frac{1}{2}</math> ins. diam., bears S. 13<math>\frac{3}{4}</math>° E., 73<math>\frac{1}{2}</math> lks. dist., mkd. T10N R10E <math>\frac{1}{4}</math> S 2 BT.</p> <p style="text-align: center;">An oak, 7 ins. diam., bears S. 41° W., 79 lks. dist., mkd. T10N R10E <math>\frac{1}{4}</math> S 2 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p style="text-align: center;"><hr style="width: 200px; margin: auto;"/></p> <p>N. 89°48' W., beginning new measurement.</p>	
1.05	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 35, T. 11 N., R. 10 E.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E <hr style="width: 50px; margin: auto;"/><math>\frac{1}{4}</math> S 35 T10N 1967</p> <p>from which</p> <p style="text-align: center;">A pine, 7<math>\frac{1}{2}</math> ins. diam., bears N. 32<math>\frac{1}{4}</math>° E., 90<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 35 BT.</p> <p style="text-align: center;">A pine, 10 ins. diam., bears N. 84<math>\frac{1}{4}</math>° W., 74 lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 35 BT.</p>	

CHAINS	
6.60	N. end of gravel pit.
11.50	Track road, bears S. 20° E. and N. 20° W.
26.00	Track road, bears N. and SE.
32.10	Spur, slopes S.
35.80	Low ridge, bears N. and S.
40.04	<p>The cor. orig. set for secs. 2, 3, 34 and 35, monumented by a granite stone, 12x9x9 ins. above ground, firmly set and plainly mkd. with 2 notches on the E. and 4 notches on the W. face and an "X" on top, from which the original bearing trees</p> <p>A pine, bears N. 16½° E., 11 lks. dist., mks. illegible.</p> <p>An oak, bears S. 21½° E., 105 lks. dist., mks. illegible.</p> <p>A pine, bears N. 51° W., 95 lks. dist., mkd. with an overgrown blaze.</p> <p>This cor. now functions as the cor. of secs. 2 and 3, T. 10 N., R. 10 E. only.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E  <math>\frac{S \ 35}{S \ 3   S \ 2}</math>  T10N  1967</p> <p>from which</p> <p>A pine, 7½ ins. diam., bears S. 14½° E., 35 lks. dist., mkd. T10N R10E S 2 BT.</p> <p>A pine, 10 ins. diam., bears S. 66½° W., 40 lks. dist., mkd. T10N R10E S 3 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling.  Soil, gravel loam.  Timber, medium pine and juniper, scattered oak.  Undergrowth, dense manzanita, scattered cacti.</p>
1.01	<p>N. 89°41' W., along the N. bdy. of sec. 3, T. 10 N., R. 10 E.</p> <p>Over gently rolling land, through medium timber and undergrowth.</p> <p>Point for the cor. of secs. 34 and 35, T. 11 N., R. 10 E.</p>

BOOK 4832

6.

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E  <u>S 34   S 35</u>                      S 3                      T10N                      1967</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears N. 24° E., 66½ lks. dist., mkd. T11N R10E S 35 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 49¾° W., 135½ lks. dist., mkd. T11N R10E S 34 BT.</p>
8.10	<p>Fence, bears S. 2° W. and N. 2° E. 170 lks. to fence extending irreg. W.</p>
9.10	<p>Track road, bears S. and N. 100 lks., thence irreg. W. along fence line.</p>
20.045	<p>Point for the E 1/16 sec. cor. of sec. 3, T. 10 N., R. 10 E., at proportionate dist.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E  <hr style="width: 10%; margin: auto;"/>                     E 1/16 S 3                      T10N                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7½ ins. diam., bears S. 75¾° E., 43½ lks. dist., mkd. T10N R10E E 1/16 S 3 BT.</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S. 10¼° W., 73 lks. dist., mkd. T10N R10E E 1/16 S 3 BT.</p>
40.09	<p>The ¼ sec. cor. orig. set for secs. 3 and 34, monumented by a granite stone, 6x6x6 ins. above ground, firmly set in a concrete collar, plainly mkd. ¼ on N. face and X on top, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, bears N. 37½° E., 50 lks. dist., mkd. ¼ S 34. I remove the 34.</p> <p style="padding-left: 40px;">An oak, bears S. 60½° E., 83 lks. dist., mkd. with scribe mks. visible but illegible.</p> <p>This cor. now functions as the ¼ sec. cor. of sec. 3, T. 10 N., R. 10 E. only.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E  <hr style="width: 10%; margin: auto;"/>                     ¼ S 3                      T10N                      1967</p>



CHAINS	
	<p>from which</p> <p>A pine, 9 ins. diam., bears S. 25½° E., 60½ lks. dist., mkd. T10N R10E ¼ S 3 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>N. 89°43' W., beginning new measurement.</p>
0.92	<p>Point for the ¼ sec. cor. of sec. 34, T. 11 N., R. 10 E.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E ¼ S 34</p> <p style="text-align: center;">T10N 1967</p>
	<p>from which</p> <p>A pine, 11 ins. diam., bears N. 73° E., 51 lks. dist., mkd. T11N R10E ¼ S 34 BT.</p> <p>A pine, 16 ins. diam., bears N. 41½° W., 62 lks. dist., mkd. T11N R10E ¼ S 34 BT.</p>
13.90	<p>Track road, bears S. and N. 100 lks. to dead end.</p>
26.95	<p>State Highway No. 87, bears N. 1°53' E. and S. 1°53' W.; cattle guard bears North, 30 lks. dist.</p>
36.10	<p>Low sag, drains N.</p>
40.08	<p>The cor. orig. set for secs. 3, 4, 33 and 34 is determined by using record distance from three of the original bearing trees</p> <p>A pine, 17 ins. diam., bears N. 25¾° E., 78 lks. dist., mkd. T11N R10E S 34 BT. (Record - N. 24° E., 78 lks.) I remove S 34 from the bearing tree</p> <p>A juniper, 12 ins. diam., bears S. 32° E., 46 lks. dist., mkd. T10N R10E S 3 BT.</p> <p>A juniper, 20 ins. diam., bears S. 87° W., 112 lks. dist., mkd. T10N R10E S 4 BT. (Record - S. 89° W., 112 lks. dist.)</p> <p>An oak, 11 ins. diam., bears N. 31½° W., 138 lks. dist., mkd. with an overgrown blaze. (Record - N. 31° W., 138 lks. dist.)</p> <p>This corner now functions as the cor. of secs. 3 and 4, T. 10 N., R. 10 E. only.</p> <p>At the corner point</p>

BOOK 4832

8.

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">                     T11N R10E  <u>    S 34</u>                      S 4   S 3                      T10N                      1967                 </p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears S. 59<math>\frac{3}{4}</math>° E., 91 lks. dist., mkd. T10N R10E S 3 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 83<math>\frac{1}{2}</math>° W., 54 lks. dist., mkd. T10N R10E S 4 BT.</p> <p>The corner is 28 lks. south of a fence bearing E. and W.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, medium pine and juniper, with some oak.                      Undergrowth, dense manzanita with oak brush and cacti.</p>
<p>0.84</p> <p>4.00</p> <p>22.80</p> <p>25.40</p> <p>33.50</p> <p>38.70</p> <p>40.24</p>	<p>N. 89°36' W., along the N. bdy. of sec. 4.</p> <p>Over rolling land, through medium timber and undergrowth.</p> <p>Point for the cor. of secs. 33 and 34, T. 11 N., R. 10 E.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">                     T11N R10E  <u>    S 33   S 34</u>                      S 4                      T10N                      1967                 </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 35<math>\frac{1}{4}</math>° E., 57 lks. dist., mkd. T11N R10E S 34 BT.</p> <p style="padding-left: 40px;">An oak, 9 ins. diam., bears N. 36<math>\frac{1}{2}</math>° W., 50 lks. dist., mkd. T11N R10E S 33 BT.</p> <p>Small draw, drains N.</p> <p>Bladed road, bears N. 13<math>\frac{1}{2}</math>° E. and S. 13<math>\frac{1}{2}</math>° W.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains South for 60 lks., thence S. 60° W.</p> <p>Power line, bears N. 18°40' E. and S. 18°40' W.</p> <p>Fence cor., fences bear E., S. and W.</p> <p>The <math>\frac{1}{4}</math> sec. cor. originally set for secs. 4 and 33, monumented by a granite stone, 12x10x18 ins., firmly set in a collar of stone and plainly mkd. <math>\frac{1}{4}</math> on the N. face, from which the original bearing trees</p>

CHAINS	
	<p>A dead cedar, 11 ins. diam., bears S. 34° E., 45½ lks. dist., mkd. ¼ S 4 BT.</p> <p>A stump, 12½ ins. diam., bears N. 63° W., 50 lks. dist., mkd. S 33 BT. (I remove the S 33.)</p> <p>This cor. now functions as the ¼ sec. cor. of sec. 4, T. 10 N., R. 10 E. only.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N ----- ¼ S 4 T10N R10E 1967</p> <p>from which</p> <p>A pine, 12 ins. diam., bears S. 35¾° W., 48½ lks. dist., mkd. T10N R10E ¼ S 4 BT.</p> <p>A power pole, with spike in it, bears N. 44½° W., 82 lks. dist.</p> <p>Deposit the orig. cor. stone in the mound, alongside the iron post.</p> <p>Cor. falls on E-W. fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°47' W., beginning new measurement.</p>
0.60	<p>Point for the ¼ sec. cor. of sec. 33, T. 11 N., R. 10 E.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E ----- ¼ S 33 T10N 1967</p> <p>from which</p> <p>A power pole with spike in it, bears N. 2½° E., 57½ lks. dist.</p> <p>An oak, 13 ins. diam., bears N. 85½° W., 111½ lks. dist., mkd. T11N R10E ¼ S 33 BT.</p> <p>Cor. falls beneath a power line bearing S. and N.</p>
21.50	<p>Spur, slopes S.</p>
31.40	<p>Wash, 30 lks. wide, 2 ft. deep, drains SW.</p>
39.80	<p>Wash, 15 lks. wide, 3 ft. deep, drains irregularly S.</p>
40.30	<p>The cor. orig. set for secs. 4, 5, 32 and 33, determined from the remains of three original bearing trees</p>

BOOK 4832

10.

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS

An oak, 12½ ins. diam., bears N. 57½° E., 103 lks. dist., with sealed blaze.

An oak, 15 ins. diam., bears S. 62¼° E., 86 lks. dist., with sealed blaze.

An oak, 11¼ ins. diam., bears N. 21¼° W., 70 lks. dist., illegibly scribed.

This cor. now functions as the cor. of secs. 4 and 5, T. 10 N., R. 10 E. only.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T11N  
S 33  
-----  
S 5 | S 4  
T10N R10E

1967

from which

A juniper, 5 ins. diam., bears S. 27¾° E., 54 lks. dist., mkd. T10N R10E S 4 BT.

A pine, 17½ ins. diam., bears S. 71¼° W., 67 lks. dist., mkd. T10N R10E S 5 BT.

A granite stone, 22x12x4 ins., lying loose on the ground alongside fence cor. of fences bearing S. and E., plainly mkd. with 4 notches and WC on one face, and 2 notches on **opposite** face, bears N. 16° E., 7 lks. dist. (Record gives no mention of a witness corner and bearing trees do not fit.) Bury the stone at this point.

Land, nearly level.

Soil, gravel loam.

Timber, medium pine and oak.

Undergrowth, medium manzanita and oak brush.

N. 89°38' W., along the N. bdy. of sec. 5.

Over rolling land, through medium dense timber and undergrowth.

0.30 Point for the cor. of secs. 32 and 33, T. 11 N., R. 10 E.

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T11N R10E  
S 32 | S 33  
-----  
S 5  
T10N

1967

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>from which</p> <p>A cedar, 10 ins. diam., bears N. 9° E., 87½ lks. dist., mkd. T11N R10E S 33 BT.</p> <p>A pine, 21½ ins. diam., bears N. 30° W., 52 lks. dist., mkd. T11N R10E S 32 BT.</p>
11.50	Wash, 20 lks. wide, 1 ft. deep, drains S. 15° E.
22.90	Small ravine, drains S.
28.90	Rocky wash, 10 lks. wide, 1 ft. deep, drains S. 30° E.
35.50	Wash, 10 lks. wide, 2 ft. deep, drains S.
39.53	<p>The ¼ sec. cor. orig. set for secs. 5 and 32, monumented by a granite stone, 15x8x6 ins., loosely set and plainly mkd. ¼ on N. face, from which an original bearing tree</p> <p>A pine, 15½ ins. diam., bears N. 25½° E., 100 lks. dist., illegibly scribed.</p> <p>This cor. now functions as the ¼ sec. cor. of sec. 5, T. 10 N., R. 10 E. only.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N</p> <p style="text-align: center;"> <math display="block">\frac{1}{4} S 5</math>             T10N R10E           </p> <p style="text-align: center;">1967</p> <p>from which</p> <p>A juniper, 9 ins. diam., bears S. 9¾° E., 115 lks. dist., mkd. T10N R10E ¼ S 5 BT.</p> <p>A power pole, bears S. 67° W., 11½ lks. dist.</p> <p>Deposit the orig. cor. stone in the mound of stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 89°48' W., beginning new measurement.</p>
0.10	Power line, bears N., S. and W.; thence along cleared area for power line.
0.77	<p>Point for the ¼ sec. cor. of sec. 32, T. 11 N., R. 10 E.</p> <p>Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E</p> <p style="text-align: center;"> <math display="block">\frac{1}{4} S 32</math>             T10N           </p> <p style="text-align: center;">1967</p>

BOOK 4832

12.

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS	
11.20	Fence, bears N. and S.; enter medium dense young cedar and juniper.
17.50	Ridge, bears N. and S.
32.60	Wash, 20 lks. wide, 3 ft. deep, drains irregularly S.
39.15	Bladed road, bears N. and S.
40.01	<p>The cor. orig. set for secs. 5, 6, 31 and 32, identical with Cor. 1 of H.E.S. 576, monumented by a granite stone, 12x8x20 ins., firmly set and plainly mkd. with 5 notches on E. and 1 notch on W. face, with + on top. This cor. now functions as the cor. of secs. 5 and 6, T. 10 N., R. 10 E. only, and Cor. No. 1 of H.E.S. 576, from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 19 ins. diam., bears S. 19° W., 309 lks. dist., mkd. 10 N 10E S 6 BT.</p> <p style="padding-left: 40px;">A dead cedar, 12½ ins. diam., bears S. 6¾° E., 201 lks. dist., mkd. T10N R10E S 5 BT.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T11N              HES 576              Cor 1 S 32              S 6   S 5              T10N R10E              1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears S. 55½° E., 172 lks. dist., mkd. T10N R10E S 5 BT.</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears S. 9¾° E., 55½ lks. dist., mkd. T10N R10E S 5 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. falls beneath power line 4 lks. N. of a fence bearing irreg. W.</p> <p>A granite stone, 9x4x12 ins. above the ground, firmly set and plainly mkd. 1 HES 576 on N. face was located on the NW. side of the orig. cor. stone, from which the original bearing trees</p> <p style="padding-left: 40px;">A dead cedar, 17 ins. diam., bears S. 55½° E., 337 lks. dist., mkd. HES 576 X BT.              (Record, S. 57°20' E., 342 lks. dist.)</p> <p style="padding-left: 40px;">A cedar limb, 7½ ins. diam., bears S. 32° W., 322 lks. dist., mkd. 1 HES 576 X BT.              (Record, S. 30°45' W., 403 lks. dist.)</p> <p>Bury this stone on the NW. side of the iron post.</p> <p>Land, gently rolling.              Soil, rocky loam.              Timber, medium dense pine and juniper with scattered oak.              Undergrowth, medium manzanita with oak brush, Spanish bayonet and cacti.</p>

CHAINS	
	S. 89°39' W., along the N. bdy. of sec. 6.
	Over rolling land, through medium dense timber.
0.40	Fence, bears irregularly E. and W.
0.76	Point for the cor. of secs. 31 and 32, T. 11 N., R. 10 E.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<div style="text-align: center;">                     T11N R10E  <u>S 31   S 32</u>                      S 6                      T10N                      1967                 </div>
	Raise a mound of stone N. of the cor.
	Cor. falls 5 lks. S. of fence line, bearing irreg. E. and W.
15.00	Cor. No. 2 of H.E.S. 576, monumented by a granite stone, 4x6x7 ins. above the ground, firmly set and plainly mkd. 2 HES 576 on the N. face and CC on the W. face, from which original accessories
	A rock in place, bears S. 70½° E., 117 lks. dist., mkd. 2 HES XBR.
	A dead cedar, 25 ins. diam., bears S. 8½° W., 66½ lks. dist., mkd. 2 HES 576 XBT. (Record, S. 9°05' W., 680 lks. dist.)
	A new bearing tree
	A pine, 5 ins. diam., bears S. 36½° W., 21 lks. dist., mkd. HES 576 BT.
	A cor. of fences bearing N. and E., bears N. 43½° W., 29 lks. dist.
	N. 89°32' W., beginning new measurement.
3.00	Enter mature pine and juniper; leave young juniper.
18.70	Ridge, bears SE. and NW.
20.90	Fence, bears S. 30° E. and N. 30° W.
25.06	The ¼ sec. cor. orig. set for secs. 6 and 31, monumented by a rock in place, 15x10x2 ft. above the ground, mkd. ¼ and a mound of stone N., from which the original bearing tree
	A juniper, 20 ins. diam., bears N. 30½° E., 237 lks. dist., mkd. ¼ S 31 BT. (Removed S 31 from BT.)
	This cor. now functions as the ¼ sec. cor. of sec. 6, T. 10 N., R. 10 E. only.
	At the corner point

Dep. Resurvey, South Bdy., T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>Cement a standard brass tablet in a drill hole in solid rock, brass cap mkd.</p> <p style="text-align: center;">T11N</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;"><math>\frac{1}{4}</math> S 6 T10N R10E 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. <math>29\frac{1}{2}^{\circ}</math> E., 107<math>\frac{1}{2}</math> lks. dist., mkd. T10N R10E <math>\frac{1}{4}</math> S 6 BT.</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. <math>64\frac{1}{2}^{\circ}</math> W., 43 lks. dist., mkd. T10N R10E <math>\frac{1}{4}</math> S 6 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. <math>89^{\circ}51'</math> W., beginning new measurement.</p>
0.70	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 31, T. 11 N., R. 10 E.</p> <p>Cement a standard brass tablet in a drill hole in rock in place, 4x4x3 ft. above the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E <math>\frac{1}{4}</math> S 31 T10N 1967</p> <p>Desc. steep W. slope.</p>
15.00	Deep ravine, drains SE.
27.70	Granite ledge, 15 ft. high, bears irregularly N. and S.
29.70	Top of knoll.
39.46	<p>The cor. of Tps. 10 and 11 N., Rs. 9 and 10 E., monumented by a sandstone, 6x8x16 ins., firmly set and plainly mkd. with 6 notches on each edge and a mound of stone to the S., from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. <math>26\frac{1}{4}^{\circ}</math> E., 83<math>\frac{1}{2}</math> lks. dist., illegibly scribed.</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears S. <math>63\frac{1}{2}^{\circ}</math> E., 80<math>\frac{1}{2}</math> lks. dist., mkd. T10N RS.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. <math>8^{\circ}</math> W., 53 lks. dist., mkd. T10N R9E S 1 BT.</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. <math>59\frac{1}{2}^{\circ}</math> W., 120 lks. dist., mkd. T11N R9E S 36 BT.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R9E R10E <u>S36   S31</u> S 1   S 6 T10N 1967</p>



Dep. Resurvey, Portion, East Bdy., T.11 N., R.10 E., Arizona

CHAINS	
	<p>from which</p> <p>A pine, 10 ins. diam., bears S. <math>58\frac{3}{4}^{\circ}</math> E., 110<math>\frac{1}{2}</math> lks. dist., mkd. T10N R10E S 6 BT.</p> <p>A pine, 6 ins. diam., bears S. <math>17\frac{1}{2}^{\circ}</math> W., 11<math>\frac{1}{2}</math> lks. dist., mkd. T10N R9E S 1 BT.</p> <p>U.S.M.M. No. 5, bears N. <math>32^{\circ}01'</math> E., 15.90 chs. dist., monumented by a post, 6 ins. diam., 5 ft. long, with a scattered mound of stone alongside. From U.S.M.M. No. 5, Cor. No. 2 of the Summit Mining Claim, Mineral Survey 783, bears N. <math>33^{\circ}</math> W., 86 lks. dist., monu- mented by a stone mkd. 2 N, set in a cairn.</p> <p>Deposit the orig. cor. in the mound of stone alongside the iron post.</p> <p>Land, rolling and broken, last half. Soil, gravelly loam. Timber, medium dense pine and juniper, first half, and scattered timber, last half. Undergrowth, medium manzanita and oak brush with cacti and Spanish bayonet.</p>
	<p>Dependent Resurvey of a Portion of the East Boundary Township 11 North, Range 10 East</p>
	<p>Reestablishment of the Survey Executed by C. L. Campbell in 1904</p> <hr/> <p>From the Tp. cor. of Tps. 10 and 11 N., Rs. 10 and 11 E.</p> <p>N. <math>0^{\circ}05'</math> E., bet. secs. 31 and 36.</p> <p>Over rolling land, through medium timber and under- growth.</p> <p>3.50 Draw, drains NE.</p> <p>5.60 Spur, slopes SE.</p> <p>8.90 Draw with track road in bottom, drains SE.</p> <p>22.40 Ridge, bears E. and W.</p> <p>26.50 Power line, bears N. <math>65^{\circ}</math> E. and S. <math>65^{\circ}</math> W.</p> <p>29.30 Fence, bears N. <math>85^{\circ}</math> E. and S. <math>85^{\circ}</math> W.</p> <p>30.75 State Highway No. 160, bears N. <math>86^{\circ}</math> E. and S. <math>86^{\circ}</math> W.</p> <p>33.60 Ridge, bears SE. and NW.; power line, bears N. and E.</p> <p>39.65 Bladed road, bears N. along power line and E.</p> <p>39.98 The <math>\frac{1}{2}</math> sec. cor. of secs. 31 and 36, identical with Cor. 10, H.E.S. 420, monumented by a granite stone, 10x8x6 ins., buried 4 ins. below the ground, mkd. 4 on W. face (top of stone is missing) and a <math>\frac{3}{4}</math> ins. water pipe driven alongside.</p> <p>There is no evidence of the original bearing trees.</p>

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E R11E HES 420 COR 10     <math>\frac{1}{4}</math> S 36 S 31 1967</p> <p>from which</p> <p>A pine, 7<math>\frac{1}{2}</math> ins. diam., bears S. 45° E., 5 lks. dist., mkd. T11N R11E <math>\frac{1}{4}</math> S 31 BT.</p> <p>A power pole, No. PS 49025, bears S. 3<math>\frac{1}{4}</math>° W., 74 lks. dist.</p> <p>A pine, 12<math>\frac{1}{2}</math> ins. diam., bears S. 71° W., 123<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 36 BT.</p> <p>Set a post, 3 ins. diam. and 4 ft. long, alongside the cor.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Corner falls on E. edge of road, bearing N.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°18' E., beginning new measurement.</p> <p>Along E. edge of road.</p>
9.10	Bladed road, bears E. and W.; end of N-S. road.
9.96	<p>Cor. No. 13 of HES 420, monumented by a granite stone, 17x7x6 ins. above the ground, firmly set and plainly mkd. 13 HES 420 on the S. face and CC on N. face.</p> <p>from which</p> <p>A cedar, 6 ins. diam., bears N. 58<math>\frac{1}{2}</math>° W., 38 lks. dist., illegibly scribed.</p>
15.60	Top of W. side of hill; bladed road bears SE. and NW.
28.30	Wash, 25 lks. wide, 2 ft. deep, drains S. 70° E.
35.20	Chimney on W. face of house bears East, 8 lks. dist.; power line ends at house.
39.99	<p>The cor. of secs. 25, 30, 31 and 36, identical with Cor. No. 1, H.E.S. 420, monumented by a granite stone, 12x12x20 ins., firmly set and plainly mkd. with 1 notch on S., 5 notches on N. face and + on top, with a mound of stone W. An old wooden pole is set alongside the cor., from which the original bearing trees</p> <p>A limb of a two-forked juniper, 13 ins. diam., bears S. 40<math>\frac{1}{2}</math>° E., 102 lks. dist., mkd. HES 420 XBT.</p> <p>The other limb of the above juniper, 14 ins. diam., bears S. 39<math>\frac{1}{4}</math>° E., 102 lks. dist., mkd. T11N R11E S 31 BT.</p> <p>A juniper, 6<math>\frac{1}{2}</math> ins. diam., bears S. 79° W., 39 lks. dist., mkd. HES 420 BT.</p>

## Dep. Resurvey, Portion, East Bdy., T.11 N., R. 10 E., Arizona

CHAINS		
	<p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E R11E S 25   S 30 S 36   S 31 HES 420 COR 1 1967</p> <p>from which</p> <p>A cedar, 11 ins. diam., bears S. <math>9\frac{3}{4}^{\circ}</math> W., 70 lks. dist., mkd. T11N R10E S 36 BT.</p> <p>A pine, 7 ins. diam., bears S. <math>47\frac{1}{4}^{\circ}</math> W., 57 lks. dist., mkd. T11N R10E S 36 BT.</p> <p>The NE. cor. of Seismological Building #8003, bears S. <math>68^{\circ}06'</math> W., 19.25 chs. dist.</p> <p>The NE. cor. of Storage Building #8004, bears S. <math>61^{\circ}50'</math> W., 21.20 chs. dist.</p> <p>The NE. cor. of warehouse, bears S. <math>60^{\circ}31'</math> W., 21.45 lks. dist.</p> <p>Deposit the orig. cor. stone in the mound of stone alongside the iron post.</p> <p>Cor. falls on SE. side of small knoll.</p> <p>Land, rolling. Soil, gravel loam. Timber, medium pine, oak, and juniper. Undergrowth, medium dense manzanita with some oak brush, cat claw, cacti and Spanish bayonet.</p>	
	<p>N. <math>0^{\circ}06'</math> E., bet. secs. 25 and 30.</p> <p>Over rolling land, through medium timber and undergrowth.</p> <p>0.30 Top of small knoll.</p> <p>1.70 Draw, drains S. <math>60^{\circ}</math> E.</p> <p>4.30 Draw, drains W.</p> <p>7.90 Spur, slopes N. <math>60^{\circ}</math> W.</p> <p>10.30 Wash, 15 lks. wide, 3 ft. deep, drains S. <math>20^{\circ}</math> W.</p> <p>28.10 Paved road, bears irregularly E. and W.</p> <p>29.80 Top of hill.</p> <p>35.60 Track road, bears N. <math>80^{\circ}</math> E. and S. <math>80^{\circ}</math> W.</p>	

CHAINS	
39.95	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, monumented by a granite stone, 7x3x10 ins., firmly set and plainly mkd. <math>\frac{1}{4}</math> on W. face, and a mound of stone to the W., from which original bearing trees</p> <p>An oak, 9 ins. diam., bears N. 49° E., 11 lks. dist., mkd. with a sealed blaze</p> <p>A cedar, 18 ins. diam., bears N. 78<math>\frac{1}{4}</math>° W., 51 lks. dist., mkd. <math>\frac{1}{4}</math> S 25 BT.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E R11E <math>\frac{1}{4}</math> S 25   S 30 1967</p> <p>from which</p> <p>A cedar, 12 ins. diam., bears N. 20° E., 49 lks. dist., mkd. T11N R11E <math>\frac{1}{4}</math> S 30 BT.</p> <p>Deposit the orig. cor. stone in mound of stone alongside the iron post.</p> <p>Cor. falls on W. slope, 30 lks. E. of small draw draining S.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°07' E., beginning new measurement.</p>
5.10	Bladed road, bears N. 30° E. and S. 30° W.
13.00	Spur, slopes W. from high knoll, 3 chs. E.
26.20	E. edge of small wire corral enclosing a seismometer installation.
33.20	Spur, slopes NE.
34.10	Wash, 20 lks. wide, 6 ft. deep, drains S. 80° E.
39.98	<p>The cor. of secs. 19, 24, 25 and 30, monumented by a granite stone, 4x6x14 ins., firmly set and plainly mkd. with 2 notches on S. and 4 notches on N. face, from which original bearing trees</p> <p>A juniper, 9 ins. diam., bears N. 21<math>\frac{3}{4}</math>° E., 62<math>\frac{1}{2}</math> lks. dist., mkd. R11E S 19 BT.</p> <p>A dead juniper, 7 ins. diam., bears S. 31° E., 46 lks. dist., illegibly scribed.</p> <p>A dead juniper, 9 ins. diam., bears S. 1<math>\frac{1}{2}</math>° W., 77<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E S 25 BT.</p> <p>A dead juniper, 12<math>\frac{1}{2}</math> ins. diam., bears N. 51<math>\frac{1}{2}</math>° W., 31 lks. dist., mkd. T11N R10E S 24 BT.</p> <p>At the corner point</p>

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E R11E S 24   S 19 S 25   S 30</p> <p style="text-align: center;">1967</p> <p>from which</p> <p>A cedar, 7 ins. diam., bears S. 60<math>\frac{3}{4}</math>° E., 45<math>\frac{1}{2}</math> lks. dist., mkd. T11N R11E S 30 BT.</p> <p>A pine, 11 ins. diam., bears N. 80<math>\frac{1}{4}</math>° W., 105<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E S 24 BT.</p> <p>A cedar, 11 ins. diam., bears N. 28<math>\frac{1}{2}</math>° W., 37<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E S 24 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, light gravel loam. Timber, medium dense pine and juniper, with some oak. Undergrowth, dense manzanita with oak brush, cat claw, cacti and Spanish bayonet.</p>
	<p>Survey of a Portion of the Subdivisional Lines Township 11 North, Range 10 East</p>
	<p>The defective conditions found in the resurvey of the south boundary and a portion of the east boundary indicate the rectangular limits for subdivisional surveys was likely to be reached at an early stage. Therefore, a sectional correction line was surveyed west on a true latitudinal curve from the sec. cor. of secs. 25, 30, 31 and 36, on the east boundary, to an intersection with the west boundary where a closing corner was established. A sectional guide meridian was surveyed north from the cor. of sections 1, 2, 35 and 36 on the south boundary of the township.</p> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>North, on a sectional guide meridian, bet. secs. 35 and 36.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>
2.75	Power line, bears N. 71 $\frac{1}{2}$ ° E. and S. 71 $\frac{1}{2}$ ° W.
7.40	Fence, bears N. 80° E. and S. 80° W.
9.30	State Highway No. 160, bears N. 80° E. and S. 80° W.
9.80	Track road, bears N. 60° W. and S. 30° E. to highway.
13.20	Spur, slopes E.
31.80	Ravine, drains N. 30° E.; track road, bears N. 30° E. and S. 30° W.
37.10	Spur, slopes NE.

BOOK 4832

20.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS		
39.65	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E <math>\frac{1}{4}</math> S 35 S 36 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. <math>20\frac{3}{4}^{\circ}</math> E., 24<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 36 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. <math>54\frac{1}{2}^{\circ}</math> W., 18<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 35 BT.</p>	
40.80	Wash, 30 lks. wide, 2 ft. deep, drains irregularly E.	
42.30	Track road, bears irregularly E. and W.	
51.60	Ridge, bears SE. and NW.	
68.70	Gulch, 100 lks. wide, 8 ft. deep, with small stream in bottom, course S. $60^{\circ}$ E.	
74.10	Track road, bears SE. and NW.	
77.40	Track road, bears SE. and NW.	
79.65	<p>Intersect the sectional correction line.</p> <p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E S 26 S 25 S 35 S 36 1967</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears N. <math>51\frac{1}{2}^{\circ}</math> E., 67<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E S 25 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. <math>35\frac{1}{2}^{\circ}</math> W., 151<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E S 26 BT.</p> <p style="padding-left: 40px;">SW. cor. of a cabin, bears N. <math>82\frac{1}{4}^{\circ}</math> W., 690 lks. dist.</p> <p style="padding-left: 40px;">SW. cor. of a cabin, on NE. cor. of cleared pasture, bears N. <math>58\frac{1}{2}^{\circ}</math> W., 13.60 chs. dist.</p> <p>Land, rolling. Soil, gravel loam. Timber, medium dense pine and juniper. Undergrowth, medium manzanita and oak brush.</p>	
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>West, on a sectional correction line bet. secs. 25 and 36.</p>	

## Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	
	Over rolling land, through medium timber and undergrowth.
5.70	Power line, bears N. and S.
5.80	Track road, bears SE. and N. 30° W. to paved road.
7.20	Wash, 30 lks. wide, 2 ft. deep, drains S.
8.80	Paved road, bears N. 20° W. and S. 20° E., 100 lks., thence irreg. W. to parking lot for seismological buildings.
40.13	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.  Set the iron post 18 ins. in the ground, brass cap mkd.  T11N R10E $\frac{1}{4}$ S 25 S 36  1967  from which  A juniper, 10 ins. in diam., bears S. 87 $\frac{1}{2}$ ° E., 61 lks. dist., mkd. T11N R10E $\frac{1}{4}$ S 36 BT.  A pine, 5 ins. diam., bears N. 10° W., 57 lks. dist., mkd. T11N R10E $\frac{1}{4}$ S 25 BT.
47.60	Ridge, bears N. and S.
52.50	Wash, 10 lks. wide, 1 ft. deep, drains SW.
63.90	Wash, with small stream of flowing water, 10 lks. wide, 3 ft. deep, drains SE.
80.13	The cor. of secs. 25, 26, 35 and 36.  Land, rolling. Soil, gravel loam. Timber, medium pine, and juniper with scattered oak. Undergrowth, medium manzanita with oak brush and Spanish bayonet.
	North, on a sectional guide meridian, bet. secs. 25 and 26.  Over rolling land, through medium dense timber and undergrowth.
7.80	Track road, bears N. 30° E. and S. 30° W.
14.60	Spur, slopes E.
21.10	Wash, 10 lks. wide, 3 ft. deep, drains S. 60° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.  Set the iron post 20 ins. in the ground, brass cap mkd.  T11N R10E $\frac{1}{4}$ S 26   S 25  1967

BOOK 4832

22.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS		
	<p>from which</p> <p>A juniper, 7½ ins. diam., bears N. 69¼° E., 85 lks. dist., mkd. T11N R10E ¼ S 25 BT.</p> <p>A pine, 20 ins. diam., bears N. 83¾° W., 26½ lks. dist., mkd. T11N R10E ¼ S 26 BT.</p>	
40.40	Wash, 15 lks. wide, 2 ft. deep, drains irregularly NE.	
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E S 23   S 24 S 26   S 25 1967</p>	
	<p>from which</p> <p>A cedar, 8 ins. diam., bears N. 65° E., 91 lks. dist., mkd. T11N R10E S 24 BT.</p> <p>A pine, 6 ins. diam., bears S. 41½° E., 92 lks. dist., mkd. T11N R10E S 25 BT.</p> <p>A cedar, 7½ ins. diam., bears N. 24¾° W., 55 lks. dist., mkd. T11N R10E S 23 BT.</p> <p>Land, rolling. Soil, gravel loam. Timber, medium dense pine, juniper and oak. Undergrowth, medium dense manzanita and oak brush, with cat claw and Spanish bayonet.</p>	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>N. 89°55' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>	
1.50	Wash, 10 lks. wide, 1 ft. deep, drains S.	
3.40	Wash, 10 lks. wide, 1 ft. deep, drains SE.	
5.30	Wash, 30 lks. wide, 2 ft. deep, drains SE.	
10.50	Wash, 10 lks. wide, 1 ft. deep, drains NE.	
21.60	Track road, bears S. 10° E. and N. 10° W.	
26.80	Track road on top of ridge, bears NE. and SW.	
40.26	<p>Point for the ¼ sec. cor. of secs. 24 and 25.</p> <p>Set the iron post 16 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E ¼ S 24 ¼ S 25 1967</p>	



## Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS		
	<p>from which</p> <p>An oak, 10 ins. diam., bears S. 45° E., 36 lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 25 BT.</p> <p>A juniper, 12 ins. diam., bears N. 32<math>\frac{1}{4}</math>° W., 53<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 24 BT.</p>	
51.10	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.	
68.10	Wash, 20 lks. wide, 1 ft. deep, drains S. 10° E.	
79.10	Wash, 10 lks. wide, 3 ft. deep, drains S. 10° E.	
80.26	The cor. of secs. 23, 24, 25 and 26.	
	<p>Land, rolling.</p> <p>Soil, gravel loam.</p> <p>Timber, medium dense pine, juniper and oak.</p> <p>Undergrowth, medium dense manzanita and oak brush.</p>	
	<p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>	
17.80	Ravine, 20 lks. wide, 2 ft. deep, drains SW.	
25.50	Ridge, bears E. and W.	
31.50	Fence, bears N. 60° E. and S. 60° W.	
31.80	Ravine, with track road in bottom, drains N. 60° E.	
39.13	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11N R10E <math>\frac{1}{4}</math> S 34   S 35 1967</p>	
	<p>from which</p> <p>A juniper, 12<math>\frac{1}{2}</math> ins. diam., bears N. 82<math>\frac{1}{2}</math>° E., 59 lks. dist., mkd. <math>\frac{1}{4}</math> S 35 BT.</p> <p>A pine, 7<math>\frac{1}{2}</math> ins. diam., bears S. 73<math>\frac{1}{2}</math>° W., 64 lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 34 BT.</p>	
	<p>Unable to locate any evidence of Witness Point, set at 37.42 in 1956, Exchange Survey No. 680.</p>	
59.90	Wash, 10 lks. wide, 1 ft. deep, drains SE.	
66.00	Top of ridge, bears N. 30° E. and S. 30° W.	
79.13	Intersect the sectional correction line.	
	Point for the cor. of secs. 26, 27, 34 and 35.	

BOOK 4832

24.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS

Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.

T11N R10E  
 $\frac{S}{S} \frac{27}{34} | \frac{S}{S} \frac{26}{35}$

1967

from which

A pine, 10 ins. diam., bears N.  $38\frac{1}{2}^\circ$  E., 58 lks. dist., mkd. T11N R10E S 26 BT.

A pine, 20 ins. diam., bears S.  $35^\circ$  E.,  $25\frac{1}{2}$  lks. dist., mkd. T11N R10E S 35 BT.

A pine,  $12\frac{1}{2}$  ins. diam., bears S.  $70\frac{1}{4}^\circ$  W., 82 lks. dist., mkd. T11N R10E S 34 BT.

A juniper, 6 ins. diam., bears N.  $13\frac{1}{2}^\circ$  W., 98 lks. dist., mkd. T11N R10E S 27 BT.

Cor. mkd. AP 2 ES 680, monumented by a standard U.S.F.S brass cap, bears N.  $62^\circ 09'$  E., 120 lks. dist. (Removed the cor. and defaced the bearing tree in the SW. quadrant.)

Land, rolling.

Soil, gravel loam.

Timber, medium dense pine and juniper, with some oak.

Undergrowth, medium dense manzanita and oak brush.

From the cor. of secs. 25, 26, 35 and 36.

West, on the sectional correction line bet. secs. 26 and 35.

Over rolling land, through medium dense timber and undergrowth.

- 1.90 Track road, bears NE. and SW.
- 4.20 Track road, bears N. curving to W.
- 6.90 Small stream in wash, 15 lks. wide, 5 ft. deep, course SE.
- 27.80 Wash, 20 lks. wide, 2 ft. deep, drains N.
- 29.60 Small rocky knoll.
- 39.97 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 35.

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T11N R10E  
 $\frac{1}{4} \frac{S}{S} \frac{26}{35}$

1967

from which

A juniper, 20 ins. diam., bears N.  $40^\circ$  E., 16 lks. dist., mkd. T11N R10E  $\frac{1}{4}$  S 26 BT.

A juniper, 10 ins. diam., bears S.  $23\frac{1}{2}^\circ$  W., 38 lks. dist., mkd. T11N R10E  $\frac{1}{4}$  S 35 BT.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	
40.70	Ravine, drains irregularly N.
49.10	Fence, bears N. 10° E. and S. 10° W.
52.50	Old wire fence, bears N. and S.
52.60	Wash, 10 lks. wide, 1 ft. deep, drains E.
79.94	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling. Soil, gravel loam. Timber, medium dense pine and juniper, with some oak. Undergrowth, medium dense manzanita and oak brush, with cacti and Spanish bayonet.
	N. 0°01' W., bet. secs. 26 and 27.
	Over rolling land, through medium dense timber and undergrowth.
17.00	Wash, 20 lks. wide, 3 ft. deep, drains SE.
24.50	Wash, 10 lks. wide, 1 ft. deep, drains E.
31.70	Ridge, bears N. 60° E. and S. 60° W.
38.60	Enter E. end of cleared area, bears NE. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T11N R10E  <math>\frac{1}{4}</math>                      S 27   S 26                      1967</p>
	from which
	<p style="text-align: center;">A juniper, 13<math>\frac{1}{2}</math> ins. diam., bears S. 83<math>\frac{1}{2}</math>° E.,                      145<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 26 BT.</p>
	<p style="text-align: center;">A juniper, 7<math>\frac{1}{2}</math> ins. diam., bears N. 12<math>\frac{3}{4}</math>° W.,                      24<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 27 BT.</p>
43.00	Enter timber, bears SE. and NW.
46.70	Wash, 10 lks. wide, 3 ft. deep, drains S. 60° W.
56.40	Fence, bears S. 65° E. and N. 65° W.
60.00	Ridge, bears E. and W.
71.70	Huston Mesa Road, bears S. 80° E. and N. 80° W.
79.75	Power line, bears N. 43° E. and S. 43° W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T11N R10E  <math>\frac{1}{4}</math>                      S 22   S 23                      S 27   S 26                      1967</p>

CHAINS	
	<p>from which</p> <p>A power pole, bears N. <math>54\frac{3}{4}^{\circ}</math> E., 122<math>\frac{1}{2}</math> lks. dist.</p> <p>A pine, 5 ins. diam., bears S. <math>34\frac{3}{4}^{\circ}</math> E., 51 lks. dist., mkd. T11N R10E S 26 BT.</p> <p>A pine, 7<math>\frac{1}{2}</math> ins. diam., bears S. <math>37^{\circ}</math> W., 110 lks. dist., mkd. T11N R10E S 27 BT.</p> <p>A pine, 9 ins. diam., bears N. <math>30\frac{3}{4}^{\circ}</math> W., 35 lks. dist., mkd. T11N R10E S 22 BT.</p> <p>Triangulation station "Huston" bears N. <math>79^{\circ}36'</math> E., 14.36 chs. dist., monumented by a standard brass tablet, cemented in a drill hole, mkd. Huston 1946.</p> <p>Land, rolling. Soil, gravel loam. Timber, medium dense pine and juniper. Undergrowth, medium dense manzanita and oak brush, with cat claw and cacti.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. <math>89^{\circ}58'</math> W., bet. secs. 23 and 26.</p> <p>Over rolling land, through medium timber and undergrowth.</p>
14.40	Large granite outcrop.
15.30	Track road, bears S. $20^{\circ}$ E. and N. $20^{\circ}$ W.
17.10	Wash, 10 lks. wide, 2 ft. deep, drains S. $20^{\circ}$ E.
24.80	Wash, 20 lks. wide, 2 ft. deep, drains irreg. S.
30.80	Fence, bears N. and S.
37.60	Ridge, bears N. and S.
39.94	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E <math>\frac{1}{4}</math> <math>\frac{S\ 23}{S\ 26}</math> 1967</p>
	<p>from which</p> <p>A pine, 15 ins. diam., bears S. <math>27\frac{1}{2}^{\circ}</math> W., 54 lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 26 BT.</p> <p>A pine, 5 ins. diam., bears N. <math>15^{\circ}</math> W., 65 lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 23 BT.</p>
41.20	Small ravine, drains S. $30^{\circ}$ W.
56.90	Huston Mesa Road, bears NE. and SW.
69.90	South edge of Huston Mesa, bears irreg. N. $30^{\circ}$ E. and N. $30^{\circ}$ W.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	
79.88	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, gravelly loam. Timber, medium pine, juniper and medium oak first <math>\frac{1}{2}</math> mile. Undergrowth, medium dense manzanita and oak brush.</p>
	<p>From the cor. of secs. 33 and 34, on the S. bdy. of the Tp.</p> <p>N. <math>0^{\circ}01'</math> W., bet. secs. 33 and 34.</p> <p>Over rolling land, through medium timber.</p>
0.28	Fence, bears E. and W.
5.50	Track road, bears N. $70^{\circ}$ E. and S. $70^{\circ}$ W.
26.60	Wash, 10 lks. wide, 1 ft. deep, drains S. $80^{\circ}$ W.
38.72	<p>Point for the <math>\frac{1}{2}</math> sec. cor. of secs. 33 and 34.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11N R10E <math>\frac{1}{2}</math> S 33   S 34 1967</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears N. <math>50\frac{1}{2}^{\circ}</math> E., 46 lks. dist., mkd. T11N R10E <math>\frac{1}{2}</math> S 34 BT.</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears S. <math>29\frac{1}{2}^{\circ}</math> W., 46 lks. dist., mkd. <math>\frac{1}{2}</math> S 33 BT.</p>
41.10	Fence, bears N. $85^{\circ}$ E. and S. $85^{\circ}$ W., 150 lks. to end; enter cleared land.
42.21	<p>Intersect the line between Cors. 1 and 8 of H.E.S. 446.</p> <p>Point for the closing cor. of secs. 33 and 34.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">HES 446 <del>          </del> S 33   S 34 C   C T11N R10E 1967</p> <p>from which</p> <p style="padding-left: 40px;">Cor. No. 1 of HES 446, bears S. <math>64^{\circ}17'</math> W., 230 lks. dist., monumented by a granite stone, 24x10x8 ins. above ground, with X chiseled on top.</p>
43.20	Wash, 10 lks. wide, 2 ft. deep, drains SW.
44.10	Fence, bears NE. and SW.; thence through developed area.

<p>CHAINS 75.64</p>	<p>Intersect the line bet. cors. 3 and 4, HES 446.</p> <p>Point for the closing cor. of secs. 33 and 34.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T11N</td><td>R10E</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">C</td><td>C</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 33</td><td>S 34</td></tr> </table> <p>HES 446</p> <p>1967</p> </div> <p>from which</p> <p>An oak, 14 ins. diam., bears N. 71½° E., 33 lks. dist., mkd. HES 446 BT.</p> <p>Cor. No. 3, HES 446, bears N. 83°45' W., 83½ lks. dist., monumented by a granite stone, 22x14x9 ins. above the ground, mkd. 3 HES 44.</p> <p>Cor. No. 4, HES 446, bears S. 83°45' E., 27.95 chs. dist., monumented by an old ¾ in. pipe, 6 lks. N. of old fence cor.</p> <p>Cor. falls 2 lks. S. of fence bearing S. 84° E. and N. 84° W., 12 lks. to end.</p>	T11N	R10E	C	C	S 33	S 34
T11N	R10E						
C	C						
S 33	S 34						
<p>77.50</p>	<p>Wash, 10 lks. wide, 2 ft. deep, drains SE.</p>						
<p>78.72</p>	<p>Intersect the sectional correction line.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T11N</td><td>R10E</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 28</td><td>S 27</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 33</td><td>S 34</td></tr> </table> <p>1967</p> </div> <p>from which</p> <p>A cedar, 9 ins. diam., bears N. 82° E., 70½ lks. dist., mkd. T11N R10E S 27 BT.</p> <p>A pine, 32½ ins. diam., bears S. 49½° E., 142½ lks. dist., mkd. T11N R10E S 34 BT.</p> <p>A cedar, 5 ins. diam., bears S. 79½° W., 114½ lks. dist., mkd. T11N R10E S 33 BT.</p> <p>A cedar, 12½ ins. diam., bears N. 52° W., 86½ lks. dist., mkd. T11N R10E S 28 BT.</p> <p>Cor. mkd. WP ES 680, bears N. 74°32' E., 278 lks. dist., monumented by a standard U.S.F.S. brass cap; removed the cor. and defaced the bearing tree in the SW. quadrant.</p> <p>Land, rolling. Soil, gravelly loam. Timber, medium pine, and juniper. Undergrowth, manzanita and oak brush.</p>	T11N	R10E	S 28	S 27	S 33	S 34
T11N	R10E						
S 28	S 27						
S 33	S 34						

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS

From the cor. of secs. 26, 27, 34 and 35.

West, on the sectional correction line bet. secs. 27 and 34.

Over rolling land, through medium timber and undergrowth.

2.20 Ridge, bears N. and S.

23.06 Intersect the line bet. cors. 7 and 8 of H.E.S. 446.

Point for the closing cor. of secs. 27 and 34.

Set the iron post 22 ins. in the ground, brass cap mkd.

T11N R10E  
HES / S 27 C  
446 / S 34 C  
1967

from which

An oak, 7½ ins. diam., bears N. 54¾° E., 76 lks. dist., mkd. CC S 27 HES 446 BT.

A cedar, 11 ins. diam., bears South, 44 lks. dist., mkd. CC S 27 HES 446 BT.

Cor. 8 of H.E.S. 446, bears S. 40°48' W., 20.37 chs. dist., monumented by a granite stone, 4x4x9 ins. above the ground, mkd. 8 HES 446.

AP 3 of ES 680, bears N. 42° W., 79 lks. dist., monumented by a standard U.S.F.S. brass cap; removed the cor. and defaced the bearing tree in the SE. quadrant.

Cor. falls on old fence bearing N. 40° E. and S. 40° W.

Thence through developed land.

39.97 Point for the ¼ sec. cor. of secs. 27 and 34.

This corner was not monumented.

45.95 Intersect the line bet. cors. 4 and 5 of H.E.S. 446.

Point for the closing cor. of secs. 27 and 34.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11N R10E  
C S 27  
C S 34  
1967 HES 446

from which

An oak, 15 ins. diam., bears N. 1° W., 3 lks. dist., mkd. HES CC S 27 BT.

AP 9 of ES 680, bears N. 45° E., 88 lks. dist., monumented by a standard U.S.F.S. brass cap; removed the cor., defaced the bearing tree in the SW. quadrant.

Cor. 4 of H.E.S. 446, bears S. 45°27' W., 8.72 chs. dist.

Enter timber, bears NE. and SW.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS

- 56.50 S. edge of gravel pit.
- 58.50 Track road, bears N. 60° W. from gravel pit.
- 63.80 State Highway No. 87, bears N. 1°10' E. and S. 1°10' W.
- 68.90 Ridge, bears N. and S.
- 78.70 Track road, bears N. 30° E. and S. 30° W.
- 79.94 The cor. of secs. 27, 28, 33 and 34.


Land, rolling.  
 Soil, gravel loam.  
 Timber, medium dense pine and juniper, with some oak.  
 Undergrowth, medium dense manzanita and oak brush,  
 cacti and Spanish bayonet.

N. 0°01' W., bet. secs. 27 and 28.

Over rolling land, through moderate timber and undergrowth.


- 3.00 Wash, 10 lks. wide, 2 ft. deep, drains SW. about 100 lks. to wash, draining S.
- 6.07 Fence, bears S. 71° E. and N. 71° W.; power line bears S. 64° E. and N. 64° W.
- 6.18 Intersect the line bet. cors. 1 and 2, H.E.S. 123.  
 Point for the closing cor. of secs. 27 and 28.  
 Set the iron post 20 ins. in the ground, brass cap mkd.

HES 123




from which




Cor. No. 1, H.E.S. 123, bears S. 64°22' E.,  
 2.07 chs. dist., monumented by a Forest Service  
 iron post, 2½ ins. diam., firmly set with 2 ins.  
 above ground, brass cap mkd.



From Cor. 1, H.E.S. 123, Cor. No. 6 bears N. 82°48' E.,  
 14.47 chs. dist., monumented by a Forest Service iron  
 post, 2½ ins. diam., set 4 ins. below the surface of a  
 bladed road, brass cap mkd.





CHAINS	
	Thence through residential area, by traverse, topography as calculated to true line.
25.66	Fence, bears S. 40° E. and N. 40° W.
25.86	Intersect the line bet. cors 5 and 6, H.E.S. 123.
	Point for the closing cor. of secs. 27 and 28.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	
	from which
	Cor. No. 5, H.E.S. 123, bears N. 40°48' W., 24.14 chs. dist., monumented by a Forest Service iron post, 2½ ins. diam., firmly set 3 ins. above ground, brass cap mkd.
	
	Cor. No. 6, H.E.S. 123, bears S. 40°48' E., 24.79 chs. dist., previously described.
	Raise a mound of stone N. of the cor.
30.20	Power line, bears N. 13°45' E. and S. 13°45' W.
39.30	Track road, bears N. 80° E. and S. 80° W.
40.00	Point for the ¼ sec. cor. of secs. 27 and 28.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	
	from which
	A pine, 13 ins. diam., bears S. 34° E., 50 lks. dist., mkd. T11N R10E ¼ S 27 BT.
	An oak, 9 ins. diam., bears N. 50½° W., 31½ lks. dist., mkd. T11N R10E ¼ S 28 BT.
47.00	Track road, bears SE. and NW.
62.50	Bladed road, bears N. 50° E. and S. 50° W.
63.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° E.
72.50	Wash, 10 lks. wide, 1 ft. deep, drains irreg. E.

BOOK 4832

32.

Subdivision, T. 11 N., R. 10 E., Arizona

<p>CHAINS</p> <p>79.10</p> <p>80.00</p>	<p>Spur, slopes NW.</p> <p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">             T11N R10E  <u>S 21   S 22</u>  <u>S 28   S 27</u> </p> <p style="text-align: center;">1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12½ ins. diam., bears N. 68¼° E., 122 lks. dist., mkd. T11N R10E S 22 BT.</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 41¼° E., 108 lks. dist., mkd. T11N R10E S 27 BT.</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 49° W., 78 lks. dist., mkd. T11N R10E S 21 BT.</p> <p>Land, rolling. Soil, gravel loam. Timber, medium pine, juniper and oak. Undergrowth, medium manzanita and oak brush.</p>
<p>7.10</p> <p>7.30</p> <p>12.70</p> <p>21.60</p> <p>22.80</p> <p>40.00</p>	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land, through moderate timber and undergrowth.</p> <p>Small ravine, drains irregularly S.</p> <p>Power line, bears SE. and NW.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains SE.</p> <p>Wash, 20 lks. wide, 3 ft. deep, drains SE.</p> <p>Same wash, 20 lks. wide, 4 ft. deep, drains N. from N. 20° W.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 27.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">             T11N R10E              ¼ <u>S 22</u>              S 27         </p> <p style="text-align: center;">1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 32¾° E., 36 lks. dist., mkd. T11N R10E ¼ S 27 BT.</p> <p style="padding-left: 40px;">A juniper, 7½ ins. diam., bears N. 44¼° W., 12 lks. dist., mkd. T11N R10E ¼ S 22 BT.</p>
<p>41.20</p>	<p>Ridge, bears S. 80° E. and W.</p>

## Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	
53.80	Desc. along S. slope of ridge.
61.60	State Highway No. 87, bears S. 7° E. and N. 7° W.
62.60	Wash, 10 lks. wide, 4 ft. deep, drains N. 30° W.
66.30	Power line, bears N. 15° E. and S. 15° W.
76.70	Wash, 10 lks. wide, 3 ft. deep, drains N.
76.80	Bladed road, bears N. 15° E. and S. 15° W.
80.00	The cor. of secs. 21, 22, 27 and 28.
	Land, rolling. Soil, gravel loam. Timber, medium pine, juniper and some oak. Undergrowth, medium manzanita and oak brush.
	From the cor. of secs. 32 and 33 on the S. bdy. of the Tp.
	N. 0°02' W., bet. secs. 32 and 33.
	Over rolling land, through medium timber and undergrowth.
15.00	Track road, bears SE. and NW.
28.00	Top of mesa; thence over nearly level land.
38.30	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T11N R10E $\frac{1}{4}$ S 32   S 33 1967
	from which
	A juniper, 7 $\frac{1}{2}$ ins. diam., bears S. 60 $\frac{3}{4}$ ° E., 36 lks. dist., mkd. T11N R10E $\frac{1}{4}$ S 33 BT.
	A pine, 5 ins. diam., bears N. 53 $\frac{1}{2}$ ° W., 81 lks. dist., mkd. T11N R10E $\frac{1}{4}$ S 32 BT.
	Cor. mkd. WP ES 680, bears S. 60°24' E., 135 lks. dist., monumented by a standard U.S.F.S brass cap; removed the cor. and destroyed accessories.
46.90	Bladed road, bears NE. and SW.
52.90	Bladed road, bears NE. and SW.
57.80	Center of dirt landing strip, 120 lks. wide, bears N. 45° E., 7.00 chs. to end and S. 45° W., 34.90 chs.; at 22.50 intersect another landing strip bearing N. 81 $\frac{3}{4}$ ° E., 6.70 chs. to end and S. 81 $\frac{3}{4}$ ° W., 73.70 chs. to private land.
78.30	Intersect the sectional correction line.
	Point for the cor. of secs. 28, 29, 32 and 33.

BOOK 4832

34.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T11N R10E	
S 29	S 28
S 32	S 33

1967

from which

A juniper, 14 ins. diam., bears N. 51° E.,  
70 lks. dist., mkd. T11N R10E S 28 BT.

A juniper, 8 ins. diam., bears S. 36° E.,  
107 lks. dist., mkd. T11N R10E S 33 BT.

A pine, 5 ins. diam., bears S. 62½° W.,  
193 lks. dist., mkd. T11N R10E S 32 BT.

A pine, 5 ins. diam., bears N. 43¼° W.,  
107 lks. dist., mkd. T11N R10E S 29 BT.

AP 10 of ES 680, bears N. 65°18' E., 177 lks.  
dist., monumented by a standard U.S.F.S. brass  
cap; removed the cor. and defaced the bearing  
tree in the SE. quadrant.

Land, rolling for first ¼ mile, then nearly level.  
Soil, gravel loam.

Timber, medium juniper and scattered pine.  
Undergrowth, scattered oak brush.

From the cor. of secs. 27, 28, 33 and 34.

West, on the sectional correction line, bet. secs. 28  
and 33.

Over rolling land, through medium timber and under-  
growth.

0.30 Wash, 20 lks. wide, 4 ft. deep, drains S.

1.10 Track road, bears S. 20° E. and N. 20° W.

6.80 Bladed road, bears S. 15° E. and N. 15° W.

7.90 Power line, bears S. 13° E. and N. 13° W.

9.30 Power line, bears N. 6° E. and S. 6° W.

14.20 Bladed road to airport, bears S. curving E., and N.  
curving W.

17.30 Same road, bears N. 30° E. and S. 30° W.

40.01 Point for the ¼ sec. cor. of secs. 28 and 33.

Set the iron post 5 ins. in the ground, mound of stone  
to top, brass cap mkd.

T11N R10E	
¼ S 28	S 33

1967

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>from which</p> <p>A pine, 7½ ins. diam., bears N. 54¼° E., 39½ lks. dist., mkd. T11N R10E ¼ S 28 BT.</p> <p>A pine, 12 ins. diam., bears S. 43° E., 39½ lks. dist., mkd. T11N R10E ¼ S 33 BT.</p> <p>Cor. mkd. WP ES 680, bears N. 75°11' E., 236 lks. dist., monumented by a standard U.S.F.S. brass cap; removed the cor. and destroyed accessories.</p> <p>40.20 Track road, bears N. and S.</p> <p>74.30 Rocky wash, 20 lks. wide, 1 ft. deep, drains NW.</p> <p>80.02 The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, gravel loam. Timber, medium juniper and scattered pine. Undergrowth, medium manzanita and oak brush, with cat claw and Spanish bayonet.</p>
	<p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over rolling land, through medium timber and undergrowth.</p> <p>10.00 Rocky wash, 30 lks. wide, 2 ft. deep, drains N. 30° W.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 28 and 29.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E           ¼           S 29   S 28           1967</p> <p>from which</p> <p>A cedar, 7 ins. diam., bears N. 88½° E., 64½ lks. dist., mkd. T11N R10E ¼ S 28 BT.</p> <p>A juniper, 10 ins. diam., bears S. 15° W., 29 lks. dist., mkd. T11N R10E ¼ S 29 BT.</p> <p>42.40 Power line and track road, bears S. 47½° E. and N. 47½° W.</p> <p>45.20 Ridge, bears SE. and NW.</p> <p>51.50 Wash, 10 lks. wide, 1 ft. deep, drains irreg. W.</p> <p>54.80 Fence, bears S. 65° E., curving S., and bears W., curving S.</p> <p>79.70 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W.</p> <p>80.00 Point for the cor. of secs. 20, 21, 28 and 29.</p>

CHAINS	
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E  <math>\frac{S}{S} \frac{20}{29}   \frac{S}{S} \frac{21}{28}</math>                      1967</p> <p>from which</p> <p>A pine, <math>7\frac{1}{2}</math> ins. diam., bears S. <math>76\frac{1}{2}^\circ</math> E.,                      118<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E S 28 BT.</p> <p>A juniper, 11 ins. diam., bears S. <math>11\frac{1}{2}^\circ</math> E.,                      59<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E S 28 BT.</p> <p>A juniper, <math>12\frac{1}{2}</math> ins. diam., bears N. <math>45^\circ</math> W.,                      86 lks. dist., mkd. T11N R10E S 20 BT.</p> <p>Land, rolling.                      Soil, gravel loam.                      Timber, medium pine, juniper and oak.                      Undergrowth, medium manzanita and oak brush.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling and broken land, through moderate timber and undergrowth.</p>
1.40	Ravine, drains N. $20^\circ$ W.
5.10	Wash, 10 lks. wide, 2 ft. deep, drains N.
5.80	Track road, bears N. and S.
9.70	Wash, 10 lks. wide, 2 ft. deep, drains SE.
18.00	Wash, 10 lks. wide, 1 ft. deep, drains SE.
36.90	Ridge, bears S. $30^\circ$ E. and N. $30^\circ$ W.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E  <math>\frac{S}{S} \frac{21}{S 28}</math>                      1967</p> <p>from which</p> <p>A juniper, <math>7\frac{1}{2}</math> ins. diam., bears S. <math>40^\circ</math> W.,                      72<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 28 BT.</p> <p>A pine, 10 ins. diam., bears N. <math>28\frac{3}{4}^\circ</math> W.,                      167<math>\frac{1}{2}</math> lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 21 BT.</p>
74.20	Spur, slopes S. $30^\circ$ E.
75.30	Small ravine, drains S.
80.08	The cor. of secs. 20, 21, 28 and 29.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	
	<p>Land, high rolling. Soil, rocky clay loam. Timber, medium pine and juniper. Undergrowth, medium manzanita and oak brush.</p>
<p>15.60 17.30 19.60 37.96</p>	<p>From the cor. of secs. 31 and 32, on the S. bdy. of the Tp.  N. 0°02' W., bet. secs. 31 and 32.  Over nearly level land, through medium timber.  Road, bears W., and E. 150 lks., thence S.  Wash, 30 lks. wide, 2 ft. deep, drains N. 30° E.  Road, bears irreg. E. and W.  Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32.  This corner was not monumented.</p>
<p>44.94</p>	<p>Intersect the line bet. cors. 5 and 6 of H.E.S. 576.  Point for the closing cor. of secs. 31 and 32.  Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R10E C C <u>S 31   S 32</u> HES 576  1967</p> </div> <p>from which</p> <p>A juniper, 8 ins. diam., bears N. 70<math>\frac{3}{4}</math>° E., 53 lks. dist., mkd. HES 576 CC BT.</p> <p>A juniper, 5 ins. diam., bears N. 54<math>\frac{1}{2}</math>° W., 77 lks. dist., mkd. HES 576 CC BT.</p> <p>Cor. 6 of HES 576, bears East, 52 lks. dist., monumented by an iron post, mkd. 6 HES 576, in a mound of stone; cor. is located in a fence bearing N. and S.</p>
<p>45.15</p>	<p>Fence, bears W. and E. for 50 lks., thence S.</p>
<p>67.83</p>	<p>Intersect the line bet. cors. 1 and 2 of HES 611.  Point for the closing cor. of secs. 31 and 32.  Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>HES 611 <u>S 31   S 32</u> C   C  1967</p> </div>

Subdivision, T. 11 N., R. 10 E., Arizona

<p>CHAINS</p>	<p>from which</p> <p>A juniper, 10½ ins. diam., bears S. 18° E., 97 lks. dist., mkd. HES 611 CC BT.</p> <p>A juniper, 7½ ins. diam., bears S. 55¾° W., 126½ lks. dist., mkd. HES 611 CC BT.</p> <p>Cor. 2 of HES 611, bears N. 26°50' W., 6.91 chs. dist., monumented by an iron post; mkd. 2 HES 611.</p> <p>72.30 Track road, bears SE. and NW.</p> <p>73.49 Intersect the line bet. cors. 2 and 3 of H.E.S. 611.</p> <p>Point for the closing cor. of secs. 31 and 32. Cor. falls in wash.</p> <p>This corner was not monumented.</p> <p>from the point for the closing corner</p> <p>Cor. 2 of H.E.S. 611 bears N. 81°01' W., 3.15 chs. dist.</p> <p>73.70 Wash, 90 lks. wide, 4 ft. deep, drains SE.</p> <p>77.96 Intersect the sectional correction line.</p> <p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T11N R10E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table> <p>1967</p> </div> <p>from which</p> <p>A cedar, 5 ins. diam., bears N. 45½° E., 48 lks. dist., mkd. T11N R10E S 29 BT.</p> <p>A cedar, 5 ins. diam., bears S. 25¾° E., 83½ lks. dist., mkd. T11N R10E S 32 BT.</p> <p>A cedar, 8½ ins. diam., bears S. 27¼° W., 91½ lks. dist., mkd. T11N R10E S 31 BT.</p> <p>A juniper, 9 ins. diam., bears N. 46½° W., 28 lks. dist., mkd. T11N R10E S 30 BT.</p> <p>Land, gently rolling. Soil, gravel loam. Timber, medium juniper. Undergrowth, scattered cacti, oak brush and cat claw.</p>	T11N R10E		S 30	S 29	S 31	S 32
T11N R10E							
S 30	S 29						
S 31	S 32						
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>West, on the sectional correction line, bet. secs. 29 and 32.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>						



Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS		
8.20	Low ridge, bears N. and S.	
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.	
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.	
	<p style="text-align: center;">T11N R10E  <math>\frac{1}{4}</math> <math>\frac{S\ 29}{S\ 32}</math>                      1967</p>	
	from which	
	A pine, 10 ins. diam., bears S. $79\frac{1}{2}^\circ$ E., 68 lks. dist., mkd. T11N R10E $\frac{1}{4}$ S 32 BT.	
	A juniper, 10 ins. diam., bears N. $13^\circ$ W., $111\frac{1}{2}$ lks. dist., mkd. T11N R10E $\frac{1}{4}$ S 29 BT.	
45.00	Ridge, bears SE. and NW.	
79.98	The cor. of secs. 29, 30, 31 and 32.	
	Land, gently rolling. Soil, gravel loam with exposed rock. Timber, medium dense juniper and scattered pine. Undergrowth, medium oak brush, manzanita with cat claw and cacti.	
	West, on the sectional correction line, bet. secs. 30 and 31.	
	Over rolling land, through medium timber and undergrowth.	
2.80	Wash, 30 lks. wide, 7 ft. deep, drains SE.	
33.40	Ridge, bears SE. and NW.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.	
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.	
	<p style="text-align: center;">T11N R10E  <math>\frac{1}{4}</math> <math>\frac{S\ 30}{S\ 31}</math>                      1967</p>	
	from which	
	A juniper, $12\frac{1}{2}$ ins. diam., bears S. $41\frac{1}{2}^\circ$ E., 77 lks. dist., mkd. T11N R10E $\frac{1}{4}$ S 31 BT.	
	A dike bet. two ponds, bears S. $24\frac{1}{4}^\circ$ W., 34.00 chs. dist.	
52.00	Wash area, drains SE.; asc. over E. slope.	
78.60	Intersect the W. bdy. of the Tp.	
	Point for the closing cor. of secs. 30 and 31.	

BOOK 4832

40.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS

Set the iron post 22 ins. in the ground, brass cap mkd.

T11N  
R9E | R10E  
S 36 | S 30 C  
          | S 31 C  
1967

from which

A cedar, 10½ ins. diam., bears N. 23¾° E.,  
110 lks. dist., mkd. T11N R10E S 30 CC BT.

A pine, 4 ins. diam., bears S. 61¾° E.,  
157½ lks. dist., mkd. T11N R10E S 31 CC BT.

From point of intersection the cor. orig. set as the  
cor. of secs. 25, 30, 31 and 36, T. 11 N., Rs. 9 and  
10 E., bears North, 2.31 chs. dist., monumented by a  
2 ins. iron post, set, mkd. and witnessed as described  
in the official record of the 1919 survey. Remarked  
the brass cap to read

T11N  
R9E | R10E  
S 25 | S 30  
S 36 |  
1967  
1919

from which a new bearing tree

A cedar, 8 ins. diam., bears S. 66° W., 71½ lks.  
dist., mkd. T11N R9E S 36 BT.

Land, rolling.  
Soil, gravel loam.  
Timber, medium juniper.  
Undergrowth, scattered oak brush and manzanita.

The point for the West ¼ sec. cor. of sec. 31 is  
40.00 chs. south of the closing cor. of secs. 30 and  
31 and on the W. bdy. of the Tp.

At the cor. point

Set the iron post 7 ins. in the ground, mound of stone  
to top, brass cap mkd.

T11N  
R9E R10E  
          | ¼  
          | S 31  
1967

from which

A pine, 8 ins. diam., bears S. 88½° E.,  
40 lks. dist., mkd. T11N R10E ¼ S 31 BT.

The cor. orig. set as the ¼ sec. cor. of  
secs. 31 and 36, bears North, 2.31 chs. dist.,  
monumented by an iron post, 1 in. diam., set,  
mkd. and witnessed as described in the official  
record of the 1919 survey. Remarked the brass  
cap to read

CHAINS	
	<p style="text-align: center;"> <math>\frac{1}{4}</math>                      S 36                        1967                      1919                 </p>
<p>15.50</p> <p>27.40</p> <p>29.80</p> <p>40.00</p> <p>40.50</p> <p>47.00</p> <p>63.00</p> <p>67.60</p> <p>77.50</p> <p>80.00</p>	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°02' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through medium timber and undergrowth.</p> <p>Ridge, bears SE. and NW.</p> <p>Stock pond, bears East, 1.20 chs. dist. to center.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains N. 30° W.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 30.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">                     T11N R10E  <math>\frac{1}{4}</math>                      S 30   S 29                      1967                 </p> <p>from which</p> <p style="padding-left: 40px;">                     A juniper, 22<math>\frac{1}{2}</math> ins. diam., bears N. 25° E.,                      53 lks. dist., mkd. T11N R10E <math>\frac{1}{4}</math> S 29 BT.                 </p> <p style="padding-left: 40px;">                     A large granite outcrop, bears S. 86<math>\frac{1}{2}</math>° W.,                      36 lks. dist., mkd. + B0, on N. center portion.                 </p> <p>Edge of mesa, bears E. and irreg. SW.</p> <p>Ravine, drains N. 60° E.</p> <p>Spur, slopes E.</p> <p>Desc. over ledgy sandstone cliffs on brushy N. slope.</p> <p>Rocky wash, 60 lks. wide, 2 ft. deep, drains NW.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">                     T11N R10E                      S 19   S 20                      S 30   S 29                      1967                 </p> <p>from which</p> <p style="padding-left: 40px;">                     A juniper, 10 ins. diam., bears S. 65° E.,                      58 lks. dist., mkd. T11N R10E S 29 BT.                 </p> <p style="padding-left: 40px;">                     A juniper, 10 ins. diam., bears N. 77<math>\frac{3}{4}</math>° W.,                      50 lks. dist., mkd. T11N R10E S 19 BT.                 </p>

BOOK 4832

42.

Subdivision, T. 11 N., R. 10 E., Arizona

CHAINS	<p>Land, rolling first half, then mountainous. Soil, rocky loam. Timber, medium juniper, first half, scattered on remainder. Undergrowth, medium manzanita and oak brush.</p>
<p>0.10 15.00 33.60 39.99</p>	<p>From the cor. of secs. 20, 21, 28 and 29. S. 89°57' W., bet. secs. 20 and 29. Over rolling land, through medium timber and undergrowth. Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W. Stock pond, bears N. 1.00 ch. dist. Ridge, bears SE. and NW. Point for the ¼ sec. cor. of secs. 20 and 29. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11N R10E ¼ S 20           S 29 1967</p> <p>from which A juniper, 6 ins. diam., bears N. 26¼° W., 12 lks. dist., mkd. T11N R10E ¼ S 20 BT.</p>
<p>41.00 53.10 68.60 79.98</p>	<p>Power line, bears S. 47½° E. and N. 47½° W. Wash, 20 lks. wide, 3 ft. deep, drains N. 20° W., 1.00 ch. to stock pond. Rocky ledge, bears irreg. N. and S. The cor. of secs. 19, 20, 29 and 30. Land, rolling. Soil, gravel loam. Timber, medium cedar and juniper with some pine. Undergrowth, medium manzanita and oak brush.</p>
<p>1.00 32.10 32.80 40.00</p>	<p>West, bet. secs. 19 and 30. Over high rolling land, through medium undergrowth. Wash, 1 ft. deep, 20 lks. wide, drains NW. Track road, bears N. and S. Ridge, bears N. and S.; desc. over W. slope. Point for the ¼ sec. cor. of secs. 19 and 30.</p>

CHAINS

Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.

T11N R10E  
 $\frac{1}{4}$  S 19  
 S 30  
 1967

from which

A juniper, 10 ins. diam., bears N. 6° E., 49 lks. dist., mkd. T11N R10E  $\frac{1}{4}$  S 19 BT.

42.20 Ravine, drains NE.

51.00 Ridge, bears N. and S.

63.00 Low sag, drains NW.

76.00 Ridge, bears N. and S.

77.40 Rocky rim of canyon, bears irreg. N. and S.

78.47 Intersect the W. bdy. of the Tp.

Point for the closing cor. of secs. 19 and 30.

Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.

T11N  
 R9E | R10E  
 S 25 | S 19 C  
 | S 30 C  
 1967

From point of intersection the cor. orig. set as the cor. of secs. 19, 24, 25 and 30, T. 11 N., Rs. 9 and 10 E., bears North 2.47 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1919 survey. Remarkd the brass cap to read

T11N  
 R9E | R10E  
 S 24 | S 19  
 S 25 |  
 1967  
 1919

Land, high rolling.  
 Soil, gravel loam.  
 Timber, scattered juniper and cedar.  
 Undergrowth, medium oak brush and manzanita.

The point for the W.  $\frac{1}{4}$  sec. cor. of sec. 30 is at midpoint and on the W. bdy. of the Tp.

At the corner point

Survey of Tract 37, T. 11 N., R. 10 E., Arizona

CHAINS

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T11N  
R9E | R10E  
          | ¼  
          | S 30

1967

from which

A cedar, 9 ins. diam., bears N. 16° E.,  
46 lks. dist., mkd. T11N R10E ¼ S 30 BT.

A cedar, 5 ins. diam., bears S. 73° E.,  
25 lks. dist., mkd. T11N R10E ¼ S 30 BT.

The cor. orig. set as the ¼ sec. cor. of  
secs. 25 and 30, bears North 2.39 chs. dist.,  
monumented by a 1 in. iron post, set, mkd.  
and witnessed as described in the official  
record of the 1919 survey. Remarkd the  
brass cap to read

¼  
S 25 |  
1967  
1919

Survey of Tract 37, Section 34  
Township 11 North, Range 10 East

Comprising the following described lands:

NE¼ SW¼, S¼ NW¼ SW¼, S¼ SW¼, W¼ SE¼, Sec. 34, T.11 N.,  
R. 10 E., under Patent No. 02-67-0049, Arizona.

The location of this tract is based upon the subdivision  
of section 34, had the boundaries and section subdivision  
been run regular commencing at corners established on  
the south boundary of the Tp. by Campbell and Oakes in  
1905.

The N-S. and E-W. center lines of section 34 **were run**  
and temporary points set to control the survey of the  
tract.

Beginning at the E 1/16 sec. cor. of sec. 3, T. 10 N.,  
R. 10 E., identical with Angle Point No. 1, Tract 37;  
add markings on brass cap to read:

T11N R10E  
TR 37 |  
AP 1 |  
E 1 S 3  
16

T10N R10E

1967

Thence, N. 0°01' W., on line 1-2, Tract 37.

Survey of Tract 37, T. 11 N., R. 10 E., Arizona

CHAINS		
40.00	<p>Over rolling land, through moderate timber.</p> <p>Point for Angle Point No. 2, Tract 37.</p> <p>Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	$\begin{array}{r l} \text{T11N R10E} & \\ \text{AP 2} & \text{S 34} \\ \text{TR 37} & \end{array}$ <p>1968</p>	
	<p>Thence, N. 89°42' W., on line 2-3, Tract 37.</p>	
40.08	<p>Point for Angle Point No. 3, Tract 37.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	$\begin{array}{r l} \text{T11N R10E} & \\ \text{S 34} & \text{AP 3} \\ & \text{TR 37} \end{array}$ <p>1968</p>	
	<p>from which</p>	
	<p>A pine, 10 ins. diam., bears N. 57½° W., 54 lks. dist., mkd. AP 3 TR 37 BT.</p>	
	<p>Thence, S. 0°01' E., on line 3-4, Tract 37.</p>	
10.00	<p>Point for Angle Point No. 4, Tract 37.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	$\begin{array}{r l} \text{T11N R10E} & \\ \text{S 34} & \text{AP 4} \\ & \text{TR 37} \end{array}$ <p>1968</p>	
	<p>from which</p>	
	<p>A pine, 15 ins. diam., bears N. 34° W., 99 lks. dist., mkd. AP 4 TR 37 BT.</p>	
	<p>Thence N. 89°42' W., along line 4-5, Tract 37.</p>	
20.04	<p>Point for Angle Point No. 5, Tract 37.</p> <p>Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	$\begin{array}{r l} \text{T11N R10E} & \\ \text{S 34} & \text{AP 5} \\ & \text{TR 37} \end{array}$ <p>1968</p>	
	<p>from which</p>	
	<p>The ¼ sec. cor. of secs. 33 and 34, bears N. 5°31' W., 8.77 chs. dist.</p>	
	<p>The cor. is set alongside a local cor., which is a 1 in. water pipe.</p>	
	<p>Thence, S. 0°01' E., along line 5-6, Tract 37.</p>	

BOOK 4832

46.

Survey of Tract 37, T. 11 N., R. 10 E., Arizona

<p>CHAINS</p> <p>30.00</p>	<p>The cor. of secs. 3 and 4, T. 10 N., R. 10 E., identical with Angle Point No. 6, Tract 37. Add markings on brass cap to read:</p> <p style="text-align: center;">T11N R10E</p> <p style="text-align: center;">TR 37</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">AP</td> <td style="padding: 0 5px;">6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">3</td> </tr> </table> <p style="text-align: center;">T10N R10E</p> <p style="text-align: center;">1967</p> <p>Thence, S. 89°43' E., bet. secs. 3 and 34 on line 6-7, Tract 37.</p>	S 34	AP	6	S 4	S	3
S 34	AP	6					
S 4	S	3					
<p>40.08</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 3, T. 10 N., R. 10 E., identical with Angle Point No. 7, Tract 37. Add markings on brass cap to read:</p> <p style="text-align: center;">T11N R10E</p> <p style="text-align: center;">TR 37</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black; padding: 0 5px;">AP</td> <td style="padding: 0 5px;">7</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 0 5px;"><math>\frac{1}{4}</math> S</td> <td style="padding: 0 5px;">3</td> </tr> </table> <p style="text-align: center;">T10N R10E</p> <p style="text-align: center;">1967</p> <p>Thence, S. 89°41' E., bet. secs. 3 and 34, on line 7-1, Tract 37.</p>	AP	7	$\frac{1}{4}$ S	3		
AP	7						
$\frac{1}{4}$ S	3						
<p>20.045</p>	<p>The E <math>\frac{1}{16}</math> sec. cor. of sec. 3, T. 10 N., R. 10 E., identical with Angle Point No. 1, Tract 37, and place of beginning.</p>						
<p>General Description</p>							
<p>The elevation ranges from about 5300 ft. above sea level in the northern part of section 36 to 4700 ft. in the southeast portion of section 36. The land is rolling except for the mountains in the northeast part of section 30. The soil is gravel loam and the timber consists of pine, juniper and oak. The pine is in sections 33 through 36, with cedar and juniper predominant in the remainder. The oak is scattered throughout.</p> <p>The Homestead Entry Surveys are well developed and have been subdivided with the exceptions of Homestead Entry Surveys 420 and 611. The main siesmological buildings are in section 36. State Highways Nos. 87 and 160 pass through the township along with numerous track roads and power line s.</p> <p>The only streams noted were in the northeast portion of section 35. The forest land is primarily used for the grazing of livestock.</p>							





84

BOOK 4832

CERTIFICATE OF SURVEY

I, Kenneth D. Herman, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of June, 1967, I have made a dependent resurvey of the south boundary and a portion of the east boundary and the survey of a portion of the subdivisional lines, in Township 11 North, Range 10 East, and

I, Jerrold E. Knight, HEREBY CERTIFY upon honor that, in pursuance of Amended Supplemental Special Instructions bearing date of the 30th day of April, 1968, I have surveyed Tract 37, Section 34, Township 11 North, Range 10 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 30, 1968  
(Date)

*Kenneth D. Herman*  
(Cadastral Surveyor)

September 17, 1968  
(Date)

*Jerrold E. Knight*  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date OCT 3 1968

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the dependent resurvey of the south boundary and a portion of the east boundary and the survey of a portion of the subdivisional lines and Tract 37 in Section 34, Township 11 North, Range 10 East, of the Gila and Salt River Meridian, Arizona,

executed by Kenneth D. Herman and Jerrold E. Knight, having been critically examined and found correct, are hereby approved.

FEB 5 1969  
(Date)

*J. J. [Signature]*  
(Chief, Division of Engineering)  
Acting Chief, Division of Cadastral Surveys

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief, Division of Engineering)