

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1

FIELD NOTES

DEPENDENT RESURVEY

of a

PORTION OF SUBDIVISIONAL LINES

and a

SURVEY OF PARTIAL SUBDIVISIONS

in

SECTIONS 1, 2, 11, 12 and 14

and a

METES AND BOUNDS SURVEY

of

TRACT 38, SECTION 12

TOWNSHIP 7 NORTH, RANGE 27 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Jerrold E. Knight, Cadastral Surveyor

Under special instructions dated May 23, 19 68, which provided for the surveys

included under Group Number 483, approved May 23, 1968,

and assignment instructions dated May 23, 19 68.

Survey commenced May 24, 19 68

Survey completed June 27, 19 68

18

INDEX DIAGRAM

Township 7 North, Range 27 East

6	5	4	3	29	19	18
				28	6	19
7	8	9	10	13	12	5
				11	26	4
18	17	16	15	10	24	3
				9	15	14
19	20	21	22	22	13	13
				21	1	10
30	29	28	27	7	23	24
				26	25	25
31	32	33	34	35	36	

- NW $\frac{1}{4}$ sec. 12 ----- pg. 16
- SW $\frac{1}{4}$ sec. 1 ----- pg. 20
- SW $\frac{1}{4}$ sec. 14 ----- pg. 23
- NW $\frac{1}{4}$ sec. 14 ----- pg. 24
- SE $\frac{1}{4}$ sec. 11 ----- pg. 27
- Tract 38 ----- pgs. 30 - 32

Township 7 North, Range 27 East,
Gila and Salt River Meridian, Arizona

CHAINS

The boundaries and subdivisional lines were surveyed in 1883 by W. R. Fitzgerald. The north, east, south, and a portion of the west boundary and subdivisional lines, were resurveyed in 1940 by White, Warner and Motoh. The Fort Apache Indian Reservation boundary through the township was surveyed in 1906 by J. B. Wright and re-traced in 1940 by White, Warner and Motoh.

The following notes are those of a dependent resurvey of a portion of the subdivisional lines and a survey of partial subdivisions in sections 1, 2, 11, 12 and 14, and of a metes and bounds survey of tract 38 in section 12, Township 7 North, Range 27 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated May 23, 1968.

Because of the many improvements in the area and the restrictions on clearing trees for line, most of the random lines were run as a traverse. Topography was adjusted from the random lines. Much topography was omitted through private lands. Direct ties were taken to objects significant in locating corner positions. Only the true line bearing and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of section 14, as scaled from U. S. Geological Survey Quadrangle BIG LAKE, ARIZ., 1958, is Latitude, 33°59'41" North, and Longitude, 109°27'20" West.

The mean magnetic declination was determined to be 14° East.

Dependent Resurvey of a Portion of the
Subdivisional Lines of
T. 7 N., R. 27 E., G&SR M., Arizona

Reestablishment of the Survey Executed
in 1940, by White, Warner and Motoh

Beginning at the cor. of secs. 13, 14, 23 and 24, T. 7 N., R. 27 E., monumented by an iron post, 2 ins. diam., set firmly with 14 ins. showing above the ground, in a collar of stone. The post is slightly bent, brass cap mkd.

T7N	R27E
S14	S13
S23	S24
1940	

from which

A pine, 15 ins. diam., bears N. 52½° E., 34 lks. dist., mkd. T7N R27E S13 BT

A spruce, 15 ins. diam., bears S. 7½° E., 74 lks. dist., mkd. T7N R27E S24 BT

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS		
	<p>A pine, 30 ins. diam., bears S. 88$\frac{3}{4}$° W., 196 lks. dist., mkd. T7N R27E S23 BT.</p> <p>A pine, 10 ins. diam., bears N. 77° W., 25 lks. dist., mkd. T7N R27E S14 BT. (Record dist. 241 lks.)</p> <p>N. 0°09' W., bet. secs. 13 and 14.</p> <p>Over nearly level land; through dense pine.</p>	
6.70	East Fork of the Little Colorado River, 20 lks. wide, water 1 ft. deep, course N. 60° W.	
20.02	Point for the S 1/16 sec. cor. of secs. 13 and 14, at proportionate dist.	
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7N R27E S 1/16 S14 S13 1968</p> <p>from which</p> <p>A pine, 18 ins. diam., bears S. 67° E., 44 lks. dist., mkd. S 1/16 S13 BT.</p> <p>A fence cor., bears N. 22° E., 59 lks. dist.; fences bear N. 3° W. and West.</p>	
20.57	Fence, bears W. and E., for 22 lks., thence irregularly N. 3° W.	
30.80	Fence cor.; fences bear irregularly S. and W.	
36.40	W. edge of East Fork Road, Forest Route No. 79A, bladed dirt, bears irregularly SE. and N.; continue along W. edge of road.	
39.44	The witness $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented by an iron post, 1 in. diam., set with the top flush with the ground, brass cap mkd.	
	<p style="text-align: center;">W C $\frac{1}{4}$ S14 S13 1940</p> <p>from which</p> <p>A pine, 19 ins. diam., bears N. 67$\frac{1}{2}$° E., 65 lks. dist., mkd. WC $\frac{1}{4}$ S13 BT.</p> <p>A pine, 16 ins. diam., bears S. 34° W., 12 lks. dist., mkd. WC $\frac{1}{4}$ S14 BT.</p>	
40.04	<p>The true point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. The point falls in the East Fork Road and no attempt was made to recover the original stone cor. monument.</p> <p>Land, nearly level in the S. $\frac{1}{2}$. Gentle SW. slope for the N. $\frac{1}{2}$. Soil, sandy loam. Timber, medium to dense pine, fir and aspen. Undergrowth, dense willows along the Little Colorado River, moderate grass throughout.</p>	

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS	
	<p>From the cor. of secs. 11, 12, 13 and 14, monumented by an iron post, 2 ins. diam., set with 24 ins. showing above the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T7N R27E S11 S12 S14 S13 1940 </p> <p>Cor. located at the S. side of a fence cor.; fences bear N., S. and W.</p> <p>N. 0°51' E., bet. secs. 11 and 12.</p> <p>Through dense willows; over bottom land of Little Colorado River; along E. side of fence.</p>
5.50	Little Colorado River, 40 lks. wide, water 1 ft. deep, course NW. for 1.00 ch., thence NE.
8.30	Fence, bears irregularly N. 10° E. and S. 10° W.
14.80	Little Colorado River, course NW.
18.10	Fence, and abandoned power line, bear E. and W.
19.91	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12 at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T7N R27E S 1/16 S11 S12 1968 </p> <p>Cor. located in overflow area of the river. There are no bearing trees or rocks available.</p>
19.96	Fence, bears E. and W.
31.30	Leave dense willows; enter pasture.
34.50	Fence, bears W. and E. for 1.00 ch., thence irregularly N. and S.
38.50	Power line, bears NE. and SW.
39.20	Driveway, bears NE. and SW.
39.47	<p>The witness ¼ sec. cor. of secs. 11 and 12, monumented by an iron post, 1 in. diam., set with 6 ins. showing above the ground, brass cap mkd.</p> <p style="text-align: center;"> W C ¼ S11 S12 1940 </p> <p>from which</p> <p>A yellow pine, 47 ins. diam., bears N. 85° E., 220 lks. dist., mkd. WC ¼ S12 BT (Record dist. 260 lks.)</p>

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS	
	<p>A yellow pine, 26 ins. diam., bears S. 4° W., 242 lks. dist., mkd. WC $\frac{1}{4}$ S11 BT</p> <p>The NW. cor. of a cattleguard, bears East, 6 lks. dist.</p> <p>The NW. cor. of the Greer Schoolhouse, bears S. 33°50' E., 338 lks. dist.</p> <p>The SW cor. of a concrete water reservoir, 8 x 8 x 6 ft. high, bears S. 4°45' E., 2.78 chs. dist.</p> <p>The NE. cor. of a house, bears S. 57$\frac{3}{4}$° W., 254 lks. dist.</p> <p>The SE. cor. of a house, bears N. 44$\frac{1}{2}$° W., 143 lks. dist.</p> <p>Witness cor. is located under fence bearing E. and W.</p>
39.80	Arizona Highway No. 373, paved, bears N. 85° E. and S. 85° W.
39.82	The true point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12. No attempt was made to recover the original stone cor. monument.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 1°26' E., beginning new measurement.
.30	Fence, bears E. and W.; asc. SW. slope through medium dense timber.
6.20	Fence, bears irregularly NW. and SE.
7.60	Spur, slopes west; desc. NW. slope.
12.70	Fence, bears NE. and SW.
17.10	Leave timber; continue over bottom land of Little Colorado River through dense willows.
18.82	Angle point No. 4, tract 38, hereinafter described.
19.40	Fence, bears E. and W.
19.56	Point for the N 1/16 sec. cor. of secs. 11 and 12, at proportionate dist. This cor. also functions as angle point No. 5, tract 38.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p>T7N R27E N 1/16 S11 S12 TR38 AP 5 1968</p>
23.30	Little Colorado River, 40 lks. wide, water 1 ft. deep, course irregularly E.
31.40	Fence, bears W. and E. for 45 lks., thence N.; enter pasture.

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

<p>CHAINS 39.12</p>	<p>The cor. of secs. 1, 2, 11 and 12, monumented by an iron post, 2 ins. diam., set with 6 ins. showing above the ground, with a mound of stone west of the cor., brass cap mkd.</p> <p style="text-align: center;"> T7N R27E <u>S 2 S 1</u> <u>S11 S12</u> 1940 </p> <p>from which</p> <p style="padding-left: 40px;">A pine stump, 15 ins. diam., bears N. 14½° W., 212 lks. dist., mkd. T7N R27E S2 BT.</p> <p style="padding-left: 40px;">There is no remaining evidence of the other bearing trees.</p> <p>Cor. located 2 lks. S. of a fence cor.; fences bear N., westerly and southerly.</p> <p>Land, mountainous in the S. ½; nearly level bottom land in the N. ½. Soil, rocky, clay loam on the mountain and sandy loam on the bottom land. Timber, medium dense pine on the mountain. Undergrowth, dense willows along the Little Colorado River; grass in pasture.</p>
<p>10.10</p>	<p>From the ¼ sec. cor. of secs. 1 and 12, monumented by an iron post, 1 in. diam., set with 6 ins. showing above the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;"> ¼ <u> S 1</u> <u> S12</u> 1940 </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears N. 30½° E., 135 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. 79° E., 55 lks. dist., with a partially healed blaze mkd. S12 BT.</p> <p>Cor. located under fence bearing W. and E. for 5 lks., thence N.</p> <p>S. 89°10' W., bet. secs. 1 and 12.</p> <p>Over nearly level bottom land of the Little Colorado River; through dense willows; along the S. side of fence.</p>
<p>16.40</p>	<p>Little Colorado River, 100 lks. wide, water 1 ft. deep, course NE.</p>
<p>17.00</p>	<p>Power line, bears N. 2°23' E. and S. 2°23' W.</p>
<p>17.70</p>	<p>Fence cor., fences bear N., S. and E.</p>
<p>18.47</p>	<p>Arizona Highway No. 373, paved, bears N. 2°23' E. and S. 2°23' W. Bridge, bears south 40 lks. dist.</p>
<p>18.47</p>	<p>Highway right-of-way fence, bears N. 2°23' E. and S. 2°23' W.</p> <p>Angle point No. 1, tract 38, herinafter described.</p>

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS

19.55 Point for the W 1/16 sec. cor. of secs. 1 and 12 at proportionate dist. This cor. also functions as angle point No. 7, tract 38.

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7N R27E
W 1/16 S 1
S12 | AP 7
| TR 38
1968

from which

A re-bar, $\frac{3}{4}$ in. diam., bears east 1 lk. dist.

29.30 Fence, bears N. and S.

38.00 Leave dense willows; enter pasture.

39.10 The cor. of secs. 1, 2, 11 and 12.

Land, nearly level river bottom land.
Soil, sandy loam.
Timber, none.
Undergrowth, dense willows and grass.

N. 1°50' W., bet. secs. 1 and 2.

Over pasture; along the W. side of fence.

4.30 Irrigation canal, bears NE. and SW.; asc. gentle S. slope; enter medium dense pines.

20.23 Point for the S 1/16 sec. cor. of secs. 1 and 2. This cor. is not monumented.

from which

A fence cor., bears N. 72°45' E. 14 lks. dist.; fences bear S. and irregularly E.

30.70 Top of ascent, bears E. and W.; desc. N. slope.

40.46 The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented by an iron post, 1 in. diam., set with 12 ins. showing above the ground, brass cap mkd.

$\frac{1}{4}$
S2 | S1
1940

from which

A pine, 12 ins. diam., bears N. 31 $\frac{3}{4}$ ° E., 49 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A pine, 10 ins. diam., bears N. 15 $\frac{3}{4}$ ° W., 49 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

The SE cor. of Burk's house, bears N. 58° W., 291 lks. dist. (Record dist. 293 lks.)

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS	
	<p>From the true point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23 which is not monumented.</p>
	<p>S. $89^{\circ}33'$ W., bet. secs. 14 and 23.</p>
	<p>Desc. W. slope, through moderately dense pine.</p>
.05	<p>The witness $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented by an iron post, 1 in. diam., set firmly in a mound of stone, brass cap mkd.</p>
	<p style="text-align: center;"> $\frac{1}{4} \frac{S14}{S23} WC$ 1940 </p>
	<p>from which</p>
	<p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. $14\frac{3}{4}^{\circ}$ E., 15 lks. dist., mkd. with a healed blaze.</p>
	<p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. $13\frac{1}{2}^{\circ}$ W., 37 lks. dist., mkd. with a healed blaze.</p>
1.60	<p>Little Colorado River, West Fork, 25 lks. wide, water 1 ft. deep, course N.; asc. E. slope.</p>
6.20	<p>Forest Route No. 575, graded dirt road, bears irregularly N. and S.</p>
6.40	<p>Asc. steep E. slope.</p>
19.785	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 14 and 23 at proportionate dist.</p>
	<p>Set the iron post 14 ins. in the ground, in a mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;"> T7N R27E W $\frac{1}{16} \frac{S14}{S23}$ 1968 </p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 23 ins. diam., bears N. 5° E., 7 lks. dist., mkd. W $\frac{1}{16}$ S14 BT</p>
25.10	<p>Top of steep ascent; continue across gentle E. slope.</p>
39.57	<p>The cor. of secs. 14, 15, 22 and 23, monumented by an iron post, 2 ins. diam., set firmly in a mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;"> T7N R27E $\frac{S15}{S22} \frac{S14}{S23}$ 1940 </p>
	<p>from which</p>
	<p style="padding-left: 40px;">A spruce, 8 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 14 lks. dist., mkd. T7N R27E S14 BT</p>
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. $39\frac{1}{4}^{\circ}$ E., 64 lks. dist., mkd. T7N R27E S23 BT</p>
	<p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. $59\frac{1}{4}^{\circ}$ W., 85 lks. dist., mkd. T7N R27E S22 BT</p>

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS		
	<p>A pine, 22 ins. diam., bears N. 39° W., 99 lks. dist., mkd. T7N R27E S15 BT</p> <p>Land, mountainous. Soil, rocky, clay loam. Timber, moderately dense pine and fir. Undergrowth, dense willows along the Little Colorado River.</p>	
20.00	<p>N. 0°04' W., bet. secs. 14 and 15.</p> <p>Over a gentle E. slope; through dense timber.</p> <p>Point for the S 1/16 sec. cor. of secs. 14 and 15, at proportionate dist.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7N R27E S 1/16 S15 S14 1968</p> <p>from which</p> <p>A pine, 8 ins. diam., bears N. 69° E., 45 lks. dist., mkd. S 1/16 S14 BT</p> <p>A pine, 12 ins. diam., bears S. 33° E., 21 lks. dist., mkd. S 1/16 S14 BT.</p>	
39.90	<p>The witness ¼ sec. cor. of secs. 14 and 15, monumented by an iron post, 1 in. diam., set with 10 ins. showing above the ground, brass cap mkd.</p> <p style="text-align: center;">W C ¼ S15 S14 1940</p> <p>from which</p> <p>A pine, 30 ins. diam., bears S. 57½° E., 33 lks. dist., mkd. WC ¼ S14 BT</p> <p>A pine, 25 ins. diam., bears N. 57¾° W. 58 lks. dist., mkd. WC ¼ S15 BT</p>	
40.00	<p>The ¼ sec. cor. of secs. 14 and 15, monumented by a stump, 24 ins. diam., 15 ins. high. No markings are visible.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°12' E., beginning new measurement.</p> <p>Over gently rolling land; through moderate to dense timber.</p>	
2.20	<p>Desc. along E. slope.</p>	
11.60	<p>Asc. along SE. slope.</p>	
20.06	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15, at proportionate dist. Point falls in the NW track of Forest Route No. 87, a graded dirt road, and cannot be perpetuated because the road is scheduled to be reworked.</p>	

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS	
	from which
	<p>The iron post, set 18 ins. in the ground, in a collar of stone, for a reference monument, bears S. 45° E., 60.6 lks. dist., brass cap mkd. T7N R27E N 1/16 S14 RM 40 FT 1968 and an arrow pointing to the true cor.</p>
	<p>The iron post, set 18 ins. in the ground, in a collar of stone, for a reference monument, bears S. 45° W., 60.6 lks. dist., brass cap mkd. T7N R27E N 1/16 S15 RM 40 FT 1968 and an arrow pointing to the true cor.</p>
20.20	Forest Route No. 87, bears N. 25° E. and S. 25° W.
27.80	Enter meadow, edge bears N. 70° E. and S. 70° W.
35.10	Enter timber, edge bears NE. and SW.
40.12	<p>The cor. of secs. 10, 11, 14 and 15, monumented by an iron post, 2 ins. diam., set with 8 ins. showing above the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T7N R27E <u>S10</u> <u>S11</u> <u>S15</u> <u>S14</u> 1940</p>
	from which
	<p>A pine stump, 10 ins. diam., 5 ft. high, bears N. 19¼° E., 27 lks. dist., mkd. T7N R27E S11 BT.</p>
	<p>A pine, 15 ins. diam., bears S. 56½° E., 59 lks. dist., mkd. T7N R27E S14 BT.</p>
	<p>A pine, 15 ins. diam., bears S. 15° W., 41 lks. dist., mkd. T7N R27E S15 BT</p>
	<p>A pine, 15 ins. diam., bears N. 73° W., 60 lks. dist., mkd. T7N R27E S10 BT</p>
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, medium dense pine and fir. Undergrowth, grass.</p>
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°33' W., bet. secs. 11 and 14.
	Along a wire fence; over a pasture.
3.90	Fence cor., fences bear E., W. and S.
10.40	Fence cor., fences bear N., S., E. and W.; enter farm yard.
13.40	Pole fence, bears S.; wire fence, bears E. and W.; leave farm yard.
13.70	Power line, bears N. and S.
13.90	Forest Route No. 575, graded gravel road, main street of Greer, Arizona, bears N. and S.; cattle guard across road, wire fence continues W. from cattle guard.

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS

- 14.40 Fence, angles to S., thence irregularly W.
- 19.80 Fence cor., bears S. 10 lks. dist., fences bear irregularly S. and E.
- 20.15 Point for the E 1/16 sec. cor. of secs. 11 and 14 at proportionate dist., mkd. by a local pipe, 1 in. diam., set with 2 ins showing above the ground, in a circle of stones. This cor. is not monumented.
- 20.30 Power line, bears N. and S.
- 20.70 Enter dense willows.
- 35.60 Leave willows.
- 35.80 Bladed dirt road, bears S. and N. for 330 lks., thence, E. and W.; enter scattered timber.
- 37.60 Bladed dirt road, bears S. and N. for 290 lks., thence, E. and W.; enter yard.
- 40.30 Leave yard.
- 40.30 The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented by an iron post, 1 in. diam., set with 15 ins. showing above the ground, in a mound of stone to top, brass cap mkd.

$\frac{1}{4}$ S11
S14
1940

from which

A pine, 14 ins. diam., bears S. $40\frac{3}{4}^\circ$ W.,
71 lks. dist., mkd. $\frac{1}{4}$ S14 BT

A pine, 10 ins. diam., bears N. $47\frac{1}{2}^\circ$ W.,
93 lks. dist., mkd. $\frac{1}{4}$ S11 BT

A developed spring, 5 x 5 ft. concrete box,
bears North 8.15 chs. dist.; water flows E.

Cor. located under a fence bearing irregularly N. 25° W.
and S. 25° E.

S. $89^\circ 37'$ W., beginning new measurement.

Asc. E. slope; through medium dense timber.

.10 Power line, bears irregularly N. and S.

19.22 Point for the W 1/16 sec. cor. of secs. 11 and 14, at proportionate dist.

Set the iron post 6 ins. in the ground, in a mound of stone to top, brass cap mkd.

T7N R27E
W 1/16 S11
S14
1968

from which

A pine, 4 ins. diam., bears N. $5\frac{1}{2}^\circ$ E., 18
lks. dist., mkd. W. 1/16 S11 BT.

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS	
	<p>A white fir, 4 ins. diam., bears S. 26° W., 16 lks. dist., mkd. W 1/16 S14 BT</p>
27.10	<p>Ridge, bears N. and S.; desc. W. slope.</p>
33.40	<p>Forest Route No. 87, a graded dirt road, bears irregularly N. and S.</p>
38.44	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, nearly level in the E. $\frac{1}{4}$, mountainous in the W. portion. Soil, sandy loam in the E. $\frac{1}{4}$, rocky, clay loam in the W. portion. Timber, medium dense pine and fir in the W. $\frac{1}{2}$. Undergrowth, grass throughout, dense willows along the center E. $\frac{1}{4}$.</p>
	<p>North bet. secs. 10 and 11.</p> <p>Desc. over a NE. slope; through medium dense timber.</p>
17.90	<p>Forest Route No. 87, bears N. 30° W. and S. 30° E.</p>
40.26	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented by an iron post, 1 in. diam., set with 8 ins. showing above the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;"> $\frac{1}{4}$ S10 S11 1940 </p>
	<p>from which</p>
	<p>A pine, 12 ins. diam., bears S. 20$\frac{1}{4}$° E., 30 lks. dist., mkd. $\frac{1}{4}$ S11BT</p>
	<p>A pine, 23 ins. diam., bears N. 51° W., 32 lks. dist., mkd. $\frac{1}{4}$ S10 BT</p>
	<p>N. 0°08' W., beginning new measurement.</p>
	<p>Asc. over a SE. slope; through medium dense timber.</p>
5.40	<p>Forest Route No. 87; bears NE. and SW.</p>
14.30	<p>Ridge, bears NE. and SW.; desc. steep N. slope.</p>
30.20	<p>Benny Creek, dry channel, 30 lks. wide, 1 ft. deep, course NE.; asc. SE. slope.</p>
37.10	<p>Rim of canyon, bears NE. and SW.</p>
40.38	<p>The cor. of secs. 2, 3, 10 and 11, monumented by an iron post, 2 ins. diam., set firmly in a mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;"> T7N R27E S 3 S 2 S10 S11 1940 </p>
	<p>from which</p>
	<p>A pine, 18 ins. diam., bears N. 49° E., 21 lks. dist., mkd. T7N R27E S2 BT (Record bearing N. 52$\frac{1}{2}$° E.)</p>

Dep. Res., Subdivisional Lines, T. 7 N., R. 27 E.

CHAINS	
	<p>A pine, 20 ins. diam., bears S. 23° W., 26 lks. dist., mkd. T7N R27E S10 BT (Record bearing S. 18½° W.)</p> <p>A pine, 22 ins. diam., bears N. 54° W., 32 lks. dist., mkd. T7N R27E S3 BT (Record bearing N. 61¼° W.)</p> <p>Land, mountainous. Soil, rocky, clay loam. Timber, medium dense pine and fir. Undergrowth, dense willows along Benny Creek.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°09' W., bet. secs. 2 and 11.</p> <p>Asc. gentle E. slope; over pasture; along N. side of fence.</p>
5.90	Canal, 10 lks. wide, 4 ft. deep, course N. 35° E.
6.00	Enter scattered timber.
18.50	Fence, bears N. and S. for 25 lks. to fence cor., fences bear N., S. and E.
20.05	Forest Route No. 87, bears N. 40° E. and S. 40° W.
20.105	Point for the E 1/16 sec. cor. of secs. 2 and 11 at proportionate dist. Point falls in the west track of road and cannot be perpetuated because the road is scheduled to be reworked.
	<p>from which</p> <p>The iron post, set 16 ins. in the ground, in a mound of stone to top, for a reference monument, bears North 60.6 lks. dist., brass cap mkd. T7N R27E E 1/16 S2 RM 40 FT 1968 and an arrow pointing to the true cor.</p> <p>The iron post, set 18 ins. in the ground, in a collar of stone for a reference monument, bears N. 89°09' W., 60.6 lks. dist., brass cap mkd. T7N R27E E 1/16 S2 RM 40 FT S11 1968 and an arrow pointing to the true cor.</p>
20.30	Asc. steep E. slope.
40.21	The ¼ sec. cor. of secs. 2 and 11, monumented by an iron post, 1 in. diam., firmly set in a mound of stone to top, brass cap mkd.
	<p style="text-align: center;">¼ S2 S11 1940</p> <p>from which</p> <p>A pine, 25 ins. diam., bears S. 12° W., 102 lks. dist., mkd. ¼ S11 BT (Record bearing S. 5¼° W., Record diam. 36 ins.)</p> <p>A pine, 20 ins. diam., bears N. 32½° W., 162 lks. dist., mkd. ¼ S2 BT (Record bearing N. 2½° W.)</p>

Surv., Partial Subdivision, Sec. 12, T. 7 N., R. 27 E.

CHAINS	
	N. 89°10' W., beginning new measurement. Asc. E. slope; through medium dense timber.
.30	Top of ridge, bears N. and S.; desc. gentle W. slope.
15.60	Ravine, drains N.; asc. E. slope.
21.90	Ridge, bears N. and S.; desc. gentle W. slope.
23.20	E. rim of canyon; desc. steep W. slope.
32.40	Benny Creek, dry channel, 30 lks. wide, 1 ft. deep, course N. 20° E.; asc. E. slope.
39.60	W. rim of canyon; continue over nearly level land.
40.15	The cor. of secs. 2, 3, 10 and 11. Land, mountainous. Soil, rocky, clay loam. Timber, medium dense pine and fir. Undergrowth, dense willows along Benny Creek.
Surv., Partial Subdivision, Sec. 12, T. 7 N., R. 27 E.	
From the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented by an iron post, 1 in. diam., set with 12 ins. showing above the ground, in a collar of stone, brass cap mkd.	
$\frac{1}{4}$ <u>S 12</u> S 13 1940	
from which	
A pine, 13 ins. diam., bears S. 52 $\frac{3}{4}$ ° E., 70 lks. dist., mkd. $\frac{1}{4}$ S13 BT.	
A pine, 15 ins. diam., bears N. 62° W., 37 lks. dist., mkd. $\frac{1}{4}$ S12 BT.	
A developed spring, 4 x 4 ft. concrete box, bears N. 8° W., 7.20 chs. dist.	
N. 0°21' E., on the N. and S. center line of sec. 12.	
Desc. NW. slope, through dense timber.	
12.30	Butler Canyon, 300 lks. wide, drains N. 40° W.; asc. SW. slope.
14.00	Desc. gentle NW. slope.
26.40	Track road, bears NE. and SW.; asc. gentle SW. slope.
38.98	Point for the $\frac{1}{4}$ sec. cor. of sec. 12, at the intersection with the E. and W. center line of Sec. 12. Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
T7N R27E C $\frac{1}{4}$ +S 12 1968	

Surv., Partial Subdivision, Sec. 12, T. 7 N., R. 27 E.

CHAINS	
	<p>from which</p> <p>A pine, 10 ins. diam., bears S. 53° W., 41 lks. dist., mkd. C$\frac{1}{4}$ S12 BT.</p> <p>A pine, 8 ins. diam., bears N. 37° W., 32 lks. dist., mkd. C$\frac{1}{4}$ S12 BT.</p> <p>The NE. cor. of a cabin, 20 ft. by 12 ft., bears S. 26° E., 79 lks. dist.</p> <p>The NW. cor. of a cabin, 32 ft. by 16 ft., bears N. 56° E., 148 lks. dist.</p>
46.70	Power line, bears E. and W.
48.50	Track road, bears irregularly E. and W.
58.10	Bladed road, bears N. 45° W. and S. 45° E.
58.705	Point for the C-N 1/16 sec. cor. of sec. 12.
	<p>Set the iron post 10 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N 1/16 S 12</p> <p> </p> <p>C</p> <p>1968</p> </div>
	<p>from which</p> <p>A pine, 10 ins. diam., bears N. 48° E., 18 lks. dist., mkd. C N 1/16 S 12 BT.</p> <p>A pine, 12 ins. diam., bears N. 40° W., 60 lks. dist., mkd. C N 1/16 S12 BT.</p>
66.00	Bladed dirt road, bears NE. and SW.
72.00	Fence, bears NE. and SW.
78.30	Track road, bears NE. and SW.
78.43	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 12.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, medium dense pine and fir. Undergrowth, grass.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented by an iron post, 1 in. diam., set in a mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>$\frac{1}{4}$</p> <p>S12 S 7</p> <p>1940</p> </div>
	<p>from which</p> <p>A pine, 13 ins. diam., bears S. 66° E., 81 lks. dist., mkd. $\frac{1}{4}$ S7 BT.</p> <p>A pine, 20 ins. diam., bears S. 72$\frac{3}{4}$° W., 72 lks. dist., mkd. $\frac{1}{4}$ S12 BT.</p>

Surv., Partial Subdivision, Sec. 12, T. 7 N., R. 27 E.

CHAINS	
	S. 89°42' W., on the E. and W. center line of sec. 12.
	Desc. W. slope, through medium dense timber.
18.80	Slope changes to SE.; asc.
23.50	Track road, bears irregularly N. and S.
24.70	Small spring, course N., undeveloped.
39.95	The $\frac{1}{4}$ sec. cor. of sec. 12.
42.10	Fence, bears N. and S.
47.00	Track road, bears NW. and SE.
52.60	Creek, 4 lks. wide, water 3 ins. deep, course N.
59.875	Point for the C-W 1/16 sec. cor. of sec. 12.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<u>C W 1/16 @</u> S12 1968
	from which
	A pine, 8 ins. diam., bears S. 7° W., 50 lks. dist., mkd. C W 1/16 S12 BT.
	A pine, 10 ins. diam., bears N. 68° W., 33 lks. dist., mkd. C W 1/16 S12 BT.
	A local cor., a water pipe, $\frac{3}{4}$ ins. diam., set with 14 ins. showing above the ground, bears N. 44°30' E., 32 lks. dist.
	A developed spring, 4 ft. x 4 ft. concrete box, bears S. 84°40' E., 10.20 chs. dist.
	Raise a mound of stone N. of cor.
66.50	Track road, bears irregularly N. 70° E. and S. 70° W.
69.50	Forest Route No. 79A, bladed dirt road, bears N. and S.
74.40	Leave timber.
76.20	Fence, bears N. and S. for 25 lks. to fence cor., fences bear W. and N.
77.20	Power line, bears irregularly NE. and W.
78.60	Arizona Highway No. 373, bears W. and curves to the NE.
79.80	The true point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Land, gently rolling. Soil, rocky, clay loam. Timber, medium dense pine and fir. Undergrowth, grass.

Surv., Partial Subdivision, Sec. 12, T. 7 N., R. 27 E.

CHAINS									
	Subdivision, NW $\frac{1}{4}$ of Section 12								
	From the C-W 1/16 sec. cor. of sec. 12.								
	N. 0°52' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 12.								
	Over gently rolling land sloping N. and W.; through medium dense timber.								
2.80	Track road, bears E. and W.								
5.20	Track road, bears N. 75° W. and S. 75° E.								
13.50	Power line, bears NE. and S. 40° W.								
15.00	Arizona Highway No. 373, curves NE. and SW.								
17.49	Intersect line 3-4, tract 38 at a point from which angle point No. 3 bears S. 86°32' E., 18.5 lks. dist., hereinafter described.								
17.50	Fence, bears W. and E. for 18 lks. to fence cor., fences bear N. and W.								
17.70	Telephone line, bears E. and W.								
19.63	Point for the NW 1/16 sec. cor. of sec. 12, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ of sec. 12. This cor. also functions as angle point No. 6 tract 38. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.								
	<table border="0"> <tr> <td colspan="2">T7N R27E</td> </tr> <tr> <td>NW 1/16</td> <td>AP 6</td> </tr> <tr> <td>S 12</td> <td>TR 38</td> </tr> <tr> <td colspan="2">1968</td> </tr> </table>	T7N R27E		NW 1/16	AP 6	S 12	TR 38	1968	
T7N R27E									
NW 1/16	AP 6								
S 12	TR 38								
1968									
	from which								
	A local cor., a water pipe, $\frac{3}{4}$ ins. diam., bears N. 85°50' E., 19 lks. dist.								
	The SE. cor. of a house, bears S. 45°01' W., 232 lks. dist.								
	The NW. cor. of a house, bears S. 86°26' W., 10.74 chs. dist.								
20.60	Driveway, bears N. 70° E. and S. 70° W.								
22.60	Fence, bears E. and W.; enter pasture.								
37.50	Fence, bears E. and W.; leave pasture.								
38.60	Little Colorado River, 30 lks. wide, water 1 ft. deep, course E.								
39.28	The W 1/16 sec. cor. of secs. 1 and 12.								

Surv., Partial Subdivision, Sec. 1, T. 7 N., R. 27 E.

CHAINS	
	<p>From the C-N 1/16 sec. cor. of sec. 12.</p> <p>S. 89°24' W., on the E. and W. center line of the NW$\frac{1}{4}$ of sec. 12.</p> <p>Over gently rolling land, NW. slope, through medium dense timber.</p>
.40	Bladed dirt road, bears N. 40° W. and S. 40° E.
3.10	Fence, bears N. 25° W. and S. 25° E.
7.00	Graded dirt road, bears N. 50° E. and S. 50° W.
12.00	Fence, bears N. and S. Fence is E. side of Forest Ranger Station.
17.70	Fence, bears N. 10° E. and S. 10° W. Fence is W. side of Forest Ranger Station and also the right-of-way fence for the highway.
17.80	Power line, bears N. 10° E. and S. 10° W.
18.40	Arizona Highway No. 373, curves N. 15° E. and SW.
19.20	Fence, bears N. 8° E. and S. 8° W.
19.25	Intersect line 2-3, tract 38 at a point from which angle point No. 2 bears N. 8°34' E., 80 lks. dist., hereinafter described.
19.725	The NW 1/16 sec. cor. of sec. 12.
22.60	Fence, bears N. and S.
27.80	Fence, bears N. and S.
38.80	Fence, bears N. and S.
39.47	The N 1/16 sec. cor. of secs. 11 and 12.
Surv., Partial Subdivision, Sec. 1, T. 7 N., R. 27 E.	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.</p> <p>N. 1°06' W., on the N. and S. center line of sec. 1.</p> <p>Along the W. side of a fence bearing N. 4° W., through dense willows.</p>
1.70	Cross fence bearing N. 4° W. and S. 4° E.
6.20	Little Colorado River, 30 lks. wide, water 1 ft. deep, course irregular NE.
12.00	Enter open field, edge bears E. and W.; fence cor., bears W., 50 lks. dist., fences, bear N. 4° W., S. 4° E. and East.
19.98	Point for the C-S 1/16 sec. cor. of sec. 1.
	<p>Set the iron post 16 ins. in the ground, in a mound of stone to top, brass cap mkd.</p>

CHAINS		
	<p style="text-align: center;"> C S 1/16 S 1 C 1968 </p> <p>from which</p> <p>A pine, 6 ins. diam., bears N. 28½° W., 22 lks. dist., mkd. CS 1/16 S1 BT.</p> <p>The NE. cor. of an old sawmill building, bears N. 89°30' W., 11.60 chs. dist.</p> <p>A fence, bearing irregularly N. and S., bears west, 50 lks. dist.</p>	
22.40	Fence, bears N. 82° W. and S. 82° E.	
31.60	Track road, bears N. 60° W. and S. 60° E.	
39.60	Canal, 10 lks. wide, 3 ft. deep, drains NE.	
39.96	Point for the C¼ sec. cor. of sec. 1, at the intersection with the E. and W. center line of sec. 1.	
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.	
	T7N R27E C ¼ +S 1 1968	
	<p>from which</p> <p>A pine, 12 ins. diam., bears N. 46° W., 36 lks. dist., mkd. C¼ S1 BT.</p>	
48.80	Bladed road, bears N. 30° W. and S. 30° E.	
53.50	Bladed road, bears SE. and NW.	
55.00	Graded dirt road, bears N. 80° E. and S. 80° W.	
57.50	Power line, bears SW. and NE.	
64.90	S. edge of Bunch Reservoir, bears E. and W.; thence across water on a calculated bearing and distance.	
79.91	True point for the ¼ sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp. Point falls in Bunch Reservoir.	
	<p>from which</p> <p>The witness ¼ sec. cor. of secs. 1 and 36, bears N. 89°38' W., 650 lks. dist., (Record), monumented with an iron post, 1 in. diam., set firmly in the ground; post has been bent over but is solid, brass cap mkd.</p> <p style="text-align: center;"> ¼ S 36 S 1 1940 </p>	

Surv., Partial Subdivision, Sec. 1, T. 7 N., R. 27 E.

CHAINS	
	<p>from which</p> <p>A pine, 13 ins. diam., bears S. 21½° E., 61 lks. dist., mkd. with a healed blaze.</p> <p>A pine, 13 ins. diam., bears N. 31¼° W., 129 lks. dist., mkd. with a healed blaze.</p> <p>Land, gently rolling to nearly level. Soil, sandy loam. Timber, scattered pine. Undergrowth, dense willows along river, grass in field.</p>
	<p>From the true point for the ¼ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., which falls in River Reservoir and is not monumented.</p> <p>from which</p> <p>The witness ¼ sec. cor. of secs. 1 and 6, bears N. 45° W., 3.50 chs. dist., (Record), monumented with an iron post, 1 in. diam., set firmly with 8 ins. showing above the ground, brass cap mkd.</p> <p style="text-align: center;">¼ S1 S6 WC 1940</p> <p>from which</p> <p>A pine, 15 ins. diam., bears N. 31° E., 117 lks. dist., mkd. with a healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 54¾° W., 37 lks. dist., mkd. with a healed blaze.</p> <p>S. 89°53' W., on the E. and W. center line of sec. 1.</p> <p>On a calculated line across River Reservoir.</p>
3.30	West edge of River Reservoir, bears irregularly N. and S.; thence across Forest Service campground; through scattered timber.
10.70	Track road, bears N. and S.
12.60	East edge of Tunnel Reservoir, bears irregularly N. and S.; thence by triangulation across the water.
32.20	West edge of Tunnel Reservoir, bears irregularly N. and S.; thence across campground; through scattered timber.
39.50	Leave campgrounds and timber; enter open field.
39.57	The C¼ sec. cor. of sec. 1.
48.60	Canal, 10 lks. wide, 3 ft. deep, drains NE.
56.00	Power line, bears N. 45° E. and S. 45° W.
59.37	Point for the C-W 1/16 sec. cor. of sec. 1.
	Set the iron post 16 ins. in the ground, in a mound of stone to top, brass cap mkd.

Surv., Partial Subdivision, Sec. 1, T. 7 N., R. 27 E.

CHAINS	
	<p>C W 1/16 C S1 1968</p>
	<p>from which</p> <p style="padding-left: 40px;">A re-bar, bears N. 41° E., 22 lks. dist.</p>
60.50	Arizona Highway No. 373, paved, bears S. 6° E. and N. 6° W.
64.30	Track road, bears N. and S.; enter timber.
79.17	The ¼ sec. cor. of secs. 1 and 2.
	<p>Land, nearly level. Soil, sandy loam. Timber, scattered pine. Undergrowth, grass.</p>
	<p>Subdivision, SW¼ of Section 1</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the W 1/16 sec. cor. of secs. 1 and 12.</p> <p>N. 1°28' W., on the N. and S. center line of the SW¼ of sec. 1.</p> <p>Asc. gentle S. slope.</p>
20.10	<p>Point for the SW 1/16 sec. cor. of sec. 1, at the intersection with the E. and W. center line of the SW¼ of sec. 1.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p>SW 1/16 + S 1 1968</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 50° E., 17 lks. dist., mkd. SW 1/16 S1 BT.</p> <p style="padding-left: 40px;">NW. cor. of Basket's house, bears S. 83°25' W., 3.03 chs. dist.</p> <p>Cor. falls under the step of a shed 12 ft. x 12 ft. The NE. cor. of the shed bears N. 45° E., 1.5 lks. dist.</p>
20.50	Fence, bears irregularly E. and W.
25.40	Canal, 15 lks. wide, 3 ft. deep, drains irregularly N.
30.70	Road to Basket House Cabins, bears NE. and SW. for 50 lks., thence S.
34.80	Arizona Highway No. 373, paved, bears N. 15° W. and S. 15° E.
36.30	Power line, bears NE. and SW.
40.20	The C-W 1/16 sec. cor. of sec. 1.

Surv., Partial Subdivision, Sec. 1, T. 7 N., R. 27 E.

CHAINS	
	<p>From the C-S 1/16 sec. cor. of sec. 1.</p> <p>S. 89°31' W., on the E. and W. center line of the SW$\frac{1}{4}$ of sec. 1.</p> <p>Over gently rolling land.</p>
.50	Fence, bears S. 5° E. and N. 5° W.
15.70	Power line, bears N. and S.
16.20	Fence, bears S. 5° E. and N. 5° W.
17.00	Arizona Highway No. 373, bears N. 5° W. and S. 5° E.
19.67	The SW 1/16 sec. cor. of sec. 1.
20.20	Canal, 10 lks. wide, 3 ft. deep, drains N.
35.90	Power line, bears NW. and SE.
39.20	Fence, bears S. and N. for 4 lks., thence, irregularly E.
39.35	The point for the S 1/16 sec. cor. of secs. 1 and 2.
Surv., Partial Subdivision, Sec. 14, T. 7 N., R. 27 E.	
	<p>From the true point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</p> <p>N. 0°44' W., on the N. and S. center line of sec. 14.</p> <p>Desc. NW. slope, through dense timber.</p>
5.00	Base of steep slope, bears N. 30° E. and S. 30° W.; over nearly level bottom land.
8.20	Little Colorado River, 40 lks. wide, water 1 ft. deep, course N. 10° E.
18.00	Forest Route No. 575, graded dirt road, bears N. 25° E. and S. 25° W.; asc. along SE. slope through dense timber.
20.00	Point for the C-S 1/16 sec. cor. of sec. 14.
	<p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S 14</p> <p> </p> <p> C</p> <p> 1968</p> </div> <p>from which</p> <p>A pine, 9 ins. diam., bears S. 52° E., 25 lks. dist., mkd. C S 1/16 S14 BT.</p> <p>A pine, 8 ins. diam., bears S. 56° W., 30 lks. dist., mkd. C S 1/16 S14 BT.</p>

Surv., Partial Subdivision, Sec. 14, T. 7 N., R. 27 E.

CHAINS		
20.70	Fence, bears irregularly E. and W.	
40.00	Point for the $C\frac{1}{4}$ sec. cor. of sec. 14, at the intersection with the E. and W. center line of sec. 14. This cor. is not monumented.	
	from which	
	A local pipe, 1 in. diam., bears N. $76^{\circ}36'$ E., 28 lks. dist.	
40.10	Fence, bears irregularly E. and W.	
43.20	Power line, bears N. $89^{\circ}46'$ W. and S. $89^{\circ}46'$ E.	
60.04	Point for the C-N $1/16$ sec. cor. of sec. 14, marked by a local survey marker mkd. SE. cor. $NE\frac{1}{4}$ sec. 14; SW. cor. $NW\frac{1}{4} NE\frac{1}{4}$; T7N R27E; NE. cor. $SE\frac{1}{4} NW\frac{1}{4}$; NW cor. $SW\frac{1}{4} NE\frac{1}{4}$; Lacy C. Greer, 8-5-1955.	
	Set the iron post 16 ins. in the ground, with mound of stone to top, brass cap mkd.	
	<div style="text-align: center;"> <p>C</p> <p>N $1/16$ S 14</p> <p> </p> <p>C</p> <p>1968</p> </div>	
	from which	
	A pine, 10 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ E., 32 lks. dist., mkd. C N $1/16$ S14 BT.	
	Reset the local survey marker, inverted and alongside the iron post.	
65.90	Fence, bears irregularly E. and W. for 25 lks., thence, irregularly N. and S.	
80.08	The $\frac{1}{4}$ sec. cor. of secs. 11 and 14.	
	Land, rolling. Soil, sandy loam to clay loam. Timber, dense pine and fir. Undergrowth, grass.	
	From the true point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.	
	S. $89^{\circ}33'$ W., on the E. and W. center line of sec. 14,	
	Through private yard.	
3.20	Leave yard, across meadow.	
24.30	Little Colorado River, 30 lks. wide, water 1 ft. deep, course irregularly NE.; leave meadow.	
27.40	Forest Route No. 575, graded dirt, bears irregularly S. 30° W. and N. 30° E.; enter dense timber; asc. E. slope.	
39.93	The point for the $C\frac{1}{4}$ sec. cor. of sec. 14.	
55.50	Asc. steep NE. slope.	

Surv., Partial Subdivision, Sec. 14, T. 7 N., R. 27 E.

CHAINS	
59.455	<p>Point for the C-W 1/16 sec. cor. of sec. 14.</p> <p>Set the iron post 16 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C — W 1/16 — C S 14 1968</p> <p>from which</p> <p style="padding-left: 40px;">A white fir, 4 ins. diam., bears S. 61° W., 20 lks. dist., mkd. CW 1/16 S14 BT.</p> <p style="padding-left: 40px;">The NW. cor. of a cabin, bears N. 26°30' E., 324 lks. dist.</p>
78.98	<p>The ¼ sec. cor. of secs. 14 and 15.</p> <p>Land, mountainous. Soil, sandy loam. Timber, dense pine and fir. Undergrowth, dense willows along river.</p>
<p>Subdivision, SW¼ of Section 14</p> <hr style="width: 30%; margin: auto;"/>	
	<p>From the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0°26' W., on the N. and S. center line of the SW¼ of sec. 14.</p> <p>Over a steep E. slope; through dense timber.</p>
2.70	Slope changes to NE.
5.80	Bottom of desc.; asc. over SE. slope.
20.00	<p>Point for the SW 1/16 sec. cor. of sec. 14, at the intersection with the E. and W. center line of the SW¼ of sec. 14.</p> <p>Set the iron post 14 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">SW 1/16 + S14 1968</p> <p>from which</p> <p style="padding-left: 40px;">A white fir, 10 ins. diam., bears S. 4° E., 37 lks. dist., mkd. SW 1/16 S14 BT.</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears N. 68° W., 16 lks. dist., mkd. X BT.</p>
26.60	Slope changes to E.
34.40	Begin desc., steep NE. slope.
40.00	<p>The C-W 1/16 sec. cor. of sec. 14.</p> <hr style="width: 30%; margin: auto;"/> <p>From the C-S 1/16 sec. cor. of sec. 14.</p> <p>S. 89°32' W., on the E. and W. center line of the SW¼ of sec. 14.</p>

Surv., Partial Subdivision, Sec. 11, T. 7 N., R. 27 E.

CHAINS	
	Asc. steep E. slope; through dense timber.
19.67	The SW 1/16 sec. cor. of sec. 14.
23.80	Top of steep asc.; continue asc. over gentle E. slope.
39.33	The S 1/16 sec. cor. of secs. 14 and 15.
<u>Subdivision, NW$\frac{1}{4}$ of Section 14</u>	
	From the C-W 1/16 sec. cor. of sec. 14.
	N. 0°15' W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 14.
	Desc. N. slope; through dense timber.
10.10	Draw, drains E.; asc. SE. slope.
19.60	Abandoned fence, bears E. and W.
20.07	Point for the NW 1/16 sec. cor. of sec. 14, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ of sec. 14.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	NW 1/16 + S14 1968
	from which
	A pine, 14 ins. diam., bears S. 56° W., 16 lks. dist., mkd. NW 1/16 S14 BT.
	A pine, 5 ins. diam., bears N. 19° W., 18 lks. dist., mkd. NW 1/16 S14 BT.
	A fence cor., bears S. 26° W., 52 lks. dist.; fences bear irregularly S. and E. and are nearly abandoned.
40.11	The W 1/16 sec. cor. of secs. 11 and 14.
	—————
	From the C-N 1/16 sec. cor. of sec. 14.
	S. 89°34' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 14.
	Asc. E. slope; through dense timber.
.10	Fence, bears irregularly N. and S.
9.40	Track road, bears irregularly N. and S.
19.39	The NW 1/16 sec. cor. of sec. 14.
38.76	The true point for the N 1/16 sec. cor. of secs. 14 and 15.
Surv., Partial Subdivision, Sec. 11, T. 7 N., R. 27 E.	

Surv., Partial Subdivision, Sec. 11, T. 7 N., R. 27 E.

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.
	N. $1^{\circ}12'$ E., on the N. and S. center line of sec. 11.
	Desc. gentle NE. slope; through medium timber.
2.55	Track road, bears E. and W.
2.70	Fence, bears E. and W.
11.00	Fence, bears E. and W.
14.22	Intersect the NE. cor. of a cabin.
16.62	The SE. cor. of a cabin, bears West, 10 lks. dist.
18.52	Intersect the NE. cor. of a porch of a cabin.
20.04	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 11.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">C S $\frac{1}{16}$ S 11 C 1968</p>
	from which
	<p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 35° W., 72 lks. dist., mkd. CS $\frac{1}{16}$ S11 BT.</p>
	<p style="padding-left: 40px;">A local survey cor., a pipe, $\frac{1}{2}$ in. diam., bears N. $1^{\circ}12'$ E., 15 lks. dist.</p>
21.00	Fence, bears N. 70° E. and S. 70° W.
24.50	Track road, bears irregularly SE. and NW.
24.80	Small stream, 4 lks. wide, 4 ins. deep, drains E.; begin asc. gentle SE. slope.
37.50	Track road, bears irregularly E. and W.
40.08	Point for the C $\frac{1}{4}$ sec. cor. of sec. 11, at the intersection with the E. and W. center line of sec. 11.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7N R27E C$\frac{1}{4}$+S11 1968</p>
	from which
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. $61\frac{1}{2}^{\circ}$ E., 31 lks. dist., mkd. C$\frac{1}{4}$ S11 BT.</p>
	<p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 25° E., 23 lks. dist., mkd. C$\frac{1}{4}$ S11 BT.</p>
53.40	Forest Route No. 87, bladed dirt road, bears N. 20° E., curving NE. and S. 20° W. and curving SW.; begin asc. steep SE. slope.
79.78	The $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Surv., Partial Subdivision, Sec. 11, T. 7 N., R. 27 E.

CHAINS	<p>Land, mountainous. Soil, rocky, clay loam. Timber, medium to dense pine and fir. Undergrowth, grass.</p>
	<p>From the true point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.</p> <p>S. $89^{\circ}56'$ W., on the E. and W. center line of sec. 11.</p> <p>Along paved Arizona Highway No. 373.</p> <p>5.00 N. edge of Arizona Highway No. 373, bears N. 85° E. and S. 65° W.; enter dense willows.</p> <p>5.40 Fence, bears N. 85° E. and S. 65° W.</p> <p>8.40 Little Colorado River, 40 lks. wide, water 1 ft. deep, course northerly.</p> <p>11.70 Fence, bears N. 80° E. and S. 80° W.; enter open field.</p> <p>17.80 Fence, bears N. and S.</p> <p>18.30 Canal, 10 lks. wide, 1 ft. deep, course irregularly N.</p> <p>20.02 Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 11.</p>
	<p>Set the iron post with the top 4 ins. below the surface of the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>C — $\frac{E \ 1/16}{S \ 11}$ — C</p> <p>1968</p> </div>
	<p>from which</p> <p>A nail driven in a post, 6 x 6 ins., 3 ft. high, bears S. $3^{\circ}40'$ E., 47 lks. dist.</p> <p>A nail driven in a power pole, bears S. $75^{\circ}40'$ W., 72 lks. dist.</p> <p>The SW. cor. of a house, bears N. $47^{\circ}30'$ W., 51 lks. dist.</p> <p>Corner located in a driveway.</p>
20.90	Fence, bears N. and S.; asc. E. slope through medium timber.
23.80	Track road, bears N. 20° E. and S. 20° W.
27.80	Asc. steep E. slope.
40.04	The $C\frac{1}{4}$ sec. cor. of sec. 11.
46.70	Track road, bears irregularly SE. and NW.
79.30	The $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Surv., Partial Subdivision, Sec. 11, T. 7 N., R. 27 E.

CHAINS	<p>Land, nearly level in the E. $\frac{1}{4}$; mountainous in the W. Soil, sandy loam in the E. $\frac{1}{4}$; rocky, clay loam in the W. Timber, medium to dense pines and fir in the W. $\frac{3}{4}$. Undergrowth, dense willows along the Little Colorado River, grass in the field.</p>
	<p>Subdivision, SE$\frac{1}{4}$ of Section 11</p> <hr/>
	<p>From the point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 1°02' E., on the N. and S. center line of the SE$\frac{1}{4}$ of sec. 11.</p> <p>Over open land.</p>
.80	<p>Old fence, bears N. 25° W. for approximately 1.00 ch., thence N. and S. 25° E. for approximately 1.00 ch., thence S.</p>
1.80	<p>Graded dirt road, bears E. and W.</p>
5.70	<p>Base of hill bears E. and W.; asc. S. slope.</p>
6.60	<p>Top of asc.; thence gradual desc. over NE. slope; fence bears E. and W.</p>
10.60	<p>Private road, bears S. 20° E. and N. 20° W.</p>
12.50	<p>Rail fence, bears E. and W.</p>
19.99	<p>Point for the SE 1/16 sec. cor. of sec. 11, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$ of sec 11.</p> <p>Set the iron post 6 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">SE 1/16 + S11 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 80° W., 27 lks. dist., mkd. SE 1/16 S11 BT.</p> <p style="padding-left: 40px;">A pipe, $\frac{1}{2}$ in. diam., bears N. 7$\frac{1}{2}$° E., 7 lks. dist., with tag mkd. LS 1476.</p>
20.25	<p>Fence, bears irregularly E. and W.</p>
31.90	<p>Graded dirt road, bears NE. and SW. for 1.00 ch., then curves NW.</p>
36.00	<p>Small stream, 5 lks. wide, 1 ft. deep, course NE.; enter field.</p>
39.40	<p>Fence bears E. and W.</p>
39.96	<p>The C-E 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 11 and 12.</p>

Surv., Partial Subdivision, Sec. 2, T. 7 N., R. 27 E.

CHAINS	
	S. 89°43' W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 11. Over bottom land; through dense willows.
1.10	Little Colorado River, 60 lks. wide, water 1 ft. deep, course irregularly N.
3.80	Enter open field, edge bears NW. and SE.
14.30	Arizona Highway No. 373, paved, the main street of Greer, Arizona, bears N. 20° E. and S. 20° W.
15.00	Begin asc. E. slope, enter timber.
20.00	Top of asc.; desc. gradual W. slope.
20.09	The SE 1/16 sec. cor. of sec. 11.
22.20	Telephone line, bears N. and S.; fence, bears S. 8° E. and N. 8° W.; enter open field.
35.20	Enter timber, edge bears N. and S.
40.18	The C-S 1/16 sec. cor. of sec. 11
Surv., Partial Subdivision, Sec. 2, T. 7 N., R. 27 E.	
	From the $\frac{1}{4}$ sec. cor. of sec. 2 and 11. N. 1°39' W., on the N. and S center line of sec. 2. Asc. SE. slope; through dense timber.
.70	Top of Asc.; over nearly level land.
12.70	Rim, bears SE. and NW.; desc. NE. slope.
13.20	Fence, bears SE. and NW.
40.34	Point for the C $\frac{1}{4}$ sec. cor. of sec. 2, at the intersection with the E. and W. center line of sec. 2. Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	T7N R27E C $\frac{1}{4}$ + S2 1968
	from which A pine, 10 ins. diam., bears N. 56 $\frac{1}{2}$ ° E., 41 lks. dist., mkd. C $\frac{1}{4}$ S2 BT. A pine, 10 ins. diam., bears S. 17 $\frac{1}{2}$ ° W., 63 lks. dist., mkd. C $\frac{1}{4}$ S2 BT.
61.40	Logging road, bears irregularly E. and W.
64.30	S. rim of canyon, bears E. and W.
67.30	Benny Creek, course E.

Surv., Partial Subdivision, Sec. 2, T. 7 N., R. 27 E.

<p>CHAINS 68.70</p> <p>75.30</p> <p>80.25</p>	<p>N. rim of canyon, bears E. and W.</p> <p>Logging road, bears irregularly E. and W.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an iron post, 1 ins. diam., set with 6 ins. showing above a collar of stone, brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 35}{S\ 2}$ 1940</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears N. 30° E., 39 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 40$\frac{1}{4}$° E., 97 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p>Land, mountainous. Soil, rocky, clay loam. Timber, dense pine, aspen and fir. Undergrowth, dense willows along Benny Creek.</p>
<p>12.10</p> <p>16.60</p> <p>20.04</p>	<p>From the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.</p> <p>N. 89°15' W., on the E. and W. center line of sec. 2.</p> <p>Over nearly level land, through dense pines.</p> <p>Forest Route No. 87, gravelled road, bears S. 50° E., and N. 50° W.</p> <p>Driveway, bears N. and S.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 2. The point is marked by a pipe, 1 ins. diam., mkd. T7N R27E 1/16 cor. S2 PE 6123.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C ——— E 1/16 ——— C S 2 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 43$\frac{1}{2}$° W., 91 lks. dist., mkd. CE 1/16 S2 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 35° W., 37 lks. dist., mkd. CE 1/16 S2 BT.</p> <p>Raise a mound of stone N. of the cor. Reset the local cor., inverted and alongside the iron post.</p>
<p>23.70</p> <p>40.08</p> <p>67.90</p> <p>71.10</p> <p>80.10</p>	<p>Fence, bears S. 12° E. and N. 12° W.</p> <p>The $C\frac{1}{4}$ sec. cor. of sec. 2.</p> <p>Benny Creek, 15 lks. wide, 2 ft. deep, course N.</p> <p>Asc. SE. slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., set with 8 ins. showing above</p>

Surv., Tract 38, Section 12, T. 7 N., R. 27 E.

CHAINS

the ground, brass cap mkd.

$\frac{1}{4}$
 S3 | S 2
 1940

from which

A pine, 13 ins. diam., bears S. $54\frac{1}{2}^\circ$ E., 14 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

A pine, 14 ins. diam., bears N. 87° W., 38 lks. dist., mkd. with visible scribes in a partially healed blaze.

Land, rolling.

Soil, rocky, clay loam.

Timber, dense pine and fir.

Undergrowth, dense willows along Benny Creek.

Surv., Tract 38, Section 12, T. 7 N., R. 27 E.

From angle point No. 1, Tract 38, determined by the intersection of the sec. line bet. secs. 1 and 12 and the right-of-way on the west side of Arizona Highway No. 373.

At the cor. point

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7N R27E
 S 1
 AP 1 |
 TR 38 | S 12
 1968

from which

The W $\frac{1}{16}$ sec. cor. of secs. 1 and 12, bears S. $89^\circ 10'$ W., 108 lks. dist.

A local re-bar, $\frac{3}{4}$ ins. diam., bears North 1 lk. dist.

Cor. is located underneath right-of-way fence.

Thence, S. $2^\circ 23'$ W., with line 1-2, tract 38,

Along fence line, over bottom land.

.90 Little Colorado River, 30 lks. wide, water 1 ft. deep, course E.

18.70 Driveway, bears N. 70° E. and S. 70° W.

18.88 Highway right-of-way marker, a brass tablet, 3 ins. diam., set in a concrete block, mkd. Point AHD 109+15.81 1959. Highway marker is identical with angle point No. 2, tract 38.

from which

Surv., Tract 38, Section 12, T 7 N., R. 27 E.

CHAINS		
	<p>The iron post, set 10 ins. in the ground, in a mound of stone to top, for a reference monument, bears N. 2°23' E., 98.5 lks. dist., mkd. T7N R27E AP 2 TR 38 RM 65 FT 1968 and an arrow pointing to the true cor.</p> <p>The iron post, set 18 ins. in the ground, in a collar of stone, for a reference monument, bears S. 8°34' W., 60.6 lks. dist., mkd. T7N R27E AP 2 TR 38 RM 40 FT 1968 and an arrow pointing to the true cor.</p> <p>From this RM, the right-of-way fence, bears East, 7 lks. dist.</p> <p>Thence, S. 8°34' W., with line 2-3, tract 38.</p> <p>Over gently rolling land, through moderate timber.</p>	
.80	Intersect the E. and W. center line of the NW¼ of sec. 12 at a point from which the NW 1/16 sec. cor. of sec. 12, bears S. 89°24' W., 47.5 lks. dist.	
2.98	<p>Point for angle point No. 3, tract 38, marked by a re-bar ¾ in. diam. This cor. was pointed out by Forest Service personnel.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R27E TR 38 <u>AP 3</u> S 12 1968</p> </div> <p>Reset the re-bar alongside the iron post.</p> <p>Cor. located 2 lks. South of fence cor.; fences bear N. 10° E. and Westerly.</p> <p>Thence, N. 86° 32' W., with line 3-4, tract 38.</p> <p>Over gently rolling land; through moderate timber.</p>	
.185	Intersect the N. and S. Center line of the NW¼ of sec. 12 at a point from which the NW 1/16 sec. cor. of sec. 12, bears N. 0°52'E., 214 lks. dist.	
19.20	Fence, bears N. and S.	
19.945	<p>Intersect the sec. line bet. secs. 11 and 12.</p> <p>Point for angle point No. 4, tract 38, marked by a re-bar, ¾ ins. diam. This cor. was pointed out by Forest Service personnel as being a cor. of the tract.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R27E S11 TR 38 <u>AP 4</u> S 12 1968</p> </div>	

Surv., Tract 38, Sec. 12, T. 7 N., R. 27 E.

CHAINS	
	Reset the re-bar alongside the iron post.
	Thence, N. 1°26' E., with line 4-5, tract 38, on the line bet. secs. 11 and 12.
	Over bottom land, through dense willows.
.74	The N 1/16 sec. cor. of secs. 11 and 12, identical with angle point No. 5, tract 38, heretofore described.
	Thence N. 89°24' E., with line 5-6, tract 38, on the E. and W. center line of the NW ¼, sec. 12.
	Over gently rolling land; through moderate timber.
.70	Fence, bears N. and S.
11.70	Fence, bears N. and S.
16.90	Fence, bears N. and S.
19.745	The NW 1/16 sec. cor. of sec. 12, identical with angle point, No. 6, tract 38, heretofore described.
	Thence N. 0°52' E. with line 6-7, tract 38, on the N. and S. center line of the NW ¼, sec. 12.
	Over bottom land.
1.00	Driveway, bears N. 70° E. and S. 70° W.
3.00	Fence, bears E. and W.; enter pasture.
17.90	Fence, bears E. and W.; leave pasture.
19.00	Little Colorado River, 30 lks. wide, water 1 ft. deep, course E.
19.65	The W 1/16 sec. cor. of secs. 1 and 12, identical with angle point No. 7, tract 38, heretofore described.
	Thence, N. 89°10' E. with line 7-8, tract 38, on the line bet. secs. 1 and 12.
1.08	Angle point No. 1, tract 38, and point of beginning.
General Description	
<p>The portion of Township 7 North, Range 27 East, included in this survey, lies in the south-central part of Apache County, approximately 15 miles southwest of Springerville, Arizona. The town of Greer, a very small town of approximately 100 permanent residents, lies in the SE ¼ of section 11. There are numerous forest campgrounds, equipped with fireplaces, tables, and running water, in the area. Private land owners have developed most of the patented land and built summer cabins. The summer tourist industry seems to be the major source of income for the area, although the lumber and cattle industries are present.</p> <p>The land is mountainous, with a valley approximately one-half mile wide along the Little Colorado River. The river is approximately 8400 feet in elevation. The mountains, rising sharply to approximately 9000 feet on</p>	

CHAINS

either side of the river, have a dense growth of pine, fir and aspen. The soil is sandy loam along the river but rocky, clay loam in the remainder of the area. There are many small springs, most of which have been developed in the surveyed sections. The river provides good trout fishing, as do the three reservoirs in section 1.

Arizona Highway No. 373, a paved all-weather road, enters in section 1 and ends at Greer. Several all-weather Forest Routes give excellent access to all portions of the township.

There is no mining activity within the area surveyed.

34

BOOK 4835

CHAINS		

CERTIFICATE OF SURVEY

I, Jerrold E. Knight, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 23rd day of May, 19 68,

I have dependently resurveyed a portion of subdivisional lines and surveyed partial subdivisions in sections 1, 2, 11, 12 and 14 and a metes and bounds survey of Tract 38, section 12, Township 7 North, Range 27 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 25, 1969
(Date)

Jerrold E. Knight
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date APR 22 1969

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of subdivisional lines and a survey of partial subdivisions in sections 1, 2, 11, 12 and 14 and a metes and bounds survey of Tract 38, section 12, Township 7 North, Range 27 East of the Gila and Salt River Meridian, Arizona

executed by Jerrold E. Knight

having been critically examined and found correct, are hereby approved.

MAY 22 1969
(Date)

Clark J. Gunn
~~(Chief, Division of Engineering)~~
Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Engineering)~~