

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

NORTH BOUNDARY (4TH STANDARD PARALLEL NORTH)

the EAST and WEST BOUNDARIES

and the

SUBDIVISIONAL LINES

of

TOWNSHIP 16 NORTH, RANGE 21 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens Cadastral Surveyor

Gary T. Oviatt Cadastral Surveyor

Under special instructions dated August 1, 19 66, which provided for the surveys
included under Group Number 447, approved August 1, 1966,
and assignment instructions dated September 27, 19 66.

Survey commenced October 19, 19 66

Survey completed November 21, 19 66

INDEX DIAGRAM

Township 16 North, Range 21 East,
 6 4 4 3 3 1

13	6 48	49 5 48	39 4 38	31 3 31	25 2 24	19 1 19	9
12	7 47	47 8 46	38 9 37	30 10 30	23 11 23	18 12 17	
12	18 45	45 17 44	36 16 35	29 15 28	22 14 22	17 13 16	
11	19 43	44 20 43	35 21 34	28 22 27	22 23 21	16 24 16	9
10	30 41	42 29 41	33 28 33	27 27 26	21 26 21	15 25 15	8
10	31	40 32	32 33	26 34	20 35	14 36	7

Township 16 North, Range 21 East
Gila and Salt River Meridian, Arizona

CHAINS

The north boundary (the Fourth Standard Parallel North) was surveyed by J. L. Harris in 1879. The east boundary was surveyed by C. B. Foster in 1875, retraced by H. Meyrick in 1883 and again retraced and part of the corners remonumented by Forrest and Warner in 1944. The south and west boundaries and subdivisional lines were surveyed by H. Meyrick in 1883. The south boundary was concurrently resurveyed by Owens and Herman under this same group. The field notes thereof are included under T. 15 N., R. 21 E. The subdivisional lines were partially retraced and the ¼ sec. cor. of secs. 11 and 12 was remonumented by Forrest and Warner in 1944.

The following notes are those of a dependent resurvey of the north, east and west boundaries and subdivisional lines of Township 16 North, Range 21 East, designed to restore the corners in their true original location according to the best available evidence.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 1, 1966.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented by a standard iron post 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is Latitude 34°44'01" N. and Longitude 110°03'53.4" W. as calculated from the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp. Latitude and Longitude was scaled for the cor. of secs. 7, 12, 13 and 18 from U.S.G.S. Quadrangle "Holbrook, Arizona." The mean magnetic declination was found to be 14° East.

Dependent Resurvey of the North Boundary
(Fourth Standard Parallel North)
T. 16 N., R. 21 E., G&SR M., Arizona

Reestablishment of the Survey
Executed by J. L. Harris in 1879

From the standard cor. of Tps. 17 N., Rs. 21 and 22 E., monumented by an iron post, 3 ins. diam., set in a mound of stone, 7 ft. base, to the top, brass cap mkd.

SC
T17N
R21E R22E
S36|S31
1944

Cor. is in E-W fence line.

S. 89°40' W., along the S. bdy. of sec. 36,
T. 17 N., R. 21 E.

Over rolling land, through scattered cedar timber, desc.
W. slope.

19.50 Fence, barbed wire, bears N., S. and E.

Dep. Res. of North Boundary, T. 16 N., R. 21 E.

CHAINS	
21.70	Right bank of Little Colorado River, 20 ft. high, bears N. and S.
23.70	Center of Little Colorado River, course N.
25.70	Left bank of Little Colorado River, 20 ft. high, bears N. and S., asc. E. slope.
39.70	Spur, slopes N., desc. W. slope.
40.20	The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented by a $\frac{3}{4}$ in. rebar in a rock collar, reportedly established by the Arizona State Highway Dept. and locally accepted. I accept this as the best remaining evidence of the original cor. position.
	At the corner point
	Set the iron post, over an "X" chisled on solid rock, in a mound of stone to top, brass cap mkd.
	SC T17N R21E $\frac{1}{4}$ S36 1966
	S. 89°40' W., beginning new measurement.
	Desc. over W. slope.
3.50	Enter nearly level land, moderate sage brush.
15.80	Washboard Wash, 4.00 chs. wide, 20 ft. banks, drains N. 20° E.
25.00	Irrigation ditch, 3 ft. wide, drains W. from the N.
26.10	Fence cor.; fences bear N., S. and W.
40.21	The standard cor. of secs. 35 and 36, monumented by a $1\frac{1}{2}$ in. "T" iron, 20 ins. above the ground, mound of stone to the top, mkd. T17N R21E S35-36, the cor. was established by the Arizona Highway Dept. and is locally accepted. I accept this as the best remaining evidence of the original cor. position.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	SC T17N R21E S35 S36 1966
	from which
	A fence bearing E. and W., bears North 06 lks. dist.
	Raise a mound of stone N. of the cor.
	Deposit the "T" iron alongside the iron post.
	Land, rolling to nearly level. Soil, sandy, clay loam. Timber, widely scattered cedar with salt cedar along river banks. Undergrowth, sage brush and bunch grass.

Dep. Res. of North Boundary, T. 16 N., R. 21 E.

CHAINS	
	<p>S. 89°59' W., along the S. bdy. of sec. 35, T. 17 N., R. 21 E.</p> <p>Over nearly level land along N. edge of open field.</p>
11.50	Telephone line, bears S. 30° E. and N. 30° W.
28.20	Leave nearly level land; asc. over rocky E. slope through moderate timber.
30.50	Fence cor.; fences bear N., E. and W.
40.81	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate distance. There is no remaining evidence of the original corner. This corner is not monumented.
66.00	Leave cedar timber, enter open rolling land.
71.40	Fence cor.; fences bear S. and E.
72.90	Wash, 6 lks. wide, 4 ft. deep, drains NE.
81.62	Point for the standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SC T17N R21E <u>S34 S35</u> 1966</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, nearly level first $\frac{1}{4}$ mile, then rolling. Soil, clay loam. Timber, moderate cedar. Undergrowth, sage brush and bunch grass.</p>
	<p>S. 89°59' W., along the S. bdy. of sec. 34, T. 17 N., R. 21 E.</p> <p>Over gently rolling range land.</p>
11.10	Rocky wash, 60 lks. wide, 10 ft. deep, drains NE.
40.81	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 34 at proportionate distance; there is no remaining evidence of the original cor.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SC T17N R21E $\frac{1}{4}$ <u>34</u> 1966</p> <p>Raise a mound of stone N. of the cor.</p>

Dep. Res. of North Boundary, T. 16 N., R. 21 E.

CHAINS	
51.30	Wash, 6 lks. wide, 1 ft. deep, drains NE.
81.62	<p>Point for the standard cor. of secs. 33 and 34 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SC T17N R21E <u>S33 S34</u> 1966</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
40.81	<p>S. 89°59' W., along the S. bdy. of sec. 33, T. 17 N., R. 21 E.</p> <p>Over rolling range land.</p> <p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original cor. This corner is not monumented.</p>
81.62	<p>Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SC T17N R21E <u>S32 S33</u> 1966</p> <p>from which</p> <p style="padding-left: 40px;">A stock pond, bears S. 30° W., 2.50 chs. dist.</p> <p style="padding-left: 40px;">A fence bearing E. and W., bears South 28 lks. dist.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <p>S. 89°59' W., along the S. bdy. of sec. 32, T. 17 N., R. 21 E.</p> <p>Over rolling land.</p>

Dep. Res. of North Boundary, T. 16 N., R. 21 E.

CHAINS	
40.81	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SC T17N R21E $\frac{1}{4}$ <u>S32</u> 1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing E. and W., bears South 18 lks. dist.</p> <p>Raise a mound of stone N. of the cor.</p>
52.90	<p>Wash, 15 lks. wide, 4 ft. deep, drains N.</p>
53.40	<p>Fence, barbed wire, bears S. $12^{\circ}30'$ E. and N. $12^{\circ}30'$ W.; power line, parallels fence.</p>
57.40	<p>Arizona State Highway No. 77, bears S. $12^{\circ}30'$ E. and N. $12^{\circ}30'$ W.</p>
60.50	<p>Telephone line, bears S. $12^{\circ}30'$ E. and N. $12^{\circ}30'$ W.; fence, parallels telephone line.</p>
81.62	<p>The standard cor. of secs. 31 and 32, monumented by a mound of stone in the cor. of old fence line bearing N. and E. I accept this as the best remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SC T17N R21E <u>S31 S32</u> 1966</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, rolling. Soil, clay loam. No timber; undergrowth, sage brush and bunch grass.</p>

Dep. Res. of North Boundary, T. 16 N., R. 21 E.

CHAINS

S. 89°19' W., along the S. bdy. of sec. 31.
T. 17 N., R. 21 E.

Over rolling land.

12.80 Apache Railroad, bears S. 31° E. and N. 27°25' W.

14.60 Abandoned railroad grade, bears NE. and SW.

39.52 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original cor. This cor. is not monumented.

79.04 Point for the standard cor. of Tps. 17 N., Rs. 20 and 21 E. at proportionate distance; there is no remaining evidence of the original cor.

Set the iron post 20 ins. in the ground, brass cap mkd.

SC
T17N
R20E R21E
S36|S31
1966

Raise a mound of stone N. of the cor.

The south boundary of sections 35 and 36, T. 17 N., R. 20 E., was retraced for control. Corner points were determined by the broken boundary method, based on the plat of Tp. 17 N., R. 20 E., approved November 15, 1921. No intervening corners were found and no corners were remonumented. Calculated bearings and distances are as follows:

- S. 89°10' W., 39.68 to the point for the standard $\frac{1}{4}$ sec. cor. of sec. 36.
- S. 89°04' W., 39.96 to the point for the standard cor. of secs. 35 and 36.
- S. 88°58' W., 39.70 to the point for the standard $\frac{1}{4}$ sec. cor. of sec. 35.
- S. 89°05' W., 40.04 to the standard cor. of secs. 34 and 35, monumented by an iron post, 2 ins. diam., as described in the official record of the 1921 resurvey.

Land, rolling.

Soil, clay loam.

No timber; undergrowth, sage brush and bunch grass.

Dep. Res. of East Boundary, T. 16 N., R. 21 E.

CHAINS

Dependent Resurvey of the East Boundary,
T. 16 N., R. 21 E., G&SR M., Arizona

Reestablishment of the Survey
Executed by H. Meyrick in 1883

Proportions along the East boundary are by the broken boundary method, based on the field note record as executed by H. Meyrick in 1883.

From the cor. of Tps. 15 and 16 N., Rs. 21 and 22 E., monumented by an iron post, 2½ ins. diam., described in the concurrent resurvey notes of T. 15 N., R. 21 E.

N. 0°59' W., bet. secs. 31 and 36.

Over rolling land.

18.70 Wash, 150 lks. wide, 2 ft. deep, drains SW.

22.10 Fence, barbed wire, bears S. 67°18' E. and N. 67°18' W.

40.62 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original corner.

Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.

T16N
R21E R22E
¼
S36|S31
1966

from which

A fence bearing N. and S., bears West, approx. 2.62 chs. dist.

N. 1°19' W., beginning new measurement.

Over rolling land.

30.50 Track road, bears S. 8° E. and N. 8° W.

40.58 Point for the cor. of secs. 25, 30, 31 and 36 at proportionate dist.; there is no remaining evidence of the original corner.

Set the iron post 22 ins. in the ground, brass cap mkd.

T16N
R21E R22E
S25|S30
S36|S31
1966

from which

A fence bearing N. and S., bears West, approx. 2.30 chs. dist.

Dep. Res. of East Boundary, T. 16 N., R. 21 E.

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 1°13' W., bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
13.70	Track road, bears NE. and SW.
40.59	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by a sand stone 20 X 18 X 4 ins., nearly buried, plainly mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R21E R22E $\frac{1}{4}$ S25 S30 1966</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence bearing N. and S., bears West, approx. 1.60 chs. dist.</p> <p>Deposit the original cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°59' W., beginning new measurement.</p> <p>Over rolling land.</p>
10.70	Track road, bears N. 1° E. and S. 1° W.
33.80	Spur, slopes SW.
40.31	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R21E R22E S24 S19 S25 S30 1966</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cement post, 3 ins. diam., bears N. 84°33' E., 5.92 chs. dist.</p> <p style="padding-left: 40px;">A fence bearing N. and S., bears West 120 lks. dist.</p> <p>Raise a mound of stone W. of the cor.</p>

Dep. Res. of East Boundary, T. 16 N., R. 21 E.

CHAINS	
	<p>Land, rolling. Soil, sandy loam. No timber; Undergrowth, sage brush and bunch grass.</p>
<p>9.00 21.06 40.50</p>	<p>N. 1°09' W., bet. secs. 19 and 24. Over rolling land. Wash, 20 lks. wide, 2 ft. deep, drains NE. Fence, barbed wire bears N. 80° E. and S. 80° W. The ¼ sec. cor. of secs. 19 and 24, monumented by an iron post, 1 in. in diam., as described in the official record of the 1944 retracement. The E. bdy. was retraced from this cor. to the ¼ sec. cor. of secs. 1 and 6 and found to be essentially the same as recorded in the official record of the retracement by Forest and Warner in 1944.</p>
<p>.20 9.30 39.06</p>	<p>From the ¼ sec. cor. of secs. 1 and 6 on the E. bdy. of the Tp., monumented by an iron post, 1 in. in diam., as described in the official record of the 1944 retracement. N. 0°13' E., bet. secs. 1 and 6. Over nearly level land. Gulley, 8 ft. wide, 6 ft. deep, drains NW. Washboard Wash, 5.70 chs. wide, with 12 ft. banks, drains W. from S 70° W. Intersect the Fourth Standard Parallel North. Point for the closing cor. of Tps. 16 N., Rs. 21 and 22 E. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R21E S36 S1 S6 R21E R22E T16N CC 1966</p> </div> <p>from which</p> <p>The original closing cor. bears N. 0°13' E., 34 lks. dist., monumented by a sandstone, 20 X 8 X 6 ins., firmly set, mkd. with 6 notches on the E., S. and W. faces. I mark this cor. as an "AM" and bury in place.</p> <p>The standard ¼ sec. cor. of sec. 36, T17N, R21E, bears N. 89°40' E., 8.49 chs. dist.</p> <p>Raise a mound of stone S. of the cor.</p> <p>Land, nearly level. Soil, clay loam. Timber, salt cedar along wash bottom. Undergrowth, sage brush and bunch grass.</p>

Dep. Res., W. Bdy., T. 16 N., R. 21 E.

CHAINS	<p>Dependent Resurvey of the West Boundary Township 16 North, Range 21 East</p>
	<p>Reestablishment of the Survey Executed by H. Meyrick in 1883</p>
	<p>From the cor. of Tps. 15 and 16 N., Rs. 20 and 21 E., monumented by an iron post 2½ ins. diam., described in the concurrent resurvey notes of T. 15 N., R. 21 E.</p>
	<p>N. 0°24' E., bet. secs. 31 and 36.</p>
	<p>Over rolling land.</p>
9.20	<p>Wash, 30 lks. wide, 10 ft. deep, drains N. 60° E.</p>
41.11	<p>The ¼ sec. cor. of secs. 31 and 36, monumented by a sandstone 9 x 6 x 3 ins., lying on top of ground, plainly mkd. ¼.</p>
	<p>At the corner point</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T16N R20E R21E ¼ S36 S31 1966</p>
	<p>Set a railroad tie, 6 x 8 ins. diam., 4 ft. long, along- side the cor. Bury the original cor. by the iron post.</p>
	<p>N. 0°21' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
39.63	<p>Point for the cor. of secs. 25, 30, 31 and 36, at propor- tionate distances; there is no remaining evidence of the original corner.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T16N R20E R21E S25 S30 S36 S31 1966</p>
	<p>Set a cedar post alongside and raise a mound of stone W. of the cor.</p>
	<p>Land, rolling. Soil, clay loam. No timber; Undergrowth, sage brush and bunch grass.</p>
	<p>N. 0°21' W., bet. secs. 25 and 30.</p>
	<p>Over gently rolling land.</p>
24.60	<p>Track road, bears S. 60° E. and N. 60° W.</p>

Dep. Res., W. Bdy., T. 16 N., R. 21 E.

CHAINS	
<p>39.63</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R20E R21E $\frac{1}{4}$ S25 S30 1966</p> <p>Set a cedar post alongside the cor.</p>
<p>79.26</p>	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R20E R21E S24 S19 S25 S30 1966</p> <p>Set a cedar post alongside the cor.</p> <p>Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>N. 0°21' W., bet. secs. 19 and 24.</p> <p>Over rolling land.</p> <p>37.00 Wash area, 1.00 ch. wide, 1 ft. deep, drains SE.</p> <p>39.63 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R20E R21E $\frac{1}{4}$ S24 S19 1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing N. and S., bears East, 56 lks. dist.</p> <p>Deposit glass and set a squared cedar post, 4 x 8 ins. diam., 8 ft. long, alongside the cor.</p> <p>78.53 Fence, barbed wire bears E. and W., and cor. of fences extending N., S. and W., bears East .46 lks. dist.</p> <p>79.26 Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distances; there is no remaining evidence of the original corner.</p>

Dep. Res., W. Bdy., T. 16 N., R. 21 E.

CHAINS

Set the iron post 22 ins. in the ground, brass cap mkd.

T16N
R20E R21E
S13|S18
S24|S19
1966

from which

A cor. of fences bearing N., S. and W. bears
S. 30° E., .83 lks. dist.

Deposit glass and set a squared cedar post, 4 x 8 ins.
diam., 4 ft. long, alongside the cor.

Land, rolling.
Soil, clay loam.
Timber, none.
Undergrowth, sage brush and bunch grass.

N. 0°21' W., bet. secs. 13 and 18.

Over rolling land.

39.63 Point for the ¼ sec. cor. of secs. 13 and 18, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set the iron post 24 ins. in the ground, brass cap mkd.

T16N
R20E R21E
¼
S13|S18
1966

79.26 The cor. of secs. 7, 12, 13 and 18, monumented by a sqd.
wooden post, 18 ins. long, mkd. VII, XII, XIII, XVIII and
4 notches on S. and 2 notches on N. faces.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T16N
R20E R21E
S12|S7
S13|S18
1966

Set a cedar post, 8 ins. diam., 4 ft. long, alongside the
cor. Bury the original cor. alongside the iron post.

Cor. is in a N-S fence line.

Land, rolling.
Soil, clay loam.
Timber, none.
Undergrowth, sage brush and bunch grass.

N. 1°04' W., bet. secs. 7 and 12.

Over rolling land.

CHAINS	
40.00	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented by a cedar post, 3 ins. diam., 3 ft. long, dimly mkd. lying loose on ground.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R20E R21E $\frac{1}{4}$ S12 S7 1966</p> <p>Set a sqd. cedar post, 3 ft. long, alongside the cor. Set the original cor. alongside the iron post. Cor. is in a N-S fence.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 1°27' E., beginning new measurement.</p> <p>Over rolling land.</p>
41.70	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R20E R21E <u>S1 S6</u> S12 S7 1966</p> <p>Set a cedar post, 4 ins. diam., 4 ft. long, alongside and raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
41.70	<p>N. 1°27' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R20E R21E $\frac{1}{4}$ S1 S6 1966</p> <p>Set a cedar post, 3 ins. diam., 3 ft. long, alongside and raise a mound of stone W. of the cor.</p>
83.66	<p>Intersect the 4th Standard Parallel North.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS

Point for the closing cor. of Tps. 16 N., Rs. 20 and 21 E. at proportionate distance; there is no remaining evidence of the original corner.

Set the iron post 22 ins. in the ground, brass cap mkd.

T17N R20E
 S36
 S1|S6
 R20E R21E
 T16N
 CC
 1966

from which

The standard cor. of Tps. 17 N., Rs. 20 and 21 E. bears N. 89°10' E., 12.75 chs. dist.

Raise a mound of stone S. of the cor.

Land, rolling.
 Soil, clay loam.
 Timber, none.
 Undergrowth, sage brush and bunch grass.

Dependent Resurvey of the Subdivisional Lines
 Township 16 North, Range 21 East

Reestablishment of the Survey Executed
 by H. Meyrick in 1883

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.

N. 1°19' W., bet. secs. 35 and 36.

Over rolling land.

- 5.30 Wash, 15 lks. wide, 3 ft. deep, drains E.
- 14.90 Wash, 40 lks. wide, 5 ft. deep, drains S. 85° E.
- 40.56 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36 at proportionate distance; there is no remaining evidence of the original corner.

Set the iron post 23 ins. in the ground, brass cap mkd.

T16N R21E
 $\frac{1}{4}$
 S35|S36
 1966

Set a cedar post, 3 ins. diam., alongside the cor.

- 81.12 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{S26}{S35} \frac{S25}{S36}$ 1966</p> <p>Set a cedar post, 3 ins. diam., alongside the cor.</p> <p>Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp. S. 89°57' W., bet. secs. 25 and 36.</p> <p>Over nearly level land.</p>
1.10	Track road, bears N. and S.
2.30	Fence, barbed wire, bears N. and S.
39.62	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4} \frac{S25}{S36}$ 1966</p>
79.24	<p>Deposit glass in hole alongside the cor.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 1°26' W., bet. secs. 25 and 26.</p> <p>Over gently rolling land.</p>
11.90	Ridge of small hills, bears N. 80° E. and W.
40.56	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
45.60	Wash, 20 lks. wide, 3 ft. deep, drains NE.
80.46	Fence, barbed wire, bears S. 89°29' E. and N. 89°29' W.
81.12	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp.
	N. 89°51' W., bet. secs. 24 and 25.
	Over nearly level land.
1.20	Fence, barbed wire, bears N, and S.
39.84	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.68	The point for the cor. of secs. 23, 24, 25 and 26.
	Land, nearly level.
	Soil, clay loam.
	Timber, none.
	Undergrowth, sage brush and bunch grass.
	N. 1°42' W., bet. secs. 23 and 24.
	Over gently rolling land.
40.56	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	from which
	A dirt dam on E. end of 2 stock ponds, bears
	N. 0°58' E., 14.20 chs. dist.
55.70	Wash, 5 lks. wide, 2 ft. deep, drains NE.
74.80	Wash, 3 lks. wide, 1 ft. deep, drains S. 70° E.
81.12	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	Land, gently rolling.
	Soil, clay loam.
	Timber, none.
	Undergrowth, sage brush and bunch grass.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy., an iron post, set, mkd. and witnessed as described in the retracement of 1944.
	N. 89°49' W., bet. secs. 13 and 24.
	Over nearly level land.
.01	Fence, barbed wire, bears N. and S.
8.70	Spur, slopes S. 10° W.
17.60	Wash, 10 lks. wide, 3 ft. deep, drains S. 5° W.
40.08	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>from which</p> <p>A dry stock pond, bears N. 34°45' E., 4.50 chs. dist.</p>
80.16	<p>The point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Land, nearly level. Soil, gravelly clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 0°38' W., bet. secs. 13 and 14.</p> <p>Over gently rolling land.</p>
33.70	Track road, bears SE. and NW.
38.50	Fence, barbed wire, bears E. and W.
40.55	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
58.56	Telephone line, bears S. 88°44' E. and N. 88°44' W.
61.23	Highway, black top, Woodruff Road, bears S. 88°44' E. and N. 88°44' W.
64.23	Electric Line, bears S. 88°44' E. and N. 88°44' W.
81.10	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the retracement of 1944.</p> <p>N. 89°49' W., bet. secs. 12 and 13.</p> <p>Over nearly level land.</p>
0.16	Fence, barbed wire, bears S. 1°40' E. and N. 1°40' W.
3.60	Wash, 10 lks. wide, 3 ft. deep, drains SW.
32.60	Track road, bears NE. and SW.
39.80	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	<p>from which</p> <p>A stock pond, bears S. 77°0' E., 29.94 chs. dist.</p>
79.60	The point for the cor. of secs. 11, 12, 13 and 14.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 0°18' W., bet. secs. 11 and 12.</p> <p>Over gently rolling land.</p>
7.60	Enter scattered cedar timber.
11.60	Wash, 10 lks. wide, 1 ft. deep, drains N. 4° W.
20.40	Wash, 15 lks. wide, 3 ft. deep, drains N. 30° E.
24.80	Wash, 70 lks. wide, 12 ft. deep, drains NW.
27.35	S. rim of Washboard Wash, bears E. and W., desc. steep N. slope.
29.15	Washboard Wash, 50 lks. wide, drains E. approx. 2 chs., thence N.; asc. steep S. slope.
31.15	N. rim of Washboard Wash, bears E. and W., thence over gently rolling land.
38.40	Wash, 20 lks. wide, 2 ft. deep, drains S. 60° E.
39.20	Fence, barbed wire, bears S. 55° E. and N. 55° W.
40.55	The ¼ sec. cor. of secs. 11 and 12, monumented by an iron post, 1 in. in diam., set in a mound of stone (5 ft. diam., 3 ft. high) to the top, brass cap mkd.
	<p>GL ¼ S11 S12 1944</p>
	<hr style="width: 20%; margin: auto;"/>
	<p>N. 2°08' W., beginning new measurement.</p> <p>Over rolling land.</p>
5.00	Leave scattered cedar timber.
5.30	Head of wash, drains SE.
30.00	Wash, 7 lks. wide, 2 ft. deep, drains E.
40.24	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 12 ins. in the ground in a mound of stone to top, brass cap mkd.</p>
	<p>T16N R21E S2 S1 S11 S12 1966</p>
	<p>Land, gently rolling to rolling. Soil, clay loam. Timber, none, except for strip of scattered cedar. Undergrowth, sage brush and bunch grass.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the retracement of 1944.</p> <p>S. 89°52' W., bet. secs. 1 and 12.</p> <p>Over rolling land through scattered cedar timber.</p>
29.30	Power line, bears S. 20° E. and N. 20° W.
40.03	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
43.40	E. rim of Washboard Wash, bears SE. and NW.; desc. steep W. slope.
45.60	Washboard Wash, 50 lks. wide, drains NW.
47.37	W. rim of Washboard Wash, bears SE. and N. 30° W., thence over rolling open land.
66.50	Round knoll.
74.40	Spur, slopes N.
80.06	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, clay loam and rocky. Timber, scattered cedar first half mile. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 4°49' E., bet. secs. 1 and 2.</p> <p>Over gently rolling land.</p>
19.20	Track road, bears N. 65° E. and S. 65° W.
40.35	<p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E ¼ S2 S1 1966</p>
46.50	<p>Set a sqd. cedar post, 4 ft. long, alongside the cor.</p> <p>Track road bears E. and W., enter scattered cedar timber.</p>
59.00	Wash, 20 lks. wide, 3 ft. deep, drains NE.
80.30	<p>Intersect the 4th Standard Parallel North.</p> <p>Point for the closing cor. of secs. 1 and 2, on the N. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Set the iron post 4 ins. in the ground in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17N R21E $\frac{S}{S2} \frac{35}{S1}$ C C T16N R21E 1966</p> <p>from which</p> <p style="padding-left: 40px;">An E-W fence bears N., 2 lks. dist.</p> <p style="padding-left: 40px;">The point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, bears S. 89°59' W., 43 lks. dist.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none to scattered cedar last half mile. Undergrowth, sage brush and bunch grass.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.</p> <p>N. 1°16' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land.</p>
4.20	<p>Wash, 5 lks. wide, 2 ft. deep, drains E.</p>
40.49	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S34}{S34} \frac{S35}{S35}$ 1966</p>
	<p>Set a cedar post, 3 ins. diam., 3 ft. long, alongside the cor.</p>
80.98	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{S27}{S27} \frac{S26}{S26}$ $\frac{S34}{S34} \frac{S35}{S35}$ 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS					
<p>10.60</p> <p>13.90</p> <p>16.20</p> <p>39.49</p> <p>78.98</p>	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°53' W., bet. secs. 26 and 35.</p> <p>Over nearly level land.</p> <p>Bottom of ridge, asc. E. slope.</p> <p>Top of ridge, bears N. 10° E. and S. 10° W.; desc. W. slope.</p> <p>Bottom of ridge, thence over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>				
<p>40.49</p> <p>80.98</p>	<p>N. 1°26' W., bet. secs. 26 and 27.</p> <p>Over nearly level land.</p> <p>Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 23 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R21E</p> <table border="1" style="margin: auto;"> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> </table> <p>1966</p> </div> <p>from which</p> <p style="padding-left: 40px;">An E-W fence bears S., 1.26 chs. dist.</p> <p>Set a cedar post, 4 ins. diam., 4 ft. long, alongside the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>	S22	S23	S27	S26
S22	S23				
S27	S26				
<p>39.48</p>	<p>From the point for the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°48' W., bet. secs. 23 and 26.</p> <p>Over nearly level land.</p> <p>Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>				

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

<p>CHAINS 78.96</p>	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
<p>40.51</p>	<p>N. 2°24' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S22 S23 1966</p> <p>Deposit glass in the hole.</p>
<p>81.02</p>	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E S15 S14 S22 S23 1966</p> <p>Deposit glass in the hole.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
<p>39.95</p>	<p>From the point for the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°42' W., bet. secs. 14 and 23.</p> <p>Over nearly level land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
<p>79.90</p>	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 0°31' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
37.95	Fence, bears E. and bears W. 8 lks. dist. to a cor. of fences bearing E., W. and N. 6° E.
40.48	Point for the ¼ sec. cor. of secs. 14 and 15 at proportionate dist.; there is no remaining evidence of the original corner. This corner is not monumented.
47.50	Washboard Wash, 2.70 chs. wide, 5 ft. deep, drains NE.
73.00	Telephone line, bears S. 75°30' E. and N. 75°30' W.
76.40	Fence, bears W. and bears E. 3.47 chs. dist. to a cor. of fences bearing W. and S. 6° W.
78.63	Black top road, to Woodruff, bears S. 65°48' E. and N. 65°48' W.
79.57	Power line, bears S. 75°30' E. and N. 75°30' W.
80.96	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T16N R21E <u>S10</u> <u>S11</u> <u>S15</u> <u>S14</u> 1966</p>
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>From the point for the cor. of secs. 11, 12, 13 and 14. S. 89°36' W., bet. secs. 11 and 14.</p>
	<p>Over gently rolling land.</p>
19.90	Wash, 50 lks. wide, 2 ft. deep, drains irreg. S.
39.89	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
71.90	Washboard Wash, 150 lks. wide, 2 ft. deep, drains irreg. N.
79.78	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, grama and bunch grass.</p>
	<p>N. 1°08' W., bet. secs. 10 and 11. Over gently rolling land.</p>
4.00	Wash, 5 lks. wide, 1 ft. deep, drains E.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS		
11.86	Bladed road, bears N. 40° E. and S. 40° W.	
13.10	Wash, 10 lks. wide, 1 ft. deep, drains SE.	
23.80	Track road, bears SE. and NW.	
34.90	Wash, 20 lks. wide, 2 ft. deep, drains SE.	
40.49	<p>Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 3 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T16N R21E ¼ S10 S11 1966</p>	
75.90	Wash, 7 lks. wide, 1 ft. deep, drains N. 80° E.	
80.98	<p>Point for the cor. of secs. 2, 3, 10 and 11 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post, 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E S3 S2 S10 S11 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>	
	From the cor. of secs. 1, 2, 11 and 12.	
	S. 89°48' W., bet. secs. 2 and 11.	
	Over nearly level land.	
24.50	Bladed road, bears N. 50° E. and SW.	
39.89	<p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 8 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T16N R21E ¼ S2 S11 1966</p>	
44.95	Fence, barbed wire, bears SE. and NW.	
60.40	Track road, bears S. 15° E. and N. 15° W.	
79.78	The cor. of secs. 2, 3, 10 and 11.	

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>N. 3°11' E., bet. secs. 2 and 3. Over rolling land.</p>
37.30	Fence, barbed wire, bears S. 32°07' E. and N. 32°07' W.
40.54	<p>Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground, brass cap mkd. T16N R21E ¼ S3 S2 1966</p> <p>Raise a mound of stone W. of the cor.</p>
50.10	Track road, bears SE. and NW.
76.70	Fence, barbed wire, bears E. and W.
80.34	<p>Intersect the 4th Standard Parallel North. Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground in a mound of stone to top, brass cap mkd. T17N R21E S34 S3 S2 T16N R21E CC 1966</p> <p>from which</p> <p> The standard ¼ sec. cor. of sec. 34, bears S. 89°59' W., 10 lks. dist.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>Point for the ¼ sec. cor. of sec. 2 is at midpoint and on the N. bdy. of the Tp. Set the iron post 22 ins. in the ground, brass cap mkd. ¼ S2 T16N R21E 1966</p> <p>from which</p> <p> The standard cor. of secs. 34 and 35 bears S. 89°59' W., 26 lks. dist.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Raise a mound of stone S. of the cor.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 1°06' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
5.49	Arizona State Highway No. 77 bears S. 12°30' E. and N. 12°30' W.
20.40	Power line, bears S. 12°30' E. and N. 12°30' W.
20.70	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.
24.60	Wash, 5 lks. wide, 3 ft. deep, drains N. 75° E.
40.47	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 21 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S33 S34 1966</p>
	<p>Set a cedar post, 4 ins. diam., 3 ft. long, alongside the cor.</p>
50.40	Wash, 5 lks. wide, 1 ft. deep, drains E.
80.94	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distances; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E S28 S27 S33 S34 1966</p>
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°55' W., bet. secs. 27 and 34.</p> <p>Over nearly level land.</p>
30.00	Track road, bears NE. and SW.
39.40	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
78.80	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ <u>S27</u> S34 1966</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the cor.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
40.48	<p>N. 1°40' W., bet. secs. 27 and 28.</p> <p>Over gently rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ <u>S28</u> <u>S27</u> 1966</p>
80.96	<p>Set a cedar post, 4 ins. diam., 3 ft. long, alongside the cor.</p> <p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E <u>S21</u> <u>S22</u> <u>S28</u> <u>S27</u> 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
39.55	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°55' W., bet. secs. 22 and 27.</p> <p>Over nearly level land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27 at proportionate distance; there is no remaining evidence of the original corner.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
79.10	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S22}{S27}$ 1966</p> <p>Set a cedar post 4 ins. diam., 3 ft. long, alongside the cor.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
40.52	<p>N. 3°06' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p>
81.04	<p>Set the iron post 8 ins. in the ground in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $S21 S22$ 1966</p> <p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p>
26.90	<p>Set the iron post 21 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{S16 S15}{S21 S22}$ 1966</p> <p>from which</p> <p style="text-align: center;">A windmill bears N. 68°12' W., 12.50 chs. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
26.90	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°55' W., bet. secs. 15 and 22.</p> <p>Wash, 50 lks. wide, 3 ft. deep, drains S. 40° E.</p>
40.02	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Set the iron post 21 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S15}{S22}$ 1966</p> <p>Deposit glass in the hole.</p>
54.60	Low ridge, bears N. and S.
80.04	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 0°08' W., bet. secs. 15 and 16.</p> <p>Over gently rolling land.</p>
.20	Desc. into wash area.
5.10	Washboard Wash, 35 lks. wide, 8 ft. deep, drains NE.
10.70	Leave wash area; asc. slight S. slope.
25.70	Wash, 4 lks. wide, 1 ft. deep, drains E.
40.46	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S16 S15 1966</p> <p>Deposit glass in hole.</p>
50.70	Wash, 40 lks. wide, 5 ft. deep, drains E.
75.20	Fence, barbed wire, bears E. and W.
80.92	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T16N R21E S9 S10 S16 S15 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°52' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land.</p>
5.50	Power line, bears S. 75°30' E. and N. 75°30' W.
5.70	Black top road, to Woodruff, bears S. 65°48' E. and N. 65°48' W.
31.50	Telephone line, bears S. 75°30' E. and N. 75°30' W.
39.76	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S10}{S15}$ 1966</p> <p>from which</p> <p style="padding-left: 40px;">A stock pond bears S. 88°52' W., 19.25 chs. dist.</p> <p style="padding-left: 40px;">An E-W fence bears S., approx. 8 chs. dist.</p> <p>Raise a mound of stone N. of the cor.</p>
55.60	Wash, 40 lks. wide, 2 ft. deep, drains irreg. SE.
69.35	Track road, bears SE, and NW.
79.52	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, grama and bunch grass.</p>
	<p>N. 1°00' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p>
9.50	Telephone line, bears S. 75°29' E. and N. 75°29' W.
18.20	Black top road, to Woodruff, bears S. 81°09' E. and N. 81°09' W.
18.90	Electric line, bears S. 75°29' E. and N. 75°29' W.
40.47	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S9 S10 1966</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	Raise a mound of stone W. of the cor.
47.00	Wash, 10 lks. wide, 3 ft. deep, drains S. 75° E.
80.94	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 23 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T16N R21E $\frac{S4}{S9} \frac{S3}{S10}$ 1966</p>
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	From the cor. of secs. 2, 3, 10 and 11.
	S. 89°50' W., bet. secs. 3 and 10.
	Over nearly level land.
13.50	Ridge, bears N. 10° E. and S.
39.67	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T16N R21E $\frac{1}{4} \frac{S3}{S10}$ 1966</p>
	Raise a mound of stone N. of the cor.
79.34	The cor. of secs. 3, 4, 9 and 10.
	<p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	N. 1°39' E., bet. secs. 3 and 4.
	Over rolling land.
9.10	Asc. SW. slope.
11.30	Top of hill, over rolling land.
24.70	Desc. N. slope.
40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	Set the iron post 23 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T16N R21E</p>
	<p style="text-align: center;">$\frac{1}{4}$</p>
	<p style="text-align: center;">S4 S3</p>
	<p style="text-align: center;">1966</p>
	Raise a mound of stone W. of the cor.
51.30	Top of small hill.
71.00	Top of small hill.
80.13	Fence, barbed wire, bears E. and W.
80.51	Intersect the 4th Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T17N R21E</p>
	<p style="text-align: center;">S33</p>
	<p style="text-align: center;">S4 S3</p>
	<p style="text-align: center;">C C</p>
	<p style="text-align: center;">T16N R21E</p>
	<p style="text-align: center;">1966</p>
	from which
	<p style="text-align: center;">The point for the standard $\frac{1}{4}$ sec cor. of sec. 33, bears S. 89°59' W., 18 lks. dist.</p>
	Raise a mound of stone S. of the cor.
	Land, rolling.
	Soil, clay loam.
	Timber, none.
	Undergrowth, sage brush and bunch grass.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
	N. 1°25' W., bet. secs. 32 and 33.
	Over gently rolling land.
2.25	Fence, barbed wire, bears N. 89°20' E. and S. 89°20' W.
40.42	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T16N R21E</p>
	<p style="text-align: center;">$\frac{1}{4}$</p>
	<p style="text-align: center;">S32 S33</p>
	<p style="text-align: center;">1966</p>
	Set a cedar post, 3 ft. long, alongside the cor.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
80.84	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{S29}{S32} \frac{S28}{S33}$ 1966</p> <p>Set a cedar post, 4 ft. long, alongside the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
11.90	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°57' W., bet. secs. 28 and 33.</p> <p>Over nearly level land.</p>
12.00	<p>Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.</p>
15.14	<p>Power line, bears S. 12°30' E. and N. 12°30' W.</p>
18.10	<p>Arizona State Highway No. 77, bears S. 12°30' E. and N. 12°30' W.</p>
18.15	<p>Telephone line, bears S. 12°30' E. and N. 12°30' W.</p>
18.15	<p>Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.</p>
39.72	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4} \frac{S28}{S33}$ 1966</p> <p>Raise a mound of stone N. of the cor.</p>
79.44	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 1°39' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p>
2.14	<p>Fence, bears E. and bears W., 3.46 lks. dist. to a cor. of fences bearing N., S. and W.</p>
39.30	<p>Wash, 5 lks. wide, 2 ft. deep, drains N. 30° E.</p>
40.42	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Set the iron post, 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S29 S28 1966</p> <p>Set a cedar post, 3 ins. diam., 3 ft. long, alongside and raise a mound of stone W. of the cor.</p>
54.80	Low ridge, bears S. 80° E. and N. 80° W.
58.30	Washboard Wash, 30 lks. wide, 3 ft. deep, drains N. 75° E.
80.84	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E S20 S21 S29 S28 1966</p> <p>from which</p> <p style="text-align: center;">A fence cor., with fences bearing N., E. and W., bears N. 81°10' W., 3.10 chs. dist.</p> <p>Deposit glass in the hole, set a cedar post, 5 ft. long, alongside and raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°51' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p>
27.54	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.
27.64	Electric line, bears S. 12°30' E. and N. 12°30' W.
30.64	Arizona State Highway No. 77, bears S. 12°30' E. and N. 12°30' W.
33.64	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.; Telephone line, bears S. 12°30' E. and N. 12°30' W.
39.70	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S21 S28 1966</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	Raise a mound of stone N. of the cor.
70.70	Wash, 40 lks. wide, 6 ft. deep, drains irreg. NE.
79.40	The cor. of secs. 20, 21, 28 and 29.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.
	N. 3°52' W., bet. secs. 20 and 21.
	Over gently rolling land.
.43	Fence, barbed wire, bears E. and W.
11.10	Wash, 5 lks. wide, 2 ft. deep, drains E.
32.20	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° E.
40.50	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 19 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T16N R21E $\frac{1}{4}$ S20 S21 1966</p>
	from which
	A N-S fence bears West 46 lks. dist.
50.10	Fence, barbed wire, bears N. and S.
50.80	Track road, bears N. 85° E. and S. 85° W.
73.63	Wash area, 3 chs. wide, drains E.
81.00	The cor. of secs. 16, 17, 20 and 21, monumented by a sandstone 17 x 16 x 5 ins., dimly mkd., and in a mound of stones.
	At the corner point
	Set the iron post, 15 ins. in the ground, in a mound of stones to top, brass cap mkd.
	<p style="text-align: center;">T16N R21E S17 S16 S20 S21 1966</p>
	Deposit the original cor. stone alongside the iron post. Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.
	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°28' W., bet. secs. 16 and 21.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	Over gently rolling land.
6.60	Washboard Wash, 120 lks. wide, 5 ft. deep, drains N. 40° E.
40.25	The ¼ sec. cor. of secs. 16 and 21, monumented by a sandstone 20 x 6 x 3 ins. set in a mound of stone, mkd. ¼ on N. face.
	At the corner point
	Set the iron post 8 ins. in the ground, in a mound of stone to top, brass cap mkd.
	T16N R21E ¼ $\frac{S16}{S21}$ 1966
	Deposit the original cor. stone alongside the iron post.
	N. 89°55' W., beginning new measurement.
	Over gently rolling land.
.74	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.
.79	Power line, bears S. 12°30' E. and N. 12°30' W.
3.83	Arizona State Highway No. 77, bears S. 12°30' E. and N. 12°30' W.
6.88	Telephone line, bears S. 12°30' E. and N. 12°30' W.
6.93	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.
38.00	Fence, barbed wire, bears N. and S.
40.20	The cor. of secs. 16, 17, 20 and 21.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.
	N. 0°23' E., bet. secs. 16 and 17.
	Over gently rolling land.
40.42	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 21 ins. in the ground, brass cap mkd.
	T16N R21E ¼ S17 S16 1966
	from which
	A stock pond bears S. 3° W., 18.00 chs. dist.
	A N-S fence bears E., 1.85 chs. dist.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	Deposit glass in hole.
60.74	Wash, 4 lks. wide, 2 ft. deep, drains N. 75° E.
72.96	Track road, bears N. 71°40' E. and S. 71°40' W.
80.84	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T16N R21E S8 S9 S17 S16 1966
	from which
	A cor. of fences bearing E. and S., bears S. 50°50' E., 1.60 chs. dist.
	Set a cedar post alongside and raise a mound of stone W. of the cor.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 89°43' W., bet. secs. 9 and 16.
	Over nearly level land.
29.50	Wash, 20 lks. wide, 3 ft. deep, drains irreg. SE.
39.84	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post, 22 ins. in the ground, brass cap mkd.
	T16N R21E ¼ S9 S16 1966
	Raise a mound of stone N. of the cor.
58.70	Power line, bears S. 12°30' E. and N. 12°30' W.
61.10	Fence, bears S. 12°30' E. and N. 12°30' W.
61.80	Arizona State Highway No. 77, bears S. 12°30' E. and N. 12°30' W.
65.10	Telephone line and fence bears S. 12°30' E. and N. 12°30' W.
68.10	Wash, 20 lks. wide, 2 ft. deep, drains irreg. SE.
79.68	The cor. of secs. 8, 9, 16 and 17.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	<p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>N. 0°54' W., bet. secs. 8 and 9. Over gently rolling land.</p>
40.42	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 24 ins. in the ground, brass cap mkd. T16N R21E $\frac{1}{4}$ S8 S9 1966</p>
57.40	<p>Raise a mound of stone W. of the cor. Track road, bears E. and W.</p>
62.40	<p>Track road, bears S. 30° E. and N. 30° W.</p>
71.92	<p>Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.</p>
72.12	<p>Telephone line, bears S. 12°30' E. and N. 12°30' W.</p>
80.84	<p>Point for the cor. of secs. 4, 5, 8 and 9 at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground, brass cap mkd. T16N R21E S5 S4 S8 S9 1966</p>
	<p>Deposit glass in hole and raise a mound of stone W. of the cor. Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
39.76	<p>From the cor. of secs. 3, 4, 9 and 10. S. 89°34' W., bet. secs. 4 and 9. Over nearly level land. Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9 at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, brass cap mkd. T16N R21E $\frac{1}{4}$ S4 S9 1966</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	Raise a mound of stone N. of the cor.
74.86	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.
74.93	Power line, bears S. 12°30' E. and N. 12°30' W.
78.18	Arizona State Highway No. 77, bears S. 12°30' E. and N. 12°30' W.
79.52	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass
	N. 0°03' E., bet. secs. 4 and 5.
	Over gently rolling land.
6.19	Arizona State Highway No. 77, bears S. 12°30' E. and N. 12°30' W.
20.36	Power line, bears S. 12°30' E. and N. 12°30' W.
20.60	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.
33.20	Track road, bears E. and W.
33.40	Wash, 3 lks. wide, 1 ft. deep, drains N. 15° W.
40.42	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 12 ins. in the ground, in a mound of stone to top, brass cap mkd.
	T16N R21E 1/4 S5 S4 1966
61.20	Wash, 5 lks. wide, 3 ft. deep, drains W.
80.76	Fence, barbed wire, bears E. and W.
80.94	Intersect the 4th Standard Parallel North.
	Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T17N R21E S32 S5 S4 T16N R21E C C 1966
	from which
	The standard 1/4 sec. cor. of sec. 32 bears S. 89°59' W., 11 lks. dist.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Raise a mound of stone S. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 4 is at midpoint and on the N. bdy of the Tp.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S4 T16N R21E 1966 </p> <p>from which</p> <p style="text-align: center;">The standard cor. of secs. 32 and 33, T. 17 N., R. 21 E., bears S. 89°59' W., 15 lks. dist.</p> <p>Deposit glass in the hole.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp.</p> <p>N. 1°21' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p>
1.90	Track road, bears E. and W.
2.05	Fence, barbed wire, bears E. and W.
40.43	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T16N R21E $\frac{1}{4}$ S31 S32 1966 </p>
48.00	S. edge of eroded flat lands.
56.83	Old fence, bears N. 5° E. and S. 5° W.
74.60	Old fence, bears S. 89° E. and N. 89° W.
80.86	<p>Point for the cor. of secs. 29, 30, 31 and 32 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T16N R21E S30 S29 S31 S32 1966 </p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
39.48	<p>From the cor. of secs. 28, 29, 32 and 33. N. 89°57' W., bet. secs. 29 and 32. Over gently rolling land. Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E ¼ <u>S29</u> S32 1966</p>
43.44	<p>Raise a mound of stone N. of the cor.</p>
44.04	<p>Fence, bears N. and S.</p>
44.04	<p>Track road, bears N. and S.</p>
63.30	<p>Apache Railroad, bears SE. and NW.</p>
71.14	<p>Wash, 20 lks. wide, 5 ft. deep, drains irreg. SW.</p>
78.96	<p>The cor. of secs. 29, 30, 31 and 32.</p>
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
	<p>S. 89°50' W., bet. secs. 30 and 31.</p>
	<p>Over gently rolling land.</p>
7.20	<p>Washboard Wash, 40 lks. wide, 6 ft. deep, drains N.-NE.</p>
31.50	<p>Wash, 30 lks. wide, 4 ft. deep, drains S.-SE.</p>
39.53	<p>Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E ¼ <u>S30</u> S31 1966</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS		
63.06	<p>from which</p> <p>A windmill bears S. 77°15' E., 16.00 chs. dist.</p> <p>A dyke bears S. 88°47' E., 17.00 chs. dist.</p> <p>Set a cedar post, 3 ft. long, alongside and raise a mound of stone N. of the cor.</p> <p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>	
0.60	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 2°05' W., bet. secs. 29 and 30.</p> <p>Old fence line bears W. and E., 2.34 lks. dist. to an old cor. of fences bearing N-S-E and W.</p>	
2.40	Wash, 10 lks. wide, 3 ft. deep, drains N. 60° E.	
7.30	Washboard Wash, 70 lks. wide, 6 ft. deep, drains NE.	
10.00	Wash, 10 lks. wide, 3 ft. deep, drains E.	
14.10	Wash, 90 lks. wide, 3 ft. deep, drains SE.	
15.45	Apache Railroad, bears S. 48°15' E. and N. 48°15' W.	
40.44	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S30 S29 1966</p> <p>Set a cedar post 5 ins. diam., 3 ft. long, alongside and raise a mound of stone W. of the cor.</p>	
65.00	Wash, 5 lks. wide, 2 ft. deep, drains S. 50° E.	
80.88	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T16N R21E S19 S20 S30 S29 1966</p>	

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
39.74	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29. S. 89°59' W., bet. secs. 20 and 29. Over nearly level land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 15 ins. in the ground in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S20}{S29}$ 1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing E. and W., bears N., 84 lks. dist.</p>
44.70	Fence, bears N. and S.
45.40	Track road, bears N. and S.
74.40	Old fence line, bears N. and S.
79.48	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
15.50	<p>S. 88°20' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land.</p> <p>Apache Railroad, bears N. 40°17' E. and S. 40°17' W.</p>
39.64	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S19}{S30}$ 1966</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing E. and W., bears N. 2.67 chs. dist.</p>
60.78	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp.

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30. N. 2°31' W., bet. secs. 19 and 20. Over nearly level land.</p> <p>1.16 Fence, barbed wire, bears S. 89°30' E. and N. 89°30' W.</p> <p>22.70 Wash, 5 lks. wide, 2 ft. deep, drains E.</p> <p>22.05 Apache Railroad, bears N. 22°50' E. and S. 22°50' W.</p> <p>40.45 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S19 S20 1966</p> <p>Deposit glass in the hole.</p> <p>63.50 Track road, bears N. 75° E. and S. 75° W.</p> <p>80.90 Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E S18 S17 S19 S20 1966</p> <p>Deposit glass in the hole.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21. N. 89°58' W., bet. secs. 17 and 20. Over nearly level land.</p> <p>38.79 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
<p>40.33</p> <p>50.70</p> <p>77.58</p>	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S17}{S20}$ 1966</p> <p>Deposit glass in the hole.</p> <p>Old road, bears N. and S.</p> <p>Apache Railroad, bears N. 22°30' E. and S. 22°30' W.</p> <p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
<p>26.50</p> <p>38.82</p> <p>57.20</p> <p>57.82</p>	<p>S. 86°36' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p> <p>Ridge, bears N. and S.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S18}{S19}$ 1966</p> <p>Deposit glass in the hole.</p> <p>Fence, barbed wire, bears N. and S.</p> <p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>
<p>10.50</p> <p>16.30</p> <p>20.40</p>	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 1°04' W., bet. secs. 17 and 18.</p> <p>Over nearly level land.</p> <p>Wash, 15 lks. wide, 3 ft. deep, drains E.</p> <p>Wash, 5 lks. wide, 2 ft. deep, drains E.</p> <p>Wash, 10 lks. wide, 5 ft. deep, drains S. 85° E.</p>

Dep. Res., Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS		
40.42	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 23 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S18 S17 1966</p> <p>Deposit glass in the hole.</p>	
80.84	<p>Point for the cor. of secs. 7, 8, 17 and 18 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21 E S7 S8 S18 S17 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, nearly level. Soil, clay loam, traces of lime. Timber, none. Undergrowth, sage brush and bunch grass.</p>	
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°57' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land.</p>	
16.76	<p>Apache Railroad, bears N. 22°30' E. and S. 22°30' W.</p>	
39.82	<p>Point for the $\frac{1}{4}$ cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ S8 S17 1966</p> <p>Set a sqd. post, 3 ins. diam., 3 ft. long, alongside and raise a mound of stone N. of the cor.</p>	
41.10	<p>Old road, bears N. and S.</p>	
79.64	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>	

Dep. Res., Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
40.01	<p>S. 85°05' W., bet. secs. 7 and 18.</p> <p>Over gently rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S7}{S18}$ 1966</p>
57.00	<p>The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 1°05' W., bet. secs. 7 and 8.</p> <p>Over gently rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{1}{4}$ $\frac{S7}{S8}$ 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Point for the cor. of secs. 5, 6, 7 and 8 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R21E $\frac{S6}{S7}$ $\frac{S5}{S8}$ 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam, traces of lime. Timber, none. Undergrowth, sage brush and bunch grass.</p>
80.84	

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS		
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>	
	<p>S. 89°58' W., bet. secs. 5 and 8.</p>	
	<p>Over gently rolling land.</p>	
1.75	<p>Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.</p>	
1.79	<p>Telephone line, bears S. 12°30' E. and N. 12°30' W.</p>	
13.42	<p>Apache Railroad, bears N. 2°30' E. and S. 2°30' W.</p>	
39.93	<p>Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p>	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T16N R21E ¼ $\frac{S5}{S8}$ 1966</p>	
	<p>Raise a mound of stone N. of the cor.</p>	
42.90	<p>Old road, bears N. and S.</p>	
79.85	<p>The cor. of secs. 5, 6, 7 and 8.</p>	
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>	
	<hr/> <p>S. 85°57' W., bet. secs. 6 and 7.</p>	
	<p>Over gently rolling land.</p>	
12.50	<p>Ridge, bears N. 30° E. and S. 30° W.</p>	
20.70	<p>Ridge, bears N. and S.</p>	
39.93	<p>Point for the ¼ sec. cor. of secs. 6 and 7 at proportionate distance; there is no remaining evidence of the original corner.</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T16N R21E ¼ $\frac{S6}{S7}$ 1966</p>	
	<p>Raise a mound of stone N. of the cor.</p>	
55.03	<p>The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the T</p>	
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage brush and bunch grass.</p>	

Dep. Res. of Subdivisional Lines, T. 16 N., R. 21 E.

CHAINS	
	<p>From the cor. of secs. 5, 6, 7 and 8.</p>
	<p>N. 0°20' W., bet. secs. 5 and 6.</p>
	<p>Over gently rolling land.</p>
40.42	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T16N R21E</p>
	<p style="text-align: center;">$\frac{1}{4}$</p>
	<p style="text-align: center;">S6 S5</p>
	<p style="text-align: center;">1966</p>
	<p>Raise a mound of stone W. of the cor.</p>
59.80	<p>Spur, slopes E.</p>
80.45	<p>Intersect the 4th Standard Parallel North</p>
	<p>Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T17N R21E</p>
	<p style="text-align: center;">S31</p>
	<p style="text-align: center;">S6 S5</p>
	<p style="text-align: center;">T16N R21E</p>
	<p style="text-align: center;">CC</p>
	<p style="text-align: center;">1966</p>
	<p>from which</p>
	<p style="padding-left: 40px;">The point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, bears S. 89°19' W., 5 lks. dist.</p>
	<p>Raise a mound of stone S. of the cor.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, clay loam.</p>
	<p>Timber, none.</p>
	<p>Undergrowth, sage brush and bunch grass.</p>
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 6 at proportionate distance.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">$\frac{1}{4}$ S6</p>
	<p style="text-align: center;">T16N R21E</p>
	<p style="text-align: center;">1966</p>
	<p>from which</p>
	<p style="padding-left: 40px;">The standard Tp. cor. of Tps. 17 N., Rs. 20 and 21E, bears S. 89°19' W., 5 lks. dist.</p>
	<p>Raise a mound of stone S. of the cor.</p>

Township 16 North, Range 21 East
Gila and Salt River Meridian, Arizona

CHAINS	General Description
	<p>The land in Township 16 North, Range 21 East, is gently rolling range land. Drainage is mostly into Washboard Wash which drains from the SW. cor. to the NE. cor. of the township, the SE. cor. drains SE. into Silver Creek. The soil is clay loam.</p> <p>No timber, except patches of cedar along Washboard Wash and the S. bdy. Livestock grazing is the primary interest. Windmills and stock ponds afford a continual water supply.</p> <p>The Apache Railroad cuts N-S across the W. portion, Arizona State No. 77 cuts N-S across the central portion, and the Woodruff Highway cuts E-W across the E. portion of the township. Some track roads give access to most of the township.</p>

CERTIFICATE OF SURVEY

We I, Boyd S. Owens and Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of August, 19 66, we have made a dependent resurvey of the north boundary (4th Standard Parallel North), the east and west boundaries and subdivisional lines of Township 16 North, Range 21 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~^{US} and under ~~my~~^{OUR} direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 2, 1968
(Date)

Boyd S. Owens
(Cadastral Surveyor)

December 2, 1968
(Date)

Gary T. Oviatt
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date DEC 13 1968

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the north boundary (4th Standard Parallel North), the east and the west boundaries and subdivisional lines of Township 16 North, Range 21 East, Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens, Cadastral Surveyor and Gary T. Oviatt, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 18 1969
(Date)

Clark I. Gumm
(Chief, Division of Engineering)
Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)