

1

Form 9180-6  
(April 1965)  
(formerly 4-679)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

EXTERIORS and SUBDIVISIONAL LINES

SURVEY

of the

SUBDIVISION of Section 12

Township 15 North, Range 19 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Kenneth D. Herman, Cadastral Surveyor

Under special instructions dated August 1, 19 66, which provided for the surveys  
included under Group Number 448, approved August 1, 1966,  
and assignment instructions dated November 4, 19 66.

Survey commenced December 1, 19 66

Survey completed January 20, 19 67

# INDEX DIAGRAM

Township 15 North, Range 19 East

22 16 6	21 61 5	20 52 4	19 44 3	18 37 2	17 29 1 5
61 16 7	60 60 8	51 50 9	44 43 10	36 35 11	29 28 12 4
59 15 18	58 58 17	49 49 16	42 42 15	35 34 14	27 26 13 4
57 14 19	57 56 20	48 47 21	41 40 22	33 32 23	26 25 24 3
56 13 30	55 54 29	47 46 28	39 39 27	32 31 26	24 23 25 2
54 12 31	53 52 32	45 45 33	38 37 34	30 30 35	23 22 36 1
11	10	9	9	7	7

Subdivision of Section 12 - Pages 62-63

Township 15 North, Range 19 East  
Gila and Salt River Meridian, Arizona

CHAINS

The north, south and east boundaries were surveyed in 1883 by M. N. Grant. The west boundary and subdivisional lines were surveyed in 1883 by H. Meyrick.

The following notes are those of a dependent resurvey of the exteriors and subdivisional lines, designed to restore the corners in their true original location, according to the best available evidence, and survey of the subdivision of Section 12 of Township 15 North, Range 19 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 1, 1966.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches diameter, flanged at the base, and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 34°38'37" North, and Longitude 110°16'20" West, scaled from U.S. Army Map Service Quadrangle "Holbrook," scale 1:250,000, dated 1954.

The mean magnetic declination was found to be 14° East.

Dependent Resurvey of the East Boundary  
Township 15 North, Range 19 East

Reestablishment of the Survey  
Executed by M. N. Grant in 1883

From the cor. of Tps. 14 and 15 N., Rs. 19 and 20 E., hereinafter described.

N. 0°22' E., bet. secs. 31 and 36.

Over gently rolling land, through medium timber.  
.20 Fence, barbed wire, bears N. 77° E. and S. 77° W.  
10.10 Leave timber, enter railed area.

40.42 The ¼ sec. cor. of secs. 31 and 36, monumented by an old post, squared on S. side with illegible scribe marks, firmly set in ground with old pointed post alongside. Record called for a sandstone.

At the corner point

Set the iron post 18 ins. in the ground, brass cap mkd.

T15N  
R19E R20E  
¼  
S 36 | S 31  
1966

Set the inverted old wooden posts and a new cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.

Dep. Resurvey, East Bdy., T. 15 N., R. 19 E., Arizona

CHAINS	
	<p>N. 0°28' E., beginning new measurement.</p> <p>Over gently rolling land, through railed area.</p>
20.60	<p>Leave railed area, enter open range land.</p>
40.44	<p>The cor. of secs. 25, 30, 31 and 36, monumented by a wooden stake, mkd. with 5 notches on one side and 1 notch on another side.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E R20E <u>S 25   S 30</u> <u>S 36   S 31</u> 1966</p> </div> <p>Set the inverted wooden stake alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, clay loam. Timber, medium cedar to railed area, to none. Undergrowth, sage, rabbit brush and bunch grass.</p>
	<p>N. 0°38' W., bet. secs. 25 and 30.</p> <p>Over nearly level land.</p>
9.00	<p>Track road, bears N. 60° E. and S. 60° W.</p>
40.03	<p>The ¼ sec. cor. of secs. 25 and 30, monumented by a sandstone, 18 x 10 x 3 ins., lying loose on ground, mkd. ¼ on one side.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E R20E ¼ <u>S 25   S 30</u> 1966</p> </div> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p>
	<p>N. 0°33' E., beginning new measurement.</p> <p>Over nearly level land.</p>
41.53	<p>The cor. of secs. 19, 24, 25 and 30, monumented by a sandstone, 18 x 12 x 3 ins., firmly set, mkd. with 2 notches on S. face and 4 notches on N. face, and with a mound of stone and wooden stake alongside.</p> <p>At the corner point</p>

Dep. Resurvey, East Bdy., T. 15 N., R. 19 E., Arizona

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E R20E <u>S 24   S 19</u> <u>S 25   S 30</u> 1966</p> <p>Bury the orig. corner and the wooden stake alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage and rabbit brush and bunch grass.</p>
40.79	<p>N. 0°29' E., bet. secs. 19 and 24.</p> <p>Over nearly level land.</p> <p>The ¼ sec. cor. of secs. 19 and 24, monumented by an old squared cedar post, firmly set, mkd. with "S" on one face.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E R20E ¼ <u>S 24   S 19</u> 1966</p> <p>Set the inverted old squared cedar post alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>N. 0°06' E., beginning new measurement.</p> <p>Over nearly level land.</p>
5.70	<p>Track road, bears N. 80° E. and S. 80° W.</p>
40.79	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E R20E <u>S 13   S 18</u> <u>S 24   S 19</u> 1966</p> <p>Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage and rabbit brush and bunch grass.</p>

BOOK 4840

4.

Dep. Resurvey, East Bdy., T. 15 N., R. 19 E., Arizona

CHAINS	
	<p>N. 0°06' E., bet. secs. 13 and 18.</p>
	<p>Over nearly level land.</p>
1.70	<p>Fence, barbed wire, bears N. 87°50' E. and S. 87°50' W.</p>
40.79	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, monumented by an old cedar post, 3 ft. long, loosely set, squared on one face, with illegible scribe marks.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E R20E <math>\frac{1}{4}</math> S 13   S 18 1966</p>
	<p>Set the inverted old cedar post and a new cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.</p>
	<p style="text-align: center;">—————</p>
	<p>N. 0°21' E., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
13.00	<p>Enter medium timber.</p>
40.42	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E R20E S 12   S 7 S 13   S 18 1966</p>
	<p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, nearly level to gently rolling. Soil, clay loam. Timber, medium cedar, last half. Undergrowth, rabbit brush and bunch grass.</p>
	<p>N. 0°21' E., bet. secs. 7 and 12.</p>
	<p>Over gently rolling land, through medium timber.</p>
20.21	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 7 and 12, at proportionate dist.</p>
	<p>Set the iron post 18 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E R20E S <math>\frac{1}{16}</math> S 12   S 7 1966</p>

CHAINS	
	<p>Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.</p>
40.30	<p>Leave medium timber; enter scattered timber and sand hills.</p>
40.42	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12, monumented by a mound of stone and a squared stake, 2 ins. diam., 15 ins. long, no marks visible. Record called for a sandstone.</p>
	<p>At the corner point</p>
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E R20E <math>\frac{1}{4}</math> S 12   S 7  1966</p>
	<p>Bury the squared stake alongside the iron post.</p>
	<p style="text-align: center;">_____</p>
	<p>N. 0°20' E., beginning new measurement.</p>
	<p>Over gently rolling hills, through scattered timber.</p>
1.60	<p>Sandy ridge, bears E. and W.</p>
5.60	<p>Wash, 50 lks. wide, 20 ft. deep, drains easterly.</p>
40.48	<p>The cor. of secs. 1, 6, 7 and 12, monumented by a sandstone, 20 x 10 x 2 ins., firmly set, no marks visible, in mound of stone with a squared stake alongside. Record called for a sandstone.</p>
	<p>At the corner point</p>
	<p>Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E R20E S 1   S 6 S12   S 7  1966</p>
	<p>Bury the squared stake alongside the iron post.</p> <p>Land, gently rolling. Soil, clay loam to sandy. Timber, medium to scattered cedar. Undergrowth, sage and rabbit brush.</p>
40.45	<p>N. 0°27' E., bet. secs. 1 and 6.</p> <p>Over gently rolling land, through medium timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.</p>

Dep. Resurvey, South Bdy., T. 15 N., R. 19 E., Arizona

CHAINS

60.70

Desc. N. slope.

76.70

Leave medium timber, enter scattered timber.

80.90

The cor. of Tps. 15 and 16 N., Rs. 19 and 20 E.,  
monumented by an old squared cedar post, 2 ins. diam.,  
4 ft. long, firmly set in ground, mkd. S on E. face,  
other marks illegible.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T16N	
R19E	R20E
S 36	S 31
S 1	S 6
T15N	

1966

Set the inverted old squared post alongside the iron  
post.

Land, gently rolling.

Soil, sandy.

Timber, medium to scattered cedar.

Undergrowth, sage and rabbit brush and bunch grass.

Dependent Resurvey of the South Boundary  
Township 15 North, Range 19 East

Reestablishment of the Survey  
Executed by M. N. Grant in 1883

The cor. of Tps. 14 and 15 N., Rs. 19 and 20 E.,  
monumented by a sandstone, 24 x 12 x 4 ins., mkd.  
plainly with 6 notches on 4 sides.

At the corner point

Set an iron post, 12 ins. in the ground, mound of  
stone to the top, brass cap mkd.

T15N	
R19E	R20E
S 36	S 31
S 1	S 6
T14N	

1966

from which

A cor. of fences, bearing N. 77° E., S. 7° E.  
and S. 77° W., bears N. 13°18' E., 21 lks.  
dist.

Deposit the orig. cor. in the mound surrounding the  
iron post.



CHAINS

N. 89°55' W., bet. secs. 1 and 36.

Over gently rolling land, through medium timber.

.95 Fence, barbed wire, bears N. 77° E. and S. 77° W.

40.26 The ¼ sec. cor. of secs. 1 and 36, monumented by a sandstone, 24 x 10 x 6 ins., set upright in a mound of stone, mkd. ¼ on the E. face.

At the corner point

Set the iron post 6 ins. in the ground, mound of stone to the top, brass cap mkd.

T15N R19E

¼	S 36
	S 1
	T14N

1966

from which

An E-W. fence, bears S., 75 lks. dist.

Deposit the orig. cor. in the mound surrounding the iron post.

---

West, beginning new measurement.

Over gently rolling land, through medium timber.

4.00 Leave timber.

40.27 The cor. of secs. 1, 2, 35 and 36, monumented by a cedar post, 2½ ins. diam., 24 ins. long, mks. obliterated. Record called for a sandstone.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T15N R19E

S 35	S 36
S 2	S 1

T14N

1966

from which

A reservoir, bears N. 22°48' E., 8.44 chs. dist.

An E-W. fence, bears S., 102 lks. dist.

Set the inverted old cedar post and a new cedar post, 2½ ins. diam., 3½ ft. long, alongside the iron post.

Land, gently rolling.

Soil, clay loam.

Timber, medium cedar, first half mile, open last half mile.

Undergrowth, sagebrush, rabbit brush and bunch grass.

N. 89°57' W., bet. secs. 2 and 35.

Over gently rolling land.

CHAINS		
12.70	Wash, 1 ft. deep, 15 lks. wide, drains SW.	
34.60	Track road, bears N. 50° E. and S. 50° W.	
39.40	Track road, bears N. 50° E. and S. 50° W.	
40.20	<p>The ¼ sec. cor. of secs. 2 and 35, monumented by a squared cedar post, 2 ins. diam., 12 ins. above ground, firmly set, marks illegible. Record called for a sandstone.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> <math>\frac{S \ 35}{S \ 2}</math>                      T14N                      1966</p> <p>from which</p> <p style="padding-left: 40px;">An E-W. fence, bears S., 134 lks. dist.</p> <p>Set the inverted old squared cedar post and a new cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <hr style="width: 10%; margin: 20px auto;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over gently rolling land.</p>	
8.50	Enter scattered timber.	
27.90	Track road, bears SE. and NW.	
40.24	<p>The cor. of secs. 2, 3, 34 and 35, monumented by a sandstone, 12 x 6 x 2 ins., mkd. with 2 notches on one side, and a squared cedar post, 3 ins. diam., 2 ft. long, alongside the orig. corner.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{S \ 34 \   \ S \ 35}{S \ 3 \   \ S \ 2}</math>                      T14N                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A cor. of fences bearing E-W. and N. 2°38' E., bears S. 2°40' W., 162 lks. dist.</p> <p>Bury the orig. cor. alongside the iron post.</p> <p>Set a cedar post, 5 ins. in diam., 5 ft. long, alongside the iron post.</p> <p>Land, gently rolling.                      Soil, clay loam.                      Timber, none to scattered cedar, last 1/3 mile.                      Undergrowth, sagebrush, rabbit brush and bunch grass.</p>	

CHAINS					
	<p>S. 89°56' W., bet. secs. 3 and 34.</p> <p>Over gently rolling land and scattered timber.</p>				
.05	Fence, barbed wire, bears N. 2°38' E. and S. 2°38' W.				
8.00	Leave timber.				
39.70	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">An E-W. fence, bears S., 100 lks. dist.</p>				
56.20	Enter scattered timber.				
68.80	Enter heavy timber.				
72.20	Power lines bear N. 0°30' E. and S. 0°30' W., a track road bears along the line.				
79.40	<p>The cor. of secs. 3, 4, 33 and 34, monumented by a squared cedar post, <math>2\frac{1}{2}</math> ins. diam., 3 ft. long, loosely set, mkd. S 33 on one side, T 15 N R 1 on one side, S. on another side; other scribing illegible.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> </table> <p>T14N</p> <p>1966</p> </div> <p>from which</p> <p style="padding-left: 40px;">An E-W fence, bears S., 222 lks. dist.</p> <p>Set the inverted old squared cedar post and a new cedar post, <math>3\frac{1}{2}</math> ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, clay loam. Timber, scattered to heavy cedar. Undergrowth, bunch grass and rabbit brush.</p>	S 33	S 34	S 4	S 3
S 33	S 34				
S 4	S 3				
39.80	<p>S. 89°01' W., bet. secs. 4 and 33.</p> <p>Over nearly level land, through medium timber.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 33, monumented by a squared cedar post, 2 ins. diam., 3 ft. long, loosely set, mkd. <math>\frac{1}{4}</math> S on one face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"><math>\frac{1}{4}</math> S 33</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;"></td> </tr> </table> <p>T14N</p> <p>1966</p> </div>	$\frac{1}{4}$ S 33		S 4	
$\frac{1}{4}$ S 33					
S 4					

CHAINS					
39.85	<p>from which</p> <p>An E-W. fence, bears South, 158 lks. dist.</p> <p>Set the inverted old squared cedar post and a new cedar post, 4 ins. diam., 3 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°23' W., beginning new measurement.</p> <p>Over nearly level land, through scattered timber.</p> <p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> </table> <p>T14N</p> <p>1966</p> </div> <p>from which</p> <p>An E-W. fence, bears South, 60 lks. dist.</p> <p>Set a cedar post, 3 ins. diam., 5 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, clay loam. Timber, medium to scattered cedar, widely scattered pine. Undergrowth, bunch grass, oak and rabbit brush.</p>	S 32	S 33	S 5	S 4
S 32	S 33				
S 5	S 4				
.44 7.00 10.50 10.60 39.85	<p>S. 89°23' W., bet. secs. 5 and 32.</p> <p>Over nearly level land, through scattered timber.</p> <p>Natural gas line, bears S. 2° E. and N. 2° W., a track road follows along the gas line.</p> <p>Fence, barbed wire, bears S. 85°30' E. and N. 85°30' W.</p> <p>Fence, barbed wire, bears N. 82°30' E. and S. 82°30' W.</p> <p>Dim track road, bears N. 82°30' E. and S. 82°30' W.</p> <p>The ¼ sec. cor. of secs. 5 and 32, monumented by squared and pointed cedar post, 2 ins. diam., 2 ft. long, laying loose on ground, mkd. with faint scribe marks visible.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S 32</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;"></td> </tr> </table> <p>T14N</p> <p>1966</p> </div>	¼ S 32		S 5	
¼ S 32					
S 5					

BOOK 4840

11.

Dep. Resurvey, South Bdy., T.15 N., R. 19 E., Arizona

CHAINS	
	<p>Set the inverted old squared and pointed cedar post and a new cedar post, 4 ins. diam., 6 ft. long, alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>S. 89°07' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p>
11.00	<p>New highway, black top, Holbrook to Heber, bears N. 56° E. and curves southerly.</p>
39.26	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">             T15N R19E              S 31   S 32              S 6   S 5              T14N              1966         </p> <p>Set a cedar post, 5 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, nearly level to gently rolling.              Soil, clay loam.              Timber, scattered cedar.              Undergrowth, sage and rabbit brush and thistle.</p>
	<p>S. 89°07' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land, through scattered timber.</p>
28.90	<p>Wash, 20 lks. wide, with 5 ft. banks, drains SW.</p>
30.90	<p>Wash, 30 lks. wide, with 10 ft. banks, drains SW., curves and joins the next wash approx. 1 ch. S.</p>
31.50	<p>Wash, 30 lks. wide, with 10 ft. banks, drains SW.</p>
36.30	<p>Bladed gravel road, old Holbrook to Heber Road, bears N. 30° E. and S. 30° W.</p>
39.26	<p>Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.</p>
58.00	<p>Leave timber; enter open area.</p>
79.79	<p>The cor. of Tps. 14 and 15 N., Rs. 18 and 19 E., monumented by a sandstone, 20 x 10 x 6 ins., dimly mkd. and loosely set alongside a large post, used as a cor. of fences bearing N., E. and W.</p> <p>At the corner point</p>

CHAINS	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R18E R19E S 36   S 31 S 1   S 6 T14N 1966</p> <p>Bury the orig. cor. alongside the iron post.</p> <p>Land, gently rolling. Soil, clay loam, some sand. Timber, scattered cedar to none. Undergrowth, sage, rabbit brush, bunchgrass and thistle.</p>
	<p>Dependent Resurvey of the West Boundary Township 15 North, Range 19 East</p>
	<p>Reestablishment of the Survey Executed by H. Meyrick in 1883</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of Tps. 14 and 15 N., Rs. 18 and 19 E. N. 0°39' E., bet. secs. 31 and 36.</p> <p>Over gently rolling land.</p>
32.80	Enter marsh area.
35.12	S. edge of water.
40.59	Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.; falls in marsh and water, where corner cannot be perpetuated.
41.80	N. edge of water.
42.59	Point selected for the witness ¼ sec. cor. of secs. 31 and 36.
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R18E R19E WC ¼ S 36   S 31 1966</p> <p>from which</p> <p style="text-align: center;">A N-S. fence, bears West, 5 lks. dist.</p> <p>Raise a mound of stone W. of the corner.</p>
48.00	Leave marsh area.
53.00	Wash, 30 lks. wide, with 8 ft. banks, drains SW.
65.80	Enter medium timber.

CHAINS	
66.20	Wash, 50 lks. wide, 4 ft. deep, drains SW.
81.18	<p>The cor. of secs. 25, 30, 31 and 36, monumented by a sandstone, 25 x 8 x 3 ins., firmly set, mkd. with 5 notches on N. side, mound of stone, and a local iron pipe alongside.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground to bedrock, mound of stone to the top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R18E R19E S 25   S 30 S 36   S 31</p> </div> <p>1966</p> <p>from which</p> <p style="padding-left: 40px;">A N-S. fence, bears West, 4 lks. dist.</p> <p>Deposit the orig. cor. alongside the iron post.</p> <p>Set the 1-inch local iron pipe alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy first <math>\frac{3}{4}</math> mile, then rocky. Timber, none, to medium cedar last <math>\frac{1}{4}</math> mile. Undergrowth, sage, rabbit brush and thistle.</p>
	N. 0°06' E., bet. secs. 25 and 30.
	Over gently rolling land, through medium timber.
3.70	Leave medium timber.
19.80	Track road, bears SE. and NW.
40.81	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, monumented by a squared post, 2 ins. diam., 20 ins. long, lying loose on ground, mkd. <math>\frac{1}{4}</math> on one face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R18E R19E <math>\frac{1}{4}</math> S 25   S 30</p> </div> <p>1966</p> <p>from which</p> <p style="padding-left: 40px;">A N-S. fence, bears West, 7 lks. dist.</p> <p>Bury the orig. cor. alongside the iron post.</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>

CHAINS	
	<p>N. 0°03' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
8.30	<p>Bladed road to Hutchinson Ranch, bears S. 73° E. and N. 83° W.</p>
17.70	<p>Track road, bears SW., and NE. for 1.00 ch., thence bears N.</p>
29.00	<p>Desc. N. slope.</p>
40.00	<p>Bottom of swale, asc. S. slope.</p>
40.75	<p>The cor. of secs. 19, 24, 25 and 30, monumented by a sandstone, 14 x 14 x 4 ins., lying loose on ground, mkd. with 4 notches on one face and 2 notches on opposite face.</p>
	<p>At the corner point</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R18E R19E S 24   S 19 S 25   S 30</p>
	<p style="text-align: center;">1966</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A N-S. fence, bears West, 1 lk. dist.</p>
	<p>Bury the orig. cor. alongside the iron post.</p>
	<p>Raise a mound of stone W. of the corner.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, sandy loam.</p>
	<p>Timber, none.</p>
	<p>Undergrowth, sage, rabbit brush and bunch grass.</p>
	<p>N. 0°03' E., bet. secs. 19 and 24.</p>
	<p>Over gently rolling land.</p>
10.00	<p>Desc. N. slope.</p>
18.86	<p>Track road, bears SE. and NW., fence, barbed wire, bears northerly and southerly.</p>
28.00	<p>Asc. S. slope.</p>
34.34	<p>Track road, bears NE. and SW.</p>
40.85	<p>Point for the ½ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R18E R19E ½ S 24   S 19</p>
	<p style="text-align: center;">1966</p>



Dep. Resurvey, West Bdy., T. 15 N., R. 19 E., Arizona

CHAINS	
81.71	<p>from which</p> <p>A N-S. fence, bears East, 3 lks. dist.</p> <p>A N-S. track road, bears West, 05 lks. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R18E R19E S 13   S 18 S 24   S 19 1966</p> </div> <p>from which</p> <p>A N-S. fence, bears East, 7 lks. dist.</p> <p>A N-S. track road, bears West, 5 lks. dist.</p> <p>A cor. of fences, bearing N. 88°20' E., S. and S. 88°20' W., bears N. 15°50' E., 22 lks. dist.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage, rabbit brush and bunch grass.</p>
0.20	<p>N. 0°03' E., bet. secs. 13 and 18.</p> <p>Over nearly level land.</p> <p>Fence, bears N. 88°20' E. and S. 88°20' W.</p>
0.40	<p>Track road, bears East and West.</p>
40.85	<p>Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R18E R19E ¼ S 13   S 18 1966</p> </div> <p>from which</p> <p>A N-S. track road, bears East, 27 lks. dist.</p> <p>Raise a mound of stone West of the cor.</p>
79.70	<p>Track road, bears NE. and SW.</p>
81.71	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

Dep. Resurvey, West Bdy., T. 15 N., R. 19 E., Arizona

CHAINS		
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R18E R19E S 12   S 7 S 13   S 18 1966</p> <p>from which</p> <p style="text-align: center;">A N-S track road, bears East, 33 lks. dist.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage, rabbit brush and bunch grass.</p>	
	<p>N. 0°03' E., bet. secs. 7 and 12.</p> <p>Over nearly level land.</p>	
29.50	Track road, bears NE. and SW.	
40.85	Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.	
81.71	<p>The cor. of secs. 1, 6, 7 and 12, monumented by a sandstone, 21 x 12 x 3 ins., firmly set in the ground, mkd. with 5 notches on S. edge and 1 notch on N. edge.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R18E R19E S 1   S 6 S 12   S 7 1966</p> <p>Deposit the orig. cor. alongside the iron post.</p> <p>Set a post, 4 ins. diam., 5 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sage, rabbit brush and bunch grass.</p>	
	<p>N. 0°23' E., bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p>	
3.00	Enter scattered timber.	
20.00	Leave scattered timber.	
24.50	Track road, bears SE. and NW.	

Dep. Resurvey, North Bdy., T.15 N., R. 19 E., Arizona

CHAINS	
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.
61.00	Enter scattered timber.
75.80	Wash, 30 lks. wide, 2 ft. deep, drains NW.
81.01	<p>The cor. of Tps. 15 and 16 N., Rs. 18 and 19 E., monumented by a sandstone, 12 x 10 x 3 ins., firmly set in the ground, in a cor. of fences bearing N. 1°45' E., East and West, and some remains of a fence bearing South, marked with 4 notches on one side and 3 notches on another, with a scattering of stones around.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R18E R19E <u>S 36   S 31</u> S 1   S 6 T15N</p> <p>1966</p> </div> <p>Bury the orig. cor. alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, scattered cedar. Undergrowth, sage, rabbit brush and bunch grass.</p>
<p>Dependent Resurvey of the North Boundary Township 15 North, Range 19 East</p>	
<p>Reestablishment of the Survey Executed by M. N. Grant in 1883</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the cor. of Tps. 15 and 16 N., Rs. 19 and 20 E. S. 89°53' W., bet. secs. 1 and 36.</p> <p>Over gently rolling land, through widely scattered timber.</p>	
39.55	Highway, black top, Holbrook to Heber, bears NE. and SW.
40.14	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R19E <u>  S 36</u> <math>\frac{1}{4}</math> S 1 T15N</p> <p>1966</p> </div>

Dep. Resurvey, North Bdy., T. 15 N., R. 19 E., Arizona

CHAINS	<p>Raise a mound of stone N. of the corner.</p> <p>48.00 Crest of hill.</p> <p>80.29 The cor. of secs. 1, 2, 35 and 36, monumented by a squared cedar post, 3 ins. diam., 18 ins. long, lying loose on the ground, dimly mkd. Record called for a sandstone.</p> <p>At the corner point</p> <p>Set the iron post, 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T16N</td><td>R19E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T15N</td></tr> <tr><td colspan="2">1966</td></tr> </table> </div> <p>Deposit the cedar post alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, sage, rabbit brush and bunch grass.</p> <hr style="border: 0.5px solid black;"/> <p>S. 89°19' W., bet. secs. 2 and 35.</p> <p>Over gently rolling land, through widely scattered timber.</p> <p>39.80 Track road, bears NE. and SW.</p> <p>40.50 The ¼ sec. cor. of secs. 2 and 35, monumented by a squared cedar post, 2 ins. diam., 2 ft. long, lying loose on the ground, mkd. ¼ on one side. Record called for a sandstone.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T16N</td><td>R19E</td></tr> <tr><td>¼ S 35</td><td></td></tr> <tr><td>¼ S 2</td><td></td></tr> <tr><td colspan="2">T15N</td></tr> <tr><td colspan="2">1966</td></tr> </table> </div> <p>Set the inverted old squared cedar post and a new cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89°13' W., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered timber.</p> <p>8.00 Enter medium scattered timber.</p>	T16N	R19E	S 35	S 36	S 2	S 1	T15N		1966		T16N	R19E	¼ S 35		¼ S 2		T15N		1966	
T16N	R19E																				
S 35	S 36																				
S 2	S 1																				
T15N																					
1966																					
T16N	R19E																				
¼ S 35																					
¼ S 2																					
T15N																					
1966																					

CHAINS

40.30

The cor. of secs. 2, 3, 34 and 35, monumented by a sandstone, 25 x 10 x 4 ins., lying loose on ground, mkd. with 4 notches on one side and 2 notches on another side.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T16N R19E

S 34 | S 35

S 3 | S 2

T15N

1966

Deposit the orig. cor. alongside the iron post.

Raise a mound of stone W. of the cor.

Land, gently rolling.

Soil, sandy loam.

Timber, widely scattered to medium cedar.

Undergrowth, sage, rabbit brush and bunch grass.

22.00

S. 89°42' W., bet. secs. 3 and 34.

Over gently rolling land, through scattered timber.

Top of rise.

40.14

The 1/4 sec. cor. of secs. 3 and 34, monumented by a sandstone, 20 x 10 x 4 ins., firmly set in a mound of stone, mkd. 1/4 on E. face.

At the corner point

Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.

T16N R19E

1/4 S 34

S 3

T15N

1966

Deposit the orig. cor. in the mound surrounding the iron post.

N. 89°56' W., beginning new measurement.

Over gently rolling land, through scattered timber.

12.60

Wash, 40 lks. wide, with 10 ft. banks, drains irreg. N., asc. E. slope.

31.19

Power line, bears N. 0°23' E. and S. 0°23' W.

39.84

The cor. of secs. 3, 4, 33 and 34, monumented by a sandstone, 20 x 10 x 4 ins., firmly set in a mound of stone, mkd. with 3 notches on E. and W. faces.

At the corner point

CHAINS		
	<p>Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T16N R19E  <math>\frac{S}{S} \frac{33}{4}   \frac{S}{S} \frac{34}{3}</math>                      T15N                      1966</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, scattered cedar.                      Undergrowth, rabbit brush and bunch grass.</p>	
32.00	<p>S. 89°40' W., bet. secs. 4 and 33.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Leave timber.</p>	
40.05	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 33, monumented by a sandstone, 24 x 12 x 3 ins., lying loose in a mound of stone, mkd. <math>\frac{1}{4}</math> on one side.</p> <p>At the corner point</p> <p>Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T16N R19E  <math>\frac{1}{4} \frac{S}{S} \frac{33}{4}</math>                      T15N                      1966</p> <p>from which</p> <p style="padding-left: 40px;">An E-W. track road, bears South, 20 lks. dist.                      An E-W. fence, bears South, 43 lks. dist.</p> <p>Deposit the orig. cor. alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>	
39.88	<p>N. 89°55' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>The cor. of secs. 4, 5, 32 and 33, monumented by a mound of stone with a squared stake in center, marks illegible. Record called for a sandstone.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T16N R19E  <math>\frac{S}{S} \frac{32}{5}   \frac{S}{S} \frac{33}{4}</math>                      T15N                      1966</p>	

CHAINS

from which

An E-W. track road, bears South, 10 lks. dist.

A sandstone, with dimensions conforming with the record and marked with two notches on one edge, was found being used as a fence weight in an E-W. wire fence, 17 lks. South.

Bury the squared stake alongside the iron post.

Land, gently rolling.

Soil, sandy loam.

Timber, scattered cedar first 1/3 mile, then none.

Undergrowth, sage, rabbit brush and bunch grass.

N. 89°58' W., bet. secs. 5 and 32.

Over gently rolling land.

3.80 Natural gas line, bears N. and S.

4.10 Track road, bears N. 11°42' E. and S. 11°42' W.

39.83 Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; falls in the center of a track road bearing S. 89°50' E. and N. 89°50' W.; there is no remaining evidence of the orig. cor.

Set the iron post 20 ins. in the ground, brass cap mkd.

T16N R19E  
 $\frac{1}{4} \begin{array}{r} S \ 32 \\ S \ 5 \end{array}$   
 T15N  
 1966

from which

An E-W. fence, bears South, 9 lks. dist.

Raise a mound of stone N. of the cor.

55.50 Wash, 40 lks. wide, 2 ft. deep, drains NE.

79.66 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; falls in the center of a track road bearing S. 89°58' E. and N. 89°58' W.; there is no remaining evidence of the orig. cor.

Set the iron post 10 ins. in the ground, mound of stone to the top, brass cap mkd.

T16N R19E  
 $\begin{array}{r} S \ 31 \ | \ S \ 32 \\ S \ 6 \ | \ S \ 5 \end{array}$   
 T15N  
 1966

from which

An E-W. fence, bears South, 10 lks. dist.

Land, gently rolling.

Soil, sandy loam.

Timber, none.

Undergrowth, sage, rabbit brush and bunch grass.

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS	
	N. 89°58' W., bet. secs. 6 and 31.
	Over gently rolling land.
7.50	Track road, bears NE. and SW.
39.83	Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.
56.00	Enter widely scattered timber.
76.40	Enter medium timber.
78.16	The cor. of Tps. 15 and 16 N., Rs. 18 and 19 E.
	Land, gently rolling.
	Soil, sandy loam.
	Timber, none to scattered cedar the last 1/3 mile.
	Undergrowth, sage, rabbit brush and bunch grass.
Dependent Resurvey of the Subdivisional Lines Township 15 North, Range 19 East	
Reestablishment of the Survey Executed by H. Meyrick in 1883	
<hr/> From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.	
N. 0°23' E., bet. secs. 35 and 36.	
Over gently rolling land.	
10.90	Track road, bears NE. and SW.
40.07	Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
Set the iron post 24 ins. in the ground, brass cap mkd.	
T15N R19E $\frac{1}{4}$ S 35   S 36 1966	
Raise a mound of stone W. of the cor.	
80.14	The cor. of secs. 25, 26, 35 and 36, monumented by a sandstone, 20 x 20 x 3 ins., firmly set in a mound of stone, mkd. with 1 notch on two sides.
At the corner point	
Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.	
T15N R19E S 26   S 25 S 35   S 36 1966	
Deposit the orig. cor. in the mound surrounding the iron post.	



CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, none, to widely scattered. Undergrowth, sage, rabbit brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89°31' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p> <p>10.90 Track road, bears NE. and SW.</p> <p>40.29 The ¼ sec. cor. of secs. 25 and 36, monumented by a squared wood post, 2½ ins. diam., 30 ins. long, lying loose on the ground, mkd. ¼ on one side.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ S 25 S 36 1966</p> <p>Set the inverted old squared post and a new cedar post, 4 ins. diam., 4½ ft. long, alongside the iron post.</p> <hr/> <p>S. 89°28' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>29.70 Enter widely scattered timber.</p>
	<p>40.29 The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none to widely scattered cedar, last 1/3 mile. Undergrowth, rabbit brush and bunch grass.</p>
	<p>N. 0°17' W., bet. secs. 25 and 26.</p> <p>Over gently rolling land, through widely scattered timber.</p> <p>37.00 Enter medium timber.</p> <p>40.67 The ¼ sec. cor. of secs. 25 and 26, monumented by a sandstone, 18 x 10 x 2 ins., firmly set in mound of stone, dimly mkd. ¼ on one face.</p> <p>At the corner point</p> <p>Set the iron post, 6 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ S 26   S 25 1966</p>

CHAINS								
	<p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°14' W., beginning new measurement.</p> <p>Over gently rolling land, through medium timber.</p>							
15.25	<p>Wash, 30 lks. wide, 1 ft. deep, drains NE.</p>							
40.38	<p>The cor. of secs. 23, 24, 25 and 26, monumented by a sandstone, 16 x 12 x 2 ins., loosely set in a mound of stone, mkd. with one notch on one side and two notches on another side.</p> <p>At the corner point</p> <p>Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T15N R19E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 23</td><td style="padding: 0 5px;">S 24</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 26</td><td style="padding: 0 5px;">S 25</td></tr> </table> <p>1966</p> </div> <p>from which</p> <p style="margin-left: 40px;">A location monument, SW. cor. of oil claim, Hill Top #1, 03-21-1918, bears N. 36°20' E., 1.16 chs. dist.</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered to medium cedar. Undergrowth, rabbit brush and bunch grass.</p>	T15N R19E		S 23	S 24	S 26	S 25	
T15N R19E								
S 23	S 24							
S 26	S 25							
40.42	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89°04' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p> <p>The ¼ sec. cor. of secs. 24 and 25, monumented by a squared cedar post, 3 ins. diam., 2 ft. long, lying loose on ground, dimly mkd.</p> <p>At the corner point</p> <p>Set the iron post, 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T15N R19E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">¼ S 24</td><td style="padding: 0 5px;">S 25</td></tr> </table> <p>1967</p> </div> <p>Set the inverted squared cedar post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°11' W., beginning new measurement.</p> <p>Over gently rolling land.</p>	T15N R19E		¼ S 24	S 25			
T15N R19E								
¼ S 24	S 25							

BOOK 4840

25.

Dep. Resurvey, Subdivisional Lines, T.15 N., R.19 E., Arizona

CHAINS	
24.00	Enter scattered timber.
40.48	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none to scattered cedar last <math>\frac{1}{4}</math> mile. Undergrowth, bunch grass.</p>
	N. $0^{\circ}34'$ W., bet. secs. 23 and 24.
	Over gently rolling land, through medium timber.
20.20	Leave timber, enter railed area.
31.50	Track road, bears E. and W.
40.02	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 24, monumented by a squared post, 2 ins. diam., 30 ins. long, lying loose on the ground, mkd. with <math>\frac{1}{4}</math> on one side.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E <math>\frac{1}{4}</math> S 23   S 24 1966</p>
	from which
	A stock pond, bears East, 7.00 chs. dist.
	Set the inverted squared post alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> <p>N. <math>0^{\circ}58'</math> E., beginning new measurement.</p>
	Over gently rolling land.
19.60	Leave railed area, enter medium timber.
22.00	Wash, 30 lks. wide, 5 ft. deep, drains SW.
41.52	Fence, barbed wire, bears East and West.
41.59	<p>The cor. of secs. 13, 14, 23 and 24, monumented by a sandstone, 15 x 12 x 4 ins., firmly set in a mound of stone, mkd. with 3 notches on S. side and 1 notch on E. side.</p> <p>At the corner point</p> <p>Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E S 14   S 13 S 23   S 24 1966</p>
	from which
	Petroglyphs on S. side of a rock on the N. side of a wash, bears N. $26^{\circ}31'$ E., 2.70 chs. dist.

BOOK 4840

Dep. Resurvey, Subdivisional Lines, T.15 N., R.19 E., Arizona

CHAINS		
	<p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p>	
<p>36.00</p> <p>39.95</p>	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89°40' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land.</p> <p>Wash, 15 lks. wide, 1 ft. deep, drains N.</p> <p>The ¼ sec. cor. of secs. 13 and 24, monumented by a sandstone, 16 x 13 x 5 ins., properly mkd. and loosely set in a mound of stone, 1½ lks. North of an E-W. fence.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ <math>\frac{S \ 13}{S \ 24}</math> 1967</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 87°58' W., beginning new measurement.</p> <p>Over gently rolling land.</p>	
<p>1.50</p> <p>41.03</p>	<p>Fence, barbed wire, bears E. and W., enter medium timber.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar last ½ mile. Undergrowth, rabbit brush and bunch grass.</p>	
	<p>N. 0°43' W., bet. secs. 13 and 14.</p> <p>Over gently rolling land, through medium timber.</p> <p>Wash, 50 lks. wide, with 8 ft. banks, drains NE.</p> <p>The ¼ sec. cor. of secs. 13 and 14, monumented by a sandstone, 21 x 12 x 2 ins., properly mkd. and firmly set in a mound of stone.</p> <p>At the corner point</p>	

CHAINS	
40.72	<p>Set the iron post, 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E S 14<sup>1/4</sup>   S 13 1966</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Set a cedar post, 4 ins. diam., 3 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°32' E., beginning new measurement.</p> <p>Over gently rolling land, through medium timber.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented by a squared and pointed post, 3 ins. diam., 3½ ft. long, loosely set, marks illegible.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E S 11   S 12 S 14   S 13 1966</p> <p>Set the inverted squared and pointed post and a new cedar post, 3 ins. diam., 3½ ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium to thick cedar. Undergrowth, rabbit brush and bunch grass.</p>
20.95	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 88°01' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land, through medium timber.</p> <p>Point for the E 1/16 sec. cor. of secs. 12 and 13, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E E 1/16   S 12 S 13 1967</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p>
33.90	<p>Draw, drains S. 22° W.</p>
41.90	<p>The ¼ sec. cor. of secs. 12 and 13, monumented by a sandstone, 14 x 10 x 1½ ins., firmly set in a mound of stone, mkd. ¼ on one side.</p>

CHAINS		
39.50	<p>At the corner point</p> <p>Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{12}{13}</math>                      1967</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°58' W., beginning new measurement.</p> <p>Over gently rolling land, through medium timber.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, gently rolling.                      Soil, sandy loam and rock.                      Timber, medium cedar.                      Undergrowth, rabbit brush and bunch grass.</p>	
40.83	<p>N. 0°48' E., bet. secs. 11 and 12.</p> <p>Over gently rolling land, through medium timber.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, monumented by a squared post, 2 ins. diam., 2 ft. long, lying loose on the ground, dimly mkd. <math>\frac{1}{4}</math> on one side.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>                      S 11   S 12                      1966</p> <p>Set the inverted squared post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°58' E., beginning new measurement.</p> <p>Over gently rolling land, through medium timber.</p>	
35.50	<p>Top of rise; leave timber.</p>	
40.83	<p>The cor. of secs. 1, 2, 11 and 12, monumented by a squared post, 2 ins. diam., 2 ft. long, lying loose on ground, mkd. 2 on one side and illegible marks on two other sides.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{S}{S}</math> <math>\frac{2}{11}</math>   <math>\frac{S}{S}</math> <math>\frac{1}{12}</math>                      1966</p>	

Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 19 E., Arizona

CHAINS	
	<p>Set the inverted squared post along with a new cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, sage, rabbit brush and bunch grass.</p>
<p>40.38</p>	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>S. 89°25' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through medium timber.</p> <p>The ¼ sec. cor. of secs. 1 and 12, monumented by a squared post, 2 ins. diam., 2 ft. long, lying loose on the ground, mkd. ¼ on one side.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ <math>\frac{S}{S}</math> <math>\frac{1}{12}</math> 1967</p> <p>Set the inverted squared post alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>S. 89°31' W., beginning new measurement.</p> <p>Over gently rolling land, through medium timber.</p> <p>16.20 Track road, bears N. 22° E. and S. 22° W.</p> <p>30.00 Leave medium timber; enter widely scattered timber.</p> <p>40.17 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar to widely scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>
<p>40.60</p> <p>40.73</p> <p>41.73</p>	<p>N. 0°36' E., bet. secs. 1 and 2.</p> <p>Over gently rolling land.</p> <p>Highway, graded gravel, Holbrook to Heber, bears NE. and SW.</p> <p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate dist.; falls on N. edge of road where a monument cannot be perpetuated.</p> <p>Point selected for the witness ¼ sec. cor. of secs. 1 and 2.</p>

Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 19 E., Arizona

<p>CHAINS</p>	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>  S 2 ↓ S 1  W C  1966</p> <p>from which</p> <p style="padding-left: 40px;">The N. end of culvert under road, bears S. 22°30' W., 73½ lks. dist.</p> <p>81.49 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.</p> <p>Land, gently rolling.  Soil, sandy loam.  Timber, none.  Undergrowth, rabbit brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.</p> <p>N. 1°20' E., bet. secs. 34 and 35.</p> <p>Over gently rolling land, through scattered timber.</p> <p>15.80 Track road, bears SE. and NW.</p> <p>40.05 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.</p> <p>73.00 Enter dense timber.</p> <p>80.10 The cor. of secs. 26, 27, 34 and 35, monumented by a squared post, 2 ins. diam., 22 ins. long, firmly set in ground, mkd. 26-27-34-35.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <u>S 27   S 26</u>  <u>S 34   S 35</u>  1966</p> <p>from which</p> <p style="padding-left: 40px;">A stock pond, bears S. 25°08' E., 14.40 chs. dist.</p> <p>Set the inverted orig. post along with a new cedar post, 3 ins. diam., 4½ ft. long, alongside the iron post.</p> <p>Land, gently rolling.  Soil, sandy loam.  Timber, scattered to thick cedar.  Undergrowth, sage, rabbit brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°34' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through widely scattered timber.</p>
---------------	---



Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 19 E., Arizona

CHAINS  
39.98

The  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, monumented by a squared post,  $1\frac{1}{2}$  ins. diam., 26 ins. long, lying loose on ground, dimly mkd.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T15N R19E

$\frac{1}{4}$ S 26  
S 35

1967

Set the inverted orig. post alongside the iron post.

Raise a mound of stone N. of the corner.

\_\_\_\_\_

N.  $89^{\circ}33'$  W., beginning new measurement.

Over gently rolling land, through widely scattered timber.

35.10 Track road, bears SE. and N.  $22^{\circ}$  W.; enter railed area.

39.06 Fence, barbed wire, bears N. and S.; enter medium timber.

39.11 The cor. of secs. 26, 27, 34 and 35.

Land, gently rolling.

Soil, sandy loam.

Timber, widely scattered cedar.

Undergrowth, rabbit brush and bunch grass.

N.  $0^{\circ}12'$  W., bet. secs. 26 and 27.

Over gently rolling land, through medium timber.

40.15 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 8 ins. in the ground, mound of stone to the top, brass cap mkd.

T15N R19E

$\frac{1}{4}$ S 27 | S 26

1966

70.40 Track road, bears East and West.

78.00 Leave timber.

80.31 The cor. of secs. 22, 23, 26 and 27, monumented by a squared post, 2 ins. diam., 30 ins. long, firmly set, dimly mkd.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T15N R19E

S 22 | S 23  
S 27 | S 26

1966

Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 19 E., Arizona

CHAINS		
	<p>Set the inverted orig. post along with a new cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p>	
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°29' W., bet. secs. 23 and 26.</p> <p>Over nearly level land, through scattered timber.</p>	
24.20	Track road, bears NE. and SW.; enter railed area.	
35.20	Leave railed area; enter scattered timber.	
39.98	<p>The ¼ sec. cor. of secs. 23 and 26, monumented by a sandstone, 18 x 12 x 6 ins., lying loose on ground, mkd. ¼ on one face.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ <u>S 23</u>       S 26       1967</p> <p>Deposit the original cor. alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>S. 89°30' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p>	
1.80	Wash, 50 lks. wide, with 10 ft. banks, drains irreg. SE.	
7.00	Leave timber; enter railed area.	
8.00	Top of small knoll.	
39.03	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, nearly level to gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, bunch grass.</p>	
	<p>N. 0°19' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land.</p>	
0.10	Fence, barbed wire, bears N. and S.	
40.86	<p>The ¼ sec. cor. of secs. 22 and 23, monumented by a sandstone, 12 x 12 x 4 ins., firmly set in a mound of stone, mkd. ¼ on W. face.</p> <p>At the corner point</p>	

CHAINS	
	<p>Set the iron post 12 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>                      S 22   S 23                      1966</p> <p>Bury the orig. cor. alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A N-S. fence, bears East, 31 lks. dist.</p> <p style="text-align: center;">—————</p> <p>N. 0°04' W., beginning new measurement.</p> <p>Over nearly level land.</p>
2.00	Enter scattered timber.
27.20	Fence, barbed wire, bears irreg. N. and S.
40.60	Fence, barbed wire, bears N. 88°40' E. and S. 88°40' W.
40.70	<p>The cor. of secs. 14, 15, 22 and 23, as determined from the only remaining original bearing tree</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 13° W., 40 lks. dist., mkd. T15N R19E S 22 BT.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, collar of stone, brass cap mkd.</p> <p style="text-align: center;">T15N R19E                      S 15   S 14                      S 22   S 23                      1966</p> <p>from which</p> <p style="padding-left: 40px;">A corner of fences, bearing N. 88°40' E., S. and S. 88°40' W., bears SW., 13 lks. dist.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling to nearly level.                      Soil, sandy loam.                      Timber, scattered cedar.                      Undergrowth, rabbit brush and bunch grass.</p>
1.00	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°29' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Enter railed area.</p>
39.78	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>

BOOK 4840

34.

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS		
	<p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> <math>\frac{S 14}{S 23}</math>                      1967</p> <p>from which                      An E-W. fence, bears North, 59 lks. dist.</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p>	
75.60	Fence, barbed wire, bears N. 88°30' E. and S. 88°30' W.; leave railed area; enter scattered timber.	
79.56	The cor. of secs. 14, 15, 22 and 23.	
	<p>Land, gently rolling.                      Soil, sandy loam.                      Timber, scattered cedar.                      Undergrowth, rabbit brush and bunch grass.</p>	
	<p>N. 0°38' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land, through scattered timber.</p>	
9.75	Highway, bladed gravel, new Holbrook to Heber, bears N. 6°10' E. and S. 6°10' W.	
41.53	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 15, monumented by a squared post, 3 ins. diam., 2 ft. long, lying loose on ground, mkd. <math>\frac{1}{4}</math> on one side.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>                      S 15   S 14                      1966</p>	
	<p>Set the inverted orig. post alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>	
	<p style="text-align: center;">—————</p> <p>N. 0°17' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p>	
39.75	<p>The cor. of secs. 10, 11, 14 and 15, monumented by a squared post, 2 ins. diam., 15 ins. long, lying loose in mound of stone, mkd. 10, 15 on two sides; other marks illegible.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to the top, brass cap mkd.</p>	
	<p style="text-align: center;">T15N R19E  <math>\frac{S 10}{S 15}</math>   <math>\frac{S 11}{S 14}</math>                      1966</p>	

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS	
	<p>Set the inverted orig. post along with a new cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, sage, rabbit brush and bunch grass.</p>
<p>8.00</p> <p>15.60</p> <p>24.70</p> <p>39.62</p>	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°51' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through medium timber.</p> <p>Dim track road, bears NE. and SW.</p> <p>Dim track road, bears S. 22° E. and N. 22° W.</p> <p>Low sag, bears S. 22° E. and N. 22° W.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14, monumented by a cedar post, 4 ins. diam., 4 ft. long, firmly set in ground, dimly mkd.</p> <p>At the corner point</p> <p>Set the iron post, 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E <math>\frac{1}{4}</math> <math>\frac{S 11}{S 14}</math> 1967</p> <p>Set the inverted orig. post alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>
<p>14.40</p>	<p>S. 89°26' W., beginning new measurement.</p> <p>Over gently rolling land, through medium timber.</p> <p>Highway, bladed gravel, new from Holbrook to Heber, bears N. 20°40' E. and S. 20°40' W.; enter widely scattered timber.</p>
<p>40.46</p>	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium to widely scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>
<p>21.50</p>	<p>N. 0°31' E., bet. secs. 10 and 11.</p> <p>Over gently rolling land, through widely scattered timber.</p> <p>Old highway, bladed gravel, Holbrook to Heber, bears N. 42°20' E. and S. 42°20' W.</p>

BOOK 4840

36.

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS						
40.50	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 11, monumented by a squared post, 2 ins. diam., 26 ins. long, lying loose on ground, mkd. <math>\frac{1}{4}</math> on one side. Record called for a sandstone. This corner was not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°31' E., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered timber.</p>					
40.56	<p>The cor. of secs. 2, 3, 10 and 11, monumented by a sandstone, 16 x 12 x 3 ins., lying loose in mound of stone, mkd. with 2 notches on one face and 5 notches on another face.</p> <p>At the corner point</p> <p>Set the iron post 4 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p>1966</p> </div> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, sage, rabbit brush and bunch grass.</p>	S 3	S 2	S 10	S 11	
S 3	S 2					
S 10	S 11					
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°15' W., bet. secs. 2 and 11.</p> <p>Over gently rolling land, through widely scattered timber.</p>					
24.40	<p>New highway, bladed gravel, Holbrook to Heber, bears N. 20°45' E. and S. 20°45' W.</p>					
40.30	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"><math>\frac{1}{4}</math> S 2</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p>1967</p> </div>	$\frac{1}{4}$ S 2	S 11			
$\frac{1}{4}$ S 2	S 11					
40.77	<p>Old graded road from Holbrook to Heber, bears NE. and SW.</p>					
80.60	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>					

CHAINS	
19.70	<p>N. 0°31' E., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through widely scattered timber.</p> <p>Track road, bears NE. and SW.</p>
40.74	<p>The ¼ sec. cor. of secs. 2 and 3, monumented by a squared post, 2 ins. diam., 16 ins. long, lying loose on the ground, mkd. with ¼ on one side.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>  S 3   S 2  1966</p> <p>Set the inverted orig. post along with a new cedar post, 3 ins. diam., 5 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°24' E., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered timber.</p>
40.75	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.</p> <p>Land, gently rolling.  Soil, sandy loam.  Timber, widely scattered cedar.  Undergrowth, bunch grass.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°17' W., bet. secs. 33 and 34.</p> <p>Over nearly level land, through thick timber.</p> <p>The ¼ sec. cor. of secs. 33 and 34, monumented by a sandstone, 7 x 6 x 2 ins., lying loose on ground, mkd. with ¼ on one side, and a squared post, 2 ins. diam., 20 ins. long, alongside stone; no marks.</p> <p>At the corner point</p> <p>Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>  S 33   S 34  1966</p> <p>Bury the orig. cor. and the squared post alongside the iron post.</p> <p>Set a new cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>

CHAINS		
41.29	<p>N. 2°13' W., beginning new measurement.</p> <p>Over gently rolling land, through medium timber.</p> <p>Point for the sec. cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{S \ 28}{S \ 33}   \frac{S \ 27}{S \ 34}</math>                      1966</p> <p>Land, nearly level to gently rolling.                      Soil, sandy loam.                      Timber, thick to scattered cedar.                      Undergrowth, rabbit brush and bunch grass.</p>	
6.90 42.31	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 88°50' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Track road, bears North and S. 22° W.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 34, monumented by a squared post, 2 ins. diam., 26 ins. long, firmly set in the ground, dimly mkd.</p> <p>At the corner point,</p> <p>Set the iron post, 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4} \frac{S \ 27}{S \ 34}</math>                      1967</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 5 ins. diam., bears S. 16° E., 28 lks. dist., mkd. <math>\frac{1}{4}</math> S 34 BT.</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears N. 21° W., 17 lks. dist., mkd. <math>\frac{1}{4}</math> S 27 BT.</p> <p>Set the inverted orig. post along with a new cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.</p>	
16.30 31.40 31.50 40.77	<p>N. 89°32' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Track road, bears SE. and NW.</p> <p>Power line, bears N. 0°18' E. and S. 0°18' W.</p> <p>Track road, bears N. 0°18' E. and S. 0°18' W.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p>	



CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>
31.55	<p>N. 1°36' E., bet. secs. 27 and 28.</p> <p>Over gently rolling land, through scattered timber.</p> <p>New highway, bladed gravel, Holbrook to Heber, bears N. 45°50' E. and S. 45°50' W.</p>
41.28	<p>The ¼ sec. cor. of secs. 27 and 28, monumented by a squared post, 2 ins. diam., 26 ins. long, firmly set, mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E           ½           S 28 S 27  1966</p> <p>Set the inverted orig. cor. post along with a new cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.</p>
29.30	<p>N. 0°40' E., beginning new measurement.</p> <p>Over nearly level land, through scattered timber.</p> <p>Track road, bears SE. and NW.</p>
39.91	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E S 21 S 22 S 28 S 27  1966</p> <p>Set a cedar post, 4 ins. diam., 3 ft. long, alongside the cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>
0.06	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°38' W., bet. secs. 22 and 27.</p> <p>Over nearly level land, through scattered timber.</p> <p>Fence, barbed wire, bears N. and S.</p>
19.80	<p>Track road, bears SE. and NW.</p>

Dep. Resurvey, Subdivisional Lines, T.15 N., R.19 E., Arizona

CHAINS		
39.89	<p>The ¼ sec. cor. of secs. 22 and 27, monumented by a squared cedar post, 3 ins. diam., 3 ft. long, mkd. dimly S. on one face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> <math>\frac{S\ 22}{S\ 27}</math>                      1967</p> <p>Set the inverted orig. cor. post alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 86°47' W., beginning new measurement.</p> <p>Over nearly level land, through medium timber.</p>	
5.80	<p>New highway, bladed gravel, Holbrook to Heber, bears N. 36°46' E. and S. 36°46' W.</p>	
33.00	<p>Power line, bears S. 0°20' E. and N. 0°20' W.</p>	
33.50	<p>Track road, bears S. 0°20' E. and N. 0°20' W.</p>	
41.31	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, nearly level.                      Soil, sandy loam.                      Timber, scattered to medium cedar.                      Undergrowth, yellow brush and bunch grass.</p>	
31.60	<p>N. 0°15' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land, through scattered cedar.</p> <p>Wash, 20 lks. wide, 1½ ft. deep, drains NE.</p>	
39.91	<p>The ¼ sec. cor. of secs. 21 and 22, monumented by a squared post, 2½ ins. diam., 3 ft. long, one end charred; marks not visible.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> <math>\frac{S\ 21}{S\ 22}</math>                      1966</p> <p>Set the orig. cor. post along with a new cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>	
9.00	<p>N. 0°42' E., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Old highway, graded gravel, Holbrook to Heber, bears N. 14°10' E. and S. 14°10' W.</p>	

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

<p>CHAINS 39.11</p>	<p>The cor. of secs. 15, 16, 21 and 22, monumented by a sandstone, 16 x 14 x 2 ins., lying loose on ground in an E-W. fence line, mkd. with 3 notches on adjacent faces</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E  <math>\frac{S}{S} \frac{16}{21}   \frac{S}{S} \frac{15}{22}</math>              1966</p> </div> <p>Bury the original cor. alongside the iron post.</p> <p>Land, gently rolling.              Soil, sandy loam.              Timber, scattered cedar.              Undergrowth, rabbit brush and bunch grass.</p>
<p>1.20</p> <p>4.40</p> <p>40.10</p>	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°47' W., bet. secs. 15 and 22.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Gravel highway, Holbrook to Heber, bears N. 6°10' E. and S. 6°10' W.</p> <p>Fence, barbed wire, bears S. 67° E. and N. 67° W.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 22, monumented by a sandstone, 25 x 15 x 4 ins., firmly set in a mound of stone, mkd. <math>\frac{1}{4}</math> on N. face.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E  <math>\frac{1}{4} \frac{S}{S} \frac{15}{22}</math>              1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">An E-W fence bears South, 8 lks. dist.</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>S. 89°05' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p>
<p>.90</p> <p>32.00</p> <p>32.85</p> <p>33.55</p> <p>40.41</p>	<p>Wash, 15 lks. wide, 1 ft. deep, drains N.</p> <p>Power line, bears S. 0°20' E. and N. 0°20' W.</p> <p>Old graded highway, Holbrook to Heber, bears N. 14°10' E. and S. 14°10' W.</p> <p>Cor. of fences, barbed wire, bearing N., E. and W., bears North, 32 lks. dist.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p>

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS		
	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>	
41.02	<p>N. 0°24' W., bet. secs. 15 and 16. Over gently rolling land, through scattered timber. Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E 1/4 S 16   S 15 1966</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p>	
78.40	Track road, bears E. and W.	
79.80	Track road, bears SE. and NW.	
82.05	<p>The cor. of secs. 9, 10, 15 and 16, monumented by a squared post, 2 ins. diam., 2 ft. long, firmly set in ground, mkd. 9-10-15-16. from which one remaining orig. bearing tree A cedar, 12 ins. diam., bears N. 57° E., 51 lks. dist., mkd. T15N R19E S 10 At the corner point Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E S 9   S 10 S16   S 15 1966</p> <p>Set the inverted orig. cor. post alongside the iron post.</p>	
19.60	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar with a few pine. Undergrowth, rabbit brush and bunch grass.</p> <p>From the cor. of secs. 10, 11, 14 and 15. N. 89°19' W., bet. secs. 10 and 15. Over gently rolling land, through widely scattered timber. Old highway, graded gravel, Holbrook to Heber, bears N. 41°45' E. and S. 41°45' W.</p>	

CHAINS							
40.28	<p>The ¼ sec. cor. of secs. 10 and 15, monumented by a sandstone, 16 x 4 x 3 ins., lying loose in a mound of stone, mkd. ¼ on one face.</p> <p>Reset the orig. cor. 10 ins. in the ground and in a mound of stone.</p> <p style="text-align: center;">—————</p> <p>S. 89°41' W., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered timber.</p>						
10.00	Track road, bears irreg. N. and S.						
12.10	Fence, barbed wire, bears N. 14° E. and S.						
30.70	Power line, bears N. 0°23' E. and S. 0°23' W.; track road follows along under line.						
40.12	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedars. Undergrowth, rabbit brush and bunch grass.</p>						
	N. 0°14' W., bet. secs. 9 and 10.						
	Over gently rolling land, through scattered timber.						
40.36	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.						
42.00	Ravine, drains N. 22° E.						
64.30	Ravine, drains East.						
68.00	Fence line, old, bears irreg. SE. and NW.						
75.40	Ravine, drains irreg. N.						
80.72	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a sandstone, 20 x 6 x 6 ins., firmly set in a mound of stone, mkd. with 3 notches on one face and 5 notches on another.</p> <p>At the corner point</p> <p>Set the iron post, 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T15N R19E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table> <p>1966</p> </div> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Land, gently rolling with deep ravines. Soil, sandy loam and rocky surfaces. Timber, scattered cedar with a few pines. Undergrowth, rabbit brush and bunch grass.</p>	T15N R19E		S 4	S 3	S 9	S 10
T15N R19E							
S 4	S 3						
S 9	S 10						

CHAINS		
	<p>From the cor. of secs. 2, 3, 10 and 11.</p>	
	<p>S. 89°49' W., bet. secs. 3 and 10.</p>	
	<p>Over gently rolling land, through scattered timber.</p>	
16.30	<p>Track road, bears NE. and SW.</p>	
40.80	<p>The ¼ sec. cor. of secs. 3 and 10, monumented by a squared post, 3 ins. diam., 26 ins. long, lying loose on ground, mkd. ¼ on one side. Reset the orig. cor. 15 ins. in the ground.</p>	
	<hr/> <p>N. 89°57' W., beginning new measurement.</p>	
	<p>Over gently rolling land, through scattered timber.</p>	
30.40	<p>Power line, bears N. 0°23' E. and S. 0°23' W.</p>	
38.30	<p>Ravine, drains N. 22° E.</p>	
40.63	<p>The cor. of secs. 3, 4, 9 and 10.</p>	
	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>	
	<hr/> <p>N. 0°08' E., bet. secs. 3 and 4.</p>	
	<p>Over gently rolling land, through medium timber.</p>	
7.30	<p>Ravine, drains S. 67° E. for 4.00 chs. to a wash draining N. 22° E.</p>	
10.35	<p>Fence, barbed wire, bears N. 35°15' E. and S. 35°15' W.</p>	
40.65	<p>The ¼ sec. cor. of secs. 3 and 4, monumented by a sandstone, 12 x 10 x 3 ins., lying loose in a mound of stone, mkd. ¼ on one side.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 15 ins. in the ground, mound of stone to the top, brass cap mkd.</p>	
	<p style="text-align: center;">T15N R19E S 4 <sup>¼</sup>   S 3 1967</p>	
	<p>Bury the orig. cor. alongside the iron post.</p>	
	<p>Corner falls on S. bank of ravine, draining E.-SE.</p>	
	<hr/> <p>N. 2°48' E., beginning new measurement.</p>	
	<p>Over gently rolling land, through medium timber.</p>	
1.80	<p>Ravine, drains E.-SE.</p>	
36.70	<p>Fence, barbed wire, bears S. 66°45' E. and N. 66°45' W.</p>	

CHAINS	
40.79	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam and bare rock. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p>
36.50	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 2°17' W., bet. secs. 32 and 33.</p> <p>Over nearly level land, through scattered timber.</p> <p>New highway, black top, Holbrook to Heber, bears N. 45°50' E. and S. 45°50' W.</p>
37.73	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E S 32   <sup>¼</sup> S 33 1966</p>
75.46	<p>Set a cedar post, 4 ins. diam., 3 ft. long, alongside the iron post.</p> <p>The cor. of secs. 28, 29, 32 and 33, monumented by a squared post, 2 ins. diam., 3 ft. long, lying loose on the ground, mkd. with 32 on one side.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E S 29   S 28 S 32   S 33 1966</p> <p>Set the inverted orig. post along with a new cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.</p> <p>Land, nearly level to gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>
34.47	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 84°58' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land, through medium timber.</p> <p>Highway from Holbrook to Heber, new black top, bears N. 45°56' E. and S. 45°56' W.</p>
40.58	<p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS		
81.16	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{28}{33}</math>                      1967</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, medium cedar.                      Undergrowth, rabbit brush and bunch grass.</p>	
23.40	<p>N. 2°51' E., bet. secs. 28 and 29.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Old highway, graded gravel, Holbrook to Heber, bears N. 48° E. and S. 48° W.</p>	
27.95	<p>Graded road to Hutcherson's Ranch, bears N. 67°40' E. and S. 67°40' W.</p>	
42.20	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 29, monumented by a squared post, 2 ins. diam., 2<math>\frac{1}{2}</math> ft. long, lying loose on the ground, mkd. <math>\frac{1}{4}</math> on one side, an unmarked stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> S 29   S 28                      1966</p>	
39.32	<p>Set the inverted orig. post along with a new cedar post, 2 ins. diam., 4 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°45' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p> <p>The cor. of secs. 20, 21, 28 and 29, monumented by a sandstone, 24 x 20 x 4 ins., firmly set in a mound of stone, mkd. with 4 notches on one side and 2 notches on another side.</p> <p>At the corner point</p> <p>Set the iron post, 4 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> S 20   S 21  <math>\frac{1}{4}</math> S 29   S 28                      1966</p>	



CHAINS		
	<p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Land, gently rolling. Soil, sandy loam, bare rock. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>	
<p>4.00</p> <p>13.90</p> <p>41.26</p> <p>70.00</p> <p>82.52</p>	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 85°16' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land, through medium timber.</p> <p>Track road, bears SE. and NW.</p> <p>Old highway, graded gravel, Holbrook to Heber, bears N. 18°40' E. and curves SW.</p> <p>Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ <math>\frac{S\ 21}{S\ 28}</math> 1967</p> <p>Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Sag, drains N. 10° W.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p>	
<p>36.20</p> <p>40.63</p>	<p>N. 0°22' E., bet. secs. 20 and 21.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Low swale, drains NW.</p> <p>The ¼ sec. cor. of secs. 20 and 21, monumented by a sandstone, 30 x 15 x 4 ins., firmly set, mkd. ¼ on W. face, and with a mound of stone W. of the cor.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E S 20   <math>\frac{1}{4}</math> S 21 1966</p> <p>Deposit the orig. cor. in the rebuilt mound of stone W. of the cor.</p>	

CHAINS						
40.49	<p>N. 0°20' E., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p> <p>The cor. of secs. 16, 17, 20 and 21, monumented by a sandstone, 22 x 15 x 2 ins., firmly set in a mound of stone, mkd. with 3 notches on S. face and 4 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table border="1" style="margin: auto;"> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> <p>1966</p> </div> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>A cor. of fences bearing N. and W., bears N. 9°45' E., 1.78 chs. dist.</p> <p>Land, gently rolling. Soil, sandy loam and solid rock. Timber, scattered cedar. Undergrowth, rabbit brush, bunch grass.</p>	S 17	S 16	S 20	S 21	
S 17	S 16					
S 20	S 21					
12.50 41.10	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 86°40' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains N.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 16</td> <td></td> </tr> <tr> <td>¼ S 21</td> <td></td> </tr> </table> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">An E.-W. fence, bears North, 7 lks. dist.</p> <p style="padding-left: 40px;">An old house foundation, bears S. 24°43' W., 15.43 chs. dist.</p>	¼ S 16		¼ S 21		
¼ S 16						
¼ S 21						
48.00	<p>Top of rise.</p>					
82.20	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>					

Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 19 E., Arizona

CHAINS		
	<p>N. 2°15' W., bet. secs. 16 and 17.</p>	
	<p>Over rolling land, through medium timber.</p>	
1.75	<p>Fence, barbed wire, bears irregularly E. and W.</p>	
6.80	<p>Ravine, drains N. 22° E.</p>	
40.64	<p>The ¼ sec. cor. of secs. 16 and 17, monumented by a squared post, 2 ins. diam., 2 ft. long, lying loose on ground, mkd. ¼ on one side. Record called for a sandstone.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 18 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T15N R19E</p>	
	<p style="text-align: center;">S 17   S 16</p>	
	<p style="text-align: center;">1966</p>	
	<p>Set the inverted squared post alongside the iron post.</p>	
	<p>Raise a mound of stone W. of the cor.</p>	
	<hr style="width: 20%; margin: auto;"/>	
	<p>N. 3°13' E., beginning new measurement.</p>	
	<p>Over gently rolling land, through scattered timber.</p>	
21.10	<p>Track road, bears NE. and SW.</p>	
40.68	<p>The cor. of secs. 8, 9, 16 and 17, monumented by a squared stake, 3 ins. diam., 2 ft. long, mkd. 8 on one side, loosely set and with a rock and cedar post alongside.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T15N R19E</p>	
	<p style="text-align: center;">S 8   S 9</p>	
	<p style="text-align: center;">S 17   S 16</p>	
	<p style="text-align: center;">1966</p>	
	<p>Set the inverted squared stake alongside the iron post.</p>	
	<p>Raise a mound of stone W. of the corner</p>	
	<p>Land, rolling to gently rolling.</p>	
	<p>Soil, rocky to sandy loam.</p>	
	<p>Timber, medium to scattered cedar</p>	
	<p>Undergrowth, rabbit brush and bunch grass.</p>	
	<hr/>	
	<p>From the cor. of secs. 9, 10, 15 and 16.</p>	
	<p>S. 86°01' W., bet. secs. 9 and 16.</p>	
	<p>Over gently rolling land; medium cedar.</p>	
1.80	<p>Track road, bears irregularly N. and S.</p>	

Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 19 E., Arizona

<p>CHAINS 11.10</p> <p>39.80</p> <p>40.47</p> <p>51.10</p> <p>67.80</p> <p>80.94</p>	<p>Ravine, drains N.</p> <p>Ravine, drains N.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{9}{16}</math> 1967</p> <p>Leave medium timber; enter scattered timber.</p> <p>Track road, bears NE. and SW.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy loam with rocky spots. Timber, medium to scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>
<p>40.36</p> <p>14.10</p> <p>21.10</p> <p>45.00</p> <p>45.19</p>	<p>N. <math>1^{\circ}16'</math> W., bet. secs. 8 and 9.</p> <p>Over gently rolling land, through scattered timber.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 8 and 9, monumented by a sandstone, 16 x 5 x 2 ins., firmly set in a mound of stone, mkd. <math>\frac{1}{4}</math> on one side.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E <math>\frac{1}{4}</math> S 8   S 9 1966</p> <p>Deposit the orig. cor. in the mound surrounding the iron post</p> <p style="text-align: center;">—————</p> <p>N. <math>1^{\circ}09'</math> E., beginning new measurement.</p> <p>Over gently rolling land, through medium timber</p> <p>Fence, barbed wire, bears irregularly E. and W.</p> <p>Wash, 50 lks. wide, 3 ft. deep, drains NE.</p> <p>Leave medium timber; enter widely scattered timber.</p> <p>The cor. of secs. 4, 5, 8 and 9, monumented by a sandstone, 18 x 12 x 3 ins., lying loose on ground, mkd. with 4 notches on one side and 5 notches on another; also a squared post, firmly set in ground, marks illegible, alongside the sandstone.</p>

CHAINS	
	<p>At the corner point</p> <p>Set the iron post, 20 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{S\ 5}{S\ 8}   \frac{S\ 4}{S\ 9}</math></p> <p style="text-align: center;">1966</p> <p>Bury the orig. cor. and set the squared post alongside the iron post.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, scattered to medium to widely scattered cedar.                      Undergrowth, rabbit brush and bunch grass.</p>
1.30	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°19' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land, through widely scattered timber.</p>
40.20	<p>Old fence line, bears irreg. N. and S.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 9, monumented by a squared post, 2 ins. diam., 30 ins. long, firmly set, mkd. <math>\frac{1}{4}</math> on N. face.</p>
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4} \frac{S\ 4}{S\ 9}</math></p> <p style="text-align: center;">1967</p> <p>Set the inverted squared post alongside the iron post.                      Raise a mound of stone N. of the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>S. 89°37' W., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered timber.</p>
21.80	<p>Track road, bears irreg. N. and S.</p>
32.00	<p>Ravine, drains NE.</p>
40.15	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, widely scattered cedar.                      Undergrowth, rabbit brush and bunch grass.</p>

CHAINS		
	<p>N. 2°55' E., bet. secs. 4 and 5.</p> <p>Over gently rolling land, through widely scattered timber.</p>	
12.20	<p>Track road, bears E-SE. and W-NW.</p>	
41.47	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5, monumented by a squared post, 3 ins. diam., 2 ft. long, mkd. <math>\frac{1}{4}</math> on one side and lying loose on the ground.</p>	
	<p>At the corner point</p> <p>Set the iron post 13 ins. in the ground, mound of stone to the top, brass cap mkd.</p>	
	<p style="text-align: center;">T15N R19E <math>\frac{1}{4}</math> S 5   S 4 1966</p>	
	<p>Set the inverted squared post along with a new cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.</p>	
	<p style="text-align: center;">—————</p> <p>N. 0°32' E., beginning new measurement.</p> <p>Over gently rolling land, through widely scattered timber.</p>	
40.35	<p>Fence, barbed wire, bears S. 89°40' E. and N. 89°40' W.</p>	
40.42	<p>Track road, bears S. 89°40' E. and N. 89°40' W.</p>	
40.52	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>	
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 3°02' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, through scattered timber.</p>	
29.46	<p>Highway, graded gravel, old highway from Holbrook to Heber, bears N. 51°05' E. and S. 58°30' W.</p>	
38.06	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E <math>\frac{1}{4}</math> S 31   S 32 1967</p> <p>Set a cedar post, 4 ins. diam., 5<math>\frac{1}{2}</math> ft. long, alongside the iron post.</p>	

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS					
52.66	Track road, bears NE. and SW.				
76.12	<p>The cor. of secs. 29, 30, 31 and 32, monumented by a squared post, 2½ ins. diam., 28 ins. long, firmly set in the ground, marked illegibly.</p> <p>At the corner point</p> <p>Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table border="1" style="margin: auto;"> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A stock pond, bears N. 84°47' E., 14.10 chs. dist.</p> <p style="padding-left: 40px;">A corral, bears S. 70°59' E., 16.90 chs. dist.</p> <p>Set the inverted squared post along with a new cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.</p>	S 30	S 29	S 31	S 32
S 30	S 29				
S 31	S 32				
7.24	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 82°00' W., bet. secs. 29 and 32.</p> <p>Over gently rolling land, through scattered cedar.</p> <p>7.24 Natural gas line, bears S. 7°20' E. and N. 7°20' W.</p> <p>7.54 Track road, bears S. 7°20' E. and N. 7°20' W.</p> <p>21.28 Old highway, graded gravel, Holbrook to Heber, bears N. 47°30' E. and S. 47°30' W.</p> <p>37.13 The ¼ sec. cor. of secs. 29 and 32, monumented by a squared post, 2 ins. diam., 2 ft. long, firmly set, mkd. ¼ on one side.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R19E</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 29</td> <td></td> </tr> <tr> <td>¼ S 32</td> <td></td> </tr> </table> <p>1967</p> </div> <p>Set the inverted squared post along with a new cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 82°37' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered timber.</p>	¼ S 29		¼ S 32	
¼ S 29					
¼ S 32					

Dep. Resurvey, Subdivisional Lines, T.15 N., R.19 E., Arizona

CHAINS	
28.77	Track road, bears NE. and SW.
29.78	Track road, bears SE. and NW.
43.72	The cor. of secs. 29, 30, 31 and 32.  Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.
	S. 89°10' W., bet. secs. 30 and 31.  Over gently rolling land, through scattered timber.
37.40	Track road, bears SE. and NW.
37.94	The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented by a squared post, 2 ins. diam., 26 ins. long, firmly set, dimly mkd.  At the corner point  Set the iron post, 20 ins. in the ground, brass cap mkd.  <div style="text-align: center;">                         T15N R19E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{30}{31}</math>                          1967                     </div> Set the inverted squared post along with a new cedar post, 2½ ins. diam., 3 ft. long, alongside the iron post.
15.30	N. 83°03' W., beginning new measurement.  Over gently rolling land, through scattered timber.
37.12	Wash, 15 lks. wide, 1 ft. deep, drains SW.  The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.  Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, rabbit brush and bunch grass.
18.20	From the cor. of secs. 29, 30, 31 and 32.  N. 2°21' E., bet. secs. 29 and 30.  Over gently rolling land, through scattered timber.
34.80	Track road, bears SE. and NW.
41.80	Graded road, Hutcherson's Ranch, bears S. 73° E. and N. 73° W.
41.80	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.  Set the iron post 22 ins. in the ground, brass cap mkd.



CHAINS	
	<p style="text-align: center;">T15N R19E  <math>\frac{1}{2}</math>                      S 30   S 29                      1967</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p>
42.00	<p>Leave scattered timber; enter open range land.</p>
83.61	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a sandstone, 12 x 4 x <math>1\frac{1}{2}</math> ins., lying loose in a mound of stone, mkd. with 3 notches on one side.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E                      S 19   S 20                      S 30   S 29                      1967</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, scattered cedar, first half mile, to none.                      Undergrowth, rabbit brush and bunch grass.</p>
4.00	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 88°46' W., bet. secs. 20 and 29.</p> <p>Over gently rolling land, through medium timber.</p> <p>Leave timber; enter open range land.</p>
17.75	<p>Natural gas line, bears S. 7°10' E. and N. 7°10' W.</p>
18.05	<p>Track road, bears S. 7°10' E. and N. 7°10' W.</p>
38.46	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
42.70	<p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math> S 20                      S 29                      1967</p> <p>Set a cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.</p> <p>Track road, bears N. and S.</p>
76.93	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, none.                      Undergrowth, rabbit brush and bunch grass.</p>

CHAINS		
39.63	<p>N. 88°38' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land.</p> <p>The ¼ sec. cor. of secs. 19 and 30, monumented by a squared and sharpened cedar post, 4 ins. diam., 30 ins. long, loosely set, dimly md. Record called for a sandstone.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ S 19 S 30 1967</p> <p>Set the squared and sharpened cedar post along with a new cedar post, 3 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 88°32' W., beginning new measurement.</p> <p>Over gently rolling land.</p>	
38.51	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, rabbit brush and bunch grass.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 4°23' W., bet. secs. 19 and 20.</p> <p>Over gently rolling land.</p>	
39.04	<p>The ¼ sec. cor. of secs. 19 and 20, monumented by a sandstone, 24 x 15 x 3 ins., loosely set, mkd. ¼ on one side.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E ¼ S 19   S 20 1967</p> <p>Bury the orig. cor. alongside the iron post.</p> <p>Raise a mound of stone W. of the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 3°57' E., beginning new measurement.</p> <p>Over gently rolling land.</p>	
41.63	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>	

CHAINS	
	<p>Set the iron post 6 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{S}{18}   \frac{S}{17}</math>  <math>\frac{S}{19}   \frac{S}{20}</math>                      1967</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, none.                      Undergrowth, sage, rabbit brush and bunch grass.</p>
<p>2.10</p> <p>15.20</p> <p>28.90</p> <p>29.20</p> <p>38.79</p> <p>77.58</p>	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°17' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Ravine, drains N.</p> <p>Leave scattered timber; enter open range land.</p> <p>Natural gas line, bears S. 7°10' E. and N. 7°10' W.</p> <p>Track road, bears S. 7°10' E. and N. 7°10' W.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4} \frac{S}{17}</math>  <math>\frac{S}{20}</math>                      1967</p> <p>Set a cedar post, 3 ins. diam., 5 ft. long, alongside the iron post.</p> <p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling.                      Soil, sandy loam.                      Timber, scattered cedar, first 15 chains, then none.                      Undergrowth, sage, rabbit brush and bunch grass.</p>
<p>38.90</p>	<p>N. 87°39' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4} \frac{S}{18}</math>  <math>\frac{S}{19}</math>                      1967</p> <p>Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.</p>

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS	
77.91	Fence, barbed wire, bears N. 0°10' E. and S. 0°10' W.
77.98	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, sage, rabbit brush and bunch grass.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°45' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p>
2.40	Fence, barbed wire, bears S. 89°30' E. and N. 89°30' W.
3.10	Track road, bears irreg. E. and W.
41.53	<p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>  S 18   S 17  1967</p> <p>Set a post, 3 ins. diam., 4 ft. long, alongside the iron post.</p>
83.06	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15N R19E  S 7   S 8  S 18   S 17  1967</p> <p>Set a post, 3 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, sage, rabbit brush and bunch grass.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 86°50' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land, through scattered timber.</p>
24.30	Ravine, drains N.
34.28	Natural gas line, bears N. 11°10' E. and S. 11°10' W.

CHAINS	
34.53	Track road, bears N. 11°10' E. and S. 11°10' W.; leave timber.
40.74	<p>The ¼ sec. cor. of secs. 8 and 17, monumented by a sandstone, 16 x 9 x 2 ins., loosely set in a mound of stone, mkd. ¼ on one side.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{S}{S} \frac{8}{17}</math>            ¼            1967</p> <p>Deposit the orig. cor. alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°11' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
29.00	Top of rise.
38.66	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling.            Soil, sandy loam.            Timber, scattered cedar first 35.00 chs., then none.            Undergrowth, sage, rabbit brush and bunch grass.</p>
	<p>N. 88°33' W., bet. secs. 7 and 18.</p> <p>Over gently rolling land.</p>
17.40	Fence, broken barbed wire, bears N. 71°40' E. and S. 71°40' W.
38.47	<p>Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{S}{S} \frac{7}{18}</math>            ¼            1967</p> <p>Set a post, 3 ins. diam., 3 ft. long, alongside the iron post.</p>
76.35	Track road, bears N. and S.
76.68	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.</p> <p>Land, gently rolling.            Soil, sandy loam.            Timber, none.            Undergrowth, sage, rabbit brush and bunch grass.</p>

CHAINS	
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 2°04' W., bet. secs. 7 and 8.</p> <p>Over gently rolling land.</p>
12.08	<p>Fence, broken barbed wire, bears N. 71°40' E. and S. 71°40' W.</p>
41.55	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8, monumented by a sandstone, 20 x 8 x 3 ins., lying loose on the ground, mkd. <math>\frac{1}{4}</math> on one side.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  <math>\frac{1}{4}</math>  S 7   S 8  1967</p> <p>Deposit the orig. cor. in the mound surrounding the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 3°35' E., beginning new measurement.</p> <p>Over gently rolling land.</p>
36.85	<p>Track road, bears NE. and SW.</p>
40.90	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E  S 6   S 5  S 7   S 8  1967</p> <p>Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Land, gently rolling.  Soil, sandy loam.  Timber, none.  Undergrowth, rabbit brush and bunch grass.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°44' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p>
4.60	<p>Track road, bears NE. and SW.</p>
17.60	<p>Natural gas line, bears N. 11°20' E. and S. 11°20' W.</p>
17.90	<p>Track road, bears N. 11°20' E. and S. 11°20' W.</p>

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 19 E., Arizona

CHAINS	
39.17	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, 10 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> 5 8 1967</p>
74.56	<p>Track road, bears NE. and SW.</p>
78.34	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, rabbit brush and bunch grass.</p>
38.60	<p>N. 89°03' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land.</p> <p>Track road, bears NE. and SW.</p>
39.31	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.</p>
47.20	<p>Track road, bears NE. and SW.</p>
60.70	<p>Track road, bears SE. and NW.</p>
77.64	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, rabbit brush and bunch grass.</p>
25.10	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°48' E., bet. secs. 5 and 6.</p> <p>Over gently rolling land.</p> <p>Track road, bears NE. and SW.</p>
40.82	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">A stock pond, bears S. 72°40' E., 15.90 chs. dist.</p>
82.20	<p>Fence, barbed wire, bears N. 89°40' E. and S. 89°40' W.</p>
82.30	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Timber; none. Undergrowth, rabbit brush and bunch grass.</p>

Subdivision, Section 12, T. 15 N., R. 19 E., Arizona

CHAINS		
20.67	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 12 and 13.</p> <p>N. <math>1^{\circ}21'</math> E., on the N-S center line of sec. 12.</p> <p>Over gently rolling land, through medium timber.</p> <p>Point for the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 12.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E CS <math>\frac{1}{16}</math> S 12 1967</p> <p>Deposit glass in hole and set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.</p>	
35.70	<p>Track road, bears E. and W.</p>	
41.34	<p>Point for the C <math>\frac{1}{4}</math> sec. cor. of sec. 12.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E C <math>\frac{1}{4}</math> S 12 1967</p> <p>Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.</p>	
81.98	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.</p> <p>S. <math>89^{\circ}14'</math> W., on the E-W. center line of sec. 12.</p> <p>Over gently rolling land, through medium timber.</p> <p>12.30 Ravine, drains N.</p> <p>20.57 Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 12.</p> <p>Set the iron post over an "X" chiseled on solid rock, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">T15N R19E CE <math>\frac{1}{16}</math> S 12 1967</p> <p>41.14 The C <math>\frac{1}{4}</math> sec. cor. of sec. 12.</p> <p>52.70 Track road, bears SE. and NW.</p> <p>81.04 The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p>	



CHAINS		
<p>20.43</p> <p>40.87</p>	<p>From the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0°50' E., on the N-S center line of the SE ¼ of sec. 12.</p> <p>Point for the SE 1/16 sec. cor. of sec. 12.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15N R19E SE <math>\frac{1}{16}</math> S 12 1967</p> <p>Raise a mound of stone W. of the iron post.</p> <p>The C-E 1/16 sec. cor. of sec. 12.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p>	
<p>20.75</p> <p>41.51</p>	<p>From the S 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.</p> <p>S. 88°37' W., on the E-W center line of the SE ¼ of sec. 12.</p> <p>Over gently rolling land, through medium timber.</p> <p>The SE 1/16 sec. cor. of sec. 12.</p> <p>The C-S 1/16 sec. cor. of sec. 12.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium cedar. Undergrowth, rabbit brush and bunch grass.</p>	
<p>General Description</p>		
<p>The land in Township 15 North, Range 19 East, is gently rolling. The soil is sandy loam. Drainage is mostly to the north. The elevation ranges from about 5,600 feet to 6,200 feet above sea level. Grazing of livestock is the primary interest as there is good grass throughout the township. Stock ponds afford a water supply.</p> <p>The Holbrook to Heber highway cuts northeast to southwest across the township. Many track roads give good access to most of the township. A power line bears North and South through the center of the township and a natural gas line bears North and South through the western portion of the township.</p>		

Form 4-680  
(June 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Howard H. Thomas	Surveying Technician, Supv.
Martin W. Fuller	Surveying Aid
Arvel R. Jones	Surveying Aid
Miguel Luna	Surveying Aid
Jerrold E. Knight	Supv., Cadastral Surveyor
Ray E. Thiessen	Supv., Surveying Technician
Ronald G. Williams	Surveying Aid

CERTIFICATE OF SURVEY

1/ We, Boyd S. Owens and Kenneth D. Herman, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of August, 1966, we have made a dependent resurvey of the exteriors and subdivisional lines, and a survey of the subdivision of Section 12 of Township 15 North, Range 19 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~<sup>us</sup> and under ~~my~~<sup>our</sup> direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 28, 1968  
(Date)

*Boyd S. Owens*  
(Cadastral Surveyor)

March 28, 1968  
(Date)

*Kenneth D. Herman*  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date JAN 6 1969

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the dependent resurvey of the exteriors and subdivisional lines, and a survey of the subdivision of Section 12 of Township 15 North, Range 19 East, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens and Kenneth D. Herman, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUN 4 1969  
(Date)

*Thomas A. Tillman*  
(Chief, Division of Engineering)  
Acting Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Engineering)~~