

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

EAST and WEST BOUNDARIES

and

SUBDIVISIONAL LINES

and the

ESTABLISHMENT of the NORTH

1/2 SECTION CORNERS of SECTIONS 4 and 6,

and

SURVEY of SUBDIVISIONS

in SECTION 16,

TOWNSHIP 20 N., RANGE 19 E.

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Louis D. Gilbert Supervisory Cadastral Surveyor

Under special instructions dated June 23, 1967, which provided for the surveys included under Group Number 459, approved June 26, 1967, and assignment instructions dated June 23, 1967.

Survey commenced August 10, 1967

Survey completed August 30, 1967

INDEX DIAGRAM

Township 20 North, Range 19 East,
 $\frac{1}{4}$ $\frac{1}{4}$

7	6 36	37 5 36	29 4 29	24 8 23	18 2 18	13 1 12	4
6	7 35	35 8 34	28 9 28	23 10 22	17 11 17	11 12 11	3
6	18 34	34 17 33	27 16 27	22 15 21	16 14 16	10 13 10	3
5	19 33	33 20 32	26 21 26	21 22 20	15 23 15	10 24 9	2
5	30 32	32 29 31	25 28 25	20 27 19	14 26 14	9 25 8	2
4	31 31	31 32 32	25 33 25	19 34 19	13 35 13	7 36 7	1

Subdivision of Section 16---Page 38

Township 20 North, Range 19 East
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The south boundary of Township 20 North, Range 19 East was surveyed in 1882 by H. Meyrick. The west one mile of the south boundary was retraced in 1944 by Forrest and Warner. The south boundary was resurveyed in 1966 under Group No. 449 by Owens and Oviatt. The east and west boundaries were surveyed in 1882 by F. Follman. Owens and Oviatt retraced the east and west boundaries and re-monumented the closing township corners with regulation iron posts in 1966. These closing corners were needed for control of the resurvey of Township 19 North, Range 19 East under Group 449. The north boundary, the Fifth Standard Parallel North, was surveyed in 1882 by F. Follman and resurveyed in 1947 by Ty White. The subdivisional lines were surveyed in 1882 by F. Follman. A portion of the subdivisional lines were retraced in 1944 by Forrest and Warner.</p> <p>The following field notes are those of a dependent resurvey of the east and west boundaries and subdivisional lines, designed to restore the corners in their original location according to the best available evidence, together with the establishment of the north $\frac{1}{4}$ section corners of sections 4 and 6, and the survey of the subdivision in section 16.</p> <p>This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated June 23, 1967.</p> <p>Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, $2\frac{1}{2}$ inches in diameter, flanged at the base and with a brass cap riveted to the top.</p> <p>The geographic position of the SE. corner of the township as determined by traverse to U.S.C. & G. S. triangulation station "ASYLUM," located in section 16, T. 20 N., R. 20 E., is Latitude $35^{\circ}04'50''$ N., and Longitude $110^{\circ}16'15.4''$ W.</p> <p>The mean magnetic declination was observed to be 14° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey East Boundary, T. 20 N., R. 19 E.</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by F. Follman in 1882</p> <hr/> <p>From the cor. of Tps. 19 and 20 N., Rs. 19 and 20 E., monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field note record of the dependent resurvey of the E. bdy., T. 19 N., R. 19 E., in 1966.</p> <p>N. $0^{\circ}52'$ E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p> <p>40.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey
East Boundary, T. 20 N., R. 19 E.

CHAINS		
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E R20E $\frac{1}{4}$ S 36 S 31 1967</p> <p>Raise a mound of stone W. of the cor.</p>	
55.20	Wash, 45 lks. wide, 6 ft. deep, drains N. 50° E.	
71.20	Wash, 20 lks. wide, 3 ft. deep, drains W.	
80.06	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E R20E <u>S 25 S 30</u> S 36 S 31 1967</p> <p>Land, rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>	
	<p>N. 0°52' E., bet. secs. 25 and 30.</p> <p>Over gently rolling land.</p>	
20.015	<p>Point for the S 1/16 sec. cor. of secs. 25 and 30. This corner is not monumented.</p>	
40.03	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>	
42.40	Wash, 5 lks. wide, 2 ft. deep, drains E., thence over badlands.	
49.80	Top of mesa, bears E. and S. 45° W., thence over gently rolling land.	
60.045	Point for the N 1/16 sec. cor. of secs. 25 and 30. This corner is not monumented.	
80.06	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Land, gently rolling to rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>	
	<p>N. 0°52' E., bet. secs. 19 and 24.</p> <p>Over gently rolling land.</p>	

Dependent Resurvey
East Boundary, T. 20 N., R. 19 E.

CHAINS	
3.80	Wash, 15 lks. wide, 2 ft. deep, drains NE.
25.70	Track road, bears E. and W.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
80.06	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. $0^{\circ}52'$ E., bet. secs. 13 and 18. Over nearly level land.
4.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° E.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
56.70	Track road, bears N. 20° E. and S. 20° W.
80.06	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. $0^{\circ}52'$ E., bet. secs. 7 and 12. Over nearly level land.
6.50	Track road, bears S. 10° E. and N. 10° W.
18.90	Fence, barbed wire, bears S. 75° E. and N. 75° W.
26.30	Track road, bears NE. and W.
30.40	Wash, 1.25 chs. wide, 6 ft. deep, drains W.
31.50	Track road, bears SE. and NW.
34.20	Track road, bears E. and W.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
42.00	Track road, bears N. 80° E. and S. 80° W.
55.10	Track road, bears SE. and NW.
58.50	Wash, 60 lks. wide, 6 ft. deep, drains NW.
69.70	Fence, barbed wire, bears N. 60° E. and S. 60° W.
72.10	SW. cor. of pond.

Dependent Resurvey
West Boundary, T. 20 N., R. 19 E.

CHAINS	
	<p>From the cor. of Tps. 19 and 20 N., Rs. 18 and 19 E., monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the dependent resurvey of the W. bdy., T. 19 N., R. 19 E., in 1966.</p>
	<p>N. 1°07' E., bet. secs. 31 and 36.</p>
	<p>Over nearly level land.</p>
18.00	<p>Fence, barbed wire, bears E. and W.</p>
40.03	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
54.90	<p>Wash, 1.00 ch. wide, 2 ft. deep, drains SE.</p>
61.20	<p>Wash, 30 lks. wide, 2 ft. deep, drains SW. from NW.</p>
76.40	<p>Track road, bears E. and W.</p>
80.06	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
	<p>Land, nearly level to gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 1°07' E., bet. secs. 25 and 30.</p>
	<p>Over gently rolling land.</p>
20.80	<p>Track road, bears SE. and NW.</p>
40.03	<p>Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
47.80	<p>Underground pipe line, bears S. 19°45' E. and N. 19°45' W.</p>
80.06	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 1°07' E., bet. secs. 19 and 24.</p>
	<p>Over gently rolling land.</p>
40.03	<p>Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
46.80	<p>Track road, bears N. 40° E. and S. 40° W.</p>
63.30	<p>Wash, 20 lks. wide, 4 ft. deep, drains S. 70° W.</p>
67.20	<p>Fence, barbed wire, bears E. and W.</p>

Dependent Resurvey
West Boundary, T. 20 N., R. 19 E.

CHAINS 69.50	SW. cor. of stock pond, bears East, 5.00 chs. dist., 4.00 chs. long, 2.00 chs. wide.
80.06	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented. Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 1°07' E., bet. secs. 13 and 18. Over nearly level land.
40.03	Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
80.06	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented. Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 1°07' E., bet. secs. 7 and 12. Over rolling land.
21.00	Fence, barbed wire, bears NE. and SW.
40.03	Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
47.30	Wash, 10 lks. wide, 2 ft. deep, drains W.
52.20	Top of spur, slopes SW.
62.70	Fence, barbed wire, bears E. and W.
80.06	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 23 ins. in the ground, brass cap mkd. T20N R18E R19E S 1 S 6 S12 S 7 1967 Deposit glass in hole. Land, rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	N. 1°07' E., bet. secs. 1 and 6. Over nearly level land.
13.90	Track road, bears N. 80° E. and S. 80° W.
33.90	Wash, 20 lks. wide, 2 ft. deep, drains W.
40.03	Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground, brass cap mkd.
	T20N R18E R19E ¼ S 1 S 6 1967
	Set a wooden post, 4 ins. square, 6 ft. long, alongside the cor.
49.60	Wash, 1.00 ch. wide, 3 ft. deep, drains W.
64.60	Wash, 30 lks. wide, 2 ft. deep, drains SW., thence over rolling land.
80.00	Intersect the closing cor. of Tps. 20 N., Rs. 18 and 19 E., on the Fifth Standard Parallel North, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the retracement of the W. bdy. of T. 20 N., R. 19 E., in 1966. from which The Standard cor. of Tps. 21 N., Rs. 18 and 19 E., bears S. 89°58' E., 15.83 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey of the Fifth Standard Parallel North in 1947. Land, nearly level to rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
Dependent Resurvey of the Subdivisional Lines Township 20 North, Range 19 East	
Reestablishment of the Survey Executed by F. Follman, in 1882	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the dependent resurvey of the N. bdy. of T. 19 N., R. 19 E., in 1966. N. 0°52' E., bet. secs. 35 and 36. Over rolling badlands.
5.30	Wash, 20 lks. wide, 3 ft. deep, drains W.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 35 S 36 1967</p> <p>Leave badlands, thence over gently rolling land.</p>
49.90	Wash, 80 lks. wide, 5 ft. deep, drains NW.
76.30	Wash, 1.40 chs. wide, 3 ft. deep, drains W.
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E S 26 S 25 S 35 S 36 1967</p> <p>Land, rolling badlands to gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. S. 89°45' W., bet. secs. 25 and 36. Over rolling badlands.</p>
11.00	Leave badlands, thence over gently rolling land.
29.70	Wash, 1.50 chs. wide, 3 ft. deep, drains NW.
33.50	Wash, 1.00 ch. wide, 3 ft. deep, drains S. 20° W.
39.90	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 25 S 36 1967</p> <p>from which</p> <p style="padding-left: 40px;">A stock pond, bears S. 20°57' E., 56.24 chs. dist.</p>
46.90	Track road, bears N. and S.
52.20	Wash, 1.00 ch. wide, 3 ft. deep, drains NW.
60.60	Same wash, drains S. 35° W.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
79.80	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling badlands to gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 0° 51' E., bet. secs. 25 and 26.</p> <p>Over gently rolling land.</p>
28.00	<p>Enter rolling badlands.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T20N R19E ½ S 26 S 25 1967</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T20N R19E S 23 S 24 S 26 S 25 1967</p> <p>Deposit glass in hole.</p> <p>Land, rolling badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89° 41' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p>
7.20	<p>Wash, 10 lks. wide, 2 ft. deep, drains NE.</p>
34.00	<p>Track road, bears N. and S.</p>
39.92	<p>Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Enter rolling badlands.</p>
79.84	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, gently rolling and badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>

Dependent Resurvey
 Subdivisional Lines, T. 20 N , R 19 E.

CHAINS	
	N. 1° 00' E., bet. secs. 23 and 24.
	Over rolling badlands.
4.00	Leave badlands and enter gently rolling land.
40.00	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
77.60	Track road, bears NE. and SW.
80.00	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	<div style="text-align: center;"> T20N R19E S 14 S 13 S 23 S 24 1967 </div>
	Land, gently rolling and badlands.
	Soil, clay loam.
	Timber, none.
	Undergrowth, bunch grass and sagebrush,
	From the point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	S. 89° 37' W., bet. secs. 13 and 24.
	Over rolling land.
1.10	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° E.
23.70	Track road, bears N. and S.
39.80	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	Enter badlands.
53.00	Leave badlands, thence over gently rolling land.
78.00	Track road, bears NE. and SW.
79.60	The cor. of secs. 13, 14, 23 and 24.
	Land, gently rolling and badlands.
	Soil, clay loam.
	Timber, none.
	Undergrowth, bunch grass and sagebrush,
	N. 0° 48' E., bet. secs. 13 and 14.
	Over gently rolling land.
19.00	Enter rolling badlands.
40.00	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 22 ins. in the ground, brass cap mkd.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	<p style="text-align: center;">T20N R19E $\frac{1}{4}$ S14 S13 1967</p> <p>Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor.</p>
45.00	Ascend steep SW. slope.
54.70	Top of ridge, bears SE. and NW.
80.00	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E <u>S 11 S 12</u> S 14 S 13 1967</p> <p>Land, rolling badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 89°33' W., bet. secs. 12 and 13.</p> <p>Ascend over rolling land.</p>
39.81	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">A house, bears N. 5°28' E., 25.63 chs. dist.</p> <p>Continue ascent over heavy rolling land.</p>
55.50	Top of ascent, thence over top of mesa, bears northerly and southeasterly.
62.80	Descend steep W. slope.
79.62	The cor. of secs. 11, 12, 13 and 14.
	<p>Land, rolling to heavy rolling. Soil, rocky, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 1°03' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
1.00	Ascend steep S. slope.
5.60	Top of ridge, bears E. and W.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
9.60	Draw, drains N. 80° W.
21.00	Draw, drains W.
23.20	Top of spur, slopes W.; desc. along steep W. slope.
32.80	Bottom of descent.
35.20	Fence, barbed wire, bears N. 80° E. and S. 80° W.
35.30	Bladed road, bears N. 80° E. and S. 80° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented. Continue over nearly level land.
49.90	Wash, 20 lks. wide, 2 ft. deep, drains SW.
59.50	Cottonwood Wash, 40 lks. wide, 8 ft. deep, drains W.
76.90	Wash, 20 lks. wide, 5 ft. deep, drains W.
80.00	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented. Land, rolling to nearly level. Soil, rocky, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. S. 89°29' W., bet. secs. 1 and 12. Over gently rolling land, along fence line.
27.00	Cor. of fences, bears North 1 lk. dist.; fences bear N., E. and W.
28.60	Cor. of fences, bears North, 4 lks. dist.; fences bear N., E. and W.
29.90	Red adobe cabin, bears North, 1.30 chs. dist.
30.80	Windmill, bears North, 60 lks. dist., and wooden shed bears North, 1.40 chs. dist.
32.10	SW. cor. of pond, bears North, 40 lks. dist.
32.20	Fence, barbed wire, bears SE. and NW.
32.30	Trail road, bears SE. and NW.
36.20	Cor. of fences, bears North, 20 lks. dist.; fences bear N. 60° E. and W.
36.30	Left bank of Cottonwood Wash, 10 ft. high, bears N. and S.
37.10	Center of Cottonwood Wash, 60 lks. wide, 2 ft. deep, drains S.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
39.69	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Continue along fence line.</p>
44.50	<p>Right bank of Cottonwood Wash, 8 ft. high, bears N. and S.</p>
59.90	<p>Cross fence line, bearing E. and W.; thence along S. side of same.</p>
79.38	<p>The point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. $0^{\circ}20'$ E., bet. secs. 1 and 2.</p> <p>Over gently rolling land.</p>
0.40	<p>Fence, barbed wire, bears E. and W.</p>
24.50	<p>Track road, bears SE. and NW.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
68.90	<p>Leave gently rolling land; thence over rolling land.</p>
79.10	<p>Fence, barbed wire, bears E. and W.</p>
80.17	<p>Intersect the Fifth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">The Standard cor. of secs. 35 and 36, T. 21 N., R. 19 E., bears N. $89^{\circ}29'$ E., 12.15 chs. dist., monumented by an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.</p> <p>Land, gently rolling to rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post, set, mkd. and witnessed as described in the field note record of the dependent resurvey of the N. bdy., T. 19 N., R. 19 E. in 1966.</p> <p>N. $0^{\circ}50'$ E., bet. secs. 34 and 35.</p> <p>Over gently rolling land.</p>
22.70	<p>Wash, 15 lks. wide, 3 ft. deep, drains NW.</p>
27.40	<p>Wash, 40 lks. wide, 2 ft. deep, drains SW.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

<p>CHAINS 39.99</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
<p>70.90</p>	<p>Wash, 1.10 chs. wide, 3 ft. deep, drains W.</p>
<p>79.98</p>	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19E $\frac{S}{S}$ $\frac{27}{34}$ $\frac{S}{S}$ $\frac{26}{35}$ 1967</p> </div> <p>Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°46' W., bet. secs. 26 and 35.</p> <p>Over nearly level land.</p>
<p>39.93</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{26}{35}$ 1967</p> </div>
<p>40.10</p>	<p>Track road, bears SE. and NW.</p>
<p>79.86</p>	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 0°51' E., bet. secs. 26 and 27.</p> <p>Over gently rolling land.</p>
<p>2.70</p>	<p>Track road, bears E. and W.</p>
<p>36.20</p>	<p>Top of lava ridge, bears SE. and NW.; thence over badlands.</p>
<p>39.99</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 27 S 26 1967</p>
61.20	<p>Top of lava ridge, bears SE. and NW.; thence over badlands.</p>
79.98	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 23 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E <u>S 22 S 23</u> S 27 S 26 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling and badlands. Soil, clay loam. Timber, none Undergrowth, bunch grass and sagebrush.</p>
26.90 29.20 39.94	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°45' W., bet. secs. 23 and 26.</p> <p>Over rolling badlands.</p> <p>Leave badlands; thence over gently rolling land. Track road, bears S. 60° E. and N. 60° W.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ <u>S 23</u> S 26 1967</p> <p>Deposit glass in hole.</p>
79.88	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling and badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
39.99	<p>N. 1°03' E., bet. secs. 22 and 23.</p> <p>Over nearly level land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
79.98	<p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 22 S 23 1967</p> <p>Set a wooden post, 4 ins. in diam., 3 ft. long, alongside the cor.</p> <p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 13 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E S 15 S 14 S 22 S 23 1967</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
39.89	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°44' W., bet. secs. 14 and 23.</p> <p>Over nearly level land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 19 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 14 S 23 1967</p>
79.78	<p>Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor.</p> <p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
38.00	<p>N. 0°54' E., bet. secs. 14 and 15.</p> <p>Over nearly level land.</p> <p>Diversion dam, S. end, bears East, 4.60 chs. dist.</p>
39.99	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	<p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 15 S 14 1967</p> <p>Raise a mound of stone W. of the cor.</p>
47.00	Diversion Dam, bears SE. and NW.
79.98	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T20N R19E S 10 S 11 S 15 S 14 1967</p> <p>Set a wooden post, 4 ins. in diam., 3 ft. long, alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°46' W., bet. secs. 11 and 14.
	Descend over rolling land.
14.00	Bottom of mesa; thence over nearly level land.
39.80	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 11 S 14 1967</p>
67.00	Cor. of diversion dams, bears E., S. and W.
79.60	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling to nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 1°04' E., bet. secs. 10 and 11.
	Over nearly level land.
1.45	Fence, barbed wire, bears N. 80° E. and S. 80° W.
1.75	Bladed road, bears N. 80° E. and S. 80° W.
25.90	Cottonwood Wash, 4.00 chs. wide, 6 ft. deep, drains SW.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS 40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 10 S 11 1967</p> <p>Raise a mound of stone W. of the cor.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E S 3 S 2 S 10 S 11 1967</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 1, 2, 11 and 12. S. 89°45' W., bet. secs. 2 and 11. Over nearly level land.</p>
3.40	Wash, 50 lks. wide, 7 ft. deep, drains NW. from S.
10.30	Left bank of wash, 10 ft. high, bears S. and NW.
34.20	Wash, 2.00 chs. wide, 2 ft. deep, drains S.
39.20	Fence, barbed wire, bears S. 20° E. and N. 20° W. to fence cors. extending S. 20° E. and W., thence along same.
39.78	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Continue along fence line.</p>
71.90	Track road, bears S. 5° E. and N. 5° W.
79.56	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 0°24' E., bet. secs. 2 and 3. Over gently rolling land.</p>
0.55	Fence, barbed wire, bears E. and W.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

<p>CHAINS 8.10</p>	<p>Base of mesa, ascend over rolling land.</p>
<p>12.50</p>	<p>Rim of mesa, continue ascent.</p>
<p>39.99</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
<p>79.40</p>	<p>Fence, barbed wire, bears E. and W.</p>
<p>80.12</p>	<p>Intersect the Fifth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">The Standard cor. of secs. 34 and 35, T. 21 N., R. 19 E., bears N. $89^{\circ}51'$ E., 12.52 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.</p> <p>Land, gently rolling to rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field note record of the dependent resurvey of the N. bdy. T. 19 N., R. 19 E., in 1966.</p> <p>N. $0^{\circ}52'$ E., bet. secs. 33 and 34.</p> <p>Over nearly level land.</p>
<p>21.90</p>	<p>Wash, 70 lks. wide, 3 ft. deep, drains S. 60° W.</p>
<p>36.80</p>	<p>Wash, 2.50 chs. wide, 3 ft. deep, drains S. 60° W.</p>
<p>39.95</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
<p>75.70</p>	<p>Fence, barbed wire, bears E. and W., and cor. of fences bearing S. and W., bears East, 5.00 chs. dist.</p>
<p>77.50</p>	<p>Track road, bears S. 60° E. and N. 60° W.</p>
<p>79.90</p>	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. $89^{\circ}43'$ W., bet. secs. 27 and 34.</p> <p>Over nearly level land.</p>
<p>23.60</p>	<p>Track road, bears N. 80° E. and S. 80° W.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS 39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.80	Point for the cor. of secs. 27, 28, 33 and 34. Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. $0^{\circ}48'$ E., bet. secs. 27 and 28. Over nearly level land.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.90	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground, brass cap mkd. $\begin{array}{c} T20N R19E \\ \hline S 21 S 22 \\ \hline S 28 S 27 \\ 1967 \end{array}$ Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor. Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 22, 23, 26 and 27. S. $89^{\circ}39'$ W., bet. secs. 22 and 27. Over rolling land.
21.70	Top of lava ridge, bears N. and S.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. $\begin{array}{c} T20N R19E \\ \hline \frac{1}{4} \frac{S 22}{S 27} \\ 1967 \end{array}$
79.86	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	N. 1°18' E., bet. secs. 21 and 22. Over nearly level land.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T20N R19E $\frac{1}{4}$ S 21 S 22 1967
52.60	Diversion Dam, bears NE. and SW.
56.60	Track road, bears NE. and SW.
61.50	Wash, 1.00 ch. wide, 2 ft. deep, drains W. from N. 45° E.
70.50	Fence, barbed wire, bears NE. and SW.
74.30	Left bank of Cottonwood Wash, bears N. and SW.
79.90	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground, brass cap mkd. T20N R19E S 16 S 15 S 21 S 22 1967 Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor. Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, willows, bunch grass and sagebrush.
	From the cor. of secs. 14, 15, 22 and 23. S. 89°36' W., bet. secs. 15 and 22. Over nearly level land.
39.74	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 7 ins. in the ground, mound of stone to top, brass cap mkd. T20N R19E $\frac{1}{4}$ S 15 S 22 1967
40.70	Wash, 20 lks. wide, 2 ft. deep, drains S.
61.60	Diversion Dam, bears NE. and SE.
66.90	Bladed road, bears NE. and SW.
68.60	Fence, barbed wire, bears NE. and SW.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

<p>CHAINS 79.48</p>	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
<p>6.40</p> <p>14.70</p> <p>39.95</p>	<p>N. 0°45' E., bet. secs. 15 and 16.</p> <p>Over nearly level land.</p> <p>Cottonwood Wash, 1.20 chs. wide, 3 ft. deep, drains S. 80° W.</p> <p>Right bank of Cottonwood Wash, 4 ft. high, bears N. 75° E. and S. 75° W.</p> <p>Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E ¼ S 16 S 15 1967</p>
<p>79.90</p>	<p>Set a wooden post 4 ins. in diam., 4 ft. long, alongside the cor.</p> <p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E S 9 S 10 S 16 S 15 1967</p> <p>Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
<p>3.90</p> <p>4.30</p> <p>9.10</p> <p>11.30</p> <p>19.90</p> <p>39.83</p>	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°31' W., bet. secs. 10 and 15.</p> <p>Over nearly level land.</p> <p>Fence, barbed wire, bears N. 80° E. and S. 80° W.</p> <p>Bladed road, bears N. 80° E. and S. 80° W.</p> <p>Track road, bears S. 10° E. and N. 10° W.</p> <p>Windmill, bears South, 10 lks. dist.</p> <p>Cottonwood Wash, 2.00 chs. wide, 6 ft. deep, drains SW.</p> <p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{10}{15}$ 1967</p> <p>Deposit glass in hole.</p>
67.90	Enter low rolling hills.
79.66	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, nearly level to rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 1°05' E., bet. secs. 9 and 10.</p> <p>Over low rolling hills.</p>
39.95	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{9}{10}$ 1967</p> <p>Raise a mound of stone W. of the cor.</p>
53.80	Track road, bears S. 60° E. and N. 60° W.
79.90	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{S}{S}$ $\frac{4}{9}$ $\frac{S}{S}$ $\frac{3}{10}$ 1967</p> <p>Set a wooden post, 5 ins. in diam., 3 ft. long, alongside the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°25' W., bet. secs. 3 and 10.</p> <p>Over nearly level land, along fence line.</p>
39.85	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ $\frac{S\ 3}{S\ 10}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">An E-W fence line bears North, 1.01 chs. dist.</p> <p>Raise a mound of stone N. of the cor.</p>	
49.70	Cor. of fences extending N. and E., bears North, 1.10 chs. dist.	
62.00	Top of ridge, bears N. and S.	
72.00	Top of spur, slopes SW.	
79.70	The cor. of secs. 3, 4, 9 and 10.	
	<p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>	
	<p>N. 0°47' E., bet. secs. 3 and 4.</p> <p>Over gently rolling land.</p>	
11.50	Enter rolling badlands.	
19.10	Top of ridge, bears N. 10° E. and SW.	
39.95	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ $\frac{S\ 4}{S\ 3}$ 1967</p>	
47.60	Top of ridge, bears S. 40° E. and N. 40° W.	
80.03	<p>Intersect the Fifth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T21N R19E $\frac{S\ 33}{S\ 4\ S\ 3}$ C C T20N R19E 1967</p>	

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	from which
	<p>The Standard cor. of secs. 33 and 34, T. 21 N., R. 19 E., bears N. 89°55' E., 12.81 chs. dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.</p> <p>An E-W fence line, bears North, 2 lks. dist.</p> <p>Raise a mound of stone S. of the cor.</p> <p>Land, gently rolling to rolling badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the dependent resurvey of the N. bdy. of T. 19 N., R. 19 E. in 1966.</p> <p>N. 0°59' E., bet. secs. 32 and 33.</p> <p>Over gently rolling land.</p>
15.50	Wash, 4.00 chs. wide, 5 ft. deep, drains SW.
31.40	Fence, barbed wire, bears N. 80° E. and S. 80° W.
39.97	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
77.30	Fence, barbed wire, bears E. and W., and cor. of fences, extending E., S. and W., bears East, 3.25 chs. dist.
79.94	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°50' W., bet. secs. 28 and 33.</p> <p>Over nearly level land.</p>
5.60	Track road, bears S. 60° E. and N. 60° W.
39.84	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.68	The point for the cor. of secs. 28, 29, 32 and 33.
	<p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. 0°55' E., bet. secs. 28 and 29.</p> <p>Over nearly level land.</p>
7.60	Bladed road, bears N. 50° E. and S. 50° W.

Dependent Resurvey
 Subdivisional Lines, T. 20 N., R. 19 E.

<p>CHAINS 39.97</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
<p>75.30</p>	<p>Wash, 30 lks. wide, 3 ft. deep, drains SW.</p>
<p>79.94</p>	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. $89^{\circ}49'$ W., bet. secs. 21 and 28.</p> <p>Over nearly level land.</p>
<p>34.70</p>	<p>S. edge of Diversion Dam, bears northerly approx. 10.00 chs. dist. to stock pond.</p>
<p>36.60</p>	<p>Bladed road, bears N. and S.</p>
<p>39.78</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>
<p>47.60</p>	<p>N. end of Diversion Dam, bears southerly approx. 8 chs. dist.</p>
<p>72.70</p>	<p>Wash, 30 lks. wide, 3 ft. deep, drains SW.</p>
<p>79.56</p>	<p>The point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>N. $1^{\circ}16'$ E., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p>
<p>.35</p>	<p>Wash, 40 lks. wide, 4 ft. deep, drains S. 25° W.</p>
<p>5.10</p>	<p>Ascend steep S. slope.</p>
<p>8.10</p>	<p>S. edge of mesa, bears NE. and SW.</p>
<p>11.60</p>	<p>Fence, barbed wire, bears N. 20° E. and S. 20° W.</p>
<p>14.60</p>	<p>NW. edge of mesa, bears N. 10° E. and S. 40° W., desc. along W. slope.</p>
<p>28.80</p>	<p>Left bank of Cottonwood Wash, 5 ft. high, bears N. 80° E. and S. 80° W.</p>
<p>37.30</p>	<p>Center of same, drains W.</p>
<p>39.97</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Leave wash area, continue over nearly level land.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
79.94	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Land, gently rolling to nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°49' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p>
2.10	Cottonwood Wash, 1.30 chs. wide, 4 ft. deep, drains S.
27.50	Cottonwood Wash, 1.80 chs. wide, 5 ft. deep, drains NW.
39.80	<p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E ¼ S 16 S 21 1967</p> <p>Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor.</p>
41.00	Cottonwood Wash, 70 lks. wide, 4 ft. deep, drains S.
59.70	<p>Point for the W 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E W1/16 S 16 S 21 1967</p> <p>Set a wooden post, 3 ins. in diam., 3 ft. long, alongside the cor.</p>
79.60	<p>The point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
39.97	<p>N. 0°45' E., bet. secs. 16 and 17.</p> <p>Over nearly level land.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E ¼ S 17 S 16 1967</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS					
79.94	<p>Set a wooden post, 3 ins. in diam., 3 ft. long, alongside the cor.</p> <p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19E</p> <table border="1" style="margin: auto;"> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table> <p>1967</p> </div> <p>Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>	S 8	S 9	S 17	S 16
S 8	S 9				
S 17	S 16				
39.81	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°52' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19E</p> <table border="1" style="margin: auto;"> <tr> <td>$\frac{1}{4}$ S 9</td> </tr> <tr> <td>S 16</td> </tr> </table> <p>1967</p> </div> <p>Set a wooden post, 4 ins. in diam., 4 ft. long, alongside the iron post.</p>	$\frac{1}{4}$ S 9	S 16		
$\frac{1}{4}$ S 9					
S 16					
46.30	<p>Wash, 30 lks. wide, 3 ft. deep, drains S. 25° E.</p>				
79.62	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>				
1.00 3.50 24.30 34.10 39.97	<p>N. 1°03' E., bet. secs. 8 and 9.</p> <p>Over nearly level land.</p> <p>Fence, barbed wire, bears N. 65° E. and S. 65° W., a cor. of fences bears N. 65° E., 3 lks. dist., fences bear S. 65° W. and N. 45° W.</p> <p>Track road, bears N. 45° E. and S. 80° W.</p> <p>Enter gently rolling land.</p> <p>Wash, 3 lks. wide, 3 ft. deep, drains E.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p>				

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
41.50	Wash, 5 lks. wide, 3 ft. deep, drains E.
42.50	Wash, 10 lks. wide, 4 ft. deep, drains E.
79.94	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T20N R19E $\frac{S\ 5}{S\ 8} \frac{S\ 4}{S\ 9}$ 1967 </div> Set a wooden post 3 ins. in dia., 4 ft. long, alongside the cor. Land, nearly level to gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 3, 4, 9 and 10. S. 89°55' W., bet. secs. 4 and 9. Over gently rolling land.
12.90	Top of ridge bears N. and S.
29.90	Stock pond, bears South, 4.50 chs. dist.
39.84	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 24 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T20N R19E $\frac{1}{4} \frac{S\ 4}{S\ 9}$ 1967 </div> Raise a mound of stone N. of the cor.
64.20	Wash, 40 lks. wide, 4 ft. deep, drains S. 75° E.
70.50	Bladed road, bears N. and S.
79.68	The cor. of secs. 4, 5, 8 and 9. Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 1°02' E., bet. secs. 4 and 5. Over gently rolling land.
3.50	Wash, 20 lks. wide, 2 ft. deep, drains E.
7.30	Bladed road, bears E. and W.
9.10	Wash, 10 lks. wide, 2 ft. deep, drains E.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

<p>CHAINS 27.60</p> <p>30.30</p> <p>39.97</p> <p>70.20</p> <p>79.94</p>	<p>Wash, 15 lks. wide, 2 ft. deep, drains E.</p> <p>Wash, 15 lks. wide, 2 ft. deep, drains S. 45° E.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T20N R19E $\frac{1}{4}$ S 5 S 4 1967</p> <p>Set a wooden post alongside the cor.</p> <p>Wash, 30 lks. wide, 3 ft. deep, drains SE.</p> <p>Intersect the Fifth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T21N R19E S 32 ----- S 5 S 4 C C T20N R19E 1967</p> <p>from which</p> <p style="text-align: center;">The Standard cor. of secs. 32 and 33, T. 21 N., R. 19 E., bears N. 89°55' E., 13.15 chs. dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey of the Fifth Standard Parallel North, in 1947.</p> <p style="text-align: center;">An E-W fence line bears North, 1 lk. dist.</p> <hr/> <p>The point for the $\frac{1}{4}$ sec. cor. of sec. 4 is on the N. bdy. of the Tp. and midpoint bet. the closing cors.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T21N R19E $\frac{1}{4}$ S 4 ----- T20N R19E 1967</p> <p>from which</p> <p style="text-align: center;">The Standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 21 N., R. 19 E., bears N. 89°55' E., 12.98 chs. dist., monumented by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey of the Fifth Standard Parallel North in 1947.</p>
---	---

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the dependent resurvey of the N. bdy. of T. 19 N., R. 19 E., in 1966.</p> <p>N. 0°58' E., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p>
16.40	Fence, barbed wire, bears E. and W.
39.99	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">A windmill, bears N. 37°30' E., 2.21 chs. dist.</p> <p style="padding-left: 40px;">A windmill, bears S. 57°31' W., 44.62 chs. dist.</p>
59.20	Left bank of Cottonwood Wash, 10 ft. high, bears E. and W., curving N.; thence up wash.
68.70	Center of same wash, drains S. 4° W.
76.00	Center of same, drains S. 80° W., curving to S. 4° W.
76.40	Right bank of Cottonwood Wash, 15 ft. high, bears N. 80° E. and S. 80° W., curving S. 4° W.
79.98	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°49' W., bet. secs. 29 and 32.</p> <p>Over nearly level land.</p>
9.60	Bladed road, bears NE. and SW.
23.30	Fence, barbed wire, bears N. and S.
39.93	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
66.60	Cut bank, 6 ft. high, bears NE. and S.
71.40	Left bank of Cottonwood Wash, 6 ft. high, bears N. 60° E. and S. 60° W.
73.10	Center of same wash, drains S. 60° W.
74.90	Right bank of same wash, 6 ft. high, bears N. 60° E. and S. 60° W.
77.40	Cut bank, 6 ft. high, bears N. and SW.
79.86	The point for the cor. of secs. 29, 30, 31 and 32.

Dependent Resurvey
 Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p> <hr/> <p>S. 89°48' W., bet. secs. 30 and 31. Over gently rolling land.</p> <p>20.00 Enter low rolling hills.</p> <p>39.83 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>65.00 Underground pipeline, bears S. 10° E. and N. 10° W.</p> <p>73.10 Track road, bears S. 20° E. and N. 20° W.</p> <p>82.95 The point for the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp. Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 29, 30, 31 and 32. N. 1°00' E., bet. secs. 29 and 30. Over nearly level land.</p> <p>21.00 Enter gently rolling hills.</p> <p>39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>58.00 Leave gently rolling hills and enter nearly level land.</p> <p>79.98 Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented. Land, nearly level to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 20, 21, 28 and 29. S. 89°49' W., bet. secs. 20 and 29. Over nearly level land.</p> <p>.20 Wash, 50 lks. wide, 3 ft. deep, drains SW.</p> <p>4.00 Fence, barbed wire, bears N. and S.</p> <p>9.00 Left bank of Cottonwood Wash, 8 ft. high, bears N. and S.</p> <p>10.40 Center of same wash, 1.00 ch. wide, 6 ft. deep, drains S.</p> <p>17.60 Right bank of same wash, 6 ft. high, bears N. and S.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
39.88	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.76	The point for the cor. of secs. 19, 20, 29 and 30. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	S. $89^{\circ}49'$ W., bet. secs. 19 and 30. Over gently rolling land.
39.81	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
82.79	The point for the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp. Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 19, 20, 29 and 30. N. $1^{\circ}09'$ E., bet. secs. 19 and 20. Over nearly level land.
11.70	Wash, 1.00 ch. wide, 3 ft. deep, drains W.
26.00	Enter gently rolling hills.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented. Thence over nearly level land.
79.98	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented. Land, nearly level to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 16, 17, 20 and 21. S. $89^{\circ}52'$ W., bet. secs. 17 and 20. Over nearly level land.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.86	The point for the cor. of secs. 17, 18, 19 and 20.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>S. 89°51' W. bet. secs. 18 and 19. Over gently rolling land.</p>
29.50	Fence, barbed wire, bears N. 55° E. and S. 55° W.
39.85	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
55.90	Base of bluff, bears irregularly N. and S., thence ascend.
59.70	Top of bluff bears irregularly N. and S., thence over table land.
59.80	Track road, bears N. 30° E. and S. 30° W.
68.20	Wash, 40 lks. wide, 4 ft. deep, drains S. 45° W.
82.76	The point for the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.
	<p>Land, nearly level to rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the point for the cor. of secs. 17, 18, 19 and 20. N. 0°53' E., bet. secs. 17 and 18. Over gently rolling land.</p>
29.20	Fence, barbed wire, bears N. 60° E. and S. 60° W.
39.99	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
66.60	Track road, bears E. and W.
79.98	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	<p>Land, gently rolling. Soil, sandy loam. Timber, none Undergrowth, bunch grass and sagebrush.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17. S. 89°52' W., bet. secs. 8 and 17. Over nearly level land.</p>
1.50	Fence, barbed wire, bears N. 50° E. and S. 50° W.
14.30	Track road, bears N. 75° E. and S. 75° W.

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
39.85	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
44.10	Wash, 30 lks. wide, 2 ft. deep, drains S.
51.20	Wash, 20 lks. wide, 2 ft. deep, drains S.
79.70	The point for the cor. of secs. 7, 8, 17 and 18. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	S. $89^{\circ}54'$ W., bet. secs. 7 and 18. Over gently rolling land.
2.50	Wash, 20 lks. wide, 3 ft. deep, drains S. 40° W.
5.70	Wash, 10 lks. wide, 3 ft. deep, drains S.
13.60	Base of hills, bears N. and S., thence ascend.
16.60	Top of ridge, bears N. and S.
18.30	Track road, bears N. and S. 80° W.
22.30	Track road, bears N. and S. 10° W.
22.60	Wash, 30 lks. wide, 3 ft. deep, drains S. 10° W.
39.76	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Point falls in track road, bearing N. and S. This corner is not monumented.
82.45	The point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp. Land, gently rolling to rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 7, 8, 17 and 18. N. $1^{\circ}01'$ E., bet. secs. 7 and 8. Over gently rolling land.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
51.40	Track road, bears N. 45° E. and S. 45° W.
79.98	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey
 Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	<p>Set the iron post 18 ins. in the ground, rock collar to top, brass cap mkd.</p> $\begin{array}{r} \text{T20N R19E} \\ \hline \text{S } 6 \mid \text{S } 5 \\ \text{S } 7 \mid \text{S } 8 \\ \hline 1967 \end{array}$ <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
<p>26.10</p> <p>31.70</p> <p>39.87</p> <p>47.70</p> <p>57.20</p> <p>61.70</p> <p>67.60</p> <p>79.74</p>	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°57' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p> <p>Track road, bears N. 45° E. and S. 45° W.</p> <p>Wash, 15 lks. wide, 2 ft. deep, drains N. 45° E.</p> <p>Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.</p> <p>Ascend steep E. slope of mesa.</p> <p>Top of mesa bears N. and S. 45° E.</p> <p>Stock pond, bears North, 4.00 chs. dist.</p> <p>Track road, bears N. 15° E. and S. 15° W.</p> <p>Track road, bears S. 50° E. and N. 50° W.</p> <p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, gently rolling and rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
<p>39.75</p> <p>53.20</p> <p>53.50</p>	<p>S. 89°56' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T20N R19E} \\ \hline \frac{1}{4} \frac{\text{S } 6}{\text{S } 7} \\ \hline 1967 \end{array}$ <p>Set a wooden post, 3 ins. in diam., 3 ft. long, alongside the cor.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains N. 40° W.</p> <p>Track road, bears S. 40° E. and N. 40° W.</p>

Dependent Resurvey
Subdivisional Lines, T. 20 N., R. 19 E.

CHAINS	
70.90	Top of mesa, bears N. and S., descend over steep W. slope to gently rolling land.
82.28	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp. Land, gently rolling to rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 5, 6, 7 and 8. N. 1°10' E., bet. secs. 5 and 6. Over gently rolling land.
7.10	Track road, bears SE. and NW.
15.80	Enter rolling badlands.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T20N R19E $\frac{1}{4}$ S 6 S 5 1967 </div> from which A stock pond, bears N. 89°38' W., 13.96 chs. dist. Set a wooden post, 4 ins. in diam., 3 ft. long, alongside the cor.
56.30	Wash, 20 links wide, 4 ft. deep, drains W.
63.50	Wash, 20 lks. wide, 2 ft. deep, drains SW.
79.92	Intersect the Fifth Standard Parallel North. Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T21N R19E S 31 <hr style="width: 50%; margin: 0 auto;"/> S 6 S 5 C C T20N R19E 1967 </div> from which The Standard cor. of secs. 31 and 32, T. 21 N., R. 19 E., bears S. 89°58' E., 13.62 chs. dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey of the Fifth Standard Parallel North, in 1947.

Subdivision of Sec. 16, T. 20 N., R. 19 E.

CHAINS	<p>A fence, bears North, 1 lk. dist., fence bears E. and W.</p> <p>Land, gently rolling to rolling Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p> <hr/> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 6, at proportionate distance and on the N. bdy. of the Tp., falls in wash, 1.00 ch. wide, 4 ft. deep, drains S. in unsafe location from the true point</p> <p>Point selected for the witness $\frac{1}{4}$ sec. cor. of sec. 6, bears S. $89^{\circ}58'$ E., 2.60 chs. dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>WC ←—————</p> <p>$\frac{1}{4}$ S6</p> <p>T20N R19E</p> <p>1967</p> </div> <p>from the true point for the $\frac{1}{4}$ sec. cor. of sec. 6</p> <p>The Standard $\frac{1}{4}$ sec. cor. of sec. 31, bears S. $89^{\circ}58'$ E., 13.62 chs. dist., monumented by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey of the Fifth Standard Parallel North, in 1947.</p> <p>An E-W fence, bears North, 2 lks. dist.</p>
	<p>Survey of Partial Subdivision, Section 16, T. 20 N., R. 19 E., G&SR M., Arizona</p>
7.40	<p>From the $\frac{1}{4}$ sec. cor. of sec. 16 and 21.</p> <p>N. $0^{\circ}43'$ W., on the N. and S. center line of sec. 16.</p> <p>Over nearly level land.</p> <p>Center of Cottonwood Wash, 2.60 chs. wide, 5 ft. deep, drains SW.</p>
39.98	<p>Point for the C $\frac{1}{4}$ sec. cor. of sec. 16. This corner is not monumented.</p>
66.90	<p>Wash, 40 lks. wide, 3 ft. deep, drains SE.</p>
73.10	<p>Wash, 1.00 ch. wide, 3 ft. deep, drains SW.</p>
79.96	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.</p> <p>S. $89^{\circ}51'$ W., on the E. and W. center line of sec. 16.</p>

Subdivision of Sec. 16, T. 20 N., R. 19 E.

CHAINS	
	Over nearly level land.
23.60	Wash, 20 lks. wide, 2 ft. deep, drains S.
31.80	Wash, 40 lks. wide, 5 ft. deep, drains S.
39.81	The point for the C $\frac{1}{4}$ sec. cor. of sec. 16.
59.71	Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 16.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T20N R19E C $\frac{W1/16}{S 16}$ C 1967</p>
	Deposit glass in hole.
79.61	The $\frac{1}{4}$ sec cor. of secs. 16 and 17.
	Land, nearly level.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunch grass and sagebrush.
	From the W $\frac{1}{16}$ sec. cor. of secs. 16 and 21.
	N. $0^{\circ}44'$ E., on the N. and S. center line of the SW $\frac{1}{4}$
	of sec. 16.
	Over nearly level land.
39.97	The C-W $\frac{1}{16}$ sec. cor. of sec. 16.
	General Description
	Township 20 North, Range 19 East is located about 29
	miles east-northeast of Winslow, Arizona. The elevation
	ranges from about 5,500 feet above sea level on the north
	boundary of the township, to about 5,100 feet above sea
	level in the southwest corner of the township. The main
	drainage is carried by Cottonwood Wash which traverses
	the township from the northeast corner to the southwest
	corner. Several track roads traverse the township.
	These roads give access to stock ponds and windmills.
	The area is primarily used for grazing. The vegetation
	consists mainly of scattered to moderate bunch grass
	and sagebrush. There was no mining activity noted in
	the township.

41

BOOK 4844

CERTIFICATE OF SURVEY

I, Louis D. Gilbert, HEREBY CERTIFY upon honor that,
 in pursuance of special instructions bearing date of the 23rd day of June, 19 67,
 I have dependently resurveyed the east and west boundaries and subdivisional
 lines, established the north $\frac{1}{4}$ section corners of sections 4 and 6, and
 surveyed subdivisions in section 16, Township 20 North, Range 19 East
 of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by me and under my direction;
 and that said survey has been made in strict conformity with said special instructions, the Manual
 of Instructions for the Survey of the Public Lands of the United States, and in specific manner
 described in the foregoing field notes.

December 13, 1968
(Date)

Louis D. Gilbert
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JAN 29 1969

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the east and west boundaries
 and subdivisional lines, establishment of the north $\frac{1}{4}$ section corners of
 sections 4 and 6, and the survey of subdivisions in section 16, Township
 20 North, Range 19 East, Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert

having been critically examined and found correct, are hereby approved.

JUN 25 1969
(Date)

Clark F. Gumm
(Chief, Division of Engineering)
Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)