

BOOK 4848

Form 9180-6  
(April 1965)  
(formerly 4-679)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

1

# FIELD NOTES

DEPENDENT RESURVEY

of the

SOUTH BOUNDARY OF THE LUIS MARIA BACA FLOAT NO. 5

FROM THE 36 MILE CORNER TO THE 42 MILE CORNER

and

DEPENDENT RESURVEY OF THE EAST BOUNDARY

and

SURVEY OF THE SUBDIVISIONAL LINES

of

FRACTIONAL TOWNSHIP 17 NORTH, RANGE 8 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

## EXECUTED BY

Jerrold E. Knight, Cadastral Surveyor

Under special instructions dated July 10, 19 68, which provided for the surveys included under Group Number 485, approved July 10, 1968, and assignment instructions dated July 10, 19 68.

Survey commenced July 26, 19 68

Survey completed September 23, 19 68

(17)

# BOOK 4848 INDEX DIAGRAM

Fractional Township 17 North, Range 8 West

6	5	4	3	2	1
7	8	9	10	11 12	5 12
18	17 LUIS	16 MARIA BACA	15	14	13
4	4	3	3	2	2
<del>18</del> 29 28 27	<del>20</del> 28 23 27 26	<del>21</del> 23 19 22	<del>22</del> 20 15 19	<del>23</del> 16 11 15	<del>24</del> 12 8 11
30 26 25	29 22 25	28 18 21	27 14 17	26 10 13	25 7 10
31 24	32 20	33 16	34 12	35 9	36 5

Fractional Township 17 North, Range 8 West  
Gila and Salt River Meridian, Arizona

## CHAINS

The south boundary of Luis Maria Baca Float No. 5 through Fractional Township 17 North, Range 8 West, was surveyed in 1877 by C. B. Foster. The 37th mile was resurveyed by A. B. Mader in 1905. The 40th, 41st and 42nd miles were retraced and the 43rd mile was resurveyed by Ty White in 1938. The east boundary of Fractional Township 17 North, Range 8 West, was surveyed in 1905 by A. B. Mader. The south boundary (the Fourth Standard Parallel North), was surveyed in 1930 by W. E. Hiester. The west boundary was surveyed in 1938 by Ty White.

The following notes are those of a dependent resurvey of the south boundary of the Luis Maria Baca Float No. 5 from the 36th mile corner to the 42d mile corner and of the east boundary of Fractional Township 17 North, Range 8 West, designed to restore the corners to their original position according to the best available evidence; and a survey of the subdivisional lines of Fractional Township 17 North, Range 8 West.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 10, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. The northwest portion of the township was extremely rugged and impossible to chain. Various portions of the lines were measured by triangulation or with a Model 6 Geodimeter. Distances to some items to topography were estimated in the field. These distances are noted as such in the body of these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of the township as calculated from the U.S.G.S. triangulation data given at the closing corner of Township 15 North, Ranges 7 and 8 West is: Latitude 34°48'20" North, and Longitude 113°03'04.5" West.

The mean magnetic declination was found to be 14° East.

Dependent Resurvey of a Portion of the South  
Boundary of LMBF No. 5

Reestablishment of the Survey, executed by  
C. B. Foster in 1877

A. B. Mader resurveyed from the 36 to the 37 mile corner on the south boundary of the LMBF No. 5, in 1905. In determining the points for the lost 37 and 38 mile corners, the resurvey by Mader was considered, but not used in proportioning, because it would create an imbalance not consistent with the record or with corner relationships on the ground. Proportions from the 36 to the 39 mile corners are therefore based on the record of the original survey executed by C. B. Foster in 1877.

Beginning at the 36th Mi. Cor. of Luis Maria Baca Float No. 5, monumented by a volcanic stone, 12x12x11 ins. set firmly in the ground, mkd. 36 M B and other illegible marks, with a mound of stone N.

Dep. Resurvey, Portion of S. Bdy., LMBF No. 5

CHAINS	
	<p>At the corner point</p>
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">LMBF NO 5</p>
	<p style="text-align: center;"><u>36 M.</u></p>
	<p style="text-align: center;">S19</p>
	<p style="text-align: center;">T17N R7W</p>
	<p style="text-align: center;">1968</p>
	<p>Bury the orig. cor. alongside the iron post.</p>
	<p>The cor. is located 1 lk. N. of a fence bearing S. 89° E. and N. 89° W.</p>
	<p>N. 88°15' W., on the 37th mile of LMBF No. 5.</p>
	<p>Over gently rolling S. slope; along the N. side of fence.</p>
13.20	<p>Fence, bears N. 53° W. and S. 53° E. for 20 lks. to cor. of fences bearing S. 89° E. and N. 53° W.; enter scattered timber.</p>
14.70	<p>Low spur, slopes S.</p>
32.50	<p>Swale, drains S.</p>
46.50	<p>Knoll, desc. W. slope.</p>
57.10	<p>E. rim of Pine Creek, bears S. and N. for approximately 5 ch. thence W.; desc. steep W. slope through dense oak brush.</p>
72.70	<p>Pine Creek, 50 lks. wide, small stream flowing water, course N. 25° W.; asc. steep E. slope.</p>
77.70	<p>Low rim on W. side of Pine Creek bears S. and N. for approximately 50 lks., thence W.; continue asc. over NE. slope.</p>
80.91	<p>Point for the 37th Mile Cor. at proportionate dist; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">LMBF NO 5</p>
	<p style="text-align: center;"><u>37 M</u></p>
	<p style="text-align: center;">S24</p>
	<p style="text-align: center;">T17N R8W</p>
	<p style="text-align: center;">1968</p>
	<p>Cor. is located on steep N. slope, near the top of low rim of Pine Creek.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, sandy loam, rocky.</p>
	<p>Timber, scattered juniper.</p>
	<p>Undergrowth, dense oak brush along Pine Creek.</p>
	<p>N. 88°15' W., on the 38th mile of LMBF No. 5.</p>
	<p>Asc. along steep NE. slope, through dense oak brush.</p>
10.00	<p>High rim on W. side of Pine Creek, bears generally N. and S.; over gently rolling land through widely scattered junipers.</p>
53.50	<p>Wash, 50 lks. wide, 2 ft. deep, drains NE.; asc. E. slope.</p>

## Dep. Resurvey, Portion of S. Bdy., LMBF No. 5

CHAINS	
80.91	<p>Point for the 38th Mi. Cor. at proportionate dist; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">LMBF NO 5  <u>38 M</u>  S23  T17N R8W  1968</p> <p>Land, gently rolling.  Soil, sandy loam, rocky.  Timber, widely scattered juniper.  Undergrowth, grass.</p>
	<p>N. 88°15' W., on the 39th mile of LMBF No. 5.  Asc. E. slope through scattered timber.</p>
6.80	<p>Low ridge, bears N. 15° W. and S. 15° E.; desc. gentle NW. slope.</p>
39.40	<p>Track road, bears NE. and SW.</p>
45.80	<p>Track road, bears N. 25° W. and S. 25° E.</p>
61.00	<p>Low ridge, bears NE. and SW.</p>
80.91	<p>The 39th Mi. Cor., set by Ty White in 1938, monumented by an iron post, 2 in. diam., set with 8 ins. above the ground, a mound of stone N., brass cap mkd.</p> <p style="text-align: center;">LMBF NO 5  <u>39 M</u>  PL  1938</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">LMBF NO 5  <u>39 M</u>  S22  T17N R8W  1968  1938</p> <p>Land, gently rolling.  Soil, sandy loam, rocky.  Timber, widely scattered juniper.  Undergrowth, grass.</p>
	<p style="text-align: center;">Reestablishment of the Survey executed by  C. B. Foster in 1877 and Retraced by  Ty White in 1938</p> <hr style="width: 20%; margin: auto;"/>
	<p>S. 87°15' W., on the 40th mile of LMBF No. 5.</p>
	<p>Over gently rolling land.</p>
4.30	<p>Track road, bears NE. and S. 60° W.</p>
50.60	<p>End of track road bearing SE.</p>
54.50	<p>E. rim of Burro Creek Canyon, bears N. and S., desc. over nearly vertical broken ledges. A search was made on the rim for a cor. set at 58.00 chs. on the 40th mile at the time of the original survey in 1877. No evidence was found of this cor. The proportionate point for the cor. places it on the ledges and cannot be occupied.</p>

Dep. Resurvey, Portion of S. Bdy., LMBF No. 5

<p>CHAINS 76.12</p>	<p>Point for the 40th Mi. Cor. at proportionate dist., there was no cor. set at this point originally.</p> <p>Set the iron post 6 ins. in the ground, in a mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">LMBF NO 5 <u>40 M</u> S21 T17N R8W 1968</p> <p>Land, gently rolling on the E. ½, steep, rocky W. slope on the W. portion. Timber, widely scattered juniper. Soil, sandy loam, rocky. Undergrowth, grass on the E. ½ mile, dense oak brush in the canyon.</p>
<p>18.00 38.40 41.40 68.50 72.40 76.12</p>	<p>S. 87°15' W., on the 41st mile of LMBF No. 5.</p> <p>Desc. steep SW. slope through dense oak brush.</p> <p>Approximate dist. to Burro Creek, 120 lks. wide, water 3 ins. deep, course S. for 2 chs. thence SW.; asc. along a SE. slope.</p> <p>Ravine, 150 lks. wide, 30 ft. vertical walls, drains S.</p> <p>Small prominent rocky spur, slopes S.; desc. SW. slope.</p> <p>(Approximate dist.) Ravine, steep rock walls, 100 lks. wide, 30 ft. deep, drains S.</p> <p>Spur, slopes S. 20° E., asc. gently SE. slope.</p> <p>Point for the 41st Mi. Cor. at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">LMBF NO 5 <u>41 M</u> S 20 T17N R8W 1968</p> <p>Land, sharply rolling. Soil, sandy loam, rocky. Timber, scattered juniper. Undergrowth, dense oak brush.</p>
<p>22.60 23.80 36.80 47.50 59.50</p>	<p>S. 87°15' W., on the 42nd mile of LMBF No. 5.</p> <p>Asc. SE. slope.</p> <p>W. rim of Burro Creek Canyon, bears irregularly N. and S. thence, over rolling land.</p> <p>Top of asc.; desc. SW. slope.</p> <p>Ravine, (Approx. dist.), 5 chs. wide, 50 ft. walls, drains S.; asc. SE. slope.</p> <p>Spur, slopes S.; desc. SW. slope.</p> <p>Draw, drains S.; asc. SE. slope.</p>

Dep. Resurvey, E. Bdy., Frac. T. 17 N., R. 8 W.

CHAINS	
63.80	Top of asc.; desc. steep SW. slope.
76.12	The 42d Mi. Cor., monumented by an iron post, 2 ins. diam., set in a mound of stone to top, brass cap mkd.
	<p style="text-align: center;">LMBF NO 5  <u>42 M</u>                      PL                      1938</p>
	Remark the brass cap to read
	<p style="text-align: center;">LMBF NO 5  <u>42 M</u>                      S19                      T17N R8W                      1968                      1938</p>
	<p>Land, rolling.                      Soil, sandy loam, rocky.                      Timber, widely scattered juniper.                      Undergrowth, dense oak brush.</p>
	<p>Dependent Resurvey of the East Boundary                      Frac. T. 17 N., R. 8 W., G&amp;SR M., Ariz.</p>
	<p>Reestablishment of the Survey executed by                      A.B. Mader in 1905</p>
	<p>Beginning at the standard cor. of Tp. 17 N., Rs. 7 and 8 W., monumented by a malpais rock-in-place, 6 x 8 ft. with 14 ins. showing above the surface, mkd. with an X with 6 notches on the E. and 6 notches on the W., with a mound of stone N.</p>
	from which the remains of the orig. bearing trees
	<p>A stump hole, bears N. 15° E., 400 lks. dist., with a dead juniper, 27 ins. diam., mkd. with a healed blaze, lying alongside. (Record bearing N. 15° 05' E.)</p>
	<p>A stump hole, bears N. 89° W., 229 lks. dist., with a dead juniper, 20 ins. diam., mkd. with a healed blaze, lying alongside. (Record bearing N. 89° 04' W.)</p>
	<p>A stump hole, bears N. 23° W., 264 lks. dist., with a dead juniper, 20 ins. diam., no visible mks., lying alongside. (Record bearing and dist. N. 21° 33' W., 252 lks. dist.)</p>
	At the corner point
	Set the iron post over the X on the rock, mound with stone to the top, brass cap mkd.
	<p>SC                      T17N                      R8WR7W  <u>S36 S31</u>                      1968</p>
	from which

Dep. Resurvey, E. Bdy., Frac. T. 17 N., R. 8 W.

CHAINS	
	<p>A fence, bears South, 220 lks. dist.; fence bears N. 87° E. and S. 87° W.</p> <p>The E. gate post in fence, bears S. 53° 25' W., 330 lks. dist.</p> <p>Raise a mound of stone N. of cor.</p> <p>North bet. secs. 31 and 36.</p> <p>Asc. gentle S. slope.</p>
17.20	Track road, bears N. 85° W. and S. 85° E., along the top of a low ridge; desc. gentle N. slope.
40.02	<p>The ¼ sec. cor. of secs. 31 and 36, monumented by a Malpais stone, 14 x 10 x 6 ins. firmly set in the ground, mkd. ¼ on the W. face, with a mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, in a collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R8W R7W ¼ S36 S31 1968</p> </div> <p>Raise a mound of stone W. of cor. and bury the orig. cor. alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' W., beginning new measurement.</p>
5.20	Head of swale, drains NW.; asc. gentle S. slope.
7.60	Track road, bears NW. and E.
16.00	Low ridge, bears NW. and SE.; desc. NW. slope.
20.10	Enter scattered juniper and oak.
39.98	<p>The cor. of secs. 25, 30, 31 and 36, monumented by a malpais stone, 15 x 10 x 5 ins., firmly set in the ground, mkd. with 5 notches on the N. face and 1 notch on the S. face, with a mound of stone W. from which the orig. bearing tree</p> <p>A juniper, 40 ins. diam., bears N. 57 3/4° E., 347 lks. dist., mkd. with a healed blaze. (Record bearing N. 57° 56' E.)</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R8W R7W S25 S30 S36 S31 1968</p> </div> <p>from which</p> <p>A stock pond, bears N. 65° W., 8.10 chs. dist.</p>



Dep. Resurvey, E. Bdy., Frac. T. 17 N., R. 8 W.

CHAINS	
	<p>Raise a mound of stone W. of cor. and bury the orig. cor. alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, widely scattered juniper and oak. Undergrowth, moderate grass and oak brush.</p>
	<p>N. 0° 02' E., bet. secs. 25 and 30.</p>
	<p>Desc. over gentle N. slope.</p>
2.60	<p>Track road, bears E. and W.</p>
3.50	<p>Wash, 15 lks. wide, 2 ft. deep, drains NE.; asc. gentle S. slope.</p>
8.50	<p>Track road, bears NW. and SE.</p>
10.00	<p>Enter dense oak brush.</p>
21.30	<p>Low ridge, bears NW. and SE.</p>
40.02	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, monumented by a malpais stone, 14 x 8 x 7 ins., set firmly in the ground, mkd. <math>\frac{1}{4}</math> on the W. face, from which the remains of the orig. bearing trees</p>
	<p style="padding-left: 40px;">A juniper stump, 14 ins. diam., bears S. 43<math>\frac{1}{2}</math>° W., 83 lks. dist., with a juniper tree lying alongside mkd. with illegible scribing. (Record bearing S. 43° 28' W.)</p>
	<p>At the corner point</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T17N R8W R7W <math>\frac{1}{4}</math> S25   S30 1968</p>
	<p>Raise a mound of stone W. of the cor. and bury the orig. cor. alongside the iron post.</p>
	<p style="text-align: center;">_____</p>
	<p>N. 0° 01' E., beginning new measurement.</p>
24.80	<p>S. Rim of Pine Creek, bears S. 36° E. and N. 80° W.; desc. steep rocky N. slope.</p>
30.00	<p>Pine Creek, 130 lks. wide, course N. 75° W.; asc. steep rocky S. slope.</p>
34.20	<p>N. Rim of Pine Creek, bears N. 75° W. and S. 54° E.; asc. gentle S. slope.</p>
40.02	<p>The cor. of secs. 19, 24, 25 and 30, monumented by a malpais stone 14 x 10 x 6 ins., firmly set in the ground, mkd. with 4 notches on the N. face and 2 notches on the S. face, with a mound of stone W.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 20 ins. diam., bears N. 71° E., 88 lks. dist., mkd. T17N R7W S19 BT. (No record of this tree in the 1905 survey).</p>

Dep. Resurvey, E. Bdy., Frac. T. 17 N., R. 8 W.

CHAINS

A juniper, 22 ins. diam., bears N.  $14\frac{1}{2}^\circ$  W.,  
131 lks. dist., mkd. T17N R8W S24 BT. (Record  
bearing N.  $74^\circ 42'$  W.)

At the corner point

Set the iron post 8 ins. in the ground, mound of stone  
to top, brass cap mkd.

T17N  
R8W R7W  
S24 | S19  
S25 | S30  
1968

Bury the orig. cor. alongside the iron post and raise  
a mound of stone W. of cor.

Soil, sandy loam, rocky.  
Timber, scattered juniper and oak.  
Undergrowth, moderate grass, moderate to dense oak  
brush.

N.  $0^\circ 03'$  E., bet., secs. 19 and 24.

Asc. over gentle S. slope.

38.60 Fence, bears N.  $89^\circ$  W., and S.  $89^\circ$  E.

38.71 Intersect the S. Bdy. of LMBF No. 5.

Point for the closing cor. of secs. 19 and 24.

Set the iron post 10 ins. in the ground, mound of  
stone to top, brass cap mkd.

LMBF NO 5  
S24 | S19  
cc  
T17N  
R8W R7W  
1968

from which

The 36th Mi. Cor. on the S. Bdy. of LMBF No. 5,  
bears S.  $88^\circ 15'$  E., 6.67 chs. dist., hereto-  
fore described.

The original closing cor. of secs. 19 and 24,  
bears N.  $0^\circ 03'$  E., 5 lks. dist., monumented  
by a malpais stone, 18 x 11 x 12 ins. showing  
above ground, mkd. cc on S. face, BLV on N.  
face, 6 grooves on E. face, 6 grooves on W.  
face, with a mound of stone S. Added marks  
AM on S. face.

An orig. bearing tree, a juniper, 35 ins. diam.,  
bears S.  $20\frac{1}{2}^\circ$  E., 106 lks. dist., mkd. with a  
healed blaze.

An orig. bearing tree, a juniper, 17 ins. diam.,  
bears S.  $11\frac{3}{4}^\circ$  W., 73 lks. dist., mkd. cc T17N  
R8W S24 BT.

Land, gently rolling.  
Soil, rocky sandy loam.  
Timber, scattered juniper and pinion.  
Undergrowth, moderate grass.

## Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS

Survey of the Subdivisional Lines  
Fractional T. 17 N., R. 8 W., G&SR M., Arizona

From the standard cor. of secs. 35 and 36, on the S. Bdy. of the Tp., monumented by an iron post 2 ins. diam., set firmly with 12 ins. showing above the ground, brass cap mkd.

SC  
T17N R8W  
S35|S36  
1930

from which orig. bearing trees

A juniper, 25 ins. diam., bears N. 89° E., 304 lks. dist., mkd. T17N R8W S36 SC BT.

A juniper, 15 ins. diam., bears N. 66¼° W., 228 lks. dist., mkd. with a partially healed blaze showing only 35 SC.

North, bet. secs. 35 and 36.

Asc. over gentle S. slope through scattered timber.

- .04 Fence, bears E. and W.
- 8.00 Top of ascent; desc. gentle N. slope.
- 21.50 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. SE. slope.
- 40.00 Point for the ¼ sec. cor. of secs. 35 and 36.
- Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T17NR8W  
¼  
S35|S36  
1968

- 44.60 Low ridge, bears E. and W., desc. N. slope.
- 48.40 Edge of malpais ledge bears E. and W.; desc. steep N. slope.
- 57.80 Draw, drains, NW.; asc. S. slope.
- 64.60 Spur, slopes SW.; desc. N. slope.
- 80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T17N R8W  
S26|S25  
S35|S36  
1968

from which

The S. W. cor. of a cabin, bears N. 58° 45' W., 14.97 chs. dist.

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
	<p>Land, gently rolling. Soil, Sandy loam, rocky. Timber, scattered juniper. Undergrowth, moderate grass, dense oak brush.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36 on the E. Bdy. of the Tp.</p> <p>West, bet, secs. 25 and 36.</p> <p>Desc. W. slope through scattered timber.,</p> <p>8.20 Track road, bears S. and N. for 2 chs. thence E.</p> <p>9.40 Wash, 15 lks. wide, 4 ft. deep, drains N.; asc. E. slope.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 36.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T17NR8W</p> <p><math>\frac{1}{4}</math> <u>S25</u></p> <p>S36</p> <p>1968</p> </div> <p>Raise a mound of stone N. of the cor.</p> <p>58.70 Track road, bears NW. and SE.</p> <p>65.70 Low ridge, bears N. and S.; desc. W. slope.</p> <p>78.50 Wash, 30 lks. wide, 2 ft. deep, drains NW.; asc. E., slope.</p> <p>80.00 The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, scattered juniper. Undergrowth, dense oak brush.</p>
	<p>North, bet. secs. 25 and 26.</p> <p>Desc. N. slope through dense oak brush.</p> <p>4.20 Wash, 30 lks. wide, 1 ft. deep, drains NW.; asc. SW. slope.</p> <p>7.70 Small spur, slopes W.</p> <p>12.40 Wash, 10 lks. wide, 2 ft. deep, drains W.</p> <p>19.10 Track road, bears irregularly E. and W.</p> <p>33.30 S. rim of mesa, bears N. and S.; desc. gradually across top of mesa.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T17NR8W</p> <p><math>\frac{1}{4}</math></p> <p>S26   S25</p> <p>1968</p> </div>

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
	Raise a mound of stone W. of the cor.
53.00	Desc. N. side of mesa.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T17NR8W  <u>S23   S24</u>  <u>S26   S25</u>                      1968</p>
	Land, gently rolling. Soil, sandy loam, rocky. Timber, scattered juniper. Undergrowth, grass and dense oak brush.
	From the cor. of secs. 19, 24, 25 and 30 on the E. Bdy. of the Tp.
	S. 89° 59' W., bet. secs. 24 and 25.
	Over gently rolling S. slope through scattered juniper and dense oak brush.
21.20	Malpais ledge, bears SW. and NE.; desc. steep NW. slope.
27.60	Ravine, drains SW. into Pine Creek; asc. SE. slope.
34.00	Spur, slopes S.; desc. SW. slope.
40.01	Point for the ¼ sec. cor. of secs. 24 and 25.
	Set the iron post 10 ins. in the ground, in a mound of stone to the top, brass cap mkd.
	<p style="text-align: center;">T17N R8W                      ¼ <u>    </u>                          <u>S24</u>                          <u>S25</u>                      1968</p>
42.10	Pine Creek, 100 lks. wide, 10 ft. deep, course NW.; asc. NE. slope.
69.30	Spur, slopes N.; desc. NW. slope.
80.02	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, sandy loam, rocky. Timber, scattered juniper. Undergrowth, grass, dense oak brush.
	North, bet. secs. 23 and 24.
	Desc. NW. slope.
15.40	Malpais ledge on S. side of box canyon, bears NE. and SW.
18.90	Bottom of box canyon, 100 lks. wide, 3 ft. deep, drains NE., asc. S. slope.
23.00	Top of malpais ledge on N. side of box canyon, bears NE. and SW.
27.80	Spur, slopes E.; desc. NE. slope.

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	<p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 24.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17N R8W <math>\frac{1}{4}</math> S23 S24 1968</p>
41.02	<p>Point selected for the witness closing cor. of secs. 23 and 24.</p> <p>Set the iron post 14 ins. in the ground, in a mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">W↑C <u>LMBF NO 5</u> S23 S24 CC T17NR8W 1968</p>
41.12	<p>Intersect the S. Bdy. of LMBF No. 5.</p> <p>Point for the closing cor. of secs. 23 and 24. Point falls 1 lk. south of a near vertical ledge and can not be perpetuated.</p> <p>From the true point the 37th Mi. Cor. of LMBF No. 5, bears S. <math>88^{\circ} 15' E.</math>, 5.87 chs. dist.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, scattered juniper. Undergrowth, dense oak brush, grass.</p> <hr/> <p>The point for the N. <math>\frac{1}{4}</math> sec. cor. of sec. 24 is at midpoint bet. the closing corners and on the S. Bdy. of LMBF No. 5.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"><u><math>\frac{1}{4}</math> S24</u> T17N R8W 1968</p> <p>from which</p> <p style="text-align: center;">The 37 mi. cor., bears N. <math>88^{\circ} 15' W.</math>, 34.19 chs. dist.</p> <p>Raise a mound of stone S. of the cor.</p> <hr/> <p>From the standard cor. of secs. 34 and 35 on the S. Bdy. of the tp., monumented by an iron post, 2 ins. diam., set firmly with 10 ins. showing above the ground, a mound of stone. brass cap mkd.</p> <p style="text-align: center;">SC T17NR8W <u>S34 S35</u> 1930</p>

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
	<p>from which the remains of the orig. bearing trees</p> <p>A stump hole, bears N. 34° E., 187 lks. dist., with a dead juniper, 8 ins. diam., mkd. with a healed blaze showing BT only, lying alongside.</p> <p>A stump hole, bears N. 22½° W., 173 lks. dist., with a dead juniper, 6 ins. diam., mkd. T17N R8W S34 SC BT, lying alongside.</p> <p>Indian ruins, bears N. 38° 45' E., 50.75 chs. dist. The ruins consist of rock walls 5 ft. high, 80 lks. long and 40 lks. wide. They are on the western and lower of two prominent knolls.</p> <p>There are no new bearing trees available.</p> <p>North, bet. secs. 34 and 35.</p> <p>Over nearly level railed area.</p>
6.10	Track road, bears S. 82° E. and N. 72° W.
7.40	Fence, bears S. 62° E. and N. 62° W.; enter scattered timber.
17.10	Desc. N. slope.
28.00	Wash, 50 lks. wide, 2 ft. deep, drains W., a stock pond bears S. 66° E., 4 chs. dist.; asc. S. slope.
40.00	Point for the ¼ sec. cor. of secs. 34 and 35.
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W ¼ S34   S35 1968</p> <p>Cor. is located on SW. slope.</p>
59.00	Draw, drains W.
75.30	Spur, slopes W.; desc. NW. slope.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T17NR8W S27   S26 S34   S35 1968</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, scattered juniper. Undergrowth, grass, dense oak brush.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89° 59' W., bet. secs. 26 and 35.</p> <p>Asc. E. slope, through dense oak brush.</p>

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

<p>CHAINS 4.20</p>	<p>Low spur, slopes NW.; desc. W. slope.</p>
<p>17.30</p>	<p>Draw, drains NW.; asc. over gentle NE. slope.</p>
<p>22.20</p>	<p>Confluence of two washes, one from the SE. and one from the SW., draining NW.; enter open meadow.</p>
<p>30.50</p>	<p>Low spur, slopes NE. This spur is covered with many sherds, chippings and other Indian remains.</p>
<p>37.90</p>	<p>Track road, bears NE. and SW.</p>
<p>38.60</p>	<p>Wash, 20 lks. wide, 3 ft. deep, drains NE.</p>
<p>40.04</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35.</p> <p>Set the iron post, 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T17NR8W <math>\frac{1}{4}</math> <math>\frac{S26}{S35}</math> 1968</p> <p>from which</p> <p style="padding-left: 40px;">Five Indian Matates, located on rocky point of spur, bear N. <math>32^{\circ} 12'</math> E., 13.40 chs. dist.</p> <p style="padding-left: 40px;">S. end of a stock pond, bears N. <math>30^{\circ}</math> E., 20 chs. dist.</p> <p>Raise a mound of stone N. of the cor.</p>
<p>51.20</p>	<p>Low spur, slopes N.</p>
<p>70.00</p>	<p>Base of low spur, bears N. and S.; asc. gentle E. slope; enter scattered timber.</p>
<p>80.08</p>	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, scattered juniper in the E. 20 chs. and in the W. 10 chs. Undergrowth, grass, dense oak brush in the E. 20 chs.</p> <hr/> <p>North, bet. secs. 26 and 27.</p> <p>Over gently rolling land through scattered junipers.</p>
<p>5.00</p>	<p>Draw, drains E.; leave scattered junipers.</p>
<p>22.30</p>	<p>Low hill.</p>
<p>35.80</p>	<p>Draw, drains NE.</p>
<p>40.00</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 27.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T17NR8W <math>\frac{1}{4}</math> <math>S27 S26</math> 1968</p> <p>Raise a mound of stone W. of the cor.</p>
<p>52.80</p>	<p>Spur, slopes E.</p>



Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

<p>CHAINS 66.70  70.70  80.00</p>	<p>Track road, bears N. 70° W. and S. 70° E.</p> <p>Draw, drains NW.</p> <p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T17NR8W S22 S23 ----- S27 S26 1968</p> </div> <p>Cor. is located on SE. slope.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, widely scattered juniper. Undergrowth, grass.</p>
<p>7.60  18.70  27.80  40.04</p>	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 57' W., bet. secs. 23 and 26.</p> <p>Desc. W. slope through scattered juniper.</p> <p>Wash, 30 lks. wide, 2 ft. deep, drains NE.; asc. E. slope.</p> <p>Low spur, slopes N; desc. W. slope.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. E. slope.</p> <p>Point for the ¼ sec. cor. of secs. 23 and 26.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T17NR8W ¼ S23 ----- S26 1968</p> </div> <p>Raise a mound of stone N. of the cor.</p>
<p>54.90  70.00  80.08</p>	<p>Low ridge, bears N. and S.; desc. W. slope.</p> <p>Draw, drains NE.; asc. E. slope.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, widely scattered juniper. Undergrowth, grass.</p>
<p>17.00  25.00  40.00</p>	<p>North, bet. secs. 22 and 23.</p> <p>Over gently rolling land.</p> <p>Spur, slopes E.</p> <p>Draw, drains NE.; asc. SE. slope.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 23.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p>

CHAINS	
43.65	<p style="text-align: center;">T17NR8W  <math>\frac{1}{4}</math>                      S22 S23                      1968</p> <p>Intersect the S. Bdy. of LMBF No. 5.</p> <p>Point for the closing cor. of secs. 22 and 23.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"><u>LMBF NO 5</u>                      S22 S23                      C C                      T17NR8W                      1968</p> <p>From this point the 38th Mi. Cor. of LMBF No. 5, bears S. 88° 15' E., 5.08 chs. dist.</p> <p>Land, gently rolling.                      Soil, sandy loam, rocky.                      Timber, widely scattered juniper.                      Undergrowth, grass.</p>
	<p>The point for the N. <math>\frac{1}{4}</math> sec. cor. of sec. 23 is at midpoint bet. the closing corners and on the S. Bdy. on LMBF No. 5.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"><u><math>\frac{1}{4}</math> S23</u>                      T17N R8W                      1968</p> <p>from which</p> <p style="padding-left: 40px;">The 38 mi. cor. bears N. 88° 15' W., 34.98 chs. dist.</p> <p>Raise a mound of stone S. of the cor.</p>
	<p>From the standard cor. of secs. 33 and 34 on the S. Bdy. of the Tp., monumented by an iron post 2. ins. diam., set with 12 ins. showing above the ground, a mound of stone N., brass cap mkd.</p> <p style="text-align: center;">S C                      T17N R8W  <u>S33 S34</u>                      1930</p> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A cedar stump, 25 ins. diam., bears N. 49<math>\frac{1}{2}</math>° E., 358 lks. dist. A limb lying alongside is mkd. T17NR8W S34 SC BT.</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam. bears N. 74<math>\frac{1}{2}</math>° W., 92 lks. dist., mkd. T17N R8W S33 SC BT</p> <p>No new bearing trees available.</p> <p>N. 0° 01' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>

## Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS		
10.70	Track road, bears N. 40° E. and S. 40° W. for 1 ch. thence W.	
11.80	Fence, bears N. 69° E. and S. 69° W.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34. Set the iron post 20 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T17NR8W <math>\frac{1}{4}</math> S33 S34 1968</p> <p>Raise a mound of stone W. of the cor.</p>	
46.30	Malpais ledge, bears E. and W., desc. steep N. slope.	
64.70	Wash, 20 lks. wide, 5 ft. deep, drains NE.; asc. SE. slope.	
67.40	Spur, slopes E.; desc. NE. slope.	
72.60	Same wash, 100 lks. wide, 5 ft. deep, drains N. for 1 ch. thence NW.; asc. S. slope.	
80.00	Point for the cor. of secs. 27, 28, 33 and 34. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.	
	<p style="text-align: center;">T17NR8W <u>S28 S27</u> S33 S34 1968</p>	
	Cor. is located on a steep SW. slope.	
	Land, gently rolling in the S. to sharply rolling in the N.	
	Soil, sandy loam, rocky.	
	Timber, scattered juniper and pine.	
	Undergrowth, grass, dense oak brush.	
	From the cor. of secs. 26, 27, 34 and 35.	
	S. 89° 58' W., bet. secs. 27 and 34.	
	Over gently rolling mesa.	
34.00	Low ridge, bears N. and S.; desc. gentle W. slope.	
37.20	Malpais ledge, bears N. and S.; desc. steep W. slope.	
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.	
	<p style="text-align: center;">T17NR8W <math>\frac{1}{4}</math> <u>S27</u> S34 1968</p>	
50.50	Draw, drains NW.; asc. SE. slope.	
54.10	Spur, slopes NE.	
65.10	Spur, slopes N.	

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
76.20	Track road, bears N. 30° W. and S. 30° E.
78.50	Rocky point on top of ridge bearing NW. and SE.; desc. steep W. slope.
80.10	The cor. of secs. 27, 28, 33 and 34.  Land, gently rolling in the E. to sharply rolling in the W. Soil, sandy loam, rocky. Timber, scattered juniper and pine. Undergrowth, grass, dense oak brush on the W. half.
N. 0° 01' W., bet. secs. 27 and 28.	
Asc. SW. slope through dense oak brush and scattered juniper and pine.	
6.80	Track road, bears irregularly NW. and SE. along the top of a ridge; slope changes to E.
9.30	Slope changes to NE.
12.00	Slope changes to N.
32.80	Ravine, drains W.; asc. S. slope.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.  Set the iron post 7 ins. in the ground, mound of stone to top, brass cap mkd.  <div style="text-align: center;">                     T17NR8W                      1/4                      S28   S27                      1968                 </div>
47.20	Spur, slopes SW.; desc. NW. slope.
52.20	Draw, drains SW.; asc. SW. slope.
64.50	Ridge, bears NW. and SE.; desc. NE. slope.
76.80	Draw, drains NE.; asc. SE. slope.
78.90	Low Spur, slopes E.; desc. along E. slope.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.  Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.  <div style="text-align: center;">                     T17NR8W                      S21   S22                      S28   S27                      1968                 </div>
Cor. is located on an E. slope.	
Land, sharply rolling. Soil, sandy loam, rocky. Timber, scattered juniper and pine. Undergrowth, dense oak brush.	

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
	From the cor. of secs. 22, 23, 26 and 27.
	West, bet. secs. 22 and 27.
	Over gently rolling land.
23.50	Track road, bears N. 30° W. and S. 30° E.
40.03	Point for the ¼ sec. cor. of secs. 22 and 27.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	<div style="text-align: center;">                     T17NR8W                      ¼ <u>S22</u>                            S27                            1968                 </div>
	Raise a mound of stone N. of the cor.
59.20	Draw, drains SW.
68.40	Low spur, slopes S.
76.70	Draw, drains NW.; asc. E. slope.
80.06	The cor. of secs. 21, 22, 27 and 28.
	Land, gently rolling.
	Soil, sandy loam, rocky.
	Timber, scattered juniper.
	Undergrowth, grass in the E. half, dense oak brush in the W. half.
	N. 0° 01' W., bet. secs. 21 and 22.
	Desc. over E. slope through dense oak brush.
13.50	Wash, 50 lks. wide, 4 ft. deep, drains NW. approximately 15 chs. to a stock pond; asc. SW. slope.
32.50	Spur, slopes SW.; desc. NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 21 and 22.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<div style="text-align: center;">                     T17NR8W                      ¼ <u>S21</u>   <u>S22</u>                            1968                 </div>
45.73	Intersect the S. Bdy. of LMBF No. 5.
	Point for the closing cor. of secs. 21 and 22.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	<div style="text-align: center;"> <u>LMBF NO 5</u>  <u>S21</u>   <u>S22</u>                      C C                      T17NR8W                      1968                 </div>
	from which
	The 39th Mi. Cor. of LMBF No. 5, bears N. 87° 15' E.,
	4.28 chs. dist.

## Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

## CHAINS

Raise a mound of stone S. of the Cor. The Cor. is located in a track road bearing NE. and S. 60° W.

Land, rolling.  
Soil, sandy loam, rocky.  
Timber, scattered juniper and pine.  
Undergrowth, grass, dense oak brush.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 22 is at midpoint bet, the closing corners and on the S. Bdy. of LMBF No. 5.

At the corner point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

$\frac{1}{4}$  S22  
T17NR8W  
1968

from which

The 39 Mi. Cor. bears N. 88° 15' W., 35.78 chs. dist.

Raise a mound of stone S. of cor.

From the standard cor. of secs. 32 and 33, on the S. Bdy. of the tp., monumented by an iron post, 2 ins. diam., set firmly in a mound of stone to the top, with a mound of stone N., brass cap mkd.

SC  
T17NR8W  
S32 | S33  
1930

from which original bearing trees

A pine, 15 ins. diam., bears N. 45° E., 142 lks. dist., mkd. T17N R8W S33 SC BT.

A pine, 7 ins. diam., bears N. 26° W., 30 lks. dist., mkd. T17N R8W S32 BT (Record diam. 14 ins.)

N. 0° 02' W., bet. secs. 32 and 33.

Over gently rolling land; through dense oak brush and scattered juniper and pine.

4.50 Track road, bears N. 30° E. and S. 30° W.

6.00 Low saddle, bears E. and W.; desc. NW. slope.

8.50 Track road, bears S. 40° E. and N. 80° W.

16.00 Spur, slopes NW.

27.60 Spur, slopes NW.

39.90 Wash, 10 lks. wide, 3 ft. deep, drains SW.; asc. SW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 32 and 33.

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS		
	<p>Set the iron post 7 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W  <math>\frac{1}{2}</math>                      S32   S33                      1968</p>	
42.43	Fence, bears N. 60° W. and S. 60° E.	
50.60	Ridge, bears NE. and SW. ; desc. NE. slope.	
60.00	Draw, drains NE.; asc. SE. slope.	
70.00	Top of ascent; over nearly level land.	
79.90	Point selected for witness cor. of secs. 28, 29, 32 and 33.	
	<p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W  <math>\frac{S29 \uparrow S28}{S32   S33}</math>                      W C                      1968</p>	
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Mark an X on rock ledge at the true point which is 1 lk. south of the edge of a ledge 40 ft. high, bearing E. and W.</p> <p>Land, rolling.                      Soil, sandy loam, rocky.                      Timber, scattered juniper and pine.                      Undergrowth, dense oak brush.</p>	
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89° 57' W., bet. secs. 28 and 33.</p> <p>Over rolling land; through dense oak brush.</p>	
18.40	Small white spur, slopes N.	
40.03	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 33.</p> <p>Set the iron post over an X marked on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W  <math>\frac{1}{4}</math> <math>\frac{S28}{S33}</math>                      1968</p>	
	<p>Cor. is located at the base of a ledge 7 ft. high, facing NW.</p>	
65.00	(Approx. dist) Draw drains NW.; asc. E. slope.	
76.10	Top of cliffs, bears S. and N.; asc. slightly.	
80.06	<p>True point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling,                      Soil, rocky.</p>	

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
	<p>Timber, scattered juniper and pine. Undergrowth, dense oak brush.</p>
	<p>N. 0° 02' W., bet. secs. 28 and 29.</p> <p>Desc. abruptly over ledges facing N.</p>
30.00	(Approx. dist.) Bottom of canyon, drains W., asc. SW. slope.
40.00	<p>Point for the ¼ sec. cor. of secs. 28 and 29.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W ¼ S29   S28 1968</p> <p>Cor. is located on a steep S. slope.</p>
49.20	S. edge of ridge.
51.50	Ridge, bears E. and W.
52.50	N. edge of ridge; desc. steep N. slope.
57.50	Jeep trail, bears irregularly NW. and SE.
78.00	(Approx. dist) Ravine, drains NW. from E.; asc. SW. slope.
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W S20   S21 S29   S28 1968</p> <p>Cor. is located on steep SW. slope.</p> <p>Land, sharply rolling. Soil, rocky. Timber, scattered juniper and pine. Undergrowth, dense oak brush.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89° 55' W., bet. secs. 21 and 28.</p> <p>Asc. E. slope through dense oak brush.</p>
10.70	Ridge, bears SE. and NW.; desc. SW. slope.
37.50	Draw, drains S. from head 3 chs. N.; asc. SE. slope.
40.03	<p>Point for the ¼ sec. cor. of secs. 21 and 28.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W ¼ S21 S28 1968</p>



Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
44.00	Top of ascent, bears NE. and SW.; thence across mesa.
57.00	Edge of mesa, bears S. 60° E. and N. 60° W.; desc. SW. slope.
58.40	Desc. abruptly over steep ledges.
80.06	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling and broken. Soil, sandy loam, rocky. Timber, scattered juniper and pine. Undergrowth, dense oak brush.
	N. 0° 02' W., bet. secs. 20 and 21.
	Asc. steep rocky SW. slope.
25.00	(Approx. dist.) Spur, slopes W.; desc. NW. slope.
36.00	(Approx. dist.) Draw, drains W., asc. SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 20 and 21.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T17NR8W $\frac{1}{4}$ S20 S21 1968
40.80	Small draw, drains W.; asc. sharply.
41.85	Intersect the S. Bdy. of LMBF No. 5.
	Point for the closing cor. of secs. 20 and 21.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<u>LMBF NO 5</u> S20 S21 C C T17NR8W 1968
	from which
	The 40th Mi. Cor. of LMBF NO. 5, bears N. 87° 15' E., 8.30 chs. dist.
	Cor. is located on steep SW. slope.
	Land, rolling and broken. Soil, sandy loam, rocky. Timber, widely scattered juniper and pine. Undergrowth, dense oak brush.
	The point for the N. ¼ sec. cor. of sec. 21 is at mid-point bet. the closing corners and on the S. Bdy. of LMBF No. 5.
	At the corner point
	Set the iron post 18 ins. in the ground, brass cap mkd.

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	<u>LMBF NO 5</u> ½ S 21 T17NR8W 1968
	from which  The 40 Mi. Cor., bears S. 87° 15' W., 31.77 chs. dist.  Raise a mound of stone S. of the cor.
	From the standard cor. of secs. 31 and 32 on the S. Bdy. of the Tp. monumented by an iron post, 2 ins. diam., set firmly in a mound of stone to the top, a mound of stone N., brass cap mkd.  <div style="text-align: center;">                         S C                          T17NR8W  <u>S31 S32</u>                          1930                     </div> from which original bearing trees  A pine, 7 ins. diam., bears N. 68½° E., 55 lks. dist., mkd. T17N R8W S32 SC BT.  A pine, 7 ins. diam., bears N. 80° W., 98 lks. dist., mkd. T17N R8W S31 SC BT.  N. 0° 02' W., bet. secs. 31 and 32.  Asc. S. slope through medium dense juniper and pine and dense oak brush.
5.50	Track road, bears N. 20° E. and S. 60° W.
12.00	Top of ascent; desc. gradual NW. slope.
18.30	Desc. abruptly over ledges.
28.00	(Approx. dist.) Ravine drains NW.; asc. SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 31 and 32.  Set the iron post over an X marked on solid rock, in a mound of stone to the top, brass cap mkd.
	T17NR8W ½ <u>S31 S32</u> 1968
	Cor. is located on very steep rocky SW. slope.
51.90	Point on spur approximately 1 ch. W. of top of canyon; spur slopes W.; desc. NW. slope.
65.00	(Approx. dist.) Jeep trail, bears N. 60° E. and S. 60° W.
70.00	(Approx. dist.) Slope changes to SW.; asc.
74.50	Rim of canyon, bears NW. and SE.; desc. gradually across N. slope of mesa.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.  Set the iron post 22 ins. in the ground, brass cap mkd.

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS	
	<p style="text-align: center;">T17NR8W  <math>\frac{S30}{S31}   \frac{S29}{S32}</math>                      1968</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, sharply rolling.                      Soil, sandy loam, rocky.                      Timber, scattered juniper and pine.                      Undergrowth, dense oak brush.</p>
	<p>From the true point for the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89° 52' W., bet. secs. 29 and 32.</p> <p>Asc. along a NE. slope through dense oak brush.</p>
13.30	Top of ascent; desc. along a NW. slope.
28.50	E. edge of canyon, bears NW. and SE.; desc. abruptly.
35.00	(Approx. dist.) Bottom of canyon, drains NW.; asc. NE. slope.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T17NR8W  <math>\frac{1}{4} \frac{S29}{S32}</math>                      1968</p>
76.20	Top of ascent; thence across mesa.
79.98	The cor. of secs. 29, 30, 31 and 32.
	Land, broken. Soil, rocky. Timber, scattered juniper and pine. Undergrowth, dense oak brush.
	N. 89° 57' W., bet. secs. 30 and 31.
	Over mesa.
3.30	W. rim of mesa; desc. abruptly over ledges.
35.00	(Approx. dist.) Jeep trail, bears N. and S.
38.75	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T17N R8W  <math>\frac{1}{4} \leftarrow \frac{S30}{S31} \text{ WC}</math>                      1968</p>
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, falls on face of ledge sloping S. and can not be occupied.

Survey, Subdivisions Lines, Frac. T. 17 N., R. 8 W.

CHAINS		
79.90	<p>The cor. of secs. 25, 30, 31 and 36 on the W. Bdy. of the Tp., monumented by an iron post, 2 ins. diam., set firmly in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T17N R9W R8W <u>S25</u>   <u>S30</u> <u>S36</u>   <u>S31</u> 1938</p> <p>Cor. is located on W. slope approximately 2.50 chs. E. of Burro Creek.</p> <p>Land, steep, rocky, precipitous. Soil, rocky. Timber, scattered juniper and pine. Undergrowth, dense oak brush.</p>	
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 02' W., bet. secs. 29 and 30.</p> <p>Over mesa through dense oak brush and scattered juniper and pine.</p>	
16.40	<p>Malpais ledge, bears NW. and SE.; desc. abruptly over N. slope.</p>	
40.00	<p>Point for the ¼ sec. cor. of secs. 29 and 30.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W ¼ <u>S30</u>   <u>S29</u> 1968</p>	
48.00	<p>(Approx. dist.) Draw, drains N. 80° W.; asc. steep S. slope.</p>	
56.50	<p>Spur, slopes W.; desc. along W. slope.</p>	
58.90	<p>Begin desc. steep N. slope.</p>	
70.00	<p>(Approx. dist.) Burro Creek, 150 lks. wide, water 4 ins. deep, course W.; asc. S. slope.</p>	
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T17NR8W <u>S19</u>   <u>S20</u> <u>S30</u>   <u>S29</u> 1968</p> <p>Land, rolling and broken. Soil, rocky. Timber, scattered juniper and pine; oak along Burro Creek Undergrowth, dense oak brush.</p>	
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 51' W., bet. secs. 20 and 29.</p>	

## Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

CHAINS		
	Desc. steep SW. slope through dense oak brush.	
2.00	(Approx. dist.) Ravine, drains N. 15° W.; asc. steep E. slope.	
15.00	Spur, slopes N. 20° W. desc. along NW. slope.	
25.50	(Approx. dist.) Jeep trail, bears irregularly NW. and SE.	
27.00	(Approx. dist.) Slope changes to NE.; asc.	
39.96	Point for the ¼ sec. cor. of secs. 20 and 29.  Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.  T17NR8W ¼ <u>S20</u> S29 1968	
41.00	Spur, slopes N.; desc. NW. slope.	
43.00	Jeep trail, bears irregularly N. and S.	
43.20	Begin abrupt desc. over broken NW. slope.	
70.00	(Approx. dist.) Burro Creek, 150 lks. wide, water 4 ins. deep, course S. 10° W.; asc. broken SE. slope.	
79.92	The cor. of secs. 19, 20, 29 and 30.  Land, broken. Soil, rocky. Timber, scattered juniper and pine; oak along Burro Creek. Undergrowth, dense oak brush.	
	S. 89° 58' W., bet. secs. 19 and 30.  Asc. SE. slope.	
28.00	(Approx. dist.) Spur, slopes S.; desc. nearly vertical rocky W. slope.	
32.00	(Approx. dist.) Burro Creek, course NW. from SE.; continue along bottom of creek.	
35.00	(Approx. dist.) Burro Creek, course SW.; leave creek bottom; asc. steep E. slope.	
40.00	Point for the ¼ sec. cor. of secs. 19 and 30.  Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.  T17NR8W ¼ <u>S19</u> S30 1968	
51.30	Slope changes to S.	
55.90	Desc. over steep W. slope.	
58.80	Ravine, drains S.; asc. E. slope.	

Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

<p>CHAINS</p> <p>69.00</p> <p>76.30</p> <p>79.90</p>	<p>Spur, slopes S.; desc. SW. slope.</p> <p>Slope changes to W.</p> <p>The cor. of secs. 19, 24, 25 and 30 on the W. Bdy. of the Tp., monumented by an iron post, 2 ins. diam., set in a mound of stone to the top, a mound of stone W., brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R9W R8W <u>S24</u>   <u>S19</u> <u>S23</u>   <u>S30</u> 1938</p> </div> <p>Land, sharply rolling, broken. Soil, rocky. Timber, scattered juniper and pine; oak along Burro Creek. Undergrowth, oakbrush, rabbit brush, cacti.</p>
<p>10.00</p> <p>38.23</p>	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 02' W., bet. secs. 19 and 20.</p> <p>Asc. steep SE. slope.</p> <p>(Approx. dist.) Fence, Bears E. and W.</p> <p>Intersect the S. Bdy. of LMBF No. 5.</p> <p>Point for the closing cor. of secs. 19 and 20.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p><u>LMBF NO 5</u> <u>S19</u>   <u>S20</u> C C T17NR8W. 1968</p> </div> <p>from which</p> <p style="padding-left: 40px;">The 41st Mi. Cor. of LMBF No. 5, bears N. 87° 15' E., 12.18 chs. dist.</p> <p>Cor. falls on a steep E. slope.</p> <p>Land, broken. Soil, rocky. Timber, widely scattered juniper. Undergrowth, medium oak brush, rabbit brush, cacti.</p>
	<p>The point for the N. ¼ sec. cor. of sec. 20, is at midpoint bet. the closing corners and on the S. Bdy. of LMBF No. 5</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>¼ S20 T17N R8W 1968</p> </div>

## Survey, Subdivisional Lines, Frac. T. 17 N., R. 8 W.

## CHAINS

from which

The 41 Mi. Cor., bears S. 87° 15' W., 27.82 chs. dist.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 19 is S. 87° 15' W., 40.04 chs. dist. from the closing cor. of secs. 19 and 20, and on the S. Bdy. of LMBF No. 5.

At the corner point

Set the iron post 8 ins. in the ground, in a mound of stone to the top, brass cap mkd.

$\frac{1}{4}$  S19  
T17NR8W  
1968

from which

The 42 Mi. Cor., bears S. 87° 15' W., 23.90 chs. dist.

## General Description

Fractional Township 17 North, Range 8 West, is located in Yavapai County, approximately 15 miles north of Bagdad, Arizona. It can be reached by dirt roads from either Bagdad or Prescott. The north boundary of the township is a portion of the south boundary of Luis Maria Baca Float No. 5, a private land grant.

The eastern part of the township is gently rolling land while the western part is extremely broken. Burro Creek, the dominant topographic feature in the area, enters the township in section 20 and exits in section 30. Pine Creek, in the northeast corner, drains northwest into Burro Creek. Elevations range from 6000 feet in section 35 to 3800 feet at the bottom of Burro Creek.

There are several track roads in the township. These are mostly used by ranchers who maintain the several stock ponds in the township. Grass in the eastern part affords good grazing for cattle. The land is too rocky to be used for cultivation. Dense oak brush covers most of the hill sides. There are scattered juniper and pine trees in most of the township.

Old Indian ruins found throughout the tp., (chippings, sherds, matates, etc.) most prominent recorded in the field notes.

There is no known mining activity in the township.





CERTIFICATE OF SURVEY

I, **Jerrold E. Knight**, HEREBY CERTIFY upon honor that,  
in pursuance of special instructions bearing date of the 10th day of **July**, 19 **68**,

I have dependently resurveyed the south boundary of the Luis Maria Baca Float No. 5 from the 36 Mi. Cor. to the 42 Mi. Cor.; and dependently resurveyed the east boundary and surveyed the subdivisional lines of Fractional Township 17 North, Range 8 West,

of the **Gila and Salt River** Meridian, in the State of **Arizona**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 24, 1969  
(Date)

*Jerrold E. Knight*  
(Cadastral Surveyor)

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

**SUBMITTED FOR APPROVAL**  
Date APR 29 1969

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the dependent resurvey of the south boundary of the Luis Maria Baca Float No. 5 from the 36 Mi. Cor. to the 42 Mi. Cor.; and the dependent resurvey of the east boundary and survey of the subdivisional lines of Fractional Township 17 North, Range 8 West, of the Gila and Salt River Meridian, Arizona,

executed by **Jerrold E. Knight**

having been critically examined and found correct, are hereby approved.

DEC 10 1969  
(Date)

*[Signature]*  
Acting (Chief, Division of Engineering) Cadastral Survey

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief, Division of Engineering)~~