



BOOK 4853  
INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4853  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# INDEX TO SECTION CORNER MONUMENTS

Tp. 21 N., R. 8 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
5	5	3	2		1
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 24 N., R. 8 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	15	17	16	15	13
15	15	11	11	9	
19	14	20	21	22	24
14	14	10	9		
7	30	13	29	28	27
7	13	12	12	9	10
	31	32	33	34	35
					36

Tp. \_\_\_\_\_ R. \_\_\_\_\_ Mer. \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4853

1B

Township 21 North, Range 8 East  
 Township 24 North, Range 8 East  
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 17, 1968 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Township 21 North, Range 8 East, G&SR M., Arizona

The subdivisional lines were surveyed in 1879 by L. L. Harris and a portion of the subdivisional lines were re-surveyed in 1902 by Caudle and Caudle. The cor. of secs. 7, 8, 17 and 18 was reestablished in 1919 by the survey of H.E.S. No. 377 by Hodson and Hendrix.

Re monumentation, T. 21 N., R. 8 E., G&SR M., Arizona

The ¼ sec. cor. of secs. 13 and 24, monumented by a limestone, 20 x 10 x 8 ins., lying loose on the ground, mkd. ¼ on N. face, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 12 ins. diam., bears N. 23½° E., 111 lks. dist., mkd. 13 BT.

A pine stump, with a fallen tree, 12 ins. diam., alongside, bears S. 40½° E., 51 lks. dist., tree mkd. 24 B.

At the cor. point

Set the iron post, 6 ins. in the ground, mound of stone to top, brass cap mkd.

T21N R8E

¼  $\frac{S13}{S24}$

1968

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

The cor. of secs. 21, 22, 27 and 28, monumented by a limestone, 18 x 10 x 6 ins., set 5 ins. in the ground, mkd. with 3 notches on E. face and 2 notches on S. face, with mound of stone to the W. From the cor., the remains of the orig. bearing trees

A pine, 24 ins. diam., bears N. 42½° E., 72 lks. dist., mkd. with an overgrown blaze.

A pine stump, 33 ins. diam., bears S. 83 3/4° E., 196 lks. dist., no mks.

A pine, 28 ins. diam., bears S. 43½° W., 118 lks. dist., mkd. with an overgrown blaze.

A pine, 32 ins. diam., bears N. 52° W., 64 lks. dist., mkd. TXXINRVIIE XXI.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T21N R8E  
S21|S22  
S28|S27  
 1968

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 15, 16, 21 and 22, monumented by a stump hole, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 36 ins. diam., bears N. 44° E., 59 lks. dist., mkd. with faint scribe mks.

A pine stump, 32 ins. diam., bears S. 66° E., 79 lks. dist., no mks.

A pine stump, 42 ins. diam., bears S. 78° W., 155 lks. dist., no mks.

A dead pine snag, 32 ins. diam., bears N. 58° W., 78 lks. dist., mkd. TXXINRVIIE XVI.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R8E  
S16|S15  
S21|S22  
 1968

from which

A pine, 22 ins. diam., bears S. 26° E., 129 lks. dist., mkd. T21N R8E S22 BT.

Cor. is N. 40° W., 30 lks. dist., from fence cor., from which fences bear N. and E.

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

The cor. of secs. 20, 21, 28 and 29, monumented by a stump hole, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 36 ins. diam., bears N. 89° E., 148 lks. dist., mkd. with an overgrown blaze.

A pine stump, 33 ins. diam., bears S. 3° E., 35 lks. dist., mkd. with an overgrown blaze.

A pine, 28 ins. diam., bears S. 50° W., 31 lks. dist., mkd. with an overgrown blaze.

A pine stump, 24 ins. diam., bears N. 54° W., 31 lks. dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R8E  
S20 | S21  
S29 | S28  
 1968

from which

A pine, 6 ins. diam., bears S. 70° E., 85 lks. dist., mkd. T21N R8E S28 BT.

Cor. is 65 lks. E. of a track road, bearing N. and S.

The cor. of secs. 16, 17, 20 and 21, monumented by a sandstone, 21 x 12 x 6 ins., set 6 ins. in the ground, mkd. with 3 notches on S. face and 4 notches on E. face, from which the remains of the orig. bearing trees

A pine, 33 ins. diam., bears N. 68° E., 108 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears S. 63° E., 62 lks. dist., mkd. TXXINRVIIE XXI.

A pine stump, 21 ins. diam., bears S. 45° W., 68 lks. dist., mkd. XXIN RVIIE XX.

A pine stump, 15 ins. diam., bears N. 46° W., 10 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 8 ins. in the ground to bedrock, mound of stone to top, brass cap mkd.

T21N R8E  
S17 | S16  
S20 | S21  
 1968

Bury the orig. cor. stone alongside the iron post.

Cor. is near the top of a hill on a steep S. slope, 100 lks. E. of a power line bearing N. and S.

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, monumented by a limestone, 24 x 12 x 6 ins., set 6 ins. in the ground, mkd.  $\frac{1}{4}$  on W. face, from which the orig. bearing trees

A pine, 32 ins. diam., bears S. 66° E., 119 lks. dist., mkd. with a blaze, partly overgrown, and faint scribe mks.

A pine, 24 ins. diam., bears N. 69° W., 78 lks. dist., mkd. with a blaze, partly overgrown, and faint scribe mks.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T21N R8E

$\frac{1}{4}$   
S17|S16  
1968

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 260 lks. E. of a power line bearing N. and S.

The cor. of secs. 8, 9, 16 and 17, monumented by a sandstone, 24 x 9 x 5 ins., set 12 ins. in the ground, mkd. with 4 notches on E. face and 4 notches on S. face, from which the remains of the orig. bearing trees

A pine stump, 48 ins. diam., bears N. 51° E., 98 lks. dist., no mks.

A pine, 42 ins. diam., bears S. 61° E., 131 lks. dist., mkd. with an overgrown blaze. (Note: record bearing and dist. S. 53° E., 60 lks.).

A pine stump, 24 ins. diam., bears S. 67° W., 64 lks. dist., mkd. with an overgrown blaze.

A dead pine snag, 32 ins. diam., bears N. 41° W., 66 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T21N R8E

S 8|S 9  
S17|S16  
1968

Bury the orig. cor. stone alongside the iron post.

Cor. is about 3 chs. E. of a power line bearing N. and S.

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

The cor. of secs. 17, 18, 19 and 20, monumented by a limestone, 12 x 9 x 6 ins., set 6 ins. in the ground, in a mound of stone, mkd. with 5 notches on E. face and 3 notches on S. face, from which the remains of the orig. bearing trees

A pine stump, 23 ins. diam., bears S. 79° E., 136 lks. dist., no mks.

A pine, 32 ins. diam., bears S. 30° W., 100 lks. dist., mkd. with an overgrown blaze.

A pine, 28 ins. diam., bears N. 29° W., 89 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R8E  
 $\frac{S18}{S19} | \frac{S17}{S20}$   
 1968

Bury the orig. cor. stone alongside the iron post.

Cor. is 3 lks. S. and 45 lks. E. of a fence cor., from which fences bear N., E. and W., and about 170 lks. W. of a track road bearing N. and S.

The  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, monumented by a water pipe,  $\frac{1}{2}$  in. diam., set in a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 27 ins. diam., bears North, 33 lks. dist., no mks.

A pine, 36 ins. diam., bears S. 30° W., 140 lks. dist., mkd. with a blaze, partly overgrown, and scribe mark S.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R8E  
 $\frac{1}{4} \frac{S18}{S19}$   
 1968

from which

A pine, 10 ins. diam., bears North, 37 lks. dist., mkd.  $\frac{1}{4}$  T21N R8E S18 BT.

Bury orig. water pipe alongside the iron post.

Cor. is on a fence bearing E. and W., 25 lks. W. of a track road bearing N. and S.



## Remonumentation, T. 21 N., R. 8 E., Arizona

## CHAINS

The cor. of secs. 7, 8, 17 and 18, monumented by a brass cap, 1½ ins. diam., set in concrete, mkd. T21N R8E 7 8 18 17 RLS 4321, from which the orig. bearing trees

A pine, 23 ins. diam., bears N. 46½° E., 272 lks. dist., mkd. T21N R8E S8 BT.

A pine, 36 ins. diam., bears S. 71° E., 384 lks. dist., mkd. T21N R8E S17 BT.

from which new accessories

An iron post, set 24 ins. in the ground, in a collar of stone, for a reference monument, bears S. 56° W., 56.1 lks. dist., brass cap mkd. T21N R8E RM 37 FT 1968 and an arrow pointing to the true cor.

An iron post, set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 35° W., 56.1 lks. dist., brass cap mkd. T21N R8E RM 37 FT 1968 and an arrow pointing to the true cor.

Cor. is on the W. shoulder of a black top road, bearing N. and S., 13 ft. W. of center line of road.

Remonumentation, T. 24 N., R. 8 E., Arizona

CHAINS

Township 24 North, Range 8 East, G&SR M., Arizona

The west boundary was surveyed in 1883 by A. E. Shoemaker and resurveyed in 1902 by J. A. Lamport. The subdivisional lines were surveyed in 1902 by J. A. Lamport.

Remonumentation, T. 24 N., R. 8 E., G&SR M., Arizona

The cor. of secs. 25, 30, 31 and 36, T. 24 N., Rs. 7 and 8 E., monumented by a malpais stone, 22 x 12 x 6 ins., set 16 ins. in the ground, mkd. with 5 notches on N. face and 1 notch on S. face, with mound of stone to the W. From the cor., the remaining orig. bearing tree

A cedar, 15 ins. diam., bears S. 12½° E., 61 lks. dist., mkd. T24N R8E S31 BT.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T24N  
R7E R8E  
S25|S30  
S36|S31  
1968

No new bearing trees available.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is on the top of a ridge bearing NE. and SW.

The ¼ sec. cor. of secs. 25 and 30, T. 24 N., Rs. 7 and 8 E., monumented by a granite stone, 24 x 8 x 6 ins., lying loose upon the ground, in a collar of stone, with mound of stone to the E., verified by record course and dist. from the remains of an orig. bearing tree

A stump hole, with a dead and fallen pinon tree, 9 ins. diam., alongside, bears S. 80° E., 33 lks. dist., mkd. ¼ S30 BT.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T24N  
R7E R8E  
¼  
S25|S30  
1968

from which

A cedar, 4 ins. diam., bears S. 3° W., 28 lks. dist., mkd. X BT.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is in the center of a swale, draining northeasterly from the S.

Remonumentation, T. 24 N., R. 8 E., Arizona

<p>CHAINS</p>	<p>The cor. of secs. 19, 24, 25 and 30, T. 24 N., Rs. 7 and 8 E., monumented by a malpais stone, 17 x 10 x 6 ins., set 9 ins. in the ground, in a mound of stone, mkd. X on top and with faint scribe mks. on the N. and S. faces, from which the remains of an orig. bearing tree</p> <p>A stump hole, with a dead and fallen pinon tree, 15 ins. diam., alongside, bears S. 72¼° E., 37 lks. dist., mkd. T24N R8E S30 BT.</p> <p>At the cor. point</p> <p>Set the iron post, 26 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">             T24N              R7E R8E  <u>S24 S19</u>  <u>S25 S30</u>              1968         </p> <p>from which</p> <p>A cedar, 12 ins. diam., bears S. 18° W., 134 lks. dist., mkd. T24N R7E S25 BT.</p> <p>A cedar, 12 ins. diam., bears S. 44½° W., 172 lks. dist., mkd. T24N R7E S25 BT.</p> <p>Raise a mound of stone W. of the iron post.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. is 65 lks. N. of forest road No. 45142, which bears E. and W.</p> <hr/> <p>The cor. of secs. 27, 28, 33 and 34, monumented by a lava stone, 24 x 8 x 5 ins., set 18 ins. in the ground, mkd. with 3 notches on E. face and 1 notch on S. face, with mound of stone to the W. From the cor., the remains of the orig. bearing trees</p> <p>A stump hole, with a dead and fallen pine tree, 15 ins. diam., alongside, bears N. 54¼° E., 128 lks. dist., mkd. T24N R8E S27 BT.</p> <p>A pine, 22 ins. diam., bears S. 61 3/4° E., 160 lks. dist., mkd. with an overgrown blaze.</p> <p>A pine, 30 ins. diam., bears S. 30¼° W., 77 lks. dist., mkd. T24N R8E S33 BT.</p> <p>A stump hole, bears N. 44¼° W., 155 lks. dist.</p> <p>At the cor. point</p> <p>Set the iron post, 26 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">             T24N R8E  <u>S28 S27</u>  <u>S33 S34</u>              1968         </p> <p>from which</p> <p>A pinon, 9 ins. diam., bears N. 72° E., 130½ lks. dist., mkd. T24N R8E S27 BT.</p>
---------------	--

Remonumentation, T. 24 N., R. 8 E., Arizona

CHAINS

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is at the foot, on the N. side, of a 70 ft. high hill, about 4½ chs. S. of forest road No. 4546, which bears E. and W.

The ¼ sec. cor. of secs. 21 and 22, monumented by a lava stone, 15 x 10 x 6 ins., set 10 ins. in the ground, mkd. ¼ on W. face, with mound of stone to the W. From the cor., the orig. bearing tree

A cedar, 12 ins. diam., bears N. 88 ¾° E., 325 lks. dist., mkd. ¼ S22 BT.

At the cor. point

Set the iron post, 12 ins. in the ground, mound of stone to top, brass cap mkd.

T24N R8E  
¼  
S21|S22  
1968

Bury the orig. cor. stone alongside the iron post.

Cor. is about 5 chs. W. of a track road, bearing N. and S.

The cor. of secs. 15, 16, 21 and 22, monumented by a lava stone, 23 x 16 x 10 ins., set 17 ins. in the ground, mkd. with 3 notches on E. face and 3 notches on S. face, with mound of stone to the W. From the cor., the reamining orig. bearing tree

A cedar, 9 ins. diam., bears S. 62° E., 117 lks. dist., mkd. T24N R8E S22 BT.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T24N R8E  
S16|S15  
S21|S22  
1968

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is on a ridge bearing N. and S., 65 lks. S. of a track road bearing E. and W.

The cor. of secs. 28, 29, 32 and 33, monumented by a lava stone, 26 x 10 x 6 ins., set 18 ins. in the ground, mkd. with 4 notches on E. face and 1 notch on S. face, with mound of stone to the N.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, T. 24 N., R. 8 E., Arizona

CHAINS

T24N R8E  
 $\frac{S29}{S32} | \frac{S28}{S33}$   
 1968

from which

A cedar, 9 ins. diam., bears N.  $20\frac{1}{2}^\circ$  E., 28 lks. dist., mkd. T24N R8E S28 BT.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 160 lks. S. of forest road No. 4546, which bears E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 28 and 33, monumented by a lava rock, 15 x 10 x 8 ins., set 9 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, from which the remains of the orig. bearing trees

A cedar, 20 ins. diam., bears S.  $20^\circ$  W., 20 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

A stump hole, with a dead and fallen pinon tree, 8 ins. diam., alongside, bears N.  $39^\circ$  W., 192 lks. dist., mkd.  $\frac{1}{4}$  S28 BT.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T24N R8E  
 $\frac{1}{4} \frac{S28}{S33}$   
 1968

from which

A pinon, 5 ins. diam., bears S.  $49\frac{1}{2}^\circ$  E., 14 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about  $2\frac{1}{2}$  chs. N. of forest road No. 4546, which bears E. and W., and 5 lks. N. of a fence bearing E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, monumented by a lava stone, 16 x 12 x 8 ins., set 12 ins. in the ground, with a mound of stone to the N.

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T24N R8E  
 $\frac{1}{4} \frac{S21}{S28}$   
 1968

No new bearing trees available.

Rebuild the mound of stone N. of the iron post.

Remonumentation, T. 24 N., R. 8 E., Arizona

CHAINS

Bury the orig. cor. stone alongside the iron post.

Cor. is about 8 chs. E. of a fence cor., from which fences bear N. and W.

The cor. of secs. 16, 17, 20 and 21, reestablished by record course and dist. from the remaining orig. bearing trees

A cedar, 15 ins. diam., bears S. 37½° E., 421 lks. dist., mkd. T24N R8E S21 BT.

A cedar, 15 ins. diam., bears S. 30½° W., 152 lks. dist., mkd. T24N R8E.

A cedar, 8 ins. diam., bears N. 18° E., 310 lks. dist., mkd. T24N R8E S16 BT. (Note: record dist. 261 lks.).

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T24N R8E  
 $\frac{S17}{S20} | \frac{S16}{S21}$   
 1968

No new bearing trees available.

Raise a mound of stone W. of the iron post.

Cor. is 20 lks. E. of a power line bearing N. and S.

The ¼ sec. cor. of secs. 16 and 21, monumented by a lava stone, 15 x 12 x 10 ins., set 11 ins. in the ground, mkd. ¼ on N. face, with mound of stone to the N. From the cor., the orig. bearing trees

A cedar, 17 ins. diam., bears N. 64° E., 102 lks. dist., mkd. with a blaze, partly overgrown, and faint scribe marks. (Note: record bearing N. 20½° E.).

A cedar, 10 ins. diam., bears S. 20½° W., 123 lks. dist., mkd. with an overgrown blaze. (Note: record bearing S. 64° W.).

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T24N R8E  
 $\frac{1}{4} \frac{S16}{S21}$   
 1968

No new bearing trees available.

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 24 N., R. 8 E., Arizona

<p>CHAINS</p>	<p>The cor. of secs. 8, 9, 16 and 17, monumented by a lava stone, 14 x 14 x 5 ins., set 10 ins. in the ground, mkd. with 4 notches on E. face and 4 notches on S. face, with mound of stone to the W. From the cor., the orig. bearing tree</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 35½° E., 90 lks. dist., mkd. T24N R8E S16 BT.</p> <p>At the cor. point</p> <p>Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T24N R8E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S17</td> <td style="padding: 0 5px;">S16</td> </tr> </table> <p>1968</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears S. 69° W., 101 lks. dist., mkd. T24N R8E S17 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. is 30 lks. E. of a power line bearing N. and S., and about 8 chs. W. of U. S. Highway 89.</p> <hr/> <p>The cor. of secs. 29, 30, 31 and 32, monumented by a lava rock in place, 6 x 2 x 1½ ft. above ground, mkd. X on top at cor. pt., with mound of stone to the W. From the cor., the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam., bears N. 67° E., 14 lks. dist., mkd. T24N R8E S29 BT.</p> <p style="padding-left: 40px;">A stump hole, with a dead and fallen pinon tree, 10 ins. diam., alongside, bears S. 35° W., 30 lks. dist., mkd. T24N R8E S31 BT.</p> <p style="padding-left: 40px;">A pinon stump, 12 ins. diam., bears N. 62½° W., 34 lks. dist., no mks.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 89° W., 21 lks. dist., mkd. T24N R8E S31 BT.</p> <p>Cor. is 20 lks. N. of a wash, draining northeasterly.</p> <hr/> <p>The ¼ sec. cor. of secs. 29 and 32, monumented by a lava stone, 16 x 16 x 12 ins., set 10 ins. in the ground, mkd. ¼ on N. face, with mounds of stone to the N. and S.</p> <p>At the cor. point</p> <p>Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T24N R8E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S29</td> <td style="padding: 0 5px;">S32</td> </tr> </table> <p>1968</p> </div>	S 8	S 9	S17	S16	¼ S29	S32
S 8	S 9						
S17	S16						
¼ S29	S32						

## Remonumentation, T. 24 N., R. 8 E., Arizona

## CHAINS

from which

A pinon, 6 ins. diam., bears S.  $49\frac{1}{4}^{\circ}$  E., 298 lks. dist., mkd.  $\frac{1}{4}$  S32 BT.

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 115 lks. E. of U. S. Highway 89, which bears N. and S., and 100 lks. S. of forest road No. 4546, which bears E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 30 and 31, monumented by a lava stone, 14 x 12 x 6 ins., set 9 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, with mound of stone to the N. From the cor., the remaining orig. bearing tree

A pinon, 12 ins. diam., bears S.  $45\frac{3}{4}^{\circ}$  W., 205 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.

At the cor. point

Set the iron post, 27 ins. in the ground, brass cap mkd.

T24N R8E  
 $\frac{1}{4}$  S30  
 S31  
 1968

No new bearing trees available.

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is on top of small ridge, bearing NE. and SW.

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, monumented by a lava stone, 24 x 14 x 6 ins., set 12 ins. in the ground, in a mound of stone, mkd.  $\frac{1}{4}$  on W. face, from which the remaining orig. bearing tree

A cedar, 14 ins. diam., bears S.  $10^{\circ}$  E., 50 lks. dist., mkd.  $\frac{1}{4}$  S29 BT.

At the cor. point

Set the iron post, 19 ins. in the ground, in a collar of stone, brass cap mkd.

T24N R8E  
 $\frac{1}{4}$   
 S30|S29  
 1968

No new bearing trees available.

Bury the orig. cor. stone alongside the iron post.

Cor. is on the E. side of a small knoll.



Remonumentation, T. 24 N., R. 8 E., Arizona

CHAINS

The cor. of secs. 19, 20, 29 and 30, monumented by a broken lava stone, 14 x 10 x 6 ins., set 6 ins. in the ground, in a mound of stone, mkd. with 4 notches on E. face and 2 notches on S. face, from which the orig. bearing trees

A cedar, 6 ins. diam., bears S. 52° E., 361 lks. dist., mkd. T24N R8E S29 BT. (Note: record bearing S. 38½° E.).

A cedar, 9 ins. diam., bears N. 70° W., 126 lks. dist., mkd. with a blaze, partly overgrown, and faint scribe mks. (Note: record bearing N. 20½° W.)

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T24N R8E  
 S19|S20  
 S30|S29  
 1968

No new bearing trees available.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 60 lks. N. of a track road bearing E. and W., and 25 lks. S. of a fence cor., from which fences bear N. and E.

The ¼ sec. cor. of secs. 19 and 20, monumented by a lava stone, 30 x 14 x 10 ins., set 14 ins. in the ground, mkd. ¼ on W. face, with mound of stone to the W. From the cor., the orig. bearing trees

A cedar, 8 ins. diam., bears S. 22° E., 108 lks. dist., mkd. ¼ S20 BT. (Note: record dist. 353 lks.).

A cedar, 8 ins. diam., bears N. 37 ¾° W., 353 lks. dist., mkd. ¼ S19 BT. (Note: record dist. 108 lks.).

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T24N R8E  
 ¼  
 S19|S20  
 1968

No new bearing trees available.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 10 chs. N. of a fence cor., from which fences bear N. and E.

Remonumentation, T. 24 N., R. 8 E., Arizona

CHAINS

The cor. of secs. 17, 18, 19 and 20, monumented by a lava stone, 14 x 12 x 8 ins., set 9 ins. in the ground, mkd. with 5 notches on E. face and 3 notches on S. face, with scattered mound of stone to the W. From the cor., the remaining orig. bearing tree

A cedar, 7 ins. diam., bears N. 21 3/4° W., 559 lks. dist., mkd. T24N R8E S18 BT.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T24N R8E  
 S18|S17  
 S19|S20  
 1968

Bury the orig. cor. stone alongside the iron post.

Cor. is on the N. edge of a small wash area draining SE., about 10 chs. E. of the base of a hill.

The 1/4 sec. cor. of secs. 18 and 19, monumented by a lava stone, 30 x 6 x 6 ins., set 24 ins. in the ground, mkd. 1/4 on N. face, with scattered mound of stone to the N. From the cor., the orig. bearing trees

A pinon, 15 ins. diam., bears S. 55° E., 144 lks. dist., mkd. with an overgrown blaze.

A pinon, 11 ins. diam., bears N. 48° W., 276 lks. dist., mkd. 1/4 S18 BT.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T24N R8E  
 1/4 S18  
 S19  
 1968

from which

A cedar, 7 ins. diam., bears S. 11° E., 22 lks. dist., mkd. 1/4 S19 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is on the W. slope of a small draw, draining W.

The 1/4 sec. cor. of secs. 17 and 18, monumented by a lava stone, 20 x 10 x 6 ins., set 14 ins. in the ground, mkd. 1/4 on W. face, with mound of stone to the W. From the cor., the orig. bearing tree

A cedar, 8 ins. diam., bears S. 57 1/4° W., 122 lks. dist., mkd. 1/4 S18 BT.

At the cor. point

Remonumentation, T. 24 N., R. 8 E., Arizona

<p>CHAINS</p>	<p>Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T24N R8E  <math>\frac{1}{4}</math>  S18 S17  1968</p> <p>No new bearing trees available.</p> <p>Rebuild mound of stone W. of the iron post.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. is in the bottom of a small swale, draining N.</p>	
	<p>The cor. of secs. 7, 8, 17 and 18, monumented by a lava stone, 18 x 12 x 6 ins., set 14 ins. in the ground, mkd. with 5 notches on E. face and 4 notches on S. face, from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears N. <math>58\frac{1}{2}^{\circ}</math> E., 55 lks. dist., mkd. T24N R8E S8 BT.</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears S. <math>32\frac{3}{4}^{\circ}</math> E., 167 lks. dist., mkd. T24N R8E S17 BT.</p> <p style="padding-left: 40px;">A cedar, 5 ins. diam., bears S. <math>48\frac{1}{2}^{\circ}</math> W., 174 lks. dist., mkd. T24N R8E S18 BT.</p> <p style="padding-left: 40px;">A cedar, 5 ins. diam., bears N. <math>51\frac{1}{2}^{\circ}</math> W., 154 lks. dist., mkd. T24N R8E S7 BT.</p> <p>At the cor. point</p> <p>Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T24N R8E  S 7 S 8  S18 S17  1968</p> <p>No new bearing trees available.</p> <p>Bury the orig. cor. stone alongside the iron post.</p>	
	<p style="text-align: center;"><u>General Statement</u></p> <p>The official record was found to be in error for some of the bearings and distances given for the bearing trees. A few of the trees were misnamed as to specie. A ring growth count was made on several trees which proved they were marked at the time of the original survey.</p> <p>Where the original corner monument appeared to be undisturbed, it was accepted as the true point for the corner.</p>	



18

BOOK 4853

CERTIFICATE OF SURVEY

(I) ~~(ME)~~, Howard H. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 17th day of June, 1968, (I) ~~(ME)~~ have remonumented a portion of the cadastral survey corners in Township 21 North, Range 8 East, and Township 24 North, Range 8 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~XXXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 14, 1969  
(Date)

*Howard H. Thomas*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date JUL 3 0 1969

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 21 North, Range 8 East, and Township 24 North, Range 8 East, of the Gila and Salt River Meridian, Arizona,

executed by Howard H. Thomas, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUN 3 1970  
(Date)

*Clark L. Sumner*  
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)