

Form 4-679  
(January 1963)

**BOOK 4854**  
**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**BUREAU OF LAND MANAGEMENT**

**FIELD NOTES**

of

REMONUMENTATION

in

TOWNSHIP 20 NORTH, RANGE 6 EAST

TOWNSHIP 21 NORTH, RANGE 6 EAST

TOWNSHIP 21 NORTH, RANGE 7 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

**EXECUTED BY**

Howard H. Thomas, Cadastral Surveyor

Under special instructions dated June 17, 19 68, which provided for the surveys  
included under Group Number 501, approved June 17, 1968  
and assignment instructions dated June 26, 19 68.

Survey commenced July 1, 19 68

Survey completed September 12, 19 68

BOOK 4854  
INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION  
CORNER MONUMENTS

Tp. 20 N., R. 6 E. Mer. G&SR

6	5	4	7	3	2	1
11	10		7			4
7	8	9	10	11	12	2
		8	6	5	3	1
18	17	16	15	14	13	
				5		
19	10	20	21	22	23	24
9	9	8	6	4		
30	29	28	27	26	25	
	9					
31	32	33	34	35	36	
3	2					

Tp. 21 N., R. 6 E. Mer. G&SR

6	5	4	3	2	1	14
				16	16	14
7	8	9	10	15	12	13
				15		12
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
		18	17			12
31	32	33	34	35	36	
		13				

Tp. 21 N., R. 7 E. Mer. G&SR

6	5	4	3	2	1	
	20					
7	20	8	9	10	11	12
	19					
18	17	16	15	14	13	19
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Township 20 North, Range 6 East  
 Township 21 North, Range 6 East  
 Township 21 North, Range 7 East  
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 17, 1968 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long,  $2\frac{1}{2}$  inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Township 20 North, Range 6 East, G&SR M., Arizona

The east and south boundaries and subdivisional lines were surveyed in 1878 by J. L. Harris. The south boundary was retraced in 1900 by C. R. Caudla. The  $\frac{1}{4}$  sec. cor. of Secs. 19 and 20 and the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30 were reestablished in 1915 in the survey of H.E.S. No. 396 by C. D. Hodson.

Remonumentation, T. 20 N., R. 6 E., G&SR M., Arizona

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, T. 20 N., Rs. 6 and 7 E., monumented by a wooden stake set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A rotten pine stump, 20 ins. diam., bears N.  $61^{\circ}$  E., 34 lks. dist. mkd. with faint scribe mks.

A rotten pine stump, 27 ins. diam., bears S.  $70^{\circ}$  W., 34 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T20N  
 R6E R7E  
 $\frac{1}{4}$   
 S12 S 7  
 1968

from which

An oak, 14 ins. diam., bears N.  $65^{\circ}$  E., 15 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

Raise a mound of stone W. of the iron post.

Cor. is under a fence, bearing N. and S., on a general S. slope.

Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

The cor. of secs. 1, 6, 7 and 12, T. 20 N., Rs. 6 and 7 E., monumented by a water pipe, 1 in. diam., set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A dead pine, 21 ins. diam., bears N. 32° E., 35 lks. dist., mkd. with a blaze, partly overgrown, and faint scribe mks. (Note: record dist. 14 lks.).

A pine stump, 32 ins. diam., bears S. 35° W., 109 lks. dist., mkd. with faint scribe mks.

A stump hole, with a rotted log, 20 ins. diam., alongside, bears N. 30° W., 35 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N  
R6E R7E  
S 1 | S 6  
S12 | S 7  
1968

from which

A pine, 18 ins. diam., bears S. 55° E., 61 lks. dist., mkd. T20N R7E S7 BT.

A pine, 8 ins. diam., bears S. 42° W., 82 lks. dist., mkd. T20N R6E S12 BT.

Deposit water pipe alongside iron post.

Cor. is under a fence, bearing N. and S., 10 lks. E. of a tract road, bearing N. and SW.

The cor. of secs. 5, 6, 31 and 32, Tps. 19 and 20 N., R. 6 E., monumented by a malpais stone, 15 x 10 x 9 ins., set 10 ins. in the ground, in a mound of stone, mkd. with 5 notches on E. face and 1 notch on W. face. This cor. now refers to secs. 31 and 32 only.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
S31 | S32  
1968

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 40 lks. W. of a road intersection, from which roads bear N., S., E. and NW.

## Remonumentation, T. 20 N., R. 6 E., Arizona

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, Tps. 19 and 20 N., R. 6 E., monumented by a malpais stone, broken in half, 16 x 8 x 5 ins., set 8 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face. This cor. now refers to sec. 31 only.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
 $\frac{1}{4}$  S31  
1968

from which

A pine, 28 ins. diam., bears S. 40° E., 438 lks. dist., mkd. T19N R6E S6 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 2 chs. E. of a large dyke, bearing N. and S.

The cor. of secs. 11, 12, 13 and 14, monumented by rotted wood set in ground, in center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A dead pine snag, 26 ins. diam., bears N. 20° E., 33 lks. dist., mkd. with faint scribe mks. (Note: record dist. 51 lks.).

A stump hole, with a dead and fallen pine tree, 30 ins. diam., alongside, bears S. 19° E., 72 lks. dist., mkd. TXXN.

A stump hole, bears S. 71° W., 17 lks. dist.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
S11 | S12  
S14 | S13  
1968

from which

A pine, 11 ins. diam., bears S. 74° E., 103 lks. dist., mkd. T20N R6E S13 BT.

A pine, 18 ins. diam., bears S. 68° W., 78 lks. dist., mkd. T20N R6E S14 BT.

Raise a mound of stone W. of the iron post.

Cor. is 20 lks. S. of a fence, bearing E. and W.

BOOK 4854

4.

Remonumentation, T, 20 N., R. 6 E., Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 12, monumented by a squared post, 3 ins. diam., set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 26 ins. diam., bears S.  $2^{\circ}$  E., 4 lks. dist., mkd. with an overgrown blaze.

A rotted pine stump, bears N.  $12\frac{1}{2}^{\circ}$  W., 42 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 12 ins. in the ground to bedrock, in a mound of stone, brass cap mkd.

T20N R6E  
 $\frac{1}{4}$  S 1  
 S12  
 1968

from which

A pine, 24 ins. diam., bears S.  $64^{\circ}$  W., 57 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

Bury the orig. cor. post alongside the iron post.

Cor. is 4 lks. N. of a fence, bearing E. and W.

The cor. of secs. 22, 23, 26 and 27, monumented by rotted wood set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A dead pine stump, 40 ins. diam., bears N.  $60^{\circ}$  E., 136 lks. dist., mkd. TXXN RVIE XXIII.

A dead pine stump, 33 ins. diam., bears S.  $84^{\circ}$  E., 120 lks. dist., mkd. TXXN RVIE XXVI. (Note: record dist. 20 lks.).

A stump hole, with a dead and fallen pine tree, 21 ins. diam., alongside, bears S.  $76^{\circ}$  W., 88 lks. dist., mkd. with faint scribe mks. (Note: record dist. 78 lks.).

A pine stump, 21 ins. diam., bears N.  $28^{\circ}$  W., 80 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
 S22|S23  
 S27|S26  
 1968

from which

A pine, 11 ins. diam., bears N.  $76^{\circ}$  E., 10 lks. dist., mkd. T20N R6E S23 BT.

A pine, 7 ins. diam., bears S.  $50^{\circ}$  W., 28 lks. dist., mkd. T20N R6E S27 BT.

Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

Raise a mound of stone W. of the iron post.

Cor. is on a gentle E. slope, about 5 chs. W. of a track road, bearing N. and S.

The cor. of secs. 14, 15, 22 and 23, monumented by rotted wood set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A stump hole, with fallen tree, 27 ins. diam., alongside, bears N. 27° E., 51 lks. dist., mkd. with faint scribe mks.

A pine stump, 15 ins. diam., bears S. 44½° E., 81 lks. dist., mkd. with faint scribe mks.

A stump hole, with fallen pine tree, 12 ins. diam., alongside, bears S. 30° W., 73 lks. dist., mkd. with faint scribe mks.

A pine, 30 ins. diam., bears N. 86° W., 63 lks. dist., mkd. RVII NIX. (Note: record dist. 53 lks.)

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
 S15 | S14  
 S22 | S23  
 1968

from which

A pine, 8 ins. diam., bears S. 65° E., 28½ lks. dist., mkd. T20N R6E S23 BT.

Raise a mound of stone W. of the iron post.

Cor. is about 5 chs. W. of a track road, bearing N. and S.

The cor. of secs. 10, 11, 14 and 15, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 27 ins. diam., bears S. 44½° E., 81 lks. dist., mkd. N RVIE XIV.

A dead pine, 33 ins. diam., bears N. 86° W., 53 lks. dist., mkd. TXXN RVIE X.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
 S10 | S11  
 S15 | S14  
 1968

from which



Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

A pine, 11 ins. diam., bears S. 22° W., 55 lks. dist., mkd. T20N R6E S15 BT.

Raise a mound of stone W. of the iron post.

Cor. is 10 lks. E. of a track road, bearing N. and S.

The cor. of secs. 21, 22, 27 and 28, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 32 ins. diam., bears N. 30° E., 113 lks. dist., mkd. TXXN RVIE XXII.

A stump hole, with roots in hole and a pine log, 21 ins. diam., alongside, bears S. 77° E., 20 lks. dist., mkd. TXXN RVIE XXVII. (Note: record bearing and dist. S. 13° E., 28 lks.).

A pine, 28 ins. diam., bears N. 27½° W., 71 lks. dist., mkd. TXXN RVIE XXI.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
S21 | S22  
S28 | S27  
 1968

Raise a mound of stone W. of the iron post.

The cor. of secs. 9, 10, 15 and 16, monumented by a squared post, 3 x 3 ins., set in the ground, in the center of a mound of stone, mkd. TXXN on two sides, from which the remains of the orig. bearing trees

A pine stump, 12 ins. diam., bears N. 80° E., 4 lks. dist., with log alongside mkd. TXXN RVIE.

A stump hole, bears S. 30° E., 80 lks. dist.

A pine, 33 ins. diam., bears S. 42° W., 120 lks. dist., mkd. with an overgrown blaze.

A pine stump, 6 ins. diam., bears N. 58° W., 76 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 15 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R6E  
S 9 | S10  
S16 | S15  
 1968

from which

A pine, 11 ins. diam., bears N. 56° W., 84 lks. dist., mkd. T20N R6E S9 BT.

Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

Bury the orig. cor. post alongside the iron post.

Cor. is about 5 chs. S. of a track road, bearing E. and W.

The cor. of secs. 3, 4, 9 and 10, monumented by rotted wood set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A stump, 21 ins. diam., bears N. 65° E., 36 lks. dist., mkd. with faint scribe mks.

A pine, 20 ins. diam., bears S. 50° E., 62 lks. dist., mkd. TXXN RVIE X.

A stump, 12 ins. diam., bears S. 63° W., 71 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
S 4 | S 3  
S 9 | S10  
1968

from which

A pine, 12 ins. diam., bears N. 45° E., 17 lks. dist., mkd. T20N R6E S3 BT.

A pine, 15 ins. diam., bears S. 25° W., 46 lks. dist., mkd. T20N R6E S9 BT.

Raise a mound of stone W. of the iron post.

The ¼ sec. cor. of secs. 3 and 4, monumented by rotted wood set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A stump hole, with a dead and fallen pine tree, 33 ins. diam., alongside, bears S. 50° E., 118 lks. dist., mkd. ¼ S3 BT.

A pine, 42 ins. diam., bears N. 30° W., 61 lks. dist., mkd. ¼ S4 BT.

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R6E  
¼  
S4 | S3  
1968

from which

A pine, 11 ins. diam., bears N. 66° E., 57 lks. dist., mkd. ¼ S3 BT.

Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

Cor. is on the NW. slope of Woody Mountain, on the S. edge of a draw, draining westerly.

The cor. of secs. 20, 21, 28 and 29, monumented by rotted and charred wood set in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A double pine, 18 ins. diam., bears N. 9° E., 26 lks. dist., mkd. TXXN RVIE/XXI.

A pine, 30 ins. diam., bears S. 32° E., 59 lks. dist., mkd. TXXN RVIE/XXVIII.

A pine stump, 13 ins. diam., bears N. 24° W., 40 lks. dist., mkd. TXXN RVIE/XX.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
S20|S21  
S29|S28  
 1968

Raise a mound of stone W. of the iron post.

The cor. of secs. 8, 9, 16 and 17, monumented by a squared post, 3 x 3 ins., set in the ground in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A dead pine, 24 ins. diam., bears N. 38° E., 45 lks. dist., mkd. TXXN RVIE IX.

A pine, 21 ins. diam., bears S. 32° E., 97 lks. dist., mkd. TXXN R6 E XVI.

A stump hole, bears S. 65° W., 29 lks. dist.

A pine, 32 ins. diam., bears N. 50° W., 69 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R6E  
S 8|S 9  
S17|S16  
 1968

Bury the orig. cor. post alongside the iron post.

Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

The cor. of secs. 29, 30, 31 and 32, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 27 ins. diam., bears S. 29° E., 76 lks. dist., mkd. TXXN RVIE XXX.

A pine, 33 ins. diam., bears S. 63° W., 34 lks. dist., mkd. with a blaze, partly overgrown,, and faint scribe mks.

A pine, 22 ins. diam., bears N. 10° W., 65 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
S30|S29  
S31|S32  
 1968

Raise a mound of stone W. of the iron post.

Cor. is 25 lks. S. of a track road, bearing E. and W., and 10 lks. N. and 25 lks. E. of a fence cor., from which fences bear E. and S.

The cor. of secs. 19, 20, 29 and 30, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine stump, 34 ins. diam., bears N. 70° E., 54 lks. dist., mkd. with faint scribe mks.

A pine, 24 ins. diam., bears S. 43° E., 54 lks. dist., mkd. with an overgrown blaze.

A pine, 33 ins. diam., bears S. 55° W., 32 lks. dist., mkd. TXXN RVIEXXX.

A pine, 35 ins. diam., bears N. 86° W., 77 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 12 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R6E  
S19|S20  
S30|S29  
 1968

The ¼ sec. cor. of secs. 19 and 30, monumented by a malpais stone, 16 x 12 x 9 ins., set 8 ins. in the ground, in a mound of stone, mkd. ¼ on N. face, from which the remains of the orig. bearing trees

A pine, 30 ins. diam., bears N. 70° E., 55 lks. dist., mkd. with an overgrown blaze.

A stump hole, bears S. 37° W., 17 lks. dist.

## Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E

$\frac{1}{4}$   $\frac{S19}{S30}$

1968

from which

A pine, 14 ins. diam., bears N. 87° W., 26 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

Raise a mound of stone N. of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, monumented by a malpais stone, 18 x 12 x 12 ins., set 9 ins. in the ground, in a collar of stone, with mound of stone to the W. From the cor., the remains of the orig. bearing trees

A dead pine, 18 ins. diam., bears S. 8° E., 21 lks. dist., mkd.  $\frac{1}{4}$  S.

A pine, 20 ins. diam., bears N. 52° W., 44 lks. dist., mkd. with a blaze, partly overgrown, and faint scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E

$\frac{1}{4}$   
S19|S20

1968

from which

A pine, 14 ins. diam., bears N. 70° E., 45 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

Rebuild the orig. mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 5, 6, 7 and 8, monumented by pieces of a rotted wood stake set in the ground, in the center of a mound of stone, mkd. with faint scribe mks., verified by record course and dist. from the remains of the orig. bearing trees

A pine, 24 ins. diam., bears N. 30° E., 11 lks. dist., mkd. with faint scribe mks.

A pine, 30 ins. diam., bears S. 39° E., 143 lks. dist., mkd. with an overgrown blaze.

A pine stump, 22 ins. diam., bears S. 40° W., 58 lks. dist., mkd. with faint scribe mks.

Remonumentation, T. 20 N., R. 6 E., Arizona

CHAINS

A dead and fallen pine, 24 ins. diam., bears N. 50° W., 151 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
 $\frac{S6}{S7}$   
 1968

from which

A pine, 9 ins. diam., bears S. 83° W., 46 lks. dist., mkd. T20N R6E S7 BT.

Raise a mound of stone W. of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 6 and 7, monumented by rotted wood set in ground, in center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 22 ins. diam., bears N. 65° E., 149 lks. dist., mkd. with faint scribe mks.

A pine stump, 24 ins. diam., bears S. 84° W., 8 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R6E  
 $\frac{1}{4} \frac{S6}{S7}$   
 1968

from which

A pine, 15 ins. diam., bears S. 47° W., 59 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

A pine, 15 ins. diam., bears N. 14° W., 30 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

Raise a mound of stone N. of the iron post.

Cor. is about 10 chs. N. of a track road, bearing E. and W., and 2 lks. W. of a fence cor., from which fences bear N. and E.

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

Township 21 North, Range 6 East, G&SR M., Arizona

The east, south and north boundaries and subdivisional lines were surveyed in 1878 by J. L. Harris.

Remonumentation, T. 21 N., R. 6 E., G&SR M., Arizona

The cor. of secs. 25, 30, 31 and 36, T. 21 N., Rs. 6 and 7 E., reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 30 ins. diam., bears N. 5° E., 4 lks. dist., mkd. with an overgrown blaze.

A pine stump, 30 ins. diam., bears S. 40° W., 158 lks. dist., mkd. with faint scribe mks.

A pine, 24 ins. diam., bears N. 3° W., 4 lks. dist., mkd. XXINRVI.

At the cor. point

Set the iron post, 10 ins. in the ground, mound of stone to top, brass cap mkd.

T21N  
R6E R7E  
S25|S30  
S36|S31  
1968

Cor. is at a fence cor., from which fences bear N., S. and W., 40 lks. W. of a graded road, bearing N. and S.

The cor. of secs. 7, 12, 13 and 18, T. 21 N., Rs. 6 and 7 E., reestablished by record course and dist. from the remains of the orig. bearing trees

A stump hole, with a dead and fallen pine tree, 15 ins. diam., alongside, bears N. 64° E., 133 lks. dist., mkd. with a blaze.

A stump hole, with a dead and fallen pine tree, 15 ins. diam., alongside, bears S. 54° E., 68 lks. dist., mkd. with faint scribe mks.

A stump hole, with a dead and fallen pine tree, 18 ins. diam., alongside, bears S. 83° W., 23 lks. dist. (Note: record bearing N. 70° W.).

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T21N  
R6E R7E  
S12|S 7  
S13|S18  
1968

from which

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

A pine, 10 ins. diam., bears S. 20° E., 62 lks. dist., mkd. T21N R7E S18 BT.

A pine, 12 ins. diam., bears S. 64° W., 24 lks. dist., mkd. T21N R6E S13 BT.

Cor. is 25 lks. N. of a fence cor., from which fences bear N., E. and S.

The cor. of secs. 1, 6, 7 and 12, T. 21 N., Rs. 6 and 7 E., reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 28 ins. diam., bears S. 45° E., 70 lks. dist., mkd. with an overgrown blaze.

A pine stump, 28 ins. diam., bears S. 43° W., 60 lks. dist., mkd. TXXINRVIE X11.

A pine stump, 22 ins. diam., bears N. 41° W., 56 lks. dist., mkd. TXXINRVIE 1.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T21N  
R6E R7E  
S 1 | S 6  
S12 | S 7  
1968

from which

A pine, 8 ins. diam., bears N. 47° E., 38 lks. dist., mkd. T21N R7E S6 BT.

A pine, 14 ins. diam., bears N. 49° W., 27 lks. dist., mkd. T21N R6E S1 BT.

Cor. is 5 lks. S. of a fence cor., from which fences bear N., E. and S.

The standard ¼ sec. cor. of sec. 33, monumented by rotted wood set in the ground, in the center of a mound of stone, with mound of stone to the N., verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 18 ins. diam., bears N. 65° E., 42 lks. dist., no mks.

A pine stump, 20 ins. diam., bears S. 31° W., 20 lks. dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

S C  
T21N R6E  
¼ S33  
1968



Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

from which

A pine, 9 ins. diam., bears N. 33° E., 27½ lks. dist., mkd. T21N R6E SC¼ S33 BT.

A pine, 7 ins. diam., bears S. 80° E., 26 lks. dist., mkd. T20N R6E S4 BT.

Rebuild the mound of stone N. of the iron post.

Cor. is 20 lks. E. of a fence cor., from which fences bear N. and W.

The cor. of secs. 1, 2, 35 and 36, Tps. 21 and 22 N., R. 6 E., reestablished by record course and dist. from the remains of the orig. bearing trees

A stump hole, bears N. 21° E., 79 lks. dist.

A pine, 27 ins. diam., bears S. 40° E., 66 lks. dist., mkd. with a blaze, partly overgrown, and scribe mks. RVIE.

A pine stump, 18 ins. diam., bears S. 38° W., 84 lks. dist.

A dead pine, 28 ins. diam., bears N. 2½° W., 87 lks. dist., mkd. TXXIINRVIEXXXV.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T22N R6E  
 S35|S36  
 S 2|S 1  
 T21N  
 1968

from which

A pine, 11 ins. diam., bears S. 73° W., 50 lks. dist., mkd. T21N R6E S2 BT.

Cor. is 40 lks. W. of forest road No. 4506B, bearing N. and S.

The cor. of secs. 1, 2, 11 and 12, monumented by a squared post, 3 x 3 ins., set in the ground, surrounded by bits of charred wood, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 30 ins. diam., bears N. 80° E., 46 lks. dist., no mks.

A pine stump, with a dead and fallen tree, 30 ins. diam., alongside, bears S. 85° E., 63 lks. dist., mkd. with a burned out blaze.

A stump hole, bears S. 50° W., 190 lks. dist.

A pine stump, with a dead and fallen tree, 32 ins. diam., alongside, bears N. 78° W., 99 lks. dist., tree mkd. RVIE with remainder of mks. burned out.

## Remonumentation, T. 21 N., R. 6 E., Arizona

## CHAINS

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T21N R6E  
 S 2 | S 1  
 S11 | S12  
 1968

from which

A pine, 10 ins. diam., bears S. 45° E., 52 lks. dist., mkd. T21N R6E S12 BT.

A pine, 8 ins. diam., bears S. 5° E., 35 lks. dist., mkd. T21N R6E S12 BT.

Bury the orig. cor. post alongside the iron post.

Cor. is 75 lks. E. of a fence, bearing N. and S.

The cor. of secs. 10, 11, 14 and 15, monumented by rotted wood in ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 30 ins. diam., bears S. 85° E., 50 lks. dist., no mks.

A pine, 33 ins. diam., bears S. 71° W., 68 lks. dist., mkd. with a blaze, partly overgrown, and scribe mks. INRVIE.

A pine, 33 ins. diam., bears N. 43° W., 91 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 15 ins. in the ground, mound of stone to top, brass cap mkd.

T21N R6E  
 S10 | S11  
 S15 | S14  
 1968

Cor. is about 2 lks. W. of a fence, bearing N. and S., and 20 lks. W. of an electric line, bearing N. and S.

The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, monumented by rotted wood in ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 12 ins. diam., bears S. 20° E., 9 lks. dist., no mks.

A pine stump, 27 ins. diam., bears West, 21 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

T21N R6E

$\frac{1}{4}$   
S10|S11  
1968

from which

A pine, 5, ins. diam., bears N. 29° E., 14 lks. dist., mkd. X BT.

A pine, 12 ins. diam., bears S. 79° E., 80 lks. dist., mkd.  $\frac{1}{4}$  S11 BT.

Cor. is 15 lks. E. of a fence, bearing N. and S., and 35 lks. W. of an electric line, bearing N. and S.

The cor. of secs. 2, 3, 10 and 11, monumented by rotted wood in ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 30 ins. diam., bears N. 35° E., 63 lks. dist., mkd. with faint scribe mks.

A pine stump, 30 ins. diam., bears S. 34° E., 79 lks. dist., no mks.

A pine stump, 30 ins. diam., bears S. 7° W., 25 lks. dist., mkd. with faint scribe mks.

A pine stump, 30 ins. diam., bears N. 63° W., 7 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R6E  
S 3 | S 2  
S10 | S11  
1968

from which

A pine, 12 ins. diam., bears S. 67° W., 46 lks. dist., mkd. T21N R6E S10 BT.

Cor. is S. 47° W., 45 lks. dist., from power pole No. 1, from which power lines bear Northeasterly and S.

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 11, monumented by rotted wood in ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A stump hole, with a dead and fallen pine tree, 22 ins. diam., alongside, bears N. 45 $\frac{1}{2}$ ° E., 16 lks. dist., mkd.  $\frac{1}{4}$  S.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

T21N R6E

$\frac{1}{4}$   $\frac{S}{S11}$   
1968

from which

A pine, 8 ins. diam., bears N. 36° E., 45 lks. dist., mkd.  $\frac{1}{4}$  S2 BT.

A pine, 7 ins. diam., bears S. 25° E., 23 lks. dist., mkd.  $\frac{1}{4}$  S11 BT.

Raise a mound of stone N. of the iron post.

Cor. is about  $\frac{1}{4}$  chs. N. of forest road No. 4506C, bearing E. and W.

The cor. of secs. 27, 28, 33 and 34, monumented by rotted wood in ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A stump hole, bears N. 54° E., 92 lks. dist.

A pine, 21 ins. diam., bears S. 2° E., 49 lks. dist., mkd. with an overgrown blaze.

A pine stump, 24 ins. diam., bears S. 39° W., 86 lks. dist., mkd. with an overgrown blaze.

A stump hole, bears N. 21° W., 91 lks. dist.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R6E

$\frac{S28}{S33}$  |  $\frac{S27}{S34}$   
1968

from which

A pine, 12 ins. diam., bears N. 46° E., 142 lks. dist., mkd. T21N R6E S27 BT.

A pine, 9 ins. diam., bears N. 17° W., 97 lks. dist., mkd. T21N R6E S28 BT.

Raise a mound of stone W. of the iron post.

Cor. is 50 lks. S. of a fence, bearing E. and W.

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

The cor. of secs. 28, 29, 32 and 33, monumented by rotted wood in ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 28 ins. diam., bears N. 35° E., 31 lks. dist., mkd. with faint scribe mks.

A pine stump, 20 ins. diam., bears S. 50° W., 53 lks. dist., no mks.

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T21N R6E  
S29|S28  
S32|S33  
 1968

from which

A pine, 12 ins. diam., bears N. 82° E., 34 lks. dist., mkd. T21N R6E S28 BT.

A pine, 8 ins. diam., bears S. 10° W., 27½ lks. dist., mkd. T21N R6E S32 BT.

Cor. is 10 lks. S. of a fence cor., from which fences bear N. and W.

Remonumentation, T. 21 N., R. 7 E., Arizona

CHAINS

Township 21 North, Range 7 East, G&SR M., Arizona

The east boundary and subdivisional lines were surveyed in 1878 by J. L. Harris.

Remonumentation, T. 21 N., R. 7 E., G&SR M., Arizona

The cor. of secs. 13, 18, 19 and 24, T. 21 N., Rs. 7 and 8 E., monumented by a water pipe, 2 ins. diam., 18 ins. long, with a 60-penny nail on top, set in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 28 ins. diam., bears N. 11° E., 66 lks. dist., no mks.

A pine stump, 32 ins. diam., bears S. 45° E., 64 lks. dist., mkd. with faint scribe mks.

A pine, 30 ins. diam., bears S. 56° W., 190 lks. dist., mkd. with a blaze, partly overgrown, and scribe mks. ER.

A pine stump, 18 ins. diam., bears N. 68° W., 173 lks. dist., no mks.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T21N  
R7E R8E  
S13|S18  
S24|S19  
1968

from which

A pine, 14 ins. diam., bears S. 10° E., 16 lks. dist., mkd. T21N R8E S19 BT.

Set water pipe alongside the iron post.

Cor is on a fence, bearing N. and S., 10 lks. S. of a track road, bearing E. and W., 45 lks. W. of a telephone line bearing N. and S., 30 lks. S. of a fence cor., from which fences bear E. and S., and 10 lks. N. of a fence cor., from which fences bear N., S. and W.

The cor. of secs. 7, 8, 17 and 18, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 26 ins. diam., bears N. 6° E., 105 lks. dist., mkd. TXXINRVIIIE VIII.

A dead pine, 36 ins. diam., bears S. 56° E., 183 lks. dist., mkd. INRVIIIE.

A pine stump, 24 ins. diam., bears S. 47° W., 184 lks. dist., no mks.

At the cor. point

## Remonumentation, T. 21 N., R. 7 E., Arizona

## CHAINS

Set the iron post, 25 ins. in the ground, brass cap mkd.

T21N R7E  
 S 7 | S 8  
 S18 | S17  
 1968

from which

A pine, 14 ins. diam., bears S. 58° W., 96½ lks. dist., mkd. T21N R7E S18 BT.

A pine, 21 ins. diam., bears N. 71° W., 115 lks. dist., mkd. T21N R7E S7 BT.

Raise a mound of stone W. of the iron post.

Cor. is 5 lks. N. of a fence, bearing E. and W., 25 lks. E. of a track road bearing N. and S.

The ¼ sec. cor. of secs. 7 and 8, monumented by a rotted stake set in the ground, in the center of a mound of stone, verified by record course and dist. from the orig. bearing trees

A pine, 30 ins. diam., bears N. 71° E., 57 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears South, 47 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R7E  
 ¼  
 S7 | S8  
 1968

from which

A pine, 12 ins. diam., bears S. 81° W., 70 lks. dist., mkd. ¼ S7 BT.

Raise a mound of stone W. of the iron post.

Cor. is 55 lks. W. of a fence, bearing N. and S.

The cor. of secs. 5, 6, 7 and 8, reestablished by record course and dist. from the remains of the orig. bearing trees

A stump hole, with a dead and fallen pine tree, 33 ins. diam., alongside, bears N. 68° E., 141 lks. dist., mkd. XXINRVIIE V.

A pine stump, 36 ins. diam., bears S. 75° E., 126 lks. dist., no mks.

A pine snag, 22 ins. diam., bears S. 73° W., 85 lks. dist., mkd. TXXINRVIIE.

## Remonumentation, T. 21 N., R. 7 E., Arizona

## CHAINS

A pine, 27 ins. diam., bears N. 18° W., 130 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 25 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R7E  
S6|S5  
S7|S8  
1968

from which

A pine, 8 ins. diam., bears N. 39° E., 90 lks. dist., mkd. T21N R7E S5 BT.

A pine, 10 ins. diam., bears S. 16° W., 7½ lks. dist., mkd. T21N R7E S7 BT.

Raise a mound of stone W. of the iron post.

Cor. is 95 lks. NW. of a fence cor., from which fences bear N., S., E. and W.

General Statement

The official record was found to be in error for some of the bearings and distances given for the bearing trees. A few of the trees were misnamed as to specie. A ring growth count was made on several trees which proved they were marked at the time of the original survey.

Where the original corner monument appeared to be undisturbed, it was accepted as the true point for the corner.



22

BOOK 4854

CERTIFICATE OF SURVEY

(I) ~~XIX~~, Howard H. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 17th day of June, 1968, (I) ~~XIX~~ have remonumented a portion of the cadastral survey corners in Township 20 North, Range 6 East, and Township 21 North, Ranges 6 and 7 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (me) and under (my) (me) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 14, 1969 (Date)

Howard H. Thomas (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date JUL 30 1969

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 20 North, Range 6 East, and Township 21 North, Ranges 6 and 7 East, of the Gila and Salt River Meridian, Arizona,

executed by Howard H. Thomas, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 3 1970 (Date)

Clark L. Gumm (Chief, Division of Cadastral Survey) Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626

23

**BOOK 4854**

Form 9180-8  
(March 1969)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

NAMES	CAPACITY
James E. Muth	Engineering Aid
(U. S. Forest Service employee)	