

Form 4-679  
(January 1963)

BOOK 4855  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 19 NORTH, RANGE 5 EAST

TOWNSHIP 19 NORTH, RANGE 6 EAST

TOWNSHIP 20 NORTH, RANGE 5 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

## EXECUTED BY

Howard H. Thomas, Cadastral Surveyor

Under special instructions dated June 17, 19 68, which provided for the surveys included under Group Number 501, approved June 17, 1968, and assignment instructions dated June 26, 19 68.

Survey commenced July 1, 19 68

Survey completed September 12, 19 68

BOOK 4855  
INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1A

Form 9180-29  
(March 1965)

BOOK 4855  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# INDEX TO SECTION CORNER MONUMENTS

Tp. 19 N. R. 5 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Diagram showing corner monuments for Township 19 N., Range 5 E., Meridian G&SR. The grid is 6x6. Monuments are marked with circles and numbers: 4, 5, 3 in row 7; 3, 4, 2, 1 in row 18; 3, 4, 2 in row 19.

Tp. 19 N. R. 6 E. Mer. G&SR

6	7	5	4	3	2	1
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Diagram showing corner monuments for Township 19 N., Range 6 E., Meridian G&SR. The grid is 6x7. Monuments are marked with circles and numbers: 6 in row 6, column 2; 6 in row 31, column 2.

Tp. 20 N. R. 5 E. Mer. G&SR

6	5	4	3	2	1	
7	8	9	10	11	12	12
18	17	16	15	14	13	11
19	20	21	22	23	24	10
30	29	28	27	26	25	9
31	32	33	34	35	36	8

Diagram showing corner monuments for Township 20 N., Range 5 E., Meridian G&SR. The grid is 6x7. Monuments are marked with circles and numbers: 15, 12 in row 7; 11, 11 in row 18; 14, 10 in row 19; 16, 13, 13, 9 in row 30; 17, 17, 15, 12, 13, 9 in row 31; 16, 8 in row 31.

Township 19 North, Range 5 East  
 Township 19 North, Range 6 East  
 Township 20 North, Range 5 East  
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 17, 1968 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Township 19 North, Range 5 East, G&SR M., Arizona

The subdivisional lines were surveyed in 1902 by A. Barry.

Re monumentation, T. 19 N., R. 5 E., G&SR M., Arizona

The cor. of secs. 16, 17, 20 and 21, monumented by a malpais stone, 18 x 12 x 8 ins., set 12 ins. in the ground, in a mound of stone, mkd. with 4 notches on E. face and 3 notches on S. face, from which the remains of the orig. bearing trees

An oak, 12 ins. diam., bears N. 18½° E., 51 lks. dist., mkd. with an overgrown blaze.

A dead pine stump, 27 ins. diam., bears S. 75½° E., 232 lks. dist., mkd. with an overgrown blaze.

A stump hole, with a dead and fallen pine tree, 21 ins. diam., alongside, bears S. 19° W., 56 lks. dist., mkd. with faint scribe mks.

An oak, 6 ins. diam., bears N. 59½° W., 28 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 12 ins. in the ground, in a mound of stone, brass cap mkd.

T19N R5E  
 S17|S16  
 S20|S21  
 1968

from which

A pine, 16 ins. diam., bears S. 72° E., 18 lks. dist., mkd. T19N R5E S21 BT.

Remonumentation, T. 19 N., R. 5 E., Arizona

CHAINS

Bury the orig. cor. stone alongside the iron post.

Cor. is 35 lks. N. of a fence, bearing E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, monumented by a sandstone, 16 x 8 x 5 ins., set 12 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, with mound of stone to the S. From the cor., the remains of the orig. bearing trees

A pine, 23 ins. diam., bears S.  $1\frac{1}{2}^\circ$  E., 67 lks. dist., mkd. with an overgrown blaze.

A pine, 21 ins. diam., bears N.  $69^\circ$  W., 63 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T19N R5E  
 $\frac{1}{4}$   $\frac{S16}{S21}$   
 1968

Bury the orig. cor. stone alongside the iron post.

Cor. is about 2 chs. S. of a road junction, from which roads bear N., S. and W., and 1 ch. N. of a fence, bearing E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, monumented by a malpais stone, 30 x 15 x 10 ins., set 18 ins. in the ground, in a mound of stone, mkd.  $\frac{1}{4}$  on N. face, from which the remains of the orig. bearing tree

A stump hole, bears S.  $67^\circ$  E., 33 lks. dist.

At the cor. point

Set the iron post, 12 ins. in the ground to bedrock, mound of stone to top, brass cap mkd.

T19N R5E  
 $\frac{1}{4}$   
 S17|S16  
 1968

from which

A pine, 11 ins. diam., bears S.  $55^\circ$  E., 12 lks. dist., mkd.  $\frac{1}{4}$  S16 BT.

A pine, 8 ins. diam., bears S.  $32^\circ$  W., 23 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is on steep N. slope, about 50 lks. from top.

Remonumentation, T. 19 N., R. 5 E., Arizona

CHAINS

The cor. of secs. 8, 9, 16 and 17, monumented by a malpais stone, 18 x 12 x 10 ins., set 12 ins. in the ground, mkd. with 4 notches on E. face and 4 notches on S. face, from which the remains of the orig. bearing trees

A pine, 24 ins. diam., bears N. 45° E., 62 lks. dist., mkd. with blaze, partly overgrown, and faint scribe mks.

A stump hole, with a dead and fallen oak tree, 8 ins. diam., alongside, bears S. 36° E., 70 lks. dist., mkd. T19N R5E S16 BT.

A pine, 17 ins. diam., bears S. 37° W., 21 lks. dist., mkd. with an overgrown blaze.

A pine, 26 ins. diam., bears N. 1° W., 63 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T19N R5E  
 S 8 | S 9  
 S17 | S16  
 1968

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 17, 18, 19 and 20, monumented by a broken malpais stone, 24 x 10 x 6 ins., set 12 ins. in the ground, mkd. with 3 notches on one piece and 5 notches on the other piece, from which the remains of the orig. bearing trees

A dead pine snag, 21 ins. diam., bears N. 12° E., 117 lks. dist., mkd. T19N R5E S17 BT.

A dead pine stump, 30 ins. diam., bears S. 27° E., 63 lks. dist., mkd. with a burned out blaze.

A rotted pine stump, bears S. 85° W., 59 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T19N R5E  
 S18 | S17  
 S19 | S20  
 1968

from which

A pine, 7 ins. diam., bears S. 62° E., 11 lks. dist., mkd. T19N R5E S20 BT.

A pine, 8 ins. diam., bears N. 5° W., 15 lks. dist., mkd. T19N R5E S18 BT.

Raise a mound of stone W. of the iron post.

Remonumentation, T. 19 N., R. 5 E., Arizona

CHAINS

Bury the orig. cor. stone alongside the iron post.

Cor. is 10 lks. N. of the center of a track road, bearing E. and NW.

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, monumented by a malpais stone, 18 x 10 x 6 ins., set 12 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, with mound of stone to the N. From the cor., the remains of the orig. bearing trees

A stump hole, with a rotted and fallen pine tree alongside, bears S.  $73\frac{1}{2}^\circ$  W., 46 lks. dist., tree mkd. with faint scribe mks.

A dead pine, 24 ins. diam., bears N.  $43^\circ$  W., 40 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T19N R5E  
 $\frac{1}{4}$   $\frac{S17}{S20}$   
 1968

from which

A pine, 10 ins. diam., bears S.  $10^\circ$  W., 32 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

A pine, 13 ins. diam., bears N.  $4^\circ$  W., 14 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 5 lks. S. of a fence, bearing E. and W.

The cor. of secs. 7, 8, 17 and 18, monumented by a malpais stone, 18 x 14 x 5 ins., set 12 ins. in the ground, mkd. with 5 notches on E. face and 4 notches on S. face, with mound of stone to the W. From the cor., the remains of the orig. bearing trees

A dead pine stump, 33 ins. diam., bears N.  $10\frac{1}{2}^\circ$  E., 64 lks. dist., mkd. T19N.

A pine, 40 ins. diam., bears S.  $26^\circ$  E., 31 lks. dist., mkd. with an overgrown blaze.

A dead pine stump, 27 ins. diam., bears S.  $79^\circ$  W., 40 lks. dist., mkd. T19N R5E S18 BT.

A dead pine stump, 24 ins. diam., bears N.  $55\frac{1}{2}^\circ$  W., 112 lks. dist., mkd. T19N R5E S7 BT.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T19N R5E  
 $\frac{S7}{S18} | \frac{S8}{S17}$   
 1968

from which

## Remonumentation, T. 19 N., R. 5 E., Arizona

## CHAINS

A pine, 9 ins. diam., bears S. 85° E., 9 lks. dist., mkd. T19N R5E S17 BT.

A pine, 7 ins. diam., bears N. 20° W., 14 lks. dist., mkd. T19N R5E S7 BT.

Rebuild the orig. mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, monumented by a malpais stone, 24 x 14 x 8 ins., set 18 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, with mound of stone to the N. From the cor., the remains of the orig. bearing trees

A dead pine stump, 21 ins. diam., bears S. 10° W., 43 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

An oak, 8 ins. diam., bears N. 17 $\frac{1}{2}$ ° W., 46 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T19N R5E

$\frac{1}{4}$   $\frac{S 8}{S17}$   
1968

from which

A pine, 9 ins. diam., bears S. 26° E., 48 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

Rebuild the orig. mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is on a medium steep S. slope, about 5 chs. N. of a draw, draining E. from W.



Remonumentation, T. 19 N., R. 6 E., Arizona

CHAINS

Township 19 North, Range 6 East, G&SR M., Arizona  
 Portions of the subdivisional lines were surveyed in 1900 by C. R. Caudle and in 1902 by W. O. Secor.

Remonumentation, T. 19 N., R. 6 E., G&SR M., Arizona

The cor. of secs. 29, 30, 31 and 32, monumented by a limestone, 16 x 10 x 6 ins., set 10 ins. in the ground, in a mound of stone, mkd. with 1 notch on S. face and 5 notches on N. face, from which the remains of the orig. bearing trees

A pine stump, 12 ins. diam., bears N. 33° E., 92 lks. dist., mkd. with faint scribe mks.

A dead pine, 24 ins. diam., bears S. 73° E., 100 lks. dist., mkd. T19N R6E S32 BT.

A stump hole, with a dead and fallen pine tree, 30 ins. diam., alongside, bears S. 52° W., 148 lks. dist., mkd. T19N R6E S31 BT.

A stump hole, with a fallen pine tree, 21 ins. diam., alongside, bears N. 39½° W., 116 lks. dist., mkd. T19N R6E S30 BT.

At the cor. point

Set the iron post, 25 ins. in the ground, in a collar of stone, brass cap mkd.

T19N R6E	
S30	S29
S31	S32
1968	

from which

A pine, 13 ins. diam., bears S. 64° E., 19 lks. dist., mkd. T19N R6E S32 BT.

A pine, 17 ins. diam., bears S. 40° W., 24 lks. dist., mkd. T19N R6E S31 BT.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 5, 6, 7 and 8, monumented by a malpais stone, 18 x 14 x 6 ins., set 16 ins. in the ground, mkd. with 5 notches on S. face and 5 notches on E. face, from which the remains of the orig. bearing trees

A pine stump, 33 ins. diam., bears N. 43° E., 182 lks. dist., mkd. T19N R6E S5 BT.

A pine, 40 ins. diam., bears S. 78 3/4° E., 91 lks. dist., mkd. with an overgrown blaze.

A pine stump, 30 ins. diam., bears S. 19° W., 113 lks. dist., mkd. T19N R6E S7 BT.

## Remonumentation, T. 19 N., R. 6 E., Arizona

## CHAINS

A pine stump, 30 ins. diam., bears N. 70° W.,  
150 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T19N R6E  
S6|S5  
S7|S8  
1968

from which

A pine, 14 ins. diam., bears N. 33° E., 57 lks.  
dist., mkd. T19N R6E S5 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is on a fence, bearing E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, monumented by a  
malpais stone, 12 x 10 x 6 ins., set 6 ins. in the  
ground, mkd.  $\frac{1}{4}$  on W. face, from which the remains of  
the orig. bearing trees

A pine stump, 30 ins. diam., bears S. 51° E.,  
74 lks. dist., mkd. with faint scribe mks.

A dead pine snag, 32 ins. diam., bears S. 68° W.,  
65 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T19N R6E  
 $\frac{1}{4}$   
S6|S5  
1968

from which

A pine, 30 ins. diam., bears S. 30° E., 141 lks.  
dist., mkd.  $\frac{1}{4}$  S5 BT.

A pine, 32 ins. diam., bears N. 54° W., 139 lks.  
dist., mkd.  $\frac{1}{4}$  S6 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about  $1\frac{1}{2}$  chs. W. of forest road No. 535, bearing  
N. and W.

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

Township 20 North, Range 5 East, G&SR M., Arizona

The east and south boundaries and subdivisional lines were surveyed in 1878 by T. L. Harris. The south boundary was resurveyed in 1902 by A. Barry. The southeast township corner was remonumented in 1900 by C. R. Caudle. The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24 and the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., were reestablished in the 1915 survey of H.E.S. #396 by C. D. Hudson.

Remonumentation, T. 20 N., R. 5 E., G&SR M., Arizona

The cor. of Tps. 19 and 20 N., Rs. 5 and 6 E., monumented by a malpais stone, 18 x 15 x 8 ins., set 9 ins. in the ground, in a scattered mound of stone, mkd. with 6 notches each on the N., E., S. and W. faces, from which the remains of the orig. bearing trees

A dead pine, 33 ins. diam., bears N. 44° E., 110 lks. dist., mkd. TXXNR.

A pine, 40 ins. diam., bears S. 75° E., 236 lks. dist., mkd. with a burned out blaze.

A pine, 33 ins. diam., bears S. 75° W., 452 lks. dist., mkd. with an overgrown blaze.

A pine, 30 ins. diam., bears N. 12° W., 157 lks. dist. mkd. NRVIEXXXVI.

At the cor. point

Set the iron post, 21 ins. in the ground, in a collar of stone, brass cap mkd.

T20N  
R5E R6E  
S36 | S31  
S 1 | S 6  
T19N  
1968

Bury the orig. cor. stone alongside the iron post.

Cor. is 50 lks. S. of a track road, bearing E. and W.

The  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, T. 20 N., Rs. 5 and 6 E., monumented by rotten wood set in the ground, in a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A dead pine, 24 ins. diam., bears N. 82° E., 99 lks. dist., mkd.  $\frac{1}{4}$  S.

A dead pine stump, 12 ins. diam., bears West, 19 lks. dist., mkd.  $\frac{1}{4}$  S.

At the cor. point

Set the iron post, 12 ins. in the ground, mound of stone to top, brass cap mkd.

## Remonumentation, T. 20 N., R. 5 E., Arizona

## CHAINS

T20N  
R5E R6E  
 $\frac{1}{4}$   
S36|S31  
1968

from which

A pine, 12 ins. diam., bears N. 88° E., 29 lks.  
dist., mkd.  $\frac{1}{4}$  S31 BT.

A pine, 12 ins. diam., bears N. 34° W., 43 $\frac{1}{2}$  lks.  
dist., mkd.  $\frac{1}{4}$  S36 BT.

Cor. is about 325 lks. S. of a fence, bearing E. and W.

The cor. of secs. 25, 30, 31 and 36, T. 20 N., Rs. 5 and  
6 E., reestablished by record course and dist. from the  
remains of the orig. bearing trees

A pine stump, 38 ins. diam., bears N. 40° E.,  
92 lks. dist., mkd. TXXN RVIEXXX.

A pine stump, 39 ins. diam., bears S. 85° E.,  
172 lks. dist., mkd. with faint scribe mks.

A stump hole, with a dead and fallen pine tree,  
27 ins. diam., alongside, bears S. 87° W.,  
30 lks. dist., no mks.

A stump hole, with a dead and fallen pine tree,  
18 ins. diam., alongside, bears N. 89° W., 30 lks.  
dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar  
of stone, brass cap mkd.

T20N  
R5E R6E  
S25|S30  
S36|S31  
1968

from which

A pine, 15 ins. diam., bears S. 49° E., 59 lks.  
dist., mkd. T20N R6E S31 BT.

A pine, 12 ins. diam., bears N. 42° W., 181 lks.  
dist., mkd. T20N R5E S25 BT.

Cor. is on the S. edge of a small clearing.

The cor. of secs. 19, 24, 25 and 30, T. 20 N., Rs. 5 and  
6 E., reestablished by record course and dist. from the  
remains of the orig. bearing trees

A pine stump, 37 ins. diam., bears N. 46° E.,  
43 lks. dist., mkd. with faint scribe mks.

A pine, 35 ins. diam., bears S. 72° E., 130 lks.  
dist., mkd. with an overgrown blaze.

A pine, 42 ins. diam., bears S. 20° W., 29 lks.  
dist., mkd. with faint scribe mks.

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N  
R5E R6E  
S24|S19  
S25|S30  
1968

Cor. is 1 ch. E. of a power line, bearing N. and S.

The 1/4 sec. cor. of secs. 19 and 24, T. 20 N., Rs. 5 and 6 E., monumented by a rotted stake set in the ground, in a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 40 ins. diam., bears N. 55° E., 16 lks. dist., mkd. with an overgrown blaze.

A pine, 30 ins. diam., bears West, 37 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T20N  
R5E R6E  
1/4  
S24|S19  
1968

Raise a mound of stone W. of the iron post.

The cor. of secs. 13, 18, 19 and 24, T. 20 N., Rs. 5 and 6 E., monumented by a broken pipe, 2 ins. diam., with top of pipe broken off and lying on ground alongside, mkd. with 3 notches on each side, verified by record course and dist. from the remains of the orig. bearing tree

A pine, 27 ins. diam., bears N. 20 3/4° W., 88 lks. dist., mkd. T20N R5E S13 BT.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N  
R5E R6E  
S13|S18  
S24|S19  
1968

from which

A pine, 20 ins. diam., bears N. 25° E., 115 lks. dist., mkd. T20N R6E S18 BT.

Cor. No. 5 of H.E.S. No. 396, bears N. 89°23' W., 31 lks. dist.

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

Bury the orig. cor. pipe alongside the iron post.

Cor. is NW. of Rogers Lake, about 2½ chs. W. of a pole corral.

The ¼ sec. cor. of secs. 13 and 18, T. 20 N., Rs. 5 and 6 E., monumented by rotted and charred wood set in the center of a mound of stone, from which the remains of the orig. bearing trees

A pine, 24 ins. diam., bears S. 70° E., 34 lks. dist., mkd. 1 S. (Note: record bearing East).

A dead and burned pine stump, bears S. 50° W., 53 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T20N  
R5E R6E  
¼  
S13|S18  
1968

from which

A pine, 8 ins. diam., bears N. 75° W., 24 lks. dist., mkd. ¼ S13 BT.

Raise a mound of stone W. of the iron post.

Cor. is 10 lks. W. of a fence, bearing E. and W.

The cor. of secs. 7, 12, 13 and 18, T. 20 N., Rs. 5 and 6 E., monumented by rotten wood in ground set in the center of a mound of stone, with a squared post on ground, alongside, post mkd. with faint scribe mks., from which the remains of the orig. bearing trees

A pine, 27 ins. diam., bears S. 50° W., 159 lks. dist., mkd. TXXN RVEXIII.

A pine stump, 27 ins. diam., bears N. 43° W., 94 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T20N  
R5E R6E  
S12|S 7  
S13|S18  
1968

from which

A pine, 12 ins. diam., bears S. 43° E., 22 lks. dist., mkd. T20N R6E S18 BT.

Raise a mound of stone W. of the iron post.

Cor. is about 160 lks. S. of a fence, bearing E. and W., and 40 lks. W. of a fence, bearing N. and S.

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

The cor. of secs. 1, 6, 7 and 12, T. 20 N., Rs. 5 and 6 E., monumented by rotten wood in ground set in the center of a mound of stone, from which the remains of the orig. bearing trees

A pine, 36 ins. diam., bears N. 4° E., 38 lks. dist., mkd. TXXN RVIE VI

A pine stump, 18 ins. diam., with broken wood alongside, bears S. 30° E., 120 lks. dist., broken wood mkd. with faint scribe mks.

A dead pine snag, 30 ins. diam., bears S. 82° W., 103 lks. dist., mkd. TXXN RVEXII.

A pine stump, 33 ins. diam., bears N. 1° W., 20 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T20N  
R5E R6E  
S 1 | S 6  
S12 | S 7  
1968

from which

A pine, 10 ins. diam., bears S. 70° E., 75 lks. dist., mkd. T20N R6E S7 BT.

A pine, 4 ins. diam., bears S. 44° W., 38 lks. dist., mkd. X BT.

The cor. of secs. 25, 26, 35 and 36, reestablished by record course and dist. from the orig. bearing trees

A pine, 21 ins. diam., bears N. 46° E., 89 lks. dist., mkd. with an overgrown blaze.

A pine, 13 ins. diam., bears S. 46° E., 40 lks. dist., mkd. XXXVI.

A pine, 23 ins. diam., bears S. 45° W., 26 lks. dist., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears N. 44° W., 80 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 11 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R5E  
S26 | S25  
S35 | S36  
1968

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

The ¼ sec. cor. of secs. 25 and 36, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 31 ins. diam., bears N. 27° E., 84 lks. dist., mkd. with an overgrown blaze.

A stump hole, with a dead and fallen pine, 21 ins. diam., alongside, bears S. 85° W., 57 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T20N R5E

¼  $\frac{S25}{S36}$   
1968

from which

A pine, 17 ins. diam., bears S. 11° E., 31 lks. dist., mkd. ¼ S36 BT.

The cor. of secs. 23, 24, 25 and 26, reestablished by record course and dist. from the remains of the orig. bearing trees

A dead pine, 40 ins. diam., bears N. 35° E., 35 lks. dist., mkd. TXXN RVE XXIV.

A pine, 38 ins. diam., bears S. 37° E., 94 lks. dist., mkd. with an overgrown blaze.

A pine, 35 ins. diam., bears S. 43½° W., 55 lks. dist., mkd. with an overgrown blaze.

A stump hole, with a dead and fallen pine tree, 30 ins. diam., alongside, bears N. 55° W., 53 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R5E

$\frac{S23|S24}{S26|S25}$   
1968

The ¼ sec. cor. of secs. 24 and 25, reestablished by record course and dist. from the remains of the orig. bearing trees

A dead pine stump, 32 ins. diam., bears S. 40° E., 40 lks. dist., no mks.

A pine, 26 ins. diam., bears N. 24° W., 33 lks. dist., mkd. with a blaze, partly overgrown. I cut open blaze and find faint scribe mks.

At the cor. point



Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R5E

$\frac{1}{4}$   $\frac{S24}{S25}$

1968

from which

A pine, 8 ins. diam., bears S. 12° W., 18 lks. dist., mkd. T20N R5E S25 BT.

Cor. is about 3 chs. W. of a bladed gravel road, bearing N. and S.

The  $\frac{1}{4}$  sec. cor. of secs. 23 and 24, monumented by rotten and charred wood set in ground in a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 24 ins. diam., bears S. 88° E., 39 lks. dist., mkd. with a rotted out blaze.

A stump hole, with a dead and fallen pine tree, 36 ins. diam., alongside, bears S. 80° W., 100 lks. dist., mkd. with a rotted out blaze.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T20N R5E

$\frac{1}{4}$  S23|S24

1968

from which

A pine, 8 ins. diam., bears S. 74° E., 28 lks. dist., mkd.  $\frac{1}{4}$  S24 BT.

A pine, 7 ins. diam., bears S. 35° W., 33 lks. dist., mkd.  $\frac{1}{4}$  S23 BT.

Raise a mound of stone W. of the iron post.

The cor. of secs. 13, 14, 23 and 24, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 27 ins. diam., bears N. 54° E., 115 lks. dist., mkd. TXXN RVE XIII.

A pine stump, 32 ins. diam., bears S. 20° E., 81 lks. dist., mkd. XXN.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R5E

$\frac{S14}{S23}$  |  $\frac{S13}{S24}$

1968

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

from which

A pine, 11 ins. diam., bears S. 63° E., 31 lks. dist., mkd. T20N R5E S24 BT.

A pine, 12 ins. diam., bears N. 78° W., 12 lks. dist., mkd. T20N R5E S14 BT.

Cor. is about 2½ chs. S. of a bladed road, bearing E. and W.

The cor. of secs. 1, 2, 11 and 12, monumented by rotten wood in the ground, in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 28 ins. diam., bears S. 6° E., 66 lks. dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears S. 32° W., 126 lks. dist., mkd. with an overgrown blaze. (Note: record bearing and distance S. 52° W., 116 lks.).

A pine stump, 24 ins. diam., bears N. 72° W., 81 lks. dist., with log alongside mkd. TXXN. (Note: record bearing N. 72° E.).

A stump hole, with a dead and fallen pine tree, 21 ins. diam., alongside, bears N. 53° W., 118 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R5E	
S 2	S 1
S11	S12
1968	

from which

A pine, 16 ins. diam., bears S. 64° W., 7 lks. dist., mkd. T20N R5E S11 BT.

The cor. of secs. 26, 27, 34 and 35, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine, 24 ins. diam., bears S. 30° E., 57 lks. dist., mkd. XXVI.

A pine stump, 28 ins. diam., bears S. 78° W., 63 lks. dist., mkd. with faint scribe mks.

A pine stump, 30 ins. diam., bears N. 40° W., 63 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

T20N R5E  
 S27|S26  
 S34|S35  
 1968

from which

A pine, 6 ins. diam., bears N. 10° E., 19 lks. dist., mkd. T20N R5E S26 BT.

A pine, 9 ins. diam., bears S. 21° W., 33 lks. dist., mkd. T20N R5E S34 BT.

The cor. of secs. 22, 23, 26 and 27, monumented by rotten and charred wood in the ground, in the center of a mound of stone, verified by record course and dist. from the orig. bearing trees

A pine, 30 ins. diam., bears N. 45° E., 66 lks. dist., mkd. with an overgrown blaze.

A pine, 27 ins. diam., bears S. 15° E., 28 lks. dist., mkd. with an overgrown blaze.

A pine, 26 ins. diam., bears S. 56° W., 19 lks. dist., mkd. with an overgrown blaze.

A pine, 36 ins. diam., bears N. 58° W., 54 lks. dist., mkd. TXXN RVE XXII.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T20N R5E  
 S22|S23  
 S27|S26  
 1968

Cor. is about 5 chs. S. of a track road, bearing NE. and SW.

*should read: ←  
 The cor. of  
 secs. 33 and  
 34, T. 20N., R5E,  
 correction  
 authorized by  
 W0 memo  
 dated 7-28-70*

The cor. of secs. 3, 4, 33 and 34, Tps. 19 and 20 N., R. 5 E., monumented by a malpais stone, 18 x 12 x 5 ins., set in the ground, in a scattered mound of stone, mkd. with 3 notches on E. face and 3 notches on W. face, from which the remains of the orig. bearing trees

A pine, 27 ins. diam., bears N. 16° E., 120 lks. dist., mkd. TXXN RVE XXXIV.

A pine stump, 8 ins. diam., bears S. 10½° E., 117 lks. dist., mkd. with faint scribe mks.

A pine stump, 48 ins. diam., bears S. 15½° W., 162 lks. dist., mkd. with faint scribe mks.

A pine, 38 ins. diam., bears N. 29½° W., 52 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS		
	<p style="text-align: center;">                     T20N R5E                      S33 S34                      S 4 S 3                      T19N                      1968                 </p> <p>from which</p> <p>A pine, 15 ins. diam., bears S. 61° W., 153 lks. dist., mkd. T19N R5E S4 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. is in the middle of an open flat.</p>	<p><i>Should read:</i></p> <p>→ T20N R5E S33 S34 T19N 1968</p> <p><i>Correction authorized by W. H. Adams dated 7-28-70</i></p>
	<p>The cor. of secs. 27, 28, 33 and 34, monumented by rotten wood in ground in center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees</p> <p>A stump hole, with a dead and fallen pine tree, 24 ins. diam., alongside, bears N. 20° E., 93 lks. dist., mkd. TXXN RVE XXVII.</p> <p>A pine, 20 ins. diam., bears S. 65° W., 59 lks. dist., mkd. with an overgrown blaze.</p> <p>A dead pine, 24 ins. diam., bears N. 32° W., 45 lks. dist., mkd. TXXN RVE XXVIII.</p> <p>At the cor. point</p> <p>Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">                     T20N R5E                      S28 S27                      S33 S34                      1968                 </p> <p>from which</p> <p>A pine, 8 ins. diam., bears S. 17° E., 47 lks. dist., mkd. T20N R5E S34 BT.</p> <p>Raise a mound of stone W. of the iron post.</p> <p>Cor. is about 3 chs. E. of a draw, draining SE.</p>	
	<p>The ¼ sec. cor. of secs. 28 and 33, monumented by rotten wood in the ground in the center of a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees</p> <p>A stump hole, with a dead and fallen pine tree, 15 ins. diam., alongside, bears N. 34° E., 42 lks. dist., mkd. ¼ S.</p> <p>A pine, 27 ins. diam., bears N. 86° W., 104 lks. dist., mkd. with an overgrown blaze.</p> <p>At the cor. point</p> <p>Set the iron post, 12 ins. in the ground, mound of stone to top, brass cap mkd.</p>	

Remonumentation, T. 20 N., R. 5 E., Arizona

CHAINS

T20N R5E

 $\frac{1}{4}$   $\frac{S28}{S33}$ 

1968

from which

A pine, 8 ins. diam., bears South, 55 lks. dist.,  
mkd.  $\frac{1}{4}$  S33 BT.

General Statement

The official record was found to be in error for some of the bearings and distances given for the bearing trees. A few of the trees were misnamed as to specie. A ring growth count was made on several trees which proved they were marked at the time of the original survey.

Where the original corner monument appeared to be undistrubed, it was accepted as the true point for the corner.

Form 9180-8  
(March 1969)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
James E. Muth	Engineering Aid
(U. S. Forest Service Employee)	

20

BOOK 4855

CERTIFICATE OF SURVEY

(I ~~we~~), Howard H. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 17th day of June, 1968, (I ~~we~~) have remonumented a portion of the cadastral survey corners in Township 19 North, Ranges 5 and 6 East, and Township 20 North, Range 5 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~xxx~~ and under (my) ~~xxxx~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 14, 1969  
(Date)

*Howard H. Thomas*  
(Cadastral Surveyor)

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date JUL 30 1969

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 19 North, Ranges 5 and 6 East, and Township 20 North, Range 5 East, of the Gila and Salt River Meridian, Arizona,

executed by Howard H. Thomas, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 3 1970  
(Date)

*Clark I. Lumm*  
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief, Division of Cadastral Survey) GPO 849-626~~