

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

OF PORTIONS OF THE

WEST AND NORTH BOUNDARIES

AND

SUBDIVISIONAL LINES

AND A

COMPLETION SURVEY

OF THE

SUBDIVISIONAL LINES,

TOWNSHIP 7 SOUTH, RANGE 20 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Louis D. Gilbert

Cadastral Surveyor

Under special instructions dated November 18, 19 68, which provided for the surveys
included under Group Number 463, approved November 18, 1968,
and assignment instructions dated November 19, 19 68.

Survey commenced November 29, 19 68

Survey completed January 15, 19 69

1A

BOOK 4868

INDEX DIAGRAM

Township 7 South, Range 20 East,

6	5	4 10	1 3	2	1
7	8	9 9	20 10 14	11 17	18 12 16
5 18 13	17	16	20 8 15 14	14	18 13
4 19 12 24	20	21	7 22	7 23	6 24
3 30 22	11 22 29	11 28	27	26	25
2 31	32	33	34	35	36

Township 7 South, Range 20 East
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The east three miles of the south boundary, the south three miles of the east boundary, the west three miles of the north boundary, the north three miles of the west boundary and a portion of the subdivisional lines were surveyed in 1877 by T. F. White. The south three miles of the west boundary was surveyed and the north two miles resurveyed in 1913 by J. F. Hesse. The south three miles of the east boundary was resurveyed and the north three miles surveyed in 1915 by T. B. Mathews. The east three miles of the south boundary was resurveyed and the west three miles surveyed in 1928 by L. R. Hanson. The east three miles of the north boundary were surveyed and the west three miles resurveyed in 1928 by W. E. Hiester. Section 32 was surveyed in 1955 by Fred R. Chappell. Sections 1 and 2 were surveyed in 1967 by Herman and Knight.</p> <p>The following field notes are those of a dependent re-survey of a portion of the west and north boundaries; a portion of the subdivisional lines, designed to restore the corners in their true original location according to the best available evidence, and a completion survey of the subdivisional lines in Township 7 South, Range 20 East, Gila and Salt River Meridian, Arizona.</p> <p>This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated November 18, 1968.</p> <p>Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.</p> <p>The geographic position of the SE. corner of Section 13, as scaled from USGS quadrangle "Jackson Mtn., Arizona", edition of 1946, scale 1:62500, is: Latitude 32°49'06" N. and Longitude 110°14'46" W.</p> <p>The magnetic declination was found to be 14° E.</p>
	<p>Dependent Resurvey, Portion North Boundary, T. 7 S., R. 20 E.</p>
<p>5.70 40.00</p>	<p>Reestablishment of the Survey executed by W. E. Hiester in 1928</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, Tps. 6 and 7 S., R. 20 E., monumented by an iron post, 2 ins. diam., 16 ins. above ground, firmly set, mound of stone W., mkd. T6S T7S R20E S2 S3 S34 S35 1928 1967.</p> <p>N. 89°58' W., bet. secs. 3 and 34.</p> <p>Over semi-mountainous land.</p> <p>Draw, drains NW.</p> <p>The ¼ sec. cor. of sec. 34 only, T. 6 S., R. 20 E., monumented by an iron post, 1 in. diam., 24 ins. above ground, firmly set in mound of stone, mkd. ¼ S34 1928. This corner now functions as the ¼ sec. cor. of secs. 3 and 34, Tps. 6 and 7 S., R. 20 E. I change the markings to read:</p>

Dependent Resurvey, Portion North Boundary,
T. 7 S., R. 20 E.

CHAINS	
	<p style="text-align: center;">T6S R20E $\frac{1}{4}$ S 34 S 3 T7S 1968 1928</p> <hr/> <p>N. 89°57' W., beginning new measurement.</p> <p>Over semi-mountainous land.</p>
14.40	Klondyke Wash, 30 lks. wide, 2 ft. deep, drains SW.
36.70	Track road, bears irregularly NE. and SW.
38.59	The cor. of secs. 3 and 4 only, T. 7 S., R. 20 E., monumented by an iron post, 2 ins. diam., 10 ins. above ground, firmly set in mound of stone, mkd. T6S R20E T7S R20E S3 S4 S34 1928.
39.88	The cor. of secs. 33 and 34 only, T. 6 S., R. 20 E., monumented by an iron post, 2 ins. diam., 22 ins. above ground, firmly set in mound of stone, mkd. T6S R20E T7S R20E S33 S34 S4 1928.
	<p>Land, semi-mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, catclaw and oak brush.</p>
<p>Dependent Resurvey, Portion West Boundary, T. 7 S., R. 20 E.</p>	
<p>Reestablishment of the Survey Executed by J. F. Hesse in 1913</p> <hr/>	
	<p>From the SE. cor. of Tp. 7 S., R. 19 E., monumented by an iron post, 3 ins. diam., 18 ins. above ground, firmly set, mkd. T7S R19E T8S R19E S36 S1 1928, mound of stone E.</p> <p>N. 0°03' W., along the E. bdy. of sec. 36, T. 7 S., R. 19 E.</p> <p>Over semi-mountainous land.</p>
2.83	The SW. cor. of Tp. 7 S., R. 20 E., monumented by an iron post, 3 ins. diam., 6 ins. above ground, firmly set, mkd. T7S R19E T7S R20E T8S R19E S1 S31 S36 1928, mound of stone E.
39.91	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor. This point now functions for the $\frac{1}{4}$ sec. cor. of sec. 36 only, T. 7 S., R. 19 E.; not monumented.
57.20	Fence, bears N. 20° E. and S. 20° W.
79.82	The cor. of secs. 25, 30, 31 and 36, monumented by an iron post, 3 ins. diam., 8 ins. above ground, firmly set, mkd. T7S R19E R20E S25 S30 S31 S36 1913. This corner now functions for the cor. of secs. 25 and 36 only, T. 7 S., R. 19 E. I change the markings to read:

Dependent Resurvey, Portion West Boundary,
T. 7 S., R. 20 E.

CHAINS	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T7S</td><td> </td><td></td></tr> <tr><td>S 25</td><td> </td><td>T7S</td></tr> <tr><td>S 36</td><td> </td><td>S 31</td></tr> <tr><td>R19E</td><td> </td><td>R20E</td></tr> <tr><td></td><td></td><td>1968</td></tr> <tr><td></td><td></td><td>1913</td></tr> </table> <p>Land, semimountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass and cacti.</p>	T7S			S 25		T7S	S 36		S 31	R19E		R20E			1968			1913
T7S																			
S 25		T7S																	
S 36		S 31																	
R19E		R20E																	
		1968																	
		1913																	
	<p>NORTH, along the E. bdy. of sec. 25, T. 7 S., R. 19 E.</p> <p>Over semi-mountainous land.</p> <p>11.30 Long Hollow, 40 lks. wide, 2 ft. deep, drains NE. and track road, bears NE. and SW.</p> <p>23.80 Wash, 20 lks. wide, 1 ft. deep, drains E.</p> <p>32.70 Spur, slopes S. 50° E.</p> <p>37.40 Draw, drains S. 50° E.</p> <p>39.80 Low spur, slopes S. 50° E.</p> <p>40.15 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by an iron post, 1 in. diam., 10 ins. above ground, firmly set, mound of stone W., mkd. $\frac{1}{4}$ S25 S30 1913. This corner now functions for the $\frac{1}{4}$ sec. cor. of sec. 25 only, T. 7 S., R. 19 E. I change the markings to read:</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T7S</td><td> </td><td></td></tr> <tr><td>$\frac{1}{4}$ S 25</td><td> </td><td></td></tr> <tr><td>R19E</td><td> </td><td></td></tr> <tr><td></td><td></td><td>1968</td></tr> <tr><td></td><td></td><td>1913</td></tr> </table> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p> <p>Over semi-mountainous land.</p> <p>4.70 Draw, drains S. 50° E.</p> <p>11.30 Fence, bears S. 52° E. and N. 52° W., 1.20 chs. dist., to cor. of fences extending N. and S. 52° E. Thence along E. side of fence.</p> <p>17.00 Spur, slopes NE.</p> <p>28.90 Wash, 30 lks. wide, 2 ft. deep, drains NE.</p> <p>34.80 Spur, slopes N. 60° E.</p> <p>37.70 Draw, drains E.</p> <p>39.58 The cor. of secs. 19, 24, 25 and 30, monumented by an iron post, 3 ins. diam., 14 ins. above ground, mkd. T7S R19E R20E S19 S24 S25 S30 1913.</p> <p>from which</p> <p style="margin-left: 40px;">Cor. of fences, bears W., 38 lks. dist., fences bear N., S. and W.</p>	T7S			$\frac{1}{4}$ S 25			R19E					1968			1913			
T7S																			
$\frac{1}{4}$ S 25																			
R19E																			
		1968																	
		1913																	

Dependent Resurvey, Portion West Boundary,
T. 7 S., R. 20 E.

CHAINS	
	<p>Land, semi-mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass and cacti.</p>
2.10	<p>N. 0°01' E., bet. secs. 19 and 24. Over semi-mountainous land. Spur, slopes S. 70° E.</p>
14.60	<p>Low spur, slopes NW.</p>
16.10	<p>Fence, bears N. 1° 20' E. and S. 1°20' W.</p>
25.80	<p>Wash, 40 lks. wide, 3 ft. deep, drains N. 25° E.</p>
39.77	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This point falls in small wash, 10 lks. wide, 4 ft. deep, draining irregularly N. 25° E.; impractical to monument.</p>
39.97	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 19 and 24. Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R19E R20E $\frac{1}{4}$ S 24 S 19 W C 1968</p>
	<p>from which A fence, bears E., 57 lks. dist.; fence bears N. 1°20' E. and S. 1°20' W.</p>
	<p>Raise a mound of stone W. of the iron post.</p>
79.54	<p>The cor. of secs. 13, 18, 19 and 24, monumented by a granite stone, 8x6x3 ins., firmly set 3 ins. in the ground, mkd. with 3 notches on N. and S. edges, with mound of stone W.</p>
	<p>from which the orig. bearing tree: A juniper, 5 ins. diam., bears N. 18° E., 66 lks. dist., mkd. T7SR20ES18BT. (Record called for a pinon, N. 8° E., 88 lks. dist.).</p>
	<p>At the corner point Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R19E R20E S 13 S 18 S 24 S 19 1968</p>
	<p>Bury the orig. cor. stone in the mound of stone.</p>

Dependent Resurvey, Portion West Boundary,
T. 7 S., R. 20 E.

CHAINS	
	<p>Corner falls on steep S. slope.</p> <p>Land, semi-mountainous. Soil, rocky loam. Timber, scattered juniper. Undergrowth, bunchgrass, mesquite and cacti.</p>
	<p>Reestablishment of the Survey Executed by T. F. White in 1877</p> <hr/>
	<p>N. 0°04' E., bet. secs. 13 and 18.</p>
	<p>Over broken land.</p>
19.83	<p>Point for the S 1/16 sec. cor. of secs. 13 and 18, at proportionate dist.</p>
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R19E R20E S 1/16 S 13 S 18 1968</p>
	<p>Cor. falls on steep E. slope.</p>
39.66	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R19E R20E 1/4 S 13 S 18 1968</p>
	<p>Raise a mound of stone W. of the iron post.</p>
50.30	<p>Power line, bears NE. and SW.</p>
50.50	<p>Bladed road, bears NE. and SW.</p>
55.70	<p>Fourmile Creek, 50 lks. wide, 2 ft. deep, course irregularly E.</p>
79.31	<p>The cor. of secs. 7, 12, 13 and 18 monumented by an iron post, 3 ins. diam., 10 ins. above ground, firmly set in small collar of stone, mkd. T7S R19E R20E S7 S12 S13 S18 1913.</p>
	<p>Land, rolling and broken. Soil, rocky loam. Timber, scattered juniper S. 20 chs. Undergrowth, bunchgrass, mesquite and cacti.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>Reestablishment of the Survey Executed by T. F. White in 1877</p> <hr/> <p>The order in which surveyed lines are normally written was deviated from to simplify the procedure of writing the completion survey in this township.</p> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., a granite stone, 16x9x3 ins., lying loose in a mound of stone, mkd. with 3 notches on a face; no other mks. legible.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R20E R21E <u>S 13 S 18</u> <u>S 24 S 19</u> 1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>This corner falls in an abandoned fence line bearing N. and S.</p> <p>N. 88°41' W., along the N. bdy. of sec. 24.</p> <p>Over mountainous land.</p> <p>15.20 Spur, slopes S. 50° E.</p> <p>33.90 Draw, drains S.</p> <p>39.03 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This point now functions for the ¼ sec. cor. of sec. 24 only; not monumented.</p> <p>43.40 Spur, slopes S.; thence descend along steep S. slope.</p> <p>78.06 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist. longitudinally and at record dist. latitudinally from the cor. of secs. 25, 26, 35 and 36; there is no remaining evidence of the orig. cor. This point now functions for the cor. of secs. 23 and 24 only.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p><u>S 13</u> <u>S 23 S 24</u> T7S R20E 1968</p> </div> <p>from which</p> <p>The cor. of secs. 25, 26, 35 and 36, bears S. 0°24' W., 160.00 chs. dist., monumented by a granite stone, 12x8x8 ins. above ground, firmly set, mkd. with 1 notch on E. and S. faces; not remonumented.</p> <p>from which an orig. bearing tree::</p> <p>A mesquite (dead), 8 ins. in diam., bears S. 32° W., 130 lks. dist., mkd. TVIISRXXEXXXV.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS					
	<p>(Record bearing S. 45° W.). There is no evidence of the other orig. bearing tree.</p> <p>Raise a mound of stone W. of the cor.</p> <p>This control line was fully retraced for evidence of intervening corners, none of which were recovered.</p> <p>Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, catclaw and cacti.</p>				
<p>24.90</p> <p>39.19</p> <p>44.00</p> <p>63.10</p> <p>65.60</p> <p>78.37</p>	<p>N. 89°43' W., along the N. bdy. of sec. 23.</p> <p>Over mountainous land, along steep S. slope.</p> <p>Wash, 30 lks. wide, 2 ft. deep, drains irregularly W. along line.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor. This point now functions for the ¼ sec. cor. of sec. 23 only; not monumented.</p> <p>Leave wash, 30 lks. wide, 2 ft. deep, drains N. 85° W.</p> <p>Track road, bears irregularly N. and S.</p> <p>Buford Canyon, 180 lks. wide, 2 ft. deep, drains S.</p> <p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist. longitudinally, and at record dist. latitudinally from the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R20E</p> <table style="margin: auto;"> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> </table> <p>1968</p> </div> <p>from which</p> <p>The cor. of secs. 34 and 35 only, T. 7 S., R. 20 E., on the S. bdy. of the Tp., bears S. 0°45' W., 240.00 chs. dist., monumented by an iron post, 2 ins. diam., 14 ins. above ground, firmly set, mkd. T7S R20E S34 S35 T8S R20E S2 1928</p> <p>Land, mountainous. Soil, rocky loam. Timber, scattered mesquite and cottonwood along Buford Canyon. Undergrowth, bunchgrass, cat claw and cacti.</p>	S 15	S 14	S 22	S 23
S 15	S 14				
S 22	S 23				
<p>6.40</p> <p>39.03</p>	<p>S. 87°17' W., bet. secs. 15 and 22.</p> <p>Over mountainous land.</p> <p>Wash, 30 lks. wide, 2 ft. deep, drains S. 25° E.</p> <p>Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the</p>				

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R20E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{15}{22}$ 1968</p>
39.20	Wash, 10 lks. wide, 2 ft. deep, drains SW.
51.30	Wash, 30 lks. wide, 1 ft. deep, drains S.
56.00	Spur, slopes S.
67.80	Spur, slopes S.
75.70	Spur, slopes S. 25° E.
78.04	Fence, bears S. 40° E. and N. 40° W., 5 lks. dist. to cor. of fences bearing N. and S. 40° E.
78.06	<p>The cor. of secs. 15, 16, 21 and 22, monumented by a granite stone, 14x12x12 ins., firmly set 8 ins. in the ground, mkd. with 3 notches on E. and S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R20E $\frac{S}{S}$ $\frac{16}{21}$ $\frac{S}{S}$ $\frac{15}{22}$ 1968</p> <p>from which</p> <p>The point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, bears N. 89°54' W., 122.33 chs. dist., as determined from the orig. bearing tree: a mesquite (dead), 10 ins. diam., bears S. 55° W., 181 lks. dist., mkd. $\frac{1}{4}$ S.; not monumented. This tie was made in order to link the survey of the township together. There was no evidence recovered of intervening corners.</p> <p>Bury the orig. cor. stone in the mound of stone.</p> <p>Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cacti and cat claw.</p>
	<p>N. 1°55' W., bet. secs. 15 and 16.</p> <p>Over mountainous land, along fence line.</p>
0.30	Spur, slopes SW.
5.30	Draw, drains SW.
16.50	Wash, 10 lks. wide, 2 ft. deep, drains S. 60° W.

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
32.20	Wash, 30 lks. wide, 2 ft. deep, drains SW.
38.90	Fence, bears W. and E., 58 lks. dist., to cor. of fences extending N., S. and W.
39.84	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R20E $\frac{1}{4}$ S 16 S 15 1968</p>
	from which
	Fence, bears E., 63 lks. dist.; fence, bears N. and S.
58.70	Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.
64.40	Fence, bears S. 1°30' E. and N. 1°30' W.
79.68	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist. latitudinally, and at record dist. longitudinally from the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R20E S 9 S 10 S 16 S 15 1968</p>
	from which
	The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, bears N. 88°53' W., 39.91 chs. dist., monumented by a granite stone, 8x6x5 ins. above ground, firmly set in mound of stone mkd. with $\frac{1}{4}$ on N. face; not remonumented.
	Cor. of fences, bear N. 19°11' W., 1.22 chs. dist.; fences, bear S. 1°30' E. and NW.
	Raise a mound of stone W. of the iron post.
	Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cat claw and cacti.
	N. 0°21' W., along the E. bdy. of sec. 9.
	Over mountainous land.
1.20	Track road, bears E. and W.
6.40	Wash, 15 lks. wide, 2 ft. deep, drains W.
28.10	Wash, 15 lks. wide, 1 ft. deep, drains N. 65° W.
28.40	Track road, bears S. 65° E. and N. 65° W.
39.82	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at propor-

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>tionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R20E $\frac{1}{2}$ S 9 S 10 1968</p>
39.90	Track road, bears irregularly E. and W.
43.80	Wash, 30 lks. wide, 2 ft. deep, drains irregularly NW.
49.10	Spur, slopes S. 60° W.
69.60	Wash, 25 lks. wide, 2 ft. deep, drains S. 30° W.
78.60	Spur, slopes S. 30° W.; thence descend steep W. slope.
79.64	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist. latitudinally and at record dist. from the $\frac{1}{2}$ sec. cor. of sec. 5 and 8. This corner now functions for the cor. of secs. 4 and 9 only.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S S 4 S 10 S 9 R20E 1968</p>
	<p>from which</p> <p>The $\frac{1}{2}$ sec. cor. of secs. 5 and 8, bears N. 89°31' W., 120.10 chs. dist., monumented by a post, 20 ins. long, 3 ins. squared, firmly set in mound of stone, no markings legible. This corner is 1 lk. W. of a fence, bearing N. and S.</p> <p>This control line was fully retraced for evidence of intervening corners, none of which were recovered.</p> <p>Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, mesquite and cacti.</p>
	<p>N. 0°44' W., along the E. bdy. of sec. 4.</p> <p>Over mountainous land.</p>
31.10	Klondyke Wash, 20 lks. wide, 2 ft. deep, drains S. 10° W.
39.82	Point for the $\frac{1}{2}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor. This point now functions for the $\frac{1}{2}$ sec. cor. of sec. 4 only; not monumented.
79.43	<p>The cor. of secs. 3 and 4 only, T. 7 S., R. 20 E., on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, mountainous. Soil, rocky loam.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
37.81	<p>Timber, none. Undergrowth, bunchgrass, mesquite and cacti.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, monumented by an iron post, 2½ ins. diam., 14 ins. above ground, firmly set in mound of stone, mkd. T7S R20E S28 S29 S32 S33 1955.</p> <p>N. 2°07' E., bet. secs. 28 and 29.</p> <p>Over semi-mountainous land.</p> <p>Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R20E ¼ S 29 S 28 1968</p>
75.62	<p>The cor. of secs. 20, 21, 28 and 29, as determined from the orig. bearing tree:</p> <p style="padding-left: 40px;">A tisote (dead), 8 ins. diam., bears N. 86° E., 190 lks. dist., mkd. VII EXXI B, no other markings legible. There is no evidence of the other orig. bearing tree.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R20E S 20 S 21 S 29 S 28 1968</p> <p>Set a wooden post, 4 ft. long, 3 ins. squared, alongside the iron post.</p> <p>Land, semimountainous to rolling. Soil, rocky loam. Timber, scattered tisote. Undergrowth, bunchgrass, mesquite and cacti.</p>
27.00 40.00	<p>S. 89°50' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p> <p>Spur, slopes N.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 29, at record dist. from the cor. of secs. 20, 21, 28 and 29; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R20E ¼ S 20 S 29 1968</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	Raise a mound of stone N. of the iron post.
45.70	Long Hollow, 60 lks. wide, 2 ft. deep, drains N. 80° E. and track road, bears N. 80° E. and S. 80° W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30, at record dist. from the cor. of secs. 20, 21, 28 and 29 and the cor. of secs. 17, 18, 19 and 20; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R20E $\frac{S\ 19}{S\ 30} \frac{S\ 20}{S\ 29}$ 1968</p>
	Set a wooden post, 5 ft. long, 3 ins. squared, alongside the iron post.
	Land, rolling. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, mesquite and cacti.
	N. 0°21' W., bet. secs. 19 and 20.
	Over rolling land.
17.90	Spur, slopes E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at record dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R20E $\frac{1}{4}$ $S19 S\ 20$ 1968</p>
55.90	Wash, 40 lks. wide, 2 ft. deep, drains N. 55° E.
69.80	Spur, slopes N. 50° E.
80.00	The cor. of secs. 17, 18, 19 and 20, as determined from an orig. bearing tree:
	<p style="text-align: center;">A mesquite, 12 ins. diam., bears N. 85° E., 290 lks. dist., mkd. XVII, no other markings legible. There is no evidence of the other orig. bearing tree.</p>
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R20E $\frac{S\ 18}{S\ 19} \frac{S\ 17}{S\ 20}$ 1968</p>
	from which
	<p style="text-align: center;">The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, bears N. 89°42' E., 40.02 chs. dist., hereinbefore described. This</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>tie was made in order to link the survey of this township together.</p> <p>Set a wooden post, 4 ft. long, 3 ins. squared, alongside the iron post.</p> <p>Land, rolling. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, mesquite and cacti.</p>
	<p>N. 89°59' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
12.30	Spur, slopes S.
19.10	Spur, slopes N.
27.80	Wash, 30 lks. wide, 2 ft. deep, drains N. 20° W. from S. 10° W.
39.10	Spur, slopes N.
40.28	<p>Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R20E</p> <p>¼ $\frac{S\ 18}{S\ 19}$</p> <p>1968</p> </div>
	<p>Set a wooden post, 4 ft. long, 3 ins. squared, alongside the iron post.</p>
57.30	Fence, bears N. 65° E. and S. 65° W.
59.40	Wash, 80 lks. wide, 3 ft. deep, drains N. 20° E.
65.50	Spur, slopes N.; thence over broken land.
80.56	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.</p> <p>Land, rolling and broken. Soil, rocky loam. Timber, scattered juniper W. 10 chs. Undergrowth, bunchgrass, mesquite and cacti.</p>
	<p>Completion Survey of the Subdivisional Lines, T. 7 S., R. 20 E.</p>
	<p>The defective conditions found in the resurvey of a portion of the W. bdy. and portions of the subdivisional lines indicated the rectangular limits for the subdivisional surveys would be excessive. Therefore, a sectional guide meridian was surveyed North from the cor. of secs. 14, 15, 22 and 23, to an intersection with the S. bdy. of sec. 2 where a closing cor. was established.</p>

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS																
	<p>A sectional correction line was surveyed West from the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., to an intersection with the sectional guide meridian, where a closing cor. was established. Also, a sectional correction line was surveyed West from the closing cor. of secs. 29 and 30, determined by a line surveyed S. 0°03' E., from the cor. of secs. 19, 20, 29 and 30 intersecting the N. bdy. of sec. 32, to an intersection with the W. bdy. of the Tp., where a closing cor. was established.</p> <p>From the cor. of secs. 14, 15, 22 and 23, hereinbefore described.</p> <p>NORTH, on a sectional guide meridian, along the E. bdy. of sec. 15.</p> <p>Over mountainous land.</p>															
19.10	Spur, slopes S. 5° E.															
40.00	Point for the ¼ sec. cor. of sec. 15 only.															
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.															
	<table border="0"> <tr><td>T7S</td><td> </td><td></td></tr> <tr><td>¼</td><td> </td><td></td></tr> <tr><td>S 15</td><td> </td><td></td></tr> <tr><td>R20E</td><td> </td><td></td></tr> <tr><td>1969</td><td></td><td></td></tr> </table>	T7S			¼			S 15			R20E			1969		
T7S																
¼																
S 15																
R20E																
1969																
44.10	Draw, drains S. 15° E.															
55.50	Spur, slopes S. 50° W.															
62.40	Draw, drains S. 55° W.															
72.60	Track road, bears N. 80° E. and S. 80° W.															
75.91	Point for the cor. of secs. 10 and 15 only, at intersection with a line run E. from the cor. of secs. 9, 10, 15 and 16.															
	Set the iron post 22 ins. in the ground, brass cap mkd.															
	<table border="0"> <tr><td>T7S</td><td> </td><td></td></tr> <tr><td>S 10</td><td> </td><td>S 14</td></tr> <tr><td>S 15</td><td> </td><td></td></tr> <tr><td>R20E</td><td> </td><td></td></tr> <tr><td>1969</td><td></td><td></td></tr> </table>	T7S			S 10		S 14	S 15			R20E			1969		
T7S																
S 10		S 14														
S 15																
R20E																
1969																
	from which															
	The N. cor. of a cabin, bears N. 34°55' W. 18.59 chs. dist.															
	Raise a mound of stone W. of the iron post.															
	Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cat claw and cacti.															
	NORTH, on a sectional guide meridian, along the E. bdy. of sec. 10.															

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS											
	Over mountainous land.										
14.90	Draw, drains W.										
19.30	Spur, slopes S. 75° W.										
24.00	Track road in draw, bears N 55° E and S. 55° W.; draw drains S, 55° W.										
37.80	Spur, slopes S. 60° W.										
40.00	Point for the ¼ sec. cor. of sec. 10 only.										
	Set the iron post 20 ins. in the ground, brass cap mkd.										
	<table border="0"> <tr><td>T7S</td><td> </td></tr> <tr><td>¼</td><td> </td></tr> <tr><td>S 10</td><td> </td></tr> <tr><td>R20E</td><td> </td></tr> <tr><td>1969</td><td></td></tr> </table>	T7S		¼		S 10		R20E		1969	
T7S											
¼											
S 10											
R20E											
1969											
	from which										
	Quinn Mine derrick, bears S. 62°56' E., 14.00 chs. dist.										
	Raise a mound of stone W. of the iron post.										
45.10	Draw, drains S. 70° W.										
47.80	Spur, slopes S. 75° W.										
55.60	Wash, 40 lks. wide, 4 ft. deep, drains S. 75° W.										
82.19	Intersect the S. bdy. of sec. 2.										
	Point for the closing cor. of secs. 10 and 11.										
	Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.										
	<table border="0"> <tr><td>S 2</td><td> </td></tr> <tr><td>S 10</td><td> S 11</td></tr> <tr><td>C C</td><td></td></tr> <tr><td>T7S R20E</td><td></td></tr> <tr><td>1969</td><td></td></tr> </table>	S 2		S 10	S 11	C C		T7S R20E		1969	
S 2											
S 10	S 11										
C C											
T7S R20E											
1969											
	from which										
	The cor. of secs. 2, 3, 10 and 11, bears West 3.24 chs. dist., monumented by an iron post, 2½ ins. diam., 16 ins. above ground firmly set in collar of stone, mkd. T7S R20E S2 S3 S10 S11 1967. This cor. now functions for the cor. of secs. 2 and 3 only. I change the markings to read:										
	<table border="0"> <tr><td>T7S R20E</td><td></td></tr> <tr><td>S 3</td><td> S 2</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td>1967</td><td></td></tr> <tr><td>1969</td><td></td></tr> </table>	T7S R20E		S 3	S 2	S 10		1967		1969	
T7S R20E											
S 3	S 2										
S 10											
1967											
1969											
	The ¼ sec. cor. of secs. 2 and 11, bears E., 36.76 chs. dist., monumented by an iron post, 2½ ins. diam., 14 ins. above ground, firmly set in a mound of stone, mkd. T7S R20E ¼ S2 S11 1967.										

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cat claw and cacti.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., 12 ins. above ground, firmly set, mkd. T7S R20E R21E S7 S12 S13 S18 1915.</p> <p>from which the orig. bearing trees:</p> <p>A black oak stump (burned), bears N. 24$\frac{1}{4}$° E., 149 lks. dist.; no markings legible.</p> <p>A black oak stump (burned), bears S. 81° E., 174 lks. dist., mkd. S.; no other markings legible.</p> <p>A black oak (burned), 12 ins. diam., bears S. 30$\frac{1}{2}$° W., 19 lks. dist., mkd. T7S R20E S13 BT.</p> <p>A black oak stump (burned), bears N. 20$\frac{1}{4}$° W., 139 lks. dist., mkd. 20E S12 BT.; no other markings legible.</p> <p>WEST, on a sectional correction line, bet. secs. 12 and 13.</p> <p>Over mountainous land.</p>
0.10	Wash, 10 lks. wide, 1 ft. deep, drains S. 25° W.
4.00	Spur, slopes S. 25° W.
26.10	Draw, drains NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T7S R20E $\frac{1}{4}$ <u>S 12</u> S 13 1969</p>
69.40	Buford Canyon, 80 lks. wide, 2 ft. deep, drains irregularly SW.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	<p>T7S R20E <u>S 11</u> <u>S 12</u> S 14 S 13 1969</p>
	Raise a mound of stone W. of the iron post.
	<p>Land, mountainous. Soil, rocky loam. Timber, scattered oak E. 5 chs. Undergrowth, bunchgrass, cat claw and cacti.</p>

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>WEST, on a sectional correction line, bet, secs. 11 and 14.</p>
	<p>Over mountainous land.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p>
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R20E $\frac{1}{4}$ $\frac{S\ 11}{S\ 14}$ 1969</p>
42.40	<p>Spur, slopes S.</p>
61.40	<p>Track road, bears N. 60° E. and S. 60° W.</p>
76.53	<p>Intersect the sectional guide meridian.</p>
	<p>Point for the closing cor. of secs. 11 and 14.</p>
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">S 10 $\frac{T7S}{S\ 11\ C}{S\ 14\ C}$ R20E 1969</p>
	<p>from which</p>
	<p style="text-align: center;">The cor. of secs. 10 and 15, bears SOUTH, 1.77 chs. dist., hereinbefore described.</p>
	<p>Land, mountainous.</p>
	<p>Soil, rock loam.</p>
	<p>Timber, none.</p>
	<p>Undergrowth, bunch grass, cat claw and cacti.</p>
	<p>Point for the $\frac{1}{4}$ sec. of sec. 14 only, established at 40.00 chs. in southing from the closing cor. of secs. 11 and 14, and on the sectional guide meridian.</p>
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S $\frac{1}{4}$ S 14 R20E 1969</p>
	<p>from which</p>
	<p style="text-align: center;">The $\frac{1}{4}$ sec. cor. of sec. 15 only, bears NORTH, 2.32 chs. dist., hereinbefore described.</p>
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 11 only, established at midpoint between the closing cors. of secs. 10 and 11, 11 and 14, and on the sectional guide meridian.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p style="text-align: center;"> T7S $\frac{1}{4}$ S 11 R20E 1969 </p> <p>from which</p> <p style="text-align: center;">The $\frac{1}{4}$ sec. cor. of sec. 10 only, bears SOUTH, 1.98 chs. dist., hereinbefore described.</p> <p>Raise a mound of stone E. of the iron post.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 0°13' E., bet. secs. 11 and 12.</p> <p>Over mountainous land.</p>
29.00	Track road, bears N. 57° E. and S. 57° W.
40.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;"> T7S R20E $\frac{1}{4}$ S 11 S 12 1969 </p> <p>Raise a mound of stone W. of the iron post.</p>
41.70	Draw, drains S. 65°W.
72.90	Draw, drains S. 50°W.
80.46	The cor. of secs. 1, 2, 11 and 12, monumented by an iron post, 2½ ins. diam., 16 ins. above ground, firmly set in mound of stone, mkd. T7S R20E S1 S2 S11 S12 1967.
	<p>Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cat claw and cacti.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 0°01' E., bet. secs. 13 and 14.</p> <p>Over mountainous land.</p>
12.10	Buford Canyon, 70 lks. wide, 2 ft. deep, drains S. 20° W.
37.50	Spur, slopes N. 40° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;"> T7S R20E $\frac{1}{4}$ S 14 S 13 1969 </p>

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
44.90	Draw, drains N. 70° W.
50.40	Spur, slopes N. 80° W.
53.70	Draw, drains N. 80° W.
59.00	Spur, slopes S. 60° W.
77.50	Wash, 40 lks. wide, 2 ft. deep, drains S. 60° W.
78.16	Intersect the N. bdy. of sec. 23.
	Point for the closing cor. of secs. 13 and 14.
	Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.
	$\begin{array}{c} C C \\ T7S R20E \\ \hline S 14 S 13 \\ \hline S 23 \\ 1969 \end{array}$
	from which
	The cor. of secs. 23 and 24, bears S. 89°43' E., 1.82 chs. dist., hereinbefore described.
	Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cat claw and cacti.
	Point for the $\frac{1}{4}$ sec. cor. of sec. 13 only, established at midpoint bet. secs. 13, 18, 19 and 24 on the E. bdy., and the closing cor. of secs. 13 and 14, and on the N. bdy. of sec. 23.
	Set the iron post over an "X" chiseled in rock, mound of stone to top, brass cap mkd.
	$\begin{array}{c} T7S R20E \\ \hline \frac{1}{4} S 13 \\ \hline 1969 \end{array}$
	from which
	The point for the $\frac{1}{4}$ sec. cor. of sec. 24 only, bears S. 88°41' E., 91 lks. dist., hereinbefore described.
	Point for the $\frac{1}{4}$ sec. cor. of sec. 14 only, established at 40.00 chs. in westing from the closing cor. of secs. 13 and 14, and on the N. bdy. of sec. 23.
	Set the iron post 4 ins. in the ground, over an "X" chiseled in rock, mound of stone 6 ft. in diam., to top, brass cap mkd.
	$\begin{array}{c} T7S R20E \\ \hline \frac{1}{4} S 14 \\ \hline 1969 \end{array}$
	from which
	The point for the $\frac{1}{4}$ sec. cor. of sec. 23 only,

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>bears S. 89°43' E., 2.63 chs. dist., hereinbefore described.</p> <p>This cor. falls in a washed ares, 30 lks. wide, 2 ft. deep draining N. 85° W. It is very unlikely this wash will carry enough water, at any one time, to destroy the cor. position.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>EAST, bet. secs. 10 and 15.</p> <p>Over mountainous land.</p>
7.80	Track road, bears S. 60° E. and N. 80° W.
37.30	Abandoned fence, bears N. and S.
40.00	<p>Point for the ¼ sec. cor. of sec. 15 only.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> <u>¼ S 15</u> T7S R20E 1969 </p>
40.20	Abandoned fence, bears N. and S.
40.59	<p>Point for the ¼ sec. cor. of sec. 10 only, at 40.00 chs. in westing from the cor. of secs. 10 and 15.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T7S R20E <u>¼ S 10</u> 1969 </p>
58.30	Spur, slopes N. 25° W.
67.20	Spur, slopes N. 15° W.
79.50	Spur, slopes N. 25° W.
80.59	<p>The cor. of secs. 10 and 15 only, hereinbefore described.</p> <p>Land, mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cat claw and cacti.</p>
	<p>From the closing cor. of secs. 10 and 11.</p> <p>WEST, along the N. bdy. of sec. 10.</p> <p>Over mountainous land.</p>
3.24	The cor. of secs. 2 and 3 only, hereinbefore described.
6.60	Ridge, bears N. 50° E. and S. 50° W.
17.80	Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.
32.40	Track road, bears N. 40° E. and S. 40° W.

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS																
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 10 only.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 10 T7S R20E 1969 </p>															
43.24	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 3 only, at 40.00 chs. in westing from the cor. of secs. 2 and 3.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T7S R20E $\frac{1}{4}$ S 3 1969 </p>															
43.90	<p>Draw, drains S. 30° W.</p>															
50.50	<p>Spur, slopes S. 30° W.</p>															
58.70	<p>Draw, drains S. 20° W.</p>															
61.60	<p>Spur, slopes S. 20° W.</p>															
71.70	<p>Wash, 110 lks. wide, 9 ft. deep, drains S. 15° W.</p>															
79.70	<p>Spur, slopes S. 30° W.</p>															
81.02	<p>Intersect the E. bdy. of sec. 4.</p> <p>Point for the closing cor. of secs. 3 and 10.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> <table border="0"> <tr><td></td><td>T7S</td><td></td></tr> <tr><td>S 4</td><td>S 3 C</td><td></td></tr> <tr><td></td><td>S 10 C</td><td></td></tr> <tr><td></td><td>R20E</td><td></td></tr> <tr><td></td><td>1968</td><td></td></tr> </table> </p> <p>from which</p> <p style="padding-left: 40px;">The cor. of secs. 4 and 9 only, bears S. 0°44' E., 2.64 chs. dist., hereinbefore described.</p> <p>Raise a mound of stone W. of the iron post.</p> <p>Land, mountainous. Soil, rocky loam. Timber, scattered juniper. Undergrowth, bunchgrass, cat claw and cacti.</p>		T7S		S 4	S 3 C			S 10 C			R20E			1968	
	T7S															
S 4	S 3 C															
	S 10 C															
	R20E															
	1968															
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 3 only, established at 40.00 chs. in northing from the closing cor. of secs. 3 and 10.</p> <p>Set the iron post over an "X" chiseled in rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> <table border="0"> <tr><td></td><td>T7S</td><td></td></tr> <tr><td></td><td>$\frac{1}{4}$</td><td></td></tr> <tr><td></td><td>S 3</td><td></td></tr> <tr><td></td><td>R20E</td><td></td></tr> <tr><td></td><td>1968</td><td></td></tr> </table> </p>		T7S			$\frac{1}{4}$			S 3			R20E			1968	
	T7S															
	$\frac{1}{4}$															
	S 3															
	R20E															
	1968															

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
	<p>from which</p> <p>The point for the $\frac{1}{4}$ sec. cor. of sec. 4 only, bears S. $0^{\circ}44'$ E., 2.82 chs. dist., hereinbefore described.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30, hereinbefore described.</p>
	<p>S. $0^{\circ}03'$ E., bet. secs. 29 and 30.</p>
	<p>Over semi-mountainous land.</p>
13.50	<p>Long Hollow, 40 lks. wide, 2 ft. deep, drains N. 65° E., and track road, bears N. 65° E. and S. 65° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R20E $\frac{1}{4}$ S 30 S 29 1968</p> <p>Raise a mound of stone W. of the iron post.</p>
44.60	<p>Wash, 30 lks. wide, 1 ft. deep, drains N. 40° E.</p>
53.60	<p>Spur, slopes N. 70° W.</p>
59.30	<p>Spur, slopes N. 10° E.</p>
75.25	<p>Intersect the N. bdy. of sec. 32.</p>
	<p>Point for the closing cor. of secs. 29 and 30 only.</p> <p>Set the iron post 26 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C C T7S R20E S 30 S 29 S 32 1968</p>
	<p>from which</p> <p>The cor. of secs. 31 and 32 only, bears N. $89^{\circ}54'$ W., 2.77 chs. dist., hereinafter described.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, bears S. $89^{\circ}54'$ E., 37.23 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 12 ins. above ground, firmly set in a mound of stone, brass cap mkd. $\frac{1}{4}$ S29 S32 1955.</p> <p>Land, semi-mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, mesquite, cat claw and cacti.</p>
	<p>N. $89^{\circ}54'$ W., along the N. bdy. of sec. 32.</p> <p>Over semi-mountainous land.</p>

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS	
2.77	<p>The cor. of secs. 29, 30, 31 and 32, monumented by an iron post, 2½ ins. diam., 12 ins. above ground, firmly set with mound of stone W., mkd. T7S R20E S29 S30 S31 S32 1955. This cor. now functions for the cor. of secs. 31 and 32 only. I change the markings to read:</p>
	$\begin{array}{r} \text{S } 30 \\ \hline \text{S } 31 \mid \text{S } 32 \\ \text{T7S R20E} \\ 1968 \\ 1955 \end{array}$
	<p>WEST, on a sectional correction line, along the N. bdy. of sec. 31 continuing measurement.</p>
40.00	<p>Point for the ¼ sec. cor. of sec. 30 only. Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	$\begin{array}{r} \text{T7S R20E} \\ \hline \frac{1}{4} \text{ S } 30 \\ 1968 \end{array}$
42.77	<p>Point for the ¼ sec. cor. of sec. 31 only, at 40.00 chs. in westing from the cor. of secs. 31 and 32. Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	$\begin{array}{r} \hline \frac{1}{4} \text{ S } 31 \\ \text{T7S R20E} \\ 1968 \end{array}$
44.70	<p>Track road, bears N. 20° E. and S. 20° W.</p>
48.10	<p>Left Branch, Long Hollow, 40 lks. wide, 2 ft. deep, drains N. 25° E.</p>
63.60	<p>Spur, slopes N. 35° E.</p>
68.20	<p>Fence, bears N. and S.</p>
81.20	<p>Intersect the W. bdy. of the Tp. Point for the closing cor. of secs. 30 and 31. Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	$\begin{array}{r} \text{T7S} \\ \text{T7S} \mid \text{S } 30 \\ \text{S } 25 \mid \text{S } 31 \\ \text{R19E} \mid \text{R20E} \\ \hline 1968 \end{array} \text{ CC}$
	<p>from which</p> <p>The cor. of secs. 25 and 36, T. 7 S., R. 19 E., bears South, 3.95 chs. dist., hereinbefore described.</p> <p>Raise a mound of stone W. of the iron post.</p> <p>Land, semi-mountainous. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, mesquite, cat claw and cacti.</p>
	<p>Point for the ¼ sec. cor. of sec. 31 on the W. bdy. of the Tp., established at 40.00 chs. in southing from the</p>

Completion Survey of the Subdivisional Lines,
T. 7 S., R. 20 E.

CHAINS											
	<p>closing cor. of secs. 30 and 31.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td> </td><td>T7S</td></tr> <tr><td> </td><td>¼</td></tr> <tr><td> </td><td>S 31</td></tr> <tr><td> </td><td>R20E</td></tr> <tr><td> </td><td>1968</td></tr> </table> </div> <p>from which</p> <p>The point for the ¼ sec. cor. of sec. 36, T. 7 S., R. 19 E., bears S. 0°03' E., 3.86 chs. dist.</p> <p>Raise a mound of stone E. of the iron post.</p>		T7S		¼		S 31		R20E		1968
	T7S										
	¼										
	S 31										
	R20E										
	1968										
	<p>Point for the ¼ sec. cor. of sec. 31, on the S. bdy. of the Tp., at 40.00 chs. in westing from the closing cor. of secs. 31 and 32, T. 7 S., R. 20 E., and on line bet. cor. of secs. 5 and 6 and the ¼ sec. cor. of sec. 6, T. 8 S., R. 20 E.</p> <p>Set the iron post, 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td>R20E</td></tr> <tr><td>¼ S</td><td>31</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1968</td></tr> </table> </div> <p>from which</p> <p>The ¼ sec. cor. of sec. 6, T. 8 S., R. 20 E., bears West, 3.18 chs. dist., monumented by an iron post, 1 in. diam., 10 ins. above ground, firmly set in mound of stone, mkd. ¼ S6 1928.</p>	T7S	R20E	¼ S	31	<hr/>		1968			
T7S	R20E										
¼ S	31										
<hr/>											
1968											
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 89°41' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>										
13.20	Spur, slopes S. 10° E.										
15.10	Spur, slopes N. 50° E.										
20.70	Draw, drains N. 5° E.										
24.10	Spur, slopes N. 25° E.										
27.80	Draw, drains N. 35° E.										
33.20	Spur, slopes N. 40° E.										
38.30	Draw, drains N. 60° E.										
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 30.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>										

Completion Survey of the Subdivisional Lines,
T. p 7 S., R. 20 E.

CHAINS	
<p>56.60</p> <p>59.40</p> <p>66.10</p> <p>81.03</p>	<p style="text-align: center;">T7S R20E S 19 S 30 1969</p> <p>Raise a mound of stone N. of the iron post.</p> <p>Spur, slopes N. 25° E.</p> <p>Draw, drains N. 5° E.</p> <p>Spur, slopes N. 10° E.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.</p> <p>Land, rolling. Soil, rocky loam. Timber, none. Undergrowth, bunchgrass, cat claw and cacti.</p>
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 30, on the W. bdy. of the Tp., established at 40.00 chs. in southing from the cor. of secs. 19, 24, 25 and 30.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S $\frac{1}{4}$ S 30 R20E 1968</p> <p>from which</p> <p style="padding-left: 40px;">The $\frac{1}{4}$ sec. cor. of sec. 25, T. 7 S., R. 19 E., bears N. 0°04' E., 42 lks. dist.</p> <p style="padding-left: 40px;">Fence, bears East, 1 lk. dist., fence bears N. and S.</p>
	<p>General Description</p>
	<p>The area embraced by this survey varies from rolling to mountainous terrain. Elevations in the surveyed area range from about 3600 feet in the southwestern portion to about 5900 feet above sea level in the northeastern portion. The soil is mostly sandy and rocky loam. Vegetation consists of bunchgrass, mesquite, cat claw, oakbrush and cacti. Widely scattered juniper timber is found in the higher elevations.</p> <p>The northeastern portion of the township drains in a southwesterly direction; the southwestern portion drains in a northeasterly direction; both drain into Aravaipa Creek, which enters on the south boundary of section 36, traverses in a northwesterly direction, leaving on the west boundary of section 6.</p> <p>The entire surveyed area is uninhabited. The primary use of this land is for grazing livestock.</p> <p>There has been considerable mineral activity in the past. Quinn Mine, located in section 11, unsurveyed, shows no evidence of recent activity.</p>

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Louis D. Gilbert, HEREBY
CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day
of November, 19 68, (I) ~~(We)~~ have made a dependent resurvey of portions
of the West and North Boundaries and Subdivisional Lines, and a completion
survey of the Subdivisional Lines of Township 7 South, Range 20 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
specific manner described in the foregoing field notes.

August 15, 1969
(Date)

Louis D. Gilbert
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JAN 16 1970

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of portions of the West and
North Boundaries and Subdivisional Lines, and a completion survey of the
Subdivisional Lines of Township 7 South, Range 20 East, of the Gila and
Salt River Meridian, Arizona,

executed by Louis D. Gilbert

having been critically examined and found correct, are hereby approved.

OCT 7 1970
(Date)

Clark F. Summers
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626