

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION

OF THE NORTH BOUNDARY OF THE TOWNSHIP

AND A PORTION OF THE SUBDIVISION LINES,

AND THE SURVEY OF A PORTION OF THE

SUBDIVISION LINES IN SECTIONS 4 AND 5

TOWNSHIP 19 NORTH, RANGE 8 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

MARLIN G. LIVERMORE II

CADASTRAL SURVEYOR

Under special instructions dated February 7, 19 67, which provided for the surveys included under Group Number 489, approved February 13, 1967, and assignment instructions dated May 21, 19 68.

Survey commenced May 24, 19 68

Survey completed June 14, 19 68

1A

BOOK 4875

INDEX DIAGRAM

Township 19 North, Range 8 East

6	3	1		8	2	1
	5	4				
	9	6				
7	8	5	10	11	12	
	8	9				
18	17	16	18	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Subdivision lines for section 4 pp. 10-15
Subdivision lines for section 5 pp. 15-22

Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS

Township 19 North, Range 8 East. The boundaries and subdivision lines were surveyed by J. L. Harris, Deputy Surveyor, in 1879, as shown upon the official plat, approved November 8, 1879. A number of corners were remonumented by Wallace R. Ott, Surveying Technician, in 1966, accepted February 27, 1968.

The following field notes are those of the dependent resurvey of a portion of the north boundary and a portion of the subdivision lines, and the survey of a portion of the subdivision lines in sections 4 and 5, Township 19 North, Range 8 East, Gila and Salt River Meridian, Arizona.

Before restoring the corners, the lines of the original survey was retraced and a diligent search made for any evidence of the original corners, bearing trees, and calls of the original field note records. When duly identified the corner positions were remonumented.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect the identified corner locations, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner.

The dependent resurvey and survey were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the special instructions dated February 7, 1967.

The directions of all lines of this survey were determined by direct altitude observation of the sun, for azimuth and carried forward by normal transit traverse. Distances are expressed in chains, reduced to horizontal equivalents.

The data furnished with the special instructions give the geographic position of the corner of sections 3, 4, 9 and 10 as: Latitude 35° 03.0' N., Longitude 111° 32.6' W.

The magnetic declination as obtained by reference to the U. S. Geological Survey map, Lower Lake Mary, Arizona, 1962 is: 14½° E.

Dependent Resurvey of a Portion
of the North Boundary
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

Re-establishment of the Survey Executed by
J. L. Harris, Deputy Surveyor, in 1879

Beginning at the cor. of Tps. 19 and 20 N., R. 8 E., secs. 3, 4, 33 and 34, monumented with an iron post, 2½ ins. in diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, as described in the official record of the remonumentation of a number of corners in Tp. 19 N., R. 8 E., by Wallace R. Ott, executed in 1966, with brass cap mkd.

T20N R8E
S 33 | S 34
S 4 | S 3
T19N
1966

Dependent Resurvey of a Portion
of the North Boundary
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>substantiated by:</p> <p>A pine, 13 ins. in diam., bears N. 84° E., 114 lks. dist., mkd. T20N R8E S3/4 BT.</p> <p>A pine, 12 ins. in diam., bears S. 42° E., 110 lks. dist., mkd. T19N R8E S3 BT.</p> <hr/> <p>S. 89° 39' W., along the N. boundary of the township, between secs. 4 and 33.</p> <p>Over rolling land, through scattering timber.</p>
25.18	Enter open meadow.
26.98	Road, bears NW-SE.
31.48	Wash, drains NE.
34.78	Road, bears NE-SW., enter scattering timber.
40.19	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. in diam., firmly set, projecting 12 ins. above the ground, and in a collar of stone, as described in the official record of the remonumentation of a number of corners in Tp. 19 N., R. 8 E., by Wallace R. Ott, executed in 1966, with brass cap mkd.</p> <p style="text-align: center;">T20N R8E 1/4 S 33 S 4 T19N 1966</p> <p>substantiated by:</p> <p>A pine, 21 ins. in diam., bears S. 47 1/2° W., 120 lks. dist., mkd. T19N R8E 1/4 S4 BT.</p> <p>A pine, 8 ins. in diam., bears N. 48 1/2° W., 7 lks. dist., mkd. T20N R8E 1/4 S33 BT.</p> <hr/> <p>S. 89° 37' W., beginning new measurement.</p>
19.93	<p>The point for the W 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. in diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R8E W 1/16 S 33 S 4 T19N 1968</p> <p>No other suitable accessory available.</p>
39.86	<p>The cor. of secs. 4, 5, 32 and 33, marked with an iron pipe, 1 in. in diam., firmly set, projecting 6 ins. above the ground, and in a small collar of stone. This corner has long been accepted as the position for the corner and is accepted as the best available evidence of the position of the original corner point.</p>

Dependent Resurvey of a Portion
of the North Boundary
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R8E S 32 S 33 S 5 S 4 T19N 1968</p> <p>deposit the iron pipe alongside the iron post, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. in diam., bears N. 22° E., 123 lks. dist., mkd. T20N R8E S33 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears S. $76\frac{1}{4}^\circ$ E., 80 lks. dist., mkd. T19N R8E S4 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears N. $87\frac{1}{2}^\circ$ W., 117 lks. dist., mkd. T20N R8E S32 BT.</p>
	<p>S. $89^\circ 37'$ W., between secs. 5 and 32.</p> <p>Over rolling land, through scattering timber.</p>
3.50	Road, bears NW-SE.
20.00	The point for the E $1/16$ sec. cor. of secs. 5 and 32.
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T20N R8E E 1/16 S 32 S 5 T19N 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears N. $44\frac{1}{2}^\circ$ W., 64 lks. dist., mkd. E $1/16$ S32 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. in diam., bears S. $53\frac{1}{4}^\circ$ E., 31 lks. dist., mkd. E $1/16$ S5 BT.</p>
31.53	Road, bears NW-SE.
31.87	Small creek, course N-NE.
40.00	<p>The $1/4$ sec. cor. of secs. 5 and 32, monumented with a pine post loosely set and in a mound of stone, 3 ft. base, 2 ft. high, substantiated by:</p> <p style="padding-left: 40px;">A pine stump, 20 ins. in diam., bears N. $11\frac{3}{4}^\circ$ W., 34 lks. dist., (record: N. 20° W., 42 lks. dist.) blazed, no marks visible.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion
of the North Boundary
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T20N R8E

$\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$

T19N

1968

deposit the pine post in the mound of stone alongside the iron post.

from which

A pine, 8 ins. in diam., bears S. $19\frac{3}{4}^\circ$ W., 55 lks. dist., mkd. $1/4$ S5 BT.

A pine, 12 ins. in diam., bears N. $69\frac{1}{4}^\circ$ W., 124 lks. dist., mkd. $1/4$ S32 BT.

N. $89^\circ\ 36'$ W., beginning new measurement.

8.30 Wash, drains S., ascend over E. slope.

27.29 Road, bears N-S.

36.08 Top of ascent; thence, over rolling land.

39.74 The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, $2\frac{1}{2}$ ins. in diam., firmly set, on bedrock, and in a mound of stone, as described in the official record of the remonumentation of a number of corners in Tp. 19 N., R. 8 E., by Wallace R. Ott, executed in 1966, with brass cap mkd.

T20N R8E

$\frac{S\ 31}{S\ 6}$ | $\frac{S\ 32}{S\ 5}$

T19N

1966

substantiated by:

A pine, 14 ins. in diam., bears N. 46° E., 22 lks. dist., mkd. T20N R8E S32 BT.

A pine, 10 ins. in diam., bears N. 57° W., 27 lks. dist., mkd. S31 BT.

Dependent Resurvey of a Portion
of the Subdivision Lines
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

From the cor. of secs. 3, 4, 9 and 10, monumented with an iron post, $2\frac{1}{2}$ ins. in diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, as described in the official record of the remonumentation of a number of corners in this township, by Wallace R. Ott, executed in 1966, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivision Lines
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T19N R8E S 4 S 3 ----- S 9 S 10 1966</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A pine, 13 ins. in diam., bears N. 24½° E., 82 lks. dist., (record: N. 21½° E.) mkd. T19N R8E S3 BT.</p> <p style="padding-left: 40px;">A pine, 16 ins. in diam., bears S. 3½° E., 83 lks. dist., (record: S. 7½° E.) mkd. T19N R8E S10 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>NORTH, between secs. 3 and 4.</p> <p>Over rolling land, through scattering timber.</p>	
15.43	Fence, bears NW-SE.	
40.18	The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. in diam., firmly set, projecting 4 ins. above the ground, as described in the official record of the remonumentation of a number of corners in this township, by Wallace R. Ott, executed in 1966, with brass cap mkd.	
	<p style="text-align: center;">T19N R8E S 4 S 3 ----- 1966</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A pine, 12 ins. in diam., bears N. 81½° E., 19 lks. dist., mkd. T19N R8E 1/4 S3 BT.</p> <p style="padding-left: 40px;">An oak, 8 ins. in diam., bears S. 47° W., 36 lks. dist., mkd. T19N R8E 1/4 S4 BT.</p> <p style="padding-left: 40px;">A mound of stone, W. of the corner.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 09' W., beginning new measurement.</p>	
38.40	Road, bears E-W.	
40.20	Intersect the N. boundary of the township, the cor. of secs. 3, 4, 33 and 34.	
	<p>From the cor. of secs. 3, 4, 9 and 10,</p> <p>N. 89° 58' W., between secs. 4 and 9.</p> <p>Over rolling land, through scattering timber.</p>	
10.90	Fence, bears NE-SW.	
19.00	Remnants of an old railroad grade, bears N-S.	
39.89	The 1/4 sec. cor. of secs. 4 and 9, mkd. by a lava stone, 22x10x10 ins., set in a mound of stone. This corner has long been accepted as the position for the corner and is accepted as the best available evidence of the position of the original corner point.	

Dependent Resurvey of a Portion
of the Subdivision Lines
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS																						
40.08	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R8E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">$\frac{1}{4}$</td> <td style="padding-right: 5px;">S</td> <td style="padding-right: 5px;">4</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-right: 5px;">S</td> <td style="padding-right: 5px;">9</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td colspan="2" style="text-align: center;">1968</td> </tr> </table> </div> <p>deposit the lava stone alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears N. $81\frac{3}{4}^\circ$ E., 82 lks. dist., mkd. $1/4$ S4 BT.</p> <p style="padding-left: 40px;">A pine, 18 ins. in diam., bears S. $12\frac{1}{4}^\circ$ E., 59 lks. dist., mkd. $1/4$ S9 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^\circ 47'$ W., beginning new measurement.</p> <p>The cors. of secs. 4, 5, 8 and 9, monumented with an iron post, $2\frac{1}{2}$ ins. in diam., firmly set, projecting 4 ins. above the ground, as described in the official record of the remonumentation of a number of corners in this township, by Wallace R. Ott, executed in 1966, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R8E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-right: 5px;">5</td> <td style="border-left: 1px solid black; padding-left: 5px;">S</td> <td style="padding-left: 5px;">4</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-right: 5px;">8</td> <td style="border-left: 1px solid black; padding-left: 5px;">S</td> <td style="padding-left: 5px;">9</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td colspan="3" style="text-align: center;">1966</td> </tr> </table> </div> <p>substantiated by:</p> <p style="padding-left: 40px;">A pine, 8 ins. in diam., bears S. 57° E., 23 lks. dist., mkd. S9 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. in diam., bears N. 4° W., 13 lks. dist., mkd. T19N R8E S5 BT.</p>	$\frac{1}{4}$	S	4		S	9		1968		S	5	S	4	S	8	S	9		1966		
$\frac{1}{4}$	S	4																				
	S	9																				
	1968																					
S	5	S	4																			
S	8	S	9																			
	1966																					
20.04	<p>N. $0^\circ 23'$ W., between secs. 4 and 5.</p> <p>Over rolling land, through scattering timber.</p> <p>The point for the S $1/16$ sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R8E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-right: 5px;">1/16</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-right: 5px;">5 S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="text-align: center;">1968</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 24 ins. in diam., bears N. $83\frac{1}{2}^\circ$ E., 42 lks. dist., mkd. S $1/16$ S4 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. in diam., bears N. $67\frac{3}{4}^\circ$ W., 47 lks. dist., mkd. S $1/16$ S5 BT.</p>	S	1/16	S	5 S 4		1968															
S	1/16																					
S	5 S 4																					
	1968																					

Dependent Resurvey of a Portion
of the Subdivision Lines
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
30.06	<p>The point for the N-S 1/64 sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N S 1/64 S 5 S 4 1968</p> <p>No other suitable accessory available.</p>
40.08	<p>The 1/4 sec. cor. of secs. 4 and 5, mkd. by a steel pin, ½ in. in diam., encased in an iron pipe, 1 in. in diam., projecting 2 ins. above the ground. This corner has long been accepted as the position for the corner and is accepted as the best available evidence of the position of the original corner point.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R8E 1/4 S 5 S 4 1968</p> <p>deposit the iron pipe and the steel pin alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p> <p>No other suitable accessory available.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0° 02' E., beginning new measurement.</p>
	<p>Through open meadow.</p>
0.40	<p>Road, bears NE-SW.</p>
5.00	<p>Leave meadow, over rolling land, through scattering timber.</p>
15.04	<p>The N-S-N 1/256 sec. cor. mkd. by an iron pipe, ½ in. in diam., projecting 4 ins. above the ground, set in a concrete cone, 18 ins. in diam. Not of record, this corner has long been accepted as the position for the corner, and is accepted as the point for the corner; this corner point was not remonumented.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears N. 65° E., 82 lks. dist., mkd. N S N 1/256 S4 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. in diam., bears N. 28° W., 55 lks. dist., mkd. N S N 1/256 S5 BT.</p>
20.05	<p>The point for the N 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion
of the Subdivision Lines
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
39.92	<p style="text-align: center;">T19N R8E N 1/16 S 5 S 4 1968</p> <p>from which</p> <p>A pine, 8 ins. in diam., bears N. 42° E., 23 lks. dist., mkd. N 1/16 S5 BT.</p> <p>A pine, 10 ins. in diam., bears S. 58$\frac{1}{4}$° W., 27 lks. dist., mkd. N 1/16 S5 BT.</p> <p>Intersect the N. boundary of the township, the cor. of secs. 4, 5, 32 and 33.</p>
7.59	<p>From the cor. of secs. 4, 5, 8 and 9, S. 89° 30' W., between secs. 5 and 8. Over rolling land, through scattering timber.</p> <p>Small creek, course N.</p>
20.01	<p>The point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. in diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
40.02	<p style="text-align: center;">T19N R8E E 1/16 $\frac{S 5}{S 8}$ 1968</p> <p>from which</p> <p>A pine, 18 ins. in diam., bears N. 47° E., 44 lks. dist., mkd. E 1/16 S5 BT.</p> <p>A pine, 18 ins. in diam., bears S. 59$\frac{1}{4}$° E., 26 lks. dist., mkd. E 1/16 S8 BT.</p> <p>The 1/4 sec. cor. of secs. 5 and 8, mkd. by a granite stone, 18x15x4 ins., firmly set, and in a mound of stone. This corner has long been accepted as the position for the corner and is accepted as the best available evidence of the position of the original corner point.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R8E $\frac{1}{4}$ $\frac{S 5}{S 8}$ 1968</p> <p>deposit the granite stone alongside the iron post and raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of the corner.</p> <p>from which</p>

Dependent Resurvey of a Portion
of the Subdivision Lines
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS					
	<p>A pine, 14 ins. in diam., bears N. 27° W., 33 lks. dist., mkd. 1/4 S5 BT.</p> <p>A pine, 14 ins. in diam., bears S. 6$\frac{1}{4}$° E., 12 lks. dist., mkd. 1/4 S8 BT.</p> <hr/> <p>S. 89° 18' W., beginning new measurement.</p> <p>39.70 The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2$\frac{1}{2}$ ins. in diam., firmly set, projecting 4 ins. above the ground, as described in the official record of the remonumentation of a number of corners in this township, by Wallace R. Ott, executed in 1966, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R8E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>1966</p> </div> <p>substantiated by:</p> <p>A pine, 10 ins. in diam., bears N. 35° E., 25 lks. dist., (record: N. 34° E., 45 lks. dist.), mkd. T19N R8E S5 BT.</p> <p>A pine, 11 ins. in diam., bears S. 16$\frac{1}{2}$° E., 32 lks. dist., mkd. T19N R8E S8 BT.</p> <p>A mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, W. of the corner.</p>	S 6	S 5	S 7	S 8
S 6	S 5				
S 7	S 8				
	<p>N. 0° 31' W., between secs. 5 and 6.</p> <p>Over rolling land, through scattering timber.</p> <p>9.00 Trail road, bears NE-SW.</p> <p>40.13 The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 2$\frac{1}{2}$ ins. in diam., firmly set on bedrock, and in a mound of stone, as described in the official record of the remonumentation of a number of corners in this township, by Wallace R. Ott, executed in 1966, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R8E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1/4</td> </tr> </table> <p>1966</p> </div> <p>substantiated by:</p> <p>A pine, 16 ins. in diam., bears N. 67$\frac{1}{2}$° E., 40 lks. dist., mkd. 1/4 S5 BT.</p> <p>A pine, 13 ins. in diam., bears N. 86° W., 21 lks. dist., mkd. T19N R8E 1/4 S6 BT.</p> <hr/> <p>N. 0° 07' E., beginning new measurement.</p> <p>2.00 Road, bears S-SW. and N-NE.</p>	S 6	S 5		1/4
S 6	S 5				
	1/4				

The Survey of a Portion of the
Subdivision Lines in Sections 4 and 5
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.
20.06	<p>The point for the C-N $1/16$ sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R8E C N $1/16$ S 4 C 1968</p> <p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.</p> <p>No other suitable accessory available.</p>
35.11	<p>The point for the C-N-N-N $1/256$ sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N N N $1/256$ S 4 1968</p> <p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.</p>
39.97	Intersect the N. boundary of the township, the $1/4$ sec. cor. of secs. 4 and 33.
40.07	<p>From the $1/4$ sec. cor. of secs. 3 and 4,</p> <p>S. $89^{\circ} 55'$ W., on the E. and W. center line of sec. 4.</p> <p>The center $1/4$ sec. cor. of sec. 4.</p> <p style="text-align: center;">_____</p> <p>S. $89^{\circ} 43'$ W., beginning new measurement.</p>
20.08	<p>The point for the C-W $1/16$ sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R8E C W $1/16$ C S 5 1968</p> <p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the corner.</p> <p>No other suitable accessory available.</p>
40.16	<p>The $1/4$ sec. cor. of secs. 4 and 5.</p> <hr/> <p>Thence, in the NW $1/4$ of sec. 4.</p>

The Survey of a Portion of the
 Subdivision Lines in Sections 4 and 5
 Township 19 North, Range 8 East
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the C-W 1/16 sec. cor. of sec. 4.</p> <p>N. 0° 08' W., on the N. and S. center line of the NW 1/4 of sec. 4.</p>
5.01	<p>The point for the C-S-S-NW 1/256 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 16 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C S S NW 1/256 S 4 1968</p>
20.04	<p>Intersect the E. and W. center line of the NW 1/4 of sec. 4, the point for the NW 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R8E NW 1/16 S 4 1968</p> <p>raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p> <p>No other suitable accessory available.</p>
25.06	<p>The point for the C-S-N-NW 1/256 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C S N NW 1/256 S 4 1968</p>
30.08	<p>The point for the C-N-NW 1/64 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N NW 1/64 S 4 1968</p> <p>No other suitable accessory available.</p>
39.95	<p>Intersect the N. boundary of the township, the W 1/16 sec. cor. of secs. 4 and 33.</p>
20.00	<p>From the C-N 1/16 sec. cor. of sec. 4,</p> <p>S. 89° 43' W., on the E. and W. center line of the NW 1/4 of sec. 4.</p> <p>Intersect the N. and S. center line of the NW 1/4 of sec. 4, the NW 1/16 sec. cor. of sec. 4.</p>

The Survey of a Portion of the
Subdivision Lines in Sections 4 and 5
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
35.00	The point for the C-W-W-NW 1/256 sec. cor. of sec. 4. Did not monument.
40.00	The N 1/16 sec. cor. of secs. 4 and 5.
	<p>Thence, with a limited survey of a portion of the subdivision lines of the NW 1/4 in section 4 along a calculated line for the boundary between the Coconino National Forest and private lands, and other government lands.</p> <hr/> <p>From the C-N-N-N 1/256 sec. cor. of sec. 4, S. 89° 38' W., on the E. and W. N-N-N 1/256 line of sec. 4.</p>
9.97	<p>The calculated position, the point for the C-N-NE-NW 1/256 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N NE NW 1/256 S 4 1968</p>
5.02	<p>S. 0° 14' E., on the N. and S. E-W 1/64 line of sec. 4.</p> <p>The calculated position, the point for the NE-NW 1/64 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE NW 1/64 S 4 1968</p> <p>set a wooden post, 5 ft. long, 5 ins. in diam., N. of the corner.</p> <p>No suitable accessories available.</p>
9.98	<p>S. 89° 40' W., on the E. and W. N-N 1/64 line of sec. 4.</p> <p>Intersect the N. and S. center line of the NW 1/4, the C-N-NW 1/64 sec. cor. of sec. 4.</p>
14.99	<p>From the C-S-N-NW 1/256 sec. cor. of sec. 4, S. 89° 41' W., on the E. and W. S-N-N 1/256 line of sec. 4.</p> <p>The SW-NW-NW 1/256 sec. cor. of sec. 4, mkd. by an iron pipe, 1 in. in diam., projecting 3 ins. above the ground. Not of record, this corner has long been accepted as the position for the corner, and is accepted as the point for the corner.</p>

The Survey of a Portion of the
 Subdivision Lines in Sections 4 and 5
 Township 19 North, Range 8 East
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW NW NW 1/256 S 4 1968</p>	
	<p>deposit the iron pipe alongside the iron post, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/>	
5.02	<p>SOUTH, on the N. and S. W-W-W 1/256 line of sec. 4.</p> <p>Intersect the E. and W. center line of the NW 1/4, the C-W-W-NW 1/256 line of sec. 4.</p> <hr style="width: 20%; margin: 10px auto;"/>	
5.01	<p>SOUTH, continue on the N. and S. W-W-W 1/256 line of sec. 4.</p> <p>The calculated position, the point for the NW-SW-NW 1/256 sec. cor. of sec. 4.</p>	
	<p>Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW SW NW 1/256 S 4 1968</p> <hr style="width: 20%; margin: 10px auto;"/>	
5.02	<p>S. 89° 43' W., on the E. and W. N-S-N 1/256 line of sec. 4.</p> <p>The N-S-N 1/256 sec. cor. of secs. 4 and 5.</p>	
10.01	<p>From the C-N-S-N 1/256 sec. cor. of sec. 4,</p> <p>S. 89° 43' W., on the E. and W. N-S-N 1/256 line of sec. 4.</p> <p>The calculated position, the point for the C-N-SE-NW 1/256 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N SE NW 1/256 S 4 1968</p>	
5.02	<p>raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0° 14' E., on the N. and S. E-W 1/64 line of sec. 4.</p> <p>The calculated position, the point for the SE-NW 1/64 sec. cor. of sec. 4.</p>	

The Survey of a Portion of the
Subdivision Lines in Sections 4 and 5
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE NW 1/64 S 4 1968</p> <p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the corner.</p> <p>No other suitable accessory available.</p> <hr style="width: 20%; margin: auto;"/> <p>S. $89^{\circ} 43'$ W., on the E. and W. S-N 1/64 line of sec. 4.</p>
5.01	<p>The calculated position, the point for the C-W-SE-NW 1/256 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C W SE NW 1/256 S 4 1968</p> <p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the corner.</p> <hr style="width: 20%; margin: auto;"/> <p>S. $0^{\circ} 11'$ E., on the N. and S. W-E-W 1/256 line of sec. 4.</p>
5.01	<p>The calculated position, the point for the SW-SE-NW 1/256 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW SE NW 1/256 S 4 1968</p> <p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the corner.</p> <hr style="width: 20%; margin: auto;"/> <p>S. $89^{\circ} 43'$ W., on the E. and W. S-S-N 1/256 line of sec. 4.</p>
5.02	<p>Intersect the N. and S. center line of the NW 1/4, the C-S-S-NW 1/256 sec. cor. of sec. 4.</p>
20.09	<p>Thence, in sec. 5.</p> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. $0^{\circ} 14'$ W., on the N. and S. center line of sec. 5.</p> <p>The point for the C-S 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p>

The Survey of a Portion of the
 Subdivision Lines in Sections 4 and 5
 Township 19 North, Range 8 East
 Gila and Salt River Meridian, Arizona

CHAINS		
40.18	<p style="text-align: center;">T19N R8E C S 1/16 S 5 C 1968</p> <p>raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. in diam., bears S. 59½° E., 50 lks. dist., mkd. C S 1/16 S5 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears S. 46½° W., 34 lks. dist., mkd. C S 1/16 S5 BT.</p> <p>The center 1/4 sec. cor. of sec. 5, mkd. by a steel rod, 1 in. in diam., projecting 4 ins. above the ground, in a small mound of stone. Not of record, this corner has long been accepted as the position for the corner, and is accepted as the point for the corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
20.07	<p style="text-align: center;">T19N R8E C N 1/4 S 5 C 1968</p> <p>deposit the steel rod alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 18 ins. in diam., bears N. 47¼° E., 64 lks. dist., mkd. C 1/4 S5 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. in diam., bears S. 46° E., 65 lks. dist., mkd. C 1/4 S5 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 11' W., beginning new measurement.</p> <p>The point for the C-N 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
39.93	<p style="text-align: center;">T19N R8E C N 1/16 S 5 C 1968</p> <p>No suitable accessories available.</p> <p>Intersect the N. boundary of the township, the 1/4 sec. cor. of secs. 5 and 32.</p>	
	<p>From the 1/4 sec. cor. of secs. 4 and 5, S. 89° 38' W., on the E. and W. center line of sec. 5.</p>	

The Survey of a Portion of the
Subdivision Lines in Sections 4 and 5
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
19.94	<p>The point for the C-E 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R8E C—E 1/16—C S 5 1968</p> <p>from which</p> <p style="text-align: center;">A pine, 14 ins. in diam., bears S. 71½° W., 81 lks. dist., mkd. C E 1/16 S5 BT.</p> <p>This corner point is located in a N-S. fence line.</p>
39.88	<p>The center 1/4 sec. cor. of sec. 5.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 21' W., beginning new measurement.</p>
39.94	<p>The 1/4 sec. cor. of secs. 5 and 6.</p>
	<p>Thence, in the NE 1/4 of sec. 5.</p> <p>From the C-E 1/16 sec. cor. of secs. 5 and 8.</p> <p>N. 0° 05' W., on the N. and S. center line of the NE 1/4 of sec. 5.</p>
5.01	<p>The point for the C-S-S-NE 1/256 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S S NE 1/256 S 5 1968</p> <p>raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p>
20.05	<p>Intersect the E. and W. center line of the NE 1/4, the point for the NE 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R8E NE 1/16 S 5 1968</p> <p>from which</p> <p style="text-align: center;">A pine, 12 ins. in diam., bears S. 58½° E., 66 lks. dist., mkd. NE 1/16 S5 BT.</p>

The Survey of a Portion of the
 Subdivision Lines in Sections 4 and 5
 Township 19 North, Range 8 West
 Gila and Salt River Meridian, Arizona

CHAINS	
39.93	<p>A pine, 10 ins. in diam., bears S. $61\frac{1}{2}^{\circ}$ W., 89 lks. dist., mkd. NE $1/16$ S5 BT.</p> <p>Intersect the N. boundary of the township, the E $1/16$ sec. cor. of secs. 5 and 32.</p>
19.97	<p>From the N $1/16$ sec. cor. of secs. 4 and 5, S. $89^{\circ} 39'$ W., on the E. and W. center line of the NE $1/4$ of sec. 5.</p> <p>Intersect the N. and S. center line of the NE $1/4$, the NE $1/16$ sec. cor. of sec. 5.</p>
39.94	<p>Intersect the N. and S. center line, the C-N $1/16$ sec. cor. of sec. 5.</p>
14.97	<p>Thence, with a limited survey of a portion of the subdivision lines of the NE $1/4$, section 5, along a calculated line for the boundary between the Coconino National Forest and private lands, and other government lands.</p> <hr/> <p>From the N-S-N $1/256$ sec. cor. of secs. 4 and 5, S. $89^{\circ} 39'$ W., on the E. and W. N-S-N $1/256$ line of sec. 5.</p> <p>The NW-SE-NE $1/256$ sec. cor. of sec. 5, mkd. by a steel rod, 1 in. in diam., projecting 1 in. above the ground, and set in a mound of stone. Not of record, this corner has long been accepted as the position for the corner, and is accepted as the point for the corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW SE NE $1/256$ S 5 1968</p> <p>deposit the steel rod alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.</p> <hr/> <p>S. $0^{\circ} 03'$ E., on the N. and S. W-E-E $1/256$ line of sec. 5.</p>
10.03	<p>The SW-SE-NE $1/256$ sec. cor. of sec. 5, mkd. by a steel rod, 1 in. in diam., projecting 1 in. above the ground. Not of record, this corner has long been accepted as the position for the corner and is accepted as the point for the corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW SE NE $1/256$ S 5 1968</p>

The Survey of a Portion of the
Subdivision Lines in Sections 4 and 5
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>deposit the steel rod alongside the iron post, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.</p>
4.99	<p>S. $89^{\circ} 38'$ W., on the E. and W. S-S-N $1/256$ line of sec. 5.</p> <p>Intersect the N. and S. center line of the NE $1/4$, the C-S-S-NE $1/256$ sec. cor. of sec. 5.</p>
	<p>Thence, in the SE $1/4$ of sec. 5.</p> <p>From the E $1/16$ sec. cor. of secs. 5 and 8.</p> <p>N. $0^{\circ} 20'$ W., on the N. and S. center line of the SE $1/4$ of sec. 5.</p>
15.04	<p>The point for the C-N-S-SE $1/256$ sec. cor. of sec. 5. Did not monument.</p>
20.05	<p>Intersect the E. and W. center line of the SE $1/4$, the point for the SE $1/16$ sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T19N R8E SE $1/16$ S 5 1968</p>
	<p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.</p> <p>No other suitable accessory available.</p>
25.07	<p>The point for the C-S-N-SE $1/256$ sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">C S N SE $1/256$ S 5 1968</p>
40.13	<p>Intersect the E. and W. center line, the C-E $1/16$ sec. cor. of sec. 5.</p>
	<p>From the S $1/16$ sec. cor. of secs. 4 and 5,</p> <p>S. $89^{\circ} 35'$ W., on the E. and W. center line of the SE $1/4$ of sec. 5.</p>
9.99	<p>The point for the C-E-SE $1/64$ sec. cor. of sec. 5. Did not monument.</p>
19.98	<p>Intersect the N. and S. center line of the SE $1/4$, the SE $1/16$ sec. cor. of sec. 5.</p>
24.98	<p>The point for the C-E-W-SE $1/256$ sec. cor. of sec. 5. Did not monument.</p>

The Survey of a Portion of the
Subdivision Lines in Sections 4 and 5
Township 19 North, Range 8 West
Gila and Salt River Meridian, Arizona

CHAINS	
39.96	Intersect the N. and S. center line, the C-S 1/16 sec. cor. of sec. 5.
4.99	<p>Thence, with a limited survey of a portion of the subdivision lines of the SE 1/4, section 5, along a calculated line for the boundary between the Coconino National Forest and private lands, and other government lands.</p> <hr/> <p>From the N-S 1/64 sec. cor. of secs. 4 and 5, S. 89° 36' W., on the E. and W. N-S 1/64 line of sec. 5.</p> <p>The calculated position, the point for the C-E-NE-SE 1/256 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C E NE SE 1/256 S 5 1968</p> <p>raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the corner.</p> <p>From this corner point a local corner, mkd. by a steel pin, ½ in. in diam., projecting 6 ins. above the ground, set in a small mound of stone, bears WEST, 7 lks. dist.</p> <hr/> <p>S. 0° 23' E., on the N. and S. E-E-E 1/256 line of sec. 5.</p>
5.01	<p>The calculated position, the point for the SE-NE-SE 1/256 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE NE SE 1/256 S 5 1968</p> <p>From this corner point a local corner, mkd. by a steel pin, 1 in. in diam., projecting 2 ins. above the ground, bears S. 82° 26' W., 13 lks. dist.</p> <hr/> <p>S. 89° 35' W., on the E. and W. S-N-S 1/256 line of sec. 5.</p>
4.99	<p>The calculated position, the point for the C-S-NE-SE 1/256 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S NE SE 1/256 S 5 1968</p>

The Survey of a Portion of the
Subdivision Lines in Sections 4 and 5
Township 19 North, Range 8 East
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.</p> <p>From this corner point a local corner, mkd. by a steel pin, 1 in. in diam., projecting 3 ins. above the ground, bears S. $85^{\circ} 42' W.$, 12 lks. dist.</p> <hr/> <p>S. $0^{\circ} 22' E.$, on the N. and S. E-E $1/64$ line of sec. 5.</p>
5.01	<p>Intersect the E. and W. center line of the SE $1/4$, the C-E-SE $1/64$ sec. cor. of sec. 5.</p> <hr/> <p>S. $0^{\circ} 22' E.$, continue on the N. and S. E-E $1/64$ line of sec. 5.</p>
5.01	<p>The calculated position, the point for the C-N-SE-SE $1/256$ sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N SE SE 1/256 S 5 1968</p> <p>From this corner point a local corner, mkd. by a steel pin, 1 in. in diam., projecting 3 ins. above the ground, bears S. $87^{\circ} 52' W.$, 19 lks. dist.</p> <hr/> <p>S. $89^{\circ} 34' W.$, on the E. and W. N-S-S $1/256$ line of sec. 5.</p>
9.99	<p>Intersect the N. and S. center line of the SE $1/4$, the C-N-S-SE $1/256$ sec. cor. of sec. 5.</p> <hr/> <p>S. $89^{\circ} 34' W.$, continue on the E. and W. N-S-S $1/256$ line of sec. 5.</p>
4.99	<p>The calculated position, the point for the NE-SW-SE $1/256$ sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">NE SW SE 1/256 S 5 1968</p> <p>From this corner point a local corner, mkd. by a steel pin, 1 in. in diam., projecting 3 ins. above the ground, bears WEST, 13 lks. dist.</p> <hr/> <p>N. $0^{\circ} 19' W.$, on the N. and S. E-W-E $1/256$ line of sec. 5.</p>
5.01	<p>Intersect the E. and W. center line of the SE $1/4$, the C-E-W-SE $1/256$ sec. cor. of sec. 5.</p> <hr/>

The Survey of a Portion of the
 Subdivision Lines in Sections 4 and 5
 Township 19 North, Range 8 East
 Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>N. 0° 19' W., continue on the N. and S. E-W-E 1/256 line of sec. 5.</p> <p>5.02 The calculated position, the point for the SE-NW-SE 1/256 sec. cor. of sec. 5.</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SE NW SE 1/256 S 5 1968</p> <p>From this corner point a local corner, mkd. by a steel pin, 1 in. in diam., projecting 3 ins. above the ground, bears N. 86° 06' W., 7 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 35' E., on the E. and W. S-N-S 1/256 line of sec. 5.</p> <p>4.99 Intersect the N. and S. center line of the SE 1/4, the C-S-N-SE 1/256 sec. cor. of sec. 5.</p>
	<p>General Description</p> <p>The lands encompassed in this dependent resurvey and survey are situated in the Coconino National Forest, elevation from 6930 ft. Elk Meadows valley floor (N. bdy sec. 4) to 7120 ft. (S. bdy sec. 5). There is a northeastern exposure with drainage into Upper Lake Mary (now a reservoir) of approximately 1¼ miles distance. The Elk Meadows valley land is nearly level and the remaining area of sections 4 and 5 is rolling; soil is volcanic ash; timber is pine and oak; undergrowth consists of young trees, brush, and grass.</p>

24

BOOK 4875

CERTIFICATE OF SURVEY

I, Marlin G. Livermore, II, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of February, 1967, I have dependently resurveyed a portion of the north boundary and a portion of the subdivision lines and surveyed a portion of the subdivision lines in sections 4 and 5, Township 19 North, Range 8 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

02-02-70
(Date)

Marlin G. Livermore II
(Cadastral Surveyor)
Marlin G. Livermore, II

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAR 2 1970

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the north boundary and a portion of the subdivision lines and the survey of a portion of the subdivision lines in sections 4 and 5, Township 19 North, Range 8 East, Gila and Salt River Meridian, Arizona

executed by Marlin G. Livermore, II
having been critically examined and found correct, are hereby approved.

NOV 27 1970
(Date)

Clark I. Sumner
(Chief, Division of Engineering)

Chief, Division of Cadastral Survey
CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C. 20240

IN REPLY REFER TO:

9182
9186 (420)
Group 489
Arizona

March 18, 1974

Memorandum

To: State Director, Arizona
From: Director
Subject: Cancellation of plat T. 19 N., R. 8 E., Gila and Salt River Meridian, Arizona.

The plat showing the dependent resurvey of portions of the north boundary and subdivisional lines with the survey of portions of the subdivisional lines of sections 4 and 5, Township 19 North, Range 8 East, Gila and Salt River Meridian, Arizona, accepted November 27, 1970 and suspended on January 4, 1974, is hereby cancelled effective this date.

This action is taken at the request of the Chief, Division of Cadastral Survey, Arizona.

This plat is cancelled because of certain errors in bearings shown on the plat accepted November 27, 1970 and is superseded by the plat accepted March 18, 1974.

For the Director

Clark L. Gumm
Chief, Division of Cadastral Survey

ARIZONA STATE OFFICE	
BUREAU OF LAND MANAGEMENT	
MAY 1 74	
CD	_____
ASSOC. SD	_____
PCS	_____
RESOURCES	_____
TECH SER	_____
MGMT SER	_____
PJB AFF	_____
CF	_____
ACTION	_____
INFO	_____
OTHER	_____

TECHNICAL SERVICES

1 Chief *CG*

Appraisals _____

2 Cadastral *BLo*

Engineering _____

Lands _____

Minerals _____

Protection _____

Central files _____

Division files _____

Save Energy and You Serve America.

18



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C. 20240

IN REPLY REFER TO:
9182 (420)
Op. No. 489,
Arizona

January 4, 1974

Memorandum

To: Director, DSC

From: Director

Subject: Plat suspension, T. 19 N., R. 8 E., Gila and Salt River
Meridian, Arizona

ARIZONA STATE OFFICE BU. LAND MANAGEMENT	
JAN 9 '74	
SD	_____
ASSOC. SD	_____
PCS	_____
RESOURCES	_____
TECH SER	_____
MGMT SER	_____
PUB. AFF	_____
CF	_____
_____	ACTION
_____	INFO.
_____	SEE ME

It has been noted that the plat showing survey of subdivisional lines within secs. 4 and 5 of T. 19 N., R. 8 E., Gila and Salt River Meridian, accepted November 27, 1970, is not in total agreement with the field notes which have been checked and found to be correct. The bearing of the EE-1/64 line in the SE-1/4 of sec. 5 should be S. 0° 22' E.

In order to correct this situation, the above-referenced plat is suspended this date to be superseded by a new plat drafted by your office which portrays the correct situation. A note should be added to the plat memorandum which explains the purpose of the new plat.

For the Director

(Sgd.) Clark L. Gumm

Clark L. Gumm
Chief, Division of Cadastral Survey

SD-ARIZONA ✓

1C