

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

East, South and West Boundaries

and the

Subdivisional Lines

Township 7 South, Range 23 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Kenneth D. Herman, Cadastral Surveyor

Gary T. Oviatt, Cadastral Surveyor

Under special instructions dated January 30, 19 67, which provided for the surveys
included under Group Number 451, approved January 30, 1967,
and assignment instructions dated January 30, 19 67.

Survey commenced March 16, 19 67

Survey completed May 10, 19 67

1A

BOOK 4877

INDEX DIAGRAM

Township 7 South, Range 23 East

16 6 58	59 5 58	47 4 47	39 3 39	31 2 31	24 1 6 24
15 7 56	57 8 55	46 9 45	38 10 38	30 11 30	23 12 5 22
15 18 54	54 17 53	44 16 44	37 15 36	29 14 28	21 13 4 21
14 19 52	52 20 51	43 21 42	35 22 35	27 23 27	20 24 3 19
13 30 50	50 29 49	42 28 41	34 27 33	26 26 25	19 25 2 18
12 31 11	48 32 10	40 33 9	32 34 9	25 35 8	17 36 1 7

1 B

Township 7 South, Range 23 East
Gila and Salt River Meridian, Arizona

CHAINS

The boundaries and subdivisional lines were surveyed in 1884 by L. Wolfley. The west 5 miles of the south boundary and the south 2 miles of the west boundary were retraced in 1933 by C. E. Hunter. The SW.Tp. cor. and the cor. of secs. 19, 24, 25 and 30 on the west boundary of the Tp. were remonumented with iron posts in 1933 by C. E. Hunter. The following cors. were remonumented with iron posts, by L. Mann in 1960 under the Forest Service Remonumentation Program: Cor. of sec. 23, 24, 25 and 26; cor. of secs. 14, 15, 22 and 23; cor. of secs. 15, 16, 21 and 22 and the $\frac{1}{4}$ sec. cor. of secs. 17 and 18. The north boundary was resurveyed concurrently under this same group, by Herman and Oviatt, as described in the field notes of Township 6 South, Range 23 East.

The following notes are those of a dependent resurvey of the east, south and west boundaries and the subdivisional lines of Township 7 South, Range 23 East, Gila and Salt River Meridian, Arizona, designed to restore the corners in their true original location according to the best available evidence.

This survey was executed in accordance with the specification as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated January 30, 1967.

Only the true line bearings and horizontal distances for the surveyed line are given in these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude $32^{\circ}46'27''$ North, and Longitude $109^{\circ}56'11''$ West. This position was calculated from a direct tie to U. S. Soil Erosion Service Triangulation Station BEAR located in section 11, Township 7 south, Range 23 East.

The mean magnetic declination was found to be:
 $13^{\circ}30'$ East.

Dependent Resurvey of the East Boundary
T. 7S., R. 23 E., G&SR M., Arizona

Reestablishment of the Survey Executed
by L. Wolfley in 1884

From the cor. of Tps. 7 and 8 S., Rs. 23 and 24 E., monumented by a mound of stone. This is accepted as the best remaining evidence of the position of the orig. cor.

At the corner point

Set the iron post 3 ins. in the ground, mound of stone to top, brass cap mkd.

T7S
R23E R24E
S36 | S31
S1 | S6
T8S
1967

Dep. Resurvey, E. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>N. 0°02' E., bet. secs. 31 and 36.</p> <p>Over mountainous land, through moderate undergrowth; desc. along E. slope.</p> <p>10.90 Ravine, drains E.</p> <p>21.50 Ravine, drains E.</p> <p>39.53 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E $\frac{1}{4}$ S36 S31 1967</p> <p>41.70 Fence, bears S. 56° E. and N. 56° W.</p> <p>67.70 Fence, bears E. and W. for 3.00 chs. thence N.</p> <p>79.06 The cor. of secs. 25, 30, 31 and 36, monumented by a granite stone, 4 x 2 x 1 ft. above the ground, mkd. with 5 notches on N. face, 1 notch on S. face and an "X" on top, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E S25 S30 S36 S31 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered mesquite, juniper and oak. Undergrowth, manzanita, cat claw and bunch grass.</p>
	<p>N. 0°06' W., bet. secs. 25 and 30.</p> <p>Over mountainous land, through moderate undergrowth; desc. NW. slope.</p> <p>23.80 Wash at bottom of hill, drains NE., thence across rolling foothills.</p> <p>30.20 Same wash, 40 lks. wide, 3 ft. deep, drains NW.</p> <p>35.50 Same wash, drains NE.; asc. SE. slope.</p> <p>39.36 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by a granite stone, 14 x 8 x 8 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the corner point</p>

Dep. Resurvey, E. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS		
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E $\frac{1}{4}$ S25 S30 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' W., beginning new measurement.</p> <p>Over rolling land through moderate undergrowth.</p>	
36.80	<p>Top of spur, slopes NE., desc. NW. slope.</p>	
39.76	<p>The cor. of secs. 19, 24, 25 and 30, monumented by a granite stone, 14 x 10 x 3 ins., set 6 ins. in the ground, mkd. 4 notches on N. face and 2 notches on S. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E <u>S24 S19</u> S25 S30 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous to rolling. Soil, rocky. Timber, scattered mesquite. Undergrowth, cat claw, cacti and bunch grass.</p>	
40.16	<p>N. 0°02' E., bet. secs. 19 and 24.</p> <p>Over rolling land, through moderate undergrowth; desc. NW. slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented by a granite stone, 20 x 6 x 6 ins., lying loose on the ground, mkd. $\frac{1}{4}$ on a face.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E $\frac{1}{4}$ S24 S19 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' W., beginning new measurement.</p>	

Dep. Resurvey, E. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS	<p>Over rolling land, through moderate undergrowth.</p> <p>3.00 Enter wash draining N.</p> <p>8.30 Leave wash, drains NW.</p> <p>10.10 Enter Sand Wash, drains NE.</p> <p>14.50 Leave Sand Wash.</p> <p>19.79 Point for the N 1/16 sec. cor. of secs. 19 and 24.</p> <p style="padding-left: 40px;">Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T7S R23E R24E N 1/16 S24 S19 1967</p> </div> <p>Set a mesquite post, 4 ins. diam., 4 ft. long, alongside the iron post.</p> <p>39.58 Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p style="padding-left: 40px;">Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T7S R23E R24E S13 S18 S24 S19 1967</p> </div> <p>Set a mesquite post, 4 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Land, rolling. Soil, rocky. Timber, scattered mesquite. Undergrowth, moderate creosote, cacti and cat claw.</p>
	<p>N. 0°07' W., bet. secs. 13 and 18.</p> <p>Over rolling land through moderate undergrowth.</p> <p>1.20 Track road, bears NE. and SW.</p> <p>39.57 Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist. This cor. is not monumented.</p> <p>39.80 Track road, bears E. and W.</p> <p>68.30 Track road, bears E. and W.</p> <p>75.60 Track road, bears E. and W.</p> <p>78.04 Fence, bears E. and W. for 43 lks., thence SW.</p> <p>79.14 The cor. of secs. 7, 12, 13 and 18, monumented by a granite stone, 14 x 10 x 3 ins., set 6 ins. in the ground, mkd. 4 notches on S. face and 2 notches on N. face, mound of stone W.</p> <p>At the corner point</p>

Dep. Resurvey, E. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E S12 S7 S13 S18 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cat claw and cacti.</p>
	<p>N. 0°11' W., bet. secs. 7 and 12.</p> <p>Over gently rolling land through moderate undergrowth.</p> <p>8.90 Wash, 30 lks. wide, 3 ft. deep, drains NE.</p> <p>21.60 Track road, bears E. and W.</p> <p>28.50 Cottonwood Creek, drains E.</p> <p>30.10 Base of mesa, asc. over S. slope.</p> <p>33.40 Rim, bears E. and W.; asc. across gentle S. slope.</p> <p>37.40 Top of mesa, desc. N. slope.</p> <p>39.72 The ¼ sec. cor. of secs. 7 and 12, monumented by a granite stone, 16 x 16 x 6 ins., set 8 ins. in the ground, mkd. ¼ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E ¼ S12 S7 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' W., beginning new measurement.</p> <p>Over rolling land through moderate undergrowth.</p> <p>1.80 Wash, 20 lks. wide, 1 ft. deep, drains E.</p> <p>18.00 Mesa Road, bears E. and W.</p> <p>39.77 The cor. of secs. 1, 6, 7 and 12, monumented by a granite stone, 14 x 6 x 5 ins., set 6 ins. in the ground, mkd. 5 notches on S. face and 1 notch on N. face, mound of stone alongside.</p>

Dep. Resurvey, E. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E S1 S6 S12 S7 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, gravelly loam. No timber, undergrowth, creosote, cat claw and cacti.</p>
	<p>N. 0°04' W., bet. secs. 1 and 6.</p> <p>Over gently rolling land through moderate undergrowth.</p> <p>7.30 Draw, drains NE.</p> <p>9.70 Spur, slopes NE.</p> <p>17.60 Small spur, slopes N. 25° E.</p> <p>19.79 Point for the S 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E S 1/16 S1 S6 1967</p> <p>22.70 Fence, bears E. and W.</p> <p>39.58 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist.; unable to find any evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E R24E ¼ S1 S6 1967</p> <p>from which</p> <p>A N. and S. fence line, bears West, 10 lks. dist.</p> <p>A spring, bears S. 34°34' W., 12.10 chs. dist.</p>

Dep. Resurvey, S. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS	
40.50	Track road, bears E. and W.
73.00	Fence, bears N. 25° E. and S. 25° W.
79.16	The cor. of Tps. 6 and 7 S., Rs. 23 and 24 E., monumented by an iron post 3 ins. diam., projecting 6 ins. above the ground in a collar of stone, brass cap mkd.
<p>T6S R23E R24E S36 S31 S1 S6 T7S 1916</p>	
<p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cat claw and cacti.</p>	
<p>Dependent Resurvey of the South Boundary T. 7 S., R. 23 E., G&SR M., Arizona</p>	
<p>Reestablishment of the Survey Executed by L. Wolfley in 1884</p>	
<p>From the cor. of Tps. 7 and 8 S., Rs. 23 and 24 E. S. 89°57' W., bet. secs. 1 and 36. Asc. over mountainous land through moderate undergrowth.</p>	
5.80	Spur, slopes SE.
22.30	Ridge bears N. and S.; desc. steep W. slope.
33.20	Spur, slopes N. 20° W.
39.87	Point for the ¼ sec. cor. of secs. 1 and 36 at proportionate dist.; unable to find any remaining evidence of the orig. cor. The point falls on steep rock face where the cor. cannot be perpetuated.
39.97	<p>Point selected for the witness ¼ sec. cor. of secs. 1 and 36. Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p>
<p>T7S R23E ¼ W S36 → C S1 T8S 1967</p>	
44.50	Spur, slopes NW.
69.50	Wash, 20 lks. wide, 3 ft. deep, drains NW.
75.84	Road, bears S. 20° E. and N. 30° W. (Jeep road)
79.73	<p>The cor. of secs. 1, 2, 35 and 36, monumented by a granite stone, 50 x 27 x 27 ins. above ground, mkd. with 5 notches on W. and 1 notch on E. face and an X on top. From which the orig. bearing trees:</p>

Dep. Resurvey, S. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS					
	<p>An oak tree, 12 ins. diam., bears N. 3°30' E., 154 lks. dist., mkd. with healed blaze.</p> <p>A juniper, 12 ins. diam., bears N. 84°15' W., 108 lks. dist., mkd. T7S R23E S35 BT.</p> <p>At the corner point</p> <p>Set the iron post over the X on orig. cor., mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S2</td> <td style="padding: 0 5px;">S1</td> </tr> </table> <p>T8S 1967</p> </div> <p>Land, mountainous. Soil, rocky. Timber, moderate juniper, pine and oak. Undergrowth, moderate manzanita, oak brush, cacti and grass.</p>	S35	S36	S2	S1
S35	S36				
S2	S1				
	<p>N. 89°48' W., bet. secs 2 and 35.</p> <p>Over mountainous land through moderate undergrowth.</p>				
3.40	Creek in bottom of Nuttall Canyon, course NW.				
21.40	Spur, slopes N.				
31.40	Ravine, drains N. 10° W., asc. steep E. slope.				
39.77	<p>Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S35</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S2</td> <td></td> </tr> </table> <p>T8S 1967</p> </div>	¼ S35		S2	
¼ S35					
S2					
51.10	Spur, slopes N. 25° W., desc. NW. slope.				
71.10	Spur, slopes NW.				
79.53	<p>The cor. of secs. 2, 3, 34 and 35, monumented by a granite stone, 20 x 8 x 6 ins., set in a mound of stone, no visible mks.; this was accepted as best remaining evidence of the cor. position.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S34</td> <td style="padding: 0 5px;">S35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S3</td> <td style="padding: 0 5px;">S2</td> </tr> </table> <p>T8S 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p>	S34	S35	S3	S2
S34	S35				
S3	S2				

Dep. Resurvey, S. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS	<p>Land, mountainous. Soil, rocky. Timber, moderate juniper, pine and oak. Undergrowth, moderate manzanita, oak brush and cacti.</p>
	<p>S. 89°51' W., bet. secs. 3 and 34.</p> <p>Over mountainous land through moderate undergrowth.</p> <p>31.00 Wash in bottom of Carter Canyon, 25 lks. wide, 2 ft. deep, drains N. 10° E.</p> <p>32.50 Jeep road, bears S. 35° E. and N. 35° W.</p> <p>39.60 The ¼ sec. cor. of secs. 3 and 34, monumented by a rock-in-place 4 ft. above the ground, mkd. with an X on top, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E ¼ <u>S34</u> S3</p> <p>T8S 1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 89°52' W., beginning new measurement.</p> <p>Over mountainous land through moderate undergrowth.</p> <p>36.20 Top of spur, slopes N. 30° W., from S.; desc. steep W. slope.</p> <p>39.93 The cor. of secs. 3, 4, 33 and 34, monumented by a rock-in-place 6 ft. above the ground, mkd. with 3 notches on E. and W. faces and an X on top, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post over the X on the orig. cor., mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E <u>S33</u> <u>S34</u> S4 S3</p> <p>T8S 1967</p> </div>
	<p>Land, mountainous. Soil, rocky. Timber, moderate juniper, pine and oak. Undergrowth, manzanita, oak brush, cacti and grass.</p> <p>S. 89°31' W., bet. secs. 4 and 33.</p> <p>Over mountainous land through moderate undergrowth; desc. steep W. slope.</p>

Dep. Resurvey, S. Bdy., T. 7 S., R. 23 E., Arizona

<p>CHAINS 28.00</p>	<p>Spur, slopes NW.</p>
<p>33.00</p>	<p>Creek in bottom of North Taylor Canyon, course N. 20° E., asc. E. slope.</p>
<p>37.80</p>	<p>Dirt road, bears N. 20° E. and S. 20° W.</p>
<p>39.35</p>	<p>Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ <u>S33</u> S4</p> <p style="text-align: center;">T8S 1967</p>
<p>42.10</p>	<p>Ridge, bears NE. and SW.</p>
<p>60.30</p>	<p>Rocky knoll, bears N. and S.; desc. W. slope.</p>
<p>67.90</p>	<p>Ravine, drains North, asc. steep, E. slope.</p>
<p>71.90</p>	<p>Wash, 40 lks. wide, 1 ft. deep, drains NE.</p>
<p>78.69</p>	<p>The cor. of secs. 4, 5, 32 and 33, monumented by a granite stone in place, 2 x 2 ft. above the ground, mkd. with 2 notches on W. face with a faint X on top, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post over the X on orig. cor., mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E <u>S32 S33</u> S5 S4</p> <p style="text-align: center;">T8S 1967</p> <p>Land, mountainous. Soil, rocky. Timber, moderate juniper, pine and oak. Undergrowth, manzanita, oak brush and cacti.</p>
<p>38.00</p>	<p>N. 89°51' W., bet. secs. 5 and 32.</p> <p>Over mountainous land through moderate undergrowth.</p> <p>Enter dense undergrowth.</p>
<p>39.55</p>	<p>Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ <u>S32</u> S5</p> <p style="text-align: center;">T8S 1967</p>

Dep. Resurvey, S. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS											
43.30	Top of ridge, bears N. and S.; by triangulation, topography estimated, desc. steep W. slope.										
64.00	Creek in bottom of Little Righthand Canyon, course N. 20° E., asc. steep E. slope.										
79.10	The cor. of secs. 5, 6, 31 and 32, monumented by a granite stone, 14 x 8 x 5 ins., set 6 ins. in the ground, mkd. with 5 notches on E. face, mound of stone alongside. End of triangulation.										
	At the corner point										
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T7S</td> <td>R23E</td> </tr> <tr> <td><u>S31</u></td> <td><u>S32</u></td> </tr> <tr> <td>S6</td> <td>S5</td> </tr> <tr> <td colspan="2" style="text-align: center;">T8S</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table>	T7S	R23E	<u>S31</u>	<u>S32</u>	S6	S5	T8S		1967	
T7S	R23E										
<u>S31</u>	<u>S32</u>										
S6	S5										
T8S											
1967											
	Deposit the orig. cor. stone alongside the iron post.										
	Land, mountainous.										
	Soil, rocky.										
	Timber, moderate juniper, pine and oak.										
	Undergrowth, dense manzanita and oak brush, moderate cacti.										
	S. 85°23' W., bet. secs. 6 and 31.										
	Over mountainous land through moderate undergrowth.										
15.30	Spur, slopes NE.										
38.50	Rim, bears SE. and NW.; desc. W. slope.										
44.25	Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate dist.; unable to find any remaining evidence of the orig. cor.										
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T7S</td> <td>R23E</td> </tr> <tr> <td>¼</td> <td><u>S31</u></td> </tr> <tr> <td></td> <td>S6</td> </tr> <tr> <td colspan="2" style="text-align: center;">T8S</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table>	T7S	R23E	¼	<u>S31</u>		S6	T8S		1967	
T7S	R23E										
¼	<u>S31</u>										
	S6										
T8S											
1967											
	from which										
	A ponderosa pine, 26 ins. diam., bears N. 8°00' E., 42 lks. dist., mkd. T7SR23E ¼ S31 BT.										
	A ponderosa pine 12 ins. diam., bears S. 5°00' E., 42 lks. dist., mkd. T8SR23E ¼ S6 BT.										
50.00	Head of canyon, drains NE., asc. NE. slope.										
52.00	Draw, drains NE. into canyon.										
58.10	Spur, slopes NE.										
69.60	Spur, slopes NE., desc. steep W. slope.										

Dep. Resurvey, W. Bdy.; T. 7 S., R. 23 E., Arizona

CHAINS													
84.00	Draw drains NW. into Tripp Canyon.												
87.02	<p>The SW. cor. of Tp. 7 S., R. 23 E., only, monumented by an iron post 3 ins., in diam., set, mkd. and witnessed as described in the official record of the resurvey in 1933 by C. E. Hunter. From which the original bearing trees:</p> <p style="padding-left: 40px;">A pine tree, 14 ins. diam., bears N. 82°00' E., 9 lks. dist., mkd. with a healed over blaze.</p> <p style="padding-left: 40px;">A pine tree, 10 ins. diam., bears N. 11°00' E., 28 lks. dist., mkd. with a healed over blaze.</p> <p>Land, mountainous. Soil, rocky. Timber, moderate juniper, pine and oak. Undergrowth, oak brush, cacti and grass.</p>												
<p>Dependent Resurvey of the West Boundary T. 7 S., R. 23 E., G&SR M., Arizona</p>													
<p>Reestablishment of the Survey Executed by L. Wolfley in 1884 and Retraced by C. E. Hunter in 1933</p>													
	<p>From the SW. cor. of Tp. 7 S., R. 23 E., only.</p> <p>N. 1°47' E., along the W. bdy. sec. 31.</p> <p>Over mountainous land, through moderate undergrowth, desc. along NW. slope.</p>												
4.20	Ravine, drains NW., asc. SW. slope.												
7.72	<p>True point for the cor. of Tps. 7 and 8 S., Rs. 22 and 23 E., from which the witness township corner, bears West, 50 lks. dist., monumented by an iron post 3 ins. diam., set 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T7S</td> <td style="border-left: 1px solid black; padding: 2px;">T7S</td> </tr> <tr> <td style="padding: 2px;">R22E</td> <td style="border-left: 1px solid black; padding: 2px;">R23E</td> </tr> <tr> <td style="padding: 2px;"><u>S36</u></td> <td style="border-left: 1px solid black; padding: 2px;">S31</td> </tr> <tr> <td style="padding: 2px;">S6</td> <td style="border-left: 1px solid black; padding: 2px;">WC</td> </tr> <tr> <td style="padding: 2px;">T8S</td> <td style="border-left: 1px solid black; padding: 2px;">WC</td> </tr> <tr> <td style="padding: 2px;">R23E</td> <td style="border-left: 1px solid black; padding: 2px;">1933</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A cross chiseled on a rock ledge, bears N. 28°30' W., 30 lks. dist., followed by mks. BO WC T7SR22E S36.</p>	T7S	T7S	R22E	R23E	<u>S36</u>	S31	S6	WC	T8S	WC	R23E	1933
T7S	T7S												
R22E	R23E												
<u>S36</u>	S31												
S6	WC												
T8S	WC												
R23E	1933												
	<p>N. 1°25' E., beginning new measurement.</p> <p>Over mountainous land, through moderate undergrowth.</p>												
.20	Small ravine, drains W.												
24.50	Spur, slopes W., desc. along W. face of mountain.												
30.30	Ravine, drains N. 70° W.												

Dep. Resurvey, W. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS

31.44

The 1/4 sec. cor. of sec. 31, monumented by a granite stone, 18 x 10 x 8 ins., set 6 ins. in the ground, no legible mks., with a mound of stone alongside. Accepted as the best remaining evidence of the orig. cor. position.

At the corner point

Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.

T7S
R22E | R23E
 | 1/4
 | S31
 |
1967

Deposit the orig. cor. stone alongside the iron post.

N. 1°47' E., beginning new measurement.

Over mountainous land, along W. face of mountain.

13.50

Spur, slopes W.

35.00

Spur, slopes N. 60° W.

40.37

Point for the cor. of secs. 30 and 31, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7S
R22E | R23E
S36 | S30
 | S31
 |
1967

Land, mountainous.

Soil, rocky.

Timber, moderate pine, juniper and oak.

Undergrowth, buck brush, cacti and oak brush.

N. 1°47' E., along the W. bdy. of sec. 30.

Over mountainous land, through moderate undergrowth, desc. W. face of mountain.

36.70

Low ridge, bears S. 60° E. and N. 60° W.

40.37

Point for the 1/4 sec. cor. of sec. 30, at proportionate dist.; unable to find any evidence of the orig. cor.

Set the iron post 6 ins. in the ground, over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.

T7S
R22E | R23E
 | 1/4
 | S30
 |
1967

Dep. Resurvey, W. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS											
41.00	Desc. steep N. slope.										
80.73	The cor. of secs. 19, 24, 25 and 30, monumented by an iron post 2 ins. in diam., set 18 ins. in the ground, mound of stone to top, brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T7S</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td><u>S24</u></td><td><u>S19</u></td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1933</td></tr> </table>	T7S		R22E	R23E	<u>S24</u>	<u>S19</u>	S25	S30	1933	
T7S											
R22E	R23E										
<u>S24</u>	<u>S19</u>										
S25	S30										
1933											
	Cor. is located on a N. slope.										
	Land, mountainous. Soil, rocky. Timber, moderate to scattered pine and juniper. Undergrowth, manzanita, oak buah and cacti.										
<p>Reestablishment of the Survey Executed by L. Wolfley in 1884</p> <hr/>											
	N. 0°13' W., bet. secs. 19 and 24.										
	Over rolling land, through moderate undergrowth.										
6.80	Wash, 25 lks. wide, 2 ft. deep, drains NE.										
18.00	Spur, slopes N. 75° E.										
34.90	Spur, slopes SW. to saddle bet. two knolls.										
39.99	Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate dist.; unable to find any evidence of the original corner.										
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T7S</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">¼</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1967</td></tr> </table>	T7S		R22E	R23E	¼		S24	S19	1967	
T7S											
R22E	R23E										
¼											
S24	S19										
1967											
	Cor. falls on a NW. slope.										
44.60	Wash, 20 lks. wide, 2 ft. deep, drains NE.										
72.20	Long spur, slopes NE.										
79.98	Point for cor. of secs. 13, 18, 19 and 24, at proportionate dist.; unable to find any evidence of the orig. cor.										
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T7S</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td><u>S13</u></td><td><u>S18</u></td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1967</td></tr> </table>	T7S		R22E	R23E	<u>S13</u>	<u>S18</u>	S24	S19	1967	
T7S											
R22E	R23E										
<u>S13</u>	<u>S18</u>										
S24	S19										
1967											
	Land, rolling. Soil, rocky. Timber, scattered juniper. Undergrowth, cat claw, cacti and grass.										

Dep. Resurvey, W. Bdy., T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>N. 0°13' W., bet. secs. 13 and 18.</p> <p>Over rolling land through moderate undergrowth.</p>
.24	Fence, bears E. and W.
3.30	Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E.
10.10	Mesa Road, bears NE. and SW.
26.00	Bear Springs Wash, 15 lks. wide, 2 ft. deep, drains NE.
39.99	<p>The ¼ sec. cor. of secs. 13 and 18, monumented by a mound of stone, accepted as best remaining evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R22E R23E ¼ S13 S18 1967</p> <p>Cor. is located in a N-S fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth, along fence bearing irregularly N. and S.</p>
39.03	<p>The cor. of secs. 7, 12, 13 and 18, monumented by a granite stone, 15 x 12 x 5 ins., set 6 ins. in the ground, no legible mks.; this is accepted as best remaining evidence of the original corner position.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R22E R23E S12 S7 S13 S18 1967</p> <p>from which</p> <p style="text-align: center;">Corner of fences bearing irregularly N., S. and E., bears S. 40° E., 69 lks. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, cat claw, cacti and grass.</p>
	<p>N. 0°06' E., bet. secs. 7 and 12.</p> <p>Over rolling land through moderate undergrowth.</p>

Dep. Resurvey, W. Bdy., T. 7 S., R. 23 E.

CHAINS		
15.40	Ridge, bears N. 30° E. and S. 15° W., desc. along NW. slope.	
39.64	Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist.; unable to find any remaining evidence of the original corner. The cor. point falls in wash in unsafe location.	
40.64	<p>Point selected for the witness ¼ sec. cor. of secs. 7 and 12.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R22E R23E ¼ W C S12 S7 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing irregularly N. and S., bears E., 50 lks. dist.</p>	
42.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 15° E.	
52.60	Spur, slopes E.	
58.50	Wash, 50 lks. wide, 1 ft. deep, drains NW.	
62.00	Fence, bears S. 13° E. and N. 13° W.	
79.28	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R22E R23E S1 S6 S12 S7 1967</p> <p>Set a wooden post, 3 ins. diam., 4 ft. long, alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, cat claw, cacti, sage brush and grass.</p>	
	N. 0°06' E., bet. secs. 1 and 6.	
	Over gently rolling land through moderate undergrowth.	
.05	Fence, bears N. 33½° E. and S. 1° W.	
7.70	Tripp and Underwood wash, 250 lks. wide, 3 ft. deep, drains NE.	
23.30	Track road, bears N. 50° E. and S. 60° W.	
31.70	Top of mesa, bears NE. and SW.	
37.50	Wash, 20 lks. wide, 2 ft. deep, drains E.	

Dep. Resurvey, Subdivision, T.7 S., R.23 E., Arizona

CHAINS	
39.63	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R22E R23E $\frac{1}{4}$ S1 S6 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>Continue across top of mesa.</p>
79.26	<p>The cor. of Tps. 6 and 7 S., Rs. 22 and 23 E., monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of T. 6 S., R. 23 E., under this same group.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, scattered mesquite. Undergrowth, cat claw, cacti, creosote and grass.</p>
<p>Dependent Resurvey of the Subdivisional Lines, T. 7 S., R. 23 E., G&SR M., Arizona</p>	
<p>Reestablishment of the Survey Executed by L. Wolfley in 1884</p>	
<p>From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.</p> <p>N. $0^{\circ}05'$ W., bet. secs. 35 and 36.</p> <p>Over rolling land through moderate undergrowth.</p>	
3.10	<p>Jeep road in bottom of Nuttall Canyon, bears irregularly SE. and NW.</p>
7.50	<p>Wash, 25 lks. wide, 3 ft. deep, drains NW.</p>
10.00	<p>Spur, slopes N. 50° W.</p>
14.20	<p>Ravine, drains N. 50° W.</p>
18.50	<p>Spur, slopes N. 60° W.</p>
35.40	<p>Jeep road, bears N. 25° E. and S. 25° W.</p>
39.32	<p>The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented by a granite stone, 18 x 10 x 8 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S35 S36 1967</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS									
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°17' W., beginning new measurement.</p> <p>Over rolling land through moderate undergrowth.</p>								
.25	<p>Wash, 15 lks. wide, 1 ft. deep, drains N. 60° E.; asc. SE. slope of Stowe Knoll.</p>								
10.00	<p>Spur, slopes E., cont. asc.</p>								
39.14	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T7S R23E</td></tr> <tr><td style="border-right: 1px solid black; border-bottom: 1px solid black;">S26</td><td style="border-bottom: 1px solid black;">S25</td></tr> <tr><td style="border-right: 1px solid black;">S35</td><td>S36</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Cor. falls on a SE. slope.</p> <p>Land, rolling.</p> <p>Soil, rocky.</p> <p>Timber, pine, juniper and oak.</p> <p>Undergrowth, cacti, oak brush and grass.</p>	T7S R23E		S26	S25	S35	S36	1967	
T7S R23E									
S26	S25								
S35	S36								
1967									
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89°30' W., bet. secs. 25 and 36.</p> <p>Over rolling land through moderate undergrowth, desc. W. slope.</p>								
2.20	<p>Fence, bears N. and S.</p>								
13.10	<p>Ravine, drains N.</p>								
16.10	<p>Small spur, slopes N.</p>								
21.90	<p>Wash, 20 lks. wide, 6 ft. deep, drains N. 10° E.</p>								
34.00	<p>Track road, bears NW. and curves NE.</p>								
37.20	<p>Same road, bears N. 5° E. and S. 5° W.</p>								
40.22	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T7S R23E</td></tr> <tr><td style="border-right: 1px solid black; border-bottom: 1px solid black;">¼ S25</td><td style="border-bottom: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black;">S36</td><td></td></tr> <tr><td colspan="2">1967</td></tr> </table> </div>	T7S R23E		¼ S25		S36		1967	
T7S R23E									
¼ S25									
S36									
1967									

Dep. Resurvey, Subdivision, T.7 S., R.23 E., Arizona

CHAINS	
40.70	Wash, 50 lks. wide, 3 ft. deep, drains N. 60° E.
41.80	Asc. rocky E. slope of Stowe Knoll.
58.10	Ravine, drains S.
80.44	The cor. of secs. 25, 26, 35 and 36.
	Land, rolling. Soil, rocky. Timber, scattered mesquite. Undergrowth, creosote, cacti and bunch grass.
	N. 1°15' E., bet. secs. 25 and 26.
	Asc. SE. slope of Stowe Knoll.
2.90	Top of Stowe Knoll, desc. N. slope.
39.14	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate dist.; unable to find any evidence of the original corner.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R23E ¼ S26 S25 1967
75.17	Fence, bears N. 87°10' E. and S. 87°10' W.
78.28	The cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2½ ins. diam., set 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R23E S23 S24 ----- S26 S25 1960
	This cor. was remonumented under the Forest Service Remonumentation Program by L. Mann.
	Land, rolling. Soil, rocky. Timber, scattered juniper. Undergrowth, cacti and bunch grass.
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township.
	S. 88°54' W., bet. secs. 24 and 25.
	Over rolling land, through moderate undergrowth.
13.10	Track road, bears N. and S.
19.00	Wash, 20 lks. wide, 3 ft. deep, drains N. (Sand Wash)
38.80	Spur, slopes N., desc. along NW. slope.
39.31	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; unable to find any remaining evidence of the original corner.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ $\frac{S24}{S25}$ 1967</p>
42.90	Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. NE. slope.
51.00	Spur, slopes N.
78.62	The cor. of secs. 23, 24, 25 and 26.
	<p>Land, rolling. Soil, rocky. Timber, scattered mesquite. Undergrowth, mesquite, cat claw, cacti and bunch grass.</p>
	<p>N. 0°33' W., bet. secs. 23 and 24.</p> <p>Over rolling land, through moderate undergrowth.</p>
10.00	Track road, bears N. 38° E. and S. 38° W.
14.10	Wash, 25 lks. wide, 3 ft. deep, drains N., 250 lks., thence NE.
36.30	Middle Wash, 20 lks. wide, 3 ft. deep, small stream of water, course NE.
39.53	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented by a granite stone, 18 x 10 x 5 ins., set 8 ins. in the ground, in a mound of stone, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ $\frac{S23}{S24}$ 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°35' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
30.50	Wash, 35 lks. wide, 2 ft. deep, drains N. 70° E.
40.23	<p>The cor. of secs. 13, 14, 23 and 24, monumented by a granite stone, 15 x 6 x 6 ins., set 6 ins. in the ground, mkd. 3 notches on S. face and 1 notch on E. face.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	<p style="text-align: center;">T7S R23E $\frac{S14}{S23} \frac{S13}{S24}$ 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, cat claw and bunch grass.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp.</p> <p>S. 88°58' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>2.30 Track road, bears N. 55° E. and S. 55° W.</p> <p>24.00 Wash, 50 lks. wide, 3 ft. deep, drains N.</p> <p>28.70 Wash, 40 lks. wide, 4 ft. deep, drains N. (Middle Wash)</p> <p>38.80 Enter wash area, drains N.</p> <p>39.70 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T7S R23E $\frac{1}{4} \frac{S13}{S24}$ 1967</p> <p>Raise a mound of stone N. of the corner.</p> <p>70.40 Wash, 15 lks. wide, 1 ft. deep, drains N. 30° E.</p> <p>79.40 The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cat claw, cacti, creosote and bunch grass.</p>
	<p>N. 0°28' W., bet. secs. 13 and 14.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>2.70 Wash, 20 lks. wide, 2 ft. deep, drains NE.</p> <p>12.20 East end of Bryce Knoll.</p> <p>39.52 The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented by a granite stone, 16 x 12 x 7 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S14 S13 1967</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°24' W., beginning new measurement.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
39.20	<p>Wash, 30 lks. wide, 2 ft. deep, drains N. 70° E.</p>
40.04	<p>The cor. of secs. 11, 12, 13 and 14, monumented by a mound of stone, from which the remains of the original bearing tree</p>
	<p style="text-align: center;">A mesquite, 12 ins. diam., bears S. 16° W., 115 lks. dist., mkd. with an open blaze.</p>
	<p>At the corner point</p>
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R23E S11 S12 S14 S13 1967</p>
	<p>Land, rolling. Soil, rocky. Timber, scattered mesquite. Undergrowth, cat claw, creosote and cacti.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.</p>
	<p>from which</p>
	<p style="text-align: center;">A windmill, bears S. 62°20' W., 20.40 chs. dist.</p>
	<p>S. 89°44' W., bet. secs. 12 and 13.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
5.50	<p>Wash, 20 lks. wide, 3 ft. deep, drains NE.</p>
8.90	<p>Wash, 30 lks. wide, 3 ft. deep, drains NE. (Middle Wash)</p>
35.90	<p>Fence, bears S. 43° E. and N. 43° W.</p>
39.97	<p>The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented by a granite stone, 17 x 12 x 5 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.</p>
	<p>At the corner point</p>
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ ——— S12 S13 1967</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Deposit the orig. cor. stone alongside the iron post.</p> <hr/> <p>S. 88°46' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
36.90	Wash, 30 lks. wide, 6 ft. deep, drains NE.
39.80	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, rocky. Timber, mesquite. Undergrowth, cat claw, creosote, cacti and grass.</p>
	<p>N. 0°19' E., bet. secs. 11 and 12.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
18.10	Cottonwood Creek, 50 lks. wide, 3 ft. deep, drains E.
26.20	Wash, 25 lks. wide, 2 ft. deep, drains E.
33.40	Fence, bears S. 70° E. and N. 70° W.
39.41	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by a granite stone, 14 x 12 x 5 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S11 S12 1967</p>
	<p>from which</p> <p style="text-align: center;">U.S.S.E.S. Triangulation Station BEAR, bears N. 29°23' W., 37.36 chs. Dist., monumented with a brass tablet, 3 ins. diam., set in a circular concrete post, mkd. BEAR 1935.</p>
	<p>Deposit the original cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
	<hr/> <p>N. 0°14' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
16.90	Edge of mesa, bears E. and W.
22.30	Mesa Road, bears N. 78° E. and S. 78° W.
39.50	Wash, 10 lks. wide, 10 ft. deep, drains N. 10° E.
39.95	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; unable to find any remaining evidence of the original corner.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T7S R23E $\frac{S2}{S11} \frac{S1}{S12}$ 1967 </p> <p>Set a wooden post 4 ins. diam., 5 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, clay loam. No timber; undergrowth, creosote, cat claw and grass.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp.</p> <p>S. 88°24' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>6.60 Track road, bears NE. and SW.</p> <p>36.70 Ravine, drains NE.</p> <p>39.72 The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented by a granite stone, 13 x 10 x 7 ins., set 5 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T7S R23E $\frac{1}{4} \frac{S1}{S12}$ 1967 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>S. 89°59' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>10.10 Track road, bears N. and S.</p> <p>24.90 Ravine, drains NE.</p> <p>36.00 Ravine, drains NE.</p> <p>38.70 Ravine, drains N.</p> <p>39.86 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, clay loam. No timber; undergrowth, creosote, cacti and cat claw.</p> <hr/> <p>N. 0°36' W., bet secs. 1 and 2.</p> <p>Over broken land, through scattered undergrowth.</p> <p>39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S2 S1 1967</p>
53.10	Wash, 20 lks. wide, 12 ft. deep, drains NE.
80.10	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. in diam., set, mkd. and witnessed as described in the concurrent re-survey of T. 6 S., R. 23 E., under this same group.</p> <p>Land, broken. Soil, clay loam. No timber; undergrowth, creosote, cat claw and grass.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp.</p> <p>N. 1°28' W., bet. secs. 34 and 35.</p> <p>Over mountainous land, through moderate undergrowth.</p>
9.50	Wash, 25 lks. wide, 4 ft. deep, drains N. 65° E.
16.70	Same wash, drains N. 15° E., from SE.
27.70	Same wash, drains NW.
38.00	Same wash, drains NE.
38.94	<p>Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S34 S35 1967</p>
60.00	Cont. over mountainous land. Same wash, drains N. 15° W.
77.88	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E S27 S26 S34 S35 1967</p>
	<p>Land, mountainous. Soil, rocky. Timber, scattered juniper and pine. Undergrowth, cacti, cat claw and grass.</p> <p>From the cor. of secs. 25, 26, 35 and 36.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	S. 89°45' W., bet. secs. 26 and 35.
	Over mountainous land, through moderate undergrowth; asc. SE. slope of Stowe Knoll.
4.80	Saddle on top of Stowe Knoll, bears NE. and SW.; desc. NW. slope.
12.00	Slope changes to W.
28.40	Deep ravine, drains N. 30° W.
35.50	Small ravine, drains N.
40.32	Point for the ¼ sec. cor. of secs 26 and 35, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ $\frac{S26}{S35}$ 1967</p>
61.80	Creek in bottom of Nuttall Canyon, course N. 10° W.
80.64	The cor. of secs. 26, 27, 34 and 35.
	Land, mountainous. Soil, rocky. Timber, mesquite and scattered juniper. Undergrowth, oak brush, cacti and grass.
	N. 2°15' E., bet. secs. 26 and 27.
	Over mountainous land, through moderate undergrowth.
22.10	Old fence line, bears NE. and SW.
30.10	Creek at junction of Carter and Nuttall Canyon, 50 lks. wide, 1 ft. deep, drains N. 50° E., into Middle Wash.
38.96	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S27 S26 1967</p>
72.20	Fence, bears N. 87°10' E., and S. 87°10' W.
77.92	The cor. of secs. 22, 23, 26 and 27, monumented by a granite stone, 16 x 10 x 10 ins., set 8 ins. in the ground, mkd. 2 notches on S. face and 2 notches on E. face, mound of stone W.
	At the corner point

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS							
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T7S</td> <td>R23E</td> </tr> <tr> <td><u>S22</u></td> <td><u>S23</u></td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> </table> <p>1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, cat claw, cacti and grass.</p>	T7S	R23E	<u>S22</u>	<u>S23</u>	S27	S26
T7S	R23E						
<u>S22</u>	<u>S23</u>						
S27	S26						
<p>5.10 9.70 14.70 38.50 39.91</p>	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°56' W., bet. secs. 23 and 26.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains N.</p> <p>Jeep road, bears N. 15° E. and S. 15° W.</p> <p>Wash, 30 lks. wide, 4 ft. deep, drains NE.</p> <p>Middle Wash, 100 lks. wide, 3 ft. deep, drains NE.</p> <p>The ¼ sec. cor. of secs. 23 and 26, monumented by a granite stone, 19 x 17 x 8 ins., set 8 ins. in the ground, mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T7S</td> <td>R23E</td> </tr> <tr> <td>¼ <u>S23</u></td> <td><u>S26</u></td> </tr> </table> <p>1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p>	T7S	R23E	¼ <u>S23</u>	<u>S26</u>		
T7S	R23E						
¼ <u>S23</u>	<u>S26</u>						
<p>39.29</p>	<p>S. 89°00' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, mesquite, cat claw and cacti.</p>						
<p>11.30 33.80 39.78</p>	<p>N. 1°11' E., bet. secs. 22 and 23.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains NW.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains NW.</p> <p>The ¼ sec. cor. of secs. 22 and 23, monumented by a granite stone, 24 x 12 x 10 ins., set 12 ins. in the</p>						

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S22 S23 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°09' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>10.80 Wash, 35 lks. wide, 3 ft. deep, drains NE., 50 lks. dist., thence W.</p> <p>13.90 Same wash, drains W., 290 lks. dist., thence NE.</p> <p>14.30 Track road, bears NE. and SW.</p> <p>16.90 Same wash, drains E., curving NE.</p> <p>32.10 Track road, bears N. 30° E. and S. 30° W.</p> <p>36.50 Taylor Canyon road, bears N. 60° E. and S. 40° W.</p> <p>40.20 The cor. of secs. 14, 15, 22 and 23, monumented by an iron post 2½ ins. diam., set 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E S15 S14 <hr style="width: 20%; margin: auto;"/>S22 S23 1960</p> <p>This cor. was remonumented under the Forest Service Remonumentation Program by L. Mann.</p> <p>from which</p> <p style="padding-left: 40px;">Webb Tank No. 1, bears S. 17°30' E., 21.50 chs. dist.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, cat claw, creosote and cacti.</p>
38.72	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°36' W., bet. secs. 14 and 23.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S14 <hr style="width: 20%; margin: auto;"/>S23 1967</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
51.20	Wash, 30 lks. wide, 4 ft. deep, drains N.
75.00	Taylor Canyon road, bears NE. and SW.
77.44	The cor. of secs. 14, 15, 22 and 23.
	Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, cat claw, creosote and grass.
	N. 0°46' E., bet. secs. 14 and 15.
	Over rolling land, through moderate undergrowth.
39.84	The ¼ sec. cor. of secs. 14 and 15, determined from the original bearing tree:
	<p style="padding-left: 40px;">A mesquite 16 ins. diam., bears West, 24 lks. dist., mkd. ¼ S. BT.</p>
	At the corner point
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E ¼ S15 S14 1967</p>
	N. 2°16' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
3.30	Wash in North Taylor Canyon, 30 lks. wide, 2 ft. deep, drains N. 15° E.
12.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 60° E.
27.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 35° E.
39.60	Enter wash area of Cottonwood Creek, general E. drainage.
40.10	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, in a collar of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E S10 S11 S15 S14 1967</p>
	from which
	<p style="padding-left: 40px;">A mesquite 10 ins. diam., bears N. 20° E., 73½ lks. dist., mkd. T7SR23E S11 BT.</p>
	Land, rolling.
	Soil, rocky loam.
	Timber, mesquite.
	Undergrowth, cat claw, cacti, creosote and grass.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS		
	From the cor. of secs. 11, 12, 13 and 14.	
	S. 89°48' W., bet. secs. 11 and 14.	
	Over rolling land, through heavy undergrowth.	
26.10	Taylor Canyon road, bears N. 20° E. and S. 20° W.	
29.90	Cottonwood Creek, 20 lks. wide, 3 ft. deep, drains NE.	
38.97	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate dist.; unable to find any remaining evidence of the original corner.	
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.	
	<div style="text-align: center;"> T7S R23E $\frac{1}{4}$ S11 <hr style="width: 50px; margin: 0 auto;"/> S14 1967 </div>	
	from which	
	<div style="text-align: center;"> A mesquite 4 ins. diam., bears N. 85° W., 30 lks. dist., mkd. ¼ S11 BT. </div>	
51.80	Enter Cottonwood Creek, 30 lks. wide, 3 ft. deep, drains S. 70° E. from W.	
57.20	Leave Cottonwood Creek, drains E from SW.	
69.10	Enter Cottonwood Creek area, drains S. 25° E. from irregularly W.	
77.94	The cor. of secs. 10, 11, 14 and 15.	
	Land, rolling.	
	Soil, rocky loam.	
	Timber, mesquite.	
	Undergrowth, creosote, cat claw, cacti and grass.	
	N. 2°55' E., bet. secs. 10 and 11.	
	Over wash area of Cottonwood Creek, general E. drainage.	
4.50	Leave wash area, continue over rolling land through moderate undergrowth.	
40.12	The ¼ sec. cor. of secs. 10 and 11, monumented by a sandstone, 10 x 10 x 3 ins., set 5 ins. in the ground, mkd. ¼ on W. face.	
	At the corner point	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	<div style="text-align: center;"> T7S R23E $\frac{1}{4}$ S10 S11 1967 </div>	
	Bury the orig. cor. stone alongside the iron post.	
	Raise a mound of stone W. of the corner.	

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>N. 5°54' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
11.90	<p>Mesa Road, bears N. 65° E. and S. 65° W.</p>
12.10	<p>Fence, bears E. and W.</p>
13.10	<p>Enter broken badlands.</p>
39.63	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; unable to find any remaining evidence of the original corner; cor. falls in wash, in an unsafe position, impractical to monument.</p> <p>Land, rolling to broken. Soil, rocky loam. No timber; undergrowth, creosote, cat claw, cacti and grass.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°50' W., bet. secs. 2 and 11.</p> <p>Over rolling badlands, through moderate undergrowth.</p>
1.20	<p>Fence, bears N. and S.</p>
5.80	<p>Ravine, drains NE.</p>
32.10	<p>Wash, 40 lks. wide, 6 ft. deep, drains N.</p>
36.70	<p>Track road, bears N. and S.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ $\frac{S2}{S11}$ 1967</p> <p>Set a wooden post 3 ins. in diam., 4 ft. long, alongside the iron post.</p>
42.10	<p>Ravine, drains N.</p>
48.90	<p>Ravine, drains N.</p>
64.50	<p>Ravine, drains N.</p>
80.00	<p>True point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Land, badlands. Soil, clay loam. No timber; undergrowth, creosote, cat claw and cacti.</p>
.20	<p>N. 0°39' E., bet. secs. 2 and 3.</p> <p>Over broken badlands, through moderate undergrowth.</p> <p>Point selected for the witness cor. of secs. 2, 3, 10 and 11.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E W C S3 S2 ----- S10 S11 ↓ 1967</p> </div> <p>Set a squared wooden post, 4 ins. diam., 4 ft. long, alongside the iron post.</p> <p>23.00 Wash, 15 lks. wide, 1 ft. deep drains N. 20° E. 39.42 The ¼ sec. cor. of secs. 2 and 3, monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. ¼ on W. face, mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E ¼ S3 S2 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°47' W., beginning new measurement.</p> <p>10.00 Over broken badlands, through moderate undergrowth. 26.30 Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E. Enter rolling land.</p> <p>37.70 Wash, 80 lks. wide, 4 ft. deep, drains NE.</p> <p>41.00 True point for cor. of secs. 2 and 3 only, on the N. bdy. of the Tp.</p> <p>from which</p> <p style="padding-left: 40px;">The witness corner of secs. 2 and 3 only, on the N. bdy. of the Tp., bears S. 89°53' E., 98 lks. dist., monumented by an iron post, set, mkd. and witnessed as described in the concurrent resurvey of T. 6 S., R. 23 E., under this same group.</p> <p>Land, broken to rolling. Soil, clay loam. No timber; undergrowth, creosote, cat claw and cacti.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp.</p> <p>N. 1°55' W., bet. secs. 33 and 34.</p> <p>Over mountainous land, through moderate undergrowth; asc. SW. slope.</p> <p>3.50 Top of high spur, slopes S. 70° W., desc. along W. slope of mountain.</p> <p>5.20 Spur, slopes N. 60° W.</p> <p>39.27 Point for the ¼ sec. cor. of secs. 33 and 34, at</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{2}$ S33 S34 1967</p> <p>41.30 Jeep road, bears S. 55° E. and N. 55° W.</p> <p>43.30 Wash, 10 lks. wide, 2 ft. deep, drains N. 50° W.</p> <p>45.00 Spur, slopes W.; desc. along W. slope of mountain.</p> <p>78.54 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E <u>S28 S27</u> S33 S34 1967</p> <p>Cor. falls on a NW. slope.</p> <p>Land, mountainous. Soil, rocky. Timber, juniper and oak. Undergrowth, buck brush and cacti.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°38' W., bet. secs. 27 and 34.</p> <p>Over mountainous land, through moderate undergrowth.</p> <p>Thence by triangulation, topography estimated.</p> <p>3.00 Wash, 70 lks. wide, 8 ft. deep, drains N.</p> <p>16.00 Wash in Carter Canyon, 150 lks. wide, 8 ft. deep, drains N.</p> <p>28.00 Ravine, drains N.</p> <p>31.90 Spur, slopes NE., end of triangulation.</p> <p>40.11 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ <u>S27</u> S34 1967</p> <p>from which</p> <p style="text-align: center;">A stock pond, bears N. 60° E., 16.00 chs. dist.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	Asc. E. slope of ridge.
49.90	Saddle on top of ridge, bears N. 10° E. and S. 10° W.
51.10	Fence, bears S. 30° W. and N. 30° E., 240 lks. dist., thence N. 10° E., desc. NW. slope.
67.50	Ravine, drains N.
74.20	Low spur, slopes N.
80.22	The cor. of secs. 27, 28, 33 and 34.
	Land, mountainous.
	Soil, rocky.
	Timber, mesquite.
	Undergrowth, buck brush, cacti and bunch grass.
	N. 3°31' E., bet. secs. 27 and 28.
	Over rolling land, through moderate undergrowth; desc. NW. slope.
39.32	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S28 S27 1967</p>
47.00	Taylor Canyon Road, bears NE. and SW.
47.10	Enter wash area, drains NE.
64.00	Wash in North Taylor Canyon, 60 lks. wide, 3 ft. deep, drains N. 30° E.
64.50	Leave wash area, asc. over rolling land.
69.20	Fence, bears S. 89°45' E., and N. 89°45' W.
71.00	Spur, slopes NE.; desc. over rolling land.
76.00	Wash in Little Right Hand Canyon, 30 lks. wide, 2 ft. deep, drains N. 70° E.
78.64	The cor. of secs. 21, 22, 27 and 28, monumented by a granite stone, 16 x 12 x 7 ins., set 6 ins. in the ground, mkd. with 3 notches on E. and 2 notches on S. faces.
	At the corner point
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T7S R23E S21 S22 S28 S27 1967</p>
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the corner.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Land, rolling. Soil, rocky. Timber, mesquite and scattered juniper. Undergrowth, creosote, cat claw, cacti and grass.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27. S. 89°57' W., bet. secs. 22 and 27. Over rolling land, through moderate undergrowth.</p>
1.00	Spur, slopes N.
6.80	Wash, 15 lks. wide, 2 ft. deep, drains N.
28.90	Wash, 30 lks. wide, 4 ft. deep, drains NE.
39.22	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented by a Flint stone, 17 x 10 x 6 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E $\frac{1}{4}$ $\frac{S22}{S27}$ 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 88°09' W., beginning new measurement. Over rolling land, through moderate undergrowth.</p>
1.75	Jeep road, bears NE. and SW.
11.20	Wash, 15 lks. wide, 2 ft. deep, drains N. 20° E.
21.60	Spur, slopes NE., desc. NW. slope.
28.00	Taylor Canyon Road, bears N. 15° E. and S. 15° W.
28.30	Enter wash area.
31.60	Fence, bears N. 22° E. and S. 22° W.
33.50	Fence, bears N. 55° E. and S. 55° W.
34.20	Wash in North Taylor Canyon, 50 lks. wide, 3 ft. deep, drains NE.
35.00	Leave wash area.
39.45	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, cat claw, mesquite and cacti.</p>
	<p>N. 0°32' E., bet. secs. 21 and 22. Over rolling land, through moderate undergrowth.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
3.50	Jeep road, bears E. and W.
5.50	Enter nearly level land, bears E. and W.
29.50	Jeep road, bears N. 20° E. and S. 20° W.
40.54	The ¼ sec. cor. of secs. 21 and 22, monumented by a granite stone, 17 x 10 x 7 ins., set 8 ins. in the ground and in a mound of stone, mkd. ¼ on W. face.
	At the corner point
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S21 S22 1967</p>
	from which
	Mexican Tank, bears S. 70° W., 27.00 chs. dist.
	Deposit the orig. cor. stone alongside the iron post.
	<hr style="width: 20%; margin: 0 auto;"/> <p>N. 0°10' W., beginning new measurement.</p>
	Over rolling land, through moderate undergrowth.
39.08	The cor. of secs. 15, 16, 21 and 22, monumented by an iron post, 2½ ins. diam., set 16 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E <u>S16 S15</u> S21 S22 1960</p>
	This cor. was remonumented under the Forest Service Remonumentation Program by L. Mann.
	Land, nearly level to rolling. Soil, rocky. No timber; undergrowth, creosote, cacti and cat claw.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°20' W., bet. secs. 15 and 22.
	Over rolling land, through heavy undergrowth.
10.00	Wash, 10 lks. wide, 2 ft. deep, drains N.
14.90	Wash in North Taylor Canyon, 30 lks. wide, 3 ft. deep, drains N. 20° E.
39.59	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S15 <u> </u> S22 1967</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	Raise a mound of stone N. of the corner.
65.80	Jeep road, bears S. 30° E. and N. 30° W.
74.40	Jeep road, bears N. 35° E. and S. 35° W.
79.18	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, creosote, cat claw, cacti and grass.
	N. 0°08' W., bet. secs. 15 and 16.
	Over rolling land, through moderate undergrowth.
5.30	Wash in Mexican Canyon, 50 lks. wide, 4 ft. deep, drains N. 60° E.
20.70	Wash, 30 lks. wide, 5 ft. deep, drains E.
30.35	Fence, bears N. 65° E. and S. 65° W.
39.60	Wash, 15 lks. wide, 1½ ft. deep, drains N. 80° E.
39.98	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S16 S15 1967</p>
	from which
	<p style="text-align: center;">Seven Cross Tank, bears N. 80° E., 10.00 chs. dist.</p>
	Raise a mound of stone W. of the corner.
45.10	Fence, bears N. 75° E. and S. 75° W.
62.90	Wash, 30 lks. wide, 4 ft. deep, drains N. 70° E.
66.90	Fence, bears S. 27° E. and N. 27° W.
74.40	Wash in Wide Mouth Canyon, 100 lks. wide, 4 ft. deep, drains N. 70° E.
79.96	The cor. of secs. 9, 10, 15 and 16, monumented by a granite stone, 10 x 10 x 7 ins., set 5 ins. in the ground, mkd. 4 notches on S. face and 3 notches on E. face, mound of stone W.
	At the corner point
	Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ S9 S10 S16 S15 1967</p>
	Bury the orig. cor. stone alongside the iron post.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Land, rolling. Soil, rocky loam. No timber; undergrowth, creosote, cat claw and cacti.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15. N. 89°17' W., bet. secs. 10 and 15. Over Cottonwood Creek area, drains irregularly E.</p>
10.50	Wash channel, 30 lks. wide, 2 ft. deep, drains NE.
15.60	Wash channel, 80 lks. wide, 4 ft. deep, drains N. 70° E.
19.00	Lv. wash area, continue over rolling land.
39.17	<p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ S10 S15 1967</p>
60.80	Wash in Wide Mouth Canyon, 40 lks. wide, 3 ft. deep, drains N. 70° E.
72.90	Track road, bears N. and S.
78.34	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>
	<p>N. 2°36' W., bet. secs. 9 and 10. Over gently rolling land, through moderate undergrowth.</p>
4.10	Wash, 15 lks. wide, 2 ft. deep, drains N. 65° E.
9.20	Track road, bears N. 60° E. and S. 60° W.
16.80	Wash, 30 lks. wide, 3 ft. deep, drains N. 80° E.
18.10	Cottonwood Creek, 20 lks. wide, 3 ft. deep, drains S. 80° E.
21.10	Track road, bears N. 80° E. and S. 80° W.
37.60	Mesa Road, bears N. 60° E. and S. 60° W.
39.48	<p>Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ S9 S10 1967</p> <p>Raise a mound of stone W. of the corner.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS					
70.10	Bear Spring Wash, 100 lks. wide, 2 ft. deep, drains NE.				
78.96	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a granite stone, 15 x 10 x 8 ins., set 6 ins. in the ground, mkd. 5 notches on S. face and 3 notches on E. face, mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E</p> <table border="1" style="margin: auto;"> <tr> <td>S4</td> <td>S3</td> </tr> <tr> <td>S9</td> <td>S10</td> </tr> </table> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">Center of Squaw Tank, bears S. 45° E., 8.00 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling to broken. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>	S4	S3	S9	S10
S4	S3				
S9	S10				
	<p>From the cor. of secs. 2, 3, 10 and 11.</p>				
	<p>N. 89°45' W., bet. secs. 3 and 10.</p>				
	<p>Over rough rolling land, through moderate undergrowth.</p>				
14.40	Ravine, drains N.				
29.10	Wash, 30 lks. wide, 3 ft. deep, drains N.				
39.98	<p>Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R23E</p> <table border="1" style="margin: auto;"> <tr> <td>¼</td> <td>S3</td> </tr> <tr> <td></td> <td>S10</td> </tr> </table> <p>1967</p> </div> <p>Cor. falls on a steep SE. slope.</p>	¼	S3		S10
¼	S3				
	S10				
44.40	Ravine, drains N.				
71.80	Wash, 80 lks. wide, 3 ft. deep, drains N. (Bear Springs)				
79.96	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling to broken. Soil, clay loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>				
	<p>N. 0°39' W., bet. secs. 3 and 4.</p>				

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
36.80	<p>Over rolling land, through moderate undergrowth. Wash, 30 lks. wide, 2 ft. deep, drains N. 70° E.</p>
39.36	<p>The ¼ sec. cor. of secs. 3 and 4, monumented by a granite stone, 12 x 8 x 5 ins., set 5 ins. in the ground and in a mound of stone, no legible mks.; this is accepted as best remaining evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ S4 S3 1967</p> <p>Bury the orig. cor. stone alongside the iron post. Set a squared post 4 ins. diam., 4 ft. long, alongside the iron post. Raise a mound of stone W. of the cor.</p>
21.70	<p>N. 0°39' E., beginning new measurement. Over rolling land, through moderate undergrowth. Wash, 100 lks. wide, 3 ft. deep, drains E. (Matthews)</p>
40.27	<p>The cor. of secs. 3, and 4 only on the N. bdy. of Tp., monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of T. 6 S., R. 23 E., under this same group.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>
8.70	<p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy of Tp. N. 1°33' E., bet. secs. 32 and 33. Over mountainous land, through moderate undergrowth. Ravine, drains E.</p>
37.50	<p>Ravine, drains E.</p>
39.40	<p>The ¼ sec. cor. of secs. 32 and 33, monumented by a granite stone, 18 x 11 x 7 ins., set 8 ins. in the ground, no legible mks., mound of stone W.; this is accepted as best remaining evidence of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ S32 S33 1967</p> <p>Bury the original cor. stone alongside the iron post.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS													
	<p>Cor. falls on a spur, slopes E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 7°50' W., beginning new measurement.</p> <p>Over mountainous land through moderate undergrowth.</p>												
3.50	Ravine, drains E.; asc. steep SE. slope.												
16.80	Ravine, drains SE.; asc. S. slope.												
25.80	Spur, slopes E.; desc. NE. slope.												
39.35	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T7S</td> <td style="padding: 0 5px;">R23E</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S29</td> <td style="padding: 0 5px;">S28</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1967</td> </tr> </table> </div> <p>Land, mountainous. Soil, rocky. Timber, juniper and oak. Undergrowth, manzanita, cat claw, cacti and grass.</p>	T7S	R23E		S29	S28		S32	S33		1967		
T7S	R23E												
S29	S28												
S32	S33												
1967													
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°26' W., bet. secs. 28 and 33.</p> <p>Over mountainous land, through moderate undergrowth.</p>												
5.10	Track road, bears N. and S.												
9.50	Creek in North Taylor Canyon, course N.												
19.40	Taylor Canyon Road, bears irregularly NE. and SW.												
26.00	Wash, 30 lks. wide, 4 ft. deep, drains N.; asc. SE. slope.												
40.23	<p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T7S</td> <td style="padding: 0 5px;">R23E</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td></td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">S33</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1967</td> </tr> </table> </div>	T7S	R23E		¼	S28			S33		1967		
T7S	R23E												
¼	S28												
	S33												
1967													
51.90	Spur, slopes NE.												
57.00	Ravine, drains NE.												
80.46	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered juniper, oak and mesquite. Undergrowth, cacti, cat claw and grass.</p>												

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	N. 3°55' E., bet. secs. 28 and 29.
	Over mountainous land, through moderate undergrowth, asc. SE. slope.
2.50	Spur, slopes NE.; desc. NW. slope.
15.60	Ravine, drains NW.
17.00	Ravine, drains NE.
22.50	Same ravine, drains NW., continue desc.
39.08	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R23E 1/4 S29 S28 1967
56.60	Enter Little Righthand Canyon, drains N. 70° E.
59.30	Wash, 30 lks. wide, 6 ft. deep, drains N. 70° E.
62.40	Leave Little Righthand Canyon.
65.90	Jeep road, bears N. 80° E. and S. 80° W.
70.80	Fence, bears E. and W.
78.16	The cor. of secs. 20, 21, 28 and 29, monumented by a granite stone, 14 x 9 x 3 ins., set 5 ins. in the ground, mkd. 4 notches on E. face and 2 notches on the S. face, mound of stone W.
	At the corner point
	Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R23E S20 S21 S29 S28 1967
	from which
	Top of high knoll, bears N. 70° W., 25.00 chs. dist.
	Raise a mound of stone W. of the corner.
	Land, mountainous.
	Soil, rocky.
	Timber, scattered juniper and oak.
	Undergrowth, manzanita, cacti, cat claw and grass.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 88°52' W., bet. secs. 21 and 28.
	Over high rolling land, through moderate undergrowth.
5.70	Jeep road, bears N. 60° E. and W.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
13.70	Wash, 30 lks. wide, 2 ft. deep, drains S. 70° E.
24.60	Wash in Little Righthand Canyon, 30 lks. wide, 4 ft. deep, drains S. 50° E.
27.50	Same wash, drains N. 60° E.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T7S R23E $\frac{1}{4}$ $\frac{S21}{S28}$ 1967</p>
	The cor. is located 45 lks. South of a jeep road bearing N. 85° E., and S. 85° W.
45.50	Jeep road, bears N. 85° E. and S. 85° W.
79.80	The cor. of secs. 20, 21, 28 and 29.
	<p>Land, rolling. Soil, rocky. Timber, mesquite. Undergrowth, cacti, cat claw and grass.</p>
	N. 0°26' W., bet. secs. 20 and 21.
	Over rolling land, through moderate undergrowth.
6.40	Wash in Mexican Canyon, 25 lks. wide, 3 ft. deep, drains N. 60° E., asc. SE slope.
20.30	Spur, slopes N.E., desc. N. slope.
35.50	Fence, bears NE., and SW.
37.75	Fence, bears S. 57° E. and N. 57° W.
40.20	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.
	<p>T7S R23E $\frac{1}{4}$ S20 S21 1967</p>
79.00	Wash in Wide Mouth Canyon, 20 lks. wide, 1 ft. deep, drains NE.
80.40	The cor. of secs. 16, 17, 20 and 21, monumented by a granite stone, 15x12x7 ins., set 6 ins. in the ground, mkd. 4 notches on E. face, mound of stone alongside.
	At the corner point
	Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	<p style="text-align: center;">T7S R23E S17 S16 S20 S21 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky loam. Timber, scattered oak and mesquite. Undergrowth, cacti, cat claw and grass.</p>
<p>7.60</p> <p>28.10</p> <p>30.70</p> <p>39.00</p> <p>39.70</p>	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 88°11' W., bet. secs. 16 and 21.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash in Mexican Canyon, 80 lks. wide, 5 ft. deep, drains N. curving NE.</p> <p>Wash, 30 lks. wide, 6 ft. deep, drains NE.</p> <p>Fence, bears N. and S.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains N.</p> <p>The ¼ sec. cor. of secs. 16 and 21, monumented by a granite stone, 12x12x4 ins., set 5 ins., in the ground, mkd. ¼ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>
<p>14.80</p> <p>39.50</p> <p>40.90</p>	<p style="text-align: center;">T7S R23E ¼ S16 S21 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°18' W., beginning new measurement.</p> <p>Wash, 30 lks. wide, 3 ft. deep, drains NE.</p> <p>Wash in Wide Mouth Canyon, 20 lks. wide, 2 ft. deep, drains N. from SW.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>
<p>10.70</p> <p>35.10</p>	<p>N. 0°09' E., bet. secs. 16 and 17.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Fence, bears N. 25° E. and S. 25° W.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains N. 30° E.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
40.07	<p>The ¼ sec. cor. of secs. 16 and 17, monumented by a granite stone, 13x10x5 ins., set 5 ins. in the ground, mkd. ¼ on W. face, mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S17 S16 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N.0° 15' W., beginning new measurement.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
7.70	<p>Wash, 30 lks. wide, 4 ft. deep, drains NE.</p>
18.70	<p>Wash, 50 lks. wide, 4 ft. deep, drains E. (Tunnel Canyon)</p>
39.56	<p>The cor. of secs. 8, 9, 16 and 17, monumented by a granite stone, 16x10x5 ins., set 8 ins. in the ground, mkd. 4 notches on S. face and 4 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S 8 S 9 S17 S16 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p>
	<p>S. 89° 56' W., bet secs. 9 and 16.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
6.60	<p>Fence, bears S. 30° E. and N. 30° W.</p>
12.90	<p>Track road, bears N. 25° E. and S. 25° W.</p>
34.80	<p>Wash, 10 lks. wide, 3 ft. deep, drains N. 20° E.</p>
40.24	<p>The ¼ sec. cor. of secs. 9 and 16, monumented by a granite stone, 27x10x10 ins., lying loose on the ground, mkd. ¼ on N. face, mound of stone N.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S 9 <hr style="width: 50px; margin: 0 auto;"/> S 16 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 39' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
6.00	Fence, bears N. 25° E. and S. 25° W.
40.15	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquitè. Undergrowth, cacti, creosote, cat claw and grass.</p>
	<p>N.0° 53' W., bet. secs. 8 and 9.</p> <p>Over rolling land, through moderate undergrowth.</p>
26.70	Track road, bears NE. and SW.
34.60	Wash, 30 lks. wide, 2 ft. deep, drains E.
39.65	<p>The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented by a granite stone, 10x6x3 ins., loosely set, dimly mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S 8 S 9 1967</p> <p>from which</p> <p style="padding-left: 40px;">A Water Gage, bears S. 52° 46' E., 6.60 chs. dist.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3° 08' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
6.80	Wash, 10 lks. wide, 1 ft. deep, drains SE.
11.70	Mesa Road, bears S. 80° E. and N. 80° W.
12.60	Fence, bears S. 80° E. and N. 80° W.
21.80	Leave rolling land, enter broken land, bears SE. and NW.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS									
27.80	Bear Springs Wash, 30 lks. wide, 4 ft. deep, drains N. 70° E.								
39.94	<p>The cor. of secs. 4, 5, 8 and 9, monumented by a granite stone, 18x10x8 ins., set 8 ins. in the ground, mkd. 5 notches on S. face and 4 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td>R23E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling to broken. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>	T7S	R23E	S 5	S 4	S 8	S 9	1967	
T7S	R23E								
S 5	S 4								
S 8	S 9								
1967									
32.70	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°52' W., bet. secs. 4 and 9.</p> <p>Over broken land, through moderate undergrowth.</p>								
39.62	<p>Spur, slopes S.</p> <p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 4 and 9.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td>R23E</td></tr> <tr><td>$\frac{1}{4}$ S 4</td><td>W</td></tr> <tr><td>S 9</td><td>C</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Raise a mound of stone N. of the corner.</p>	T7S	R23E	$\frac{1}{4}$ S 4	W	S 9	C	1967	
T7S	R23E								
$\frac{1}{4}$ S 4	W								
S 9	C								
1967									
39.82	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate dist.; unable to find any remaining evidence of the original corner; cor. falls in an unsafe position, impractical to monument.</p>								
79.64	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, broken. Soil, clay loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>								
14.80	<p>N. 0°01' W., bet. secs. 4 and 5.</p> <p>Over broken land, through moderate undergrowth.</p> <p>Spur, slopes NE., continue over broken land.</p>								

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS		
40.12	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented by a granite stone, 10x14x3 ins., set 5 ins. in the ground mkd. $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S 5 S 4 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p>	
	<p style="text-align: center;">—————</p> <p>N. 0°41' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>	
7.90	<p>Matthews wash, 50 lks. wide, 2 ft. deep, drains E.</p>	
31.30	<p>Wash, 25 lks. wide, 3 ft. deep, drains E.</p>	
39.71	<p>The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. in diam., set, mkd. and witnessed as described in the concurrent resurvey of T. 6 S., R. 23 E., under this same group.</p> <p>Land, broken to rolling. Soil, clay loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>	
	<p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy of the Tp.</p> <p>N. 4°04' W., bet. secs. 31 and 32.</p> <p>Over mountainous land, through moderate undergrowth.</p> <p>Distance by triangulation.</p>	
4.70	<p>Spur, slopes NE.; desc. along E. slope.</p>	
14.70	<p>Ravine, drains N. 70° E., asc. SE. slope.</p>	
25.90	<p>Spur, slopes N. 60° E.; end of triangulation.</p>	
36.20	<p>Small ravine, drains NE.; asc. SE. slope.</p>	
39.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS		
	<p>T7S R23E $\frac{1}{2}$ S31 S32 1967</p> <p>Cor. falls on a steep SE. slope.</p>	
47.40	Spur, slopes NE.; desc N. slope.	
57.00	Mexican Canyon, drains NE.	
73.60	Spur, slopes NE.	
78.00	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; unable to find any remaining evidence of the original corner.	
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.	
	<p>T7S R23E $\frac{1}{2}$ S30 S29 S31 S32 1967</p> <p>Cor. falls on steep NW. slope.</p> <p>Land, mountainous. Soil, rocky. Timber, juniper, oak, pine. Undergrowth, cat claw, manzanita, scrub oak and grass.</p>	
	From the cor. of secs. 28, 29, 32 and 33.	
	S. 89° 49' W., bet. secs. 29 and 32.	
	Over mountainous land, through moderate undergrowth.	
2.10	Top of mountain, bears NE. and SW.; desc. over steep W. slope.	
34.00	Wash in Little Righthand Canyon, drains N. 5° E.; asc. NE. slope.	
38.00	Jeep road, bears N. and S.	
40.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate dist.; unable to find any remaining evidence of the original corner.	
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.	
	<p>T7S R23E $\frac{1}{4}$ S29 S32 1967</p>	
54.50	Spur, slopes N. 20° E.; desc. NW. slope.	
63.70	Wash in bottom of Mexican Canyon, 30 lks. wide, 2 ft. deep, drains N. 20° E., asc. E. slope.	
79.00	Spur, slopes NE.; desc. along NW. slope.	
80.46	The cor. of secs. 29, 30, 31 and 32.	

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	Land, mountainous. Soil, rocky. Timber, juniper and scattered mesquite. Undergrowth, manzanita, scrub oak, cacti and grass.
	<p>S. 86° 08' W., bet. secs. 30 and 31.</p> <p>Over mountainous land, through moderate undergrowth.</p>
5.20	Ravine, drains N. 30° E.
14.70	Ravine, drains NE.
33.70	Wash in bottom of Wide Mouth Canyon, 40 lks. wide, 5 ft. deep, drains NE.; asc. steep E. slope.
39.70	Spur, slopes NE.
40.25	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T7S R23E</p> <p>¼ <u>S30</u></p> <p>S31</p> <p>1967</p>
42.10	Ravine, drains NE.
70.60	High spur, slopes N. 20° E., desc. NW. slope.
71.80	Fence, bears N. 30° E. and S. 30°W.
78.90	The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp.
	<p>Land, mountainous. Soil, rocky. Timber, juniper, pine, and oak. Undergrowth, manzanita, scrub oak, cacti and grass.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 3° 31' E., bet. secs. 29 and 30.</p> <p>Over mountainous land, through moderate undergrowth; desc. NW. slope.</p>
22.40	Ravine, drains NE.
27.30	Spur, slopes NE.; desc. N. slope.
38.97	Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>T7S R23E $\frac{1}{4}$ S30 S29 1967</p>
47.50	Wash in bottom of Wide Mouth Canyon, 25 lks. wide, 5 ft. deep, drains NE.
69.00	Fence, bears E. and W. 4.30 chs. dist., thence N.
77.94	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a granite stone, 17x12x7 ins., set 8 ins. in the ground, mkd. 2 notches on S. face and 5 notches on E. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;"> T7S R23E S19 S20 S30 S29 1967 </p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. Timber, juniper, mesquite and oak. Undergrowth, cat claw, scrub oak and grass.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 41' W., bet. secs. 20 and 29.</p> <p>Over mountainous land, through moderate undergrowth; desc. NW. slope.</p>
3.80	Wash in Mexican Canyon, drains N. 15° E.; asc. SE. slope.
11.20	Ravine, drains NE.; continue asc.
34.88	Fence, bears NE. and SW.
37.30	Spur, slopes SW.; desc. W. slope.
40.53	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate dist.; unable to find any remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T7S R23E $\frac{1}{4}$ <u>S20</u> S29 1967 </p>
61.10	Wash in bottom of Wide Mouth Canyon, 20 lks. wide, 3 ft. deep, drains N. 20° E.; asc. E. slope.
77.30	Jeep road, bears SE. and NW.
80.00	Spur, slopes N.; desc. NW. slope.
81.06	The cor. of secs. 19, 20, 29 and 30.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Land, mountainous. Soil, rocky. Timber, mesquite and scattered juniper. Undergrowth, cacti, cat claw and grass.</p>
	<p>S. 88° 23' W., bet. secs. 19 and 30. Over mountainous land, through moderate undergrowth.</p>
4.30	Fence, bears N. and S.
20.80	Wash, 20 lks. wide, 3 ft. deep, drains N.; asc. NE slope.
24.80	Wash, 15 lks. wide, 2 ft. deep, drains NE.
37.20	Spur, slopes N.; desc. NW. slope.
41.27	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate dist.; unable to find any remaining evidence of the original corner. Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T7S R23E ¼ <u>S19</u> S30 1967</p>
53.90	Ravine, drains NE.
65.00	Ravine, drains N. 25° E.
69.50	Ravine, drains N.; asc. E. slope.
76.30	Spur, slopes N.; desc. NW. slope.
80.92	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp. Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, cacti, cat claw and grass.
	<p>From the cor. of secs. 19, 20, 29 and 30. N. 0° 37' W., bet. secs. 19 and 20. Over rolling land, through moderate undergrowth.</p>
10.50	Jeep road, bears S. 15° E. and N. 15° W.
39.74	The ¼ sec. cor. of secs. 19 and 20, monumented by a granite stone, 21x12x10 ins., set 10 ins. in the ground, mkd. ¼ on W. face, mound of stone W. At the corner point Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

Dep. Resurvey, Subdivision, T. 7S., R. 23 E., Arizona

CHAINS	
	T7S R23E $\frac{1}{4}$ S19 S20 1967
	Deposit the orig. cor. stone alongside the iron post
	—————
	N. 0° 31' E , beginning new measurement.
	Over rolling land, through moderate undergrowth.
31.70	Fence, bears N. 70° E. and S. 70° W.
34.00	Center of stock tank, approx. 5.00 chs. wide and 5.00 chs. long, located in Tunnel Canyon.
40.10	Point for the cor. of secs. 17, 18, 19 and 20, at propor- tionate dist.; unable to find any remaining evidence of the orig. corner.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R23E <u>S18 S17</u> <u>S19 S20</u> 1967
	from which
	Corner of fences bearing S. and W., bears S. 6° 07' W , 5.13 chs. dist.
	Land, rolling. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89° 12' W., bet. secs. 17 and 20.
	Over rolling land, through moderate undergrowth.
4.90	Fence, bears N. and S.
6.70	Track road, bears NE. and SW.
23.30	Wash, 10 lks. wide, 2 ft. deep, drains N.
33.60	Wash, 30 lks. wide, 3 ft. deep, drains N.
40.19	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at propor- tionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.
	T7S R23E $\frac{1}{4}$ S17 S20 1967
45.80	Spur, slopes N.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
55.50	Ravine, drains N.
73.10	Wash in bottom of Tunnel Canyon, 30 lks. wide, 3 ft. deep, drains N.; asc. E. slope.
80.38	The cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, cresote, cacti and grass.
	S. 89° 48' W., bet. secs. 18 and 19.
	Over rolling land, through moderate undergrowth.
2.30	Track road, bears NE. and SW.; asc. over E. slope.
40.44	The ¼ sec. cor. of secs. 18 and 19, monumented by a granite stone, 17x10x8 ins., set 8 ins. in the ground, mkd. ¼ on N. face, mound of stone alongside.
	At the corner point.
	Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R23E ¼ S18 ——— S19 1967
	Deposit the orig. cor. stone alongside the iron post.
	Cor. falls on spur sloping N. 30° E.
	—————
	S. 87° 21' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
12.50	Wash, 20 lks. wide, 4 ft. deep, drains NE.
30.00	Spur, slopes NE.; desc. NW. slope.
40.55	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.
	Land, rolling. Soil, rocky. No timber; Undergrowth, cacti and grass.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 1° 30' W., bet. secs. 17 and 18.
	Over rolling land, through moderate undergrowth.
1.80	Track road, bears NE. and SW.
38.70	Wash, 15 lks. wide, 2 ft. deep, drains E.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS		
40.12	<p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented by an iron post $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S18 S17 1960</p> <p>This cor. was remonumented under the Forest Service remonumentation program by L. Mann.</p>	
	<p>_____</p>	
	<p>N. $1^{\circ} 18'$ W., beginning new measurement.</p>	
	<p>Over rolling land, through moderate undergrowth.</p>	
2.70	<p>Wash, 15 lks. wide, 2 ft. deep, drains NE.</p>	
17.30	<p>Track road, bears SE. and NW.</p>	
21.70	<p>Wash, 25 lks. wide, 2 ft. deep, drains NE.</p>	
39.92	<p>The cor. of secs. 7, 8, 17 and 18, monumented by a granite stone, 12x10x8 ins., set 6 ins. in the ground, mkd. 5 notches on E. face and 4 notches on S. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E S 7 S8 S18 S17 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, cresote, cat claw and grass.</p>	
	<p>From the cor. of secs. 8, 9, 16 and 17.</p>	
	<p>S. $88^{\circ} 32'$ W., bet. secs. 8 and 17.</p>	
	<p>Over rolling land, through moderate undergrowth.</p>	
7.00	<p>Wash, 10 lks. wide, 2 ft. deep, drains N.</p>	
10.30	<p>Wash, 15 lks. wide, 3 ft. deep, drains NE.</p>	
28.65	<p>Track road, bears NE. and SW.</p>	
42.73	<p>The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented by a granite stone, 10x6x5 ins., set 5 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p style="text-align: center;">T7S R23E $\frac{1}{4}$ <u>S 8</u> S17 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 30' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>9.90 Wash, 10 lks. wide, 2 ft. deep, drains NE.</p> <p>16.30 Wash, 20 lks. wide, 3 ft. deep, drains N. 70° E.</p> <p>39.45 The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, cresote, cat claw and grass.</p>
	<hr/> <p>S. 89° 53' W., bet. secs. 7 and 18.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>8.20 Mesa Road, bears N. 20° E. and S. 20° W.</p> <p>11.80 Fence, bears N. 28° E. and S. 28° W.</p> <p>39.74 The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented by a granite stone, 18x10x6 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ <u>S 7</u> S18 1967</p> <p>from which</p> <p style="padding-left: 40px;">Fence, bearing E. and W., bears South, 325 lks. dist.</p> <p>Bury the orig. cor. stone alonside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 85° 42' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>7.20 Bear Springs Wash, 15 lks. wide, 2 ft. deep, drains NE.</p> <p>14.10 Stock tank, bears south, 4.00 chs. dist.</p> <p>21.10 Wash, 20 lks. wide, 6 ft. deep, drains N. 20° E.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E. Arizona

CHAINS	
36.70	Matthews Wash, 10 lks. wide, 3 ft. deep, drains NE.
37.85	Fence, bears N. and S.
39.16	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp.
	Land, rolling. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°20' E., bet. secs. 7 and 8.
	Over rolling land, through moderate undergrowth.
13.80	Wash, 15 lks. wide, 3 ft. deep, drains N. 30° E.
19.50	Mesa Road, bears N. 44°15' E. and S. 34° W.
20.70	Fence, bears N. 40° E. and S. 40° W.
26.90	Bear Springs Wash, 30 lks. wide, 3 ft. deep, drains NE.
27.90	Jeep Road, bears NE. and SW.
40.27	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate dist.; unable to find any remaining evidence of the original corner.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T7S R23E $\frac{1}{4}$ S 7 S 8 1967
	Raise a mound of stone W. of the corner.
49.70	Leave rolling land, desc. over broken land.
63.50	Matthews Wash, 120 lks. wide, 2 ft. deep, drains NE.
80.54	The cor. of secs. 5, 6, 7 and 8, monumented by a granite stone 15x8x8 ins., set 8 ins. in the ground, mkd. 5 notches on S. face and 5 notches on E. face.
	At the corner point
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T7S R23E S 6 S 5 S 7 S 8 1967
	Bury the orig. cor. stone alongside the iron post.

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Land, rolling to broken. Soil, rocky loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9. N. 89°59' W., bet. secs. 5 and 8. Over broken land, through moderate undergrowth.</p> <p>39.48 Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate dist.; unable to find any remaining evidence of the original corner. Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ $\frac{S\ 5}{S\ 8}$ 1967</p> <p>Cor. falls on a S. slope of ridge bearing E. and W.</p> <p>58.60 Wash, 50 lks. wide, 2 ft. deep, drains NW.</p> <p>67.30 Matthews Wash, 60 lks. wide, 2 ft. deep, drains N.</p> <p>78.96 The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, broken. Soil, clay loam. Timber, mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>
	<p>S. 86°57' W., bet. secs. 6 and 7. Over broken land, through moderate undergrowth.</p> <p>40.53 Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate dist.; unable to find any remaining evidence of the original corner. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R23E ¼ $\frac{S\ 6}{S\ 7}$ 1967</p> <p>43.70 Wash, 10 lks. wide, 3 ft. deep, drains NE.</p> <p>48.30 Wash, 20 lks. wide, 2 ft. deep, drains N.</p> <p>73.20 Wash, 50 lks. wide, 3 ft. deep, drains NW.</p> <p>79.16 The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS	
	<p>Land, broken. Soil, clay loam. Timber, mesquite. Undergrowth, cacti, cresote, cat claw and grass.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8. N. 0° 20' W., bet. secs. 5 and 6. Over broken land, through moderate undergrowth.</p>
19.60	Wash, 30 lks. wide, 4 ft. deep, drains E.
32.00	Enter nearly level mesa.
40.39	<p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented by a granite stone, 15x10x6 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R23E $\frac{1}{4}$ S 6 S 5 1967</p> <p>Bury the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 18' W., beginning new measurement. Over nearly level mesa, through moderate undergrowth.</p>
11.10	Leave mesa, desc. NW. slope.
30.60	Fence, bears N. 55° E. and S. 55° W.
31.80	Wash, 20 lks. wide, 1 ft. deep, drains NE.
38.43	<p>The cor. of secs. 5 and 6 only, on the N. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. in diam., set, mkd. and witnessed as described in the concurrent resurvey of T. 6 S., R. 23 E., under this same group.</p> <p>Land, broken to nearly level. Soil, clay loam. Timber, mesquite. Undergrowth, cacti, cresote, cat claw and grass.</p>
General Description	
<p>Township 7 South, Range 23 East is located on the most north slope of the Pinaleno Mountains. The land varies from high broken in the southern portion to low rolling and nearly level in the northern portion of the township. The general elevation ranges from 3,000 feet, above sea level to 7,500 feet at its highest point in section 31.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 23 E., Arizona

CHAINS

The soil in the northern part of the township is mostly clay loam, the central and southern part is rocky. There is a heavy stand of pine, pinon and juniper over most of the mountainous region. Undergrowth consists of scrub oak, manzanita, cacti and grass over the mountain land and cacti, cresote, cat claw and mesquite in the lower lands.

There are numerous dirt roads through out the township, the main road being Mesa Road which bears westerly across the upper portion of the township entering in section 12, leaving in section 18.

There are a few stock tanks throughout the township, furnishing water for grazing, which is the primary interest.

The general drainage is to the Northeast.

62

CERTIFICATE OF SURVEY

We, Kenneth D. Herman and Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of January, 1967, We have dependently resurveyed the east, south and west boundaries and the subdivisional lines of Township 7 South, Range 23 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 28, 1968 (Date)
March 28, 1968 (Date)
(Date)

Kenneth D. Herman (Cadastral Surveyor)
Gary T. Oviatt (Cadastral Surveyor)
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date DEC 19 1969

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the east, south and west boundaries and the subdivisional lines of Township 7 South, Range 23 East, Gila and Salt River Meridian, Arizona.

executed by Kenneth D. Herman and Gary T. Oviatt
having been critically examined and found correct, are hereby approved.

MAR 2 1971 (Date)

Clark F. Sumner (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

Chief, Division of Cadastral Survey