

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY
of the
NORTH BOUNDARY (THE FIRST STANDARD PARALLEL SOUTH), the
EAST, SOUTH and WEST BOUNDARIES
and the
SUBDIVISIONAL LINES

TOWNSHIP 6 SOUTH, RANGE 23 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Kenneth D. Herman, Cadastral Surveyor
Gary T. Oviatt, Cadastral Surveyor

Under special instructions dated January 30, 19 67, which provided for the surveys
included under Group Number 451, approved January 30, 1967,
and assignment instructions dated January 30, 19 67.

Survey commenced February 1, 19 67
Survey completed March 17, 19 67

1A

BOOK 4878

INDEX DIAGRAM

		Township 6 SOUTH				Range 23 EAST			
		2($\frac{1}{4}$)	3($\frac{1}{4}$)	3($\frac{1}{4}$)	4($\frac{1}{4}$)	5($\frac{1}{4}$)	6	1st STANDARD PARALLEL SOUTH	
28	81($\frac{1}{4}$)	79	67($\frac{1}{4}$)	57($\frac{1}{4}$)	47($\frac{1}{4}$)	38($\frac{1}{4}$)			
	6	5	4	3	2	1	12		
	79	78	65	56	46	36			
27	7	77	65	55	45	35	11		
	77	8	9	10	11	12			
	77	76	64	54	44	34			
26	18	75	63	53	43	33	10		
	17	16	15	14	13	12			
	74	74	62	53	43	33			
5	19	73	61	52	41	32	9		
	20	21	22	23	24	25			
	72	71	60	51	41	31			
24	30	70	59	50	40	31	8		
	29	28	27	26	25	24			
	69	69	58	49	39	30			
23	31	67	58	48	38	29	7		
	32	33	34	35	36	36			
	21	20	18	17	15	14			

Township 6 South, Range 23 East
Gila and Slat River Meridian, Arizona

CHAINS

The south boundary was surveyed in 1884 by L. Wolfley. The north boundary (the First Standard Parallel South) and the east boundary was surveyed in 1875 by T. F. White. The west boundary and subdivisional lines were surveyed and the north, south and east boundaries resurveyed in 1900 by P. Contzen. The east boundary was resurveyed in 1916 by A. B. Rich and iron posts set on the north five miles, referring to Township 6 South, Range 24 East only, with iron posts on the south one mile set as common corners. The standard quarter section corner of section 36, Township 5 South, Range 23 East, was also remonumented with an iron post in 1916. The west boundary was retraced in 1924 by G. F. Sawyer.

The following notes are those of a dependent resurvey of the north boundary (the First Standard Parallel South), the east, south and west boundaries, and the subdivisional lines of Township 6 South, Range 23 East, Gila and Salt River Meridian, Arizona, designed to restore the corners in their true original location according to the best available evidence.

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated January 30, 1967.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude, 32°51'38" North and Longitude, 109°56'10" West. Calculated from a direct tie made to Triangulation Station MAT, located near the center of section 11.

The mean magnetic declination was found to be 13½° East.

Dependent Resurvey, First Standard Parallel South through Range 23 East

Reestablishment of the Resurvey Executed by P. Contzen in 1900

The standard cor. of T. 5 S., Rs. 22 and 23 E., monumented by a limestone, 26 x 12 x 6 ins., set 12 ins. in the ground, mkd. with 5 notches only on the E. face, and with a squared 4 x 4 wooden post set alongside.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

S C
T5S
R22E R23E
S 36 | S 31
1967

Dep. Resurvey, 1st Stan. Par. S., T. 5 S., R. 23 E., Arizona

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Reset the wooden post, alongside the cor.</p> <p>N. 89°57' E., along the S. bdy. of sec. 31.</p> <p>Over rolling land, through moderate undergrowth.</p>
9.60	<p>Center of wash area, 360 lks. wide, 2 ft. deep, drains NE.</p>
39.79	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented by a limestone, 9 x 9 x 3 ins., loosely set, dimly mkd. $\frac{1}{4}$ on N. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">S C T5S R23E $\frac{1}{4}$ S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1967</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>
	<p style="text-align: center;">S. 89°50' E., beginning new measurement.</p>
32.40	<p>Over gently rolling land, through moderate undergrowth.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains NE.</p>
39.92	<p>The standard cor. of secs. 31 and 32, monumented by a limestone, 18 x 12 x 4 ins., set 10 ins. in the ground, mkd. with 5 notches, only on E. face, from which the remains of the original bearing tree:</p>
	<p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N. 28° E., 44 lks. dist., mkd. T5S R23E S 32 BT.</p>
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">S C T5S R23E S31 S32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1967</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti and sagebrush.</p>

CHAINS	
	<p>S. 89°55' E., along the S. bdy. of sec. 32.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
27.50	Fence, bears N. and S.
39.65	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented by a mesquite post, 15 ins. long, 3 ins. diam., loosely set, scribed SC on a face; other remains of the post was found under the surface.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S C T5S R23E <u>$\frac{1}{4}$ S 32</u> 1967</p> <p>Reset the wood post, inverted, alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 89°54' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
3.40	Wash, 60 lks. wide, 2 ft. deep, drains NE.
15.30	Wash, 25 lks. wide, 1 ft. deep, drains N. 30° E.
39.82	<p>The standard cor. of secs. 32 and 33, monumented by a granite stone, 14 x 9 x 6 ins., set 6 ins. in the ground, mkd. SC on N., 4 notches on E., and 2 notches on W. faces.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S C T5S R23E <u>S32 S 33</u> 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, cresote, cacti and sagebrush.</p>
	<p>S. 89°58' E., along the S. bdy. of sec. 33.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
.10	Fence, bears S. 58° E. and N. 58° W.
39.70	Wash, 80 lks. wide, 1 ft. deep, drains N. 15° W.

Dep. Resurvey, 1st Stan. Par. S., T. 5 S., R. 23 E., Arizona

CHAINS		
39.78	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 33, at proportionate dist.; this point falls in a wash, in an unsafe position.</p>	
	<p style="text-align: center;">_____</p> <p>S. 89°52' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	
2.34	<p>The witness standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented by a granite stone, 12 x 8 x 6 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ 33 on N., dimly mkd. WC. on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">S C T5S R23E ← $\frac{1}{4}$ S 33 WC 1967</p>	
	<p>Bury the orig. cor. stone alongside the iron post.</p>	
	<p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>	
9.00	<p>Enter wash area, draining NE.</p>	
24.00	<p>Leave wash area, draining NE.</p>	
37.30	<p>Wash, 10 lks. wide, 1 ft. deep, drains NE.</p>	
39.85	<p>The standard cor. of secs. 33 and 34, monumented by a limestone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. 3 notches, only, on W. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">S C T5S R23E <u>S33 S 34</u> 1967</p>	
	<p>Bury the orig. cor. stone alongside the iron post.</p>	
	<p>Set a mesquite post, 4½ ft. long, 4 ins. diam., alongside the cor.</p>	
	<p>Land, rolling. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, creosote, cacti and sagebrush.</p>	
39.84	<p>S. 89°51' E., along the S. bdy. of sec. 34.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The standard $\frac{1}{4}$ sec. cor. of sec. 34, monumented by a limestone, 14 x 6 x 6 ins., loosely set; no legible marks. I accept this as the best available evidence of the orig. cor.</p>	

Dep. Resurvey, 1st Stan. Par. S., T. 5 S., R. 23 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S C T5S R23E <u>½ S 34</u> 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3½ ft. long, 3 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°57' E., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
18.30	Track road, bears N. 60° E. and S. 60° W.
39.92	<p>The standard cor. of secs. 34 and 35, monumented by a limestone, 10 x 7 x 8 ins., loosely set, mkd. with 2 notches on E. and W. faces, from which the remains of the original bearing tree.</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N. 70° W., 140 lks. dist., mkd. with an old blaze. (Record N. 68½° W., 140 lks. dist.)</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S C T5S R23E <u>S34 S35</u> 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a squared wood post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, creosote, cacti and sagebrush.</p>
16.30	<p>S. 89°57' E., along the S. bdy. of sec. 35.</p> <p>Over gently rolling land, through moderate undergrowth</p>
20.00	Wash, 150 lks. wide, 3 ft. deep, drains irregularly E.
	Wash, 150 lks. wide, 4 ft. deep, drains NE.
39.74	<p>The standard ¼ sec. cor. of sec. 35, monumented by a limestone, 18 x 10 x 6 ins., set 10 ins. in the ground, no legible marks. I accept this as the best available evidence of the orig. cor.</p> <p>At the corner point</p>

Dep. Resurvey, 1st Stan. Par. S., T. 5 S., R. 23 E., Arizona

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S C T5S R23E <u>¼ S 35</u> 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a squared wood post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 89°58' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	
9.00	Enter rough and broken land.	
37.90	Top of ridge, bears E. and W.; desc. E. slope.	
39.73	The standard cor. of secs. 35 and 36, monumented by a sandstone, 16 x 8 x 8 ins., set 10 ins. in the ground, mkd. SC, on N. face.	
	At the corner point	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p>S C T5S R23E <u>S35 S36</u> 1967</p>	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <p>Land, rolling to rough and broken. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti and sagebrush.</p>	
	<p>S. 89°57' E., along the S. bdy of sec. 36.</p> <p>Over rough and broken land, through moderate undergrowth.</p>	
6.00	Ridge, bears S. 60° E. and N. 60° W.	
11.60	Wash, 10 lks. wide, 1 ft. deep, drains SE.	
23.00	Descend along a S. slope.	
40.55	The standard ¼ sec. cor. of sec. 36, monumented by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1916 resurvey.	
	<hr style="width: 10%; margin: 10px auto;"/> <p>S. 89°45' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	

Dep. Resurvey, East Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
23.20	Leave rolling land; enter nearly level land.
39.22	The standard cor. of Tp. 5 S., Rs. 23 and 24 E., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1916 resurvey. Land, rolling to nearly level land. Soil, gravelly loam. No timber. Undergrowth, creosote, cacti and sagebrush.
Dependent Resurvey, East Boundary Township 6 South, Range 23 East	
Reestablishment of the Resurvey Executed by A. B. Rich in 1916	
	From the cor. of Tps. 6 and 7 S., Rs. 23 and 24 E., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey in 1916. N. 0°04' E., bet. secs. 31 and 36. Over nearly level land, through moderate undergrowth.
2.50	Dirt road, bears N. 38° E. and S. 10° W.
26.80	Wash, 20 lks. wide, 2 ft. deep, drains N. 60° E.
36.20	Fence, bears N. 70° E. and S. 70° W.
40.09	The 1/2 sec. cor. of secs. 31 and 36, monumented by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916. This iron post, having deteriorated considerably, was replaced with a new iron post set 22 ins. in the ground, brass cap mkd.
	T6S R23E R24E 1/2 S36 S31 1967
	Reset the original iron post, inverted, and a mesquite post, 3 1/2 ft. long, 4 ins. diam., alongside the cor. N. 0°04' E., beginning new measurement. Over nearly level land, through moderate undergrowth.
3.40	Wash, 20 lks. wide, 10 ft. deep, drains N. 70° E.
12.60	Canal, 30 lks. wide, 4 ft. deep, drains NE.
14.50	Fence, bears N. 70° E. and S. 70° W.; enter railed area.

Dep. Resurvey, East Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
26.30	Track road, bears N. 30° E. and S. 30° W.
40.11	<p>The cor. of secs. 25, 30, 31 and 36, monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.</p> <p>Land, nearly level. Soil, gravelly and sandy loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cat claw.</p>
	<p>N. 0°03' E., along the W. bdy. of sec. 30, T. 6S, R. 24 E.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
31.10	Wash, 30 lks. wide, 2 ft. deep, drains NE.
39.84	Fence, bears S. 76° E. and NW.
39.96	<p>Point for the ¼ sec. cor. of sec. 30, T. 6S., R. 24 E., at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T6S R23E R24E ¼ S30 1967</p>
	<p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the iron post.</p>
	<p>N. 0°04' E., beginning new measurement.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
.27	<p>Point for the ¼ sec. cor. of sec. 25, T. 6 S., R. 23 E., at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T6S R23E R24E ¼ S25 1967</p>
	<p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the iron post.</p>
10.10	Canal, 30 lks. wide, 4 ft. deep, drains E.
26.40	Wash, 50 lks. wide 2 ft. deep, drains NE.
30.10	Matthews Wash, 60 lks. wide, 2 ft. deep, drains NE.
35.90	Wash, 130 lks. wide, 2 ft. deep, drains NE.
39.84	<p>The cor. of secs. 19 and 30, T. 6 S., R. 24 E., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as</p>

Dep. Resurvey, East Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.</p> <p>Land, nearly level. Soil, clay loam. Timber, mesquite. Undergrowth, creosote, cat claw and sagebrush.</p>
	<p>N. 0°03' E., along the W. bdy. of sec. 19, T. 6 S., R. 24 E.</p> <p>Over nearly level land, through moderate undergrowth.</p>
.54	<p>The cor. of secs. 24 and 25, T. 6 S., R. 23 E., monumented by a granite stone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. 4 notches on N. and 2 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E R24E S24 S19 S25 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>
2.00	<p>Man made rock wall for erosion control, approximately 300 lks. in length, bears E. and W.</p>
31.80	<p>Track road, bears N. 30° E. and S. 30° W.</p>
39.75	<p>Point for the ¼ sec. cor. of sec. 19, T. 6 S., R. 24 E., at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E R24E ¼ S19 1967</p> </div> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
.91	<p>Point for the ¼ sec. cor. of sec. 24, T. 6 S., R. 23 E., at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>

Dep. Resurvey, East Boundary, T. 6 S., R. 23 E., Arizona

CHAINS		
39.48	<p style="text-align: center;">T6S R23E R24E $\frac{1}{4}$ S24 1967</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>The cor. of secs. 18 and 19, T. 6 S., R. 24 E., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.</p> <p>The cor. is located at a fence cor.; fences bear N. 24° 36' E., S. 2°10' W. and N. 86°40' W.</p> <p>Land, nearly level. Soil, clay loam. No timber; undergrowth, creosote sagebrush and cat claw.</p>	
1.54	<p>N. 0°04' E., along the W. bdy. of sec. 18, T. 6 S., R. 24 E.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The cor. of secs. 13 and 24, T. 6 S., R. 23 E., monumented by a granite stone, 14 x 10 x 8 ins., set 8 ins. in the ground, mkd. 3 notches on N. and S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
39.87	<p style="text-align: center;">T6S R23E R24E S13 S 18 S24 1967</p> <p>Set a mesquite post, 4 ft. long, 3½ ins. diam., alongside the cor.</p> <p>The ¼ sec. cor. of sec. 18, T. 6 S., R. 24 E., monumented by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.</p> <p>Cor. is located in cor. of fences bearing S. 26° E. and N., 32 lks. dist. to cor. of fences bearing N., N. 64° E. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' E., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
1.77	<p>The ¼ sec. cor. of sec. 13, T. 6 S., R. 23 E., monumented by a granite stone, 10 x 8 x 4 ins., set 5 ins. in the ground, mkd. ¼ 13 on W. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	

Dep. Resurvey, East Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
40.07	<p style="text-align: center;">T6S R23E R24E 1/4 S13 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Cor. is located in a fence line, bearing N. and S.</p> <p>The cor. of secs. 7 and 18, T. 6 S., R. 24 E., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.</p> <p>Cor. is located in a fence line, bearing N. and S.</p> <p>Land, nearly level. Soil, clay loam. No timber; undergrowth, creosote and sagebrush.</p>
1.85	<p>N. 0°01' W., along the W. bdy. of sec. 7, T. 6 S., R. 24 E.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The cor. of secs. 12 and 13, T. 6 S., R. 23 E., monumented by a limestone, 14 x 8 x 4 ins., set 6 ins. in the ground, mkd. 4 notches on S. and 2 notches on N. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E R24E S12 S7 S13 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Cor. is located in a fence line, bearing N. and S.</p> <p>9.20 Hunsacker Wash, 30 lks. wide, 4 ft. deep, drains N. 70° E.</p> <p>15.80 Wash, 20 lks. wide, 2 ft. deep, drains irregularly E.</p> <p>39.50 Corner of fences, bearing N. 20° E. and S.</p> <p>39.87 The 1/4 sec. cor. of sec. 7, T. 6 S., R. 24 E., monumented by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>

Dep. Resurvey, East Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
2.20	<p>The $\frac{1}{4}$ sec. cor. of sec. 12, T. 6 S., R. 23 E., monumented by a limestone, 14 x 8 x 6 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ 12 on W. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E R24E $\frac{1}{4}$ S12 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>
9.50	Top of ridge, bears E. and W.
23.10	Ridge, bears NE. and W.
26.80	Ridge, bears NE. and SW., desc. N. slope.
39.19	<p>The cor. of secs. 6 and 7, T. 6 S., R. 24 E., monumented by an iron post 3 ins. diam., lying on the ground. I reset the iron post 18 ins. in the ground, mound of stone to top, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.</p> <p>Land, nearly level to rolling. Soil, clay and gravelly loam. No timber; undergrowth, creosote, cat claw and sagebrush.</p>
	<p>N. 0°05' W., along the W. bdy. of sec. 6, T. 6 S., R. 24 E.</p> <p>Over rolling land, through moderate undergrowth.</p>
2.75	<p>The cor. of secs. 1 and 12, T. 6 S., R. 23 E., monumented by limestone, 14 x 10 x 6 ins., set 10 ins. in the ground, no legible mks. I accept this as the best available evidence of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E R24E S 1 S 6 S12 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>
9.90	Wash, 20 lks. wide, 1 ft. deep, drains irregularly E.
13.80	Base of ridge, bears irregularly E. and W., asc. S. slope.

Dep. Resurvey, East Boundary, T. 6 S., R. 23 E., Arizona

CHAINS

- 24.60 Bladed road, on top of ridge, bears N. 63° E. and S. 63°W., desc. N. slope to nearly level land.
 - 39.70 The ¼ sec. cor. of sec. 6, T. 6 S., R. 24 E., monumented by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.
-
- N. 0°04' E., beginning new measurement.
 - Over nearly level land, through moderate undergrowth.
 - 3.18 The ¼ sec. cor. of sec. 1, T. 6 S., R. 23 E., monumented by a limestone, 14 x 14 x 3 ins., set 8 ins. in the ground, mkd. ¼ S 1 on W. face.
 - At the corner point
 - Set the iron post 24 ins. in the ground, brass cap mkd.
- T6S
R23E R24E
¼ |
S 1 |
1967
- Bury the orig. cor. stone alongside the iron post.
 - Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.
 - 10.20 Aravaipa and Klondike Road, bears N. 70° E. and S. 70° W.
 - 15.40 Wash, 15 lks. wide, 1 ft. deep, drains irregularly E.
 - 20.20 Wash, 20 lks. wide, 2 ft. deep, drains irregularly E.
 - 34.20 Track Road, bears irregularly E. and W.
 - 39.93 Intersect the First Standard Parallel South.
 - The closing cor. of Tps. 6 S., Rs. 23 and 24 E., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 24 E. in 1916.
 - from which
 - The Standard Cor. of Tps. 5 S., Rs. 23 and 24 E., bears S. 89°45' E., 25.70 chs. dist.
 - Land, rolling to nearly level.
 - Soil, gravelly loam.
 - No timber; undergrowth, creosote, cat claw and cacti.

Dependent Resurvey, South Boundary
Township 6 South, Range 23 East

Reestablishment of the Resurvey
Executed by P. Contzen in 1900

From the cor. of Tps. 6 and 7 S., Rs. 23 and 24 E.

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
	S. 89°55' W., bet. secs. 1 and 36. Over nearly level land, through moderate undergrowth.
.60	Dirt Road, bears N. 10° E. and S. 10° W.
6.70	Wash, 20 lks. wide, 3 ft. deep, drains N.
17.40	Small creek course irregularly N.
20.045	Point for the E 1/16 sec. cor. of secs. 1 and 36. Set the iron post 24 ins. in the ground, brass cap mkd.
	T6S R23E $\frac{E \ 1}{1 \ 6} \quad \frac{S \ 36}{S \ 1}$ T7S 1967
	Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.
23.40	Fence, bears N. 10° E. and S. 10° W.
24.60	Wash, 10 lks. wide, 6 ft. walls, drains N. 5° E.
37.50	Enter open erroded land.
40.09	The ¼ sec. cor. of secs. 1 and 36, monumented by a granite stone, 20 x 8 x 8 ins., set 10 ins. in the ground, mkd. ¼ 36 on N. and 1 on S. faces. At the corner point Set the iron post 22 ins. in the ground, brass cap mkd.
	T6S R23E $\frac{\frac{1}{4}S \ 36}{S \ 1}$ T7S 1967
	Bury the orig. cor. stone alongside the iron post. Raise a mound of stone N. of the cor.
	<hr style="width: 20%; margin: 0 auto;"/>
	S. 89°57' W., beginning new measurement. Over erroded land.
18.00	Small creek, course N. 20° E.
20.065	Point for the W 1/16 sec. cor. of secs. 1 and 36. Set the iron post 22 ins. in the ground, brass cap mkd.
	T6S R23E $\frac{W \ 1 \ S \ 36}{16 \ S \ 1}$ T7S 1967
	Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS					
40.13	<p>The cor. of secs. 1, 2, 35 and 36, monumented by a granite stone, 18 x 8 x 6 ins., loosely set, mkd. with 5 notches on W. and 1 notch on E. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <table border="1" style="margin: auto;"> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> </table> <p>T7S 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Deposit glass in the hole at the base of the iron post.</p> <p>Land, nearly level. Soil, clay loam. Timber, scattered mesquite. Undergrowth, creosote, cat claw and sagebrush.</p>	S 35	S 36	S 2	S 1
S 35	S 36				
S 2	S 1				
.20	<p>S. 89°47' W., along the S. bdy. of sec. 35.</p>				
	<p>Over nearly level land, through moderate undergrowth.</p>				
	<p>Fence, bears N. 0°07' E. and S. 0°07' W.</p>				
9.20	<p>Wash, 20 lks. wide, 10 ft. walls, drains N. 40° E.</p>				
16.70	<p>Track road, bears N. 30° E. and S. 50° W.</p>				
32.70	<p>Wash, 20 lks. wide, 2 ft. deep, drains N. 30° E.</p>				
39.76	<p>The ¼ sec. cor. of sec. 2, T. 7 S., R. 23 E., monumented by a granite stone, 15 x 10 x 8 ins., set 8 ins. in the ground, mkd. ¼ S 2 on the S. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S</p> <hr style="width: 50px; margin: auto;"/> <p>¼ S 2</p> <p>T7S R23E</p> <p>1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p>				
40.06	<p>The ¼ sec. cor. of sec. 35, T. 6 S., R. 23 E., monumented by a limestone, 10 x 8 x 6 ins., set 6 ins. in the ground, dimly mkd. 35 on N. face.</p>				

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E <u>1/2 S 35</u> T7S 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 89°53' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
36.40	Wash, 50 lks. wide, 2 ft. deep, drains N. 25° E.
38.21	<p>The witness cor. of secs. 2 and 3, T. 7 S., R. 23 E., monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. 2, 3 and WC on the S., 4 notches on W. and 2 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S ← S 35 W S 3 S 2 C T7S R23E 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>
39.19	True point for the cor. of secs. 2 and 3, T. 7 S., R. 23 E., at proportionate dist., falls in Matthews Wash, in an unsafe position.
39.70	Center of Matthews Wash, 170 lks. wide, 1 ft. deep, drains NE.
40.12	<p>True point for the cor. of secs. 34 and 35, at proportionate dist.; falls in Matthews Wash, in an unsafe position.</p> <p>from which</p> <p style="text-align: center;">The witness cor. of secs. 34 and 35, T. 6 S., R. 23 E., monumented by a granite stone, 18 x 10 x 6 ins., set 10 ins. in the ground, bears N. 89°53'</p>

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>W., 98 lks. dist., mkd. 34, 35 WC on N., 2 notches on E. and 4 notches on W. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E W <u>S34</u> <u>S35</u> → C S 3 T7S 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, nearly level. Soil, clay and gravelly loam. Timber, mesquite. Undergrowth, creosote, cat claw and sagebrush.</p>
1.50	<p>From the true point for the cor. of secs. 34 and 35.</p> <p>S. 89°32' W. along the S. bdy. of sec. 34.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
38.90	<p>Branch of Matthews Wash, 100 lks. wide, drains NE.</p> <p>The ¼ sec. cor. of sec. 3, T. 7 S., R. 23 E., monumented by a granite stone, 18 x 6 x 6 ins., set 10 ins. in the ground, mkd. ¼ S 3 on S. face.</p>
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S</p> <hr style="width: 50px; margin: 0 auto;"/> <p>¼ S 3 T7S R23E 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>
40.10	<p>The ¼ sec. cor. of sec. 34, T. 6 S., R. 23 E., monumented by a granite stone, 20 x 12 x 6 ins., set 12 ins. in the ground, mkd. ¼ S 34 on N. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E ¼ S 34 T7S 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p>

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>
	<p>S. 89°57' W., beginning new measurement.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
20.00	<p>Spur, slopes S. 70° E.</p>
36.70	<p>Spur, slopes SE.</p>
38.63	<p>The cor. of secs. 3 and 4, T. 7 S., R. 23 E., monument-</p>
	<p>ed by a sandstone, 16 x 9 x 6 ins., set 10 ins. in the</p>
	<p>ground, mkd. 3, 4 on S. and 3 notches on E. and W.</p>
	<p>faces.</p>
	<p>At the corner point</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	$\begin{array}{r} T6S \\ S \ 34 \\ \hline S \ 4 \ \ S \ 3 \\ T7S \ R23E \\ 1967 \end{array}$
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Raise a mound of stone S. of the cor.</p>
40.04	<p>The cor. of secs. 33 and 34, T. 6 S., R. 23 E.,</p>
	<p>monumented by a sandstone, 12 x 10 x 8 ins., set 6 ins.</p>
	<p>in the ground, mkd. 33, 34 on N. and 3 notches on E.</p>
	<p>and W. faces.</p>
	<p>At the corner point</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	$\begin{array}{r} T6S \ R23E \\ S \ 33 \ \ S \ 34 \\ \hline S \ 4 \\ T7S \\ 1967 \end{array}$
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Set a mesquite post, 3½ ft. long, 4 ins. diam.,</p>
	<p>alongside the cor.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, gravelly loam.</p>
	<p>Timber, scattered mesquite.</p>
	<p>Undergrowth, creosote, sagebrush and cat claw.</p>
	<p>S. 89°57' W., along the S. bdy. of sec. 33.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
1.40	<p>Wash, 25 lks. wide, 1 ft. deep, drains S.</p>
19.00	<p>Spur, slopes S. 30° E.</p>
21.50	<p>Wash, 20 lks. wide, 3 ft. deep, drains S., asc.</p>
	<p>SE. slope.</p>

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
31.40	Top of spur, slopes S. 5° E.
33.80	Top of high spur, slopes S., desc. SW. slope.
37.86	<p>The ¼ sec. cor. of sec. 4, T. 7 S., R. 23 E., monumented by a granite stone, 18 x 10 x 4 ins., set 10 ins. in the ground, mkd. ¼ 4 on S. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S</p> <p style="text-align: center;"> $\begin{array}{r} \frac{1}{4} S 4 \\ \hline T7S R23E \\ 1967 \end{array}$ </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone S. of the cor.</p>
39.95	<p>The ¼ sec. cor. of sec. 33, T. 6 S., R. 23 E., monumented by a granite stone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. ¼ S 33 on N. face.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} T6S R23E \\ \frac{1}{4} S 33 \\ \hline T7S \\ 1967 \end{array}$ </p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89°42' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
3.90	Spur, slopes S.
22.30	Spur, slopes S.
26.50	SE. rim of mesa, bears NE. and S. 50° W.
33.30	Top of mesa, thence across nearly level land.
37.92	<p>The cor. of secs. 4 and 5, T. 7 S., R. 23 E., monumented by a granite stone, 16 x 10 x 6 ins., set 8 ins. in the ground, mkd. 4 and 5 on S., 4 notches on E., and 2 notches on W. faces, with an X chiseled on the top.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} T6S \\ S 33 \\ \hline S 5 S 4 \\ T7S R23E \\ 1967 \end{array}$ </p>

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
40.05	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone S. of the cor.</p> <p>The cor. of secs. 32 and 33, T. 6 S., R. 23 E., monument- ed by a sandstone, 14 x 12 x 6 ins., set 6 ins. in the ground, mkd. 32 and 33 on N. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E S 32 S 33 ----- S 5 T7S 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Land, rolling to nearly level. Soil, gravelly loam. No timber; undergrowth, creosote, cat claw and sage- brush.</p>
11.10	<p>S. 89°58' W., along the S. bdy. of sec. 32.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains NE.</p> <p>18.50 Top of rise, bears N. 30° E. and S. 30° W.</p> <p>22.60 Wash, 10 lks. wide, 1 ft. deep, drains NE.</p> <p>37.58 The ¼ sec. cor. of sec. 5, T. 7 S., R. 23 E., monument- ed by a granite stone, 15 x 9 x 8 ins., set 8 ins. in the ground, mkd. ¼ 5 on S. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S ----- ¼ S 5 T7S R23E 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone S. of the cor.</p>
2.52	<p>-----</p> <p>S. 88°55' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The ¼ sec. cor. of sec. 32, T. 6 S., R. 23 E., monu- mented by a granite stone, 16 x 11 x 10 ins., set 9 ins. in the ground, mkd. ¼ 32 on N. face, mound of stone N.</p>

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T6S R23E

$\frac{1}{4}$ S 32

T7S

1967

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone N. of the cor.

18.50 W. rim of mesa, bears N. and S.; rim overlooks Tripp and Underwood Valley; desc. W. slope.

26.30 Fence, bears N. 25° E. and S. 25° W.; enter Tripp and Underwood Valley.

40.02 Point for the cor. of secs. 5 and 6, T. 7 S., R. 23 E., at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T6S

S 32

S6 | S5

T7S R23E

1967

Set a mesquite post, 4 ft. long, 8 ins. diam., alongside the cor.

N. 86°35' W., beginning new measurement.

2.10 Main channel of Tripp and Underwood Wash, drains N. 60° E. and fence crossing wash, bears N. and S.

2.47 Point for the cor. of secs. 31 and 32, T. 6 S., R. 23 E., at proportionate distance; point falls in wash in an unsafe position, impractical to monument.

Land, nearly level.

Soil, gravelly loam.

Timber, mesquite.

Undergrowth, creosote, cat claw and cacti.

N. 86°35' W., along the S. bdy. of sec. 31.

Over nearly level land, through moderate undergrowth.

2.33 Point for the witness cor. of secs. 31 and 32, T. 6 S., R. 23 E. at proportionate dist.; unable to find any evidence of the original witness cor. This point falls in wash in unsafe position, impractical to monument.

2.70 Point selected for the witness cor. of secs. 31 and 32, T. 6 S., R. 23 E.

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E W <u>S31 S32</u> C S 6 T7S 1967</p>
	<p>Set a mesquite post, 4 ft. long, 6 ins. diam., alongside the iron post.</p>
	<p>Raise a mound of stone N. of the cor.</p>
14.70	<p>Leave Tripp and Underwood Valley, bears NE. and SW.</p>
20.40	<p>W. rim of Tripp and Underwood Valley, bears SE. and NW., thence over level land.</p>
37.76	<p>The ¼ sec. cor. of sec. 6, T. 7 S., R. 23 E., monumented by a granite stone, 18 x 8 x 8 ins., loosely set, mkd. ¼ on S. face.</p> <p>At the corner point</p>
	<p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S <u>¼ S 6</u> T7S R23E 1967</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p>
	<p style="text-align: center;">_____</p> <p>S. 80°55' W., beginning new measurement.</p>
	<p>Over level land, through moderate undergrowth.</p>
2.21	<p>Point for the ¼ sec. cor. of sec. 31, T. 6 S., R. 23 E., at proportionate dist.</p>
	<p>Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T6S R23E <u>¼ S 31</u> T7S 1967</p>
	<p>from which</p>
	<p style="padding-left: 40px;">The ¼ sec. cor. of sec. 31, T. 6 S., R. 23 E., monumented by a granite stone, 18x8x8 ins., with 8 ins. projecting above ground, mkd. ¼ 31 on N. face, bears North 39.7 lks. dist. I mark A M on the stone and bury it in place.</p>
	<p>Set a mesquite post, 3½ ft. long, 3 ins. diam., alongside the cor.</p>
21.30	<p>Wash, 40 lks. wide, 1 ft. deep, drains N. 10° E.</p>

Dep. Resurvey, South Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
34.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 35° E.
38.70	The cor. of Tps. 6 and 7 S., Rs. 22 and 23 E., monumented by a granite stone, 20 x 18 x 10 ins., set 12 ins. in the ground in a mound of stone, mkd. 6 notches on 2 edges only.
	At the corner point
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T6S R22E R23E S36 S31 S 1 S 6 T7S 1967
	Deposit the orig. cor. stone alongside the iron post.
	Land, nearly level.
	Soil, gravelly loam.
	Timber, mesquite.
	Undergrowth, creosote, cat claw and cacti.
Dependent Resurvey, West Boundary Township 6 South, Range 23 East	
Reestablishment of the Survey Executed by P. Contzen in 1900	
	From the cor. of Tps. 6 and 7 S., Rs. 22 and 23 E.
	N. 0°34' W., bet. secs. 31 and 36.
	Over nearly level land, through moderate undergrowth.
13.80	Wash, 25 lks. wide, 1 ft. deep, drains N. 30° E.
41.25	The ¼ sec. cor. of secs. 31 and 36, monumented by a granite stone, 18 x 8 x 6 ins., showing above the ground, mkd. ¼ 36 on W. and 31 on E. faces. This cor. was not remonumented.
	N. 0°27' W., beginning new measurement.
	Over nearly level land, through moderate undergrowth.
7.00	Aravaipa and Klondike road, bears N. 66°45' E. and S. 66°45' W.
8.30	Access road, bears N. 66°45' E. and S. 66°45' W.
9.00	Fence, parallels road.
45.86	The cor. of secs. 25, 30, 31 and 36, monumented by a quartzite stone, 14 x 8 x 8 ins., set 7 ins. in the ground, mkd. 5 notches on N. and 1 notch on S. faces.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.

Dep. Resurvey, West Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p style="text-align: center;">T6S R22E R23E S25 S30 S36 S31 1967</p> <p>from which</p> <p style="padding-left: 40px;">A chimney on the north end of Lee's Ranch House, bears N. 20°10' E., 9.50 chs. dist.</p> <p style="padding-left: 40px;">Center of earth stock tank, bears N. 55° W., 15.00 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. No timber; Undergrowth, cacti, cat claw and sagebrush.</p>
	<p>N. 0°06' W., bet. secs. 25 and 30.</p> <p>Over nearly level land, through moderate undergrowth.</p>
12.30	S. end of corral, bears E. and W.
14.50	N. end of corral, bears N. 50° E. and S. 50° W.
16.70	Dirt road, bears N. 75° E. and S. 75° W.
20.07	Point for the S 1/16 sec. cor. of secs. 25 and 30.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T6S R22E R23E S1/16 S25 S30 1967</p>
	Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.
40.14	The 1/4 sec. cor. of secs. 25 and 30, monumented by a granite stone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. 1/4 25 on W. and 30 on E. faces.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T6S R22E R23E 1/4 S25 S30 1967</p>
	Bury the orig. cor. stone alongside the iron post.
	Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.

Dep. Resurvey, West Boundary, T. 6 S., R. 23 E., Arizona

CHAINS		
	<p>N. 0°03' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>15.30 Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.</p> <p>39.98 The cor. of secs. 19, 24, 25 and 30, monumented by a granite stone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. 4 notches on N. and 2 notches on S. faces, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A mesquite 8 ins. diam., bears S. 10° W., 10 lks. dist., mkd. with an old blaze.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E S24 S19 S25 S30 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. Timber, mesquite. Undergrowth, sagebrush, cat claw and cacti.</p>	
	<p>N. 0°13' W., bet. secs. 19 and 24.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>12.30 Low rise, bears NE. and SW.</p> <p>24.70 Track road in bottom of wash, bears SW. and NE., 50 lks. dist., thence N. 15° E., wash, drains NE.</p> <p>39.99 The ¼ sec. cor. of secs. 19 and 24, monumented by a granite stone, 18 x 10 x 6 ins., set 10 ins. in the ground, mkd. ¼ 24 on W. and 19 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E ¼ S24 S19 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>	

Dep. Resurvey, West Boundary, T. 6 S., R. 23 E., Arizona

CHAINS		
37.50	Wash, 30 lks. wide, 3 ft. deep, drains N. 80° E.	
40.04	<p>The cor. of secs. 13, 18, 19 and 24, monumented by a granite stone, 18 x 10 x 3 ins., set 10 ins. in the ground, mkd. 3 notches on N. and S. faces, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A mesquite 8 ins. diam., bears N. 12$\frac{3}{4}$° E., 163 lks. dist., mkd. with an old blaze.</p> <p style="padding-left: 40px;">A mesquite 10 ins. diam., bears S. 60° E., 130 lks. dist., mkd. T6S R23E S19 BT.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E <u>S13</u> <u>S18</u> <u>S24</u> <u>S19</u> 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. Timber; mesquite. Undergrowth, creosote, cacti and cat claw.</p>	
40.15	<p>N. 0°07' W., bet. secs. 13 and 18.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ 13 on W. and 18 on E. faces, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A mesquite 10 ins. diam., bears N. 89° E., 106 lks. dist., mkd. with an old blaze.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E $\frac{1}{4}$ <u>S13</u> <u>S18</u> 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>	
7.40	<p>N. 0°07' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Bladed road, bears S. 80° E. and N. 80° W.</p>	

Dep. Resurvey, West Boundary, T. 6 S., R. 23 E., Arizona

CHAINS		
40.13	<p>The cor. of secs. 7, 12, 13 and 18, monumented by a granite stone, 18 x 12x 4 ins., set 10 ins. in the ground. mkd. 4 notches on S. and 2 notches on N. faces, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A mesquite 8 ins. diam., bears N. 23½° E., 219 lks. dist., mkd. with an old blaze and T.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E <u>S12 S 7</u> S13 S18 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 5 ft. long, 3 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. Timber, mesquite. Undergrowth, cacti, cat claw and sagebrush.</p>	
	<p>North, bet. secs. 7 and 12.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
15.20	<p>Wash, 30 lks. wide, 1 ft. deep, drains N. 60° E.</p>	
21.30	<p>Fence, bears N. 58°30' E. and S. 58°30' W.</p>	
30.00	<p>Wash, 25 lks. wide, 1 ft. deep, drains N. 70° E.</p>	
38.90	<p>Wash, 20 lks. wide, 2 ft. deep, drains NE.</p>	
40.12	<p>The ¼ sec. cor. of secs. 7 and 12, monumented by a granite stone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. ¼ 12 on W. and 7 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E ¼ <u>S12 S 7</u> 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p>	
	<p>N. 0°05' E., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
20.80	<p>Wash, 50 lks. wide, 1 ft. deep, drains irregularly E.</p>	

Dep. Resurvey, West Boundary, T. 6 S., R. 23 E., Arizona

CHAINS	
27.50	Wash, 50 lks. wide, 2 ft. deep, drains E., 100 lks., thence NE.
40.08	<p>The cor. of secs. 1, 6, 7 and 12, monumented by a granite stone, 18 x 8 x 5 ins., set 10 ins. in the ground, mkd. 1 notch on N. and 5 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E S 1 S 6 S 12 S 7 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 2 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, sandy clay loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cat claw and cacti.</p>
	N. 0°13' W., bet. secs. 1 and 6.
	Over nearly level land, through moderate undergrowth.
32.70	Wash, 50 lks. wide, 1 ft. deep, drains N. 35° E.
40.14	<p>The ¼ sec. cor. of secs. 1 and 6, monumented by a granite stone, 16 x 8 x 6 ins., set 10 ins. in the ground, mkd. ¼ 1 on W. and 6 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R22E R23E ¼ S 1 S 6 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>
	N. 0°12' W., beginning new measurement.
	Over nearly level land, through moderate undergrowth.
4.70	Wash, 30 lks. wide, 1 ft. deep, drains NE.
35.63	<p>Intersect the First Standard Parallel South.</p> <p>The closing cor. of Tps. 6 S., Rs. 22 and 23 E., monumented by a granite stone, 10 x 8 x 6 ins., set 5 ins. in the ground, mkd. 6 notches on E., W. and S. faces, and CC on S. face.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T5S R22E S36 <hr style="width: 50px; margin: 0 auto;"/> S 1 S 6 R22E R23E T6S C C 1967 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a post 4 ft. long, 4 ins. diam., alongside the cor. from which</p> <p style="padding-left: 40px;">The Standard Cor. of Tps. 5 S., Rs. 22 and 23E., bears N. 89°55' E., 25.99 chs. dist., hereinbefore described.</p> <p style="padding-left: 40px;">The Standard ¼ sec. Cor. of sec. 36, T. 5 S., R. 22 E., bears S. 89°55' W., 14.17 chs. dist., monumented by a granite stone, 14x10x8 ins., firmly set, mkd. SC ¼ 36 on N. face.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> S C T5S R22E <hr style="width: 50px; margin: 0 auto;"/> ¼ S 36 1967 </p> <p>Bury the original cor. stone alongside the iron post.</p> <p>Set a post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, clay loam. No timber; undergrowth, creosote, cacti and cat claw.</p>
	<p>Dependent Resurvey, Subdivisional Lines Township 6 South, Range 23 East</p>
<p>1.40</p> <p>6.30</p> <p>9.50</p> <p>17.20</p>	<p style="text-align: center;">Reestablishment of the Survey Executed by P. Contzen in 1900</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0°03' E., bet. secs. 35 and 36.</p> <p>Over nearly level land, through moderate undergrowth, along E. side of a N. and S. fence line.</p> <p>Wash, 20 lks. wide, 8 ft. deep, drains E.</p> <p>Fence, bears N. 69°40' E. and S. 69°40' W.</p> <p>Wash, 50 lks. wide, 10 ft. deep, drains E.</p> <p>S. side of Exclosure Test Plot, N. and S. fence line, bears W., 13 lks. dist., from which the SE. cor. of Test Plot, bears E., 315 lks. dist., the SW. cor. of Test Plot, bears W., 315 lks. dist., enter railed area.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS		
30.80	Wash, 40 lks. wide, 2 ft. deep, drains E.	
40.54	The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented by a granite stone, 18x8x6 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ 35 on W. face.	
	At the corner point	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T6S R23E $\frac{1}{4}$ S35 S36 1967	
	Bury the orig. cor. stone alongside the iron post.	
	Cor. is located in a fence line, bearing N. and S.	
	<hr style="width: 20%; margin: auto;"/> North, beginning new measurement.	
	Over nearly level land, through moderate undergrowth.	
11.10	Wash, 100 lks. wide, 1 ft. deep, drains NE.	
14.80	Wash, 220 lks. wide, 1 ft. deep, drains E.	
21.50	Matthews Wash, 100 lks. wide, 1 ft. deep, drains N. 80° E.	
40.06	The cor. of secs. 25, 26, 35 and 36, monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. 1 notch on E. and S. faces.	
	At the corner point	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T6S R23E <u>S26 S25</u> S35 S36 1967	
	Bury the orig. cor. stone alongside the iron post.	
	Cor. is located in a fence line bearing N. and S.	
	Land, nearly level.	
	Soil, clay loam.	
	No timber; undergrowth, creosote, sagebrush and cacti.	
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.	
	N. 89°47' W., bet. secs. 25 and 36.	
	Over nearly level land, through railed area.	
40.11	The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented by a granite stone, 14 x 8 x 6 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ 25 on N. and 36 on S. faces.	
	At the corner point	
	Set the iron post 24 ins. in the ground, brass cap mkd.	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{S14}{S23} \frac{S13}{S24}$ 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote, sagebrush and cacti.</p>
	<p>From the cor. of secs. 13 and 24, on the E. bdy. of the Tp.</p> <p>N. 89°46' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>2.70 Wash, 10 lks. wide, 1 ft. deep, drains NE.</p> <p>18.20 E. side of Exclosure Test Plot, bears N. and S.</p> <p>21.30 W. side of Exclosure Test Plot, bears N. and S.</p> <p>38.10 Enter broken land, bears N. and S.</p> <p>40.57 The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented by a granite stone, 12 x 10 x 6 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ 13 on N. and 24 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4} \frac{S 13}{S 24}$ 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>N. 89°58' W., beginning new measurement.</p> <p>Over broken land, through moderate undergrowth.</p> <p>40.10 The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, nearly level to broken. Soil, gravelly loam. No timber; Undergrowth, creosote, cat claw and palo verde.</p>
	<p>N. 0°14' E., bet. secs. 13 and 14.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>.20 Wash, 10 lks. wide, 2 ft. deep, drains E.</p> <p>33.00 Enter Tripp Valley, bears NE. and SW.</p> <p>40.04 The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented by a limestone, 10 x 8 x 6 ins., set 5 ins. in the ground, no legible mks., from which the remains of the original bearing trees:</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>A mesquite 12 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 151 lks. dist., mkd. BT.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S14 S13 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. $0^{\circ}02'$ E., beginning new measurement.</p> <p>Continue across Tripp Valley.</p>
.10	Wash, 10 lks. wide, 3 ft. deep, drains N. 50° E.
8.60	Center of Hunsacker Wash, 100 lks. wide, 3 ft. deep, drains N. 60° E.
38.60	Wash, 50 lks. wide, 1 ft. deep, drains E., leave Tripp Valley.
40.04	Point for the cor. of secs. 11, 12, 13 and 14, at pro- portionate dist.; unable to find any remaining evidence of the orig. cor.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E <u>S11 S12</u> S14 S13 1967</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
	<p>From the cor. of secs. 12 and 13, on the E. bdy. of the Tp.</p> <p>N. $89^{\circ}59'$ W., bet. secs. 12 and 13.</p> <p>Over nearly level land, through moderate undergrowth.</p>
16.40	Enter Hunsacker Wash, 8 ft. deep, drains NE.
20.10	Leave same wash, drains NE.
40.32	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented by a limestone, 10 x 8 x 4 ins., loosely set, no legible mks., mound of stone N. I accept this as the best remaining evidence of the orig. cor.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
<p>10.20</p> <p>22.30</p> <p>27.20</p> <p>40.23</p>	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ $\frac{S\ 12}{S13}$ 1967</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Track road, bears S. 20° E. and N. 20° W.</p> <p>Enter gently rolling land, bears NE. and SW.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains NE.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, nearly level to gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote, cat claw and scrub mesquite.</p>
<p>3.10</p> <p>22.40</p> <p>40.04</p>	<p>N. 0°03' E., bet. secs. 11 and 12.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Top of ridge, bears E. and W.</p> <p>Dirt road, bears SE. and NW.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by a granite stone, 16 x 8 x 6 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ 11 on W. and 12 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ $\frac{S11\ S12}{S12}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">Triangulation Station MAT, bears S. 76°41' W., 46.86 chs. dist., monumented with a brass tablet, set in a cement block, mkd. MAT 1945.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS		
	Over rolling land, through moderate undergrowth.	
9.20	Bladed road, bears N. 68° E. and S. 68° W.	
27.10	Aravaipa and Klondike road, bears N. 48°25' E. and S. 48°25' W.	
36.20	Wash, 25 lks. wide, 1 ft. deep, drains NE.	
40.17	The cor. of secs. 1, 2, 11 and 12, monumented by a granite stone, 16 x 9 x 8 ins., set 10 ins. in the ground, mkd. 1 notch on E. and 5 notches on S faces, from which the remains of the original bearing tree:	
	<p style="padding-left: 40px;">A mesquite 8 ins. diam., bears S. 69° E., 117 lks. dist., mkd. T6S R23E S12 BT.</p>	
	At the corner point	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T6S R23E $\frac{S}{S11} \frac{S}{S12}$ 1967</p>	
	Bury the orig. cor. stone alongside the iron post.	
	Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.	
	Land, rolling.	
	Soil, gravelly loam.	
	No timber; Undergrowth, creosote, cacti and cat claw.	
	<hr/> From the cor. of secs. 1 and 12, on the E. bdy. of the Tp.	
	N. 89°49' W., bet. secs. 1 and 12.	
	Over nearly level land, through moderate undergrowth.	
6.20	Leave nearly level land, enter rolling land.	
29.30	Wash, 30 lks. wide, 1 ft. deep, drains N. 60° E.	
32.10	Wash, 30 lks. wide, 1 ft. deep, drains N. 40° E.	
40.42	The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented by a granite stone, 12 x 10 x 6 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ S 1 on N. and 12 on S. faces.	
	At the corner point	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T6S R23E $\frac{1}{4} \frac{S}{S12}$ 1967</p>	
	Bury the orig. cor. stone alongside the iron post.	
	Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>N. 89°54' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>4.00 Bladed road, bears NE. and SW.</p> <p>16.20 Enter nearly level land, bears NE. and SW.</p> <p>26.30 Aravaipa and Klondike road, bears N. 49° E. and S. 49° W.</p> <p>38.40 Wash, 90 lks. wide, 2 ft. deep, drains N. 15° E.</p> <p>40.07 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, level to rolling to level. Soil, gravelly clay loam. Timber, mesquite Undergrowth, creosote, sagebrush and cacti.</p>
	<p>N. 0°02' W., bet. secs. 1 and 2.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>39.98 The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented by a limestone, 9 x 9 x 2 ins., set 5 ins. in the ground, no legible markings. I accepted this as the best remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S 2 S 1 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>
	<p>N. 0°44' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>3.20 Top of ridge, bears E. and W., desc. N. slope.</p> <p>36.77 Intersect the First Standard Parallel South.</p> <p>The closing cor. of secs. 1 and 2, monumented by a limestone, 12 x 6 x 6 ins., set 6 ins. in the ground, mkd. 4 notches on W. and 1 notch on E. faces, mound of stone S.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T5S R23E S35 S 2 S 1 T6S R23E C C 1967</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

<p>CHAINS</p>	<p>from which</p> <p style="padding-left: 40px;">The Standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 5 S., R. 23 E., bears S. $89^{\circ}58'$ W., 13.62 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone S. of the cor.</p> <p>Land, rolling. Soil, gravelly loam. No timber; Undergrowth, creosote, sagebrush and cacti.</p> <hr/> <p>The point for the $\frac{1}{4}$ sec. cor. of sec. 1, is at midpoint and on the N. bdy. of the Tp.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \frac{1}{4} \text{ S } 1 \\ \text{T6S R23E} \\ 1967 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">The Standard cor. of secs. 35 and 36, T. 5 S., R. 23 E., bears N. $89^{\circ}57'$ W., 13.98 chs. dist.</p> <hr/> <p>From true point for the cor. of secs. 34 and 35, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ}06'$ W., bet. secs. 34 and 35.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>.10 N. edge of wash, bears NE. and SW.</p> <p>3.90 Wash, 25 lks. wide, 2 ft. deep, drains NE.</p> <p>41.09 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented by a granite stone, 12 x 8 x 5 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ 34 on W. and 35 on E. faces, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A mesquite 8 ins. diam., bears S. 63° E., 100 lks. dist., mkd. with an old blaze.</p> <p style="padding-left: 40px;">A mesquite 6 ins. diam., bears N. $59\frac{3}{4}^{\circ}$ W., 52 lks. dist., mkd. with an old blaze.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \text{T6S R23E} \\ \frac{1}{4} \\ \text{S34 S35} \\ 1967 \end{array}$ </div> <p>Bury the orig. cor. stone alongside the iron post.</p>
---------------	---

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
39.90	<p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p style="text-align: center;">_____</p> <p>N. 0°10' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>The cor. of secs. 26, 27, 34 and 35, monumented by a granite stone, 20 x 10 x 8 ins., set 12 ins. in the ground, mkd. 2 notches on E. and 1 notch on S. faces, from which the remains of the original bearing tree:</p> <p style="padding-left: 40px;">A mesquite 10 ins. diam., bears N. 5½° E., 315 lks. dist., mkd. T6S R23E S26 BT.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E S27 S26 S34 S35 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside and raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
40.14	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°47' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>The ¼ sec. cor. of secs. 26 and 35, monumented by a sandstone, 14 x 14 x 6 ins., set 8 ins. in the ground, mkd. ¼ 26 on N. and 35 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ S26 S35 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p style="text-align: center;">_____</p> <p>N. 89°47' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
40.20	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cat claw and cacti.</p>
	<p>N. 0°03' W., bet. secs. 26 and 27.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
3.10	<p>Wash, 30 lks. wide, 1 ft. deep, drains NE.</p>
5.50	<p>Top of ridge, bears E. and W.</p>
15.60	<p>Top of ridge, bears E. and W., desc. N. slope.</p>
35.90	<p>Wash, 20 lks. wide, 1 ft. deep, drains E., asc. S. slope.</p>
39.87	<p>The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented by a sandstone, 10 x 10 x 8 ins., set 5 ins. in the ground, mkd. $\frac{1}{4}$ 27 on W. and 26 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S27 S26 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3$\frac{1}{2}$ ft. long, 4 ins. diam., alongside the cor.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°07' W., beginning new measurement.</p>
4.40	<p>Wash, 200 lks. wide, 2 ft. deep, drains E.</p>
35.60	<p>Wash, 80 lks. wide, 1 ft. deep, drains S. 60° E.</p>
40.11	<p>The cor. of secs. 22, 23, 26 and 27, monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. 2 notches on E. and 2 notches on S. faces, from which the remains of the original bearing tree:</p> <p style="padding-left: 40px;">A mesquite 12 ins. diam., bears N. 9$\frac{1}{2}$° E., 111 lks. dist., mkd. with an old blaze.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E S22 S23 S27 S26 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing S. 89°20' E. and N. 89°20' W., bears North, 3 lks. dist.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°30' W., bet. secs. 23 and 26.</p> <p>Over nearly level land, through moderate undergrowth.</p>
11.00	Wash, 15 lks. wide, 1 ft. deep, drains SE.
40.27	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, as determined from the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A mesquite stump 10 ins. diam., bears N. 52$\frac{1}{2}$° W., 156 lks. dist., mkd. with T, only legible mks.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ $\frac{S23}{S26}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing N. 89°20' W., and S. 89°20' E., bears South, 19 lks. dist.</p> <p style="padding-left: 40px;">Remains of White House, an old adobe building, bears N. 49°57' W., 15.63 chs. dist.</p> <p>Set a mesquite post, 6 ft. long, 4 ins. diam., alongside the cor.</p>
	<p style="text-align: center;">—————</p> <p>S. 89°58' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
11.90	Wash, 20 lks. wide, 2 ft. deep, drains NE.
40.14	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, sagebrush, cacti and cat claw.</p>
	<p>N. 0°08' E., bet. secs. 22 and 23.</p> <p>Over rolling land, through moderate undergrowth.</p>
.03	Fence, bears S. 89°20' E., and N. 89°20' W.
.80	Wash, 25 lks. wide, 1 ft. deep, drains E.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

<p>CHAINS</p> <p>6.80</p> <p>9.50</p> <p>29.10</p> <p>38.00</p> <p>40.07</p> <p>.60</p> <p>4.10</p> <p>8.40</p> <p>26.30</p> <p>32.00</p> <p>40.15</p>	<p>Wash, 100 lks. wide, 1 ft. deep, drains E.</p> <p>Tripp and Underwood Wash, 100 lks. wide, 1 ft. deep, drains E., asc. S. slope.</p> <p>Dirt road, bears S. 80° E. and N. 80° W.</p> <p>Top of ridge, bears E. and W., desc. N. slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented by a limestone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ 22 on W. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S22 S23 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°07' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains W., asc. S. slope.</p> <p>Spur, slopes NE., desc. N. slope.</p> <p>Enter valley, bears NE. and SW.</p> <p>Hunsacker Wash, 30 lks. wide, 2 ft. deep, drains NE.</p> <p>Leave valley, bears NE. and SW., asc. SE. slope.</p> <p>The cor. of secs. 14, 15, 22 and 23, monumented by a granite stone, 18 x 10 x 6 ins., set 10 ins. in the ground, mkd. 3 notches on S. and 2 notches on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T6S R23E S15 S14 S22 S23 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
--	---

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over broken land, through moderate undergrowth.</p>
9.70	Top of ridge, bears NE. and S., desc. NW. slope.
16.40	Wash, 20 lks. wide, 1 ft. deep, drains N., asc. E. slope.
35.00	Leave broken land, enter valley, bears NE. and SW.
39.78	<p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented by a limestone, 16 x 10 x 3 ins., set 10 ins. in the ground, no legible mks. I accept this as the best remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S14 S23 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <p style="text-align: center;">—————</p> <p>S. 89°48' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
21.60	Hunsacker Wash, 20 lks. wide, 3 ft. deep, drains NE.
40.26	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, broken to nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cat claw and palo verde.</p>
	<p>N. 0°08' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through moderate undergrowth.</p>
37.90	Wash, 25 lks. wide, 1 ft. deep, drains NE.
40.10	<p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented by a limestone, 12 x 8 x 3 ins., set 6 ins. in the ground, no legible mks., from which the remains of the original bearing trees</p> <p style="text-align: center;">A mesquite 14 ins. diam., bears S. 30$\frac{3}{4}$° W., 73 lks. dist., mkd. with an old blaze.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S15 S14 1967</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°17' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>3.20 Wash, 25 lks. wide, 1 ft. deep, drains SE.</p> <p>32.70 Aravaipa and Klondike road, bears N. 43° E. and S. 43° W.</p> <p>34.10 Fence, bears N. 43° E. and S. 43° W., enter railed area.</p> <p>40.24 The cor. of secs. 10, 11, 14 and 15, monumented by a limestone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. 1 notch on S. face, no other legible mks.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T6S R23E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S10</td><td style="padding: 0 5px;">S11</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S15</td><td style="padding: 0 5px;">S14</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p> <hr style="border: 1px solid black;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°43' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>21.30 Enter broken land, bears NE. and SW.</p> <p>40.07 The ¼ sec. cor. of secs. 11 and 14, monumented by a granite stone, 14 x 7 x 8 ins., set 8 ins. in the ground, mkd. ¼ 11 on N. and 14 on S. face, from which the remains of the original bearing trees</p> <div style="text-align: center; margin: 10px 0;"> <p>A mesquite 8 ins. diam., bears N. 12¼° W., 93½ lks. dist., mkd. BT.</p> </div> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T6S R23E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">¼ S11</td><td style="padding: 0 5px;">S14</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p>	T6S R23E		S10	S11	S15	S14	1967		T6S R23E		¼ S11	S14	1967	
T6S R23E															
S10	S11														
S15	S14														
1967															
T6S R23E															
¼ S11	S14														
1967															

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <p style="text-align: center;">—————</p> <p>N. 89°59' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
33.70	<p>Aravaipa and Klondike road, bears N. 42°20' E. and S. 42°20' W.</p>
34.90	<p>Fence, bears N. 42°20' E., 150 lks. dist. to cor. of fences bearing S. 42°20' W. and N. 47°40' W.</p>
	<p>Enter railed area, bears NE. and SW.</p>
40.10	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote, cacti and cat claw.</p>
	<p>N. 0°04' W., bet. secs. 10 and 11.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
2.60	<p>Fence, bears N. 42° E. and S. 42° W.</p>
7.60	<p>Fence, bears S. 47° E. and N. 47° W., leave railed area.</p>
40.09	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented by a limestone, 12 x 18 x 4 ins., set 6 ins. in the ground, mkd. 10 on the W. face, no other legible mks.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E 1/4 S10 S11 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p style="text-align: center;">—————</p>
	<p>N. 0°09' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
25.90	<p>Wash, 30 lks. wide, 1 ft. deep, drains NE.</p>
38.10	<p>Fence, bears N. 30° E. and S. 30° W.</p>
40.16	<p>The cor. of secs. 2, 3, 10 and 11, at cor. of fences, bearing S. 30° W. and N. 60° W. This position is harmoniously related to existing original corners and is accepted as the best remaining evidence of the original cor. position.</p> <p>At the corner point</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T6S R23E $\frac{S\ 3}{S10} \frac{S\ 2}{S11}$ 1967 </p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
8.00 18.00 40.01	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°50' W., bet. secs. 2 and 11.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Enter broken land, bears NE. and SW.</p> <p>Top of spur, slopes SE.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented by a limestone, 18 x 10 x 4 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ 2 on N. face, no other legible mks.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T6S R23E $\frac{1}{4} \frac{S\ 2}{S11}$ 1967 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 89°43' W., beginning new measurement.</p> <p>Descend over broken land, through moderate undergrowth.</p>
10.40 24.60 38.90 40.02	<p>Bottom of descent, thence over nearly level land.</p> <p>Wash, 40 lks. wide, 1 ft. deep, drains irregularly N.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains N. 30° E.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, broken to nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cacti.</p>
13.60	<p>N. 0°01' E., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Wash, 50 lks. wide, 1 ft. deep, drains NE.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
40.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented by a limestone, 16 x 8 x 3 ins., no legible mks. This position is harmoniously related to existing original corners and is accepted as the best remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S 3 S 2 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <p style="text-align: center;">—————</p> <p>N. 0°02' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
24.50	Wash, 200 lks. wide, 1 ft. deep, drains NE.
33.00	Track road, bears N. 70° E. and S. 70° W.
36.41	<p>Intersect the First Standard Parallel South.</p> <p>The closing cor. of secs. 2 and 3, monumented by a granite stone, 9 x 9 x 4 ins., set 4 ins. in the ground, mkd. CC on S., 4 notches on W. and 2 notches on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T5S S34 S 3 S 2 T6S R23E C C 1967</p> <p>from which</p> <p style="text-align: center;">The Standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 5 S., R. 23 E., bears N. 89°57' W., 12.79 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 2, is at midpoint and on the N. bdy. of the Tp.</p> <p>At the corner point</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS		
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 2 T6S R23E 1967 </p> <p>from which</p> <p style="text-align: center;"> The Standard cor. of secs. 34 and 35, T. 5 S., R. 23 E., bears N. 89°57' W., 13.11 chs. dist. </p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>	
	<p>From the cor. of secs. 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°05' E., bet. secs. 33 and 34.</p> <p>Over rolling land, through moderate undergrowth.</p>	
29.40	Top of bluff, bears E. and W.	
36.80	Top of spur, slopes E., 600 lks. dist.	
39.20	Wash, 20 lks. wide, 1 ft. deep, drains irregularly E.	
41.78	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T6S R23E $\frac{1}{4}$ S33 S34 1967 </p> <p>Raise a mound of stone W. of the cor.</p>	
43.10	Top of finger of mesa, bears E. and W.	
47.10	Top of ridge, bears E. and W., desc. N. slope.	
49.60	Wash, 10 lks. wide, 1 ft. deep, drains E., 200 lks. dist., thence NE.	
59.00	Wash, 100 lks. wide, 3 ft. deep, drains E., 600 lks. dist., thence N.	
64.00	Wash, 20 lks. wide, 2 ft. deep, drains E.	
78.70	Wash, 80 lks. wide, 2 ft. deep, drains E., from NW., asc. S. slope.	
81.67	<p>The cor. of secs. 27, 28, 33 and 34, monumented by a granite stone, 16 x 8 x 6 ins., set 8 ins. in the ground, mkd. 3 notches on E. and 1 notch on S. faces.</p> <p>At the corner point</p>	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T6S R23E S28 S27 S33 S34 1967 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cacti.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°52' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through moderate undergrowth.</p>
3.30	Wash, 50 lks. wide, 1 ft. deep, drains NE.
40.00	True point for the ¼ sec. cor. of secs. 27 and 34 at proportionate dist. falls in a wash in unsafe location.
	<p style="text-align: center;">_____</p> <p>N. 89°45' W., beginning new measurement.</p> <p>Over broken land, through moderate undergrowth.</p>
1.00	<p>The witness ¼ sec. cor. of secs. 27 and 34, monumented by a granite stone, 16x6x6 ins., set 8 ins. in the ground, mkd. ¼ 27 on N. face, WC on E. face and 34 on S. face, with a mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T6S R23E W ¼ S27 → C ¼ S34 1967 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>
9.40	Wash, 100 lks. wide, 1 ft. deep, drains irregularly NE.
10.50	Top of clay ridge, bears N. and S.
22.40	Wash, 20 lks. wide, 1 ft. deep, drains NE.
25.30	Top of clay ridge, bears N. and S.
31.70	E. rim of mesa, bears N. and S.
33.80	Wash, 50 lks. wide, 1 ft. deep, drains N.
39.86	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling to broken. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cat claw and cacti.</p>
	<p>N. 0°52' W., bet. secs. 27 and 28.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	Over broken land, through moderate undergrowth.
2.60	Wash, 50 lks. wide, 4 ft. deep, drains E., 100 lks. dist., thence irregularly N.
5.90	Same wash, drains irregularly E.
6.80	Top of ridge, bears E. and W.
8.40	Wash, 30 lks. wide, 1 ft. deep, drains N. 60° E., 110 lks. dist., thence North, 200 lks. dist., thence irregularly E.
13.70	Top of ridge, bears E. and W., desc. over broken N. slope.
26.80	Wash, 60 lks. wide, 15 ft. deep, drains E., 150 lks. dist., thence N. curving E.
39.82	<p>The ¼ sec. cor. of secs. 27 and 28, monumented by a limestone, 12 x 8 x 6 ins., set 6 ins. in the ground, no legible mks., from which the remains of the original bearing tree:</p> <p style="padding-left: 40px;">A mesquite 8 ins. diam., bears N. 51° W., 26 lks. dist., mkd. ¼ S28 BT.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <p>¼</p> <p>S28 S27</p> <p>1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
33.40	Fence, bears E. and W.
36.30	Main channel of Underwood Wash, 200 lks. wide, 2 ft. deep, drains N. 70° E.
39.86	<p>Point selected for the witness cor. of secs. 21, 22, 27 and 28.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <p>S21↑S22</p> <p>S28 S27</p> <p>W C</p> <p>1967</p> </div>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS		
40.16	<p>True point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; unable to find any remaining evidence of the original cor. This point falls in a wash area in an unsafe position, impractical to monument.</p> <p>Land, broken to nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>	
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>	
	<p>N. 89°47' W., bet. secs. 22 and 27.</p>	
	<p>Over nearly level land, through moderate undergrowth.</p>	
5.30	<p>Cor. of fences bearing S. 89°20' E. and S. 14° W., 250 lks. dist., thence N. 70° W.</p>	
6.50	<p>Wash, 20 lks. wide, 2 ft. deep, drains N. 60° E.</p>	
9.00	<p>Branch of Underwood Wash, 80 lks. wide, 1 ft. deep, drains S. 60° E.</p>	
12.50	<p>Cor. of fences bearing S. 70° E. and W.</p>	
40.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented by a granite stone, 12 x 10 x 9 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ 22 on N. and 27 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ $\frac{S22}{S27}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence bearing E. and W., bears North, 6 lks. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p>	
	<p>N. 89°47' W., beginning new measurement.</p>	
	<p>Over gently rolling land, through moderate undergrowth.</p>	
21.40	<p>Cor. of fences bearing E. and S. 50° W., bears North, 13 lks. dist.</p>	
21.60	<p>Fence, bears N. 50° E. and S. 50° W.</p>	
22.80	<p>Enter Underwood Wash, drains N. 60° E.</p>	
31.60	<p>Leave Underwood Wash, drains N. 60° E.</p>	
40.14	<p>True point for the cor. of secs. 21, 22, 27 and 28.</p>	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Land, nearly level to gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and bunch grass.</p> <hr/> <p>N. 0°20' E., bet. secs. 21 and 22, from true point. Over nearly level land, through moderate undergrowth.</p> <p>.90 Wash, 120 lks. wide, 2 ft. deep, drains N. 70° E.</p> <p>3.70 Branch of Underwood Wash, 110 lks. wide, 1 ft. deep, drains N. 70° E.</p> <p>37.70 Top of spur, slopes E.</p> <p>39.40 Wash, 30 lks. wide, 1 ft. deep, drains E.</p> <p>40.16 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S21 S22 1967</p> <p>Set a mesquite post, 3$\frac{1}{2}$ ft. long, 3 ins. diam., alongside the cor.</p> <p>42.10 S. rim of low mesa, bears N. 65° E. and SW., thence over nearly level land.</p> <p>52.30 Aravaipa and Klondike road, bears N. 55° E. and S. 55° W.</p> <p>53.90 Fence, bears N. 55° E. and S. 55° W.</p> <p>80.32 The cor. of secs. 15, 16, 21 and 22, monumented by a sandstone, 18 x 10 x 8 ins., set 10 ins. in the ground, mkd. 3 notches on E. and S. faces, from which the remains of the original bearing tree.</p> <p style="text-align: center;">A mesquite 6 ins. diam., bears N. 17° E., 236 lks. dist., mkd. 15 BT.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E S16 S15 S21 S22 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a sqd. post 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cacti.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS		
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°45' W., bet. secs. 15 and 22.</p> <p>Ascend over broken land, through moderate undergrowth..</p>	
25.00	<p>Top of ascent, thence over nearly level land.</p>	
39.99	<p>The ¼ sec. cor. of secs. 15 and 22, monumented by a granite stone, 12 x 12 x 4 ins., set 6 ins. in the ground, mkd. ¼ 15 on N. and 22 on S. faces, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A mesquite 6 ins. diam., bears N. 71° W., 134 lks. dist., mkd. BT.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ <u>S15</u> S22 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <p style="text-align: center;">—————</p> <p>N. 89°40' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
4.90	<p>Track road, bears N. 10° E. and S. 10° W.</p>	
15.60	<p>Aravaipa and Klondike road, bears N. 31°52' E. and S. 31°52' W.</p>	
16.70	<p>Fence, bears N. 31°52' E. and S. 31° 52' W.</p>	
40.06	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, broken to nearly level. Soil, gravelly loam. No timber; Undergrowth, creosote, cacti, cat claw and grass.</p> <hr/> <p>North bet. secs. 15 and 16.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>16.40 Bladed road, bears irregularly E. and W.</p> <p>37.60 Wash, 30 lks. wide 1 ft. deep, drains NE.</p> <p>40.14 The ¼ sec. cor. of secs. 15 and 16, monumented by a granite stone, 16 x 10 x 8 ins., set 8 ins. in the ground, mkd. ¼ 16 on W. and 15 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ S16 S15 1967</p>	

Dep. Resurvey, Subdivisional lines, T. 6 S., R. 23 E., Arizona

CHAINS		
	<p>Bury the orig. cor. stone alongside the iron post. Cor. is located in a fence bearing N. and S. 6° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement. Over rolling land, through moderate undergrowth.</p> <p>3.70 Wash, 40 lks. wide, 2 ft. deep, drains NE.</p> <p>11.30 Cor. of fences, bearing N. 54° E. and S.</p> <p>22.90 Wash, 20 lks. wide, 1 ft. deep, drains NE.</p> <p>32.60 Top of ridge, bears NE. and SW.</p> <p>40.04 The cor. of secs. 9, 10, 15 and 16, monumented by a granite stone, 14 x 8 x 8 ins., set 6 ins. in the ground, mkd. 4 notches on S. and 3 notches on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E S 9 S10 S16 S15 1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A squared 4 x 4 wooden post, bears NE., 5 lks. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°49' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land, through scattered undergrowth.</p> <p>1.20 Fence, bears N. 42°20' E. and S. 42°20' W.</p> <p>19.30 Enter moderate undergrowth, bears N. and S.</p> <p>40.09 Point for the ¼ sec. cor. of secs. 10 and 15 at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E ¼ S10 S15 1967</p> </div>	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>from which</p> <p>A portable rain gaging station, bears S. 65° E., 15.23 chs. dist.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>
40.40	Wash, 20 lks. wide, 1 ft. deep, drains N.
42.70	Fence, bears NE. and SW.
43.30	Wash, 50 lks. wide, 4 ft. deep, drains N.
67.70	Wash, 20 lks. wide, 1 ft. deep, drains N.
80.18	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling to broken. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cat claw, cacti and grass.</p>
	<p>N. 0°03' E., bet. secs. 9 and 10.</p> <p>Over rolling land, through moderate undergrowth.</p>
32.70	Wash, 45 lks. wide, 2 ft. deep, drains North, 500 lks. dist., thence NE.
40.07	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented by a granite stone, 16 x 10 x 8 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ 9 on W. and 10 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S 9 S10 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°08' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
19.70	Wash, 10 lks. wide, 1 ft. deep, drains irregularly NE.
40.18	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a granite stone, 18 x 10 x 6 ins., set 10 ins. in the ground, mkd. with 5 notches on S. face and 3 notches on E. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E S 4 S 3 S 9 S10 1967</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A windmill, bears N. 43°42' E., 16.70 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3½ ins. diam., alongside the cor.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°52' W., bet. secs. 3 and 10.</p> <p>Over nearly level land, through moderate undergrowth.</p>
6.20	Wash, 100 lks. wide, 1 ft. deep, drains N. 30° E.
20.30	Wash, 20 lks. wide, 2 ft. deep, drains NE.
28.70	Wash, 20 lks. wide, 2 ft. deep, drains NE.; leave nearly level land, enter rolling land.
40.11	<p>The ¼ sec. cor. of secs. 3 and 10, monumented by a granite stone, 16 x 9 x 5 ins., set 8 ins. in the ground, mkd. ¼ 3 on N. and 10 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <p>¼ <u> S 3</u></p> <p> S10</p> <p> 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 89°49' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
25.50	Wash, 25 lks. wide, 1 ft. deep, drains N. 60° E.
27.90	Top of spur, slopes S. 30° W.
40.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, level to rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sage brush and cacti.</p>
	<p>N. 0°03' E., bet. secs. 3 and 4.</p> <p>Over rolling land, through moderate undergrowth.</p>
5.40	Wash, 150 lks. wide, 1 ft. deep, drains N. 80° E.
19.40	Track road, bears N. 75° E. and S. 75° W.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

<p>CHAINS 25.10</p>	<p>Wash, 20 lks. wide, 3 ft. deep, drains N. 50° E.</p>
<p>40.15</p>	<p>The ¼ sec. cor. of secs. 3 and 4, monumented by a granite stone, 18 x 8 x 6 ins., set 10 ins. in the ground, mkd. ¼ 4 on W. and 3 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ S 4 S 3 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a squared post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p style="text-align: center;">_____</p> <p>N. 0°43' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
<p>6.10</p>	<p>Fence, bears S. 60° E. and N. 60° W.</p>
<p>32.70</p>	<p>At record dist. northerly from the ¼ sec. cor. of secs. 3 and 4 a search was made, but no evidence of the original witness closing cor. of secs. 3 and 4 was found.</p>
<p>36.26</p>	<p>Intersect the First Standard Parallel South.</p> <p>Point for the closing cor. of secs. 3 and 4, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T5S S33 ----- S3 S4 T6S R23E C C 1967</p> <p>from which</p> <p style="text-align: center;">The standard ¼ sec. cor. of sec. 33, T. 5 S., R. 23 E., bears N. 89°52' W., 11.93 chs. dist.</p> <p>Raise a mound of stone S. of the Cor.</p> <p>Land, rolling. Soil, gravelly loam Timber, mesquite Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
	<p>Point for the ¼ sec. cor. of sec. 3, is at mid-point and on the N. bdy. of the Tp.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">----- ¼ S 3 T6S R23E 1967</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	<p>from which</p> <p>The standard cor. of secs. 33 and 34 T. 5 S., R. 23 E., bears N. 89°51' W., 12.35 chs. dist.</p> <p>Set a mesquite post, 3½ ft. long, 3 ins. diam., alongside the cor.</p>								
32.20	<p>From the cor. of secs. 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0°08' W., bet. secs. 32 and 33.</p> <p>Over gentle rolling mesa, through moderate undergrowth.</p> <p>Wash, 15 lks. wide, 1 ft. deep, drains irregularly NE.</p>								
42.20	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T6S</td><td>R23E</td></tr> <tr><td>¼</td><td></td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Raise a mound of stone W. of the cor.</p>	T6S	R23E	¼		S32	S33	1967	
T6S	R23E								
¼									
S32	S33								
1967									
45.90	<p>Wash, 60 lks. wide, 1 ft. deep, drains NE.</p>								
73.10	<p>Fence, bears N. 53° E. and S. 53° W.</p>								
82.10	<p>The cor. of secs. 28, 29, 32 and 33, monumented by a granite stone, 20 x 8 x 6 ins., set 12 ins. in the ground, mkd. 4 notches on E. and 1 notch on S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T6S</td><td>R23E</td></tr> <tr><td>S29</td><td>S28</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>from which</p> <p>A windmill, bears N. 49°33' W., 15.98 chs. dist.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, Creosote, cacti and cat claw.</p>	T6S	R23E	S29	S28	S32	S33	1967	
T6S	R23E								
S29	S28								
S32	S33								
1967									
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89° 47' W., bet. secs. 28 and 33.</p>								

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS		
	Over gently rolling mesa, through moderate undergrowth.	
17.10	Wash, 80 lks. wide, 1 ft. deep, drains N.	
20.90	Wash, 50 lks. wide, 1 ft. deep, drains NE.	
40.08	The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented by a sandstone, 14 x 9 x 4 ins., set 6 ins. in the ground, mkd. $\frac{1}{2}$ on N. and 3 on S. faces.	
	At the corner point	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	T6S R23E $\frac{1}{4}$ S28 S33 1967	
	Deposit the orig. cor. stone in a mound of stone N. of the cor.	
	—————	
	N. 89°48' W., beginning new measurement.	
	Over rolling land, through moderate undergrowth.	
7.00	Top of spur, slopes N. 15° W.	
9.90	Wash, in bottom of small canyon 600 lks. wide, drains N. 30° E.	
24.90	Wash, 30 lks. wide, 1 ft. deep, drains NE.	
30.60	Fence, bears N. 53° E. and S. 53° W.	
31.90	W. rim of mesa, bears NE. and SW.	
36.40	Top of spur, slopes N.	
40.17	The cor. of secs. 28, 29, 32 and 33.	
	Land, rolling. Soil, gravelly loam. No timber; Undergrowth, creosote, cacti and cat claw.	
	N. 0°16' W., bet. secs. 28 and 29.	
	Over rolling land, through moderate undergrowth.	
9.90	Enter Tripp and Underwood Valley, bears NE. and SW.	
18.90	Wash, 15 lks. wide, 3 ft. deep, drains NE.	
31.90	Branch of Tripp and Underwood wash, drains NE.	
36.70	Tripp and Underwood wash, 100 lks. wide, 1 ft. deep, drains NE.	
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; unable to find any remaining evidence of the original cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	T6S R23E $\frac{1}{2}$ S29 S28 1967
	Raise a mound of stone W. of the cor.
59.00	Leave Tripp and Underwood Valley, bears NE. and SW.
64.80	Top of spur, slopes E.
67.90	Enter canyon, drains E.
72.30	Leave canyon, drains E.
75.60	Top of ridge, bears NE. and W., thence over gently rolling land.
79.96	The cor. of secs. 20, 21, 28 and 29, monumented by a granite stone, 16 x 10 x 4 ins., set 8 ins. in the ground, mkd. 4 notches on E. and 2 notches on S. faces, from which the remains of the original bearing trees: A mesquite 6 ins. diam., bears S. $52\frac{3}{4}^{\circ}$ W., 66 lks. dist., mkd. T6S R23E S 2 A mesquite 8 ins. diam., bears N. $64\frac{1}{2}^{\circ}$ W., 163 lks. dist., mkd. with an old blaze. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd. T6S R23E $\frac{S20}{S29}$ $\frac{S21}{S28}$ 1967 from which U.S.G.S. Triangulation Station MESQUITE, bears S. $66^{\circ}46'$ W., 25.24 chs. dist., monumented by a brass tablet 3 ins. diam., set in a cement block, mkd. Mesquite 1943. Bury the orig. cor. stone, alongside the iron post. Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor. Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.
	From the cor. of secs. 21, 22, 27 and 28. N. $89^{\circ}45'$ W., bet. secs. 21 and 28. Over gently rolling land, through moderate undergrowth.
.30	Wash, 30 lks. wide, 2 ft. deep, drains N. 60° E.
22.50	Wash, 30 lks. wide, 2 ft. deep, drains N. 60° E.
27.40	Wash, 30 lks. wide, 3 ft. deep, drains N. 60° E.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
40.09	<p>The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented by a granite stone, 14 x 10 x 8 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ 21 on N. and 28 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ $\frac{S21}{S28}$ 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 4 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°53' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
5.70	Enter rolling land, bears NE. and SW.
10.40	Track road, bears S. 20° E. and N. 20° W.
39.86	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, nearly level to broken. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cacti.</p>
	N.0°08' E., bet. secs. 20 and 21.
	Over gently rolling land, through moderate undergrowth.
9.40	Dirt road, bears SE. and NW.
11.80	Aravaipa and Klondike road, bears S. 52° W. and N. 52° E., 250 lks. dist., thence N. 87° E.
14.20	Fence, bears N. 87° E. and S. 87° W.
27.90	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° E.
40.17	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented by a granite stone, 14 x 8 x 4 ins., set 7 ins. in the ground, mkd. $\frac{1}{4}$ 20 on W. and 21 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S20 S21 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS									
	<p>N. 0°07' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>3.60 Wash, 10 lks. wide, 1 ft. deep, drains irregularly NE.</p> <p>24.70 Wash, 15 lks. wide, 2 ft. deep, drains NE.</p> <p>37.60 Wash, 15 lks. wide, 1 ft. deep, drains NE.</p> <p>40.04 The cor. of secs. 16, 17, 20 and 21, monumented by a granite stone, 16 x 14 x 6 ins., set 8 ins. in the ground, mkd. 4 notches on E. and 3 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T6S</td> <td>R23E</td> </tr> <tr> <td><u>S17</u></td> <td><u>S16</u></td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2">1967</td> </tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 7 ft. long, 3 ins. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote, sagebrush, cacti and cat claw.</p>	T6S	R23E	<u>S17</u>	<u>S16</u>	S20	S21	1967	
T6S	R23E								
<u>S17</u>	<u>S16</u>								
S20	S21								
1967									
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°49' W., bet. secs. 16 and 21.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>4.10 Fence, bears N. 6°30' E. and S. 6°30' W.</p> <p>4.40 Bladed road, bears N. 6°30' E. and S. 6°30' W.</p> <p>40.15 True point for the ¼ sec. cor. of secs. 16 and 21, at proportionate dist., falls in a wash area. The cor. point was not originally monumented and is still in unsafe location.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°54' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>0.15 Wash, 15 lks. wide, 2 ft. deep, drains N.</p> <p>1.20 The witness ¼ sec. cor. of secs. 16 and 21, monumented by a granite stone, 14 x 10 x 9 ins., set 6 ins. in the ground, mkd. WC ¼ 16 on N. and 21 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>								

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p style="text-align: center;">T6S R23E $\begin{array}{c} W \frac{1}{4} \frac{S16}{S21} \rightarrow \\ C \end{array}$ 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p>8.20 Wash, 25 lks. wide, 1 ft. deep, drains NE.</p> <p>28.70 Wash, 30 lks. wide, 3 ft. deep, drains NE.</p> <p>40.08 The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, nearly level to gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti, cat claw and bunch grass.</p>
	<p>N. 0°02' E., bet. secs. 16 and 17.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>22.80 Wash, 50 lks. wide, 2 ft. deep, drains NE.</p> <p>40.08 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented by a granite stone, 16 x 9 x 6 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ 17 on W. and 16 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\begin{array}{c} \frac{1}{4} \\ S17 S16 \\ 1967 \end{array}$</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>
	<p>N. 0°01' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>13.40 Bladed road, bears S. 50° E. and N. 50° W.</p> <p>19.30 Wash, 15 lks. wide 1 ft. deep, drains NE.</p> <p>37.00 Wash, 30 lks. wide, 2 ft. deep, drains NE.</p> <p>40.13 The cor. of secs. 8, 9, 16 and 17, monumented by a granite stone, 16 x 8 x 6 ins., set 10 ins. in the ground, mkd. 4 notches on E. and S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\begin{array}{c} S 8 S 9 \\ S17 S16 \\ 1967 \end{array}$</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti and cat claw.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°49' W., bet. secs. 9 and 16.</p> <p>Over broken land, through moderate undergrowth.</p>
11.10	Wash, 20 lks. wide, 1 ft. deep, drains N.
15.80	Wash, 20 lks. wide, 1 ft. deep, drains N.
19.20	Wash, 40 lks. wide, 3 ft. deep, drains NE.
40.15	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented by a granite stone, 16 x 8 x 6 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ 9 on N. and 16 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T6S R23E $\frac{1}{4}$ S 9 S16 1967 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°50' W., beginning new measurement.</p> <p>Over gently rolling land, through railed area, bears N. and S.</p>
20.00	Leave railed area, bears N. and S.
26.90	Wash, 10 lks. wide, 1 ft. deep, drains NE.
34.90	Wash, 40 lks. wide, 3 ft. deep, drains NE.
40.09	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, broken to rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti, cat claw and bunch grass.</p>
	<p>N. 0°03' E., bet. secs. 8 and 9.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
4.00	Wash, 40 lks. wide, 1 ft. deep, drains NE.
36.20	Wash, 10 lks. wide, 1 ft. deep, drains NE.

CHAINS		
37.90	Track road, bears N. 30° E. and S. 40° W.	
40.16	The ¼ sec. cor. of secs. 8 and 9, as determined from the remains of one of two original bearing trees:	
	A mesquite 8 ins. diam., bears N. 5° W., 151 lks. dist., mkd. BT.	
	At the corner point	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T6S R23E $\frac{1}{4}$ S 8 S 9 1967</p>	
	Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.	
	<p style="text-align: center;">_____</p> North, beginning new measurement.	
	Over gently rolling land, through moderate undergrowth.	
8.70	Wash, 100 lks. wide, 1 ft. deep, drains NE.	
17.20	Wash, 40 lks. wide, 1 ft. deep, drains E.	
25.80	Wash, 15 lks. wide, 2 ft. deep, drains NE.	
40.14	The cor. of secs. 4, 5, 8 and 9, monumented by a granite stone, 16 x 10 x 6 ins., set 10 ins. in the ground, mkd. 4 notches on E. and 5 notches on S. faces, from which the remains of one of two original bearing trees:	
	A mesquite 6 ins. diam., bears S. 63° W., 254 lks. dist., mkd. with an old blaze.	
	At the corner point	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T6S R23E S 5 S 4 S 8 S 9 1967</p>	
	Bury the orig. cor. stone alongside the iron post.	
	Set a mesquite post, 5 ft. long, 5 ins. diam., alongside the cor.	
	Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cat claw and cacti.	
	From the cor. of secs. 3, 4, 9 and 10.	
	N. 89°45' W., bet. secs. 4 and 9.	
	Over rolling land, through moderate undergrowth.	
12.30	Wash, 100 lks. wide, 2 ft. deep, drains NE.	
35.70	Top of ridge, bears N. and S.	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
40.07	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented by a granite stone, 14 x 6 x 6 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ 4 on N. and 9 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <p>$\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$</p> <p>1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 4 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°46' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>1.30 Wash, 10 lks. wide, 1 ft. deep, drains N. 20° E.</p> <p>4.60 Track road, bears N. 30° E. and S. 30° W.</p> <p>15.00 Wash, 100 lks. wide, 3 ft. deep, drains N. 20° E.</p> <p>40.20 The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cacti.</p>
8.20	<p>N. 0°01' W., bet. secs. 4 and 5.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>23.80 Wash, 30 lks. wide, 1 ft. deep, drains NE.</p> <p>40.13 The $\frac{1}{4}$ sec. cor of secs. 4 and 5, monumented by a granite stone, 9 x 8 x 6 ins., set 5 ins., in the ground, mkd. $\frac{1}{4}$ 5 on W. and 4 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <p>$\frac{1}{4}$ $S\ 5 S\ 4$</p> <p>1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' W., beginning new measurement.</p>

CHAINS	
	Over gently rolling land, through moderate undergrowth.
8.20	Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.
36.04	Intersect the First Standard Parallel South.
	The closing cor. of secs. 4 and 5, monumented by a granite stone, 14 x 8 x 8 ins., set 8 ins. in the ground, mkd. CC on S. 4 notches and E. and 2 notches on W. faces.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;"> T5S S32 <hr style="width: 50px; margin: 0 auto;"/> S 5 S 4 T6S R23E C C 1967 </p>
	from which
	<p style="text-align: center;"> The Standard ¼ sec. cor. of sec. 32, T. 5 S., R. 23 E., bears N. 89°54' W., 11.62 chs. dist. </p>
	Bury the orig. cor. stone alongside the iron post.
	Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.
	Land, gently rolling.
	Soil, gravelly loam.
	Timber, mesquite.
	Undergrowth, creosote, cat claw, sagebrush, and cacti.
	Point for the ¼ sec. cor. of sec. 4, is at mid-point and on the N. bdy. of the Tp.
	At the corner point
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;"> <hr style="width: 50px; margin: 0 auto;"/> ¼ S 4 T6S R23E 1967 </p>
	from which
	<p style="text-align: center;"> The Standard cor. of secs. 32 and 33, T. 5 S., R. 23 E., bears N. 89°58' W., 11.75 chs. dist. </p>
	Raise a mound of stone S. of the cor.
	From the true point for the cor. of secs. 31 and 32, on the S. bdy. of the Tp.
	N. 0°34' E., bet. secs. 31 and 32.
	Over rolling land, through moderate undergrowth.
.30	Left bank of Tripp and Underwood Wash, bears NE. and SW.

Dep. Resurvey, Subdivisional lines, T. 6 S., R. 23 E., Arizona

CHAINS	
1.30	Same wash, 2.00 chs. wide, 2 ft. deep, drains NE. (Branch)
14.70	Leave Tripp and Underwood Valley, bears NE. and SW.; asc. SE. slope.
18.50	Top of spur, slopes E.
23.60	Top of spur, slopes NE.
27.30	Wash, 25 lks. wide, 3 ft. deep, drains NE.
34.30	S. rim of mesa, bears NE. and SW., thence across gently rolling mesa top.
43.14	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T6S R23E $\frac{1}{4}$ S31 S32 1967
	from which
	A fence bearing N. and S., bears West, 26 lks. dist.
	Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.
45.35	Wash, 50 lks. wide, $\frac{1}{2}$ ft. deep, drains NE.
83.13	The cor. of secs. 29, 30, 31 and 32, monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. 5 notches on E. and 1 notch on S. faces, from which the remains of the original bearing tree:
	A mesquite 6 ins. diam., bears N. 52° E., 57 $\frac{1}{2}$ lks. dist., mkd. with an old blaze. (Record N. 69° E., no record dist.).
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T6S R23E S30 S29 S31 S32 1967
	from which
	A fence bearing N. and S., bears West, 66 lks. dist.
	Bury the orig. cor. stone alongside the iron post.
	Set a mesquite post, 4 ft. long, 6 ins. diam., alongside the cor.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
	<p>Land, rolling. Soil, gravelly loam. No timber; undergrowth, sagebrush, cat claw and cacti.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°51' W., bet. secs. 29 and 32.</p> <p>Over rolling land, through moderate undergrowth.</p>
4.00	Enter Tripp and Underwood Valley, bears NE. and SW.
13.20	Tripp and Underwood Wash, 200 lks. wide, 1 ft. deep, drains N. 10° E.
18.40	Wash, 100 lks. wide, 1 ft. deep, drains N. 10° E.
38.50	Leave Tripp and Underwood Valley, bears N. 30° E. and S.
39.85	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ 29 on N. and 32 on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ <u>S29</u> S32 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>
	<hr style="width: 20%; margin: 0 auto;"/>
	<p>N. 89°47' W., beginning new measurement.</p> <p>Ascend NE. slope of mesa.</p>
1.10	Top of spur, slopes S. 50° E.
5.80	Top of ridge, bears N. 25° E. and S. 25° W.
11.90	Top of spur, slopes NE.
19.20	Top of mesa, thence over nearly level land.
39.30	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling to nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cacti and cat claw.</p>
	<p>N. 89°55' W., bet. secs. 30 and 31.</p> <p>Over nearly level land, through moderate undergrowth.</p>
.66	Fence, bears N. and S.
14.80	Araviapa and Klondike road, bears N. 60° E. and S. 60° W.
23.90	Wash, 20 lks. wide, 1 ft. deep, drains NE.
38.60	Wash, 20 lks. wide, 1 ft. deep, drains NE.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
40.84	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented by a granite stone, 10 x 8 x 4 ins., set 6 ins. in the ground, no legible mks., from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A mesquite 6 ins. diam., bears S. $12\frac{1}{2}^\circ$ W., 57 lks. dist., mkd. $\frac{1}{4}$ 31 BT.</p> <p style="padding-left: 40px;">A mesquite 6 ins. diam., bears N. $72\frac{1}{2}^\circ$ W., 25 lks. dist., mkd. $\frac{1}{4}$ 30 BT.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <p>$\frac{1}{4}$ $\frac{S30}{S31}$</p> <p>1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p>
.30	<p>Wash, 15 lks. wide, 2 ft. deep, drains N. 65° E.</p>
13.20	<p>Wash, 20 lks. wide, 1 ft. deep, drains NE.</p>
20.08	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 30 and 31, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <p>W $\frac{1}{16}$ $\frac{S30}{S31}$</p> <p>1967</p> </div> <p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p>
28.40	<p>Track road, bears SE. and NW.</p>
32.50	<p>Track road, bears N. and S.</p>
32.70	<p>Fence, bears N. and S.</p>
36.55	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, sagebrush, cat claw and cacti.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. $1^\circ 02'$ W., bet. secs. 29 and 30.</p> <p>Over gently rolling land, through moderate undergrowth.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
12.20	Aravaipa and Klondike road, bears N. 49° E. and SW.
12.40	Fence, bears N. 43°30' E. and S. 43°30' W.
33.60	Wash, 10 lks. wide, 2 ft. deep, drains NE.
40.02	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented by a granite stone, 18 x 6 x 6 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ 30 on W. and 29 on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4}$ S30 S29 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°01' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
11.70	Wash, 30 lks. wide, 1 ft. deep., drains NE.
23.20	Wash, 20 lks. wide, 1 ft. deep, drains NE.
40.13	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a granite stone, 16 x 8 x 8 ins., set 10 ins. in the ground, mkd. 5 notches on E. and 2 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E <u>S19 S20</u> S30 S29 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, rolling, gently. Soil, gravelly loam. Timber, mesquite. Undergrowth, sagebrush, cat claw and cacti.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°23' W., bet. secs. 20 and 29.</p> <p>Over broken land, through moderate undergrowth.</p>
13.10	Leave broken land, enter gently rolling land.
13.30	Aravaipa and Klondike road, bears N. 50° E. and SW.

Dep. Resurvey, Subdivisional lines, T. 6 S., R. 23 E., Arizona

CHAINS	
15.90	Fence, bears N. 48°30' E. and S. 48°30' W.
35.70	Wash, 10 lks. wide, 2 ft. deep, drains NE.
39.44	The ¼ sec. cor. of secs. 20 and 29, monumented by a granite stone, 18 x 16 x 12 ins., set 10 ins. in the ground, mkd. ¼ 20 on N. and 29 on S. faces.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T6S R23E} \\ \frac{1}{4} \frac{\text{S20}}{\text{S29}} \\ 1967 \end{array}$
	Bury the orig. cor. stone alongside the iron post.
	Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.
	<hr style="width: 20%; margin: auto;"/>
	N. 89°50' W., beginning new measurement.
	Over gently rolling land, through moderate undergrowth.
20.40	Wash, 20 lks. wide, 2 ft. deep, drains NE.
40.07	The cor. of secs. 19, 20, 29 and 30.
	Land, broken to nearly level. Soil, gravelly loam. Timber, mesquite. Undergrowth, cacti, cat claw, sagebrush and grass.
	N. 89°47' W., bet. secs. 19 and 30.
	Over gently rolling land, through moderate undergrowth.
1.60	Wash, 40 lks. wide, 3 ft. deep, drains NE.
10.80	Wash, 30 lks. wide, 2 ft. deep, drains NE.
16.90	Wash, 25 lks. wide, 2 ft. deep, drains NE.
25.70	Wash, 25 lks. wide, 2 ft. deep, drains NE.
29.40	Wash, 20 lks. wide, 2 ft. deep, drains NE.
40.12	The ¼ sec. cor. of secs. 19 and 30, monumented by a limestone, 12 x 10 x 3 ins., set 6 ins. in the ground, no legible mks. on weathered remains. I accept this as the best remaining evidence of the original cor.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T6S R23E} \\ \frac{1}{4} \frac{\text{S19}}{\text{S30}} \\ 1967 \end{array}$
	Bury the orig. cor. stone alongside the iron post.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
36.63	<p>Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, cacti, catclaw and grass.</p>
4.10	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°01' W., bet. secs. 19 and 20.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Wash, 40 lks. wide, 2 ft. deep, drains NE.</p>
7.70	<p>Wash, 30 lks. wide, 2 ft. deep, drains NE.</p>
38.90	<p>Wash, 50 lks. wide, 2 ft. deep, drains N. 30° E.</p>
40.13	<p>The ¼ sec. cor. of secs. 19 and 20, monumented by a granite stone, 18 x 12 x 10 ins., set 10 ins. in the ground, mkd. ¼ 19 on W. and 20 on E. faces.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ S19 S20 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 6 ft. long, 3 ins. diam., alongside the cor.</p> <hr/> <p>N. 0°33' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
3.00	<p>Wash, 30 lks. wide, 2 ft. deep, drains NE.</p>
39.78	<p>The cor. of secs. 17, 18, 19 and 20, monumented by a granite stone, 18 x 8 x 8 ins., set 10 ins. in the ground, mkd. with 5 notches on E. and 3 notches on S. faces.</p> <p>At the cor. point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T6S R23E S18 S17 S19 S20 1967</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	<p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite Undergrowth, sagebrush, cat claw, cacti and creosote.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°47' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>2.10 Wash, 25 lks. wide, 1 ft. deep, drains NE.</p> <p>14.80 Wash, 40 lks. wide, 2 ft. deep, drains NE.</p> <p>19.80 Wash, 20 lks. wide, 1 ft. deep, drains NE.</p> <p>40.09 The ¼ sec. cor. of secs. 17 and 20, monumented by a limestone, 10 x 9 x 3 ins., set 5 ins. in the ground, no legible mks., from which the remains of the orig. bearing tree</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. 67¼° E., 50 lks. dist., mkd. B.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ $\frac{S17}{S20}$ 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 2 ins. diam., alongside the cor.</p> <hr/> <p>N. 89°48' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>7.20 Wash, 40 lks. wide, 6 ft. deep, drains NE.</p> <p>17.00 Wash, 40 lks. wide, 3 ft. deep, drains N.</p> <p>30.90 Wash, 15 lks. wide, 1 ft. deep, drains NE.</p> <p>40.03 The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cat claw, cacti and bunch grass.</p> <hr/> <p>N. 89°45' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>34.30 Wash, 15 lks. wide, 1 ft. deep, drains N.</p>
--------	---

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
40.18	<p>The ¼ sec. cor. of secs. 18 and 19, as determined from the remains of the orig. bearing trees</p> <p>A mesquite 6 ins. diam., bears S. 47½° W., 147 lks. dist., mkd. with an old blaze.</p> <p>A mesquite 6 ins. diam., bears N. 40 3/4° W., 166½ lks. dist., mkd. BT.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ $\frac{S18}{S19}$ 1967</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
10.70	Wash, 10 lks. wide, 1 ft. deep, drains NE.
21.20	Dim track road, bears N. 10° E. and S. 10° W.
28.30	Wash, 10 lks. wide, 1 ft. deep, drains NE.
36.36	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti, cat claw and bunch grass.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°06' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
16.20	Wash, 25 lks. wide, 2 ft. deep, drains NE.
40.12	<p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E ¼ S18 S17 1967</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p>
41.00	Wash, 25 lks. wide, 1 ft. deep, drains NE.
51.70	Bladed road, bears N. 85° E. and S. 75° W.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
54.60	Wash, 20 lks. wide, 2 ft. deep, drains NE.
80.24	<p>The cor. of secs. 7, 8, 17 and 18, monumented by a limestone, 10 x 8 x 3 ins., set 5 ins. in the ground, no legible mks. on weathered remains. I accept this as the best remaining evidence of the original cor.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E S 7 S 8 S18 S17 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, catclaw, sagebrush and cacti.</p>
	From the cor. of secs. 8, 9, 16 and 17.
	N. 89°49' W., bet. secs. 8 and 17.
	Over gently rolling land, through moderate undergrowth.
3.80	Wash, 30 lks. wide, 1½ ft. deep, drains NE.
17.90	Track road, bears N. 30° E. and S. 30° W.
22.80	Wash, 15 lks. wide, 1 ft. deep, drains NE.
27.20	Wash, 25 lks. wide, 2 ft. deep, drains NE.
40.15	<p>The ¼ sec. cor. of secs. 8 and 17, monumented by a limestone, 8 x 8 x 3 ins., set 7 ins. in the ground, no legible mks. on weathered remains. I accept this as the best remaining evidence of the original cor.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E S 8 ¼ S17 1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°51' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
3.50	Wash, 10 lks. wide, 1 ft. deep, drains NE.

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
13.40	Wash, 25 lks. wide, 2 ft. deep, drains NE.
40.15	The cor. of secs. 7, 8, 17 and 18.
	Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cat claw, cacti and bunch grass.
	N. 89°45' W., bet. secs. 7 and 18.
	Over gently rolling land, through moderate undergrowth.
9.50	Wash, 10 lks. wide, 1½ ft. deep, drains NE.
27.60	Wash, 15 lks. wide, 1 ft. deep, drains NE.
40.14	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T6S R23E ¼ S 7 S18 1967
	Set a mesquite post, 4 ft. long, 3 ins. diam., alongside the cor.
57.40	Dim track road, bears N. 10° E. and S. 10° W.
60.40	Wash, 20 lks. wide, 1 ft. deep, drains NE.
76.52	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cat claw, cacti and bunch grass.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°01' E., bet. secs. 7 and 8.
	Over gently rolling land, through moderate undergrowth.
.50	Wash, 30 lks. wide, 1 ft. deep, drains NE.
33.50	Wash, 20 lks. wide, 4 ft. deep, drains NE.
40.14	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T6S R23E ¼ S 7 S 8 1967

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS							
58.30	<p>Set a mesquite post, 3½ ft. long, 3 ins. diam., alongside the cor.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains NE.</p>						
64.50	<p>Wash, 20 lks. wide, 1 ft. deep, drains NE.</p>						
67.30	<p>Wash, 40 lks. wide, 3 ft. deep, drains N. 60° E.</p>						
80.27	<p>The cor. of secs. 5, 6, 7 and 8, as determined from the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S. 72½° W., 78½ lks. dist., mkd. 6 S 7 R 2.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>1967</p> </div> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush, cat claw and cacti.</p>	S 6	S 5	S 7	S 8		
S 6	S 5						
S 7	S 8						
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>						
	<p>N. 89°53' W., bet. secs. 5 and 8.</p>						
	<p>Over rolling land, through moderate undergrowth.</p>						
1.90	<p>Wash, 10 lks. wide, 2 ft. deep, drains NE.</p>						
9.00	<p>Wash, 25 lks. wide, 2 ft. deep, drains NE.</p>						
29.00	<p>Wash, 20 lks. wide, 1 ft. deep, drains NE.</p>						
39.12	<p>The witness ¼ sec. cor. of secs. 5 and 8, monumented by a granite stone, 12 x 6 x 6 ins., set 6 ins. in the ground, mkd. ¼ on N., WC on E. and 8 on S. faces.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R23E</p> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">¼ ←</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">W</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">C</td> </tr> </table> <p>1967</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 4 ins. diam., alongside the cor.</p>	¼ ←	S 5	W		S 8	C
¼ ←	S 5	W					
	S 8	C					
40.12	<p>True point for the ¼ sec. cor. of secs. 5 and 8, at proportionate dist. falls in a wash area. The cor. point was not originally monumented and is still in unsafe location.</p>						

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS	
20.50 30.60 40.18	<p>N. 89°51' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 50 lks. wide, 2 ft. deep, drains NE.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains NE.</p> <p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cacti.</p>
11.60 28.40 40.13 63.70 76.44	<p>N. 89°48' W., bet. secs. 6 and 7.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Fence, bears N. 26° E. and S. 26° W.</p> <p>Wash, 15 lks. wide, 1 ft. deep, drains NE.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R23E $\frac{1}{4} \frac{S 6}{S 7}$ 1967</p> <p>Set a mesquite post, 3$\frac{1}{2}$ ft. long, 4 ins. diam., alongside the cor.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains NE.</p> <p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <p>Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, sagebrush and cacti.</p>
4.50 14.80 18.10 40.12	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°06' W., bet. secs. 5 and 6.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains N. 50° E.</p> <p>Fence, bears N. 63°30' E. and S. 63°30' W.</p> <p>Wash, 30 lks. wide, 1 ft. deep, drains NE.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS		
	<p style="text-align: center;">T6S R23E $\frac{1}{4}$ S 6 S 5 1967</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside the cor.</p>	
50.80	Wash, 15 lks. wide, 1 ft. deep, drains NE.	
76.12	<p>Intersect the First Standard Parallel South.</p> <p>The closing cor. of secs. 5 and 6, monumented by a limestone, 18 x 16 x 6 ins., set 10 ins. in the ground, mkd. with 5 notches on E. face, no other mks. legible.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T5S S31 <hr style="width: 50px; margin: 0 auto;"/> S 6 S 5 T6S R23E C C 1967</p> <p>from which</p> <p style="padding-left: 40px;">The Standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 5 S., R. 23 E., bears N. 89°50' W., 10.79 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber. Undergrowth, creosote, cacti and sagebrush.</p>	
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 5, is at mid-point and on the N. bdy. of the Tp.</p> <p>At the cor. point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 5 <hr style="width: 50px; margin: 0 auto;"/> T6S R23E 1967</p> <p>from which</p> <p style="padding-left: 40px;">The Standard cor. of secs. 31 and 32, T. 5 S., R. 23 E., bears N. 89°55' W., 11.07 chs. dist.</p> <p>Set a mesquite post, 4 ft. long, 4 ins. diam., alongside the cor.</p>	

Dep. Resurvey, Subdivisional Lines, T. 6 S., R. 23 E., Arizona

CHAINS

Point for the $\frac{1}{4}$ sec. cor. of sec. 6, is at proportionate dist., and on the N. bdy. of the Tp.

Set the iron post 22 ins. in the ground, brass cap mkd.

 $\frac{1}{4}$ S 6
 T6S R23E
 1967

from which

The Standard Tp. cor. of Tps. 5 S., Rs. 22 and 23 E., bears S. 89°57' W., 10.33 chs. dist.

Set a mesquite post 4 ft. long, 4 ins. diam., alongside the cor.

General Description

Township 6 South, Range 23 East, lies approximately 9 miles west of Pima, Arizona. The elevation ranges from about 2900 feet in section 1 to about 3550 feet above sea level in section 31. Most of the township is gently rolling land becoming slightly broken in the SW. portion.

The soil is gravel clay loam, which supports a moderate growth of creosote, sagebrush, cacti, cat claw, mesquite and bunch grass. Livestock grazing is the primary interest at present.

Range improvements noted within the township were spreader dikes for erosion control and two test plots, one bet. secs. 13 and 24, the other bet. secs. 35 and 36.

Aravaipa and Klondike road enters the township in section 1, traversing southwesterly leaving the township in section 31.

83

CERTIFICATE OF SURVEY

~~XXX~~ (We), Kenneth D. Herman and Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of January, 1967, ~~XX~~ (We) have dependently resurveyed the exterior boundaries and subdivisional lines of Township 6 South, Range 23 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~ (us) and under ~~my~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 15, 1968 (Date) Kenneth D. Herman (Cadastral Surveyor)
March 15, 1968 (Date) Gary T. Oviatt (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date DEC 19 1969

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of the exterior boundaries and subdivisional lines of Township 6 South, Range 23 East, Gila and Salt River Meridian, Arizona,

executed by Kenneth D. Herman and Gary T. Oviatt, having been critically examined and found correct, are hereby approved.

MAR 2 1971 (Date) Clark F. Gumm (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys is a true copy of the original field notes.~~

~~(Date) (Chief, Division of Cadastral Survey) GPO 849-626~~