

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

EAST AND SOUTH BOUNDARIES

and

SUBDIVISIONAL LINES

of

TOWNSHIP 7 SOUTH, RANGE 24 EAST

Of the Gila and Salt River Meridian Meridian,

In the State of Arizona

EXECUTED BY

Kenneth D. Herman, Cadastral Surveyor

Under special instructions dated January 30, 19 67, which provided for the surveys
included under Group Number 451, approved January 30, 1967,
and assignment instructions dated January 30, 19 67.

Survey commenced March 3, 19 67

Survey completed April 25, 19 67

BOOK 4881

INDEX DIAGRAM

Township 7 South, Range 24 East

6	61 5	48 4	39 3	30 2	19 20 1	6
60 7	59 58 8	47 46 9	38 37 10	29 28 11	20 19 12	5
57 18	56 56 17	45 44 16	36 36 15	27 26 14	18 17 13	4
55 19	54 53 20	44 43 21	35 34 22	26 25 23	16 15 24	3
53 52 30	52 51 29	42 42 28	33 33 27	23 23 26	15 14 25	3
50 31	50 49 32	41 40 33	32 31 34	22 21 35	13 12 36	1
11	11	10	9	8	7	

Township 7 South, Range 24 East
Gila and Salt River Meridian, Arizona

CHAINS

The east and north boundaries were surveyed in 1875 by T. F. White. The west boundary was surveyed in 1884 by L. Wolfley. The south boundary and subdivisional lines were surveyed in 1886 by C. H. Wallace. The north 4 miles of the east boundary were retraced and the north boundary resurveyed in 1916 by A. B. Rich. The following corners were remonumented, with iron posts, by L. Mann in 1960 under the Forest Service Remonumentation Program: The cor. of Tps. 7 and 8 S., Rs. 24 and 25 E.; the $\frac{1}{4}$ sec. cor. of Secs. 25 and 36; the cor. of secs. 23, 24, 25 and 26; the $\frac{1}{4}$ sec. cor. of Secs. 26 and 35; the cor. of Secs. 26, 27, 34 and 35; the cor. of Secs. 28, 29, 32 and 33 and the cor. of Secs. 29, 30, 31 and 32. The west boundary was resurveyed concurrently under this same group as described in the field notes of Township 7 South, Range 23 East.

The following notes are those of a dependent resurvey of the east and south boundaries and subdivisional lines of Township 7 South, Range 24 East, Gila and Salt River Meridian, Arizona, designed to restore the corners in their original location according to the best available evidence.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated January 30, 1967.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude, $32^{\circ}46'25''$ North, and Longitude, $109^{\circ}50'03''$ West. This position was calculated from a direct tie to U. S. Soil Erosion Service Triangulation Station BEAR located in section 11, Township 7 South, Range 23 East.

The mean magnetic declination was found to be: $13\frac{1}{2}^{\circ}$ East.

Dependent Resurvey of the East Boundary
T. 7 S., R. 24 E., G&SR M., Arizona

Reestablishment of the Survey Executed
by T. F. White in 1875

The cor. of Tps. 7 and 8 S., Rs. 24 and 25 E., monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 10 ins. above the ground, mound of stone to top, brass cap mkd.

T7S	
R24E	R25E
S36	S31
<hr style="width: 50%; margin: 0 auto;"/>	
S1	S6
T8S	
1960	

This cor. was set in 1960 under the US Forest Service Remonumentation Program.

Dep. Resurvey, East Boundary, T. 7 S., R. 24 E.

CHAINS	
	<p>from which</p> <p>A fence cor., bears S. $30\frac{1}{4}^{\circ}$ W., 7 lks. dist.; fences bear N., S. and W.</p> <p>N. $0^{\circ}02'$ E., bet. secs. 31 and 36.</p> <p>Over mountainous land, through moderate undergrowth; asc. SW. slope.</p>
1.80	Spur, slopes W.; desc. NW. slope.
16.30	Fence, bears NW. and SE.
18.20	Ravine, drains NE. for 5 chs. thence NW.; continue desc. N. slope.
26.10	Enter same ravine, drains N.
39.85	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E $\frac{1}{4}$ S36 S31 1967</p> <p>Cor. is located in ravine, S. and E. of wash in bottom.</p>
41.00	Leave ravine, drains E.; continue desc. N. slope.
46.30	Fence, bears irregularly E. and W.
48.00	Wash in Spring Canyon, drains S. 65° E.
52.20	Fence, bears SE. and NW.
79.70	<p>The cor. of secs. 25, 30, 31 and 36, monumented by a mound of stone, 2 ft. high, 4 ft. base, from which the remains of the orig. bearing trees:</p> <p>A mesquite stump, 8 ins. diam., bears N. $87\frac{3}{4}^{\circ}$ W., 217 lks. dist., no visible marks. (Record bearing N. $88\frac{1}{2}^{\circ}$ W.)</p> <p>A mesquite stump, 7 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W., 164 lks. dist., no visible marks. (Record)</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E <u>S25 S30</u> S36 S31 1967</p> <p>Land, mountainous. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.</p>

Dep. Resurvey, East Boundary, T. 7 S., R. 24 E.

CHAINS		
<p>N. 0°01' W., bet. secs. 25 and 30.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>5.80 Wash in Hawk Hollow Canyon, 30 lks. wide, 2 ft. deep, drains NE.</p> <p>9.80 Wash, 50 lks. wide, 4 ft. deep, drains NE.</p> <p>14.40 Wash, 100 lks. wide, 3 ft. deep, drains NE.</p> <p>39.96 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by a mound of stone $1\frac{1}{2}$ ft. high, 3 ft. base, accepted as best remaining evidence of the orig. cor. position.</p>	<p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E $\frac{1}{4}$ S25 S30 1967</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>4.30 Wash, 50 lks. wide, 2 ft. deep, drains N. 65° E.</p> <p>15.20 Fence, bears S. 82° E. and N. 82° W.</p> <p>16.40 Track road, bears E. and W.</p> <p>40.02 The cor. of secs. 19, 24, 25 and 30, monumented by a granite stone, 26 x 12 x 8 ins., firmly set in a mound of stone, mkd. 2 notches on S. and 4 notches on N. faces.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E S24 S19 S25 S30 1967</p> <p>from which</p> <p style="text-align: center;">A windmill at Mud Springs, bears S. 84°18' W., 23.56 chs. dist.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, rocky loam. No timber; undergrowth, cacti, creosote, cat claw and grass.</p>	
	<p>N. 0°01' E., bet. secs. 19 and 24.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	

Dep. Resurvey, East Boundary, T. 7 S., R. 24 E.

<p>CHAINS 39.90</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented by a mound of stone, from which the remains of an orig. bearing tree:</p> <p style="padding-left: 40px;">A mesquite stump, 5 ins. diam., bears N. $5\frac{1}{2}^\circ$ W., 70 lks. dist., no visible marks.</p> <p>At the corner point</p> <p>Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E $\frac{1}{4}$ S24 S19 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. $3^\circ 49'$ E., 45 lks. dist., fences bear N. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^\circ 01'$ E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
<p>39.34</p>	<p>Point for the cor. of secs. 13, 18, 19 and 24 is at a cor. of fences, bearing E. and S. According to local testimony this is accepted as best remaining evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E <u>S13 S18</u> S24 S19 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. No timber; undergrowth, cacti, creosote, cat claw and grass.</p>
<p>20.10</p>	<p>N. $0^\circ 01'$ E., bet. secs. 13 and 18.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the S $\frac{1}{16}$ sec. cor. of secs. 13 and 18, at proportionate dist.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E S $\frac{1}{16}$ S13 S18 1967</p>

Dep. Resurvey, East Boundary, T. 7 S., R. 24 E.

CHAINS	
	Raise a mound of stone W. of the cor.
31.55	Gravelled road, bears irregularly NE. and SW.
40.20	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor. This cor. is not monumented.
52.20	Power line, bears SW. and NE., 150 lks. dist.; thence bears N.
56.50	Gravelled road, bears SW. and NE., curving abruptly to N.
57.60	Track road, bears E. and W.
58.40	Fence, bears W. and E., 20 lks. dist.; thence bears N.
58.50	Enter E. edge of cultivated field.
80.40	The point for the cor. of secs. 7, 12, 13 and 18, determined longitudinally by proportionate measurement and latitudinally by a fence bearing E. and W. This is the cor. position according to local testimony; it is accepted as the best available evidence of the position of the orig. cor.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T7S R24E R25E S12 S7 S13 S18 1967
	from which
	A fence cor. bears East $4\frac{1}{2}$ lks. dist.; fences bear E., W. and N. $0^{\circ}17'$ W.
	Land, gently rolling to nearly level. Soil, sandy loam. No timber; undergrowth, cacti, creosote and grass.
	N. $0^{\circ}01'$ E., bet. secs. 7 and 12.
	Over nearly level land, along fence line.
8.60	Fence, bears S. $0^{\circ}17'$ E. and N. $0^{\circ}17'$ W.; thence along W. side of gravelled road, bearing N. and S.
39.63	The point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12; determined longitudinally by proportionate measurement and latitudinally by extension of a fence bearing E. and W. The cor. falls in the west edge of road, bearing N. and S. and is the cor. position according to local testimony; it is accepted as the best available evidence of the position of the orig. cor. This cor. is not monumented.
	_____ N. $0^{\circ}01'$ E., beginnine new measurement.
	Over nearly level land, along a fence, bearing N. and S.
40.07	The point for the cor. of secs. 1, 6, 7 and 12; determined longitudinally by proportionate measurement and

Dep. Resurvey, East Boundary, T. 7 S., R. 24 E.

CHAINS

latitudinally by extension of a fence bearing E. and W. The cor. falls in the west edge of a road, bearing N. and S. and is the position according to local testimony; it is accepted as the best available evidence of the position of the orig. cor.

At the corner point

Set the iron post 18 ins. below the surface of the ground, brass cap mkd.

T7S
R24E R25E
S1|S6
S12|S7
1967

from which

An iron post, 30 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 60° W., 32.6 lks. dist., with brass cap mkd. T7S R24E S12 RM 21½ FT 1967 and an arrow pointing to the cor.

An iron post, 30 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 30° W., 55.3 lks. dist., with brass cap mkd. T7S R24E S1 RM 36½ FT 1967 and an arrow pointing to the cor.

The cor. is located in the W. edge of gravelled road, bearing N. and S.

The RM's are located in a fence bearing N. and S.

Land, nearly level.

Soil, sandy loam.

No timber; undergrowth, cacti, creosote and grass.

N. 0°01' E., bet. secs. 1 and 6.

Over nearly level land, along W. edge of gravelled road, bearing N. and S.

39.46

Point for the ¼ sec. cor. of secs. 1 and 6, determined longitudinally by proportionate measurement and latitudinally by extension of a fence bearing E. and W. The cor. falls in the W. edge of a road bearing N. and S. and is the position according to local testimony; it is accepted as the best remaining evidence of the position of the orig. cor.

At the corner point.

Set the iron post 12 ins. below the surface of the ground, brass cap mkd.

T7S
R24E R25E
¼
S1|S6
1967

from which

A spike in a power pole, bears S. 34°30' E., 113½ lks. dist.

Dep. Resurvey, South Boundary, T. 7 S., R. 24 E.

<p>CHAINS</p> <p>2.10</p> <p>13.80</p> <p>26.50</p> <p>37.05</p> <p>38.91</p>	<p>Over mountainous land, through moderate undergrowth.</p> <p>Spur, slopes N.; desc. W. slope.</p> <p>Wash in Hawk Hollow Canyon, 20 lks. wide, 2 ft. deep, drains N.; asc. E. slope.</p> <p>Spur, slopes N.; desc. W. slope.</p> <p>Fence, bears N. and S.</p> <p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T7S R24E <u>S35 S36</u> S2 S1 T8S 1967 </p> <p>from which</p> <p style="padding-left: 40px;">A fence cor. bears S. 63° E., 208 lks. dist., fences bear N. and E.</p> <p>Land, mountainous. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.</p>
<p>6.30</p> <p>28.50</p> <p>34.40</p> <p>35.00</p> <p>35.20</p> <p>38.91</p> <p>61.10</p> <p>77.82</p>	<p>N. 89°35' W., bet. secs. 2 and 35.</p> <p>Over mountainous land, through moderate undergrowth; desc. NW. slope.</p> <p>Ravine, drains N.; asc. E. slope.</p> <p>Spur, slopes N.; desc. W. slope.</p> <p>Water pipe line in a trail road, bears N. 25° E. and S. 25° W.</p> <p>Fence, bears N. 25° E. and S. 25° W.</p> <p>Ash creek, 50 lks. wide, 2 ft. deep, drains N. 25° E.; asc. NE. slope.</p> <p>Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T7S R24E <u>¼ S35</u> S2 T8S 1967 </p> <p>Cor. falls on a ledge 10 ft. high.</p> <p>Spur, slopes N. 25° E.; desc. along NW. slope.</p> <p>Point for the cor. of secs. 2, 3, 34 and 35, at propor-</p>

Dep. Resurvey, South Boundary, T. 7 S., R. 24 E.

CHAINS											
	<p>tionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td>R24E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td>S3</td><td>S2</td></tr> <tr><td colspan="2">T8S</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">The SW. cor. of a shed at McEnary Tunnel, bears N. 45°10' E., 15.72 chs. dist.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered juniper and oak. Undergrowth, cacti, cat claw and bunch grass.</p>	T7S	R24E	S34	S35	S3	S2	T8S		1967	
T7S	R24E										
S34	S35										
S3	S2										
T8S											
1967											
	<p>N. 89°35' W., bet. secs. 3 and 34.</p> <p>Over mountainous land, through moderate undergrowth.</p>										
6.00	Ravine, drains N.; asc. NE. slope.										
21.70	Spur, slopes N.; desc. NW. slope.										
26.00	Ravine, drains N. 25° E.; asc. E. slope.										
31.70	Spur, slopes N.; desc. W. slope.										
37.40	Wash, 20 lks. wide, 2 ft. deep, drains NW.; asc. along W. slope.										
38.70	Spur, slopes N.; desc. W. slope.										
38.91	<p>Point for the ¼ sec. cor. of secs. 3 and 34 at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td>R24E</td></tr> <tr><td>¼ S34</td><td></td></tr> <tr><td>S3</td><td></td></tr> <tr><td colspan="2">T8S</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div>	T7S	R24E	¼ S34		S3		T8S		1967	
T7S	R24E										
¼ S34											
S3											
T8S											
1967											
45.00	Deep ravine, drains N.; asc. E. slope.										
49.00	Spur, slopes N. 25° E.; desc. NW. slope.										
55.70	Junction of two washes in White Streaks Canyon, drains N. 65° E., from SW. and W.; thence asc. along wash.										
67.60	Wash; continue asc., leave wash draining E. from S. 20° W.										
77.82	<p>The cor. of secs. 3, 4, 33 and 34, monumented by a granite stone, 30 x 11 x 6 ins., set 10 ins. in the ground, mkd. 3 notches on E. and W. faces, mound of stone W.</p> <p>At the corner point</p>										

Dep. Resurvey, South Boundary, T. 7 S., R. 24 E.

CHAINS	
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E <u>S33 S34</u> S4 S3 T8S 1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.</p>
	<p>N. 89°50' W., bet. secs. 4 and 33.</p> <p>Over mountainous land, through moderate undergrowth.</p>
9.00	Spur, slopes N.
16.30	Begin desc. W. slope.
22.60	Ravine, drains N.; asc. E. slope.
28.60	Spur, slopes N.; desc. W. slope.
37.74	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 4 and 33.
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E WC $\frac{1}{4}$ ← <u>S33</u> S4 T8S 1967</p> </div>
39.70	Ravine, drains N.; asc. E. slope.
39.74	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.; cor. falls in a ravine in a position impractical to monument.
50.90	Spur, slopes N.; desc. W. slope.
65.70	Wash, 10 lks. wide, 2 ft. deep, drains N. 25° W.; continue desc..
79.48	<p>The cor. of secs. 4, 5, 32 and 33, monumented by a granite stone, 30 x 10 x 10 ins., firmly set in a mound of stone, mkd. 4 notches on E. and 2 notches on W. faces, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E <u>S32 S33</u> S5 S4 T8S 1967</p> </div>

Dep. Resurvey, South Boundary, T. 7 S., R. 24 E.

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A tram tower, bears S. 60° E., 155 lks. dist.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. Timber, widely scattered juniper and oak. Undergrowth, cacti, cat claw and bunch grass.</p>
	<p>N. 88°55' W., bet secs. 5 and 32.</p> <p>Over mountainous land, through moderate undergrowth.</p>
.60	Wash, 10 lks. wide, 2 ft. deep, drains NW.
9.00	Creek in Shingle Mill Canyon, course N.; asc. E. slope.
20.80	Jeep road, bears irregular N. and S.
40.84	<p>Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E</p> <p>¼ $\frac{S32}{S5}$</p> <p>T8S</p> <p>1967</p> </div>
58.20	Spur, slopes N. 25° E.
69.20	Spur, slopes N.; desc. NW. slope.
81.68	<p>The cor. of secs. 5, 6, 31 and 32, monumented by a rock-in-place, 10 x 4 x 1 ft., mkd. 5 notches on E. and 1 notch on W. faces and an "X" on top.</p> <p>At the corner point</p> <p>Set the iron post over the X on orig. cor., mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E</p> <p>S31 S32</p> <p>S6 S5</p> <p>T8S</p> <p>1967</p> </div> <p>Land, mountainous. Soil, rocky. Timber, scattered juniper and oak. Undergrowth, cacti, cat claw and bunch grass.</p>
	<p>N. 89°47' W., bet. secs. 6 and 31.</p> <p>Over mountainous land, through moderate undergrowth.</p>
14.90	Ravine, drains NW.; continue desc. NW. slope.
39.07	The ¼ sec. cor. of secs. 6 and 31, monumented by a granite stone, 24 x 8 x 6 ins., set 6 ins. in the

Dep. Resurvey, South Boundary, T. 7 S., R. 24 E.

CHAINS	
	<p>ground, mkd. $\frac{1}{4}$ on N. face, from which the orig. bearing trees:</p> <p>A white oak, 13 ins. diam., bears North, $12\frac{1}{2}$ lks. dist., no legible mks.; rescribe $\frac{1}{4}$ S31 BT. (Record dist. 11 lks.)</p> <p>A black oak, 18 ins. diam., bears S. 28° E., 28 lks. dist., no legible mks.; rescribed $\frac{1}{4}$ S6 BT. (Record bearing S. $25\frac{1}{2}^{\circ}$ E.)</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ <u>S31</u> S6 T8S 1967</p> <p>from which</p> <p>A mine shaft, bears N. $53^{\circ}12'$ W., 27.17 chs. dist.</p> <p>A mine shaft, bears N. $73^{\circ}17'$ W., 22.91 chs. dist.</p> <p>Deposit orig. cor. stone alongside iron post.</p> <hr/> <p>N. $88^{\circ}58'$ W., beginning new measurement.</p> <p>Over mountainous land, through moderate undergrowth; desc. NW. slope.</p> <p>3.60 Wash, 10 lks. wide, 2 ft. deep, drains N. 25° W.</p> <p>17.00 Creek in Lefthand Canyon, course N.; asc. E. slope.</p> <p>21.10 Draw, drains SE., 50 lks., thence NE., cont. asc.</p> <p>37.76 The cor. of Tps. 7 and 8 S., Rs. 23 and 24 E., monumented by an iron post $2\frac{1}{2}$ ins. diam., as described in the field notes of the resurvey of T. 7 S., R. 23 E., under this same group.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered juniper and oak. Undergrowth, manzanita, cacti, cat claw and grass.</p>
	<p>Dependent Resurvey of the Subdivisional Lines T. 7 S., R. 24 E., G&SR M., Arizona</p>
	<p>Reestablishment of the Survey Executed by C. H. Wallace in 1886</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.</p> <p>N. $2^{\circ}00'$ W., bet. secs. 35 and 36.</p> <p>Over mountainous land, through moderate undergrowth; desc. N. slope.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
14.00	Wash, 40 lks. wide, 5 ft. deep, drains NE., continue desc.
39.50	<p>The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented by a rock-in-place, 6 x 3 x 1 ft. above the ground, mkd. $\frac{1}{4}$ with X on top, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post over "X" on orig. cor., mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S35 S36 1967</p> <hr style="width: 20%; margin: auto;"/> <p>N. 1°16' W., beginning new measurement.</p> <p>Continue desc. N. slope.</p>
1.30	Fence, bears S. 55° E. and N. 55° W.
33.50	Wash, 20 lks. wide, 1 ft. deep, drains NE.
39.96	<p>The cor. of secs. 25, 26, 35 and 36, monumented by a granite stone, 36 x 10 x 5 ins., set firmly in a mound of stone, dimly mkd. 1 notch on S. and 1 notch on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S26 S25 S35 S36 1967</p> <p>Deposit orig. cor. stone alongside the iron post.</p> <p>Land, mountainous to high rolling. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.</p>
4.60	<p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land, through moderate undergrowth.</p>
34.90	Wash, 80 lks. wide, 12 ft. deep, drains NE.
40.23	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 10 ins. above the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S25 S36 1960</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS		
45.01	<p>This cor. was set in 1960 under the US Forest Service Remonumentation Program.</p> <hr/> <p>N. 89°46' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.</p>	
16.80	<p>N. 0°25' E., bet. secs. 25 and 26.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains NE.</p>	
19.00	<p>Track road, bears NE. and SW.</p>	
39.82	<p>The ¼ sec. cor. of secs. 25 and 26, monumented by a granite stone, 18 x 12 x 4 ins., loosely set, mkd. ¼ on a face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E</p> <p>¼</p> <p>S26 S25</p> <p>1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 23 lks. East, of a fence bearing N. and S.</p> <hr/>	
28.00	<p>N. 0°10' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Fence, bears E. and W.</p>	
39.40	<p>Fence, bears E. and W.</p>	
39.98	<p>The cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E</p> <p>S23 S24</p> <p>S36 S25</p> <p>1960</p> </div> <p>This cor. was set in 1960, under the US Forest Service Remonumentation Program.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw and grass.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp.
	West, bet. secs. 24 and 25.
	Over gently rolling land, through moderate undergrowth.
20.90	Bladed road to Mud Springs bears NE. and SW.
25.00	Wash, 25 lks. wide, 2 ft. deep, drains N.
42.52	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R24E $\frac{1}{4}$ $\frac{S24}{S25}$ 1967
55.50	Track road at base of mesa, bears NE. and SW.; asc. E. slope.
60.20	Rim of mesa, continue asc.
63.78	Point for the W $\frac{1}{16}$ sec. cor. of secs. 24 and 25, at proportionate dist.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R24E W $\frac{1}{16}$ $\frac{S24}{S25}$ 1967
69.60	Top of mesa, thence across nearly level mesa top.
71.20	Fence, bears N. and S.
72.20	W. rim of mesa; desc. W. slope.
85.04	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, sandy loam, rocky. Timber, scattered mesquite. Undergrowth, creosote, cat claw and grass.
	N. $3^{\circ}57'$ E., bet. secs. 23 and 24.
	Over rolling land, through moderate undergrowth.
.30	Ash Creek, 30 lks. wide, 6 ft. deep, drains N. 70° E.
7.60	Old fence, bears S. 60° E. and N. 60° W.
20.80	Power line, bears NE. and SW. for 5 chs. to its end.
29.90	Track road, bears NE. and SW.
38.70	Canal, bears E. and W.
39.70	Graded road, bears E. and W.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
39.88	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This cor. is not monumented.
40.00	Wash, 20 lks. wide, 2 ft. deep, drains E.
74.70	Old fence, bears SE. and NW.
78.90	Power line, bears E. and W. for 4 chs. thence N. 15° W.
79.76	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T7S R24E $\frac{S14}{S23} \frac{S13}{S24}$ 1967</p>
	from which
	<p>A US Soil Conservation Service Triangulation Station, a brass tablet, $2\frac{1}{2}$ ins. diam., set in a concrete block, bears N. 45° E., 13 lks. dist.</p>
	<p>Arizona Game and Fish Region 7 Offices, the NW. cor. of west building, bears S. $56^{\circ}38'$ E., 19.68 chs. dist.; the NW. cor. of the east building, bears S. $60^{\circ}55'$ E., 21.94 chs. dist.</p>
	<p>A well casing, 6 ins. diam., bears S. $66^{\circ}06'$ W., 75 lks. dist.</p>
	<p>An electric water pump, bears N. $37^{\circ}51'$ W., 12.84 chs. dist.</p>
	<p>The cor. is located 9 lks. west of a fence bearing N. and S.</p>
	<p>Land, rolling. Soil, sandy loam. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp.</p>
	<p>S. $89^{\circ}13'$ W., bet. secs. 13 and 24.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
12.60	Ravine, drains NE.
16.30	Bladed road, bears NE. and SW.
19.40	Ravine, drains NE.
39.75	Fence, bears N. and S.
39.89	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented by a granite stone, 18 x 10 x 8 ins., set firmly in a mound of stone, mkd. $\frac{1}{4}$ on N. face.</p>
	<p>At the corner point</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S13}{S24}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A. U. S. Soil Erosion Service Triangulation Station, a brass tablet, $2\frac{1}{2}$ ins. diam., set in a concrete block, bears N. 9° E., 95 lks. dist.</p> <p style="padding-left: 40px;">A concrete head gate, at the N. end of Cluff Reservoir No. 1, bears S. $75\frac{1}{4}^{\circ}$ W., 16.75 chs. dist.</p> <p style="padding-left: 40px;">A water tower, bears S. $53^{\circ}55'$ W., 29.71 chs. dist.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p style="text-align: center;">—————</p> <p>N. $88^{\circ}50'$ W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
13.40	Bladed road, bears SE. and NW.
16.20	Gravelled road, bears N. and S.
16.50	Irrigation ditch, bears N. and S.
16.60	Fence bears N. and S.; enter cultivated field.
26.20	Fence, bears N. and S., leave cultivated field.
26.80	Track road, bears N. and S., curves to E.
31.10	Drainage ditch, drains NW. (Ash Creek)
39.68	Fence, bears N. and S.
39.69	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, rolling. Soil, sandy loam. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw and grass.</p>
	<p>N. $0^{\circ}05'$ W., bet. secs. 13 and 14.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
3.90	Track road, bears irregularly E. and W.
11.00	Enter dense willow; thence by triangulation.
17.00	S. edge of Evans Pond.
25.00	N. edge of Evans Pond.
39.79	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. End of triangulation.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS		
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">T7S R24E</p>	
	<p style="text-align: center;">$\frac{1}{4}$</p>	
	<p style="text-align: center;">S14 S13</p>	
	<p style="text-align: center;">1967</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A U.S. Soil Conservation brass tablet, 2½ ins. diam., bears NE., 8½ lks. dist.</p>	
	<p style="padding-left: 40px;">A fence cor. bears NE., 7½ lks. dist., fences bear E. and S.</p>	
54.00	<p>Wash, 200 lks. wide, 2 ft. deep, drains NE.; leave willows; asc. S. slope.</p>	
59.68	<p>Point for the N 1/16 sec. cor. of secs. 13 and 14, at proportionate dist.</p>	
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">T7S R24E</p>	
	<p style="text-align: center;">N 1/16</p>	
	<p style="text-align: center;">S14 S13</p>	
	<p style="text-align: center;">1967</p>	
65.10	<p>Top of mesa, bears E. and W.</p>	
74.60	<p>Desc. along spur sloping N.</p>	
79.58	<p>The cor. of secs. 11, 12, 13 and 14, monumented by a granite stone, 12 x 6 x 4 ins., firmly set in a mound of stone, mkd. 4 notches on S. and 1 notch on E. faces.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T7S R24E</p>	
	<p style="text-align: center;"><u>S11 S12</u></p>	
	<p style="text-align: center;">S14 S13</p>	
	<p style="text-align: center;">1967</p>	
	<p>Bury the orig. cor. stone alongside the iron post.</p>	
	<p>Raise a mound of stone W. of the cor.</p>	
	<p>Land, gently rolling.</p>	
	<p>Soil, sandy loam.</p>	
	<p>Timber, scattered mesquite.</p>	
	<p>Undergrowth, creosote, cacti, cat claw and grass.</p>	
	<p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.</p>	
	<p>S. 89°33' W., bet. secs. 12 and 13.</p>	
	<p>Over cultivated field, along the S. side of fence bearing E. and W.</p>	
10.30	<p>Leave field, enter dense undergrowth.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
12.80	Ash Creek, 30 lks. wide, 2 ft. deep, drains NE.
14.10	Track road, bears N. and S.
39.88	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
40.15	Track road, bears SW. and NE. curving E.
44.20	Leave dense undergrowth; asc. NE. slope.
50.30	Spur slopes N.
59.82	Point for the W $\frac{1}{16}$ sec. cor. of secs. 12 and 13, at proportionate dist.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T7S R24E W $\frac{1}{16}$ $\frac{S12}{S13}$ 1967</p>
61.10	Fence, bears N. and S.
70.90	Top of mesa; thence across nearly level mesa.
78.90	Begin desc. W. slope.
79.76	The cor. of secs. 11, 12, 13 and 14.
	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>
	North, bet. secs. 11 and 12.
	Desc. NW. slope through moderate undergrowth.
14.10	Enter nearly level land, bears NE. and SW.
22.00	Wash, 20 lks. wide, 2 ft. deep, drains NE.
38.10	Wash, 20 lks. wide, 1 ft. deep, drains NE.
39.92	The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by a weathered post, set in a mound of stone, remains of rotted post beneath surface, this is accepted as best remaining evidence of the orig. cor.
	At the corner point
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	<p>T7S R24E $\frac{1}{4}$ S11 S12 1967</p>
	Deposit the orig. cor. post alongside the iron post.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	<p>N. 0°04' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>39.94 The cor. of secs. 1, 2, 11 and 12, monumented by remains of a weathered post, set in a small mound of stone, dimly mkd.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T7S</td><td>R24E</td></tr> <tr><td>S2</td><td>S1</td></tr> <tr><td>S11</td><td>S12</td></tr> </table> <p>1967</p> </div> <p>Deposit the orig. cor. post alongside the iron post.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, cacti, creosote, cat claw and grass.</p>	T7S	R24E	S2	S1	S11	S12
T7S	R24E						
S2	S1						
S11	S12						
	<p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp.</p> <p>S. 89°38' W., bet. secs. 1 and 12.</p> <p>Over nearly level land.</p> <p>.23 Fence, bears N. and S., thence along fence bearing W.; enter dense undergrowth.</p> <p>13.50 Fence cor., fences bear N. and E.; enter cultivated field.</p> <p>21.20 Leave cultivated field; thence over gently rolling land.</p> <p>38.70 Enter stock tank.</p> <p>39.10 Leave stock tank.</p> <p>39.60 Fence, bears N. and S.</p> <p>39.86 Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This cor. is not monumented.</p> <p>47.50 Wash, 80 lks. wide, 3 ft. deep, drains NE.</p> <p>79.72 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw and grass.</p>						
	<p>N.0°03' W., bet. secs. 1 and 2.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>11.00 Wash in Mud Hollow, 20 lks. wide, 2 ft. deep, drains NE.</p> <p>20.01 Point for the S 1/16 sec. cor. of secs. 1 and 2, at proportionate dist.</p>						

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S 1/16 S2 S1 1967</p>
40.02	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S2 S1 1967</p>
60.03	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E N 1/16 S2 S1 1967</p>
67.00	<p>Begin asc. S. slope.</p>
80.24	<p>The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 10 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T6S R24E <u>S35 S36</u> S 2 S1 T7S R24E 1916</p> <p>Land, gently rolling. Soil, sandy clay loam. Timber, none. Undergrowth, cacti, cat claw and grass.</p>
25.00	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp.</p> <p>N. $1^{\circ}32'$ E., bet. secs. 34 and 35.</p> <p>Desc. N. slope; through moderate undergrowth.</p> <p>Jeep road, bears irregularly N. and S.; cross at most westerly switchback.</p>
30.00	<p>Ravine, drains NE.; base of mountain, continue desc. rolling N. slope.</p>
38.00	<p>Ravine, drains NE.</p>
39.26	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS		
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S34 S35 1967</p>	
47.40	Jeep road, bears SE. and NW.	
71.90	Fence, bears N. 89°12' E. and S. 89°12' W.	
76.30	Wash, 30 lks. wide, 2 ft. deep, drains NW.	
78.52	<p>The cor. of secs. 26, 27, 34 and 35, monumented by an iron post, 2½ ins. diam., projecting 10 ins. above the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S27 S26 S34 S35 1960</p> <p>This cor. was set in 1960, under the US Forest Service Remonumentation Program.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, mountainous to rolling. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.</p>	
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°49' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through moderate undergrowth.</p>	
.25	Water pipe, 6 ins. diam.; bears N. and S.	
1.60	Track road, bears N. and S.	
2.30	Fence, bears NE. and SW.	
3.80	Ash creek, 10 lks. wide, 2 ft. deep, drains N.	
19.30	Ridge, bears NE. and SW.	
32.30	Wash, 10 lks. wide, 6 ft. deep, drains NE.	
36.78	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor. or the iron post set in 1960.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S26 S35 1967</p>	
42.40	<p>Cor. falls on N. slope of low spur sloping E.</p> <p>Spur, slopes S.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
73.56	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, rocky, sandy loam. No timber; undergrowth, cacti, cat claw and grass.</p>
40.08	<p>N. 0°27' W. bet. secs. 26 and 27.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>The ¼ sec. cor. of secs. 26 and 27, monumented by a granite stone-in-place, 4 x 3 x 2 ft. showing above the ground, mkd. ¼ X on W. face.</p> <p>At the corner point</p> <p>Set the iron post 30 ins. in the ground underneath the "X" on orig. cor. rock, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ½ S27 S26 1967</p> <p>Raise a mound of stone W. of the corner.</p>
12.60	<p>N. 0°17' W., beginning new measurement.</p>
24.20	<p>Spur, slopes NE.</p>
24.20	<p>South edge of White Streaks Canyon, bears NE. and SW.</p>
28.20	<p>Wash, in bottom of White Streaks Canyon, 25 lks. wide, 4 ft. deep, drains NE.</p>
34.30	<p>North edge of White Streaks Canyon, bears NE. and SW.</p>
39.81	<p>The cor. of secs. 22, 23, 26 and 27, monumented by a granite stone, 12 x 8 x 6 ins., set 6 ins. in the ground, mkd. 2 notches on the E. and S. faces, mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S22 S23 S27 S26 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of cor.</p> <p>Land, rolling. Soil, rocky and sandy loam. No timber; undergrowth, cacti, cat claw, creosote and grass.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°54' W., bet. secs. 23 and 26.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	Over rolling land, through dense undergrowth.
.40	Ash creek, drains N. 70° E.
1.30	Fence bears irregularly SE. and NW.
16.10	Wash, 30 lks. wide, 2 ft. deep, drains N.
18.52	Point for the E 1/16 sec. cor. of secs. 23 and 26, at proportionate dist.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T7S R24E E 1/16 <u>S23</u> S26 1967
	Raise a mound of stone N. of the cor.
19.10	Fence, bears SE. and NW. for 50 lks. to cor. of fences bearing NW., SE. and E.
24.50	Track road, bears SW. and NE. for 1 ch., thence NW.; leave dense undergrowth.
25.40	Wash, 30 lks. wide, 2 ft. deep, drains NW.
31.30	Waterpipe, 6 ins. diam., bears N. 15° W. and S. 15° E.
36.50	Spur, slopes N. for 1 ch.
37.04	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
	T7S R24E 1/4 <u>S23</u> S26 1967
	Raise a mound of stone N. of the cor.
	Cor. is located on a steep W. slope.
38.80	Wash, 80 lks. wide, 1 ft. deep, drains N. approximately 6 chs. to Cluff Reservoir No. 3.
47.20	Wash, 15 lks. wide, 1 ft. deep, drains N.
49.20	Spur, slopes N.
51.80	Wash, 20 lks. wide, 2 ft. deep, drains N. 25° E.
55.56	Point for the W 1/16 sec. cor. of secs. 23 and 26, at proportionate dist.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T7S R24E W 1/16 <u>S23</u> S26 1967

CHAINS	
59.70	Spur, slopes N. 25° E.
66.90	Wash in bottom of White Streaks Canyon, 100 lks. wide, 2 ft. deep, drains NE.
74.08	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling. Soil, sandy loam. Timber, scattered mesquite. Undergrowth, cacti, creosote, cat claw and grass.
	N. 0°04' W., bet. secs. 22 and 23.
	Over gently rolling land, through moderate undergrowth.
4.60	Drainage ditch, drains NE.
5.20	Track road, bears NE. and SW.
31.50	Ravine, drains NE.
39.96	The 1/4 sec. cor. of secs. 22 and 23, monumented by a granite stone, 16 x 8 x 5 ins., set 8 ins. in the ground, mkd. 1/4 on W. face, mound of stone alongside.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	$\begin{array}{c} \text{T7S R24E} \\ \frac{1}{4} \\ \text{S22 S23} \\ \text{1967} \end{array}$
	Deposit the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	<hr/> N. 0°13' E., beginning new measurement.
	Over gently rolling land, through moderate undergrowth.
11.50	Fence, bears S. 33°52' E. and N. 33°52' W.
21.50	Track road, bears NE. and SW.
39.97	The cor. of secs. 14, 15, 22 and 23, monumented by a granite stone, 26 x 16 x 12 ins., set 12 ins. in the ground, mkd. 3 notches on S. and 2 notches on E. faces, mound of stone alongside.
	At the corner point
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	$\begin{array}{c} \text{T7S R24E} \\ \text{S15 S14} \\ \text{S22 S23} \\ \text{1967} \end{array}$
	from which
	A U. S. Dept. of Agriculture Triangulation Station,

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>monumented by a brass tablet, 3½ ins. diam., bears N. 72°27' W., 11.91 chs. dist., mkd. U. S. Dept. of Agriculture TRAM TOWER 1934.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote, cacti and grass.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°48' W., bet. secs. 14 and 23.</p> <p>Over rolling land, through moderate undergrowth.</p>
4.10	Power line, bears N. 15° W., and S. 15° E.
5.60	Wash, 15 lks. wide, 3 ft. deep, drains NW.
10.40	Fence, bears irregularly N. and S.
25.90	Spur, slopes N.
35.10	Wash, 15 lks. wide, 1 ft. deep, drains NE.
38.70	Wash, 20 lks. wide, 1 ft. deep, drains NE.
39.76	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor. This cor. is not monumented.
42.60	Wash, 50 lks. wide, 1 ft. deep, drains NE.
45.20	Wash, 80 lks. wide, 1 ft. deep, drains N. (White Streaks Canyon)
47.60	Track road, bears SE. and NW.
57.70	Wash, 30 lks. wide, 1 ft. deep, drains NE.
59.64	Point for the W 1/16 sec. cor. of secs. 14 and 23, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T7S R24E W 1/16 $\frac{S14}{S23}$ 1967</p>
	Raise a mound of stone N. of the cor.
64.90	Ravine, drains NE.
71.00	Track road, bears NE. and SW.
79.52	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, rolling. Soil, sandy loam, rocky. Timber, scattered mesquite. Undergrowth, cacti, creosote, cat claw and grass.</p>
	<p>N. 0°10' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land, through moderate undergrowth.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
9.40	Wash in Mud Hollow, 20 lks. wide, 3 ft. deep, drains NE.
20.00	Point for the S 1/16 sec. cor. of secs. 14 and 15 at proportionate dist. Set the iron post 24 ins. in the ground, brass cap mkd. T7S R24E S 1/16 S15 S14 1967
29.50	Bladed road, bears N. 25° E. and S. 25° W.
40.00	The 1/4 sec. cor. of secs. 14 and 15, monumented by a granite stone, 16 x 14 x 8 ins., set 8 ins. in the ground, mkd. 1/4 on W. face, mound of stone W. At the corner point Set the iron post 22 ins. in the ground, brass cap mkd. T7S R24E 1/4 S15 S14 1967
40.11	Deposit the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the cor. N. 0°12' W., beginning new measurement. Over gently rolling land, through moderate undergrowth. The cor. of secs. 10, 11, 14 and 15, monumented by a granite stone, 14 x 10 x 6 ins., firmly set in a mound of stone, mkd. 4 notches on S. and 2 notches on E. faces. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd. T7S R24E S10 S11 S15 S14 1967
	Deposit the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the cor. Land, gently rolling. Soil, sandy and rocky loam. No timber; undergrowth, creosote, cacti and grass. From the cor. of secs. 11, 12, 13 and 14. N. 89°23' W., bet. secs. 11 and 14. Over gently rolling land, through moderate undergrowth.

Dependent Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS		
3.00	Ravine, drains N.	
11.00	Ravine, drains N.	
21.30	Ravine, drains N.	
26.90	Ravine, drains NE.	
39.78	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S11}{S14}$ 1967</p>	
	Raise a mound of stone N. of the cor.	
47.20	Wash in Mud Hollow, 30 lks. wide, 1 ft. deep, drains N.	
63.00	Bladed road, bears N. 20° E. and S. 20° W.	
72.40	Wash, 20 lks. wide, 1 ft. deep, drains NW.	
79.56	The cor. of secs. 10, 11, 14 and 15.	
	Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti and grass.	
	N. 0°06' W., bet. secs. 10 and 11.	
	Over gently rolling land, through moderate undergrowth.	
19.50	Enter ravine, draining irregularly N.	
19.84	Point for the S $\frac{1}{16}$ sec. cor. of secs. 10 and 11, at proportionate dist.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T7S R24E S $\frac{1}{16}$ S10 S11 1967</p>	
	Raise a mound of stone W. of the cor.	
39.68	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.	
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.	
	<p style="text-align: center;">T7S R24E $\frac{1}{4}$ S10 S11 1967</p>	
59.52	Point for the N $\frac{1}{16}$ sec. cor. of secs. 10 and 11, at proportionate dist.	
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p style="text-align: center;">T7S R24E N 1/16 S10 S11 1967</p> <p>79.36 The cor. of secs. 2, 3, 10 and 11, monumented by a mound of stone and a wooden stake 2 x 4 x 12 ins. long; this is accepted as best remaining evidence of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S3 S2 S10 S11 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti and grass.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°19' W., bet secs. 2 and 11.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>8.00 Wash in Mud Hollow, 30 lks. wide, 1 ft. deep, drains NE.</p> <p>18.10 Base of mesa, asc. E. slope.</p> <p>19.85 Point for the E 1/16 sec. cor. of secs. 2 and 11, at proportionate dist.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E E 1/16 S2 S11 1967</p> <p>21.20 Top of mesa; thence across nearly level land.</p> <p>30.10 Bladed road, bears NE. and SW.</p> <p>38.70 W. edge of mesa; desc. W. slope.</p> <p>39.70 The 1/4 sec. cor. of secs. 2 and 11, monumented by a granite stone, 18 x 10 x 10 ins., set 10 ins. in the ground, mkd. 1/4 on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E 1/4 S2 S11 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	<p>S. 89°51' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>31.50 Wash, 50 lks. wide, 3 ft. deep, drains NE.</p> <p>40.00 The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti, cat claw and grass.</p>	
	<p>N. 0°08' E., bet. secs. 2 and 3.</p> <p>Continue in ravine draining irregularly N. through moderate undergrowth.</p> <p>14.20 Track road, in bottom of ravine, bears NE. and SW. at this point.</p> <p>29.00 Same road, bears irregularly N. and S. 20° E.</p> <p>40.00 The 1/4 sec. cor. of secs. 2 and 3, monumented by a mound of stone with a post 1 x 2 x 12 ins. long, this is accepted as best remaining evidence of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E 1/4 S3 S2 1967</p> <p>Deposit the wood post alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Cor. is located on the E. edge of a track road, bearing N. and S.</p>	
	<p style="text-align: center;">—————</p> <p>N. 0°13' E., beginning new measurement.</p> <p>Continue in ravine draining irregularly N. through moderate undergrowth.</p> <p>11.00 Leave ravine, drains NW.; thence over gently rolling land.</p> <p>19.84 Point for the N 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E N 1/16 S3 S2 1967</p> <p>Raise a mound of stone W. of the corner.</p> <p>Cor. is located on E. side of track road curving from S. to NW.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
22.70	Track road, bears NE. and SW.
29.10	Powerline, bears N. 57° E. and S. 57° W.
35.10	Cottonwood Wash Road to Pima, bears NE. and SW.; enter yard.
40.17	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of Tp., monumented by an iron post 3 ins. diam., set 26 ins. below surface, brass cap mkd.
	<p style="text-align: center;">T6S R24E <u>S34 S35</u> S3 S2 T7S R24E 1916</p>
	<p>from which</p> <p style="padding-left: 40px;">A nail in a post 7 ins. diam. on a N. and S. fence, bears N. 72°27' E., 167 lks. dist.</p> <p style="padding-left: 40px;">A nail in a post 6 ins. diam., bears S. 18°40' W. 40½ lks. dist.</p> <p style="padding-left: 40px;">An "X" chiseled on the NE. cor. of a cement tank, 9 x 9 ft., bears S. 47°38' W., 277 lks. dist.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti and grass.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp.</p>
	<p>N. 0°13' E., bet. secs. 33 and 34.</p>
	<p>Over mountainous land, through moderate undergrowth.</p>
9.30	Spur, slopes NE.; desc. NW. slope.
38.63	The ¼ sec. cor. of secs. 33 and 34, monumented by a granite stone, 22 x10 x 6 ins., set 12 ins. in the ground, mkd. ¼ on W. face, mound of stone W.
	<p>At the corner point</p>
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R24E ¼ S33 S34 1967</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°17' W., beginning new measurement.</p>
	<p>Over mountainous land, through moderate undergrowth.</p>
20.80	Ravine, drains NE.
32.10	Fence, bears E. and W.
40.07	The cor. of secs. 27, 28, 33 and 34, monumented by a

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>granite stone, 18 x 12 x 6 ins., firmly set in a mound of stone, mkd. 1 notch on S. and 3 notches on E. faces.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E <u>S28</u> <u>S27</u> <u>S33</u> <u>S34</u> 1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. No timber; undergrowth, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°52' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through moderate undergrowth.</p>
3.30	Wash, 200 lks. wide, 2 ft. deep, drains irregularly NW.
10.00	Track road, bears N. and S.
26.60	Wash, 30 lks. wide, 2 ft. deep, drains N. 25° W.
35.80	Wash, 300 lks. wide, 2 ft. deep, drains N.
39.77	<p>The ¼ sec. cor. of secs. 27 and 34, monumented by a granite stone, 17 x 7 x 6 ins., loosely set, mkd. ¼ on a face.</p> <p>At the corner point</p> <p>Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R24E ¼ <u>S27</u> S34 1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°20' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
3.60	North end of spur, sloping N.
7.00	Wash, 50 lks. wide, 3 ft. deep, drains NE.
29.00	Ravine, drains NE.
40.08	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, gently rolling. Soil, sandy loam, rocky. Timber, scattered mesquite. Undergrowth, cacti, cat claw and grass.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>N. 0°02' E., bet. secs. 27 and 28.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
2.50	<p>Wash, 40 lks. wide, 5 ft. deep, drains NE.</p>
26.20	<p>Wash, 20 lks. wide, 2 ft. deep, drains E.; asc. S. slope of mesa. (Shingle Mill Canyon)</p>
28.90	<p>Top of mesa, thence over nearly level land.</p>
39.83	<p>The 1/2 sec. cor. of secs. 27 and 28, monumented by a granite stone, 18 x 16 x 10 ins., set 6 ins. in the ground, mkd. 1/2 on W. face, mound of stone W.</p>
	<p>At the corner point</p>
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R24E 1/2 S28 S27 1967</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p>N. 0°30' W., beginning new measurement.</p>
	<p>Over nearly level land.</p>
8.00	<p>Dim track road, bears E. and W.</p>
24.60	<p>Track road, bears NE. and SW.</p>
32.60	<p>N. rim of mesa; desc. N. slope.</p>
34.70	<p>Base of mesa; ravine, drains NE.; thence across rolling land.</p>
40.35	<p>The cor. of secs. 21, 22, 27 and 28, monumented by a granite stone, 16 x 12 x 10 ins., set 8 ins. in the ground, mkd. 2 notches on S. and 3 notches on E. faces, mound of stone W.</p>
	<p>At the corner point</p>
	<p>Set the iron post 10 ins. in the ground, in a mound of stone, to the top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R24E S21 S22 S28 S27 1967</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p>Land, rolling to nearly level.</p>
	<p>Soil, rocky.</p>
	<p>No timber, undergrowth, cacti, scrub mesquite and grass.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>
	<p>N. 89°24' W., bet. secs. 22 and 27.</p>
	<p>Over rolling land, through moderate undergrowth.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS		
3.80	Track road, bears NE. and SW.	
10.30	Wash, 25 lks. wide, 3 ft. deep, drains NE.	
16.40	Track road, bears N. 25° E. and S. 25° W.; enter dense mesquite.	
37.90	Enter wash area, drains NE. from W. (Shingle Mill Canyon)	
39.84	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.	
	<p>T7S R24E $\frac{1}{4}$ $\frac{S22}{S27}$ 1967</p>	
42.00	Leave wash area, drains E. from SW.; leave dense mesquite.	
51.20	Asc. E. slope of mesa.	
59.30	Top of mesa; desc. along NW. slope.	
64.50	Jeep road, bears NE. and SW.	
79.68	The cor. of secs. 21, 22, 27 and 28. from which Tramline stock tank, bears N. 57°45' E., 16.95 chs. dist. Land, rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, cat claw, cacti and grass.	
	N. 1°08' W., bet. secs. 21 and 22.	
	Over gently rolling land, through moderate undergrowth.	
6.00	Wash, 20 lks. wide, 2 ft. deep, drains E.	
37.00	Wash, 20 lks. wide, 2 ft. deep, drains NE.	
39.40	The ¼ sec. cor. of secs. 21 and 22, monumented by a granite stone 24 x 14 x 8 ins., set 8 ins in the ground, mkd. ¼ on W. face, mound of stone W. At the corner point Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.	
	<p>T7S R24E $\frac{1}{4}$ $\frac{S21}{S22}$ 1967</p>	
	Deposit the orig. cor. stone alongside the iron post.	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>N. 0°38' E., beginning new measurement.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
4.90	<p>Enter wash, 15 lks. wide, 2 ft. deep, drains N.</p>
12.10	<p>Leave wash, drains NW.</p>
21.10	<p>Same wash, drains NE.</p>
40.02	<p>The cor. of secs. 15, 16, 21 and 22, monumented by a granite stone, 22 x 12 x 8 ins., set 6 ins. in the ground, mkd. 3 notches on S. and E. faces, mound of stone alongside.</p>
	<p>At the corner point</p>
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R24E</p>
	<p style="text-align: center;"><u>S16</u> <u>S15</u></p>
	<p style="text-align: center;">S21 S22</p>
	<p style="text-align: center;">1967</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, gravelly loam.</p>
	<p>No timber; undergrowth, creosote, cat claw, cacti and grass.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>N. 89°39' W., bet. secs. 15 and 22.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
2.80	<p>Wash, 5 lks. wide, 1 ft. deep, drains NE. (Mud Hollow)</p>
9.40	<p>Bladed road, bears N. 25° E., and S. 25° W.</p>
20.12	<p>Point for the E 1/16 sec. cor. of secs. 15 and 22, at proportionate dist.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R24E</p>
	<p style="text-align: center;">E 1/16 <u>S15</u></p>
	<p style="text-align: center;">S22</p>
	<p style="text-align: center;">1967</p>
	<p>Raise a mound of stone N. of the cor.</p>
27.30	<p>Wash, 100 lks. wide, 2 ft. deep, drain NW.</p>
34.10	<p>Wash, 30 lks. wide, 1 ft. deep, drains NW.</p>
36.20	<p>Trail road, bears SE. and NW.</p>
40.24	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented by a granite stone 22 x 12 x 8 ins., set 6 ins. in the ground, mkd. 1/4 on N. face, mound of stone N.</p>
	<p>At the corner point</p>
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS		
	<p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S15}{S22}$ 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°51' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth. Wash, 15 lks. wide, 2 ft. deep, drains NE. The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cat claw and cacti.</p>	
<p>34.30 39.83</p>	<p>N. 0°28' W., bet. secs. 15 and 16.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>33.40 Enter ravine, draining irregularly N.; a track road follows the wash in bottom of ravine.</p> <p>39.82 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S16 S15 1967</p>	
<p>79.00 79.64</p>	<p>Leave ravine, draining irregularly NW.</p> <p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S 9 S10 S16 S15 1967</p>	
	<p>from which</p> <p style="padding-left: 40px;">Artesian Well, bears N. 9°25' E., 2.84 chs. dist.</p> <p>Raise a mound of stone W. of cor.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, creosote, cat claw, cacti and grass.</p>	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 88°56' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
1.00	Wash, 30 lks. wide, 2 ft. deep, drains N.
9.00	Wash, 120 lks. wide, 1 ft. deep, drains N.
25.30	Wash, 30 lks. wide, 1 ft. deep, drains NE.
40.23	The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented by a wood stake 18 ins. long, firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face.
	At the corner point
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S10}{S15}$ 1967</p>
	Reset the wood stake, inverted, alongside the iron post.
	<hr style="width: 20%; margin: auto;"/>
	N. 89°10' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
9.30	Track road, bears N. and S.
9.40	Fence, bears N. and S.
14.00	Wash, 15 lks. wide, 1 ft. deep, drains NW.
20.09	Point for the W 1/16 sec. cor. of secs. 10 and 15, at proportionate dist.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R24E W 1/16 $\frac{S10}{S15}$ 1967</p>
27.90	Wash, 40 lks. wide, 1 ft. deep, drains N.
40.18	The cor. of secs. 9, 10, 15 and 16.
	Land, gently rolling. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw and grass.
	N. 0°12' E., bet. secs. 9 and 10.
	Over gently rolling land, through moderate undergrowth.
.50	South fence of corral, bears E. and W.
3.50	North fence of corral, bears SE. and NW.
3.80	Enter ravine, draining irregularly N.
11.80	Leave ravine, draining irregularly N.

Dep. Resurvey, Subdivision, T. 7 S., R. 24E.

CHAINS		
31.10	Enter ravine, draining irregularly N.	
39.82	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	<p>T7S R24E $\frac{1}{4}$ S9 S10 1967</p>	
54.30	Fence, bears E. and W.	
59.73	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 9 and 10, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p>T7S R24E N $\frac{1}{16}$ S9 S10 1967</p>	
	Raise a mound of stone W. of the cor.	
70.70	Leave ravine, drains NE.; asc. S. slope.	
72.10	Top of ascent; thence over nearly level land.	
79.64	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a granite stone, 16 x 10 x 8 ins., set 6 ins. in the ground, mkd. 5 notches on S. and 3 notches on E. faces, mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E <u>S4 S3</u> S9 S10 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cat claw and cacti.</p>	
	From the cor. of secs. 2, 3, 10 and 11.	
	West, bet. secs. 3 and 10.	
	Over gently rolling land, through moderate undergrowth.	
12.40	Track road, curves S. 30° W. and N. 10° W.	
20.90	E. rim of valley bears N. and S.; desc. W. slope.	
30.00	Wash, 30 lks. wide, 1 ft. deep, drains NE.; desc. E. slope.	
34.30	W. rim of valley, bears N. and S.; thence over nearly level.	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
35.50	Track road, bears SE. and NW.
40.04	The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented by a wood stake, 24 ins. long, set in a mound of stone, no legible mks., this is accepted as best remaining evidence of the orig. cor.
	At the corner point
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T7S R24E $\frac{1}{4}$ $\frac{S3}{S10}$ 1967
	Bury the orig. cor. stake alongside the iron post.
	Raise a mound of stone N. of the cor.
	S. 89°45' W., beginning new measurement.
	Over gently rolling land, through moderate undergrowth.
7.70	Wash, 20 lks. wide, 1 ft. deep, drains NE.
11.60	Cleared landing strip, bears N. and S.
22.80	Merrill Wash, 100 lks. wide, 1 ft. deep, drains NE.
28.50	Bladed road, bears N. and S.
40.04	The cor. of secs. 3, 4, 9 and 10.
	Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cat claw and cacti.
	N. 0°24' E., bet. secs. 3 and 4.
	Over gently rolling land, through moderate undergrowth.
12.70	N. rim of mesa; desc. N. slope.
17.50	Cottonwood Wash Road, bears E. and W.
20.10	Track road, bears E. and W.
29.20	Fence, bears E. and W.
29.40	Track road, bears E. and W.
29.70	Power line, bears E. and W.
36.10	Wash, 40 lks. wide, 2 ft. deep, drains E.
36.80	Fence, bears S. 25° E. and N. 25° W.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>T7S R24E $\frac{1}{4}$ S4 S3 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">Old ruins of adobe house, bears N. 1°26' E., 4.00 chs. dist.</p> <p>Raise a mound of stone W. of the cor.</p>
41.00	Cottonwood wash, 120 lks. wide, 4 ft. deep, drains E., asc. S. slope.
48.20	Jeep road, curves NE. and NW,
48.80	Top of ascent; thence over nearly level land.
50.60	Same road, bears SE. and NW.
74.10	Wash, 20 lks. wide, 1 ft. deep, drains E.
80.19	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.
	<p>T6S R24E $\frac{1}{4}$ S33 S34 S4 S3 T7S 1916</p>
	<p>Cor. is located at a fence cor., fences bearing E. and NW.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, cottonwood along cottonwood wash. Undergrowth, creosote, cat claw and cacti.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp.</p> <p>N. 0°37' W., bet. secs. 32 and 33.</p> <p>Over mountainous land, through moderate undergrowth; desc. N. slope.</p>
34.50	Bottom of Shingle Mill Canyon, drains NE.
38.00	Jeep road, bears NE. and SW.
39.02	The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented by a granite stone, 18 x 12 x 10 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on W. face.
	<p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p>T7S R24E $\frac{1}{4}$ S32 S33 1967</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS									
	<p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 0°10' W., beginning new measurement.</p> <p>Over mountainous land, through moderate undergrowth.</p>								
4.00	Ravine, drains NE.								
16.60	Base of mesa; asc. S. slope.								
25.20	Top of mesa; thence across top of mesa.								
31.60	Fence, bears S. 89°55' E. and N. 89°55' W.								
39.94	<p>The cor. of secs. 28, 29, 32 and 33, monumented by an iron post, 2½ ins. diam., projecting 12 ins. above the ground, in a mound of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td colspan="2">T7S R24E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S29</td> <td style="padding: 0 5px;">S28</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> </tr> <tr> <td colspan="2">1960</td> </tr> </table> </div> <p>This cor. was set in 1960 under the US Forest Service Remonumentation Program.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered cottonwood in Shingle Mill Canyon. Undergrowth, cacti, cat claw, brush and grass.</p>	T7S R24E		S29	S28	S32	S33	1960	
T7S R24E									
S29	S28								
S32	S33								
1960									
	<hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°45' W., bet. secs. 28 and 33.</p> <p>Over mountainous land, through moderate undergrowth.</p>								
6.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 65° E.								
12.80	Spur, slopes NE.								
16.30	E. side of Shingle Mill Canyon, bears NE. and SW.								
19.20	Wash, 50 lks. wide, 2 ft. deep, drains NE.								
25.30	W. side of Shingle Mill Canyon, bears NE. and SW.								
35.60	Jeep road, bears N. 25° E. and S. 25° W.								
40.06	<p>The ¼ sec. cor. of secs. 28 and 33, monumented by a rock-in-place, 24 x 18 x 10 ins., with 6 ins. showing above the ground, mkd. ¼ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td colspan="2">T7S R24E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S28</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S33</td> </tr> <tr> <td colspan="2">1967</td> </tr> </table> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 0 auto;"/>	T7S R24E		¼	S28		S33	1967	
T7S R24E									
¼	S28								
	S33								
1967									

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	<p>N. 89°35' W., beginning new measurement.</p> <p>Over mountainous land, through moderate undergrowth.</p> <p>14.50 Wash, 20 lks. wide, 2 ft. deep, drains NE.</p> <p>39.95 The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, mountainous. Soil, rocky loam. Timber, scattered mesquite. Undergrowth, cacti, cat claw, brush and grass.</p>
17.90	<p>N. 0°44' W., bet. secs. 28 and 29.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Desc. N. rim of mesa.</p>
39.88	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E 1/4 S29 S28 1967</p> <p>Cor. is located on steep NW. slope, 40 lks. E. of wash, draining N.</p>
47.70	<p>Ravine, drains NE.; asc. S. slope of Coyote Knoll.</p>
67.90	<p>Top of ascent on W. slope of Coyote Knoll; desc. NW. slope.</p>
79.76	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S20 S21 S29 S28 1967</p> <p>Cor. falls on a W. slope.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, creosote, cacti, brush and grass.</p>
8.00	<p>From the cor. of secs. 21, 22, 27 and 28.</p>
40.31	<p>S. 89°59' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains NE.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ <u>S21</u> S28 1967</p> <p>65.70 Wash, 20 lks. wide, 2 ft. deep, drains NW.</p> <p>69.40 Wash, 10 lks. wide, 5 ft. deep, drains NW.</p> <p>80.63 The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, rocky. No timber; undergrowth, creosote, cat claw, cacti, brush and grass.</p> <hr/> <p>N. 0°13' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>6.00 Ravine, drains NW.</p> <p>29.70 Track road, bears E. curving S. to Coyote Stock Tank and W. curving N.</p> <p>33.00 Same road, bears NE. and SW.</p> <p>39.88 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ S20 S21 1967</p> <p>from which</p> <p style="padding-left: 40px;">Coyote stock tank, bears S. 4°57' E., 19.83 chs. dist.</p> <p>79.76 The cor. of secs. 16, 17, 20 and 21, monumented by a granite stone, 14 x 9 x 6 ins., set 6 ins. in the ground, mkd. 3 notches on S. and 4 notches on E. faces, mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E <u>S17 S16</u> S20 S21 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly loam.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw, brush and grass.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22. N. 89°45' W., bet. secs. 16 and 21. Over rolling land, through moderate undergrowth.</p>
1.50	Ravine, drains NW.
38.50	Top of ridge; desc. W. slope.
40.26	<p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ <u>S16</u> S21 1967</p>
42.50	Wash, 30 lks. wide, 1 ft. deep, drains NE.
72.50	Track road, bears irregularly N. and S.
79.60	Wash, 30 lks. wide, 1 ft. deep, drains N.
80.52	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti, cat claw and grass.</p>
40.02	<p>N. 0°04' W., bet. secs. 16 and 17. Over rolling land, through moderate undergrowth.</p> <p>The ¼ sec. cor. of secs. 16 and 17, monumented by a granite stone, 18 x 10 x 6 ins., set 10 ins. in the ground, mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ <u>S17</u> <u>S16</u> 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' W., beginning new measurement. Over rolling land, through moderate undergrowth.</p>
5.10	Enter wash, draining N. from SW.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
17.30	Leave wash, draining NE.
33.50	Wash, 30 lks. wide, 1 ft. deep, drains NE.
40.06	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T7S R24E} \\ \text{S8 S9} \\ \hline \text{S17 S16} \\ 1967 \end{array}$
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti, cat claw, brush and grass.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°05' W., bet. secs. 9 and 16.
	Over gently rolling land, through moderate undergrowth.
2.90	Wash, 80 lks. wide, 2 ft. deep, drains N.
17.40	Wash, 5 lks. wide, 2 ft. deep, drains NE.
37.30	Wash, 20 lks. wide, 1 ft. deep, drains NE.
40.25	The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented by a granite stone, 12 x 6 x 4 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.
	At the corner point
	Set the iron post 20 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T7S R24E} \\ \frac{1}{4} \text{ S9} \\ \hline \text{S16} \\ 1967 \end{array}$
	Deposit the orig. cor. stone alongside the iron post.
	Raise a mound of stone N. of the cor.
	N. 89°49' W., beginning new measurement.
	Over gently rolling land, through moderate undergrowth.
12.40	Track road, bears N. and S.
16.40	Wash, 30 lks. wide, 1 ft. deep, drains N.
24.60	Wash, 30 lks. wide, 1 ft. deep, drains NE.
35.70	Wash, 15 lks. wide, 2 ft. deep, drains NE.
39.84	The cor. of secs. 8, 9, 16 and 17.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cat claw and cacti.</p>
	<p>N. 0°11' W., bet. secs. 8 and 9. Over gently rolling land, through moderate undergrowth.</p>
.40	Fence, bears N. 77° E. and S. 77° W.
20.03	<p>Point for the S 1/16 sec. cor. of secs. 8 and 9, at proportionate dist. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S 1/16 S8 S9 1967</p>
	Raise a mound of stone W. of the cor.
40.06	<p>The ¼ sec. cor. of secs. 8 and 9, monumented by a squared wooden stake, 2 x 2 ins., projecting 6 ins. above the ground, scribed ¼ on W. side. At the corner point Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ S8 S9 1967</p>
	<p>Reset the wood stake, inverted alongside the iron post. Raise a mound of stone W. of the cor.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°23' E., beginning new measurement. Over gently rolling land, through moderate undergrowth.</p>
29.50	Cottonwood Wash Road, bears E. and W.
29.90	Power line, bears N. 70° E. and S. 70° W.
39.86	A water pipeline, 6 ins. diam., bears N. 70° E. and S. 70° W.
39.95	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S5 S4 S8 S9 1967</p>
	from which
	An electric water pump, bears S. 84°40' E., 92 lks. dist.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>Set an iron pipe, 2 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°57' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
18.00	Ravine, drains NE.
29.10	Track road, bears NE. and SW.
29.30	Fence, bears N. and S.
40.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented by a granite stone, 14 x 8 x 6 ins., loosely set in a mound of stone, mkd. $\frac{1}{4}$ on a face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S4}{S9}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">An electric water pump, bears N. 48°20' E., 71 lks. dist.</p> <p style="padding-left: 40px;">A windmill w/rock and cement water tank, bears N. 40°32' E., 233 lks. dist.</p> <p style="padding-left: 40px;">An electric water pump, bears S. 57°55' E., 359 lks. dist.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°23' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
.03	Fence, bears N. 26 $\frac{1}{2}$ ° W. and S. 26 $\frac{1}{2}$ ° E.
1.00	Man made drainage ditch, drains NE.
6.70	Wash, 100 lks. wide, 1 ft. deep, drains NE.
11.00	Power line, bears S. 15° E. and N. 15° W.
14.00	Cottonwood Wash Road, bears N. 70° E. and S. 70° W.
18.50	Power line, bears N. 70° E. and S. 70° W.
30.00	Fence line, bears NE. and SW.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
31.70	Power line, bears N. and S.
33.70	Track road, bears N. and S.
36.00	Track road, bears NE. and SW.
39.80	Water pipeline, 6 ins. diam., bears N. 70° E. and S. 70° W.
40.04	The cor. of secs. 4, 5, 8 and 9.
	Land, gently rolling. Soil, gravelly loam. No timber; undergrowth, creosote, cacti and grass.
	N. 0°08' W., bet. secs. 4 and 5.
	Over gently rolling land, through moderate undergrowth.
.50	Power line, bears E. and W.
1.90	Enter Cottonwood wash area, bearing E. and W.
5.30	Leave Cottonwood wash area, draining NE.
19.97	Point for the S 1/16 sec. cor. of secs. 4 and 5, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T7S R24E S 1/16 S5 S4 1967
	Raise a mound of stone W. of the cor.
29.60	Mesa Road, bears NE. and SW.
39.94	The 1/4 sec. cor. of secs. 4 and 5, monumented by an old 2 x 2 ins. wood post, firmly set in a collar of stone, no legible mks.; this is accepted as best remaining evidence of the orig. cor.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T7S R24E 1/4 S5 S4 1967
	Reset the orig. cor. post inverted alongside the iron post.
	Raise a mound of stone W. of the cor.
	N. 2°05' E., beginning new measurement.
	Over gently rolling land, through moderate undergrowth.
16.10	Bigler Wash, 80 lks. wide, 2 ft. deep, drains NE.
30.60	Desc. N. slope.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
39.38	<p>The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp. monumented by an iron post 3 ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T6S R24E $\frac{S32}{S5} \frac{S33}{S4}$ T7S 1916</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, cottonwood along cottonwood wash. Undergrowth, creosote, cacti, brush and grass.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp.</p> <p>N. 0°01' W., bet. secs. 31 and 32.</p> <p>Over mountainous land, through moderate undergrowth.</p>
8.20	<p>Ravine, drains NW.; asc. S. slope.</p>
15.10	<p>Ridge, bears E. and W.; desc. N. slope.</p>
38.10	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented by a granite stone, 18 x 12 x 6 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S31}{S31} \frac{S32}{S32}$ 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°14' W., beginning new measurement.</p> <p>Over mountainous land, through moderate undergrowth.</p>
19.00	<p>Ravine, drains N. 25° W.</p>
30.50	<p>Fence, bears S. 89°36' E. and N. 89°36' W.</p>
39.25	<p>The cor. of secs. 29, 30, 31 and 32, monumented by an iron post, 2$\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{S30}{S31} \frac{S29}{S32}$ 1960</p> <p>This cor. was set in 1960, under the US Forest Service Remonumentation Program.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, cacti, cat claw, brush and grass.</p>

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	From the cor. of secs. 28, 29, 32 and 33.
	S. 89°59' W., bet. secs. 29 and 32.
	Over mountainous land, through moderate undergrowth.
14.60	Ravine, drains NE.; asc. E. slope of mesa.
19.80	Top of mesa, bears N. and S.; thence over nearly level land.
40.00	W. rim of mesa; desc. W. slope.
40.64	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R24E $\frac{1}{4}$ <u>S29</u> S32 1967</p>
49.00	Ravine, drains NW.
81.28	The cor. of secs. 29, 30, 31 and 32.
	Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, cacti, cat claw, brush and grass.
	N. 89°56' W., bet. secs. 30 and 31.
	Over mountainous land, through moderate undergrowth.
5.30	Ravine, drains NE.; asc. SE. slope.
13.90	Bladed road, bears NE. and SW.
14.00	Low ridge, bears N. 25° E. and S. 25° W.; desc. W. slope.
39.91	The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented by a granite boulder 4 x 3 ft., 4 ft. high, mkd. $\frac{1}{4}$ X, mound of stone alongside.
	At the corner point
	Set the iron post over "X" on orig. cor., mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R24E $\frac{1}{4}$ <u>S30</u> S31 1967</p>
	N. 86°09' W., beginning new measurement.
	Over mountainous land, through moderate undergrowth.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
2.20	Creek in Lefthand Canyon, course NE.; asc. NE. slope.
32.50	Spur, slopes N.; desc. NW. slope.
36.69	<p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp. monumented by an iron post, 2½ ins. diam., as described in the field notes of the resurvey of T. 7 S., R. 23 E., under this same group.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, cacti, cat claw, brush and grass.</p>
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°06' E., bet. secs. 29 and 30.
	Over mountainous land, through moderate undergrowth.
3.70	Ravine, drains E.; asc. S. slope.
6.70	Bladed road, bears NE. and SW.
13.50	Top of mesa, bears NE. and SW.; thence across top of mesa.
32.60	Desc. N. slope of mesa.
39.82	<p>The ¼ sec. cor. of secs. 29 and 30, monumented by a granite stone, 20 x 12 x 6 ins., set 12 ins. in the ground, mkd. ¼ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R24E ¼ S30 S29 1967</p>
	Deposit the orig. cor. stone alongside the iron post.
	N. 0°04' E., beginning new measurement.
	Over mountainous land, through moderate undergrowth.
25.60	Creek in Lefthand Canyon, course NE.; enter rolling land.
28.30	Track road, bears NW. and SE. to end at the creek.
30.30	Same road, bears SW. and NE.
37.20	Junction of same track road, bearing SE., NW. and N. 25° W.
39.92	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a granite stone, 24 x 6 x 6 ins., set 10 ins. in the ground, mkd. 2 notches on S. and 5 notches on E. faces.</p> <p>At the corner point</p>

Dep. Resurvey, Subdivision, T.7 S., R. 24 E.

CHAINS	
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{S19}{S30}$ $\frac{S20}{S29}$ 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, mountainous to rolling. Soil, rocky. Timber, scattered cottonwood in creek area. Undergrowth, creosote, cat claw, cacti, brush and grass.</p>
12.30	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°38' W., bet. secs. 20 and 29.</p> <p>Over mountainous land, through moderate undergrowth.</p> <p>Wash, 50 lks. wide, 2 ft. deep, drains NE.</p>
27.40	<p>Bladed road, bears NE. and SW.</p>
38.60	<p>Track road, bears NE. and SW.</p>
40.19	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented by a granite stone, 13 x 12 x 4 ins., set 6 ins., in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone to N.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S20}{S29}$ 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 89°34' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
8.00	<p>Asc. E. slope of ridge, bears NE. and SW.</p>
18.00	<p>Top of ridge, desc. W. slope.</p>
27.70	<p>Track road, bears NE. and SW.</p>
31.30	<p>Creek in Lefthand Canyon, drains NE.; asc. NE. slope.</p>
40.03	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, mountainous to rolling. Soil, rocky. Timber, scattered juniper. Undergrowth, creosote, cacti, cat claw, brush and grass.</p>
	<p>N. 89°30' W., bet. secs. 19 and 30.</p>

CHAINS	
	Over rolling land, through moderate undergrowth.
.60	Track road, bears N. 25° W. and S. 25° E.
38.30	Wash, 80 lks. wide, 1 ft. deep, drains NE.
40.09	The ¼ sec. cor. of secs. 19 and 30, monumented by a granite stone, 26 x 10 x 12 ins., set 8 ins. in the ground, mkd. ¼ on N. face, mound of stone N.
	At the corner point
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R24E ¼ $\frac{S19}{S30}$ 1967
	Deposit the orig. cor. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> N. 87°36' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
15.70	Wash, 120 lks. wide, 2 ft. deep, drains N.
36.54	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the field notes of the resurvey of T. 7 S., R. 23 E., under this same group.
	Land, rolling. Soil, rocky. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw, brush and grass.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°10' E., bet. secs. 19 and 20.
	Over gently rolling land, through moderate undergrowth.
40.00	The ¼ sec. cor. of secs. 19 and 20, monumented by a granite stone, 26 x 12 x 5 ins., set 12 ins. in the ground, mkd. ¼ on W. face, mound of stone W.
	At the corner point
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R24E ¼ $\frac{S19}{S20}$ 1967
	Deposit the orig. cor. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> N. 0°04' E., beginning new measurement.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS		
	Over gently rolling land, through moderate undergrowth.	
39.96	The cor. of secs. 17, 18, 19 and 20, monumented by a granite stone, 24 x 8 x 6 ins., set 8 ins., in the ground, mkd. 3 notches on S. and 5 notches on E. faces.	
	At the corner point	
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.	
	T7S R24E S18 S17 S19 S20 1967	
	from which	
	A windmill bears N. 82°16' E., 12.40 chs. dist.	
	Deposit the orig. cor. stone alongside the iron post.	
	Land, gently rolling.	
	Soil, gravelly loam.	
	Timber, mesquite.	
	Undergrowth, cat claw, cacti, brush and grass.	
	From the cor. of secs. 16, 17, 20 and 21.	
	N. 89°49' W., bet. secs. 17 and 20.	
	Over gently rolling land, through moderate undergrowth.	
4.40	Wash, 40 lks. wide, 2 ft. deep, drains N.	
7.70	Wash, 40 lks. wide, 1 ft. deep, drains NW.	
12.10	Bladed road, bears N. and S.	
29.40	Ravine, drains N.	
40.00	The ¼ sec. cor. of secs. 17 and 20, monumented by a granite stone, 15 x 6 x 6 ins., set 8 ins. in the ground, mkd. ¼ on N. face.	
	At the corner point	
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.	
	T7S R24E ¼ S17 S20 1967	
	Deposit the orig. cor. stone alongside the iron post.	
	N. 89°54' W., beginning new measurement.	
	Over gently rolling land, through moderate undergrowth.	
7.00	Track road, bears N. and S.	
11.50	Track road, bears N., S. and SW.	

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
22.50	Enter wash area; through dense undergrowth.
35.40	Center of a small stock tank.
37.50	Leave wash area. (Lefthand Canyon)
39.60	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti, cat claw, brush and grass.
	N. 89°45' W., bet. secs. 18 and 19.
	Over gently rolling land, through moderate undergrowth.
8.80	Ravine, drains N.
12.50	Wash, 15 lks. wide, 2 ft. deep, drains N.
39.10	Wash, 10 lks. wide, 1 ft. deep, drains N.
39.77	The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented by a granite stone, 17 x 8 x 5 ins., set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.
	At the corner point
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	$\begin{array}{r} \text{T7S R24E} \\ \frac{1}{4} \text{S18} \\ \frac{1}{4} \text{S19} \\ \hline 1967 \end{array}$
	Deposit the orig. cor. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/>
	N. 87°42' W., beginning new measurement.
	Over gently rolling land, through moderate undergrowth.
13.70	Wash, 20 lks. wide, 1 ft. deep, drains N.
15.10	Track road, bears NE. and SW.
19.40	Sand Wash, 110 lks. wide, 1 ft. deep, drains N.
20.09	Point for the W $\frac{1}{16}$ sec. cor. of secs. 18 and 19, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T7S R24E} \\ \text{W } \frac{1}{16} \text{S18} \\ \text{S19} \\ \hline 1967 \end{array}$
	Raise a mound of stone N. of the cor.
22.30	Wash, 80 lks. wide, 1 ft. deep, drains N.
26.30	Wash, 80 lks. wide, 2 ft. deep, drains N.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS									
36.97	<p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the field notes of the resurvey of T. 7 S., R. 23 E., under this same group.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti, cat claw, brush and grass.</p>								
	<p>From the cor. of secs. 17, 18, 19 and 20. N. 0°24' W., bet. secs. 17 and 18. Over gently rolling land, through moderate undergrowth.</p>								
37.20	<p>Wash, 15 lks. wide, 2 ft. deep, drains NE.</p>								
40.13	<p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor. This cor. is not monumented.</p>								
76.00	<p>Wash, 75 lks. wide, 1 ft. deep, drains E. from SW.</p>								
80.26	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist. The orig. cor., a charred post, 2 x 2 x 24 ins. long, scribed "S" and other visible marks, was found in a fence approximately 2 chs. W. of the proportioned point. The post was used as a fence tightener and therefore disregarded.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T7S</td> <td>R24E</td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table> <p>Land, gently rolling. Soil, gravelly loam. Timber, scattered mesquite Undergrowth, creosote, cacti, cat claw, brush and grass.</p>	T7S	R24E	S7	S8	S18	S17	1967	
T7S	R24E								
S7	S8								
S18	S17								
1967									
	<p>From the cor. of secs. 8, 9, 16 and 17. N. 89°46' W., bet. secs. 8 and 17. Over gently rolling land, through moderate undergrowth.</p>								
6.00	<p>Wash, 5 lks. wide, 1 ft. deep, drains N.</p>								
23.50	<p>Wash, 50 lks. wide, 1 ft. deep, drains NW.</p>								
37.20	<p>Enter wash area, drains N.</p>								
39.95	<p>Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T7S</td> <td>R24E</td> </tr> <tr> <td>¼</td> <td>S8</td> </tr> <tr> <td></td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table> <p>Raise a mound of stone N. of the cor.</p>	T7S	R24E	¼	S8		S17	1967	
T7S	R24E								
¼	S8								
	S17								
1967									

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS

- 44.40 Leave wash area.
- 48.80 Bladed road, bears N. and S.
- 57.60 Small creek, course N. (Lefthand Canyon)
- 59.93 Point for the W 1/16 sec. cor. of secs. 8 and 17, at proportionate dist.
- Set the iron post 22 ins. in the ground, brass cap mkd.
- T7S R24E
W 1/16 $\frac{S8}{S17}$
1967
- Raise a mound of stone N. of the cor.
- Cor. is located 46 lks. N. of fence bearing E. and W.
- 60.20 Bladed road, bears N. and S.
- 62.20 Wash, 10 lks. wide, 1 ft. deep, drains N.
- 67.00 Wash, 15 lks. wide, 2 ft. deep, drains NE.
- 71.90 Fence, bears irregularly E. and W.
- 79.91 The cor. of secs. 7, 8, 17 and 18.
- Land, gently rolling.
Soil, gravelly loam.
Timber, mesquite.
Undergrowth, creosote, cacti, cat claw, brush and grass.
-
- N. 89°03' W., bet. secs. 7 and 18.
- Over gently rolling land, through moderate undergrowth.
- 3.00 Wash, 50 lks. wide, 1 ft. deep, drains NE.
- 12.40 Track road, bears NE. and SW.
- 21.10 Sand Wash, 150 lks. wide, 2 ft. deep, drains N.
- 39.78 The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented by a wood post 2 x 2 x 18 ins. long, firmly set in mound of stone, mkd. $\frac{1}{4}$ on N. face.
- At the corner point
- Set the iron post 22 ins. in the ground, brass cap mkd.
- T7S R24E
 $\frac{1}{4}$ $\frac{S7}{S18}$
1967
- Reset the wood post, inverted alongside the iron post.
- Raise a mound of stone N. of the cor.
- Cor. is located under fence, bearing E. and W.
-

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>S. 89°57' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth, along N. side of fence.</p>
17.00	Ravine, drains N.
36.50	<p>The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the field notes of the resurvey of T. 7 S., R. 23 E., under this same group.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite. Undergrowth, creosote, cacti, cat claw, brush and grass.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°09' E., bet. secs. 7 and 8.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
.35	Fence, bears E. and W.
4.20	Wash, 110 lks. wide, 1 ft. deep, drains NE.
8.80	Bladed road, bears NE. and SW.
20.065	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8, at proportionate dist.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S 1/16 S7 S8 1967</p>
30.40	Sand Wash, 90 lks. wide, 1 ft. deep, drains NE.
37.50	Track road, bears N. 80° E. and S. 80° W.
40.13	<p>Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ S7 S8 1967</p>
	Raise a mound of stone W. of the cor.
44.00	Cottonwood Creek, 100 lks. wide, 2 ft. deep, drains NE.; asc. S. slope.
49.70	Top of ascent; thence over nearly level land.
51.90	Mesa Road, bears E. and W.
60.195	Point for the N 1/16 sec. cor. of secs. 7 and 8, at proportionate dist.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS													
	<p>Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R24E N 1/16 S7 S8 1967</p>												
76.50	<p>Wash, 30 lks. wide, 1 ft. deep, drains E.</p>												
80.26	<p>The cor. of secs. 5, 6, 7 and 8, monumented by a wooden post 6 x 2 x 2 ins., loosely set, dimly mkd.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R24E S6 S5 S7 S8 1967</p> <p>Reset the wood post, inverted alongside the iron post.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, mesquite, cottonwood along Cottonwood Wash. Undergrowth, creosote, cacti, cat claw, brush and grass.</p>												
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°35' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through moderate undergrowth.</p> <tr> <td data-bbox="293 1542 444 1588">6.50</td> <td data-bbox="444 1542 1382 1588"> <p>Enter Cottonwood Wash, drains NE.</p> </td> </tr> <tr> <td data-bbox="293 1607 444 1653">13.00</td> <td data-bbox="444 1607 1382 1653"> <p>Leave Cottonwood Wash, drains NE.</p> </td> </tr> <tr> <td data-bbox="293 1671 444 1717">16.50</td> <td data-bbox="444 1671 1382 1717"> <p>Wash, 50 lks. wide, 2 ft. deep, drains NE.</p> </td> </tr> <tr> <td data-bbox="293 1736 444 1782">32.30</td> <td data-bbox="444 1736 1382 1782"> <p>Bladed road, bears N. and S.</p> </td> </tr> <tr> <td data-bbox="293 1800 444 1846">34.40</td> <td data-bbox="444 1800 1382 1846"> <p>Mesa Road, bears N. 60° E. and S. 60° W.</p> </td> </tr> <tr> <td data-bbox="293 1865 444 2601">39.92</td> <td data-bbox="444 1865 1382 2601"> <p>The ¼ sec. cor. of secs. 5 and 8, monumented by a granite stone, 16 x 16 x 10 ins., set 8 ins. in the ground, mkd. ¼ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ S5 S8 1967</p> <p>from which</p> <p>Ruins of old stone house, bears N. 88°32' E., 20.65 chs. dist.</p> <p>A windmill, bears N. 16° E., 10.30 chs. dist.</p> </td> </tr>	6.50	<p>Enter Cottonwood Wash, drains NE.</p>	13.00	<p>Leave Cottonwood Wash, drains NE.</p>	16.50	<p>Wash, 50 lks. wide, 2 ft. deep, drains NE.</p>	32.30	<p>Bladed road, bears N. and S.</p>	34.40	<p>Mesa Road, bears N. 60° E. and S. 60° W.</p>	39.92	<p>The ¼ sec. cor. of secs. 5 and 8, monumented by a granite stone, 16 x 16 x 10 ins., set 8 ins. in the ground, mkd. ¼ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ S5 S8 1967</p> <p>from which</p> <p>Ruins of old stone house, bears N. 88°32' E., 20.65 chs. dist.</p> <p>A windmill, bears N. 16° E., 10.30 chs. dist.</p>
6.50	<p>Enter Cottonwood Wash, drains NE.</p>												
13.00	<p>Leave Cottonwood Wash, drains NE.</p>												
16.50	<p>Wash, 50 lks. wide, 2 ft. deep, drains NE.</p>												
32.30	<p>Bladed road, bears N. and S.</p>												
34.40	<p>Mesa Road, bears N. 60° E. and S. 60° W.</p>												
39.92	<p>The ¼ sec. cor. of secs. 5 and 8, monumented by a granite stone, 16 x 16 x 10 ins., set 8 ins. in the ground, mkd. ¼ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ S5 S8 1967</p> <p>from which</p> <p>Ruins of old stone house, bears N. 88°32' E., 20.65 chs. dist.</p> <p>A windmill, bears N. 16° E., 10.30 chs. dist.</p>												

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	Deposit the orig. cor. stone alongside the iron post.
	<hr/> N. 89°33' W., beginning new measurement.
3.70	Over gently rolling land, through moderate undergrowth.
7.70	Wash, 10 lks. wide, 2 ft. deep, drains N. 35° E.
19.97	Wash, 10 lks. wide, 2 ft. deep, drains SE.
	Point for the W 1/16 sec. cor. of secs. 5 and 8, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R24E W 1/16 $\frac{S5}{S8}$ 1967</p>
	Raise a mound of stone N. of the cor.
25.00	Wash, 30 lks. wide, 1 ft. deep, drains NE.
39.94	The cor. of secs. 5, 6, 7 and 8.
	Land, rolling to gently rolling.
	Soil, gravelly loam.
	Timber, scattered mesquite, cottonwood along Cottonwood Wash.
	Undergrowth, creosote, cacti, cat claw, brush and grass.
	<hr/> N. 89°54' W., bet. secs. 6 and 7.
	Over gently rolling land, through moderate undergrowth.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented by a wood stake, 2 x 2 x 24 ins. long, firmly set, mkd. $\frac{1}{4}$ on N. face.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R24E $\frac{1}{4}$ $\frac{S6}{S7}$ 1967</p>
	Reset the wood stake, inverted alongside the iron post.
	Raise a mound of stone N. of the cor.
	<hr/> S. 89°36' W., beginning new measurement.
	Over gently rolling land, through moderate undergrowth.
8.90	Wash, 40 lks. wide, 1 ft. deep, drains NE. (Bigler Wash)
11.20	Bladed road, bears S. 30° E. and N. 30° W.
36.56	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented by an iron post 2 $\frac{1}{2}$ ins. diam., as described in the field notes of the resurvey of T. 7 S., R. 23 E., under this same group.

Dep. Resurvey, Subdivision, T. 7 S., R. 24 E.

CHAINS	
	<p>Land, gently rolling. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw, brush and grass.</p>
20.00	From the cor. of secs. 5, 6, 7 and 8.
40.19	<p>N. 0°37' E., bet. secs. 5 and 6.</p> <p>Over nearly level land, through moderate undergrowth. Bigler Wash, 40 lks. wide, 1 ft. deep, drains NE. from W. The ¼ sec. cor. of secs. 5 and 6, monumented by a wood stake 2 x 2 x 16 ins. long, firmly set, dimly mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R24E ¼ S6 S5 1967</p> <p>Reset the wood stake, inverted alongside the iron post.</p>
	—————
	N. 0°52' E., beginning new measurement.
	Over nearly level land, through moderate undergrowth.
6.40	Wash, 30 lks. wide, 3 ft. deep, drains NE.
24.50	Ravine, drains E.
29.70	Ravine, drains E.
38.69	<p>The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T6S R24E S31 S32 S6 S5 T7S R24E 1916</p> <p>Land, nearly level. Soil, gravelly loam. Timber, scattered mesquite. Undergrowth, creosote, cacti, cat claw, brush and grass.</p>
	General Description
	<p>Township 7 South, Range 24 East is located on the north slope of the Pinaleno Mountains, approximately 4 miles southwest of Pima, Arizona. The land varies from high broken in the southern portion to gently rolling and nearly level in the northern portion of the township. The elevation ranges from 3000 ft. above sea level in sec. 1 to 5600 ft. in sec. 32. The soil is generally sandy or gravelly loam and</p>

Township 7 South, Range 24 East
Gila and Salt River Meridian, Arizona

CHAINS

also rocky in the southern portion. Timber consists of widely scattered juniper and mesquite with cottonwoods along the large creeks and washes. There is a moderate growth of creosote, cat claw, cacti, brush and grass over most of the township. The general drainage is to the northeast.

Mesa Road, the Cottonwood Wash Road and the road along the east bdy., are gravelled, all weather roads. Numerous other track and bladed roads provide excellent access to the entire township.

There are several homes along Cottonwood Wash Road and some land under cultivation in secs. 1, 12 and 13. A wildlife preserve, managed by the Arizona Game and Fish Dept., is located in secs. 13, 14 and 24. Several stock tanks and two reservoirs furnish water for cattle and irrigation. There are electric water pumps in secs. 3, 4, 9 and 14 and windmills in secs. 4, 17 and 25. Secs. 31, 32, 33, 34 and 35 are a part of the Coronado National Forest.

There are two mine shafts in sec. 31 and the McEnery tunnel in sec. 35. There is no mining activity at the present time.

64

CERTIFICATE OF SURVEY

I, Kenneth D. Herman, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of January, 1967, I have dependently resurveyed the south and east boundaries and subdivisional lines of Township 7 South, Range 24 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 28, 1968
(Date)

Kenneth D Herman
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date DEC 19 1969

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the south and east boundaries and subdivisional lines of Township 7 South, Range 24 East, Gila and Salt River Meridian, Arizona,

executed by Kenneth D. Herman, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 2 1971
(Date)

Clark F. Humm
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)